

1. # importing libraries
2. **import** numpy as nm
3. **import** matplotlib.pyplot as mtp
4. **import** pandas as pd
- 5.
6. #importing datasets
7. data_set= pd.read_csv('user_data.csv')
- 8.
9. #Extracting Independent and dependent Variable
10. x= data_set.iloc[:, [2,3]].values
11. y= data_set.iloc[:, 4].values
- 12.
13. # Splitting the dataset into training and test set.
14. from sklearn.model_selection **import** train_test_split
15. x_train, x_test, y_train, y_test= train_test_split(x, y, test_size= 0.25, random_state=0)
- 16.
17. #feature Scaling
18. from sklearn.preprocessing **import** StandardScaler
19. st_x= StandardScaler()
20. x_train= st_x.fit_transform(x_train)
21. x_test= st_x.transform(x_test)

In the above code, we have pre-processed the data. Where we have loaded the dataset, which is given as:

Index	User ID	Gender	Age	EstimatedSalary	Purchased
0	15624510	Male	19	19000	0
1	15810944	Male	35	20000	0
2	15668575	Female	26	43000	0
3	15603246	Female	27	57000	0
4	15804002	Male	19	76000	0
5	15728773	Male	27	58000	0
6	15598044	Female	27	84000	0
7	15694829	Female	32	150000	1
8	15600575	Male	25	33000	0
9	15727311	Female	35	65000	0
10	15570769	Female	26	80000	0
11	15606274	Female	26	52000	0
12	15746139	Male	20	86000	0
13	15704987	Male	32	18000	0

Format Resize ☒ Background color ☐ Column min/max Save and Close Close

2. Fitting the Random Forest algorithm to the training set:

Now we will fit the Random forest algorithm to the training set. To fit it, we will import the **RandomForestClassifier** class from the **sklearn.ensemble** library. The code is given below:

1. #Fitting Decision Tree classifier to the training set
2. from sklearn.ensemble **import** RandomForestClassifier
3. classifier= RandomForestClassifier(n_estimators= 10, criterion="entropy")
4. classifier.fit(x_train, y_train)

In the above code, the classifier object takes below parameters:

- **n_estimators**= The required number of trees in the Random Forest. The default value is 10. We can choose any number but need to take care of the overfitting issue.
- **criterion**= It is a function to analyze the accuracy of the split. Here we have taken "entropy" for the information gain.

Output:

RandomForestClassifier(bootstrap=True, class_weight=None, criterion='entropy',

```
max_depth=None, max_features='auto', max_leaf_nodes=None,  
min_impurity_decrease=0.0, min_impurity_split=None,  
min_samples_leaf=1, min_samples_split=2,  
min_weight_fraction_leaf=0.0, n_estimators=10,  
n_jobs=None, oob_score=False, random_state=None,  
verbose=0, warm_start=False)
```

3. Predicting the Test Set result

Since our model is fitted to the training set, so now we can predict the test result. For prediction, we will create a new prediction vector `y_pred`. Below is the code for it:

1. `#Predicting the test set result`
2. `y_pred= classifier.predict(x_test)`

Output:

The prediction vector is given as:




By checking the above prediction vector and test set real vector, we can determine the incorrect predictions done by the classifier.

4. Creating the Confusion Matrix

Now we will create the confusion matrix to determine the correct and incorrect predictions. Below is the code for it:

1. #Creating the Confusion matrix
2. from sklearn.metrics **import** confusion_matrix
3. cm= confusion_matrix(y_test, y_pred)

Output:



As we can see in the above matrix, there are **4+4= 8 incorrect predictions** and **64+28= 92 correct predictions**