

Problem B

The Bumpy Robot

Input: standard input

Output: standard output

The bumpy robot moves around an $M \times N$ grid of square blocks. Each block has an integral height. To move from a block of height h_1 to an adjacent block of height h_2 , the amount of energy required is,

$$\Delta E = \begin{cases} \lceil \alpha_1 (h_1 - h_2) \rceil + \gamma, & \text{if } h_1 > h_2 \\ \gamma, & \text{if } h_1 = h_2 \\ \lceil \alpha_2 (h_2 - h_1) \rceil + \gamma, & \text{if } h_1 < h_2 \end{cases}$$

and the amount of time required is,

$$\Delta T = \begin{cases} \lceil \beta_1 (h_1 - h_2) \rceil + \delta, & \text{if } h_1 > h_2 \\ \delta, & \text{if } h_1 = h_2 \\ \lceil \beta_2 (h_2 - h_1) \rceil + \delta, & \text{if } h_1 < h_2 \end{cases}$$

Here, α_1 , α_2 , γ , β_1 , β_2 and δ are some known constants.

The bumpy robot must move from a given starting block to a target block in minimum amount of time that is possible without consuming more than a given amount of energy. Please help him find out whether it is possible for him to move to the target block under the given constraint and if possible to determine the minimum amount of time required for reaching there.

Note that two blocks are assumed to be adjacent if they have a side in common.

Input

The input may contain multiple test cases. Each test case begins with a line containing two integers M and N ($1 \leq M, N \leq 15$). The second line contains two positive floating point numbers a_1 and a_2 , and a positive integer g . The second line contains two more positive floating point numbers b_1 and b_2 , and another positive integer d . Then follow M lines containing N integers each giving the height of the corresponding block in the grid. The top-left corner of the grid is assumed to be in row 1 and column 1. The next line contains five integers r_s, c_s, r_t, c_t and E , where (r_s, c_s) is the row, column numbers of the starting block, (r_t, c_t) is the row-column number of the target block and E ($1 \leq E \leq 200$) is the energy constraint for the bumpy robot.

A test case containing two zeros for M and N terminates the input.

Output

For each test case in the input file print a line containing the minimum time required if the target is reachable, print "failed" otherwise.

Sample Input

```
6 6
3.2 1.2 3
5.0 2.0 2
5 -7 10 25 6 23
1 7 9 -2 20 2
12 -10 2 6 9 22
11 19 -20 4 8 0
2 2 6 8 10 12
12 10 2 3 6 9
1 1 6 6 5
6 6
1.5 0.2 1
0.2 1.5 1
5 10 20 25 30 43
15 -7 30 34 40 50
20 35 -10 40 45 55
30 35 45 -20 50 57
40 42 48 50 -25 60
50 55 60 63 68 -30
1 1 6 6 200
0 0
```

Sample Output

failed

112

Rezaul Alam Chowdhury