



Singularity Container Documentation

Release 3.0

User Docs

Oct 17, 2018

CONTENTS

1	Quick Start	1
1.1	Quick Installation Steps	1
1.1.1	Install system dependencies	1
1.1.2	Install Go	1
1.1.3	Clone the Singularity repository	2
1.1.4	Install Go dependencies	2
1.1.5	Compile the Singularity binary	2
1.2	Overview of the Singularity Interface	2
1.3	Download pre-built images	4
1.4	Interact with images	5
1.4.1	Shell	5
1.4.2	Executing Commands	6
1.4.3	Running a container	6
1.4.4	Working with Files	7
1.5	Build images from scratch	8
1.5.1	Sandbox Directories	8
1.5.2	Converting images from one format to another	8
1.5.3	Singularity Definition Files	9
2	Signing and Verifying Containers	11
2.1	Verifying containers from the Container Library	11
2.2	Signing your own containers	11
2.2.1	Generating and managing PGP keys	11
2.2.2	Signing and validating your own containers	12
3	Build a Container	15
3.1	Overview	15
3.2	Downloading an existing container from the Container Library	15
3.3	Downloading an existing container from Docker Hub	16
3.4	Creating writable <code>--sandbox</code> directories	16
3.5	Converting containers from one format to another	16
3.6	Building containers from Singularity definition files	16
3.7	Build options	17
3.7.1	<code>--builder</code>	17
3.7.2	<code>--detached</code>	17
3.7.3	<code>--force</code>	17
3.7.4	<code>--json</code>	17
3.7.5	<code>--library</code>	17
3.7.6	<code>--notest</code>	17
3.7.7	<code>--remote</code>	17

3.7.8	--sandbox	18
3.7.9	--section	18
3.7.10	--update	18
3.8	More Build topics	18
4	Security Options	19
4.1	Linux Capabilities	19
4.2	Security related action options	20
4.2.1	--add-caps	20
4.2.2	--allow-setuid	20
4.2.3	--keep-privs	20
4.2.4	--drop-caps	20
4.2.5	--security	21
5	Network virtualization	23
5.1	--dns	23
5.2	--hostname	23
5.3	--net	23
5.4	--network	24
5.5	--network-args	24

QUICK START

This guide is intended for running Singularity on a computer where you have root (administrative) privileges.

If you need to request an installation on your shared resource, see the [requesting an installation help](#) page for information to send to your system administrator.

For any additional help or support contact the Sylabs team: <https://www.sylabs.io/contact/>

1.1 Quick Installation Steps

You will need a Linux system to run Singularity.

See the [installation page](#) for information about installing older versions of Singularity.

1.1.1 Install system dependencies

You must first install development libraries to your host. Assuming Ubuntu (apply similar to RHEL derivatives):

```
$ sudo apt-get update && sudo apt-get install -y \  
    build-essential \  
    libssl-dev \  
    uuid-dev \  
    libgpgme1-dev
```

1.1.2 Install Go

Singularity 3.0 is written primarily in Go, and you will need Go installed to compile it from source.

This is one of several ways to [install and configure Go](#).

First, visit the [Go download page](#) and pick the appropriate Go archive ($\geq 1.11.1$). Copy the link address and download with `wget` like so:

```
$ export VERSION=1.11 OS=linux ARCH=amd64  
$ cd /tmp  
$ wget https://dl.google.com/go/go$VERSION.$OS-$ARCH.tar.gz
```

Then extract the archive to `/usr/local`

```
$ sudo tar -C /usr/local -xzf go$VERSION.$OS-$ARCH.tar.gz
```

Finally, set up your environment for Go

```
$ echo 'export GOPATH=${HOME}/go' >> ~/.bashrc
$ echo 'export PATH=/usr/local/go/bin:${PATH}:${GOPATH}/bin' >> ~/.bashrc
$ source ~/.bashrc
```

1.1.3 Clone the Singularity repository

Go is a bit finicky about where things are placed. Here is the correct way to build Singularity from source.

```
$ mkdir -p $GOPATH/src/github.com/sylabs
$ cd $GOPATH/src/github.com/sylabs
$ git clone https://github.com/sylabs/singularity.git
$ cd singularity
```

1.1.4 Install Go dependencies

Dependencies are managed using [Dep](#). You can use go get to install it like so:

```
$ go get -u -v github.com/golang/dep/cmd/dep
```

1.1.5 Compile the Singularity binary

Now you are ready to build Singularity. Dependencies will be automatically downloaded. You can build Singularity using the following commands:

```
$ cd $GOPATH/src/github.com/sylabs/singularity
$ ./mconfig
$ make -C builddir
$ sudo make -C builddir install
```

Singularity must be installed as root to function properly.

1.2 Overview of the Singularity Interface

Singularity's command line interface allows you to build and interact with containers transparently. You can run programs inside a container as if they were running on your host system. You can easily redirect IO, use pipes, pass arguments, and access files, sockets, and ports on the host system from within a container.

The `help` command gives an overview of Singularity options and subcommands as follows:

```
$ singularity help

Linux container platform optimized for High Performance Computing (HPC) and
Enterprise Performance Computing (EPC)

Usage:
  singularity [global options...]

Description:
  Singularity containers provide an application virtualization layer enabling
  mobility of compute via both application and environment portability. With
```

(continues on next page)

(continued from previous page)

Singularity one is capable of building a root file system that runs on any other Linux system where Singularity is installed.

Options:

-d, --debug	print debugging information (highest verbosity)
-h, --help	help for singularity
-q, --quiet	suppress normal output
-s, --silent	only print errors
-t, --tokenfile string	path to the file holding your sylabs authentication token (default "/home/david/.singularity/sylabs-token")
-v, --verbose	print additional information

Available Commands:

build	Build a new Singularity container
capability	Manage Linux capabilities on containers
exec	Execute a command within container
help	Help about any command
inspect	Display metadata for container if available
instance	Manage containers running in the background
keys	Manage OpenPGP key stores
pull	Pull a container from a URI
push	Push a container to a Library URI
run	Launch a runsript within container
run-help	Display help for container if available
search	Search the library
shell	Run a Bourne shell within container
sign	Attach cryptographic signatures to container
test	Run defined tests for this particular container
verify	Verify cryptographic signatures on container
version	Show application version

Examples:

```
$ singularity help <command>
Additional help for any Singularity subcommand can be seen by appending
the subcommand name to the above command.
```

For additional help or support, please visit <https://www.sylabs.io/docs/>

Information about subcommand can also be viewed with the help command.

```
$ singularity help verify
Verify cryptographic signatures on container
```

Usage:

```
singularity verify [verify options...] <image path>
```

Description:

The verify command allows a user to verify cryptographic signatures on SIF container files. There may be multiple signatures for data objects and multiple data objects signed. By default the command searches for the primary partition signature. If found, a list of all verification blocks applied on the primary partition is gathered so that data integrity (hashing) and signature verification is done for all those blocks.

Options:

(continues on next page)

(continued from previous page)

```
-g, --groupid uint32    group ID to be verified
-h, --help              help for verify
-i, --id uint32         descriptor ID to be verified
-u, --url string        key server URL (default "https://keys.sylabs.io")
```

Examples:

```
$ singularity verify container.sif
```

For additional help or support, please visit <https://www.sylabs.io/docs/>

Singularity uses positional syntax (i.e. the order of commands and options matters).

Global options affecting the behavior of all commands follow the main `singularity` command. Then sub commands are passed followed by their options and arguments.

For example, to pass the `--debug` option to the main `singularity` command and run Singularity with debugging messages on:

```
$ singularity --debug run library://sylabsd/examples/lolcow
```

To pass the `--containall` option to the `run` command and run a Singularity image in an isolated manner:

```
$ singularity run --containall library://sylabsd/examples/lolcow
```

Singularity 2.4 introduced the concept of command groups. For instance, to list Linux capabilities for a particular user, you would use the `list` command in the `capabilities` command group like so:

```
$ singularity capability list --user dave
```

Container authors might also write help docs specific to a container or for an internal module called an app. If those help docs exist for a particular container, you can view them like so.

```
$ singularity help container.sif # See the container's help, if provided
$ singularity help --app foo container.sif # See the help for foo, if provided
```

1.3 Download pre-built images

You can use the `search` command to locate groups, collections, and containers of interest on the [Container Library](#) .

```
$ singularity search alp
No users found for 'alp'

Found 1 collections for 'alp'
  library://jchavez/alpine

Found 5 containers for 'alp'
  library://jialipassion/official/alpine
    Tags: latest
  library://dtrudg/linux/alpine
    Tags: 3.2 3.3 3.4 3.5 3.6 3.7 3.8 edge latest
  library://sylabsd/linux/alpine
```

(continues on next page)

(continued from previous page)

```
Tags: 3.6 3.7 latest
library://library/default/alpine
Tags: 3.1 3.2 3.3 3.4 3.5 3.6 3.7 3.8 latest
library://sylabsed/examples/alpine
Tags: latest
```

You can use the `pull` and `build` commands to download pre-built images from an external resource like the [Container Library](#) or [Docker Hub](#).

When called on a native Singularity image like those provided on the Container Library, `pull` simply downloads the image file to your system.

```
$ singularity pull library://sylabsed/linux/alpine
```

You can also use `pull` with the `docker:// uri` to reference Docker images served from a registry. In this case `pull` does not just download an image file. Docker images are stored in layers, so `pull` must also combine those layers into a usable Singularity file.

```
$ singularity pull docker://godlovedc/lolcow
```

Pulling Docker images reduces reproducibility. If you were to pull a Docker image today and then wait six months and pull again, you are not guaranteed to get the same image. If any of the source layers has changed the image will be altered. If reproducibility is a priority for you, try building your images from the Container Library.

You can also use the `build` command to download pre-built images from an external resource. When using `build` you must specify a name for your container like so:

```
$ singularity build ubuntu.sif library://ubuntu
$ singularity build lolcow.sif docker://godlovedc/lolcow
```

Unlike `pull`, `build` will convert your image to the latest Singularity image format after downloading it.

`build` is like a “Swiss Army knife” for container creation. In addition to downloading images, you can use `build` to create images from other images or from scratch using a definition file. You can also use `build` to convert an image between the container formats supported by Singularity.

1.4 Interact with images

You can interact with images in several ways. It is not actually necessary to `pull` or `build` an image to interact with it. The commands listed here will work with image URIs in addition to accepting a local path to an image.

For these examples we will use a `lolcow_latest.sif` image that can be pulled from the Container Library like so.

```
$ singularity pull library://sylabsed/examples/lolcow
```

1.4.1 Shell

The shell command allows you to spawn a new shell within your container and interact with it as though it were a small virtual machine.

```
$ singularity shell lolcow_latest.sif

Singularity lolcow_latest.sif:~>
```

The change in prompt indicates that you have entered the container (though you should not rely on that to determine whether you are in container or not).

Once inside of a Singularity container, you are the same user as you are on the host system.

```
Singularity lolcow_latest.sif:~> whoami
david

Singularity lolcow_latest.sif:~> id
uid=1000(david) gid=1000(david) groups=1000(david),4(adm),24(cdrom),27(sudo),30(dip),
↪46(plugdev),116(lpadmin),126(sambashare)
```

shell also works with the library://, docker://, and shub:// URIs. This creates an ephemeral container that disappears when the shell is exited.

```
$ singularity shell library://sylabsed/examples/lolcow
```

1.4.2 Executing Commands

The exec command allows you to execute a custom command within a container by specifying the image file. For instance, to execute the cowsay program within the lolcow_latest.sif container:

```
$ singularity exec lolcow_latest.sif cowsay moo

_____
< moo >
-----
      \   ^__^
       \  (oo)\_______
          (__)\\       )\\/\\
              ||----w |
               ||     ||
```

exec also works with the library://, docker://, and shub:// URIs. This creates an ephemeral container that executes a command and disappears.

```
$ singularity exec library://sylabsed/examples/lolcow cowsay "Fresh from the library!"

_____
< Fresh from the library! >
-----
      \   ^__^
       \  (oo)\_______
          (__)\\       )\\/\\
              ||----w |
               ||     ||
```

1.4.3 Running a container

Singularity containers contain runscripts. These are user defined scripts that define the actions a container should perform when someone runs it. The runscript can be triggered with the run command, or simply by calling the container as though it were an executable.

```
$ singularity run lolcow_latest.sif
/ You have been selected for a secret \
\ mission.                             /
-----
      \   ^__^
       \  (oo)\_______
          (__)\       )\/\
              ||----w |
              ||     ||

$ ./lolcow_latest.sif
/ Q: What is orange and goes "click, \
\ click?" A: A ball point carrot.    /
-----
      \   ^__^
       \  (oo)\_______
          (__)\       )\/\
              ||----w |
              ||     ||
```

run also works with the `library://`, `docker://`, and `shub://` URIs. This creates an ephemeral container that runs and then disappears.

```
$ singularity run library://sylabse/examples/lolcow
/ Is that really YOU that is reading \
\ this?                               /
-----
      \   ^__^
       \  (oo)\_______
          (__)\       )\/\
              ||----w |
              ||     ||
```

1.4.4 Working with Files

Files on the host are reachable from within the container.

```
$ echo "Hello from inside the container" > $HOME/hostfile.txt

$ singularity exec lolcow_latest.sif cat $HOME/hostfile.txt

Hello from inside the container
```

This example works because `hostfile.txt` exists in the user's home directory. By default Singularity bind mounts `/home/$USER`, `/tmp`, and `$PWD` into your container at runtime.

You can specify additional directories to bind mount into your container with the `--bind` option. In this example, the `data` directory on the host system is bind mounted to the `/mnt` directory inside the container.

```
$ echo "Drink milk (and never eat hamburgers)." > /data/cow_advice.txt

$ singularity exec --bind /data:/mnt lolcow_latest.sif cat /mnt/cow_advice.txt
Drink milk (and never eat hamburgers).
```

Pipes and redirects also work with Singularity commands just like they do with normal Linux commands.

```
$ cat /data/cow_advice.txt | singularity exec lolcow_latest.sif cowsay  
< Drink milk (and never eat hamburgers). >  
-----  
      \      ^__^  
       \      (oo)\_____  
            (__)\\       )\\/\  
               ||----w |  
               ||     ||
```

1.5 Build images from scratch

Singularity v3.0 produces immutable images in the Singularity Image File (SIF) format. This ensures reproducible and verifiable images and allows for many extra benefits such as the ability to sign and verify your containers.

However, during testing and debugging you may want an image format that is writable. This way you can `shell` into the image and install software and dependencies until you are satisfied that your container will fulfill your needs. For these scenarios, Singularity also supports the `sandbox` format (which is really just a directory).

For more details about the different build options and best practices, read about the Singularity flow.

1.5.1 Sandbox Directories

To build into a `sandbox` (container in a directory) use the `build --sandbox` command and option:

```
$ sudo singularity build --sandbox ubuntu/ library://ubuntu
```

This command creates a directory called `ubuntu/` with an entire Ubuntu Operating System and some Singularity metadata in your current working directory.

You can use commands like `shell`, `exec`, and `run` with this directory just as you would with a Singularity image. If you pass the `--writable` option when you use your container you can also write files within the `sandbox` directory (provided you have the permissions to do so).

```
$ sudo singularity exec --writable ubuntu touch /foo  
  
$ singularity exec ubuntu/ ls /foo  
/foo
```

1.5.2 Converting images from one format to another

The `build` command allows you to build a container from an existing container. This means that you can use it to convert a container from one format to another. For instance, if you have already created a `sandbox` (directory) and want to convert it to the default immutable image format (`squashfs`) you can do so:

```
$ singularity build new-sif sandbox
```

Doing so may break reproducibility if you have altered your `sandbox` outside of the context of a definition file, so you are advised to exercise care.

1.5.3 Singularity Definition Files

For a reproducible, production-quality container you should build a SIF file using a Singularity definition file. This also makes it easy to add files, environment variables, and install custom software, and still start from your base of choice (e.g., the Container Library).

A definition file has a header and a body. The header determines the base container to begin with, and the body is further divided into sections that do things like install software, setup the environment, and copy files into the container from the host system.

Here is an example of a definition file:

```

BootStrap: library
From: ubuntu:16.04

%post
    apt-get -y update
    apt-get -y install fortune cowsay lolcat

%environment
    export LC_ALL=C
    export PATH=/usr/games:$PATH

%runscript
    fortune | cowsay | lolcat

%labels
    Author Godloved

```

To build a container from this definition file (assuming it is a file named lolcow.def), you would call build like so:

```
$ sudo singularity build lolcow.sif lolcow.def
```

In this example, the header tells Singularity to use a base Ubuntu 16.04 image from the Container Library.

The `%post` section executes within the container at build time after the base OS has been installed. The `%post` section is therefore the place to perform installations of new applications.

The `%environment` section defines some environment variables that will be available to the container at runtime.

The `%runscript` section defines actions for the container to take when it is executed.

And finally, the `%labels` section allows for custom metadata to be added to the container.

This is a very small example of the things that you can do with a definition file. In addition to building a container from the Container Library, you can start with base images from Docker Hub and use images directly from official repositories such as Ubuntu, Debian, CentOS, Arch, and BusyBox. You can also use an existing container on your host system as a base.

If you want to build Singularity images but you don't have administrative (root) access on your build system, you can build images using the [Remote Builder](#).

This quickstart document just scratches the surface of all of the things you can do with Singularity!

If you need additional help or support, contact the Sylabs team: <https://www.sylabs.io/contact/>

SIGNING AND VERIFYING CONTAINERS

Singularity 3.0 introduces the abilities to create and manage PGP keys and use them to sign and verify containers. This provides a trusted method for Singularity users to share containers. It ensures a bit-for-bit reproduction of the original container as the author intended it.

2.1 Verifying containers from the Container Library

The `verify` command will allow you to verify that a container has been signed using a PGP key. To use this feature with images that you pull from the container library, you must first generate an access token to the Sylabs Cloud. If you don't already have a valid access token, follow these steps:

1. Go to : <https://cloud.sylabs.io/>
2. Click “Sign in to Sylabs” and follow the sign in steps.
3. Click on your login id (same and updated button as the Sign in one).
4. Select “Access Tokens” from the drop down menu.
5. Click the “Manage my API tokens” button from the “Account Management” page.
6. Click “Create”.
7. Click “Copy token to Clipboard” from the “New API Token” page.
8. Paste the token string into your `~/.singularity/sylabs-token` file.

Now you can verify containers that you pull from the library, ensuring they are bit-for-bit reproductions of the original image.

```
$ singularity pull library://alpine

$ singularity verify alpine_latest.sif
Verifying image: alpine_latest.sif
Data integrity checked, authentic and signed by:
    Sylabs Admin <support@sylabs.io>, KeyID 51BE5020C508C7E9
```

In this example you can see that **Sylabs Admin** has signed the container.

2.2 Signing your own containers

2.2.1 Generating and managing PGP keys

To sign your own containers you first need to generate one or more keys.

If you attempt to sign a container before you have generated any keys, Singularity will guide you through the interactive process of creating a new key. Or you can use the `newpair` subcommand in the `key` command group like so:

```
$ singularity keys newpair
Enter your name (e.g., John Doe) : Dave Godlove
Enter your email address (e.g., john.doe@example.com) : d@sylabs.io
Enter optional comment (e.g., development keys) : demo
Generating Entity and OpenPGP Key Pair... Done
Enter encryption passphrase :
```

The `list` subcommand will show you all of the keys you have created or saved locally.

```
$ singularity keys list
Public key listing (/home/david/.singularity/sypgp/pgp-public):

0) U: Dave Godlove (demo) <d@sylabs.io>
   C: 2018-10-08 15:25:30 -0400 EDT
   F: 135E426D67D8416DE1D6AC7FFED5BBA38EE0DC4A
   L: 4096
   -----
```

In the output above, the letters stand for the following:

- U: User
- C: Creation date and time
- F: Fingerprint
- L: Key length

After generating your key you can optionally push it to the [Keystore](#) using the fingerprint like so:

```
$ singularity keys push 135E426D67D8416DE1D6AC7FFED5BBA38EE0DC4A
public key `135E426D67D8416DE1D6AC7FFED5BBA38EE0DC4A` pushed to server successfully
```

This will allow others to verify images that you have signed.

If you delete your local public PGP key, you can always locate and download it again like so.

```
$ singularity keys search Godlove
Search results for 'Godlove'

Type bits/keyID      Date          User ID
-----
pub  4096R/8EE0DC4A 2018-10-08 Dave Godlove (demo) <d@sylabs.io>
-----

$ singularity keys pull 8EE0DC4A
1 key(s) fetched and stored in local cache /home/david/.singularity/sypgp/pgp-public
```

But note that this only restores the *public* key (used for verifying) to your local machine and does not restore the *private* key (used for signing).

2.2.2 Signing and validating your own containers

Now that you have a key generated, you can use it to sign images like so:


```
$ singularity sign my_container.sif
Signing image: my_container.sif
Enter key passphrase:
Signature created and applied to my_container.sif
```

Because your public PGP key is saved locally you can verify the image without needing to contact the Keystore.

```
$ singularity verify my_container.sif
Verifying image: my_container.sif
Data integrity checked, authentic and signed by:
    Dave Godlove (demo) <d@sylabs.io>, KeyID FED5BBA38EE0DC4A
```

If you've pushed your key to the Keystore you can also verify this image in the absence of a local key. To demonstrate this, first delete your local keys, and then try to use the `verify` command again.

```
$ rm ~/.singularity/sypgp/*

$ singularity verify my_container.sif
Verifying image: my_container.sif
INFO:    key missing, searching key server for KeyID: FED5BBA38EE0DC4A...
INFO:    key retrieved successfully!
Store new public key 135E426D67D8416DE1D6AC7FFED5BBA38EE0DC4A? [Y/n] y
Data integrity checked, authentic and signed by:
    Dave Godlove (demo) <d@sylabs.io>, KeyID FED5BBA38EE0DC4A
```

Answering yes at the interactive prompt will store the Public key locally so you will not have to contact the Keystore again the next time you verify your container.

BUILD A CONTAINER

`build` is the “Swiss army knife” of container creation. You can use it to download and assemble existing containers from external resources like the [Container Library](#) and [Docker Hub](#). You can use it to convert containers between the formats supported by Singularity. And you can use it in conjunction with a Singularity definition file to create a container from scratch and customized it to fit your needs.

3.1 Overview

The `build` command accepts a target as input and produces a container as output.

The target defines the method that `build` uses to create the container. It can be one of the following:

- URI beginning with **library://** to build from the Container Library
- URI beginning with **docker://** to build from Docker Hub
- URI beginning with **shub://** to build from Singularity Hub
- path to a **existing container** on your local machine
- path to a **directory** to build from a sandbox
- path to a Singularity definition file

`build` can produce containers in two different formats that can be specified as follows.

- compressed read-only **Singularity Image File (SIF)** format suitable for production (default)
- writable **(ch)root directory** called a sandbox for interactive development (`--sandbox` option)

Because `build` can accept an existing container as a target and create a container in either supported format you can convert existing containers from one format to another.

3.2 Downloading an existing container from the Container Library

You can use the `build` command to download a container from the Container Library.

```
$ sudo singularity build lolcow.simg library://sylabs-jms/testing/lolcow
```

The first argument (`lolcow.simg`) specifies a path and name for your container. The second argument (`library://sylabs-jms/testing/lolcow`) gives the Container Library URI from which to download. By default the container will be converted to a compressed, read-only SIF. If you want your container in a writable format use the `--sandbox` option.

3.3 Downloading an existing container from Docker Hub

You can use `build` to download layers from Docker Hub and assemble them into Singularity containers.

```
$ sudo singularity build lolcow.sif docker://godlovedc/lolcow
```

3.4 Creating writable `--sandbox` directories

If you wanted to create a container within a writable directory (called a sandbox) you can do so with the `--sandbox` option. It's possible to create a sandbox without root privileges, but to ensure proper file permissions it is recommended to do so as root.

```
$ sudo singularity build --sandbox lolcow/ library://sylabs-jms/testing/lolcow
```

The resulting directory operates just like a container in a SIF file. To make changes within the container, use the `--writable` flag when you invoke your container. It's a good idea to do this as root to ensure you have permission to access the files and directories that you want to change.

```
$ sudo singularity shell --writable lolcow/
```

3.5 Converting containers from one format to another

If you already have a container saved locally, you can use it as a target to build a new container. This allows you convert containers from one format to another. For example if you had a sandbox container called `development/` and you wanted to convert it to SIF container called `production.sif` you could:

```
$ sudo singularity build production.sif development/
```

Use care when converting a sandbox directory to the default SIF format. If changes were made to the writable container before conversion, there is no record of those changes in the Singularity definition file rendering your container non-reproducible. It is a best practice to build your immutable production containers directly from a Singularity definition file instead.

3.6 Building containers from Singularity definition files

Of course, Singularity definition files can be used as the target when building a container. For detailed information on writing Singularity definition files, please see the Container Definition docs. Let's say you already have the following container definition file called `lolcow.def`, and you want to use it to build a SIF container.

```
Bootstrap: docker
From: ubuntu:16.04

%post
    apt-get -y update
    apt-get -y install fortune cowsay lolcat

%environment
    export LC_ALL=C
    export PATH=/usr/games:$PATH
```

(continues on next page)

(continued from previous page)

```
%runscript
  fortune | cowsay | lolcat
```

You can do so with the following command.

```
$ sudo singularity build lolcow.sif lolcow.def
```

The command requires `sudo` just as installing software on your local machine requires root privileges.

3.7 Build options

3.7.1 `--builder`

Singularity 3.0 introduces the option to perform a remote build. The `--builder` option allows you to specify a URL to a different build service. For instance, you may need to specify a URL to build to an on premises installation of the remote builder. This option must be used in conjunction with `--remote`.

3.7.2 `--detached`

When used in combination with the `--remote` option, the `--detached` option will detach the build from your terminal and allow it to build in the background without echoing any output to your terminal.

3.7.3 `--force`

The `--force` option will delete and overwrite an existing Singularity image without presenting the normal interactive prompt.

3.7.4 `--json`

The `--json` option will force Singularity to interpret a given definition file as a json.

3.7.5 `--library`

This command allows you to set a different library. (The default library is “<https://library.sylabs.io>”)

3.7.6 `--notest`

If you don’t want to run the `%test` section during the container build, you can skip it with the `--notest` option. For instance, maybe you are building a container intended to run in a production environment with GPUs. But perhaps your local build resource does not have GPUs. You want to include a `%test` section that runs a short validation but you don’t want your build to exit with an error because it cannot find a GPU on your system.

3.7.7 `--remote`

Singularity 3.0 introduces the ability to build a container on an external resource running a remote builder. (The default remote builder is located at “<https://build.sylabs.io>”.)

3.7.8 `--sandbox`

Build a sandbox (chroot directory) instead of the default SIF format.

3.7.9 `--section`

Instead of running the entire definition file, only run a specific section or sections. This option accepts a comma delimited string of definition file sections. Acceptable arguments include `all`, `none` or any combination of the following: `setup`, `post`, `files`, `environment`, `test`, `labels`.

Under normal build conditions, the Singularity definition file is saved into a container's meta-data so that there is a record showing how the container was built. Using the `--section` option may render this meta-data useless, so use care if you value reproducibility.

3.7.10 `--update`

You can build into the same sandbox container multiple times (though the results may be unpredictable and it is generally better to delete your container and start from scratch).

By default if you build into an existing sandbox container, the `build` command will prompt you to decide whether or not to overwrite the container. Instead of this behavior you can use the `--update` option to build `_into_` an existing container. This will cause Singularity to skip the header and build any sections that are in the definition file into the existing container.

The `--update` option is only valid when used with sandbox containers.

3.8 More Build topics

- If you want to **customize the cache location** (where Docker layers are downloaded on your system), specify Docker credentials, or any custom tweaks to your build environment, see build environment.
- If you want to make internally **modular containers**, check out the getting started guide [here](#)
- If you want to **build your containers** on the Remote Builder, (because you don't have root access on a Linux machine or want to host your container on the cloud) check out [this site](#)

SECURITY OPTIONS

Singularity 3.0 introduces many new security related options to the container runtime. This document will describe the new methods users have for specifying the security scope and context when running Singularity containers.

4.1 Linux Capabilities

Singularity provides full support for granting and revoking Linux capabilities on a user or group basis. For example, let us suppose that an admin has decided to grant a user capabilities to open raw sockets so that they can use `ping` in a container where the binary is controlled via capabilities (i.e. a recent version of CentOS).

To do so, the admin would issue a command such as this:

```
$ sudo singularity capability add --user david CAP_NET_RAW
```

This means the user `david` has just been granted permissions (through Linux capabilities) to open raw sockets within Singularity containers.

The admin can check that this change is in effect with the `capability list` command.

```
$ sudo singularity capability list --user david
CAP_NET_RAW
```

To take advantage of this new capability, the user `david` must also request the capability when executing a container with the `--add-caps` flag like so:

```
$ singularity exec --add-caps CAP_NET_RAW library://centos ping -c 1 8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=128 time=18.3 ms

--- 8.8.8.8 ping statistics ---
1 packets transmitted, 1 received, 0% packet loss, time 0ms
rtt min/avg/max/mdev = 18.320/18.320/18.320/0.000 ms
```

If the admin decides that it is no longer necessary to allow the user `dave` to open raw sockets within Singularity containers, they can revoke the appropriate Linux capability like so:

```
$ sudo singularity capability drop --user david CAP_NET_RAW
```

The `capability add` and `drop` subcommands will also accept the case insensitive keyword `all` to grant or revoke all Linux capabilities to a user or group. Similarly, the `--add-caps` option will accept the `all` keyword. Of course appropriate caution should be exercised when using this keyword.

4.2 Security related action options

Singularity 3.0 introduces many new flags that can be passed to the action commands; `shell`, `exec`, and `run` allowing fine grained control of security.

4.2.1 `--add-caps`

As explained above, `--add-caps` will “activate” Linux capabilities when a container is initiated, providing those capabilities have been granted to the user by an administrator using the `capability add` command. This option will also accept the case insensitive keyword `all` to add every capability granted by the administrator.

4.2.2 `--allow-setuid`

The SetUID bit allows a program to be executed as the user that owns the binary. The most well-known SetUID binaries are owned by root and allow a user to execute a command with elevated privileges. But other SetUID binaries may allow a user to execute a command as a service account.

By default SetUID is disallowed within Singularity containers as a security precaution. But the root user can override this precaution and allow SetUID binaries to behave as expected within a Singularity container with the `--allow-setuid` option like so:

```
$ sudo singularity shell --allow-setuid some_container.sif
```

4.2.3 `--keep-privs`

It is possible for an admin to set a different set of default capabilities or to reduce the default capabilities to zero for the root user by setting the `root default capabilities` parameter in the `singularity.conf` file to `file` or `no` respectively. If this change is in effect, the root user can override the `singularity.conf` file and enter the container with full capabilities using the `--keep-privs` option.

```
$ sudo singularity exec --keep-privs library://centos ping -c 1 8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=128 time=18.8 ms

--- 8.8.8.8 ping statistics ---
1 packets transmitted, 1 received, 0% packet loss, time 0ms
rtt min/avg/max/mdev = 18.838/18.838/18.838/0.000 ms
```

4.2.4 `--drop-caps`

By default, the root user has a full set of capabilities when they enter the container. You may choose to drop specific capabilities when you initiate a container as root to enhance security.

For instance, to drop the ability for the root user to open a raw socket inside the container:

```
$ sudo singularity exec --drop-caps CAP_NET_RAW library://centos ping -c 1 8.8.8.8
ping: socket: Operation not permitted
```

The `drop-caps` option will also accept the case insensitive keyword `all` as an option to drop all capabilities when entering the container.

4.2.5 --security

The `--security` flag allows the root user to leverage security modules such as SELinux, AppArmor, and seccomp within your Singularity container. You can also change the UID and GID of the user within the container at runtime.

For instance:

```
$ sudo whoami
root

$ sudo singularity exec --security uid:1000 my_container.sif whoami
david
```

To use seccomp to blacklist a command follow this procedure. (It is actually preferable from a security standpoint to whitelist commands but this will suffice for a simple example.) Note that this example was run on Ubuntu and that Singularity was installed with the `libseccomp-dev` and `pkg-config` packages as dependencies.

First write a configuration file. An example configuration file is installed with Singularity, normally at `/usr/local/etc/singularity/seccomp-profiles/default.json`. For this example, we will use a much simpler configuration file to blacklist the `mkdir` command.

```
{
  "defaultAction": "SCMP_ACT_ALLOW",
  "archMap": [
    {
      "architecture": "SCMP_ARCH_X86_64",
      "subArchitectures": [
        "SCMP_ARCH_X86",
        "SCMP_ARCH_X32"
      ]
    }
  ],
  "syscalls": [
    {
      "names": [
        "mkdir"
      ],
      "action": "SCMP_ACT_KILL",
      "args": [],
      "comment": "",
      "includes": {},
      "excludes": {}
    }
  ]
}
```

We'll save the file at `/home/david/no_mkdir.json`. Then we can invoke the container like so:

```
$ sudo singularity shell --security seccomp:/home/david/no_mkdir.json my_container.sif

Singularity> mkdir /tmp/foo
Bad system call (core dumped)
```

Note that attempting to use the blacklisted `mkdir` command resulted in a core dump.

The full list of arguments accepted by the `--security` option are as follows:

```
--security="seccomp:/usr/local/etc/singularity/seccomp-profiles/default.json"  
--security="apparmor:/usr/bin/man"  
--security="selinux:context"  
--security="uid:1000"  
--security="gid:1000"  
--security="gid:1000:1:0" (multiple gids, first is always the primary group)
```

NETWORK VIRTUALIZATION

Singularity 3.0 introduces full integration with `cni`, and several new features to make network virtualization easy.

A few new options have been added to the action commands (`exec`, `run`, and `shell`) to facilitate these features, and the `--net` option has been updated as well. These options can only be used by root.

5.1 `--dns`

The `--dns` option allows you to specify a comma separated list of DNS servers to add to the `/etc/resolv.conf` file.

```
$ nslookup sylabs.io | grep Server
Server:                127.0.0.53

$ sudo singularity exec --dns 8.8.8.8 ubuntu.sif nslookup sylabs.io | grep Server
Server:                8.8.8.8

$ sudo singularity exec --dns 8.8.8.8 ubuntu.sif cat /etc/resolv.conf
nameserver 8.8.8.8
```

5.2 `--hostname`

The `--hostname` option accepts a string argument to change the hostname within the container.

```
$ hostname
ubuntu-bionic

$ sudo singularity exec --hostname hal-9000 my_container.sif hostname
hal-9000
```

5.3 `--net`

Passing the `--net` flag will cause the container to join a new network namespace when it initiates. New in Singularity 3.0, a bridge interface will also be set up by default.

```
$ hostname -I
10.0.2.15
```

(continues on next page)

(continued from previous page)

```
$ sudo singularity exec --net my_container.sif hostname -I
10.22.0.4
```

5.4 --network

The `--network` option can only be invoked in combination with the `--net` flag. It accepts a comma delimited string of network types. Each entry will bring up a dedicated interface inside container.

```
$ hostname -I
172.16.107.251 10.22.0.1

$ sudo singularity exec --net --network ptp ubuntu.sif hostname -I
10.23.0.6

$ sudo singularity exec --net --network bridge,ptp ubuntu.sif hostname -I
10.22.0.14 10.23.0.7
```

When invoked, the `--network` option searches the singularity configuration directory (commonly `/usr/local/etc/singularity/network/`) for the cni configuration file corresponding to the requested network type(s). Several configuration files are installed with Singularity by default corresponding to the following network types:

- bridge
- ptp
- ipvlan
- macvlan

Administrators can also define custom network configurations and place them in the same directory for the benefit of users.

5.5 --network-args

The `--network-args` option provides a convenient way to specify arguments to pass directly to the cni plugins. It must be used in conjunction with the `--net` flag.

For instance, let's say you want to start an [NGINX](#) server on port 80 inside of the container, but you want to map it to port 8080 outside of the container:

```
$ sudo singularity instance start --writable-tmpfs \
  --net --network-args "portmap=8080:80/tcp" docker://nginx web2
```

The above command will start the Docker Hub official NGINX image running in a background instance called `web2`. The NGINX instance will need to be able to write to disk, so we've used the `--writable-tmpfs` argument to allocate some space in memory. The `--net` flag is necessary when using the `--network-args` option, and specifying the `portmap=8080:80/tcp` argument which will map port 80 inside of the container to 8080 on the host.

Now we can start NGINX inside of the container:

```
$ sudo singularity exec instance://web2 nginx
```

And the `curl` command can be used to verify that NGINX is running on the host port 8080 as expected.

```
$ curl localhost:8080
10.22.0.1 - - [16/Oct/2018:09:34:25 -0400] "GET / HTTP/1.1" 200 612 "-" "curl/7.58.0"
↪ "-"
<!DOCTYPE html>
<html>
<head>
<title>Welcome to nginx!</title>
<style>
    body {
        width: 35em;
        margin: 0 auto;
        font-family: Tahoma, Verdana, Arial, sans-serif;
    }
</style>
</head>
<body>
<h1>Welcome to nginx!</h1>
<p>If you see this page, the nginx web server is successfully installed and
working. Further configuration is required.</p>

<p>For online documentation and support please refer to
<a href="http://nginx.org/">nginx.org</a>.<br/>
Commercial support is available at
<a href="http://nginx.com/">nginx.com</a>.</p>

<p><em>Thank you for using nginx.</em></p>
</body>
</html>
```

For more information about cni, check the [cni specification](#).