

TBS

Master's Thesis

Nicolas Cuervo-Benavides

Advisor : Dr.-Ing. Holger Jäkel
Supervisor : MSc. Felix Wunsch

Start date : 17th May 2017
End date : 6th December 2017

Declaration

With this statement I declare that I have independently completed the above master's thesis. The thoughts taken directly or indirectly from external sources are properly marked as such. This thesis was not previously submitted to another academic institution and has also not yet been published.

Karlsruhe, 06.12.2017

Nicolas Cuervo-Benavides

Abstract

This thesis collects the fundamentals of machine learning and applies them in a determined, state-of-art, communications scenario. CEL thesis rules require it to be about 3-5 pages. It is a summary of what you do in your thesis. Use around 5 pictures and outline whatever you did. And now a few lines of information.

This is a
todo exam-
ple

Polar codes are the first codes to asymptotically achieve channel capacity with low complexity encoders and decoders. They were first introduced by Erdal Arikan in 2009 [Jon05]. Channel coding has always been a challenging task because it draws a lot of resources, especially in software implementations. Software Radio is getting more prominent because it offers several advantages among which are higher flexibility and better maintainability. Future radio systems are aimed at being run on virtualized servers instead of dedicated hardware in base stations [Jon05]. Polar codes may be a promising candidate for future radio systems if they can be implemented efficiently in software.

In this thesis the theory behind polar codes and a polar code implementation in GNU Radio is presented. This implementation is then evaluated regarding parameterization options and their impact on error correction performance. The evaluation includes a comparison to state-of-the-art Low-Density Parity-Check (LDPC) codes.




Figure 0.1.: Polar code encoding and decoding

The polar encoder is shown in Fig. 0.1a.

Contents

1. Introduction	3
2. Artificial Intelligence - Introduction	9
2.1. Overview	9
2.2. Machine Learning	9
2.2.1. Training Models	9
2.2.2. Testing Models	9
2.2.3. Model Evaluation	9
2.2.4. Supervised Learning	9
2.2.5. Feature Engineering	9
2.2.6. Unsupervised Learning	9
2.2.7. Reinforcement Learning	9
2.3. Deep Learning	9
2.3.1. Neural Networks	9
2.3.2. Convolutional Neural Networks	9
2.3.3. Optimization of Cost Functions	9
3. Testbed Implementation	11
3.1. Software Defined Radio approach	11
3.1.1. GNURadio	11
3.1.2. Universal Software Radio Peripheral	11
3.2. Machine Learning models in Python and Jupyter	11
3.2.1. scikit-learn	11
3.2.2. keras	11
3.3. Data set Generation	11
3.3.1. Measure Campaign	11
3.3.2. Feature Engineering	11
3.3.3. Spectrograms generation	11
4. Evaluation and Results	13
4.1. Scenario Classification	13
4.2. Performance metrics	13
4.3. Dyspan setup comparison	13
5. Live implementation in GNURadio	15
6. Conclusion	17
A. Abbreviations	19

1. Introduction

Back in 1999, Joseph Mitola III coined the term Cognitive Radio (CR)[MM99] as a way to enhance the Software-Defined Radio (SDR) capabilities by the means of a dynamic model that, based on human intervention, improved the flexibility of devices by making them fully configurable and capable of adapting to the communication system's needs, suitable to react to the changes in the surrounding environment. A formal definition for the CR concept provided at [Hay05] encloses the term nicely by describing it as a wireless system that is *intelligent and aware of its surroundings*, whilst being able to learn, adapt and react to changes in the environment, by modifying its operation parameters such as the transmission power, the modulation scheme and its carrier frequency in real-time. Analogously, Jondral [Jon05] adopts the short definition for CR as "an SDR that additionally senses its environment, tracks changes, and possibly reacts upon its findings", becoming an autonomous unit with the potential of using the spectrum efficiently.

CR systems are intended to be immerse in a network, where it interacts with other systems that could be cognitive or non-cognitive radios. According to [GAMS], CR is grouped under three paradigms: underlay, overlay and interweave. The *Underlay Paradigm* allows the CR system to operate under acceptable levels of interference, determined by an interference threshold. Here, the CR is commonly called a Secondary User (SU), providing priority to the other systems in the network which it should not significantly interfere, known also as Primary User (PU). In the *Overlay Paradigm*, the cognitive transmitter knows information about the other transmitters in the network, such as their codebooks and modulation schemes. In addition, this model assumes that message that is being transmitted is known by the CR when transmission by a non-cognitive system is initiated. This provides the cognitive system with multiple choices on how to use this information: for instance, it can be used to mitigate or completely cancel a possible interference happening in the network during transmission. Additionally, the cognitive system could also retransmit this message to other non-cognitive systems in the network, acting as a relay and, effectively, assist increasing the Signal-to-Noise-Ratio (SNR) of the non-cognitive system to a level equivalent to the possible decrease due to CR transmissions. The *Interweave Paradigm*, or opportunistic communication, identifies temporary space-time-frequency gaps where it can intelligently allocate its transmission, increasing the available resource utilization and minimizing the interference with other active users. Hybrid schemes are also actively being developed [WN07] [KWS⁺15] [WKM⁺17], where characteristics from different paradigms are combined in order to achieve an effective use of the available communication resources.

The main characteristic required to apply any of the aforementioned paradigms is awareness, being it in regard of location, spectrum, time, etc. Awareness is achieved by the means of *the cognition cycle* [MM99], which can be seen in Fig. 1.1, which enfolds the way the CR parses the stimuli from the outside world in order to plan accordingly the proper reactions. This cognition cycle revolves around the following concepts:




Figure 1.1.: The cognition Cycle[MM99]

- **Observation:** the CR receives any signals from the external world, which can contain any type of information that the system can use in its favor and the favor of a better use of its resources.
- **Orientation:** The CR determines the priority from the received signal as well as the type of reaction based on it.
- **Planning:** results from a normal-level priority, where a plan is generated and the sequence of actions to be taken are established.
- **Decision:** selects among the plan candidates the best proposal and allocates the necessary resources for its carrying-out.
- **Acting:** initiates the decided processes.
- **learning:** is an integration of observations and decisions, based on past and current states that are compared with expectations. When an expectation is met, the system achieves effectiveness. When not, observations are recorded and kept for further learning.

These aspects of CR come in handy when trying to solve one of the current major issues of communication systems: Spectrum Scarcity. The access to radio spectrum is highly regulated by government agencies such as the U.K. Offices of Communications (OfCOM), the Federal Communications Commission (USA) (FCC) and the International Telecommunications Union (ITU), and its access has been historically granted to the highest bidder on so-called *Spectrum Auctions* [Jon05] [SW14]. Therefore, the seek of new technologies that allow a more efficient access to the spectrum is paramount. In an effort to find effective solutions for this increasing issue, the Institute of Electrical and Electronics Engineers (IEEE) created a Standards Committee back in 2005 which, in association with the IEEE Communications Society (ComSoc) and the IEEE Electromagnetic Compatibility Society (EMC) dealt with the generation of standards for dynamic spectrum management. This committee

was dissolved between 2007 and 2010 and, after organizational restructuring, the functions of standardization and spectrum management was handed to the Standards Coordinating Committee 41 (SCC41) - Dynamic Spectrum Access Networks (DySpan) [IEE15]. As part of this efforts to motivate state-of-art research in this regards, DySpan has organized since 2007 the *IEEE International Symposium on Dynamic Spectrum Access Networks* [Com]. Additionally, DySpan has embolden the healthy competition since 2015 by introducing the *Spectrum Challenge*, consisting on inviting team worldwide to solve a problem related with dynamic access to the spectrum and 5G implementations. The participating teams are given a set of requirements and limitations, but are encouraged to push this limits with creativity and innovation. The Karlsruhe Institute of Technology (KIT), represented by the Communications Engineering Lab (CEL), has taken part in these competitions achieving outstanding results, being awarded with the *Subjective Winner* award on 2015 [KWS⁺15] and the *Best Overall Solution* on 2017 [WKM⁺17]. This thesis utilizes the setup used at the 2017 spectrum challenge as base testbed. Fig. 1.2 shows the main characteristics of this setup.




Figure 1.2.: The DySpan Spectrum Challenge Setup [Cha]

By using this configuration and keeping the hardware and overall physical considerations (such as Bandwidth (BW), number of antennas and central frequency), the idea of the challenge was to achieve the maximum throughput between the proposed SU systems, while interfering as little as possible with the existing PU. The competition consisted of two phases: during phase one the situational awareness of the proposed CR system is put under test, as it need to correctly identify the set of PU transmission parameters:

- Bandwidth and Carrier Frequency: along the 10MHz of maximum BW divided in four subchannels of 2.5MHz each, it needs to be detected if the PU is using one, two or four channels for its transmission. Effectively, it is needed to determine which frequencies are being used (identify the frequency hopping pattern) and when are they being used.
- Packed length: the PU transmitter sends packets in a bursty fashion to the corresponding receiver using packets of 100 or 1000 bytes.

- Inter arrival time between packets: the time between a packet transmission might vary from a situation to another. This times could be deterministic for some scenarios, as well as stochastic for others following a Poisson distribution. Correctly identifying the length of the packet, as well as the inter packet time of the current situation, allows to effective opportunistic access to the spectrum.

With this characteristics, a set of 10 different scenarios is built, whose parameters are depicted in Table 1.1

Scenario	Description
0	Single random channel, deterministic interpacket delay of 5ms
1	Single random channel, deterministic interpacket delay of 10ms
2	Two random channel hopping, deterministic interpacket delay of 5 ms
3	Four random channel hopping, deterministic interpacket delay of 10 ms
4	Two random channel hopping, deterministic interpacket delay of 5ms
5	Four synchronous channels, deterministic interpacket delay of 5ms
6	Four synchronous channels back-to-back, deterministic interpacket delay of 2ms
7	Four asynchronous random channels, Poisson distributed interpacket delay with mean of 20ms
8	Four asynchronous random channels, Poisson distributed interpacket delay with mean of 10ms
9	Four asynchronous random channels, Poisson distributed interpacket delay with mean of 5ms

Table 1.1.: Scenario description

The second phase of the competition regards the benchmark of the performance of the proposed SU implementation, where aspects such as innovation of the used waveform, machine learning algorithms used, and opportunistic access to the spectrum were considered. The proposed solutions, including the one proposed by CEL, can be found at [WKM⁺17], [PST⁺17], [PSK⁺17] and [LMH⁺17], where a high level of innovation and state-of-the-art research is compiled.

Being clear that *awareness* has been a primordial characteristic of CR since the conception of the concept until now, understanding that this is an area that invites to further research and considering the uprising research in the field of Artificial Intelligence (AI) algorithms, this work focuses on the learning aspect of CR, using the setup from Fig. 1.2 in order to effectively identify the scenarios described at Table 1.1. Previous research on this field covers aspects such as modulation recognition [OCC16a][OCC16b], resource allocation [ZMJ16], autoencoding and optimization of MIMO systems [OEC17], dynamic spectrum management [Hay05] and context awareness [PSK⁺17][WPR⁺17].

The outline of this thesis is as follows: an introduction to AI, focused on Machine Learning (ML) and Deep Learning (DL), alongside the most used algorithms used in academic and industrial fields is presented in 2.1. General techniques to avoid phenomena such as underfitting and overfitting of the ML are, as well, portrayed. Chapter 3 describes the details

of the testbed set up, the measurement of the data and the implementation of the machine learning models. The evaluation of the learning models is then presented in 4 with metrics of performance. The models are put into a live implementation, where the performance of the algorithms is put into test by classifying the scenarios of Table 1.1 in real-time - This is presented in chapter 5. Lastly, the conclusions and future work are summarized in chapter 6.

2. Artificial Intelligence - Introduction

HERE I PLAN TO DESCRIBE THE THEORY BEHIND THE SCENES THAT HAS BEEN USED FOR THE DEVELOPMENT OF THIS THESIS

2.1. Overview

2.2. Machine Learning

2.2.1. Training Models

2.2.2. Testing Models

2.2.3. Model Evaluation

Overfitting

Underfitting

2.2.4. Supervised Learning

2.2.5. Feature Engineering

K-nearest Neighbors

Support Vector Machines

Binary trees

2.2.6. Unsupervised Learning

2.2.7. Reinforcement Learning

2.3. Deep Learning

2.3.1. Neural Networks

2.3.2. Convolutional Neural Networks

2.3.3. Optimization of Cost Functions

3. Testbed Implementation

3.1. Software Defined Radio approach

3.1.1. GNURadio

3.1.2. Universal Software Radio Peripheral

3.2. Machine Learning models in Python and Jupyter

3.2.1. scikit-learn

3.2.2. keras

3.3. Data set Generation

3.3.1. Measure Campaign

3.3.2. Feature Engineering

3.3.3. Spectrograms generation

4. Evaluation and Results

4.1. Scenario Classification

4.2. Performance metrics

4.3. Dyspan setup comparison

5. Live implementation in GNURadio

6. Conclusion

So you made it! This is the last part of your thesis. Tell everyone what happened. You did something... and you could show that ... followed.

In the end make a personal statement. Why would one consider this thesis to be useful?

A. Abbreviations

AI	Artificial Intelligence
BW	Bandwidth
CEL	Communications Engineering Lab
ComSoc	IEEE Communications Society
CR	Cognitive Radio
DL	Deep Learning
DySpan	Dynamic Spectrum Access Networks
EMC	IEEE Electromagnetic Compatibility Society
FCC	Federal Communications Commission (USA)
LDPC	Low-Density Parity-Check
ITU	International Telecommunications Union
IEEE	Institute of Electrical and Electronics Engineers
KIT	Karlsruhe Institute of Technology
ML	Machine Learning
OFCOM	U.K. Office of Communications
PU	Primary User
SCC41	Standards Coordinating Committee 41
SDR	Software-Defined Radio
SNR	Signal-to-Noise-Ratio
SU	Secondary User

Bibliography

- [Cha] Dyspan Challenge. IEEE DySPAN | IEEE DySPAN.
- [Com] Comsoc. ComSoc Conference Search | IEEE Communications Society.
- [GAMS] Andrea Goldsmith, Syed Ali Jafar, Ivana Mari, and Sudhir Srinivasa. Breaking Spectrum Gridlock with Cognitive Radios : An Information Theoretic Perspective.
- [Hay05] Simon Haykin. Cognitive Radio : Brain-Empowered. 23(2):201–220, 2005.
- [IEE15] IEEE DySPAN. IEEE DySPAN Standards Committee (DySPAN-SC), 2015.
- [Jon05] Friedrich K Jondral. Software-Defined Radio—Basics and Evolution to Cognitive Radio. *EURASIP Journal on Wireless Communications and Networking*, 3:275–283, 2005.
- [KWS⁺15] Ankit Kaushik, Felix Wunsch, Andrej Sagainov, Nicolas Cuervo, Johannes Demel, Sebastian Koslowski, J Holger, and Friedrich Jondral. Spectrum Sharing for 5G Wireless Systems. (1):6–7, 2015.
- [LMH⁺17] Alex Lackpour, Sean Mason, Chase Hamilton, David Tigreros, Matthew Giovannucci, Matthew Marcou, Yuqiao Liu, Marko Jacovic, and Kapil R. Dandekar. Design and implementation of the Secondary User-Enhanced Spectrum Sharing (SUESS) radio. In *2017 IEEE International Symposium on Dynamic Spectrum Access Networks (DySPAN)*, pages 1–2. IEEE, mar 2017.
- [MM99] Joseph Mitola and Gerald Q. Maguire. Cognitive radio: making software radios more personal. *IEEE Personal Communications*, 6(4):13–18, 1999.
- [OCC16a] Timothy J. O’Shea, Johnathan Corgan, and T. Charles Clancy. Convolutional radio modulation recognition networks. *Communications in Computer and Information Science*, 629:213–226, 2016.
- [OCC16b] Timothy J. O’Shea, Johnathan Corgan, and T. Charles Clancy. Unsupervised Representation Learning of Structured Radio Communication Signals. apr 2016.
- [OEC17] Timothy J. O’Shea, Tugba Erpek, and T. Charles Clancy. Deep Learning Based MIMO Communications. pages 1–9, 2017.
- [PSK⁺17] Francisco Paisana, Ahmed Selim, Maicon Kist, Pedro Alvarez, Justin Tallon, Christian Bluemm, Andre Puschmann, and Luiz Dasilva. Context-Aware Cognitive Radio Using Deep Learning. *IEEE International Symposium on Dynamic Spectrum Access Networks (DYSPAN), Spectrum Challenge*, pages 1–2, 2017.

- [PST⁺17] Stefanos Papadakis, Manolis Surligas, Kostis Triantafyllakis, George Vardakis, Athanasios Gkiolias, Nikolaos Karamolegos, and Antonis Makrogiannakis. An agile OFDM cognitive radio engine. In *2017 IEEE International Symposium on Dynamic Spectrum Access Networks (DySPAN)*, pages 1–2. IEEE, mar 2017.
- [SW14] G. Staple and K. Werbach. The end of spectrum scarcity. *IEEE Spectrum*, 41(3):48–52, mar 2014.
- [WKM⁺17] Felix Wunsch, Sebastian Koslowski, Sebastian Muller, Nicolas Cuervo, and Friedrich K. Jondral. A cognitive overlay system based on FBMC. *2017 IEEE International Symposium on Dynamic Spectrum Access Networks, DySPAN 2017*, pages 6–7, 2017.
- [WN07] Zhiqiang Wu and Bala Natarajan. Interference tolerant agile cognitive radio maximize channel capacity of cognitive radio. In *2007 4th Annual IEEE Consumer Communications and Networking Conference, CCNC 2007*, pages 1027–1031. IEEE, jan 2007.
- [WPR⁺17] Felix Wunsch, Francisco Paisana, Sreeraj Rajendran, Ahmed Selim, Pedro Alvarez, Sebastian Muller, Sebastian Koslowski, Bertold Van den Bergh, and Sofie Pollin. DySPAN Spectrum Challenge: situational awareness and opportunistic spectrum access benchmarked. *IEEE Transactions on Cognitive Communications and Networking*, pages 1–1, 2017.
- [ZMJ16] Alessio Zappone, Bho Matthiesen, and Eduard A. Jorswieck. Energy-efficient MIMO overlay communications for device-To-device and cognitive radio systems. In *2016 IEEE Wireless Communications and Networking Conference Workshops, WCNCW 2016*, pages 115–120. IEEE, apr 2016.