



Identity Round Robin Workshop

Permission Boundaries

AWS Pop-up Loft

Greg McConnel

Solutions Architect
Amazon Web Services (AWS)



Agenda

- Intro
 - Permission boundary basics
 - Policy categories
 - Permission boundary mechanism
 - Resource restrictions
 - Q & A
-
- Workshop
 - Final Q & A


What are permission boundaries?

Mechanism to delegate the permission to create users and roles while preventing privilege escalation or unnecessarily broad permissions.


Use cases

- Developers that need to create roles for Lambda functions
- Application owners that need to create roles for EC2 instances
- Admins that need to be able to create users for particular use cases
- Any others?


Two viewpoints – the problem



Two viewpoints – old solution 1



Two viewpoints – old solution 2



Permission boundary basics

Before and After Permission Boundaries


Before

- Certain IAM policy actions (e.g. PutUserPolicy, AttachRolePolicy) are **essentially full admin-like permissions**.
- Doing any form of self-service permissions management **was non-trivial**.

Now

- Administrator can grant full admin-like permissions, but **specify a "permissions boundary."**
- **Allow developers to create principals** for their applications and attach policies, but only **within the boundary**.

Permission Boundaries – mechanism



A condition

```
"Condition": {"StringEquals":  
  {"iam:PermissionsBoundary":  
    "arn:aws:iam::ACCOUNT_ID:policy/permissionboundary"  
  }  
}
```

A condition applied to principal creation actions (users and roles)

```
"Effect": "Allow",
"Action": ["iam:CreateRole"],
"Resource": ["arn:aws:iam::ACCOUNT_ID:role/path/"],
"Condition": {"StringEquals":
  {"iam:PermissionsBoundary":
    "arn:aws:iam::ACCOUNT_ID:policy/permissionboundary"
  }
}
```

Mechanism

Developer creates a role for a Lambda function

Step 1: Create role

```
$ aws iam create-role --role-name roleforlambda  
--assume-role-policy-document file://Role_Trust_Policy_Text.json  
--permissions-boundary arn:aws:iam::<ACCOUNT_NUMBER>:policy/department_a/boundary_1
```


Step 2: Create policy

No change

Step 3: Attach policy


No change

Two viewpoints – the new solution




Policy categories


Policy permission categories



Policy permission categories



But, it's just an IAM policy right?



But, it's just an IAM policy right?

▼ Attach permissions policies

Choose one or more policies to attach to your new role.

Create policy

Identity-based policy slot

Filter policies ▼

Showing 582 results

	Policy name ▼	Used as	Description
<input type="checkbox"/>	▶ AdministratorAccess	Permissions policy (9)	Provides full access to AWS services an...
<input type="checkbox"/>	▶ AlexaForBusinessDeviceSetup	None	Provide device setup access to AlexaFor...
<input type="checkbox"/>	▶ AlexaForBusinessFullAccess	None	Grants full access to AlexaForBusiness r...
<input type="checkbox"/>	▶ AlexaForBusinessGatewayExecution	None	Provide gateway execution access to AI...
<input type="checkbox"/>	▶ AlexaForBusinessReadOnlyAccess	None	Provide read only access to AlexaForBu...
<input type="checkbox"/>	▶ AllowAssumeDeleteDDBRole	None	
<input type="checkbox"/>	▶ AllowDeleteofDDBTable	Permissions policy (1)	
<input type="checkbox"/>	▶ AmazonAPIGatewayAdministrator	None	Provides full access to create/edit/delete...

▼ Set permissions boundary

Set a permissions boundary to control the maximum permissions this role can have. This is an advanced feature used to delegate permission management to others. [Learn more](#)


☒ Create role without a permissions boundary

☐ Use a permissions boundary to control the maximum role permissions

Permission boundary slot

Permission boundary mechanism

Policy permission categories



Everything after authentication


1. **Authenticate** the principal

2. Determine which **policies** apply to the request


3. **Evaluate** the different policy types that apply which affect the order in which they are evaluated.

4. **Allow or Deny** the request

Effective Permissions - intersection




Effective permissions – mechanism




Effective permissions – mechanism


Resulting permission



Effective permissions – mechanism



Effective permissions – allow example



Effective permissions – scenario 1

Request: s3:GetObject / bucket name: example1


Permission Boundary

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogGroup",
        "logs:CreateLogStream",
        "logs:PutLogEvents"
      ],
      "Resource": "arn:aws:logs:*:*:*"
    }
  ]
}
```

Permission Policy

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogGroup",
        "logs:CreateLogStream",
        "logs:PutLogEvents",
        "s3:*"
      ],
      "Resource": "*"
    }
  ]
}
```

Effective permissions – mechanism



Effective permissions – scenario 1

Request: s3:GetObject / bucket name: example1


Permission Boundary

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogGroup",
        "logs:CreateLogStream",
        "logs:PutLogEvents"
      ],
      "Resource": "arn:aws:logs:*:*:*"
    },
    {
      "Effect": "Allow",
      "Action": ["s3:GetObject"],
      "Resource": "arn:aws:s3:::example1/*"
    }
  ]
}
```

Permission Policy

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogGroup",
        "logs:CreateLogStream",
        "logs:PutLogEvents",
        "s3:*"
      ],
      "Resource": "*"
    }
  ]
}
```

Effective permissions – mechanism



Effective permissions – scenario 1

Request: s3:GetObject / bucket name: example1


Permission Boundary

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogGroup",
        "logs:CreateLogStream",
        "logs:PutLogEvents"
      ],
      "Resource": "arn:aws:logs:*:*:*"
    },
    {
      "Effect": "Allow",
      "Action": ["s3:GetObject"],
      "Resource": "arn:aws:s3:::example1/*"
    }
  ]
}
```


Permission Policy

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogGroup",
        "logs:CreateLogStream",
        "logs:PutLogEvents"
      ],
      "Resource": "*"
    }
  ]
}
```


Effective permissions – mechanism



Effective permissions – mechanism



Resource Restrictions

Goal: carve out a space for the delegated admins to be able to modify resources without impacting other resources.

<https://docs.aws.amazon.com/general/latest/gr/aws-arns-and-namespaces.html#arns-paths>

https://docs.aws.amazon.com/IAM/latest/UserGuide/reference_identifiers.html#identifiers-arns

Resource Restrictions

- We are granting admin-like permissions (create and delete policies and roles)
- Permission boundary is one part of the delegation
- The other part is restricting the policies and roles they can impact then they could

```
"Effect": "Allow",  
"Action": [  
    "iam:CreatePolicy",  
    "iam:DeletePolicy",  
    "iam:CreatePolicyVersion",  
    "iam:DeletePolicyVersion",  
    "iam:SetDefaultPolicyVersion"  
],  
"Resource": "*/"
```

Resource Restrictions

Resource restriction using paths:

arn:aws:iam::123456789012:role/**department1/***

Example role: arn:aws:iam::123456789012:role/**department1/role1**

Resource restriction using names:

arn:aws:iam::123456789012:policy/**development-users***

Example policy: arn:aws:iam::123456789012:policy/**development-users-policy1**

Resource Restrictions - policies

- Examine permissions assigned to a delegated admin to create policies
- If there is not a resource restriction then the delegated admins could modify any customer managed policies

```
"Effect": "Allow",  
"Action": [  
    "iam:CreatePolicy",  
    "iam:DeletePolicy",  
    "iam:CreatePolicyVersion",  
    "iam:DeletePolicyVersion",  
    "iam:SetDefaultPolicyVersion"  
],  
"Resource": ""
```

VS

```
"Effect": "Allow",  
"Action": [  
    "iam:CreatePolicy",  
    "iam:DeletePolicy",  
    "iam:CreatePolicyVersion",  
    "iam:DeletePolicyVersion",  
    "iam:SetDefaultPolicyVersion"  
],  
"Resource":  
    "arn:aws:iam::ACCOUNT_ID:policy/path/name"
```

Resource Restrictions - roles

- Just like with policies we want to carve out a safe space for roles.
- Permission boundaries play a part here, but not all actions support the condition
- In addition different teams could be using the same permission boundaries

```
"Effect": "Allow",  
"Action": [  
    "iam:UpdateRole",  
    "iam:DeleteRole"  
],  
"Resource": ""
```

VS

```
"Effect": "Allow",  
"Action": [  
    "iam:UpdateRole",  
    "iam:DeleteRole"  
],  
"Resource":  
    "arn:aws:iam::ACCOUNT_ID:role/path/name*"
```

Presentation Q & A

Presentation Q & A

- How does a permission boundary differ from a standard IAM policy?
- What would happen if we delegated permissions without resource restrictions?
- The scenario where you have user in an account that need to be able to create IAM polices, roles and Lambda functions is common. How was this situation handled before permission boundaries came along?

Agenda reminder

- Intro
- Permission boundary basics
- Policy categories
- Permission boundary mechanism
- Resource restrictions
- Q & A
- Workshop
- Final Q & A

Workshop Overview


Workshop

The round is broken down into a BUILD and VERIFY phase.

BUILD (60 min): First each team will carry out the activities involved in the BUILD phase.

VERIFY (30 min): Each team will carry out the VERIFY activities as if they were part of the web admin team.

Workshop



Workshop

Final Q & A

Final Q & A

- What is the fundamental mechanism of permission boundaries?
- There are two ways of doing resource restrictions (naming and pathing.)
Which option allows you to create policies using both the AWS Console and CLI?
- Is there an advantage to using one over the other?
- Why do we not allow the web admins to attach any role to the Lambda functions?

End of day survey

<https://tinyurl.com/yb6naz8f>

