Section 2 / Floating Point Literals

Recall that all AARCH64 instructions are 4 bytes long. Recall also that this means that there are constraints on what can be specified as a literal since the literal must be encoded into the 4 byte instruction. If the literal is too large, an assembler error will result.

Given that floating point values are always at least 4 bytes long themselves, using floating point literals is extremely constrained. For example:

```
fmov    d0, 1     // 1
fmov    d0, 1.1   // 2
```

`Line 1` will pass muster but `Line 2` will cause an error.

To load a `float`, you could translate the value to binary and do as the following:

```
        .text                           // 1
        .global main                    // 2
        .align    2                     // 3
                                        // 4
main:   str       x30, [sp, -16]!       // 5
        ldr       s0, =0x3fc00000       // 6
        fcvt      d0, s0                // 7
        ldr       x0, =fmt              // 8
        bl        printf                // 9
        ldr       x30, [sp], 16         // 10
        mov       w0, wzr               // 11
        ret                             // 12
                                        // 13
        .data                           // 14
fmt:    .asciz    "%f\n"                // 15
        .end                            // 16
```

The above code is kind of found here - the file is used for miscellaneous testing.

`Line 6` puts the translated value of 1.5 into `s0` (since we are thinking of the value as a `float` it goes in an `s` register). The assembler performs some magic getting a 32 bit value seemingly fit into a 32 bit instruction. See below.

`Line 7` converts the single precision number into a double precision number for printing.

*printf() only knows how to print double precision values. When you specify a float, it will convert it to a **double** before emitting it.*

Translating `floats` and `doubles` by hand isn't a common practice for humans, though compilers are happy to do so.

Instead for us humans, the assembler directives `.float` and `.double` are used more frequently to specify `float` and `double` values putting them into RAM.

1

The following example prints an array of floats and doubles:

```
        .global main                                        // 1
        .text                                               // 2
        .align  2                                           // 3
                                                            // 4
counter .req    x20                                         // 5
dptr    .req    x21                                         // 6
fptr    .req    x22                                         // 7
        .equ    max, 4                                      // 8
                                                            // 9
main:   stp     counter, x30, [sp, -16]!                    // 10
        stp     dptr, fptr, [sp, -16]!                      // 11
        ldr     dptr, =d                                    // 12
        ldr     fptr, =f                                    // 13
        mov     counter, xzr                                // 14
                                                            // 15
1:      cmp     counter, max                                // 16
        beq     2f                                          // 17
                                                            // 18
        ldr     d0, [dptr, counter, lsl 3]                  // 19
        ldr     s1, [fptr, counter, lsl 2]                  // 20
        fcvt    d1, s1                                      // 21
        ldr     x0, =fmt                                    // 22
        add     counter, counter, 1                         // 23
        mov     x1, counter                                 // 24
        bl      printf                                      // 25
        b       1b                                          // 26
                                                            // 27
2:      ldp     dptr, fptr, [sp], 16                        // 28
        ldp     counter, x30, [sp], 16                      // 29
        mov     w0, wzr                                     // 30
        ret                                                 // 31
                                                            // 32
        .data                                               // 33
fmt:    .asciz  "%d %f %f\n"                                // 34
d:      .double 1.111111, 2.222222, 3.333333, 4.444444      // 35
f:      .float  1.111111, 2.222222, 3.333333, 4.444444      // 36
                                                            // 37
        .end                                                // 38
```

The above code is found here.

A number of interesting things in this source code:

- We use .req to give symbolic names to various registers. This can help you in remembering which register is being used for what purpose.

- We use `.equ` to encode a small integer literal value to give it a symbolic name, eliminating the use of a "magic number."

- `Lines 19` and `20` use address arithmetic to march through an array of doubles (8 bytes each) and an array of floats (4 bytes each).

`Line 19` is equivalent to:

```
//   ldr      d0, [dptr, counter, lsl 3]
d0 = dptr[counter];
```

`counter` is multiplied by 8 then added to `dptr`.

`Line 20` is equivalent to:

`counter` is multiplied by 4 then added to `fptr`.

```
//   ldr      s1, [fptr, counter, lsl 2]
s1 = fptr[counter];
```

Cool huh?

Fitting 32 bits into a 32 bit bag

This section is currently LINUX-centric - in the future it will address both native Apple and Linux equally.*

AARCH64 instructions are 32 bits in width. Yet, `line 6` from this program reads:

```
        ldr        s0, =0x3fc00000                              // 6
```

This appears to show a 32 bit constant being held in an instruction that itself is 32 bits wide. Well, the Assembler does some magic. Let's see what that magic is.

Build the program with the `-g` option to enable debugging using GDB.

`% gcc -g t.s`

Then launch GDB on the executable:

`% gdb a.out`

Set a breakpoint on line 6.

```
(gdb) b 6
Breakpoint 1 at 0x784: file t.s, line 6.
(gdb)
```

Enter a cool GDB layout (one of several cool layouts):

`layout asm`

3

Figure 1: gdb01

You should see something like this:

We expected `line 6` to read:

```
        ldr         s0, =0x3fc00000
```

Instead we find:

```
b+ 0x784 <main+4>              ldr      s0, 0x7a0 <main+32>
```

Scan downward to find `0x7a0`:

```
    0x7a0 <main+32>            .inst    0x3fc00000 ; undefined
```

Hey look! Here's our literal float. The `.inst` is an ARM specific GNU assembler directive says: ¯_(-)_/¯.

Note, the encoded "instruction" does not have to make any sense - instead the compiler has emitted a make believe instruction that happens to have the value of our literal.

What we're seeing the actual `line 6` doing is reaching ahead a short distance to load the value of another location in memory where our constant is really found.

Let us take this explanation further. Notice we see:

```
    0x78c <main+12>            ldr      x0, 0x7a8 <main+40>
```

where we expected:

```
        ldr         x0, =fmt
```

Scan down to `0x7a8`:

```
  0x7a8 <main+40>            .inst   0x00011010 ; undefined
```

`x0` is serving as a pointer to the format string of a call to `printf()`. Let's follow the pointer. . .

```
(gdb) x/s 0x00011010
0x11010:        "%f\n"
(gdb)
```

Magic.