Data Sheet

CN333 North Bridge

with Integrated UniChrome Pro 3D / 2D Graphics Controller

Preliminary Revision 0.74
September 20, 2004

VIA TECHNOLOGIES, INC.

Copyright Notice:

Trademark Notices:

VT8237 and CN333 may only be used to identify products of VIA Technologies.

C3™ and PowerSaver™ are registered trademarks of VIA Technologies.
Windows XP™, Windows 2000™, Windows ME™, Windows 98™ and Plug and Play™ are registered trademarks of Microsoft Corporation.
PCI™ is a registered trademark of the PCI Special Interest Group.
VESA™ is a trademark of the Video Electronics Standards Association.
All trademarks are the properties of their respective owners.

Disclaimer Notice:

No license is granted, implied or otherwise, under any patent or patent rights of VIA Technologies or S3 Graphics. VIA Technologies and S3 Graphics make no warranties, implied or otherwise, in regard to this document and to the products described in this document. The information provided by this document is believed to be accurate and reliable as of the publication date of this document. However, VIA Technologies and S3 Graphics assume no responsibility for any errors in this document. Furthermore, VIA Technologies and S3 Graphics assume no responsibility for the use or misuse of the information in this document and for any patent infringements that may arise from the use of this document. The information and product specifications within this document are subject to change at any time, without notice and without obligation to notify any person of such change.

Offices:

VIA Technologies Incorporated
Taiwan Office:
8th Floor, No. 533
Chung-Cheng Road, Hsin-Tien
Taipei, Taiwan ROC
Tel: (886-2) 2218-5452
Fax: (886-2) 2218-5453
Home page: http://www.via.com.tw

VIA Technologies Incorporated
USA Office:
940 Mission Court
Fremont, CA 94539
USA
Tel: (510) 683-3300
Fax: (510) 683-3301 or (510) 687-4654
Home Page: http://www.viatech.com

S3 Graphics Incorporated
USA Office:
1045 Mission Court
Fremont, CA 94539
USA
Tel: (510) 687-4900
Fax: (510) 687-4901
Home Page: http://www.s3graphics.com

REVISION HISTORY

Document Release	Date	Revision	Initials
0.6	7/16/04	Initial internal release	SV
0.7	7/26/04	Updated the system block diagram Removed video capture support	SV
0.71	7/29/04	Fixed figure 2 Updated VT1632 to VT1632A	SV
0.72	8/9/04	Fixed figure 2: removed DVP0 block	SV
0.73	8/23/04	Removed registered DIMM support	SV
0.74	9/20/04	Updated the south bridge to VT8237 Removed global motion compensation support in product feature Updated D0 F3 Rx68[3:0], system block diagram and table 1 Updated register descriptions: removed D0 F0 Rx40-44, 4A-4D, 80-C3 and D1 Rx45	SV

TABLE OF CONTENTS

LIST OF FIGURES

LIST OF TABLES

CN333 NORTH BRIDGE

133 / 100 MHz VIA C3 Front Side Bus
Integrated UniChrome Pro 3D / 2D Graphics and Video Controllers
Advanced DDR333 SDRAM Controller
1 GB / Sec Ultra V-Link Interface

PRODUCT FEATURES

- **Defines Highly Integrated Solutions for Full Featured, Power Efficient PC Designs**
  - High Performance UMA North Bridge: Integrated VIA C3 North Bridge with 133 / 100 MHz FSB support and UniChrome Pro 3D / 2D Graphics and Video Controllers in a single chip
  - Advanced memory controller supporting DDR 333 / 266 / 200 SDRAM
  - Combines with VIA VT8235-CE / VT8237 South Bridge for integrated 10/100 LAN, Audio, ATA133 IDE, LPC, USB 2.0 and Serial ATA (VT8237)
  - "Lead-Free" 31 x 31mm HSBGA (Ball Grid Array with Heat Spreader) package with 681 balls and 1mm ball pitch
- **High Performance CPU Interface**
  - Supports 133 / 100 MHz FSB VIA C3 processors
  - Eight outstanding transactions (eight-level In-Order Queue (IOQ))
  - Built-in Phase Lock Loop circuitry for optimal skew control within and between clocking regions
- **Advanced High-Performance 64-Bit DDR SDRAM Controller**
  - Supports DDR333 / 266 memory types with 2.5V SSTL-2 DRAM interface
  - Supports mixed 64 / 128 / 256 / 512 / 1024Mb DDR SDRAMs in x8 and x16 configurations
  - Supports CL 2 / 2.5 for DDR266 / 333
  - Supports 2 unbuffered double-sided DIMMs and up to 4 GBytes of physical memory
  - Programmable timing / drive for memory address, data and control signals
  - DRAM interface pseudo-synchronous with host CPU for optimal memory performance
  - Concurrent CPU, internal graphics controller and V-Link access for minimum memory access latency
  - Rank interleave and up to 16-bank page interleave (i.e., 16 pages open simultaneously) based on LRU to effectively reduce memory access latency
  - Seamless DRAM command scheduling for maximum DRAM bus utilization
    - (e.g., precharge other banks while accessing the current bank)
  - CPU Read-Around-Write capability for non-stalled operation
  - Speculative DRAM read before snoop result to reduce PCI master memory read latency
  - Supports Burst Read and Write operations with burst length of 4 or 8
  - Eight cache lines (64 quadwords) of integrated CPU-to-DRAM write buffers and eight separate cache lines of CPU-to-DRAM read prefetch buffers
  - Optional dynamic Clock Enable (CKE) control for DRAM power reduction during normal system state (S0)
  - Supports self-refresh and CAS-before-RAS DRAM refresh with staggered RAS timing
- **High Bandwidth 1 GB / Sec 16-Bit "Ultra V-Link" Host Controller**
  - Supports 66 MHz, 4x and 8x transfer modes, Ultra V-Link Host interface with 1 GB / Sec total bandwidth
  - Full duplex transfers with separate command / strobe for 4x and 8x modes
  - Request / Data split transaction
  - Transaction assurance for V-Link Host-to-Client access eliminates V-Link Host-Client Retry cycles
  - Intelligent V-Link transaction protocol to minimize data wait-states, throttle transfer latency and avoid data overflow
  - Highly efficient V-Link arbitration with minimum overhead

- **Advanced System Power Management Support**
  - ACPI 2.0 and PCI Bus Power Management 1.1 compliant
  - Supports Suspend-to-DRAM (STR) and DRAM self-refresh
  - Supports dynamic Clock Enable (CKE) control for DRAM power reduction during normal system state (S0)
  - Supports SMI, SMM and STPCLK mechanisms
  - Supports VIA PowerSaver™ Technology
  - Low-leakage I/O pads
- **Integrated Graphics with 2D / 3D / Video Controllers**
  - Optimized Unified Memory Architecture (UMA)
  - Supports 16 / 32 / 64 MB Frame Buffer sizes
  - 200 MHz Graphics Engine Clock
  - Two independent 128-bit data paths between North Bridge and graphics core to improve video performance, one for frame buffer access and one for texture / command access
  - PCI v2.2 Host Bus compliant
  - AGP v3.0 compliant

2D Acceleration

- 128-bit 2D graphics engine
- Hardware 2D rotation
- Supports ROP3, 256 operations
- Supports 8bpp, 15/16bpp and 32bpp color depth modes
- BitBLT (Bit BLock Transfer) functions including alpha BLTs
- True-color hardware cursor (64x64x32bpp) with 256-level blending effect
- Color expansion, source Color Key and destination Color Key
- Bresenham line drawing / style line function
- Transparency mode
- Window clipping
- Text function

3D Acceleration

3D Graphics Processor

- 128-bit 3D graphics engine
- Dual pixel rendering pipes and dual texture units
- Floating-point setup engine
- Internal full 32-bit ARGB format for high rendering quality
- 8K Texture Cache

Capability

- Supports ROP2
- Supports various texture formats including 16/32bpp ARGB, 8bpp Palletized (ARGB), YUV 422/420 and compressed texture (DXTC)
- Texture sizes up to 2048x2048 with Microsoft DirectX texture compression
- High quality texture filter for Nearest, Linear, Bi-linear, Tri-linear and Anisotropic modes
- Flat and Gouraud shading
- Vertex Fog and Fog Table
- Z-Bias, LOD-Bias, Polygon offset, Edge Anti-aliasing and Alpha Blending
- Bump mapping and cubic mapping
- Hardware back-face culling
- Specular lighting

Performance

- Two textures per pass
- Triangle rate up to 4.5 million triangles per second
- Pixel rate up to 200 million pixels per second for 2 textures each
- Texel bilinear fill rate up to 400 million texels per second
- High quality dithering

Video Acceleration

High Quality Video Processor

- RGB555, RGB565, RGB8888 and YUV422 video playback formats
- High quality 5-tap horizontal and 5-tap vertical scaler (up or down) for both horizontal and vertical scaling(linear interpolation for horizontal and vertical p-scaling and filtering for horizontal and vertical down-scaling)
- Independent graphics and video gamma tables
- 2 sets of Color and Chroma Key support
- Color enhancement for contrast, hue, saturation and brightness
- Display rotation in clockwise and counter-clockwise directions
- Bob, Weave, Median-filter and Adaptive de-interlacing modes
- 3:2 / 2:2 pull-down detection
- De-blocking mode support
- Combining of many special effects such as filter, scaling up or down, sub-picture blending, de-interlacing and deblocking to one pass process
- Tear-free double / triple buffer flipping
- Input video vertical blanking or line interrupt
- Video gamma correction

Video Overlay Engine

- Simultaneous graphics video playback overlay
- Supports video window overlays
- Supports 16 operations for Color and Chroma Key
- Hardware sub-picture blending

MPEG Video Playback

- MPEG-2 hardware VLD (Various Length Decode), iDCT, and motion compensation for full speed DVD and MPEG-2 playback at full D1 resolution
- High quality DVD and streaming video playback
- Video auto-flipping
- Hardware DVD sub-picture blending

DuoView+™ Dual Image Capability

- WinXP, WinME and Win98 multi-monitor, extended desktop support
- Two independent display engines, each of which can display completely different information at different resolutions, pixel depths and refresh rates (supports different images on different displays simultaneously)
- CRT, FPD and DVI monitor refresh rates are independently programmable for optimum image quality
- Improved display flexibility with simultaneous FPD / CRT, FPD, FPD / DVI and other combined operations

Full Software Support

- Microsoft DirectX 7.0, 8.0 and 9.0 compatible
- Microsoft DirectX Texture Compression (DXTC / S3TC)
- Supports OpenGL™
- Drivers for major operating systems and APIs: Windows® 9x/ME, Windows 2000, Windows XP, Direct3D™, DirectDraw™, DirectShow™ and OpenGL™ ICD for Windows 9x/ME and XP
- Windows NT 4.0 Standard VGA driver

- **Extensive Display Support for External Video Output**
  - CRT display interface
  - 12-bit Digital Video Port with support for external DVI transmitter
  - 24-bit / Dual 12-Bit FPD interface to external LVDS transmitter

CRT Display

- CRT display interface with 24-bit true-color RAMDAC up to 300 MHz pixel rate with gamma correction capability
- Supports CRT resolutions up to 1920 x 1440

12-Bit DVI Transmitter Interface

- 1.5V low-swing interface supports external DVI transmitter for a driving a DVI monitor
- Double-data-rate data transfer with clock rates up to 165 MHz
- Built-in digital phase adjuster to fine-tune signal timing between clock and data bus

24-Bit Flat Panel Display (FPD) Interface

- Supports 18/24-bit FPD interface with external LVDS transmitter chip using single or double-data rate data transfer
- Supports panel resolutions up to 1600x1200

Dual 12-Bit Flat Panel Display (FPD) Interface

- Alternate operating mode of FPD interface with external LVDS transmitters
- Single or separate sets of clock and sync signals
- Supports panel resolutions up to 1600x1200

- **Advanced Graphics Power Management Support**
  - Built-in reference voltage generator and monitor sense circuits
  - Automatic panel power sequencing and VESA DPMS (Display Power Management Signaling) CRT power-down
  - External I/O signal controls enabling of graphics accelerator into standby / suspend-off state
  - Dynamic clock gating for inactive functions to achieve maximum power saving
  - I^2C Serial Bus and DDC / E-DDC Monitor Communications for Plug-and-Play configuration

CN333 System Overview

The CN333 is a high performance, cost-effective and energy efficient UMA North Bridge with integrated UniChrome Pro graphics / video controller used for the implementation of mobile and desktop personal computer systems with 133 / 100 MHz CPU host bus ("Front Side Bus") based on VIA C3 processors.



Figure 1. System Block Diagram

The complete chipset consists of the CN333 North Bridge and the VT8237 V-Link South Bridge. The CN333 integrates VIA's most advanced system controller with a high-performance UniChrome Pro 3D / 2D graphics / video controller plus flat panel and DVI monitor. The CN333 provides superior performance between the CPU, DRAM, V-Link and integrated graphics controller with pipelined, burst and concurrent operation. The VT8237 is a highly integrated peripheral controller which includes V-Link-to-PCI / V-Link-to-LPC controllers, Ultra DMA IDE controller, USB2.0 host controller, 10/100Mb networking MAC, AC97 and system power management controllers.

VIA C3 Processor Interface

The CN333 supports 133 / 100 MHz FSB VIA C3 processors and implements an eight-deep In-Order-Queue. VIA PowerSaver technology is supported for VIA Antaur processors to reduce system power consumption while sustaining high processing power.

Memory Controller

The CN333 SDRAM controller supports up to two double-sided DDR333 / 266 DIMMs for 4 GB maximum physical memory. The DDR DRAM interface allows zero-wait-state data transfer bursting between the DRAM and the memory controller's data buffers. The different banks of DRAM can be composed of an arbitrary mixture of 64 / 128 / 256 / 512 / 1024Mb DRAMs in x8 or x16 configurations. The DRAM controller can run either synchronous or pseudo-synchronous with the host CPU bus.

Ultra V-Link

The CN333 North Bridge interfaces to the South Bridge through a high speed (up to 1 GB / Sec) 8x, 66 MHz Data Transfer interconnect bus called "Ultra V-Link". Deep pre-fetch and post-write buffers are included to allow for concurrent CPU and V-Link operation. The combined CN333 North Bridge and VT8237 South Bridge system supports enhanced PCI bus commands such as "Memory-Read-Line", "Memory-Read-Multiple" and "Memory-Write-Invalid" commands to minimize snoop overhead. In addition, advanced features are supported such as CPU write-back forward to PCI master and CPU write-back merged with PCI post write buffers to minimize PCI master read latency and DRAM utilization. Delay transaction and read caching mechanisms are also implemented for further improvement of overall system performance.

System Power Management

For sophisticated power management, the CN333 supports dynamic CKE control to minimize DDR SDRAM power consumption during normal system state (S0). A separate suspend-well plane is implemented for the memory control logic for the Suspend-to-DRAM state. VIA PowerSaver™ Technology is supported to minimize CPU power consumption while sustaining processing power. The CN333 graphics accelerator implements automatic clock gating for each graphics engine to achieve power saving, moving to standby or suspend states to further reduce power consumption when idle. Automatic panel power sequencing and VESA DPMS (Display Power Management Signaling) CRT power-down are supported. Coupled with the VT8237 South Bridge chip, a complete power conscious PC main board can be implemented with no external glue logic.

3D Graphics Engine

Featuring an integrated 128-bit 3D graphics engine, the CN333 North Bridge utilizes a highly pipelined architecture that provides high performance along with superior image quality. Several new features enhance the 3D architecture, including two pixel rendering pipes, single-pass multitexturing, bump and cubic mapping, texture compression, edge anti-aliasing, vertex fog and fog table, hardware back-face culling, specular lighting, anisotropic filtering and an 8-bit stencil buffer. The chip also offers the industry's only simultaneous usage of single-pass multitexturing and single-cycle trilinear filtering – enabling stunning image quality without performance loss. Image quality is further enhanced with true 32-bit color rendering throughout the 3D pipeline to produce more vivid and realistic images. The advanced triangle setup engine provides industry leading 3D performance for a realistic user experience in games and other interactive 3D applications. The 3D engine is optimized for AGP texturing from system memory.

128-bit 2D Graphics Engine

The CN333 North Bridge's advanced 128-bit 2D graphics engine delivers high-speed 2D acceleration for productivity applications. The enhanced 2D architecture with direct access frame buffer capability optimizes UMA performance and provides acceleration of all color depths.

MPEG Video Playback

The CN333 North Bridge provides the ideal architecture for high quality MPEG-2 based video applications. For MPEG playback, the integrated video accelerator offloads the CPU by performing planar-to-packed format conversion and motion video compensation tasks, while the enhanced scaling algorithm delivers incredible full-screen video playback.



Figure 2. Integrated UniChrome Pro Graphics Controller Internal Block Diagram

LCD and DVI Monitor Support

The CN333 provides two "Digital Video Port" interfaces: FPDP and GDVP1. The Flat Panel Display Port (FPDP) implements a 24-bit / dual 12-bit interface which is designed to drive a Flat Panel Display via an external LVDS transmitter chip (such as the VIA VT1631 or NSC DS90C387R). The CN333 can be connected to the external LVDS transmitter chip in either 24-bit or dual-12-bit modes. A wide variety of LCD panels are supported including VGA, SVGA, XGA, SXGA+ and up to UXGA-resolution TFT color panels, in either SDR (1 pixel / clock) or DDR (2 pixels / clock) modes. UXGA and higher resolutions require dual-edge data transfer (DDR) mode which is supported by the VIA VT1631 LVDS transmitter chip. Digital Video Port 1 (GDVP1) is used to drive a DVI monitor via an external DVI transmitter chip (such as the VIA VT1632A).

The flexible display configurations of the CN333 allow support of a flat panel (LVDS interface) or flat panel monitor (DVI interface) and CRT display at the same time. Internally the CN333 North Bridge provides two separate display engines, so if two display devices are connected, each can display completely different information at different resolutions, pixel depths and refresh rates. If more than two display devices are connected, the additional displays must have the same resolution, pixel depth and refresh rate as one of the first two. The maximum display resolutions supported for one display device are listed in the table below. If more than one display is implemented (i.e., if both display engines are functioning at the same time), then available memory bandwidth may limit the display resolutions supported on one or both displays. This will be dependent on many factors including primarily clock rates and memory speeds (contact VIA for additional information).

Desktop Modes for Single Display

		CRT Maximum Refresh				
Resolution	**Bpp**	**60**	**75**	**85**	**100**	**120**
640x480	8	√	√	√	√	√
	16	√	√	√	√	√
	32	√	√	√	√	√
800x600	8	√	√	√	√	√
	16	√	√	√	√	√
	32	√	√	√	√	√
1024x768	8	√	√	√	√	
	16	√	√	√	√	
	32	√	√	√	√	
1280x1024	8	√	√	√		
	16	√	√	√		
	32	√	√	√		
1400x1050	8	√				
	16	√				
	32	√				
1600x1200	8	√	√	√		
	16	√	√	√		
	32	√	√1	√2		
1920x1440	8	√	√			
	16	√	√			
	32	√	√			

Table 1. Supported CRT and Panel Screen Resolutions

Key for Desktop Mode

√ = Supported: Mode available and Overlay available
√1 = Supported, but DDR266: Mode available, overlay not available.
√2 = Supported, but DDR266: Mode not available, overlay not available.

Note: LCD Single Display modes follow the 60Hz refresh column.

PINOUTS

Pin Diagrams

Figure 3. Ball Diagram (Top View) – Flat Panel / Digital Video Output

Key	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A			HD 28#	HD 29#	HD 25#	HD 26#	HD 16#	HD 13#			GND	HD 5#	HD 15#	GND	HA 23#	HA 19#	GND			HA 11#	BNR#	NC	GND	DE FER#	HREQ 0#	GND	D RDY#	ADS#	GND	
B		HD 34#	GND	HD 31#	GND	HD 24#	HD 19#	GND			HD 10#	HD 17#	HD 4#	NC	HA 30#	HA 31#	HA 15#			GND	HA 4#	NC	B PRI#	HREQ 2#	HIT M#	D BSY#	RS2#	NC		
C	HD 43#	HD 38#	HD 22#	NC	HD 32#	NC	NC	HD 20#	HD 11#	HD 12#	NC	HD 8#	HD 6#	HA 29#	HA 27#	HA 22#	HA 10#	HA 13#	HA 3#	HA 9#	HA 8#	HREQ 1#	HREQ 4#	NC	RS1#	RS0#	BREQ 0#	NC		
D	HD 37#	GND	HD 27#		GND	HD 33#	HD 21#	HD 30#	HD 14#	HD 18#	GND	HD 9#	HD 0#	GND	HA 20#	CPU RST#	GND	HA 12#	HA 5#	HA 6#	NC	HA 7#	GND	HREQ 3#	HT RDY#	GND	NC		GND	
E	NC	HD 39#	HD 36#			NC	HD 23#	GND	HD 2#		NC	NC	HD 1#	HA 26#	HA 24#	HA 21#	HA 28#	HA 16#	NC	GND		HA 14#	E	H LOCK#	HIT#					GND
F	HD 42#	NC	HD 45#	HD 44#	HD 47#		HD 35#	HD 7#	HD 3#				HR COMP	HA 18#	HA 17#	HA 25#	GND	HA VREF0		HA VREF1			F				TEST IN#	DFT IN#	M CLKI	M CLKO
G	HD 51#	GND	HD 49#	HD 41#	GND			GND		HD VREF0			HD VREF1	HCOMP VREF	GTL VREF	GND							G				GNDA MCK	VCCA3 MCK	GND	MD 0
H	HD 63#	HD 57#	HD 55#	HD 59#	HD 48#	HD 40#	7	H8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	H23	24	25	MEM VREF0	MD 4	MD 5	GND	MD 1
J	HD 46#	NC	NC	HD 52#	NC		HD VREF3	J	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	J			GND	MD 6	MD 2	DQS 0#	DQM 0
K	HD 53#	GND	HD 54#	HD 58#	GND	HD 50#	HD VREF2	K	VCC 15	VTT	VTT	VTT	VTT	VTT	VTT	VTT	VTT	VCC25 MEM	VCC25 MEM	VCC25 MEM	VCC25 MEM	VCC 15	K				CKE 3	CKE 1	MD 3	MD 7
L	HD 62#	HD 56#	HD 61#	NC		HD 60#		L	VCC 15	VTT	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC25 MEM	VCC 15	L		MEM VREF1	GND	MD 9	MD 12	GND	MD 8
M	VCCA33 HCK1	GNDA HCK1	VCCA33 GCK	VCCA33 HCK2	GNDA HCK2	GNDA GCK		M	VCC 15	VTT	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC25 MEM	VCC 15	M			CKE 0	CKE 2	DQM 1	DQS 1#	MD 13
N	VCCA15 PLL3	GNDA PLL3	VCCA15 PLL1	GNDA PLL1	H CLK+	H CLK–	T CLK	N	VCC 15	VTT	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC25 MEM	VCC 15	N				MA 12	MA 11	MD 15	MD 14
P		DISP CLKI	DISP CLKO	VCCA15 PLL2	GNDA PLL2	G CLK	XIN	P	VCC 15	VTT	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC25 MEM	VCC 15	P			GND	MD 20	MD 11	GND	MD 10
R				VCCA33 DAC1	GNDA DAC1			R	VCC 15	VCC33 GFX	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC25 MEM	VCC 15	R		MEM VREF2	MA 9	MA 7	MD 21	MD 17	MD 16
T	AB	AG	AR	GNDA DAC2				T	VCC 15	VCC33 GFX	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC25 MEM	VCC 15	T				MA 5	MA 8	DQM 2	DQS 2#
U				VCCA33 DAC2	GNDA DAC3	NC	NC	U	VCC 15	VCC33 GFX	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC25 MEM	VCC 15	U			GND	MD 19	MD 22	GND	MD 18
V	H SYNC	V SYNC	SP DAT2	R SET	INTA#	NC		V	VCC 15	VCC15 AGP	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC25 MEM	VCC 15	V			MA 4	MA 6	MD 28	MD 24	MD 23
W		SP CLK2	NC	NC	NC			W	VCC 15	VCC15 AGP	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC25 MEM	VCC 15	W		MEM VREF3	MA 2	MA 3	MD 29	DQS 3#	MD 25
Y		NC	NC	NC	NC			Y	VCC 15	VCC15 AGP	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	VCC MEM25	VCC 15	Y		MA 0	GND	MD 30	MD 26	GND	DQM 3
AA		NC	NC	NC	NC			AA	VCC 15	VCC15 AGP	VCC15 AGP	VCC15 AGP	VCC15 AGP	VCC15 VL	VCC15 VL	VCC25 MEM	VCC25 MEM	VCC25 MEM	VCC25 MEM	VCC25 MEM	VCC25 MEM	VCC 15	AA			MA 1	MD 33	MD 32	MD 31	MD 27
AB		NC	NC	NC	NC			AB	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	VCC 15	GND	AB			BA 0	BA 1	MA 10	MD 37	MD 36
AC	NC	GND	NC	NC	GND	6	7	AC8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	AC23	24	MEM VREF4	GND	MD 34	DQM 4	GND	DQS 4#
AD	NC	NC	SBDDC DAT	SBDDC CLK	ENA VEE	AGP VREF1		AD															AD				MD 35	MD 39	MD 38	
AE	AGP COMPP	AGP COMPN	FP CLK#	ENA VDD	ENA BLT	NC	FP CLK	FP D13	FP HS	FP1 VS	FP D10	FP D20	AGP VREF0	VL COMPP	VL VREF						AGP BUSY#	MEM VREF5	AE				MD 40	MD 44		
AF	GDVP1 DE	GND	GDVP1 VS	GDVP1 D0	GND	NC	FP DE	GND	FP1 CLK#	FP1 DET	GND	FP D7	FP D9	V PAR	VD 4	DN STB+	DN STB–	VD 3	VD 7	GND	VSUS 15		GND		S WE#	GND	MD 45	MD 41	GND	DQS 5#
AG	GDVP1 HS	GDVP1 D2	GDVP1 D1	GDVP1 D5	NC	NC	FP D17	FP1 DE	FP D23	FP D22	FP D11	FP1 CLK	NC	GND	VD 1	V BE#	GND	DN CMD	UP CMD	VD 14	PWR OK		CS 3#	MD 61	CS 2#	S CAS#	S RAS#	MD 46	DQM 5	MD 42
AH	GDVP1 D3	GDVP1 CLK#	GDVP1 D6	GDVP1 D7	GDVP1 D10	GDVP1 D11	FP D18	SBPL CLK	SBPL DAT	FP D1	FP D2	FP D6	NC	VD 8	VD 5	VD 0	UP STB+	VD 2	VD 6	VD 11	RE SET#	MD 59	MA 13	MD 57	CS 1#	CS 0#	MD 54	MD 48	MD 43	MD 47
AJ	GDVP1 CLK	GND	GDVP1 D9	FP DET	GND	FP D14	FP VS	GND	FP D21	FP D3	GND	FP D5	VD 12	VD 9			UP STB–			GND	SUS ST#	MD 63	GND	DQS 7#	MD 60	GND	MD 50	MD 52	GND	MD 49
AK	GDVP1 D8	GDVP1 DET	GDVP1 D4	FP D12	FP D15	FP D16	FP D19	NC	FP D00	FP1 HS	FP D4	FP D8	VD 13	GND			GND			VD 10	VD 15	MD 58	MD 62	DQM 7	MD 56	MD 51	MD 55	DQS 6#	DQM 6	MD 53

Pin Lists

Table 2. Pin List (Listed by Pin Number)

Pin #		Pin Name	Pin #		Pin Name	Pin #		Pin Name	Pin #		Pin Name	Pin #		Pin Name	Pin #		Pin Name
A03	IO	HD28#	D03	IO	HD27#	J01	IO	HD46#	V05	O	INTA#	AE10	O	FP1VS	AH13	–	NC
A04	IO	HD29#	D06	IO	HD33#	J02	–	NC	V06	–	NC	AE11	O	FPD10	AH14	IO	VD08
A05	IO	HD25#	D07	IO	HD21#	J03	–	NC	V26	O	MA04	AE12	O	FPD20	AH15	IO	VD05
A06	IO	HD26#	D08	IO	HD30#	J04	IO	HD52#	V27	O	MA06	AE14	AI	VLCOMPP	AH16	IO	VD00
A07	IO	HD16#	D09	IO	HD14#	J05	–	NC	V28	IO	MD28	AE21	O	AGPBUSY#	AH17	I	UPSTB+
A08	IO	HD13#	D10	IO	HD18#	J27	IO	MD06	V29	IO	MD24	AE27	IO	MD40	AH18	IO	VD02
A12	IO	HD05#	D12	IO	HD09#	J28	IO	MD02	V30	IO	MD23	AE28	IO	MD44	AH19	IO	VD06
A13	IO	HD15#	D13	IO	HD00#	J29	IO	DQS0#	W02	IO	SPCLK2	AF01	O	GDVP1DE	AH20	IO	VD11
A15	IO	HA23#	D15	IO	HA20#	J30	O	DQM0	W03	–	NC	AF03	O	GDVP1VS	AH21	I	RESET#
A16	IO	HA19#	D16	O	CPURST#	K01	IO	HD53#	W04	–	NC	AF04	O	GDVP1D00	AH22	IO	MD59
A20	IO	HA11#	D18	IO	HA12#	K03	IO	HD54#	W05	–	NC	AF06	–	NC	AH23	O	MA13
A21	IO	BNR#	D19	IO	HA05#	K04	IO	HD58#	W26	O	MA02	AF07	O	FPDE	AH24	IO	MD57
A22	–	NC	D20	IO	HA06#	K06	IO	HD50#	W27	O	MA03	AF09	O	FP1CLK#	AH25	O	CS1#
A24	IO	DEFER#	D21	–	NC	K27	O	CKE3	W28	IO	MD29	AF10	I	FP1DET	AH26	O	CS0#
A25	IO	HREQ0#	D22	IO	HA07#	K28	O	CKE1	W29	IO	DQS3#	AF12	O	FPD07	AH27	IO	MD54
A27	IO	DRDY#	D24	IO	HREQ3#	K29	IO	MD03	W30	IO	MD25	AF13	O	FPD09	AH28	IO	MD48
A28	IO	ADS#	D25	IO	HTRDY#	K30	IO	MD07	Y02	–	NC	AF14	IO	VPAR	AH29	IO	MD43
B02	IO	HD34#	D27	–	NC	L01	IO	HD62#	Y03	–	NC	AF15	IO	VD04	AH30	IO	MD47
B04	IO	HD31#	E01	–	NC	L02	IO	HD56#	Y04	–	NC	AF16	O	DNSTB+	AJ01	O	GDVP1CLK
B06	IO	HD24#	E02	IO	HD39#	L03	IO	HD61#	Y05	–	NC	AF17	O	DNSTB–	AJ03	O	GDVP1D09
B07	IO	HD19#	E03	IO	HD36#	L04	–	NC	Y25	O	MA00	AF18	IO	VD03	AJ04	I	FPDET
B11	IO	HD10#	E06	–	NC	L06	IO	HD60#	Y27	IO	MD30	AF19	IO	VD07	AJ06	O	FPD14
B12	IO	HD17#	E07	IO	HD23#	L27	IO	MD09	Y28	IO	MD26	AF25	O	SWE#	AJ07	O	FPVS
B13	IO	HD04#	E09	IO	HD02#	L28	IO	MD12	Y30	O	DQM3	AF27	IO	MD45	AJ09	O	FPD21
B14	–	NC	E11	–	NC	L30	IO	MD08	AA02	–	NC	AF28	IO	MD41	AJ10	O	FPD03
B15	IO	HA30#	E12	–	NC	M26	O	CKE0	AA03	–	NC	AF30	IO	DQS5#	AJ12	O	FPD05
B16	IO	HA31#	E13	IO	HD01#	M27	O	CKE2	AA04	–	NC	AG01	O	GDVP1HS	AJ13	IO	VD12
B17	IO	HA15#	E14	IO	HA26#	M28	O	DQM1	AA05	–	NC	AG02	O	GDVP1D02	AJ14	IO	VD09
B21	IO	HA04#	E15	IO	HA24#	M29	IO	DQS1#	AA26	O	MA01	AG03	O	GDVP1D01	AJ17	I	UPSTB–
B22	–	NC	E16	IO	HA21#	M30	IO	MD13	AA27	IO	MD33	AG04	O	GDVP1D05	AJ21	I	SUSST#
B23	IO	BPRI#	E17	IO	HA28#	N05	I	HCLK+	AA28	IO	MD32	AG05	–	NC	AJ22	IO	MD63
B24	IO	HREQ2#	E18	IO	HA16#	N06	I	HCLK–	AA29	IO	MD31	AG06	–	NC	AJ24	IO	DQS7#
B25	I	HITM#	E19	–	NC	N07	I	TCLK	AA30	IO	MD27	AG07	O	FPD17/	AJ25	IO	MD60
B26	IO	DBSY#	E22	IO	HA14#	N27	O	MA12	AB02	–	NC	AG08	O	FP1DE	AJ27	IO	MD50
B27	IO	RS2#	E24	I	HLOCK#	N28	O	MA11	AB03	–	NC	AG09	O	FPD23/	AJ28	IO	MD52
B28	–	NC	E25	IO	HIT#	N29	IO	MD15	AB04	–	NC	AG10	O	FPD22/	AJ30	IO	MD49
C01	IO	HD43#	F01	IO	HD42#	N30	IO	MD14	AB05	–	NC	AG11	O	FPD11	AK01	O	GDVP1D08
C02	IO	HD38#	F02	–	NC	P02	I	DISPCLKI	AB26	O	BA0	AG12	O	FP1CLK	AK02	I	GDVP1DET
C03	IO	HD22#	F03	IO	HD45#	P03	O	DISPCLKO	AB27	O	BA1	AG13	–	NC	AK03	O	GDVP1D04
C04	–	NC	F04	IO	HD44#	P06	I	GCLK	AB28	O	MA10	AG15	IO	VD01	AK04	O	FPD12
C05	IO	HD32#	F05	IO	HD47#	P07	I	XIN	AB29	IO	MD37	AG16	IO	VBE#	AK05	O	FPD15
C06	–	NC	F07	IO	HD35#	P27	IO	MD20	AB30	IO	MD36	AG18	O	DNCMD	AK06	O	FPD16
C07	–	NC	F08	IO	HD07#	P28	IO	MD11	AC01	–	NC	AG19	I	UPCMD	AK07	O	FPD19
C08	IO	HD20#	F09	IO	HD03#	P30	IO	MD10	AC03	–	NC	AG20	IO	VD14	AK08	–	NC
C09	IO	HD11#	F13	AI	HRCOMP	R26	O	MA09	AC04	–	NC	AG21	I	PWROK	AK09	O	FPD00
C10	IO	HD12#	F14	IO	HA18#	R27	O	MA07	AC27	IO	MD34	AG23	O	CS3#	AK10	O	FP1HS
C11	–	NC	F15	IO	HA17#	R28	IO	MD21	AC28	O	DQM4	AG24	IO	MD61	AK11	O	FPD04
C12	IO	HD08#	F16	IO	HA25#	R29	IO	MD17	AC30	IO	DQS4#	AG25	O	CS2#	AK12	O	FPD08
C13	IO	HD06#	F27	I	TESTIN#	R30	IO	MD16	AD01	–	NC	AG26	O	SCAS#	AK13	IO	VD13
C14	IO	HA29#	F28	I	DFTIN#	T01	AO	AB	AD02	–	NC	AG27	O	SRAS#	AK20	IO	VD10
C15	IO	HA27#	F29	I	MCLKI	T02	AO	AG	AD03	IO	SBDDCDAT	AG28	IO	MD46	AK21	IO	VD15
C16	IO	HA22#	F30	O	MCLKO	T03	AO	AR	AD04	IO	SBDDCCLK	AG29	O	DQM5	AK22	IO	MD58
C17	IO	HA10#	G01	IO	HD51#	T27	O	MA05	AD05	O	ENAVEE	AG30	IO	MD42	AK23	IO	MD62
C18	IO	HA13#	G03	IO	HD49#	T28	O	MA08	AD27	IO	MD35	AH01	O	GDVP1D03	AK24	O	DQM7
C19	IO	HA03#	G04	IO	HD41#	T29	O	DQM2	AD28	IO	MD39	AH02	O	GDVP1CLK#	AK25	IO	MD56
C20	IO	HA09#	G30	IO	MD00	T30	IO	DQS2#	AD29	IO	MD38	AH03	O	GDVP1D06	AK26	IO	MD51
C21	IO	HA08#	H01	IO	HD63#	U06	–	NC	AE01	AI	AGPPCMP	AH04	O	GDVP1D07	AK27	IO	MD55
C22	IO	HREQ1#	H02	IO	HD57#	U07	–	NC	AE02	AI	AGPNCMP	AH05	O	GDVP1D10	AK28	IO	DQS6#
C23	IO	HREQ4#	H03	IO	HD55#	U27	IO	MD19	AE03	O	FPCLK#	AH06	O	GDVP1D11	AK29	O	DQM6
C24	–	NC	H04	IO	HD59#	U28	IO	MD22	AE04	O	ENAVDD	AH07	O	FPD18	AK30	IO	MD53
C25	IO	RS1#	H05	IO	HD48#	U30	IO	MD18	AE05	O	ENABLT	AH08	IO	SBPLCLK			
C26	IO	RS0#	H06	IO	HD40#	V01	O	HSYNC	AE06	–	NC	AH09	IO	SBPLDAT			
C27	O	BREQ0#	H27	IO	MD04	V02	O	VSYNC	AE07	O	FPCLK	AH10	O	FPD01			
C28	–	NC	H28	IO	MD05	V03	IO	SPDAT2	AE08	O	FPD13	AH11	O	FPD02			
D01	IO	HD37#	H30	IO	MD01	V04	AI	RSET	AE09	O	FPHS	AH12	O	FPD06			

Table 3. Pin List (Listed by Pin Name)

Pin #		Pin Name	Pin #		Pin Name	Pin #		Pin Name	Pin #		Pin Name	Pin #		Pin Name	Pin #		Pin Name
T01	AO	AB	AK12	O	FPD08	C14	IO	HA29#	L06	IO	HD60#	AA27	IO	MD33	AA04	–	NC
A28	IO	ADS#	AF13	O	FPD09	B15	IO	HA30#	L03	IO	HD61#	AC27	IO	MD34	AA05	–	NC
T02	AO	AG	AE11	O	FPD10	B16	IO	HA31#	L01	IO	HD62#	AD27	IO	MD35	AB04	–	NC
AE21	O	AGPBUSY#	AG11	O	FPD11	N05	I	HCLK+	H01	IO	HD63#	AB30	IO	MD36	AB05	–	NC
AE02	AI	AGPCOMPN	AK04	O	FPD12	N06	I	HCLK–	E25	IO	HIT#	AB29	IO	MD37	AC01	–	NC
AE01	AI	AGPCOMPP	AE08	O	FPD13	D13	IO	HD00#	B25	I	HITM#	AD29	IO	MD38	AC03	–	NC
T03	AO	AR	AJ06	O	FPD14	E13	IO	HD01#	E24	I	HLOCK#	AD28	IO	MD39	AC04	–	NC
AB26	O	BA0	AK05	O	FPD15	E09	IO	HD02#	F13	AI	HRCOMP	AE27	IO	MD40	AD01	–	NC
AB27	O	BA1	AK06	O	FPD16	F09	IO	HD03#	A25	IO	HREQ0#	AF28	IO	MD41	AD02	–	NC
A21	IO	BNR#	AG07	O	FPD17	B13	IO	HD04#	C22	IO	HREQ1#	AG30	IO	MD42	AE06	–	NC
B23	IO	BPRI#	AH07	O	FPD18	A12	IO	HD05#	B24	IO	HREQ2#	AH29	IO	MD43	AF06	–	NC
C27	O	BREQ0#	AK07	O	FPD19	C13	IO	HD06#	D24	IO	HREQ3#	AE28	IO	MD44	AG05	–	NC
M26	O	CKE0	AE12	O	FPD20	F08	IO	HD07#	C23	IO	HREQ4#	AF27	IO	MD45	AG06	–	NC
K28	O	CKE1	AJ09	O	FPD21	C12	IO	HD08#	V01	O	HSYNC	AG28	IO	MD46	AG13	–	NC
M27	O	CKE2	AG10	O	FPD22	D12	IO	HD09#	D25	IO	HTRDY#	AH30	IO	MD47	AH13	–	NC
K27	O	CKE3	AG09	O	FPD23	B11	IO	HD10#	V05	O	INTA#	AH28	IO	MD48	AK08	–	NC
D16	O	CPURST#	AF07	O	FPDE	C09	IO	HD11#	Y25	O	MA00	AJ30	IO	MD49	AG21	I	PWROK
AH26	O	CS0#	AJ04	I	FPDET	C10	IO	HD12#	AA26	O	MA01	AJ27	IO	MD50	AH21	I	RESET#
AH25	O	CS1#	AE09	O	FPHS	A08	IO	HD13#	W26	O	MA02	AK26	IO	MD51	C26	IO	RS0#
AG25	O	CS2#	AJ07	O	FPVS	D09	IO	HD14#	W27	O	MA03	AJ28	IO	MD52	C25	IO	RS1#
AG23	O	CS3#	P06	I	GCLK	A13	IO	HD15#	V26	O	MA04	AK30	IO	MD53	B27	IO	RS2#
B26	IO	DBSY#	AJ01	O	GDVP1CLK	A07	IO	HD16#	T27	O	MA05	AH27	IO	MD54	V04	AI	RSET
A24	IO	DEFER#	AH02	O	GDVP1CLK#	B12	IO	HD17#	V27	O	MA06	AK27	IO	MD55	AD03	IO	SBDDCDAT
F28	I	DFTIN#	AF04	O	GDVP1D00	D10	IO	HD18#	R27	O	MA07	AK25	IO	MD56	AD04	IO	SBDDCCLK
P02	I	DISPCLKI	AG03	O	GDVP1D01	B07	IO	HD19#	T28	O	MA08	AH24	IO	MD57	AH08	IO	SBPLCLK
P03	O	DISPCLKO	AG02	O	GDVP1D02	C08	IO	HD20#	R26	O	MA09	AK22	IO	MD58	AH09	IO	SBPLDAT
AG18	O	DNCMD	AH01	O	GDVP1D03	D07	IO	HD21#	AB28	O	MA10	AH22	IO	MD59	AG26	O	SCAS#
AF16	O	DNSTB+	AK03	O	GDVP1D04	C03	IO	HD22#	N28	O	MA11	AJ25	IO	MD60	AB02	–	NC
AF17	O	DNSTB–	AG04	O	GDVP1D05	E07	IO	HD23#	N27	O	MA12	AG24	IO	MD61	W02	IO	SPCLK2
J30	O	DQM0	AH03	O	GDVP1D06	B06	IO	HD24#	AH23	O	MA13	AK23	IO	MD62	AB03	–	NC
M28	O	DQM1	AH04	O	GDVP1D07	A05	IO	HD25#	F29	I	MCLKI	AJ22	IO	MD63	V03	IO	SPDAT2
T29	O	DQM2	AK01	O	GDVP1D08	A06	IO	HD26#	F30	O	MCLKO	A22	–	NC	AG27	O	SRAS#
Y30	O	DQM3	AJ03	O	GDVP1D09	D03	IO	HD27#	G30	IO	MD00	B14	–	NC	AJ21	I	SUSST#
AC28	O	DQM4	AH05	O	GDVP1D10	A03	IO	HD28#	H30	IO	MD01	B22	–	NC	AF25	O	SWE#
AG29	O	DQM5	AH06	O	GDVP1D11	A04	IO	HD29#	J28	IO	MD02	B28	–	NC	N07	I	TCLK
AK29	O	DQM6	AF01	O	GDVP1DE	D08	IO	HD30#	K29	IO	MD03	C04	–	NC	F27	I	TESTIN#
AK24	O	DQM7	AK02	I	GDVP1DET	B04	IO	HD31#	H27	IO	MD04	C06	–	NC	AG19	I	UPCMD
J29	IO	DQS0#	AG01	O	GDVP1HS	C05	IO	HD32#	H28	IO	MD05	C07	–	NC	AH17	I	UPSTB+
M29	IO	DQS1#	AF03	O	GDVP1VS	D06	IO	HD33#	J27	IO	MD06	C11	–	NC	AJ17	I	UPSTB–
T30	IO	DQS2#	C19	IO	HA03#	B02	IO	HD34#	K30	IO	MD07	C24	–	NC	AG16	IO	VBE#
W29	IO	DQS3#	B21	IO	HA04#	F07	IO	HD35#	L30	IO	MD08	C28	–	NC	AH16	IO	VD00
AC30	IO	DQS4#	D19	IO	HA05#	E03	IO	HD36#	L27	IO	MD09	D21	–	NC	AG15	IO	VD01
AF30	IO	DQS5#	D20	IO	HA06#	D01	IO	HD37#	P30	IO	MD10	D27	–	NC	AH18	IO	VD02
AK28	IO	DQS6#	D22	IO	HA07#	C02	IO	HD38#	P28	IO	MD11	E01	–	NC	AF18	IO	VD03
AJ24	IO	DQS7#	C21	IO	HA08#	E02	IO	HD39#	L28	IO	MD12	E06	–	NC	AF15	IO	VD04
A27	IO	DRDY#	C20	IO	HA09#	H06	IO	HD40#	M30	IO	MD13	E11	–	NC	AH15	IO	VD05
AE05	O	ENABLT	C17	IO	HA10#	G04	IO	HD41#	N30	IO	MD14	E12	–	NC	AH19	IO	VD06
AE04	O	ENAVDD	A20	IO	HA11#	F01	IO	HD42#	N29	IO	MD15	E19	–	NC	AF19	IO	VD07
AD05	O	ENAVEE	D18	IO	HA12#	C01	IO	HD43#	R30	IO	MD16	F02	–	NC	AH14	IO	VD08
AG12	O	FP1CLK	C18	IO	HA13#	F04	IO	HD44#	R29	IO	MD17	J02	–	NC	AJ14	IO	VD09
AF09	O	FP1CLK#	E22	IO	HA14#	F03	IO	HD45#	U30	IO	MD18	J03	–	NC	AK20	IO	VD10
AG08	O	FP1DE	B17	IO	HA15#	J01	IO	HD46#	U27	IO	MD19	J05	–	NC	AH20	IO	VD11
AF10	I	FP1DET	E18	IO	HA16#	F05	IO	HD47#	P27	IO	MD20	L04	–	NC	AJ13	IO	VD12
AK10	O	FP1HS	F15	IO	HA17#	H05	IO	HD48#	R28	IO	MD21	U06	–	NC	AK13	IO	VD13
AE10	O	FP1VS	F14	IO	HA18#	G03	IO	HD49#	U28	IO	MD22	U07	–	NC	AG20	IO	VD14
AE07	O	FPCLK	A16	IO	HA19#	K06	IO	HD50#	V30	IO	MD23	V06	–	NC	AK21	IO	VD15
AE03	O	FPCLK#	D15	IO	HA20#	G01	IO	HD51#	V29	IO	MD24	W03	–	NC	AE14	AI	VLCOMPP
AK09	O	FPD00	E16	IO	HA21#	J04	IO	HD52#	W30	IO	MD25	W04	–	NC	AF14	IO	VPAR
AH10	O	FPD01	C16	IO	HA22#	K01	IO	HD53#	Y28	IO	MD26	W05	–	NC	V02	O	VSYNC
AH11	O	FPD02	A15	IO	HA23#	K03	IO	HD54#	AA30	IO	MD27	Y02	–	NC	P07	I	XIN
AJ10	O	FPD03	E15	IO	HA24#	H03	IO	HD55#	V28	IO	MD28	Y03	–	NC			
AK11	O	FPD04	F16	IO	HA25#	L02	IO	HD56#	W28	IO	MD29	Y04	–	NC			
AJ12	O	FPD05	E14	IO	HA26#	H02	IO	HD57#	Y27	IO	MD30	Y05	–	NC			
AH12	O	FPD06	C15	IO	HA27#	K04	IO	HD58#	AA29	IO	MD31	AA02	–	NC			
AF12	O	FPD07	E17	IO	HA28#	H04	IO	HD59#	AA28	IO	MD32	AA03	–	NC			

Table 4. Power, Ground and Voltage Reference Pin List

Outer Ring Pins (Intermixed with Signal Pins)

AGPVREF[0:1]	(2 pins):	AE13, AD6
GTLVREF	(1 pin):	G15
HAVREF[0:1]	(2 pins):	F18,20
HDVREF[0:3]	(4 pins):	G10,13, K7, J7
HCOMPVREF	(1 pin):	G14
MEMVREF[0:5]	(6 pins):	H26, L25, R25, W25, AC25, AE22
VLVREF	(1 pin):	AE15
VCCA33HCK1	(1 pin):	M1
GNDAHCK1	(1 pin):	M2
VCCA33HCK2	(1 pin):	M4
GNDAHCK2	(1 pin):	M5
VCCA33GCK	(1 pin):	M3
GNDAGCK	(1 pin):	M6
VCCA33MCK	(1 pin):	G28
GNDAMCK	(1 pin):	G27
VCCA15PLL1	(1 pin):	N3
GNDAPLL1	(1 pin):	N4
VCCA15PLL2	(1 pin):	P4
GNDAPLL2	(1 pin):	P5
VCCA15PLL3	(1 pin):	N1
GNDAPLL3	(1 pin):	N2
VCCA33DAC[1:2]	(2 pins):	R4, U4
GNDADAC[1:3]	(3 pins):	R5, T4, U5
VSUS15	(1 pin):	AF21
GND	(63 pins):	A11,14,17,23,26,29, B3,5,8,20, D2,5,11,14,17,23,26,29, E8,20,30, F17, G2,5,8,16,29, H29, J26, K2,5, L26,29, P26,29, U26,29, Y26,29, AC2,5,26,29, AF2,5,8,11,20,23,26,29, AG14,17, AJ2,5,8,11,20,23,26,29, AK14,17

Center Pins

VCC15	(51 pins):	J9-22, K9,22, L9,22, M9,22, N9,22, P9,22, R9,22, T9,22, U9,22, V9,22, W9,22, Y9,22, AA9,22, AB9-21
VCC25MEM	(20 pins):	K18-21, L21, M21, N21, P21, R21, T21, U21, V21, W21, Y21, AA16-21
VCC15AGP	(7 pins):	V10, W10, Y10, AA10-13
VCC15VL	(2 pins):	AA14-15
VCC33GFX	(3 pins):	R10, T10, U10
VTT	(12 pins):	K10-17, L10, M10, N10, P10
GND	(101 pins):	L11-20, M11-20, N11-20, P11-20, R11-20, T11-20, U11-20, V11-20, W11-20, Y11-20

Pin Descriptions

CPU Interface Pin Descriptions

CPU Interface			
Signal Name	**Pin #**	**I/O**	**Signal Description**
HA[31:3]#	(see pin list)	IO	**Host Address Bus.** HA[31:3] connect to the address bus of the host CPU. During CPU cycles HA[31:3] are inputs. These signals are driven by the North Bridge during cache snooping operations.
HD[63:0]#	(see pin list)	IO	**Host CPU Data.** These signals are connected to the CPU data bus.
ADS#	A28	IO	**Address Strobe**. The CPU asserts ADS# in T1 of the CPU bus cycle.
BNR#	A21	IO	**Block Next Request**. Used to block the current request bus owner from issuing new requests. This signal is used to dynamically control the processor bus pipeline depth.
BPRI#	B23	IO	**Priority Agent Bus Request**. The owner of this signal will always be the next bus owner. This signal has priority over symmetric bus requests and causes the current symmetric owner to stop issuing new transactions unless the HLOCK# signal is asserted. The North Bridge drives this signal to gain control of the processor bus.
DBSY#	B26	IO	**Data Bus Busy**. Used by the data bus owner to hold the data bus for transfers requiring more than one cycle.
DEFER#	A24	IO	**Defer**. A dynamic deferring policy is used to optimize system performance. The DEFER# signal is also used to indicate a processor retry response.
DRDY#	A27	IO	**Data Ready**. Asserted for each cycle that data is transferred.
HIT#	E25	IO	**Hit**. Indicates that a caching agent holds an unmodified version of the requested line. Also driven in conjunction with HITM# by the target to extend the snoop window.
HITM#	B25	I	**Hit Modified**. Asserted by the CPU to indicate that the address presented with the last assertion of EADS# is modified in the L1 cache and needs to be written back.
HLOCK#	E24	I	**Host Lock**. All CPU cycles sampled with the assertion of HLOCK# and ADS# until the negation of HLOCK# must be atomic.
HREQ[4:0]#	C23, D24, B24, C22, A25	IO	**Request Command**. Asserted during both clocks of the request phase. In the first clock, the signals define the transaction type to a level of detail that is sufficient to begin a snoop request. In the second clock, the signals carry additional information to define the complete transaction type.
HTRDY#	D25	IO	**Host Target Ready**. Indicates that the target of the processor transaction is able to enter the data transfer phase.
RS[2:0]#	B27, C25, C26	IO	**Response Signals**. Indicates the type of response per the table below: **RS[2:0]# — Response type** 000 — Idle State 001 — Retry Response 010 — Defer Response 011 — Reserved 100 — Hard Failure 101 — Normal Without Data 110 — Implicit Writeback 111 — Normal With Data
CPURST#	D16	O	**CPU Reset.** Reset output to CPU. External pullup and filter capacitor to ground should be provided per CPU manufacturer's recommendations.
BREQ0#	C27	O	**Bus Request 0.** Connect to CPU bus request 0.

Note: Clocking of the CPU interface is performed with HCLK+ and HCLK–.

Note: Internal pullup resistors are provided on all GTL interface pins. If the CPU does not have internal pullups, the North Bridge internal pullups may be enabled to allow the interface to meet GTL bus interface specifications (see strap descriptions).

Note: I/O pads for the above pins are powered by VTT. Input voltage levels are referenced to HAVREF, HDVREF and GTLREF.

The pinouts were defined assuming the ATX PCB layout model shown below (and general pin layout shown) as a guide for PCB component placement. Other PCB layouts (AT, LPX and NLX) were also considered and can typically follow the same general component placement.



DDR SDRAM Memory Controller Pin Descriptions

DDR DRAM Interface			
Signal Name	**Pin #**	**I/O**	**Signal Description**
MA[13:0]	(see pin lists)	O	**Memory Address.** Output drive strength may be set by Device 0 Function 3 RxE8.
BA[1:0]	AB27, AB26	O	**Bank Address.** Output drive strength may be set by Device 0 Function 3 RxE8.
SRAS#, SCAS#, SWE#	AG27, AG26, AF25	O	**Row Address, Column Address and Write Enable Command Indicators.** Output drive strength may be set by Device 0 Function 3 Rx E8.
MD[63:0]	(see pin lists)	IO	**Memory Data.** These signals are connected to the DRAM data bus. Output drive strength may be set by Device 0 Function 3 RxE2.
DQM[7:0]	AK24, AK29, AG29, AC28, Y30, T29, M28, J30	O	**Data Mask.** Data mask of each byte lane. Output drive strength may be set by Device 0 Function 3 RxE2.
DQS[7:0]#	AJ24, AK28, AF30, AC30, W29, T30, M29, J29	IO	**DDR Data Strobe.** Data strobe of each byte lane. Output drive strength may be set by Device 0 Function 3 RxE0.
CS[3:0]#	AG23, AG25, AH25, AH26	O	**Chip Select.** Chip select of each bank. Output drive strength may be set by Device 0 Function 3 RxE4.
CKE[3:0]	K27, M27, K28, M26	O	**Clock Enables.** Clock enables for each DRAM bank for powering down the SDRAM or clock control for reducing power usage and for reducing heat / temperature in high-speed memory systems.

Note: I/O pads for all pins on this page are powered by VCC25MEM. MD / DQS input voltage levels are referenced to MEMVREF.

Ultra V-Link Pin Descriptions

Ultra V-Link Interface			
Signal Name	**Pin #**	**I/O**	**Signal Description**
VD15 **VD14** **VD13** **VD12** **VD11** **VD10** **VD9** **VD8** **VD7** **VD6** **VD5** **VD4** **VD3** **VD2** **VD1** **VD0**	AK21 AG20 AK13 AJ13 AH20 AK20 AJ14 AH14 AF19 AH19 AH15 AF15 AF18 AH18 AG15 AH16	IO IO IO IO IO IO IO IO IO IO IO IO IO IO IO IO	**V-Link Data Bus.** During system initialization, VD[7:0] are used to transmit strap information from the South Bridge (the straps are not on the VD pins but are on the indicated pins of the South Bridge chip). Check the strap pin table for details.
VPAR	AF14	IO	**V-Link Parity.**
VBE#	AG16	IO	**V-Link Byte Enable.**
UPCMD	AG19	I	**V-Link Command from Client (South Bridge) to Host (North Bridge).**
UPSTB+	AH17	I	**V-Link Strobe from Client to Host.**
UPSTB–	AJ17	I	**V-Link Complement Strobe from Client to Host.**
DNCMD	AG18	O	**V-Link Command from Host (North Bridge) to Client (South Bridge).**
DNSTB+	AF16	O	**V-Link Strobe from Host to Client.**
DNSTB–	AF17	O	**V-Link Complement Strobe from Host to Client.**

Note: I/O pads for the pins in the above table are powered by VCC15VL. Input voltage levels are referenced to VLVREF.

CRT and Serial Bus Pin Descriptions

CRT Interface			
Signal Name	**Pin #**	**I/O**	**Signal Description**
AR	T3	AO	**Analog Red.** Analog red output to the CRT monitor.
AG	T2	AO	**Analog Green.** Analog green output to the CRT monitor.
AB	T1	AO	**Analog Blue.** Analog blue output to the CRT monitor.
HSYNC	V1	O	**Horizontal Sync.** Output to CRT.
VSYNC	V2	O	**Vertical Sync.** Output to CRT.
RSET	V4	AI	**Reference Resistor.** Tie to GNDDAC through an external 82Ω 1% resistor to control the RAMDAC full-scale current value.

I/O pads for the pins in the above table are powered by VCC33GFX (i.e., 3.3V I/O).

SMB / I2C Interface			
Signal Name	**Pin #**	**I/O**	**Signal Description**
SBPLCLK	AH8	IO	**I2C Serial Bus Clock for Panel**
SBPLDAT	AH9	IO	**I2C Serial Bus Data for Panel**
SBDDCCLK	AD4	IO	**I2C Serial Bus Clock for CRT DDC**
SBDDCDAT	AD3	IO	**I2C Serial Bus Data for CRT DDC**
SPCLK2 **SPCLK1** / CAPD12 **SPDAT2,** **SPDAT1** / CAPD13	W2, AB2 V3, AB3	IO	**Serial Port (SMB/I2C) Clock and Data.** The SPCLKn pins are the clocks for serial data transfer. The SPDATn pins are the data signals used for serial data transfer. SPxxx1 is typically used for DVI monitor communications and SPxxx2 is typically used for DDC for CRT monitor communications. These pins are programmed via "Sequencer" graphics registers (port 3C5) in the "Extended" VGA register space (see the UniChrome-II Graphics Registers document for additional details). The SPxxx1 registers are programmed via 3C5.31 ("IIC Serial Port Control 1") and the SPxxx2 registers are programmed via 3C5.26 ("IIC Serial Port Control 0"). In both registers, the clock out state is programmed via bit-5 and the data out state via bit-4, clock in status may be read in bit-3 and data in status in bit-2 and the port may be enabled via bit-0.

I/O pads for SPCLK[2:1] / SPDAT[2:1] above are powered by VCC33GFX (i.e., 3.3V I/O).
All other pins in the above table are powered by VCC15AGP (i.e., 1.5V I/O).

Flat Panel Display Port (FPDP) Pin Descriptions

The FPDP can be configured as either an LVDS transmitter interface port (see the LVDS Transmitter Interface)

24-Bit / Dual 12-Bit Flat Panel Display Interface

Signal Name	Pin #	I/O	Signal Description
FPD23 / FPD0D11 **FPD22 / FPD0D10** **FPD21 / FPD0D09** **FPD20 / FPD0D08** **FPD19 / FPD0D07** **FPD18 / FPD0D06** **FPD17 / FPD0D05** **FPD16 / FPD0D04** **FPD15 / FPD0D03** **FPD14 / FPD0D02** **FPD13 / FPD0D01** **FPD12 / FPD0D00** **FPD11 / FPD1D11** **FPD10 / FPD1D10** **FPD09 / FPD1D09** **FPD08 / FPD1D08** **FPD07 / FPD1D07** **FPD06 / FPD1D06** **FPD05 / FPD1D05** **FPD04 / FPD1D04** **FPD03 / FPD1D03** **FPD02 / FPD1D02** **FPD01 / FPD1D01** **FPD00 / FPD1D00**	AG9 AG10 AJ9 AE12 AK7 AH7 AG7 AK6 AK5 AJ6 AE8 AK4, AG11 AE11 AF13 AK12 AF12 AH12 AJ12 AK11 AJ10 AH11 AH10 AK9	O	**Flat Panel Data.** For 24-bit or dual 12-bit flat panel display modes. Two FPD interface modes, 24-bit and dual 12-bit, are supported. Strap High (3C5.12[4]=1): 24-bit Strap Low (3C5.12[4]=0): Dual 12-bit In "24-bit" mode, only one set of control pins is required. However, in dual 12-bit mode, the CN333 provides two sets of control signals that are required for certain LVDS transmitter chips. In 24-bit mode, two operating modes are supported: 3C5.12[4]=1 & 3x5.88[2]=0 & 3x5.88[4]=0 Double data rate: each rising and falling clock edge transmits a complete 24-bit pixel. 3C5.12[4]=1 & 3x5.88[2]=0 & 3x5.88[4]=1 Single data rate: each clock rising edge transmits a complete 24-bit pixel. In dual 12-bit mode, 3C5.12[4]=0 & 3x5.88[2] = 1 Double data rate: Each rising and falling clock edge transmits half (12 bits) of two 24-bit pixels.
FPHS	AE9	O	**Flat Panel Horizontal Sync.** 24-bit mode or port 0 in dual 12-bit mode.
FPVS	AJ7	O	**Flat Panel Vertical Sync.** 24-bit mode or port 0 in dual 12-bit mode.
FPDE	AF7	O	**Flat Panel Data Enable.** 24-bit mode or port 0 in dual 12-bit mode.
FPDET	AJ4	I	**Flat Panel Detect.** 24-bit mode or port 0 in dual 12-bit mode.
FPCLK	AE7	O	**Flat Panel Clock.** 24-bit mode or port 0 in dual 12-bit mode.
FPCLK#	AE3	O	**Flat Panel Clock Complement.** 24-bit mode or port 0 in dual 12-bit mode. For double-data-rate data transfers.
FP1HS	AK10	O	**Flat Panel Horizontal Sync.** For port 1 in dual 12-bit mode.
FP1VS	AE10	O	**Flat Panel Vertical Sync.** For port 1 in dual 12-bit mode.
FP1DE	AG8	O	**Flat Panel Data Enable.** For port 1 in dual 12-bit mode.
FP1DET	AF10	I	**Flat Panel Detect.** For port 1 in dual 12-bit mode.
FP1CLK	AG12	O	**Flat Panel Clock.** For port 1 in dual 12-bit mode.
FP1CLK#	AF9	O	**Flat Panel Clock Complement.** For port 1 in dual 12-bit mode. For double-data-rate data transfers.

Flat Panel Power Control

Signal Name	Pin #	I/O	Signal Description
ENAVDD	AE4	IO	**Enable Panel VDD Power.**
ENAVEE	AD5	IO	**Enable Panel VEE Power.**
ENABLT	AE5	IO	**Enable Panel Back Light.**

Note: I/O pads for all pins on this page are powered by VCC15AGP (i.e., 1.5V I/O).

Digital Video Port 1 (GDVP1) Pin Descriptions

GDVP1 can be configured as either a DVI transmitter interface port (see the DVI Transmitter Interface pin lists below for details).

Digital Video Port 1 (GDVP1) – DVI Interface			
Signal Name	**Pin #**	**I/O**	**Signal Description**
GDVP1D11 **GDVP1D10** **GDVP1D9** **GDVP1D8** **GDVP1D7** **GDVP1D6** **GDVP1D5** **GDVP1D4** **GDVP1D3** **GDVP1D2** **GDVP1D1** **GDVP1D0**	AH6 AH5 AJ3 AK1 AH4 AH3 AG4 AK3 AH1 AG2 AG3 AF4	O	**Data.**
GDVP1HS	AG1	O	**Horizontal Sync.**
GDVP1VS	AF3	O	**Vertical Sync.**
GDVP1DE	AF1	O	**Data Enable.**
GDVP1DET	AK2	I	**Display Detect.** If VGA register 3C5.3E[0] = 1, 3C5.1A[4] will read 1 if a display is connected. Tie to GND if not used.
GDVP1CLK	AJ1	O	**Clock.**
GDVP1CLK#	AH2	O	**Clock Complement.**

I/O pads for the pins on this page are powered by VCC15AGP (1.5V I/O).

Clock, Reset, Power Control, GPIO, Interrupt and Test Pin Descriptions

Clocks, Resets, Power Control, General Purpose I/O, Interrupts and Test				
Signal Name	**Pin #**	**I/O**	**Signal Description**	**Power Plane**
HCLK+	N5	I	**Host Clock.** This pin receives the host CPU clock (100 / 133 / 200 MHz). This clock is used by all CN333 logic that is in the host CPU domain.	**VTT**
HCLK–	N6	I	**Host Clock Complement.**	**VTT**
MCLKO	F30	O	**Memory (SDRAM) Clock.** Output from internal clock generator to the external clock buffer for memory interface.	**VCC25MEM**
MCLKI	F29	I	**Memory (SDRAM) Clock Feedback.** Input from MCLKO.	**VCC25MEM**
DISPCLKI	P2	I	**Dot Clock (Pixel Clock) In.** Used for external EMI reduction circuit if used. Connect to GND if external EMI reduction circuit not implemented.	**VCC33GFX**
DISPCLKO	P3	O	**Dot Clock (Pixel Clock) Out.** Used for external EMI reduction circuit if used. NC if external EMI reduction circuit not implemented.	**VCC33GFX**
GCLK	P6	I	**AGP Clock.** Clock for AGP logic.	**VCC15AGP**
XIN	P7	I	**Reference Frequency Input.** External 14.31818 MHz clock source. All internal graphics controller clocks are synthesized on chip using this frequency as a reference.	**VCC33GFX**
RESET#	AH21	I	**Reset.** Input from the South Bridge chip. When asserted, this signal resets the CN333 and sets all register bits to the default value. The rising edge of this signal is used to sample all power-up strap options	**VSUS15**
PWROK	AG21	I	**Power OK.** Connect to South Bridge and Power Good circuitry.	**VSUS15**
SUSST#	AJ21	I	**Suspend Status.** For implementation of the Suspend-to-DRAM feature. Connect to an external pull-up to disable.	**VSUS15**
AGPBUSY# / NMI	AE21	O	**AGP Interface Busy.** Connect to a South Bridge GPIO pin for monitoring the status of the internal AGP bus. See Design Guide for details. Pin function selectable with Device 0 Function 0 RxBE[7] (default = NMI).	**VCC25MEM**
GPOUT / CAPD14	U7	O	**General Purpose Output.** This pin reflects the state of SRD[0].	**VCC33GFX**
GPO0 / CAPD15	AA2	O	**General Output Port.** When SR1A[4] is cleared, this pin reflects the state of CR5C[0].	**VCC33GFX**
INTA#	V5	O	**Interrupt.** PCI interrupt output (handled by the interrupt controller in the South Bridge)	**VCC33GFX**
TCLK	N7	I	**Test Clock.** This pin is used for testing and must be connected to GND through a 1K-4.7K ohm resistor for all board designs.	**VCC33GFX**
TESTIN#	F27	I	**Test In.** This pin is used for testing and must be connected to VTT through a 1K-4.7K ohm resistor for all board designs.	**VCC25MEM**
DFTIN#	F28	I	**DFT In.** This pin is used for testing and must be connected to VTT through a 1K-4.7K ohm resistor for all board designs.	**VCC25MEM**
BISTIN / CAPAFLD	U6	I	**BIST In.** This pin is used for testing and must be tied to GND with a 1K-4.7K ohm resistor on all board designs.	**VCC33GFX**

Compensation and Reference Voltage Pin Descriptions

Compensation				
Signal Name	**Pin #**	**I/O**	**Signal Description**	**Power Plane**
HRCOMP	F13	AI	**Host CPU Compensation.** Connect a 20.5 Ω 1% resistor to ground. Used for Host CPU interface I/O buffer calibration.	**VTT**
VLCOMPP	AE14	AI	**V-Link Compensation.** Connect a 360 Ω 1% resistor to ground.	**VCC15VL**
AGPCOMPN	AE2	AI	**AGP N Compensation.** Connect a 60.4 Ω 1% resistor to VCC15AGP.	**VCC15AGP**
AGPCOMPP	AE1	AI	**AGP P Compensation.** Connect a 60.4 Ω 1% resistor to ground.	**VCC15AGP**

Reference Voltages				
Signal Name	**Pin #**	**I/O**	**Signal Description**	**Power Plane**
GTLVREF	G15	P	**Host CPU Interface AGTL+ Voltage Reference.** 2/3 VTT ±2% typically derived using a resistive voltage divider. See Design Guide.	**VTT**
HDVREF[0:1]	G10, G13, K7, J7	P	**Host CPU Data Voltage Reference.** 2/3 VTT ±2% typically derived using a resistive voltage divider. See Design Guide.	**VTT**
HAVREF[0:1]	F18, F20	P	**Host CPU Address Voltage Reference.** 2/3 VTT ±2% typically derived using a resistive voltage divider. See Design Guide.	**VTT**
HCOMPVREF	G14	P	**Host CPU Compensation Voltage Reference.** 1/3 VTT ±2% typically derived using a resistive voltage divider. See Design Guide.	**VTT**
MEMVREF [0:5]	H26, L25, R25, W25, AC25, AE22	P	**Memory Voltage Reference.** 0.5 VCC25MEM ±2% typically derived using a resistive voltage divider. See Design Guide.	**VCC25MEM**
VLVREF	AE15	P	**V-Link Voltage Reference.** 0.625V ±2% derived using a resistive voltage divider. See Design Guide.	**VCC15VL**
AGPVREF[0:1]	AE13, AD6	P	**AGP Voltage Reference.** ½ VCC15AGP (0.75V) for AGP 2.0 (4x transfer mode) and 0.23 VCC15AGP (0.35V) for AGP 3.0 (8x transfer mode). See the Design Guide for additional information and circuit implementation details..	**VCC15AGP**

Power Pin Descriptions

Analog Power / Ground			
Signal Name	**Pin #**	**I/O**	**Signal Description**
VCCA33HCK1	M1	P	**Power for Host CPU Clock PLL 1** (3.3V ±5%). 400 MHz for CPU / DRAM frequencies of multiples of 100, 133 and 200 MHz.
GNDAHCK1	M2	P	**Ground for Host CPU Clock PLL 1.** Connect to main ground plane through a ferrite bead.
VCCA33HCK2	M4	P	**Power for Host CPU Clock PLL 2** (3.3V ±5%). 500 MHz for CPU / DRAM frequencies of multiples of 166 MHz.
GNDAHCK2	M5	P	**Ground for Host CPU Clock PLL 2.** Connect to main ground plane through a ferrite bead.
VCCA33MCK	G28	P	**Power for Memory Clock PLL** (3.3V ±5%)
GNDAMCK	G27	P	**Ground for Memory Clock PLL.** Connect to main ground plane through a ferrite bead.
VCCA33GCK	M3	P	**Power for AGP Clock PLL** (3.3V ±5%)
GNDAGCK	M6	P	**Ground for AGP Clock PLL.** Connect to main ground plane through a ferrite bead.
VCCA15PLL1	N3	P	**Power for Graphics Controller PLL1** (1.5V ±5%).
GNDAPLL1	N4	P	**Ground for Graphics Controller PLL1.** Connect to main ground plane through a ferrite bead.
VCCA15PLL2	P4	P	**Power for Graphics Controller PLL2** (1.5V ±5%).
GNDAPLL2	P5	P	**Ground for Graphics Controller PLL2.** Connect to main ground plane through a ferrite bead.
VCCA15PLL3	N1	P	**Power for Graphics Controller PLL3** (1.5V ±5%).
GNDAPLL3	N2	P	**Ground for Graphics Controller PLL3.** Connect to main ground plane through a ferrite bead.
VCCA33DAC[1:2]	R4, U4	P	**Power for DAC.** (3.3V ±5%)
GNDADAC[1:3]	R5, T4, U5	P	**Ground for DAC.** Connect to main ground plane through a ferrite bead.

Digital Power / Ground			
Signal Name	**Pin #**	**I/O**	**Signal Description**
VTT	(see pin lists)	P	**Power** for **CPU I/O Interface Logic (12 Pins).** Voltage is CPU dependent. See Design Guide for details.
VCC25MEM	(see pin lists)	P	**Power** for **Memory I/O Interface Logic (20 Pins).** 2.5V ±5%.
VCC15VL	AA14, AA15	P	**Power** for **V-Link I/O Interface Logic (2 Pins).** 1.5V ±5%
VCC15AGP	(see pin lists)	P	**Power** for **AGP Bus I/O Interface Logic (7 Pins).** 1.5V ±5%
VCC33GFX	R10, T10, U10	P	**Power for Graphics I/O Logic (3 Pins).** 3.3V ±5%
VCC15	(see pin lists)	P	**Power** for **Internal Logic (51 Pins).** 1.5V ±5%
VSUS15	AF21	P	**Suspend Power (1 Pin).** 1.5V ±5%
GND	(see pin lists)	P	**Digital Ground (164 Pins).** Connect to main ground plane.

Strap Pin Descriptions

Strap Pins (External pullup / pulldown straps are required to select "H" / "L")				
Signal	**Actual Strap Pin**	**Function**	**Description**	**Status Bit**
VD7	**VT8235-CD:** SDCS3# **VT8235-CE:** SDCS3# **VT8237:** PDCS3#	Number of processors installed	L: Single processor H: Dual processor VD7 is sampled during system initialization; the actual strapping pin is located on the South Bridge chip.	F2Rx50[6]
VD6	**VT8235-CD:** SDA2 **VT8235-CE:** SDA2 **VT8237:** PDA2	Auto-Configure	L: Disable Auto-Configure H: Enable Auto-Configure VD6 is sampled during system initialization; the actual strapping pin is located on the South Bridge chip.	F2Rx76[2]
VD5	**VT8235-CD:** SDA1 **VT8235-CE:** SDA1 **VT8237:** PDA1	-reserved-	Must be strapped high. VD5 is sampled during system initialization; the actual strapping pin is located on the South Bridge chip.	-
VD3	**VT8235-CD:** SA19 **VT8235-CE:** Strap_VD3 **VT8237:** GPIOD	AGTL+ Pullups	L: Enable internal AGTL+ Pullups H: Disable internal AGTL+ Pullups VD3 is sampled during system initialization; the actual strapping pin is located on the South Bridge chip.	F2Rx52[5]
VD2	**VT8235-CD:** SA18 **VT8235-CE:** Strap_VD2 **VT8237:** GPIOB	IOQ Depth	L: 8-Level deep H: 1-Level deep VD2 is sampled during system initialization; the actual strapping pin is located on the South Bridge chip.	F2Rx50[7]
VD4, VD1, VD0	**VT8235-CD:** SDA0, SA17, SA16 **VT8235-CE:** SDA0, Strap_VD1, Strap_VD0 **VT8237:** PDA0, GPIOA, GPIOC	FSB Frequency	LLL: 100MHz LLH: 133MHz LHL: -reserved- LHH: -reserved- HLL: -reserved- HLH: -reserved- HHL: -reserved- HHH: Auto VD4, VD1 and VD0 are sampled during system initialization; the actual strapping pins are located on the South Bridge chip.	F2Rx54[7:5]

REGISTERS

Register Overview

The following tables summarize the configuration and I/O registers of the CN333 North Bridge. These tables also document the power-on default value ("Default") and access type ("Acc") for each register. Access type definitions used are RW (Read/Write), RO (Read/Only), "—" for reserved / used (essentially the same as RO), RWC (or just WC) (Read / Write 1's to Clear individual bits) and W1 (Write Once then Read / Only after that). Registers indicated as RW may have some read/only bits that always read back a fixed value (usually 0 if unused); registers designated as RWC or WC may have some read-only or read write bits (see individual register descriptions following these tables for details). All offset and default values are shown in hexadecimal unless otherwise indicated.

The graphics registers are described in a separate document.

Table 5. Registers

I/O Ports

Port #	I/O Port	Default	Acc
22	PCI / AGP Arbiter Disable	00	RW
CFB-8	Configuration Address	0000 0000	RW
CFF-C	Configuration Data	0000 0000	RW

Device 0 Function 0 Registers – AGP

Header Registers

Offset	Configuration Space Header	Default	Acc
1-0	Vendor ID	**1106**	RO
3-2	Device ID	**0259**	RO
5-4	Command	**0006**	**RW**
7-6	Status	**0210**	**WC**
8	Revision ID	**0n**	RO
9	Program Interface	00	RO
A	Sub Class Code	00	RO
B	Base Class Code	**06**	RO
C	-reserved- (Cache Line Size)	00	—
D	Latency Timer	00	**RW**
E	Header Type	**00 or 80**	RO
F	-reserved- (Built In Self Test)	00	—
13-10	Graphics Aperture Base	**0000 0008**	**RW**
14-2B	-reserved-	00	—
2D-2C	Subsystem Vendor ID	0000	**W1**
2F-2E	Subsystem ID	0000	**W1**
30-33	-reserved-	00	—
37-34	Capability Pointer	**0000 0080**	RO
38-3F	-reserved-	00	—

Device-Specific Registers

Offset	AGP Drive Control	Default	Acc
40-4D	-reserved-	00	—
4F	Multiple Function Control	00	RW

Offset	AGP Power Management Control	Default	Acc
50	Power Management Capability	**01**	**RO**
51	Power Management Next Pointer	00	**RO**
52	Power Management Capabilities I	02	**RO**
53	Power Management Capabilities II	00	**RO**
54	Power Management Control/Status	00	RW
55	Power Management Status	00	**RO**
56	PCI-to-PCI Bridge Support Extension	00	**RO**
57	Power Management Data	00	**RO**

Offset	Reserved	Default	Acc
58-7F	-reserved- (K8)	00	—

Device-Specific Registers

Offset	AGP Control	Default	Acc
80-CF	-reserved-	00	—

Offset	Reserved	Default	Acc
D0-DF	-reserved-	00	—
E0-EF	-reserved-	00	—
F0-FF	-reserved-	00	—

Device 0 Function 1 Registers – Error Reporting

Header Registers

Offset	Configuration Space Header	Default	Acc
1-0	Vendor ID	**1106**	RO
3-2	Device ID for Error Reporting	**1259**	RO
5-4	Command	**0006**	**RW**
7-6	Status	**0200**	**WC**
8	Revision ID	**0n**	RO
9	Program Interface	00	RO
A	Sub Class Code	00	RO
B	Base Class Code	**06**	RO
C	-reserved- (Cache Line Size)	00	—
D	-reserved- (Latency Timer)	00	—
E	-reserved- (Header Type)	00	—
F	-reserved- (Built In Self Test)	00	—
10-2B	-reserved-	00	—
2D-2C	Subsystem Vendor ID	00	**W1**
2F-2E	Subsystem ID	00	**W1**
30-33	-reserved-	00	—
37-34	Capability Pointer	0000 0000	RO
38-3F	-reserved-	00	—

Device-Specific Registers

Offset	V-Link Error Control	Default	Acc
40-4F	-reserved-	00	—
50	NB Vlink Bus Error Status	00	**WC**
51-57	-reserved-	00	—
58	NB Vlink Bus Err Reporting Enable	00	RW
59-5F	-reserved-	00	—

Offset	Host CPU Error Control	Default	Acc
60-7F	-reserved-	00	—

Offset	DRAM Error Control	Default	Acc
80-CF	-reserved-	00	—

Offset	AGP Error Control	Default	Acc
D0-DF	-reserved-	00	—
E0	AGP Error Status 1	00	**WC**
E1	AGP Error Status 2	00	**RO**
E2-E7	-reserved-	00	—
E8	AGP Error Reporting Enable	00	RW
E9-FF	-reserved-	00	—

Device 0 Function 2 Registers – Host CPU

Header Registers

Offset	Configuration Space Header	Default	Acc
1-0	Vendor ID	**1106**	RO
3-2	Device ID for Host CPU Bus	**2259**	RO
5-4	Command	**0006**	**RW**
7-6	Status	**0200**	**WC**
8	Revision ID	**0n**	RO
9	Program Interface	00	RO
A	Sub Class Code	00	RO
B	Base Class Code	**06**	RO
C	-reserved- (Cache Line Size)	00	—
D	-reserved- (Latency Timer)	00	—
E	-reserved- (Header Type)	00	—
F	-reserved- (Built In Self Test)	00	—
10-2B	-reserved-	00	—
2D-2C	Subsystem Vendor ID	00	**W1**
2F-2E	Subsystem ID	00	**W1**
30-33	-reserved-	00	—
37-34	Capability Pointer	0000 0000	RO
38-3F	-reserved-	00	—

Device-Specific Registers

Offset	Host CPU Protocol Control	Default	Acc
40-4F	-reserved-	00	—
50	CPU Interface Request Phase Control	00	RW
51	CPU Interface Basic Control	00	RW
52	CPU Interface Advanced Control	00	RW
53	CPU Interface Arbitration Control	00	RW
54	CPU Frequency	00	RW
55	CPU Miscellaneous Control	00	RW
56	Reorder Latency	00	RW
57	-reserved-	**01**	—
58	Delivery / Trigger Control	00	RW
59	IPI Control	00	RW
5A	Destination ID	00	RW
5B	Interrupt Vector	00	RW
5C	CPU Miscellaneous Control	00	RW
5D	Write Policy	00	RW
5E	Bandwidth Timer	00	RW
5F	Miscellaneous Control	00	RW
60	DRDY L Timing 1	00	RW
61	DRDY L Timing 2	00	RW
62	DRDY L Timing 3	00	RW
63	DRDY Q Timing 1	00	RW
64	DRDY Q Timing 2	00	RW
65	DRDY Q Timing 3	00	RW
66	Burst DRDY Timing 1	00	RW
67	Burst DRDY Timing 2	00	RW
68	Lowest Priority CPU ID #0	00	RW
69	Lowest Priority CPU ID #1	00	RW
6A	Lowest Priority CPU ID #2	00	RW
6B	Lowest Priority CPU ID #3	00	RW
6C	Lowest Priority CPU ID #4	00	RW
6D	Lowest Priority CPU ID #5	00	RW
6E	Lowest Priority CPU ID #6	00	RW
6F	Lowest Priority CPU ID #7	00	RW

Offset	Host CPU AGTL+ I/O Control	Default	Acc
70	Host Address (2x) Pullup Drive	00	RW
71	Host Address (2x) Pulldown Drive	00	RW
72	Host Data (1x) Pullup Drive	00	RW
73	Host Data (1x) Pulldown Drive	00	RW
74	AGTL+ Output Delay / Stagger Ctrl	00	RW
75	AGTL+ I/O Control	00	RW
76	AGTL+ Compensation Status	00	RW
77	AGTL+ AutoCompensation Offset	00	RW
78-FF	-reserved-	00	—

Device 0 Function 3 Registers – DRAM

Header Registers

Offset	Configuration Space Header	Default	Acc
1-0	Vendor ID	**1106**	RO
3-2	Device ID for DRAM Control	**3259**	RO
5-4	Command	**0006**	**RW**
7-6	Status	**0200**	**WC**
8	Revision ID	**0n**	RO
9	Program Interface	00	RO
A	Sub Class Code	00	RO
B	Base Class Code	**06**	RO
C	-reserved- (Cache Line Size)	00	—
D	-reserved- (Latency Timer)	00	—
E	-reserved- (Header Type)	00	—
F	-reserved- (Built In Self Test)	00	—
10-2B	-reserved-	00	—
2D-2C	Subsystem Vendor ID	00	**W1**
2F-2E	Subsystem ID	00	**W1**
30-33	-reserved-	00	—
37-34	Capability Pointer	0000 0000	RO
38-3F	-reserved-	00	—

Device-Specific Registers

Offset	DRAM Control	Default	Acc
40-47	DRAM Row Ending Address:		
40	Bank 0 Ending (HA[32:25])	**01**	RW
41	Bank 1 Ending (HA[32:25])	**01**	RW
42	Bank 2 Ending (HA[32:25])	**01**	RW
43	Bank 3 Ending (HA[32:25])	**01**	RW
44	Bank 4 Ending (HA[32:25])	**01**	RW
45	Bank 5 Ending (HA[32:25])	**01**	RW
46	Bank 6 Ending (HA[32:25])	**01**	RW
47	Bank 7 Ending (HA[32:25])	**01**	RW
48	DRAM DIMM #0 Control	00	RW
49	DRAM DIMM #1 Control	00	RW
4A	DRAM DIMM #2 Control	00	RW
4B	DRAM DIMM #3 Control	00	RW
4C-4F	-reserved-	00	—
51-50	MA Map Type	**2222**	RW
52	DRAM Rank End Address Bit-33	00	RW
53	DRAM Rank Begin Address Bit-33	00	RW
54	DRAM Controller Internal Options	00	RW
55	DRAM Timing for All Banks I	00	RW
56	DRAM Timing for All Banks II	**65**	RW
57	DRAM Timing for All Banks III	**01**	RW
58-5F	-reserved-	00	—
60	DRAM Control	00	RW
61-64	-reserved-	00	—
65	DRAM Arbitration Timer	00	RW
66	DRAM Arbitration Control	00	RW
67	Reserved (Do Not Program)	00	RW
68	DRAM DDR Control	00	RW

Device-Specific Registers (continued)

Offset	Reserved	Default	Acc
69	DRAM Page Policy Control	00	RW
6A	DRAM Refresh Counter	00	RW
6B	DRAM Arbitration Control	**10**	RW
6C	DRAM Clock Control	00	RW
6D	-reserved-	00	—
6E	DRAM Control	00	RW
6F	-reserved-	00	—
70	DRAM DDR Control 1	00	RW
71	DRAM DDR Control 2	00	RW
72	DRAM DDR Control 3	00	RW
73	DRAM DDR Control 4	00	RW
74	DRAM DQS Input Delay	00	RW
75	-reserved-	00	—
76	DRAM Early Clock Select	00	RW
77	-reserved-	00	—
78	DRAM Timing Control	**13**	RW
79	DRAM DQS Output Control	**01**	RW
7A	DRAM DQS Capture Control Chan A	**44**	RW
7B	DRAM DQS Capture Control Chan B	**04**	RW
7C	DIMM0 DQS Input Delay Offset	00	RW
7D	DIMM1 DQS Input Delay Offset	00	RW
7E	DIMM2 DQS Input Delay Offset	00	RW
7F	DIMM3 DQS Input Delay Offset	00	RW

Offset	ROM Shadow	Default	Acc
80	C-ROM Shadow Control	00	RW
81	D-ROM Shadow Control	00	RW
82	F-ROM Shadow/MemHole/SMI Ctrl	00	RW
83	E-ROM Shadow Control	00	RW

Offset	DRAM Above 4G Control	Default	Acc
84	Low Top Address Low	00	RW
85	Low Top Address High	**FF**	RW
86	SMM / APIC Decoding	**01**	RW
87-9F	-reserved-	00	—

Offset	UMA Control	Default	Acc
A0	CPU Direct Access FB Base	00	RW
A1	CPU Direct Access FB Size	00	RW
A2	VGA Timer	00	RW
A3	Graphics Timer	00	RW
A4	Graphics Miscellaneous Control	00	RW
A5-AF	-reserved-	00	—

Function 3 DRAM Device-Specific Registers (continued)

Offset	Graphics Control	Default	Acc
B0	Graphics Control 1	00	RW
B1	Graphics Control 2	00	RW
B2	Graphics Control 3	00	RW
B3	Graphics Control 4	00	RW
B4	Graphics Control 5	00	RW
B5-BF	-reserved-	00	—

Offset	AGP Controller Interface Control	Default	Acc
C0	AGP Controller Interface Control	00	RW
C1-DF	-reserved-	00	—

Offset	DRAM Drive Control	Default	Acc
E0	DRAM DQSA Drive	00	RW
E1	DRAM DQSB Drive	00	RW
E2	DRAM MDA / DQMA Drive	00	RW
E3	DRAM MDB / DQMB Drive	00	RW
E4	DRAM CS / CKE Drive	00	RW
E5	-reserved-	00	—
E6	DRAM S-Port Drive Control	00	RW
E7	-reserved-	00	—
E8	DRAM MAA / ScmdA Drive	00	RW
E9	-reserved-	00	—
EA	DRAM MAB / ScmdB Drive	00	RW
EB	-reserved-	00	—
EC	Channel A Duty Cycle Control	00	RW
ED	Channel B Duty Cycle Control	00	RW
EE	DDR CKG Duty Cycle Control 1	00	RW
EF	DDR CKG Duty Cycle Control 2	00	RW
F0-FF	-reserved-	00	—

Device 0 Function 4 Registers – Power Management

Header Registers

Offset	Configuration Space Header	Default	Acc
1-0	Vendor ID	**1106**	RO
3-2	Device ID for Power Manager	**4259**	RO
5-4	Command	**0006**	**RW**
7-6	Status	**0200**	**WC**
8	Revision ID	**0n**	RO
9	Program Interface	00	RO
A	Sub Class Code	00	RO
B	Base Class Code	**06**	RO
C	-reserved- (Cache Line Size)	00	—
D	-reserved- (Latency Timer)	00	—
E	-reserved- (Header Type)	00	—
F	-reserved- (Built In Self Test)	00	—
10-3F	-reserved-	00	—

Device-Specific Registers

Offset	Reserved	Default	Acc
40-4F	-reserved-	00	—
50-5F	-reserved-	00	—
60-6F	-reserved-	00	—
70-7F	-reserved-	00	—
80-8F	-reserved-	00	—
90-9F	-reserved-	00	—

Offset	Power Management Control	Default	Acc
A0	Power Management Mode	00	RW
A1	DRAM Power Management	00	RW
A2	Dynamic Clock Stop	00	RW
A3	MA / SCMD Pad Toggle Reduction	00	RW
A4-AF	-reserved-	00	—

Offset	Reserved	Default	Acc
B0-BF	-reserved-	00	—
C0-CF	-reserved-	00	—

Offset	BIOS Scratch	Default	Acc
D0-EF	BIOS Scratch Registers	00	RW

Offset	Test	Default	Acc
F0-FF	Reserved (Do Not Program)	00	RW

Device 0 Function 7 Registers – V-Link / PCI

Header Registers

Offset	Configuration Space Header	Default	Acc
1-0	Vendor ID	**1106**	RO
3-2	Device ID for V-Link Control	**7259**	RO
5-4	Command	**0006**	**RW**
7-6	Status	**0200**	**WC**
8	Revision ID	**0n**	RO
9	Program Interface	00	RO
A	Sub Class Code	00	RO
B	Base Class Code	**06**	RO
C	-reserved- (Cache Line Size)	00	—
D	-reserved- (Latency Timer)	00	—
E	-reserved- (Header Type)	00	—
F	-reserved- (Built In Self Test)	00	—
10-2B	-reserved-	00	—
2D-2C	Subsystem Vendor ID	00	**W1**
2F-2E	Subsystem ID	00	**W1**
30-33	-reserved-	00	—
37-34	Capability Pointer	0000 0000	RO
38-3F	-reserved-	00	—

Device-Specific Registers

Offset	V-Link Control	Default	Acc
40	V-Link Revision ID	**40**	**RO**
41	V-Link NB Capability	**39**	**RO**
42	V-Link NB Downlink Command	**88**	RW
43	V-Link NB Uplink Max Req Depth	**80**	RW
44	V-Link NB Uplink Buffer Size	**82**	RW
45	V-Link NB Bus Timer	**44**	RW
46	V-Link NB Misc Control	00	RW
47	V-Link Control	00	RW
48	V-Link NB/SB Configuration	**18**	RW
49	V-Link SB Capability	**19**	**WC**
4A	V-Link SB Downlink Status	**88**	**RO**
4B	V-Link SB Uplink Max Req Depth	**80**	RW
4C	V-Link SB Uplink Buffer Size	**82**	RW
4D	V-Link SB Bus Timer	**44**	RW
4E	CCA Master High Priority	00	RW
4F	V-Link SB Miscellaneous Control	00	RW
Offset	**Bank 7 End (same as F3Rx47)**	**Default**	**Acc**
50-56	-reserved-	00	—
57	Bank 7 Ending Address (Sent to SB)	**01**	**RO**
58-5F	-reserved-	00	—
Offset	**ROM Shadow (same as F3Rx80-82)**	**Default**	**Acc**
60	-reserved-	00	—
61	C-ROM Shadow Control	00	RW
62	D-ROM Shadow Control	00	RW
63	F-ROM Shadow/MemHole/SMI Ctrl	00	RW
64	E-ROM Shadow Control	00	RW
65-6F	-reserved-	00	—

Device-Specific Registers (continued)

Offset	PCI Bus Control	Default	Acc
70	PCI Buffer Control	00	RW
71	CPU to PCI Flow Control	**48**	**WC**
72	-reserved-	00	—
73	PCI Master Control	00	RW
74	-reserved-	00	—
75	PCI Arbitration 1	00	RW
76	PCI Arbitration 2	00	RW
77-7F	-reserved-	00	—

Offset	GART	Default	Acc
80-83	-reserved-	00	—
85-84	Graphics Aperture Size	0000	RW
86-87	-reserved-	00	—
88	GART Base Address	00	RW
89-8F	-reserved-	00	—

Offset	Reserved	Default	Acc
90-9F	-reserved-	00	—
A0-AF	-reserved-	00	—

Offset	V-Link Compenation / Drive Ctrl	Default	Acc
B0	V-Link CKG Control 1	00	RW
B1	V-Link CKG Control 2	00	RW
B2	-reserved-	00	—
B4	V-Link NB Compensation Control	00	RW
B5	V-Link NB Strobe Drive Control	00	RW
B6	V-Link NB Data Drive Control	00	RW
B7	V-Link NB Receive Strobe Delay	00	RW
B8	V-Link SB Compensation Control	00	RW
B9	V-Link SB Strobe Drive Control	00	RW
BA-BF	-reserved-	00	—

Offset	Reserved	Default	Acc
C0-CF	-reserved-	00	—
D0-DF	-reserved-	00	—

Offset	DRAM > 4G (same as F3Rx84-86)	Default	Acc
E0-E3	-reserved-	00	—
E4	Low Top Address Low	00	RW
E5	Low Top Address High	**FF**	RW
E6	SMM / APIC Decoding	**01**	RW
E7-EF	-reserved-	00	—

Offset	Reserved	Default	Acc
F0-FF	-reserved-	00	—

Device 1 Registers - PCI-to-PCI Bridge

Header Registers

Offset	Configuration Space Header	Default	Acc
1-0	Vendor ID	**1106**	RO
3-2	Device ID	**B198**	RO
5-4	Command	**0007**	**RW**
7-6	Status	**0230**	**WC**
8	Revision ID	**nn**	RO
9	Program Interface	00	RO
A	Sub Class Code	**04**	RO
B	Base Class Code	**06**	RO
C	-reserved- (Cache Line Size)	00	—
D	-reserved- (Latency Timer)	00	—
E	Header Type	**01**	RO
F	-reserved- (Built In Self Test)	00	—
13-10	Graphics Aperture Base	**0000 0008**	**RW**
14-17	-reserved-	00	—
18	Primary Bus Number	00	**RW**
19	Secondary Bus Number	00	**RW**
1A	Subordinate Bus Number	00	**RW**
1B	-reserved-	00	—
1C	I/O Base	**F0**	**RW**
1D	I/O Limit	00	**RW**
1F-1E	Secondary Status	0000	RO
21-20	Memory Base	**FFF0**	**RW**
23-22	Memory Limit (Inclusive)	0000	**RW**
25-24	Prefetchable Memory Base	**FFF0**	**RW**
27-26	Prefetchable Memory Limit	0000	**RW**
28-33	-reserved-	00	—
34	Capability Pointer	**70**	RO
35-3F	-reserved-	00	

Device-Specific Registers

Offset	AGP Bus Control	Default	Acc
40	CPU-to-AGP Flow Control 1	00	RW
41	CPU-to-AGP Flow Control 2	**08**	RW
42	AGP Master Control	00	RW
43	AGP Master Latency Timer	**22**	RW
44	Reserved (Do Not Program)	**20**	RW
45	Fast Write Control	**72**	RW
47-46	PCI-to-PCI Bridge Device ID	0000	RW
48-6F	-reserved-	00	—

Offset	Power Management	Default	Acc
70	Capability ID	**01**	**RO**
71	Next Pointer	00	**RO**
72	Power Management Capabilities 1	**02**	**RO**
73	Power Management Capabilities 2	00	**RO**
74	Power Management Control / Status	00	RW
75	Power Management Status	00	**RO**
76	PCI-PCI Bridge Support Extensions	00	**RO**
77	Power Management Data	00	**RO**
78-FF	-reserved-	00	—

Miscellaneous I/O

One I/O port is defined: Port 22.

Port 22 – PCI / AGP Arbiter Disable .....RW

7-2 Reserved ..... always reads 0

1 AGP Arbiter Disable
- 0 Respond to GREQ# signal .....default
- 1 Do not respond to GREQ# signal

0 PCI Arbiter Disable
- 0 Respond to all REQ# signals.....default
- 1 Do not respond to any REQ# signals, including PREQ#

This port can be enabled for read/write access by setting bit-7 of Device 0 Configuration Register 78.

Configuration Space I/O

All North Bridge registers (listed above) are addressed via the following configuration mechanism:

Mechanism #1

These ports respond only to double-word accesses. Byte or word accesses will be passed on unchanged.

Port CFB-CF8 - Configuration Address..... RW

31 Configuration Space Enable
- 0 Disabled..... default
- 1 Convert configuration data port writes to configuration cycles on the PCI bus

30-24 Reserved .....always reads 0

23-16 PCI Bus Number
Used to choose a specific PCI bus in the system

15-11 Device Number
Used to choose a specific device in the system (devices 0 and 1 are defined)

10-8 Function Number
Used to choose a specific function if the selected device supports multiple functions (functions 0-4 and 7 are defined for device 0 but the function number is unused / ignored for Device 1).

7-2 Register Number (also called the "Offset")
Used to select a specific DWORD in the configuration space

1-0 Fixed .....always reads 0

Port CFF-CFC - Configuration Data..... RW

Refer to PCI Bus Specification Version 2.2 for further details on operation of the above configuration registers.

Device 0 Function 0 Registers – AGP

Device 0 Function 0 Header Registers

All registers are located in PCI configuration space. They should be programmed using PCI configuration mechanism 1 through CF8 / CFC with bus number, function number and device number equal to zero and function number equal to 0. (CN333 does not support external AGP port)

Offset 1-0 - Vendor ID (1106h) ..... RO

15-0 ID Code (reads 1106h to identify VIA Technologies)

Offset 3-2 - Device ID (0259h) ..... RO

15-0 ID Code (reads 0259h to identify the CN333 NB)

Offset 5-4 –Command (0006h) ..... RW

15-10 Reserved ..... always reads 0

9 Fast Back-to-Back Cycle Enable ..... RO
- 0 Fast back-to-back transactions only allowed to the same agent.....default
- 1 Fast back-to-back transactions allowed to different agents

8 SERR# Enable..... RO
- 0 SERR# driver disabled.....default
- 1 SERR# driver enabled

7 Address / Data Stepping..... RO
- 0 Device never does stepping.....default
- 1 Device always does stepping

6 Parity Error Response.....**RW**
- 0 Ignore parity errors & continue.....default
- 1 Take normal action on detected parity errors

5 VGA Palette Snoop..... RO
- 0 Treat palette accesses normally.....default
- 1 Don't respond to palette accesses on PCI bus

4 Memory Write and Invalidate Command..... RO
- 0 Bus masters must use Mem Write.....default
- 1 Bus masters may generate Mem Write & Inval

3 Special Cycle Monitoring..... RO
- 0 Does not monitor special cycles.....default
- 1 Monitors special cycles

2 PCI Bus Master..... RO
- 0 Never behaves as a bus master
- 1 Can behave as a bus master.....default

1 Memory Space..... RO
- 0 Does not respond to memory space
- 1 Responds to memory space.....default

0 I/O Space ..... RO
- 0 Does not respond to I/O space .....default
- 1 Responds to I/O space

Offset 7-6 – Status (0210h)..... RWC

15 Detected Parity Error
- 0 No parity error detected..... default
- 1 Error detected in either address or data phase. This bit is set even if error response is disabled (command register bit-6). ..... write one to clear

14 Signaled System Error (SERR# Asserted)
..... always reads 0

13 Signaled Master Abort
- 0 No abort received ..... default
- 1 Transaction aborted by the master .... write one to clear

12 Received Target Abort
- 0 No abort received ..... default
- 1 Transaction aborted by the target .... write one to clear

11 Signaled Target Abort ..... always reads 0
- 0 Target Abort never signaled

10-9 DEVSEL# Timing
- 00 Fast
- 01 Medium ..... always reads 01
- 10 Slow
- 11 Reserved

8 Data Parity Error Detected
- 0 No data parity error detected ..... default
- 1 Error detected in data phase. Set only if error response enabled via command bit-6 = 1 and the North Bridge was initiator of the operation in which the error occurred... write one to clear

7 Fast Back-to-Back Capable..... always reads 0

6 User Definable Features..... always reads 0

5 66MHz Capable..... always reads 0

4 Supports New Capability list..... always reads 1

3-0 Reserved ..... always reads 0

Offset 8 - Revision ID (0nh) ..... RO

7-0 Chip Revision Code..... always reads 0nh

Offset 9 - Programming Interface (00h) ..... RO

7-0 Interface Identifier..... always reads 00h

Offset A - Sub Class Code (00h)..... RO

7-0 Sub Class Code..... reads 00 to indicate Host Bridge

Offset B - Base Class Code (06h)..... RO

7-0 Base Class Code.. reads 06 to indicate Bridge Device

Offset D - Latency Timer (00h) ..... RW

Specifies the latency timer value in PCI bus clocks.

7-3 Guaranteed Time Slice for CPU ..... default=0

2-0 Reserved (fixed granularity of 8 clks).. always read 0
Bits 2-1 are writeable but read 0 for PCI specification compatibility. The programmed value may be read back in Rx75[6-4] (PCI Arbitration 1).

Device 0 Function 0 Header Registers (continued)

Offset E - Header Type (00h) ..... RO

7-0 Header Type Code
.....Rx4F[0]=0: reads 00h: single function
.....Rx4F[0]=1: reads 80h, multi function

Offset F - Built In Self Test (BIST) (00h) ..... RO

7 BIST Supported .....reads 0: no supported functions
6-0 Reserved ..... always reads 0

Offset 13-10 - Graphics Aperture Base (AGP 2.0) (00000008h) ..... RW

This register is interpreted per the following definition if Rx4D[2]=0 (AGP 2.0 header at Rx80h).

31-28 Upper Programmable Base Address Bits ..... def=0
27-20 Lower Programmable Base Address Bits ..... def=0
These bits behave as if hardwired to 0 if the corresponding AGP 2.0 Graphics Aperture Size register bit (Device 0 Function 0 Offset B4h) is 0.

27	26	25	24	23	22	21	20	(Base)
7	6	5	4	3	2	1	0	(Size)
RW	RW	RW	RW	RW	RW	RW	RW	1M
RW	RW	RW	RW	RW	RW	RW	0	2M
RW	RW	RW	RW	RW	RW	0	0	4M
RW	RW	RW	RW	RW	0	0	0	8M
RW	RW	RW	RW	0	0	0	0	16M
RW	RW	RW	0	0	0	0	0	32M
RW	RW	0	0	0	0	0	0	64M
RW	0	0	0	0	0	0	0	128M
0	0	0	0	0	0	0	0	256M

19-4 Reserved ..... always reads 0
3 Prefetchable ..... **always reads 1**
Indicates that the locations in the address range defined by this register are prefetchable.
2-1 Type ..... always reads 0
Indicates the address range in the 32-bit address space.
0 Memory Space ..... always reads 0
Indicates the address range in the memory address space.

Offset 13-10 - Graphics Aperture Base (AGP 3.0) (00000008h) ..... RW

This register is interpreted per the following definition if Rx4D[2]=1 (AGP 3.0 header at Rx80h).

31-22 Programmable Base Address Bits.....def=0
These bits behave as if hardwired to 0 if the corresponding AGP 3.0 Graphics Aperture Size register bit (Device 0 Function 0 Offset 94h) is 0.

31	30	29	28	-	-	27	26	25	24	23	22	(Base)
11	10	9	8	7	6	5	4	3	2	1	0	(Size)
RW	RW	RW	RW	0	0	RW	RW	RW	RW	RW	RW	4M
RW	RW	RW	RW	0	0	RW	RW	RW	RW	RW	0	8M
RW	RW	RW	RW	0	0	RW	RW	RW	RW	0	0	16M
RW	RW	RW	RW	0	0	RW	RW	RW	0	0	0	32M
RW	RW	RW	RW	0	0	RW	RW	0	0	0	0	64M
RW	RW	RW	RW	0	0	RW	0	0	0	0	0	128M
RW	RW	RW	RW	0	0	0	0	0	0	0	0	256M
RW	RW	RW	0	0	0	0	0	0	0	0	0	512M
RW	RW	0	0	0	0	0	0	0	0	0	0	1G
RW	0	0	0	0	0	0	0	0	0	0	0	2G-max
0	0	0	0	0	0	0	0	0	0	0	0	4G

21-4 Reserved .....always reads 0
3 Prefetchable ..... **always reads 1**
Indicates that the locations in the address range defined by this register are prefetchable.
2-1 Type .....always reads 0
Indicates the address range in the 32-bit address space.
0 Memory Space.....always reads 0
Indicates the address range in the memory address space.

Offset 2D-2C – Subsystem Vendor ID (0000h) R/W1

15-0 Subsystem Vendor ID .....default = 0
This register may be written once and is then read only.

Offset 2F-2E – Subsystem ID (0000h) R/W1

15-0 Subsystem ID .....default = 0
This register may be written once and is then read only.

Offset 37-34 - Capability Pointer (CAPPTR)..... RO

Contains an offset from the start of configuration space.

31-0 AGP Capability List Ptr ...always reads 0000 0080h

AGP Miscellaneous Control

Offset 4F – Multiple Function Control (00h)..... RW

7-1 Reserved ..... always reads 0

0 Bridge Configuration Supports Multiple Functions

0 Not supported, other functions 1, 2, 3, 4 and 7 cannot be seen and will return FFFFFFFFh when accessed.....default

1 Supported (this bit is reflected on Rx0E[7])

AGP Power Management Control

Offset 50 – Power Management Capability ID ..... RO

7-0 Capability ID .....always reads 01h

Offset 51 – Power Management Next Pointer ..... RO

7-0 Next Pointer..... always reads 00h (“Null” Pointer)

Offset 52 – Power Mgmt Capabilities I..... RO

7-0 Power Management Capabilities ..always reads 02h

Offset 53 – Power Mgmt Capabilities II ..... RO

7-0 Power Management Capabilities ..always reads 00h

Offset 54 – Power Mgmt Control / Status ..... RW

7-2 Reserved .....always reads 0

1-0 Power State

00 D0 ..... default

01 -reserved-

10 -reserved-

11 D3 Hot

Offset 55 – Power Management Status..... RO

7-0 Power Management Status.....always reads 00h

Offset 56 – PCI-to-PCI Bridge Support Extensions ..... RO

7-0 P2P Bridge Support Extensions ....always reads 00h

Offset 57 – Power Management Data ..... RO

7-0 Power Management Data .....always reads 00h

AGP GART / Graphics Aperture

The function of the Graphics Address Relocation Table (GART) is to translate virtual 32-bit addresses issued by an AGP device into 4K-page based physical addresses for system memory access. In this translation, the upper 20 bits (A31-A12) are remapped, while the lower 12 address bits (A11-A0) are used unchanged.

A one-level fully associative lookup scheme is used to implement the address translation. In this scheme, the upper 20 bits of the virtual address are used to point to an entry in a page table located in system memory. Each page table entry contains the upper 20 bits of a physical address (a "physical page" address). For simplicity, each page table entry is 4 bytes. The total size of the page table depends on the GART range (called the "aperture size") which is programmable in the CN333.

This scheme is shown in the figure below.



Figure 4. Graphics Aperture Address Translation

Since address translation using the above scheme requires an access to system memory, an on-chip cache (called a "Translation Lookaside Buffer" or TLB) is utilized to enhance performance. The TLB in the CN333 contains 16 entries. Address "misses" in the TLB require an access of system memory to retrieve translation data. Entries in the TLB are replaced using an LRU (Least Recently Used) algorithm.

Addresses are translated only for accesses within the "Graphics Aperture" (GA). The Graphics Aperture can be any power of two in size from 1MB to 256MB (i.e., 1MB, 2MB, 4MB, 8MB, etc) for AGP 2.0 and 4MB to 2GB for AGP 3.0. The base of the Graphics Aperture can be anywhere in the system virtual address space on an address boundary determined by the aperture size (e.g., if the aperture size is 4MB, the base must be on a 4MB address boundary). The Graphics Aperture Base is defined in Device 0 Function 0 Rx10. The Graphics Aperture Size and TLB Table Base are defined in Rx94 and Rx98 along with various control bits.

Device 0 Function 1 Registers – Error Reporting

Device 0 Function 1 Header Registers

All registers are located in PCI configuration space. They should be programmed using PCI configuration mechanism 1 through CF8 / CFC with bus number and device number equal to zero and function number equal to 1.

Offset 1-0 - Vendor ID (1106h) ..... RO

15-0 ID Code (reads 1106h to identify VIA Technologies)

Offset 3-2 - Device ID for Error Reporting (1259h)..... RO

15-0 ID Code (reads 1259h to identify CN333 NB virtual device function 1)

Offset 5-4 –Command (0006h) ..... RW

15-10 Reserved ..... always reads 0

9 Fast Back-to-Back Cycle Enable ..... RO
- 0 Fast back-to-back transactions only allowed to the same agent ..... default
- 1 Fast back-to-back transactions allowed to different agents

8 SERR# Enable ..... RO
- 0 SERR# driver disabled ..... default
- 1 SERR# driver enabled

7 Address / Data Stepping ..... RO
- 0 Device never does stepping ..... default
- 1 Device always does stepping

6 Parity Error Response ..... RW
- 0 Ignore parity errors & continue ..... default
- 1 Take normal action on detected parity errors

5 VGA Palette Snoop ..... RO
- 0 Treat palette accesses normally ..... default
- 1 Don't respond to palette accesses on PCI bus

4 Memory Write and Invalidate Command ..... RO
- 0 Bus masters must use Mem Write ..... default
- 1 Bus masters may generate Mem Write & Inval

3 Special Cycle Monitoring ..... RO
- 0 Does not monitor special cycles ..... default
- 1 Monitors special cycles

2 PCI Bus Master ..... RO
- 0 Never behaves as a bus master
- 1 Can behave as a bus master ..... default

1 Memory Space ..... RO
- 0 Does not respond to memory space
- 1 Responds to memory space ..... default

0 I/O Space ..... RO
- 0 Does not respond to I/O space ..... default
- 1 Responds to I/O space

Offset 7-6 – Status (0200h) ..... RWC

15 Detected Parity Error
- 0 No parity error detected ..... default
- 1 Error detected in either address or data phase. This bit is set even if error response is disabled (command register bit-6). ..... write 1 to clear

14 Signaled Sys Err (SERR# Asserted) . always reads 0

13 Signaled Master Abort
- 0 No abort received ..... default
- 1 Transaction aborted by master . write 1 to clear

12 Received Target Abort
- 0 No abort received ..... default
- 1 Transaction aborted by target ... write 1 to clear

11 Signaled Target Abort ..... always reads 0
- 0 Target Abort never signaled

10-9 DEVSEL# Timing
- 00 Fast
- 01 Medium ..... always reads 01
- 10 Slow
- 11 Reserved

8 Data Parity Error Detected
- 0 No data parity error detected ..... default
- 1 Error detected in data phase. Set only if error response enabled via command bit-6 = 1 and the North Bridge was initiator of the operation in which the error occurred... write one to clear

7 Fast Back-to-Back Capable ..... always reads 0

6 User Definable Features ..... always reads 0

5 66MHz Capable ..... always reads 0

4 Supports New Capability list ..... always reads 0

3-0 Reserved ..... always reads 0

Offset 8 - Revision ID (0nh) ..... RO

8-0 Chip Revision Code ..... always reads 0nh

Offset 9 - Programming Interface (00h) ..... RO

7-0 Interface Identifier ..... always reads 00h

Offset A - Sub Class Code (00h) ..... RO

7-0 Sub Class Code ..... reads 00 to indicate Host Bridge

Offset B - Base Class Code (06h) ..... RO

7-0 Base Class Code .. reads 06 to indicate Bridge Device

Offset 2D-2C – Subsystem Vendor ID (0000h) ..... W1 / RO

15-0 Subsystem Vendor ID ..... default = 0

This register may be written once and is then read only.

Offset 2F-2E – Subsystem ID (0000h) ..... W1 / RO

15-0 Subsystem ID ..... default = 0

This register may be written once and is then read only.

Offset 37-34 - Capability Pointer (CAPPTR) ..... RO

Contains an offset from the start of configuration space.

31-0 AGP Capability List Ptr ... always reads 0000 0000h

Device 0 Function 1 Device-Specific Registers

These registers are normally programmed once at system initialization time.

V-Link Error Reporting

Offset 50 – V-Link Error Status ..... WC

- **7-1 Reserved** ..... always reads 0
- **0 V-Link Parity Error Detected by NB ..... WC**
  - 0 No V-Link Parity Error Detected ..... default
  - 1 V-Link Parity Error Detected (write 1 to clear)

Offset 58 – V-Link Error Reporting Enable ..... RW

- **7 Parity Error or SERR# Reported via NMI**
  - 0 Disable ..... default
  - 1 Enable
- **6 Parity Error or SERR# Reported to SB via Vlink**
  - 0 Disable ..... default
  - 1 Enable
- **5-1 Reserved** ..... always reads 0
- **0 V-Link Parity Check Report**
  - 0 Disable ..... default
  - 1 Enable

AGP Error Reporting

Offset E0 – AGP / PCI2 Error Status 1 (00h) ..... RWC

- **7 AGP Cycle Data Parity Error ..... WC**
  - 0 Parity Error did not occur ..... default
  - 1 Parity error occurred ..... write 1 to clear
- **6 PCI #2 GSERR Error ..... WC**
  - 0 Parity Error did not occur ..... default
  - 1 Parity error occurred ..... write 1 to clear
- **5-0 Reserved** ..... always reads 0

Offset E1 – AGP / PCI2 Error Status 2 (00h) ..... RO

- **7-2 Reserved** ..... always reads 0
- **1-0 Isoch Error Code from Func 0 Rx8C[1:0] ..... RO**

Offset E8 – AGP / PCI2 Error Reporting Enable (00h) RW

- **7-5 Reserved** ..... always reads 0
- **4 Report Data Parity Errors on AGP Cycles**
  - 0 Disable ..... default
  - 1 Enable
- **3-2 Reserved** ..... always reads 0
- **1 Report Data Parity Errors on PCI2 Cycles**
  - 0 Disable ..... default
  - 1 Enable
- **0 Report Address Parity Errors on PCI2 Cycles**
  - 0 Disable ..... default
  - 1 Enable

Device 0 Function 2 Registers – Host CPU

Device 0 Function 2 Header Registers

All registers are located in PCI configuration space. They should be programmed using PCI configuration mechanism 1 through CF8 / CFC with bus number and device number equal to zero and function number equal to 2.

Offset 1-0 - Vendor ID (1106h) ..... RO

15-0 ID Code (reads 1106h to identify VIA Technologies)

Offset 3-2 - Device ID (2259h) ..... RO

15-0 ID Code (reads 2259h to identify CN333 NB virtual device function 2)

Offset 5-4 –Command (0006h) ..... RW

15-10 Reserved ..... always reads 0

9 Fast Back-to-Back Cycle Enable ..... RO
- 0 Fast back-to-back transactions only allowed to the same agent ..... default
- 1 Fast back-to-back transactions allowed to different agents

8 SERR# Enable ..... RO
- 0 SERR# driver disabled ..... default
- 1 SERR# driver enabled

7 Address / Data Stepping ..... RO
- 0 Device never does stepping ..... default
- 1 Device always does stepping

6 Parity Error Response ..... RW
- 0 Ignore parity errors & continue ..... default
- 1 Take normal action on detected parity errors

5 VGA Palette Snoop ..... RO
- 0 Treat palette accesses normally ..... default
- 1 Don't respond to palette accesses on PCI bus

4 Memory Write and Invalidate Command ..... RO
- 0 Bus masters must use Mem Write ..... default
- 1 Bus masters may generate Mem Write & Inval

3 Special Cycle Monitoring ..... RO
- 0 Does not monitor special cycles ..... default
- 1 Monitors special cycles

2 PCI Bus Master ..... RO
- 0 Never behaves as a bus master
- 1 Can behave as a bus master ..... default

1 Memory Space ..... RO
- 0 Does not respond to memory space
- 1 Responds to memory space ..... default

0 I/O Space ..... RO
- 0 Does not respond to I/O space ..... default
- 1 Responds to I/O space

Offset 7-6 – Status (0200h) ..... RWC

15 Detected Parity Error
- 0 No parity error detected ..... default
- 1 Error detected in either address or data phase. This bit is set even if error response is disabled (command register bit-6). ..... write one to clear

14 Signaled Sys Err (SERR# Asserted) . always reads 0

13 Signaled Master Abort
- 0 No abort received ..... default
- 1 Transaction aborted by master . write 1 to clear

12 Received Target Abort
- 0 No abort received ..... default
- 1 Transaction aborted by target ... write 1 to clear

11 Signaled Target Abort ..... always reads 0
- 0 Target Abort never signaled

10-9 DEVSEL# Timing
- 00 Fast
- 01 Medium ..... always reads 01
- 10 Slow
- 11 Reserved

8 Data Parity Error Detected
- 0 No data parity error detected ..... default
- 1 Error detected in data phase. Set only if error response enabled via command bit-6 = 1 and the North Bridge was initiator of the operation in which the error occurred... write one to clear

7 Fast Back-to-Back Capable ..... always reads 0

6 User Definable Features ..... always reads 0

5 66MHz Capable ..... always reads 0

4 Supports New Capability list ..... always reads 0

3-0 Reserved ..... always reads 0

Offset 8 - Revision ID (0nh) ..... RO

9-0 Chip Revision Code ..... always reads 0nh

Offset 9 - Programming Interface (00h) ..... RO

7-0 Interface Identifier ..... always reads 00h

Offset A - Sub Class Code (00h) ..... RO

7-0 Sub Class Code ..... reads 00 to indicate Host Bridge

Offset B - Base Class Code (06h) ..... RO

7-0 Base Class Code .. reads 06 to indicate Bridge Device

Offset 2D-2C – Subsystem Vendor ID (0000h) ..... W1 / RO

15-0 Subsystem Vendor ID ..... default = 0

This register may be written once and is then read only.

Offset 2F-2E – Subsystem ID (0000h) ..... W1 / RO

15-0 Subsystem ID ..... default = 0

This register may be written once and is then read only.

Offset 37-34 - Capability Pointer (CAPPTR) ..... RO

Contains an offset from the start of configuration space.

31-0 AGP Capability List Ptr ... always reads 0000 0000h

Device 0 Function 2 Device-Specific Registers

These registers are normally programmed once at system initialization time.

Host CPU Control

Offset 50 – Request Phase Control (00h) .....RW

7 CPU Hardwired IOQ (In Order Queue) Size
Default set from the inverse of the VD2 strap. This register can be written 0 to restrict the chip to one level of IOQ.
- 0 1-Level (strap pulled high)
- 1 8-Level (strap pulled low)

6 Dual CPU Support
Default set from the VD7 strap (VT8237 South Bridge PDCS3# pin) or ROMSIP.
- 0 Single (SB strap pulled low)
- 1 Dual (SB strap pulled high)

5 Fast DRAM Access
- 0 Disable .....default
- 1 Enable

4-0 Dynamic Defer Snoop Stall Count
(granularity = 2T, normally set to 01000b)

Offset 51 – CPU Interface Basic Control (00h) .....RW

7 CPU Read DRAM Fast Ready
- 0 Wait until all 8 QWs are received before DRDY is returned .....default
- 1 See Rx60-67 for DRDY timing

6 Read Around Write
- 0 Disable .....default
- 1 Enable

5 DRQ Control
- 0 Non pipelined similar to Pro266 .....default
- 1 Pipelined

4 CPU to PCI Read Defer
- 0 Disable .....default
- 1 Enable

3 Two Defer / Retry Entries
- 0 Disable .....default
- 1 Enable

2 Two Defer / Retry Entries Shared
- 0 Each entry is dedicated to 1 CPU.....default
- 1 Each entry is shared by 2 CPUs

1 PCI Master Pipelined Access
- 0 Disable .....default
- 1 Enable

0 Reserved ..... always reads 0

Offset 52 – CPU Interface Advanced Ctrl (00h) ..... RW

7 CPU RW DRAM 0WS for Back-to-Back Pipeline Access
- 0 Disable..... default
- 1 Enable

6 HREQ High Priority
- 0 Disable..... default
- 1 Enable

5 AGTL+ Pullups
Default set from the inverse of the VD3 strap.
- 0 Disable (strap pulled high)
- 1 Enable (strap pulled low)

4 Reserved .....always reads 0

3 Write Retire Policy After 2 Writes
- 0 Disable..... default
- 1 Enable

2 2-Level Defer Queue with Lock
- 0 Normal Operation..... default
- 1 Enhanced Operation (this bit should always be set to 1)

1 Consecutive Speculative Read
- 0 Disable..... default
- 1 Enable

0 Speculative Read
- 0 Disable..... default
- 1 Enable

Offset 53 – CPU Arbitration Control (00h)..... RW

7-4 Host Timer .....default = 0

3-0 BPRI Timer (units of 4 HCLKs) .....default = 0

Offset 54 – CPU Frequency (00h) ..... RW

7-5 CPU FSB Frequency..... Set from VD4,1,0 Straps
- 000 100 MHz (all three straps pulled low)
- 001 133 MHz
- 010 -reserved-
- 011 -reserved-
- 100 -reserved-
- 101 -reserved-
- 110 -reserved-
- 111 Auto

4 SDRAM Burst Length of 8
- 0 Disable ..... default
- 1 Enable (must be set for 128-bit operation)

3 Fast Host Master Read Ready
- 0 Disable (normal) ..... default
- 1 Enable (1T early)

2 PCI Master 8QW Operation
- 0 Disable ..... default
- 1 Enable

1 Sync 1T Conversion
- 0 Transparent ..... default
- 1 Sync

0 VPX Mode
- 0 Disable (AGP Mode) ..... default
- 1 Enable (VPX Mode)

Offset 55 – CPU Miscellaneous Control (00h) ..... RW

7-6 Snoop Queue
- 00 12-level ..... default
- 01 13-level
- 1x 16-level

5 Reserved ..... always reads 0

4 Fast Command with 8QW Prefetch
- 0 Disable ..... default
- 1 Enable

3 Reserved ..... always reads 0

2 Medium Threshold for Write Policy
- 0 Disable ..... default
- 1 Enable

1 DRDY Early / Late Timing Select
- 0 2T Early ..... default
- 1 2T Late

0 Reserved ..... always reads 0

Offset 56 – Reorder Latency (00h) ..... RW

7-4 Medium Threshold for Write Policy to Improve Memory Read / Write Performance
A setting of 2-4 is recommended ..... default = 0h

3-0 Maximum Reorder Latency
- 0000 Disable (same as Rx55[0]=0) ..... default
- 0001 Reorder latency 1 (Rx55[0] must be 1)
- 0010 Reorder latency 2 (Rx55[0] must be 1)
- … …
- 1100 Reorder latency 12 (Rx55[0] must be 1)
- 1101 -reserved-
- 1110 -reserved-
- 1111 -reserved-

Offset 58 – Delivery / Trigger Control (00h) ..... RW

7 Redirection Hint in Register-Triggered APIC
- 0 ..... default
- 1

6 Trigger Register
- 0 ..... default
- 1

5 Trigger Mode
- 0 ..... default
- 1

4 Delivery Status
- 0 ..... default
- 1

3 Destination Mode
- 0 ..... default
- 1

2-0 Delivery Mode
- 000 ..... default
- 001
- 010
- 011
- 100
- 101
- 110
- 111

Offset 59 – IPI Control (00h).....RW

7-1 Reserved ..... always reads 0

0 Lowest Priority IPI Support
- 0 Disable .....default
- 1 Enable

Offset 5A – Destination ID (00h).....RW

7-0 Destination ID in A[19:12] ..... default = 00h

Offset 5B – Interrupt Vector (00h).....RW

7-0 Interrupt Vector in D[7:0] ..... default = 00h

Offset 5C – CPU Miscellaneous Control (00h) .....RW

7 Reserved ..... always reads 0

6 Copy / Compare Performance Improvement
- 0 Disable .....default
- 1 Enable

5 CPU Bus Ownership
- 0 Disable .....default
- 1 Enable

4 Patch D11 in APIC Logic Mode
- 0 Disable .....default
- 1 Enable

3 Redirection Hint Information Obtained From
- 0 Address Field .....default
- 1 Data Field

2 Destination Mode Information Obtained From
- 0 Address Field .....default
- 1 Data Field

1 APIC Cluster Mode Support
- 0 Disable .....default
- 1 Enable

0 Reserved ..... always reads 0

Offset 5D – Write Policy (00h).....RW

7-4 Write Request Limit..... default = 0h

3-0 Write Request Base..... default = 0h

Offset 5E – Bandwidth Timer (00h) .....RW

7-4 Host CPU Bandwidth Timer..... default = 0h

3-0 DRAM Bandwidth Timer ..... default = 0h

Offset 5F – CPU Miscellaneous Control (00h) ..... RW

7 Same Bank But Different Sub-Bank Considered Off-Page
- 0 Disable..... default
- 1 Enable (reduces post-write burst length and may increase performance)

6 Back-to-Back Fast Read, Burst CPU-to-AGP Read and Burst CPU-to-Memory Read
- 0 Disable..... default
- 1 Enable

5 Machine Error Output
- 0 Disable..... default
- 1 Enable

4 Bus Initialization Output
- 0 Disable..... default
- 1 Enable

3 Pipeline APIC / Master Transactions
- 0 Disable..... default
- 1 Enable

2 Host CPU Bandwidth Limited
- 0 Disable..... default
- 1 Enable

1 DRAM Bandwidth Limited
- 0 Disable..... default
- 1 Enable

0 Improve CPU Access DRAM Read After Write
- 0 Disable..... default
- 1 Enable

Offset 60 – DRDY L Timing Control 1 (00h).....RW

7-6 Phase 4 L Wait States ..... default = 00b
5-4 Phase 3 L Wait States ..... default = 00b
3-2 Phase 2 L Wait States ..... default = 00b
1-0 Phase 1 L Wait States ..... default = 00b

Offset 61 – DRDY L Timing Control 2 (00h).....RW

7-6 Phase 8 L Wait States ..... default = 00b
5-4 Phase 7 L Wait States ..... default = 00b
3-2 Phase 6 L Wait States ..... default = 00b
1-0 Phase 5 L Wait States ..... default = 00b

Offset 62 – DRDY L Timing Control 3 (00h).....RW

7-4 Reserved ..... always reads 0
3-2 Phase 10 L Wait States ..... default = 00b
1-0 Phase 9 L Wait States ..... default = 00b

Offset 63 – DRDY Q Timing Control 1 (00h) .....RW

7-6 Phase 4 Q Wait States..... default = 00b
5-4 Phase 3 Q Wait States..... default = 00b
3-2 Phase 2 Q Wait States..... default = 00b
1-0 Phase 1 Q Wait States..... default = 00b

Offset 64 – DRDY Q Timing Control 2 (00h) .....RW

7-6 Phase 8 Q Wait States..... default = 00b
5-4 Phase 7 Q Wait States..... default = 00b
3-2 Phase 6 Q Wait States..... default = 00b
1-0 Phase 5 Q Wait States..... default = 00b

Offset 65 – DRDY Q Timing Control 3 (00h) .....RW

7-4 Reserved ..... always reads 0
3-2 Phase 10 Q Wait States..... default = 00b
1-0 Phase 9 Q Wait States..... default = 00b

Offset 66 – Burst DRDY Timing Control 1 (00h) ..... RW

7 Burst DRDY Wait State #8
6 Burst DRDY Wait State #7
5 Burst DRDY Wait State #6
4 Burst DRDY Wait State #5
3 Burst DRDY Wait State #4
2 Burst DRDY Wait State #3
1 Burst DRDY Wait State #2
0 Burst DRDY Wait State #1
0 0 ws DRDY Burst..... default
1 1 ws DRDY Burst

Offset 67 – Burst DRDY Timing Control 2 (00h) ..... RW

7-6 Reserved .....always reads 0
5-4 Burst DRDY Wait State #10-9
0 Disable..... default
1 Enable
3-0 Reserved .....always reads 0

Offset 68 – Lowest Priority CPU ID #0 (00h)..... RO
Offset 69 – Lowest Priority CPU ID #1 (00h)..... RO
Offset 6A – Lowest Priority CPU ID #2 (00h)..... RO
Offset 6B – Lowest Priority CPU ID #3 (00h)..... RO
Offset 6C – Lowest Priority CPU ID #4 (00h)..... RO
Offset 6D – Lowest Priority CPU ID #5 (00h)..... RO
Offset 6E – Lowest Priority CPU ID #6 (00h)..... RO
Offset 6F – Lowest Priority CPU ID #7 (00h) ..... RO

Host CPU AGTL+ I/O Control

Offset 70 – Host Address (2x) Pullup Drive.....RW

7 Reserved ..... always reads 0
6-4 Reserved (Do Not Program)..... default = 0
3 Reserved ..... always reads 0
2-0 Address Pullup Drive (HA,HREQ#) ..... default = 0

Offset 71 – Host Address (2x) Pulldown Drive.....RW

7 Reserved ..... always reads 0
6-4 Reserved (Do Not Program)..... default = 0
3 Reserved ..... always reads 0
2-0 Address Pulldown Drive (HA,HREQ#) . default = 0

Offset 72 – Host Data (1x) Pullup Drive.....RW

7 Reserved ..... always reads 0
6-4 Reserved (Do Not Program)..... default = 0
3 Reserved ..... always reads 0
2-0 Data Pullup Drive (HD)..... default = 0

Offset 73 – Host Data (1x) Pulldown Drive.....RW

7 Reserved ..... always reads 0
6-4 Reserved (Do Not Program)..... default = 0
3 Reserved ..... always reads 0
2-0 Data Pulldown Drive (HD)..... default = 0

Note: Refer to BIOS Porting Guide for recommended settings for these bits for typical system configurations.

Offset 74 – Output Delay / Stagger Control.....RW

7-6 Reserved ..... always reads 0
5 HD[63:48, 31:16] Output Stagger
0 No delay.....default
1 1 nsec delay
4 HA[31:17] Output Stagger
0 No delay.....default
1 1 nsec delay
3-0 Reserved ..... always reads 0

Offset 75 – AGTL+ I/O Control (00h) ..... RW

7 AGTL+ 1x Input Increase Delay to Filter Noise
0 Disable..... default
1 Enable
6 AGTL+ 2x Input Increase Delay to Filter Noise
0 Disable..... default
1 Enable
5 AGTL+ Slew Rate Control
0 Disable..... default
1 Enable
4 Increase Delay for First HD Strobe
0 Disable..... default
1 Enable
3 Input Pullup
0 Disable..... default
1 Enable
2 AGTL+ Strobe Internal Termination Pullups
0 Disable..... default
1 Enable
1 AGTL+ Data Internal Termination Pullups
0 Disable..... default
1 Enable
0 AGTL+ Dynamic Compensation
0 Disable..... default
1 Enable

Offset 76 – AGTL+ Comp Status (00h) ..... RW

7 Select AutoCompensation Drive
0 Disable..... default
1 Enable (RxD8-DB set automatically on-chip based on auto compensation results)
6-4 AGTL+ Compensation Result..... default = x
3 AGTL+ POS Function
0 Inputs always powered ..... default
1 Inputs powered down when not in input mode
2 Auto Configure..... Set from VD6 Strap
0 Disable (strap pulled low)
1 Enable (strap pulled high). AGTL+ Drive settings and other chip configuration settings are stored in ROM, transferred from the South Bridge (via the V-Link bus) and loaded into the North Bridge automatically after system reset. Refer to the BIOS Porting Guide for layout of the AutoConfigure settings in ROM and for recommended bit settings.
1-0 Reserved (Do Not Program)..... default = 0

Offset 77 – AGTL+ Auto Comp Offset (00h) ..... RW

7-4 AGTL+ Drive Offset to Comp Result for 2x Pad
..... default = 0
3-0 AGTL+ Drive Offset to Comp Result for 1x Pad
..... default = 0

Device 0 Function 3 Registers – DRAM

Device 0 Function 3 Header Registers

All registers are located in PCI configuration space. They should be programmed using PCI configuration mechanism 1 through CF8 / CFC with bus number and device number equal to zero and function number equal to 3.

Offset 1-0 - Vendor ID (1106h) ..... RO

15-0 ID Code (reads 1106h to identify VIA Technologies)

Offset 3-2 - Device ID (3259h) ..... RO

15-0 ID Code (reads 3259h to identify CN333 NB virtual device function 3)

Offset 5-4 –Command (0006h) ..... RW

15-10 Reserved ..... always reads 0

9 Fast Back-to-Back Cycle Enable ..... RO
- 0 Fast back-to-back transactions only allowed to the same agent ..... default
- 1 Fast back-to-back transactions allowed to different agents

8 SERR# Enable ..... RO
- 0 SERR# driver disabled ..... default
- 1 SERR# driver enabled

7 Address / Data Stepping ..... RO
- 0 Device never does stepping ..... default
- 1 Device always does stepping

6 Parity Error Response ..... RW
- 0 Ignore parity errors & continue ..... default
- 1 Take normal action on detected parity errors

5 VGA Palette Snoop ..... RO
- 0 Treat palette accesses normally ..... default
- 1 Don't respond to palette accesses on PCI bus

4 Memory Write and Invalidate Command ..... RO
- 0 Bus masters must use Mem Write ..... default
- 1 Bus masters may generate Mem Write & Inval

3 Special Cycle Monitoring ..... RO
- 0 Does not monitor special cycles ..... default
- 1 Monitors special cycles

2 PCI Bus Master ..... RO
- 0 Never behaves as a bus master
- 1 Can behave as a bus master ..... default

1 Memory Space ..... RO
- 0 Does not respond to memory space
- 1 Responds to memory space ..... default

0 I/O Space ..... RO
- 0 Does not respond to I/O space ..... default
- 1 Responds to I/O space

Offset 7-6 – Status (0200h) ..... RWC

15 Detected Parity Error
- 0 No parity error detected ..... default
- 1 Error detected in either address or data phase. This bit is set even if error response is disabled (command register bit-6). ..... write one to clear

14 Signaled Sys Err (SERR# Asserted) . always reads 0

13 Signaled Master Abort
- 0 No abort received ..... default
- 1 Transaction aborted by master . write 1 to clear

12 Received Target Abort
- 0 No abort received ..... default
- 1 Transaction aborted by target ... write 1 to clear

11 Signaled Target Abort ..... always reads 0
- 0 Target Abort never signaled

10-9 DEVSEL# Timing
- 00 Fast
- 01 Medium ..... always reads 01
- 10 Slow
- 11 Reserved

8 Data Parity Error Detected
- 0 No data parity error detected ..... default
- 1 Error detected in data phase. Set only if error response enabled via command bit-6 = 1 and the North Bridge was initiator of the operation in which the error occurred... write one to clear

7 Fast Back-to-Back Capable ..... always reads 0

6 User Definable Features ..... always reads 0

5 66MHz Capable ..... always reads 0

4 Supports New Capability list ..... always reads 0

3-0 Reserved ..... always reads 0

Offset 8 - Revision ID (0nh) ..... RO

10-0 Chip Revision Code ..... always reads 0nh

Offset 9 - Programming Interface (00h) ..... RO

7-0 Interface Identifier ..... always reads 00h

Offset A - Sub Class Code (00h) ..... RO

7-0 Sub Class Code ..... reads 00 to indicate Host Bridge

Offset B - Base Class Code (06h) ..... RO

7-0 Base Class Code .. reads 06 to indicate Bridge Device

Offset 2D-2C – Subsystem Vendor ID (0000h) ..... W1 / RO

15-0 Subsystem Vendor ID ..... default = 0

This register may be written once and is then read only.

Offset 2F-2E – Subsystem ID (0000h) ..... W1 / RO

15-0 Subsystem ID ..... default = 0

This register may be written once and is then read only.

Offset 37-34 - Capability Pointer (CAPPTR) ..... RO

Contains an offset from the start of configuration space.

31-0 AGP Capability List Ptr ... always reads 0000 0000h

Device 0 Function 3 Device-Specific Registers

These registers are normally programmed once at system initialization time.

DRAM Control

These registers are normally set at system initialization time and not accessed after that during normal system operation. Some of these registers, however, may need to be programmed using specific sequences during power-up initialization to properly detect the type and size of installed memory (refer to the VIA Technologies CN333 BIOS porting guide for details).

Table 6. System Memory Map

Space	Start	Size	Address Range	Comment
DOS	0	640K	00000000-0009FFFF	Cacheable
VGA	640K	128K	000A0000-000BFFFF	Used for SMM
BIOS	768K	16K	000C0000-000C3FFF	Shadow Ctrl 1
BIOS	784K	16K	000C4000-000C7FFF	Shadow Ctrl 1
BIOS	800K	16K	000C8000-000CBFFF	Shadow Ctrl 1
BIOS	816K	16K	000CC000-000CFFFF	Shadow Ctrl 1
BIOS	832K	16K	000D0000-000D3FFF	Shadow Ctrl 2
BIOS	848K	16K	000D4000-000D7FFF	Shadow Ctrl 2
BIOS	864K	16K	000D8000-000DBFFF	Shadow Ctrl 2
BIOS	880K	16K	000DC000-000DFFFF	Shadow Ctrl 2
BIOS	896K	64K	000E0000-000EFFFF	Shadow Ctrl 3
BIOS	960K	64K	000F0000-000FFFFF	Shadow Ctrl 3
Sys Bus Init	1MB D Top 4G-64K	— 64K	00100000-DRAM Top DRAM Top-FFFEFFFF FFFEFFFF-FFFFFFFF	Can have hole 000Fxxxx alias

Offset 40-47 – DRAM Row Ending Address:

- **Offset 40 – Bank 0 Ending (HA[32:25]) (01h) .....RW**
- **Offset 41 – Bank 1 Ending (HA[32:25]) (01h) .....RW**
- **Offset 42 – Bank 2 Ending (HA[32:25]) (01h) .....RW**
- **Offset 43 – Bank 3 Ending (HA[32:25]) (01h) .....RW**
- **Offset 44 – Bank 4 Ending (HA[32:25]) (01h) .....RW**
- **Offset 45 – Bank 5 Ending (HA[32:25]) (01h) .....RW**
- **Offset 46 – Bank 6 Ending (HA[32:25]) (01h) .....RW**
- **Offset 47 – Bank 7 Ending (HA[32:25]) (01h) .....RW**

Note : Refer to the BIOS Porting Guide or BIOS Porting Update Note for detailed programming information.

Offset 48 - DRAM DIMM #0 Control (00h)..... RW

- **7 Rank 1 Enable** .....default = 0
- **6 Rank 0 Enable** .....default = 0
- **5 Rank 1 Is Above 4GB**.....default = 0
- **4 Rank 0 Is Above 4GB**.....default = 0
- **3-0 MA Setting** (see Table below).....default = 0

Offset 49 - DRAM DIMM #1 Control (00h)..... RW

- **7 Rank 3 Enable** .....default = 0
- **6 Rank 2 Enable** .....default = 0
- **5 Rank 3 Is Above 4GB**.....default = 0
- **4 Rank 2 Is Above 4GB**.....default = 0
- **3-0 MA Setting** (see Table below).....default = 0

Offset 4A - DRAM DIMM #2 Control (00h)..... RW

- **7 Rank 5 Enable** .....default = 0
- **6 Rank 4 Enable** .....default = 0
- **5 Rank 5 Is Above 4GB**.....default = 0
- **4 Rank 4 Is Above 4GB**.....default = 0
- **3-0 MA Setting** (see Table below).....default = 0

Offset 4B - DRAM DIMM #3 Control (00h) ..... RW

- **7 Rank 7 Enable** .....default = 0
- **6 Rank 6 Enable** .....default = 0
- **5 Rank 7 Is Above 4GB**.....default = 0
- **4 Rank 6 Is Above 4GB**.....default = 0
- **3-0 MA Setting** (see Table below).....default = 0

Table 7. DIMM MA Setting

Columns	12 Rows	13 Rows	14 Rows
8	0000 32 MB/Rank	–	–
9	0001 64 MB/Rank	0100 128 MB/Rank	–
10	0010 128 MB/Rank	0101 256 MB/Rank	1000 512 MB/Rank
11	0011 256 MB/Rank	0110 512 MB/Rank	1001 1 GB/Rank
12	–	0111 1 GB/Rank	1010 2 GB/Rank

Offset 51-50 - DRAM MA Map Type (2222h) .....RW

15-13 Bank 5/4 MA Map Type (see Table below)

12 Bank 5/4 1T Command Rate
- 0 2T Command .....default
- 1 1T Command

11-9 Bank 7/6 MA Map Type (see Table below)

8 Bank 7/6 1T Command Rate
- 0 2T Command .....default
- 1 1T Command

7-5 Bank 1/0 MA Map Type (see Table below)

4 Bank 1/0 1T Command Rate
- 0 2T Command .....default
- 1 1T Command

3-1 Bank 3/2 MA Map Type (see Table below)

0 Bank 3/2 1T Command Rate
- 0 2T Command .....default
- 1 1T Command

Table 8. MA Map Type Encoding

000	–	-reserved
001	64/128Mb	8 / 9-bit Column Address.....default
010	64/128Mb	9 / 10-bit Column Address
011	64/128Mb	10 / 11-bit Column Address
100	1Gb	10 / 11 / 12-bit Column Address
101	256/512Mb	8-bit Column Address
110	256/512Mb	9-bit Column Address
111	256/512Mb	10 / 11 / 12-bit Column Address

Offset 52 - DRAM Rank End Address Bit-33 (00h).....RW

7-1 Reserved ..... always reads 0

0 Rank End Address Bit-33..... default = 0

Offset 53 - DRAM Rank Begin Address Bit-33 (00h) ....RW

7-1 Reserved ..... always reads 0

0 Rank Begin Address Bit-33..... default = 0

Offset 54 - DRAM Controller Internal Options (00h) ...RW

7-5 Reserved ..... always reads 0

4 Read-Modify-Write Option
- 0 Disable .....default
- 1 Enable

3 Apply Same-Channel Constraints on Different Channels
- 0 Disable .....default
- 1 Enable

2 Two SCMD Buses Are Exclusive & Cannot Operate Simultaneously
- 0 Disable .....default
- 1 Enable

1-0 Reserved ..... always reads 0

Offset 55 - DRAM Rank Decode Address Config (00h) RW

7-2 Reserved .....always reads 0

1-0 DRAM Rank Decode Address Configuration
- 00 ..... default
- 01
- 10
- 11

Offset 56 - DRAM Timing for All Banks I (65h) ..... RW

7-6 Active Command to Precharge Command Period
- 00 TRAS = 6T
- 01 TRAS = 7T **..... default**
- 10 TRAS = 8T
- 11 TRAS = 9T

5-4 CAS Latency
- 00 1.5T
- 01 2T
- 10 2.5T **..... default**
- 11 3T

3-2 ACTIVE to CMD
- 00 TRCD = 2T
- 01 TRCD = 3T **..... default**
- 10 TRCD = 4T
- 11 TRCD = 5T

1-0 Precharge Command to Active Command Period
- 00 TRP = 2T
- 01 TRP = 3T **..... default**
- 10 TRP = 4T
- 11 TRP = 5T

Offset 57 - DRAM Timing for All Banks II (01h)..... RW

7-6 Reserved .....always reads 0

5 Active (0) -> Active (1)
- 0 TRRD = 2T ..... default
- 1 TRRD = 3T

4 Write Recovery Time
- 0 2T ..... default
- 1 3T

3 TWTR
- 0 TWTR = 1T..... default
- 1 TWTR = 2T

2 Increase TRFC For 1 Gbit DRAMs
- 0 Disable..... default
- 1 Enable

1-0 TRFC (Refresh-to-Active or Refresh-to-Refresh)

	Bit-2=0	Bit-2=1
00	12T	21T
01	13T	22T**..... default**
10	14T	23T
11	15T	24T

Offset 60 – DRAM Control (00h).....RW

7 0WS Back-to-Back Write to Different DDR Bank
- 0 Disable .....default
- 1 Enable

6 Fast Read to Read Turnaround
- 0 Disable .....default
- 1 Enable (DQS postamble overlap with preamble)

5 Fast Read to Write Turnaround
- 0 Disable .....default
- 1 Enable

4 Fast Write to Read Turnaround
- 0 Disable .....default
- 1 Enable

3 DQSA Input Capture Extended Range Control
- 0 .....default
- 1

2 DQSB Input Capture Extended Range Control
- 0 .....default
- 1

1-0 DQS[7:4] Input Capture Extended Range Control for Channels A and B
- 00 .....default
- 01
- 10
- 11

Offset 65 - DRAM Arbitration Timer (00h) .....RW

7-4 AGP Timer (units of 4 DRAM clocks) .... default = 0

3-0 CPU Timer (units of 4 DRAM clocks)..... default = 0

Offset 66 - DRAM Arbitration Control (00h).....RW

7 DRAM Controller Queue Greater Than 2
- 0 Disable .....default
- 1 Enable

6 DRAM Controller Queue Not Equal To 4
- 0 Disable .....default
- 1 Enable

5-4 Arbitration Parking Policy
- 00 Park at last bus owner .....default
- 01 Park at CPU
- 10 Park at AGP
- 11 -reserved-

3-0 AGP / CPU Priority (units of 4 DRAM clocks)

Offset 68 – DRAM DDR Control (00h)..... RW

7 DRAM Access Timing
- 0 2T ..... default
- 1 3T

6 Non-Burst Write-to-Write Can Be Closer in Non-DQM Mode
- 0 Disable..... default
- 1 Enable

5 Zero Delay DRAM Channel Switching for Read Cycles
- 0 Disable..... default
- 1 Enable

4 Zero Delay DRAM Channel Switching for Write Cycles
- 0 Disable..... default
- 1 Enable

3-0 DRAM Operating Frequency

	CPU / DRAM	
0000	133 / 133 (DDR-266)	..... default
0001	100 / 133 (DDR-266) 133 / 166 (DDR-333)	
0101	100 / 166 (DDR-333)	
1001	-reserved-	
0010	-reserved-	
1010	-reserved-	

All other combinations are reserved.

Offset 69 – DRAM Page Policy Control (00h) .....RW

7-6 Bank Interleave
- 00 No Interleave.....default
- 01 2-way
- 10 4-way
- 11 Reserved

For 16Mb DRAMs bank interleave is always 2-way

5 Reserved ..... always reads 0

4 Auto-Precharge for TLB Read or CPU Write-Back
- 0 Disable .....default
- 1 Enable

3 DRAM 8K Page Enable
- 0 Disable .....default
- 1 Enable

2 DRAM 4K Page Enable
- 0 Disable .....default
- 1 Enable

1 Page Kept Active When Crossing Banks
- 0 Disable .....default
- 1 Enable

0 Multiple Page Mode
- 0 Disable .....default
- 1 Enable

Offset 6A - Refresh Counter (00h).....RW

7-0 Refresh Counter (in units of 16 DRAM clocks)
- 00 DRAM Refresh Disabled.....default
- 01 32 DRAM clocks
- 02 48 DRAM clocks
- 03 64 DRAM clocks
- 04 80 DRAM clocks
- 05 96 DRAM clocks
- … …

The programmed value is the desired number of 16-DRAM clock units minus one.

Offset 6B - DRAM Arbitration Control (10h)..... RW

7 DQS Input DLL Adjust
- 0 Disable..... default
- 1 Enable

6 DQS Output DLL Adjust
- 0 Disable..... default
- 1 Enable

5 Burst Refresh
- 0 Disable..... default
- 1 Enable

4 Reserved (Do Not Program)..... default = 1

3 HA14 / HA22 Swap
- 0 Normal..... default
- 1 Swap to improve performance

2-0 SDRAM Operation Mode Select
- 000 Normal SDRAM Mode ..... default
- 001 NOP Command Enable
- 010 All-Banks-Precharge Command Enable (CPU-to-DRAM cycles are converted to All-Banks-Precharge commands).
- 011 MSR to Low DIMM
- 100 CBR Cycle Enable (if this code is selected, CAS-before-RAS refresh is used; if it is not selected, RAS-Only refresh is used)
- 101 MSR to High DIMM
- 11x Reserved

Offset 6C – DRAM Clock Control (00h) ..... RW

7-5 Reserved ..... always reads 0

4 DQM Removal (Always Perform 4-Burst R/W)
- 0 Disable .....default
- 1 Enable

3 Reserved (Do Not Program)..... default = 0

2 DDR x4 Device Enable
- 0 Disable .....default
- 1 Enable

1-0 Reserved (Do Not Program)..... default = 0

Offset 6E – DRAM Control (00h) ..... RW

7 Reserved .....always reads 0

6 DRAM Scrubber
- 0 Disable..... default
- 1 Enable

5 DRAM Scrubber Redirect
- 0 Disable..... default
- 1 Enable

4-3 Reserved .....always reads 0

2 For Double-Sided DIMMs, Interleave Using Address Bit-15
- 0 Disable..... default
- 1 Enable

1 Select Address Bit 19 Instead of 14 as Sub-Bank Address
- 0 Disable..... default
- 1 Enable

0 Select Address Bit 18 Instead of 13 as Sub-Bank Address
- 0 Disable..... default
- 1 Enable

Note: Refer to the CN333 BIOS Porting Guide for SDRAM configuration algorithms and recommended settings for these bits for typical memory system configurations.

Offset 70 – DRAM DDR Control 1 (00h) ..... RW

7-0 Channel A DQS Output Delay
00h .....default
FFh

Offset 71 – DRAM DDR Control 2 (00h) ..... RW

7-0 Channel A MD Output Delay
00h .....default
FFh

Offset 72 – DRAM DDR Control 3 (00h) ..... RW

7-0 Channel B DQS Output Delay
00h .....default
FFh

Offset 73 – DRAM DDR Control 4 (00h) ..... RW

7-0 Channel B MD Output Delay
00h .....default
FFh

Offset 74 – DRAM DQS Input Delay (00h)..... RW

7 DQS Input Delay Setting
0 Auto .....default
1 Manual

6 Reserved ..... always reads 0

5-0 DQS Input Delay
(if bit-7 = 0, reads DLL calibration result)
00h .....default
FFh

Offset 76 – DRAM Early Clock Select (00h)..... RW

7 Early Clock Select - Scmd/MA Bit-2 (see bits 3-2)

6 Early Clock Select - CS, CKE Bit-2 (see bits 1-0)

5-4 Reserved (Do Not Program)..... default = 0

3-2 Early Clock Select - Scmd/MA Bits 1-0 (see bit-7)
000 .....default
001
010
011
100
101
110
111

1-0 Early Clock Select - CS, CKE Bits 1-0 (see bit-6)
000 .....default
001
010
011
100
101
110
111

Offset 78 – DRAM Timing Control (13h)..... RW

7-6 Reserved (Do Not Program)..... default = 0

5-4 Write MD / DQS / CAS Timing Range Control
00
01 **..... default**
10
11

3-0 Reserved (Do Not Program)..... default = 3

Offset 79 – DRAM DQS Output Control (01h)..... RW

7-4 Reserved .....always reads 0

3 DQS / MD Output Enable Gated with DQS Input Enable
0 Disable..... default
1 Enable

2 DQS Output Long Postamble
0 Disable..... default
1 Enable

1 DQS Output Long Preamble 2
0 Disable..... default
1 Enable

0 DQS Output Long Preamble
0 Disable
1 Enable**..... default**

Offset 7A – DRAM DQS Capture Ctrl Chan A (44h)....RW

7-6 MD Input Internal Timing Control
00
01 .....**default**
10
11

5 Process DQS Input as in QBM Mode
0 Disable .....default
1 Enable

4-0 DQS Input Capture Range - Channel A
00000
00001
00010
00011
00100 .....default
00101
…
11111

Offset 7B – DRAM DQS Capture Ctrl Chan B (04h) ....RW

7-5 Reserved (Do Not Program)..... default = 0

4-0 DQS Input Capture Range - Channel B
00000
00001
00010
00011
00100 .....default
00101
…
11111

Offset 7C – DIMM #0 DQS Input Delay Offset (00h) ... RW

Values are programmed as two's-complement

7-5 Rank 1 DQS Input 2nd-Order Delay Offset
000 ..... default
…
111

4-0 Rank 0 DQS Input Delay Offset
00000 ..... default
…
11111

Offset 7D – DIMM #1 DQS Input Delay Offset (00h) ... RW

Values are programmed as two's-complement

7-5 Rank 3 DQS Input 2nd-Order Delay Offset
000 ..... default
…
111

4-0 Rank 2 DQS Input Delay Offset
00000 ..... default
…
11111

Offset 7E – DIMM #2 DQS Input Delay Offset (00h).... RW

Values are programmed as two's-complement

7-5 Rank 5 DQS Input 2nd-Order Delay Offset
000 ..... default
…
111

4-0 Rank 4 DQS Input Delay Offset
00000 ..... default
…
11111

Offset 7F – DIMM #3 DQS Input Delay Offset (00h).... RW

Values are programmed as two's-complement

7-5 Rank 7 DQS Input 2nd-Order Delay Offset
000 ..... default
…
111

4-0 Rank 6 DQS Input Delay Offset
00000 ..... default
…
11111

Table 9. 1x Bandwidth (64-Bit DDR) Memory Address Mapping Table

MA:	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	
64/128Mb																	x32 (14,8)
2K page	28	14	24	14	13	12	11	23	22	21	20	19	18	17	16	15	x16 (14,8)
001	31	28	27	14	13	PC	26	25	10	9	8	7	6	5	4	3	x8 (14,9)
4K page	28	14	25	14	13	12	24	23	22	21	20	19	18	17	16	15	x16 (14,9)
010	31	28	27	14	13	PC	26	11	10	9	8	7	6	5	4	3	x4 (14,10)
8K page	28	14	26	14	13	25	24	23	22	21	20	19	18	17	16	15	x8 (14,10)
011	31	28	27	14	13	PC	12	11	10	9	8	7	6	5	4	3	x4 (14,11)
256/512Mb																	
2K page	28	25	24	14	13	12	11	23	22	21	20	19	18	17	16	15	x32 (15,8)
101	31	29	28	14	13	PC	27	26	10	9	8	7	6	5	4	3	
4K page	28	26	25	14	13	12	24	23	22	21	20	19	18	17	16	15	x32 (15,9)
110	31	29	28	14	13	PC	27	11	10	9	8	7	6	5	4	3	x16 (15,9)
8K page	28	27	26	14	13	25	24	23	22	21	20	19	18	17	16	15	x16 (15,10)
111	31	29	28	14	13	PC	12	11	10	9	8	7	6	5	4	3	x8 (15,10)
																	x8 (15,11)
																	x4 (15,11)
																	x4 (15,12)
1Gb																	
8K page	28	27	26	14	13	25	24	23	22	21	20	19	18	17	16	15	x16 (16,10)
100	31	30	29	14	13	PC	12	11	10	9	8	7	6	5	4	3	x8 (16,11)
																	x4 (16,12)

ROM Shadow Control

Offset 80 – C-ROM Shadow Control (00h) RW

7-6 CC000h-CFFFFh
- 00 Read/write disable.....default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

5-4 C8000h-CBFFFh
- 00 Read/write disable.....default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

3-2 C4000h-C7FFFh
- 00 Read/write disable.....default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

1-0 C0000h-C3FFFh
- 00 Read/write disable.....default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

Offset 81 – D-ROM Shadow Control (00h).....RW

7-6 DC000h-DFFFFh
- 00 Read/write disable.....default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

5-4 D8000h-DBFFFh
- 00 Read/write disable.....default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

3-2 D4000h-D7FFFh
- 00 Read/write disable.....default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

1-0 D0000h-D3FFFh
- 00 Read/write disable.....default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

Offset 82 – F-ROM Shadow /Memory Hole / SMI Control (00h)..... RW

7-6 Reserved .....always reads 0

5-4 F0000h-FFFFFh
- 00 Read/write disable ..... default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

3-2 Memory Hole
- 00 None ..... default
- 01 512K-640K
- 10 15M-16M (1M)
- 11 14M-16M (2M)

1 Disable A,BK SMRAM Direct Access

0 Enable A,BK DRAM Access

SMI Mapping Control:

Bits	SMM		Non-SMM	
1-0	Code	Data	Code	Data
00	DRAM	DRAM	PCI	PCI
01	DRAM	DRAM	DRAM	DRAM
10	DRAM	PCI	PCI	PCI
11	DRAM	DRAM	DRAM	DRAM

Offset 83 – E-ROM Shadow Control (00h) ..... RW

7-6 EC000h-EFFFFh
- 00 Read/write disable ..... default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

5-4 E8000h-EBFFFh
- 00 Read/write disable ..... default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

3-2 E4000h-E7FFFh
- 00 Read/write disable ..... default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

1-0 E0000h-E3FFFh
- 00 Read/write disable ..... default
- 01 Write enable
- 10 Read enable
- 11 Read/write enable

DRAM Above 4G Control

Offset 84 – Low Top Address Low (00h).....RW

7-4 Low Top Address Low ..... default = 0

3-0 DRAM Granularity

0 16M Total DRAM less than 4G.....default
1 32M Total DRAM less than 8G
2 64M Total DRAM less than 16G
3 128M Total DRAM less than 32G
4 256M Total DRAM less than 64G
5-7 -reserved-

Offset 85 – Low Top Address High (FFh).....RW

7-0 Low Top Address High.....default = FFh

Offset 86 – SMM / APIC Decoding (01h) ..... RW

7-6 Reserved .....always reads 0

5 APIC Lowest Interrupt Arbitration

0 Disable..... default
1 Enable

4 I/O APIC Decoding

0 FECxxxxx accesses go to PCI..... default
1 FEC00000 to FEC7FFFF accesses go to PCI
FEC80000 to FECFFFFF accesses go to AGP

3 MSI (Processor Message) Support

0 Disable (master access to FEExxxxx will go to PCI) ..... default
1 Enable (master access to FEExxxxx will be passed to host side to do snoop)

2 Top SMM

0 Disable..... default
1 Enable

1 Reserved .....always reads 0

0 Compatible SMM

0 Disable
1 Enable**..... default**

UMA Control

Offset A0 – CPU Direct Access FB Base Address (00h).RW

7-1 CPU Direct Access FB Address [27:21] ..... def = 0

0 CPU Direct Access FB

0 Disable .....default

1 Enable

Offset A1 – CPU Direct Access FB Size (00h).....RW

7 VGA

0 Disable .....default

1 Enable

6-4 CPU Direct Access FB Size

000 None .....default

001 2MB†

010 4MB†

011 8MB†

100 16MB

101 32 MB

110 64 MB

111 -reserved-

†Microsoft WHQL DCT certification requires the frame buffer size to be a minimum of 16MB. Smaller frame buffer sizes are supported for non-Windows applications to reserve more available memory for the system.

3-0 CPU Direct Access FB Address [31:28] ..... def = 0

Offset A2 – VGA Timer 1 (00h).....RW

7-4 VGA High Priority Timer..... def = 0

3-0 VGA Timer ..... def = 0

(programmed in units of 16 dot clocks)

Offset A3 – VGA Timer 2 (00h).....RW

7-4 Timer to Promote Graphics Priority..... def = 0

(programmed in units of 16 dot clocks)

3-2 Reserved ..... always reads 0

1-0 Reserved (Do Not Program)..... default = 0

Offset A4 – Graphics Miscellaneous Control (00h)..... RW

7-4 Reserved .....always reads 0

3 AGP DIO (Pad) Clock

0 Disable..... default

1 Enable

2 Graphics Data Delay to Sync with Clock

0 No sync..... default

1 Sync with clock

1-0 Graphics DISPCLK Delay Control

00 ..... default

01

10

11

Graphics Control

Offset B0 – Graphics Control 1 (00h).....RW

- **7-4 Reserved** ..... always reads 0
- **3 Frame Buffer Rank Searching**
  - 0 Automatic.....default
  - 1 Select bank per bits 2-0
- **2-0 Frame Buffer Rank Location**

Offset B1 – Graphics Control 2 (00h).....RW

- **7-4 Current High Channel Granted (Normal Priority) and Request Pending Low Request Just Arrived** ... . def = 0
- **3-0 Current Low Channel Granted and Request Pending High Request Just Arrived**..... def = 0

Offset B2 – Graphics Control 3 (00h).....RW

- **7-4 Lot Counter for High Channel to Extend Arbitration Slot to High Requests**..... def = 0
- **3-0 Lot Counter for Low Channel to Extend Arbitration Slot to Low Requests**..... def = 0

Offset B3 – Graphics Control 4 (00h).....RW

- **7 Reserved** ..... always reads 0
- **6-4 Graphics Write Queue Threshold** ..... def = 0
- **3-0 Graphics VM FIFO Threshold** ..... def = 0

Offset B4 – Graphics Control 5 (00h).....RW

- **7-4 Reserved** ..... always reads 0
- **3 Graphics Read / Write Order Control**
  - 0 R/W may be out of order.....default
  - 1 Keep original low channel R/W order as received from graphics controller
- **2 Optimize Graphics Arbitration with DRAM Hit / Miss Consideration**
  - 0 Disable .....default
  - 1 Enable
- **1 Qualify Length from Graphics Controller to Differentiate 2QW / 4QW Requests**
  - 0 Disable .....default
  - 1 Enable
- **0 Alternate Arbitration to Low / High Channel Read When Both Hit**
  - 0 Disable .....default
  - 1 Enable

AGP Controller Interface Control

Offset C0 – AGP Controller Interface Control (00h).... RW

- **7-3 Reserved** .....always reads 0
- **2 Graphics AGP Read Data Delay**
  - 0 No delay ..... default
  - 1 Delay 1 clock
- **1 AGP Controller Interface Pipe Mode (Graphics)**
  - 0 Pipe ..... default
  - 1 Pipe bypass
- **0 AGP Controller Interface Pipe Mode (North Bridge)**
  - 0 Pipe ..... default
  - 1 Pipe bypass

DRAM Drive Control

Offset E0 – DRAM DQSA Drive.....RW

7-4 High Drive
0000 Lowest.....default
… …
1111 Highest

3-0 Low Drive
0000 Lowest.....default
… …
1111 Highest

Offset E1 – DRAM DQSB Drive.....RW

7-4 High Drive
0000 Lowest.....default
… …
1111 Highest

3-0 Low Drive
0000 Lowest.....default
… …
1111 Highest

Offset E2 – DRAM MDA, DQMA Drive.....RW

7-4 High Drive
0000 Lowest.....default
… …
1111 Highest

3-0 Low Drive
0000 Lowest.....default
… …
1111 Highest

Offset E3 – DRAM MDB, DQMB Drive.....RW

7-4 High Drive
0000 Lowest.....default
… …
1111 Highest

3-0 Low Drive
0000 Lowest.....default
… …
1111 Highest

Offset E4 – DRAM CS / CKE Drive.....RW

7-4 High Drive
0000 Lowest.....default
… …
1111 Highest

3-0 Low Drive
0000 Lowest.....default
… …
1111 Highest

Offset E6 – Drive Group S-Port Control (00h) ..... RW

7 DQ S-Port Control ..... default = 0
6 CS S-Port Control ..... default = 0
5 MAA S-Port Control ..... default = 0
4 MAB S-Port Control ..... default = 0
3 DQS S-Port Control ..... default = 0
2-1 Reserved ..... always reads 0
0 DQ / DQS / DQM Terminator
0 Disable..... default
1 Enable

Offset E8 – MAA Drive (MAA, ScmdA) ..... RW

7-4 High Drive
0000 Lowest ..... default
… …
1111 Highest

3-0 Low Drive
0000 Lowest ..... default
… …
1111 Highest

Offset EA – MAB Drive (MAB, ScmdB) ..... RW

7-4 High Drive
0000 Lowest ..... default
… …
1111 Highest

3-0 Low Drive
0000 Lowest ..... default
… …
1111 Highest

Offset EC – Channel A Duty Cycle Control..... RW

7-6 DQS Duty Cycle Control – Falling ..... default = 0
5-4 DQS Duty Cycle Control - Rising ..... default = 0
3-2 DQ Duty Cycle Control – Falling..... default = 0
1-0 DQ Duty Cycle Control - Rising ..... default = 0

Offset ED – Channel B Duty Cycle Control..... RW

7-6 DQS Duty Cycle Control – Falling ..... default = 0
5-4 DQS Duty Cycle Control - Rising ..... default = 0
3-2 DQ Duty Cycle Control – Falling..... default = 0
1-0 DQ Duty Cycle Control - Rising ..... default = 0

Offset EE – DDR CKG Duty Cycle Control 1..... RW

7-2 Reserved ..... always reads 0
1-0 DDR CKG Duty Cycle Control..... default = 0

Offset EF – DDR CKG Duty Cycle Control 2..... RW

7-2 Reserved ..... always reads 0
1-0 DDR CKG Duty Cycle Control..... default = 0

Device 0 Function 4 Registers – Power Management

Device 0 Function 4 Header Registers

All registers are located in PCI configuration space. They should be programmed using PCI configuration mechanism 1 through CF8 / CFC with bus number and device number equal to zero and function number equal to 4.

Offset 1-0 - Vendor ID (1106h) ..... RO

15-0 ID Code (reads 1106h to identify VIA Technologies)

Offset 3-2 - Device ID for Power Manager (4259h)..... RO

15-0 ID Code (reads 4259h to identify CN333 NB virtual device function 4)

Offset 5-4 –Command (0006h) ..... RW

15-10 Reserved ..... always reads 0

9 Fast Back-to-Back Cycle Enable ..... RO
- 0 Fast back-to-back transactions only allowed to the same agent ..... default
- 1 Fast back-to-back transactions allowed to different agents

8 SERR# Enable ..... RO
- 0 SERR# driver disabled ..... default
- 1 SERR# driver enabled

7 Address / Data Stepping ..... RO
- 0 Device never does stepping ..... default
- 1 Device always does stepping

6 Parity Error Response ..... RW
- 0 Ignore parity errors & continue ..... default
- 1 Take normal action on detected parity errors

5 VGA Palette Snoop ..... RO
- 0 Treat palette accesses normally ..... default
- 1 Don't respond to palette accesses on PCI bus

4 Memory Write and Invalidate Command ..... RO
- 0 Bus masters must use Mem Write ..... default
- 1 Bus masters may generate Mem Write & Inval

3 Special Cycle Monitoring ..... RO
- 0 Does not monitor special cycles ..... default
- 1 Monitors special cycles

2 PCI Bus Master ..... RO
- 0 Never behaves as a bus master
- 1 Can behave as a bus master ..... default

1 Memory Space ..... RO
- 0 Does not respond to memory space
- 1 Responds to memory space ..... default

0 I/O Space ..... RO
- 0 Does not respond to I/O space ..... default
- 1 Responds to I/O space

Offset 7-6 – Status (0200h) ..... RWC

15 Detected Parity Error
- 0 No parity error detected ..... default
- 1 Error detected in either address or data phase. This bit is set even if error response is disabled (command register bit-6). ..... write one to clear

14 Signaled System Error (SERR# Asserted) ..... always reads 0

13 Signaled Master Abort
- 0 No abort received ..... default
- 1 Transaction aborted by the master ..... write one to clear

12 Received Target Abort
- 0 No abort received ..... default
- 1 Transaction aborted by the target ..... write one to clear

11 Signaled Target Abort ..... always reads 0
- 0 Target Abort never signaled

10-9 DEVSEL# Timing
- 00 Fast
- 01 Medium ..... always reads 01
- 10 Slow
- 11 Reserved

8 Data Parity Error Detected
- 0 No data parity error detected ..... default
- 1 Error detected in data phase. Set only if error response enabled via command bit-6 = 1 and the North Bridge was initiator of the operation in which the error occurred... write one to clear

7 Fast Back-to-Back Capable ..... always reads 0

6 User Definable Features ..... always reads 0

5 66MHz Capable ..... always reads 0

4 Supports New Capability list ..... always reads 0

3-0 Reserved ..... always reads 0

Offset 8 - Revision ID (0nh) ..... RO

11-0 Chip Revision Code ..... always reads 0nh

Offset 9 - Programming Interface (00h) ..... RO

7-0 Interface Identifier ..... always reads 00h

Offset A - Sub Class Code (00h) ..... RO

7-0 Sub Class Code ..... reads 00 to indicate Host Bridge

Offset B - Base Class Code (06h) ..... RO

7-0 Base Class Code .. reads 06 to indicate Bridge Device

Device 0 Function 4 Device-Specific Registers

These registers are normally programmed once at system initialization time.

Power Management Control

Offset A0 – Power Management Mode (00h).....RW

- **7 Dynamic Power Management**
  - 0 Disable .....default
  - 1 Enable
- **6 Halt / Shutdown Power Management**
  - 0 Disable .....default
  - 1 Enable
- **5 Stop Clock Power Management**
  - 0 Disable .....default
  - 1 Enable
- **4 Suspend Status Power Management**
  - 0 Disable .....default
  - 1 Enable
- **3-0 Reserved** ..... always reads 0

Offset A1 – DRAM Power Management (00h).....RW

- **7 Reserved** ..... always reads 0
- **6 Dynamic CKE when DRAM Idle**
  - 0 Disable .....default
  - 1 Enable
- **5 Dynamic DRAM I/O Pad Power Down (Float)**
  - 0 Disable .....default
  - 1 Enable
- **4-0 Reserved** ..... always reads 0

Offset A2 – Dynamic Clock Stop Control (00h)..... RW

- **7 Host Interface Power Management**
  - 0 Disable..... default
  - 1 Enable
- **6 DRAM Interface Power Management**
  - 0 Disable..... default
  - 1 Enable
- **5 V-Link Interface Power Management**
  - 0 Disable..... default
  - 1 Enable
- **4 AGP Interface Power Management**
  - 0 Disable..... default
  - 1 Enable
- **3 PCI #2 Interface Power Management**
  - 0 Disable..... default
  - 1 Enable
- **2 Graphics Interface Power Management**
  - 0 Disable..... default
  - 1 Enable
- **1 Reserved** .....always reads 0
- **0 Host Fast Power Management (DADS Fast Timing)**
  - 0 Disable..... default
  - 1 Enable

Offset A3 – DRAM Pad Toggle Reduction (00h)..... RW

- **7 MA / SCMD Pin Toggle Reduction**
  - 0 Disable..... default
  - 1 Enable (MA and S command pins won't toggle if not accessed)
- **6-0 Reserved** .....always reads 0

BIOS Scratch

Offset D0-EF – BIOS Scratch Registers ..... RW

- **7-0 No hardware function** ..... default = 0

Device 0 Function 7 Registers – V-Link

Device 0 Function 7 Header Registers

All registers are located in PCI configuration space. They should be programmed using PCI configuration mechanism 1 through CF8 / CFC with bus number and device number equal to zero and function number equal to 7.

Offset 1-0 - Vendor ID (1106h) ..... RO

15-0 ID Code (reads 1106h to identify VIA Technologies)

Offset 3-2 - Device ID for V-Link Control (7259h) ..... RO

15-0 ID Code (reads 7259h to identify the CN333 North Bridge virtual device function 7)

Offset 5-4 –Command (0006h) ..... RW

15-10 Reserved ..... always reads 0

9 Fast Back-to-Back Cycle Enable ..... RO
- 0 Fast back-to-back transactions only allowed to the same agent ..... default
- 1 Fast back-to-back transactions allowed to different agents

8 SERR# Enable ..... RO
- 0 SERR# driver disabled ..... default
- 1 SERR# driver enabled

7 Address / Data Stepping ..... RO
- 0 Device never does stepping ..... default
- 1 Device always does stepping

6 Parity Error Response ..... RW
- 0 Ignore parity errors & continue ..... default
- 1 Take normal action on detected parity errors

5 VGA Palette Snoop ..... RO
- 0 Treat palette accesses normally ..... default
- 1 Don't respond to palette accesses on PCI bus

4 Memory Write and Invalidate Command ..... RO
- 0 Bus masters must use Mem Write ..... default
- 1 Bus masters may generate Mem Write & Inval

3 Special Cycle Monitoring ..... RO
- 0 Does not monitor special cycles ..... default
- 1 Monitors special cycles

2 PCI Bus Master ..... RO
- 0 Never behaves as a bus master
- 1 Can behave as a bus master ..... default

1 Memory Space ..... RO
- 0 Does not respond to memory space
- 1 Responds to memory space ..... default

0 I/O Space ..... RO
- 0 Does not respond to I/O space ..... default
- 1 Responds to I/O space

Offset 7-6 – Status (0200h) ..... RWC

15 Detected Parity Error
- 0 No parity error detected ..... default
- 1 Error detected in either address or data phase. This bit is set even if error response is disabled (command register bit-6). ..... write one to clear

14 Signaled Sys Err (SERR# Asserted) . always reads 0

13 Signaled Master Abort
- 0 No abort received ..... default
- 1 Transaction aborted by master . write 1 to clear

12 Received Target Abort
- 0 No abort received ..... default
- 1 Transaction aborted by target ... write 1 to clear

11 Signaled Target Abort ..... always reads 0
- 0 Target Abort never signaled

10-9 DEVSEL# Timing
- 00 Fast
- 01 Medium ..... always reads 01
- 10 Slow
- 11 Reserved

8 Data Parity Error Detected
- 0 No data parity error detected ..... default
- 1 Error detected in data phase. Set only if error response enabled via command bit-6 = 1 and the North Bridge was initiator of the operation in which the error occurred... write one to clear

7 Fast Back-to-Back Capable ..... always reads 0

6 User Definable Features ..... always reads 0

5 66MHz Capable ..... always reads 0

4 Supports New Capability list ..... always reads 0

3-0 Reserved ..... always reads 0

Offset 8 - Revision ID (0nh) ..... RO

12-0 Chip Revision Code ..... always reads 0nh

Offset 9 - Programming Interface (00h) ..... RO

7-0 Interface Identifier ..... always reads 00h

Offset A - Sub Class Code (00h) ..... RO

7-0 Sub Class Code ..... reads 00 to indicate Host Bridge

Offset B - Base Class Code (06h) ..... RO

7-0 Base Class Code .. reads 06 to indicate Bridge Device

Offset 2D-2C – Subsystem Vendor ID (0000h) ..... W1 / RO

15-0 Subsystem Vendor ID ..... default = 0

This register may be written once and is then read only.

Offset 2F-2E – Subsystem ID (0000h) ..... W1 / RO

15-0 Subsystem ID ..... default = 0

This register may be written once and is then read only.

Offset 37-34 - Capability Pointer (CAPPTR) ..... RO

Contains an offset from the start of configuration space.

31-0 AGP Capability List Ptr ... always reads 0000 0000h

Device 0 Function 7 Device-Specific Registers

These registers are normally programmed once at system initialization time.

V-Link Control

Offset 40 – V-Link Specification ID (40h).....RO

7-0 Specification Revision..... always reads 40

Offset 41 – NB V-Link Capability (39h).....RO

7-6 Reserved ..... always reads 0

5 16-bit Bus Width Supported by NB .....RO
- 0 Not Supported
- 1 Supported.....**default**

4 8-Bit Bus Width Supported by NB.....RO
- 0 Not Supported
- 1 Supported.....**default**

3 4x Rate Supported by NB.....RO
- 0 Not Supported
- 1 Supported.....**default**

2 2x Rate Supported by NB.....RO
- 0 Not Supported .....default
- 1 Supported

1 Reserved ..... always reads 0

0 8x Rate Supported by NB.....RO
- 0 Not Supported
- 1 Supported.....**default**

Offset 42 – NB Downlink Command (88h) .....RW

7-4 DnCmd Max Request Depth (0=1 DnCmd).. def = 8

3-0 DnCmd Write Buffer Size (doublewords)..... def = 8

Offset 43 – NB Uplink Max Req Depth (80h) .....RO

7-4 UpCmd Max Request Depth (0=1 UpCmd).. def = 8
Indicates the maximum allowable number of outstanding UPCMD requests

3-0 Reserved ..... always reads 0

Offset 44 – NB Uplink Buffer Size (82h) .....RO

7-4 UpCmd P2C Write Buffer Size (max lines).. def = 8

3-0 UpCmd P2P Write Buffer Size (max lines) .. def = 2

Offset 45 –NB V-Link Bus Timer (44h)..... RW

7-4 Timer for Normal Priority Requests from SB
- 0000 Immediate
- 0001 1*4 VCLKs
- 0010 2*4 VCLKs
- 0011 3*4 VCLKs
- 0100 4*4 VCLKs..... default
- 0101 5*4 VCLKs
- 0110 6*4 VCLKs
- 0111 7*4 VCLKs
- 1000 8*4 VCLKs
- 1001 16*4 VCLKs
- 1010 32*4 VCLKs
- 1011 64*4 VCLKs
- 11xx Own the bus for as long as there is a request

3-0 Timer for High Priority Requests from SB
- 0000 Immediate
- 0001 1*2 VCLKs
- 0010 2*2 VCLKs
- 0011 3*2 VCLKs
- 0100 4*2 VCLKs..... default
- 0101 5*2 VCLKs
- 0110 6*2 VCLKs
- 0111 7*2 VCLKs
- 1000 8*2 VCLKs
- 1001 16*2 VCLKs
- 1010 32*2 VCLKs
- 1011 64*2 VCLKs
- 11xx Own the bus for as long as there is a request

Offset 46 – NB V-Link Misc Control (00h) ..... RW

7 Downstream High Priority
- 0 Disable High Priority Down Commands .....def
- 1 Enable High Priority Down Commands

6 Downlink Priority
- 0 Treat Downlink Cycles as Normal Priority.def
- 1 Treat Downlink Cycles as High Priority

5-4 Combine Multiple STPGNT Cycles Into One V-Link Command
- 00 Compatible, 1 command per V-Link cmd....def
- 01 2 commands per V-Link command
- 10 3 commands per V-Link command
- 11 4 commands per V-Link command

3-2 V-Link Master Access Ordering Rules
- 00 High priority read, pass normal read (not pass write) .....default
- 01 Read (high/normal) pass write (HR>LR>W)
- 1x Read / write in order (ignore bit-1)

1 Read Around Write (ignored if bit-3 = 1)
- 0 Reads always pass writes .....default
- 1 8RAW

0 Reserved ..... always reads 0

Offset 47 – V-Link Control (00h) ..... RW

7-6 Reserved ..... always reads 0

5 C2P Read L1 Ready Return Timing
- 0 V-Link bus decodes C2P Read Ack cmd .....def
- 1 Wait till previous P2C write cycles all flushed

4 Reserved ..... always reads 0

3 Down Strobe Dynamic Stop
- 0 Disable .....default
- 1 Enable

2 Auto-Disconnect
- 0 Disable .....default
- 1 Enable

1 V-Link Disconnect Cycle for STPGNT Cycle
- 0 Disable .....default
- 1 Enable

0 V-Link Disconnect Cycle for HALT Cycle
- 0 Disable .....default
- 1 Enable

Offset 48 – NB/SB V-Link Configuration (18h) ..... RW

7 V-Link Parity Check
- 0 Disable..... default
- 1 Enable

6 Reserved .....always reads 0

5 16-bit Bus Width Supported
- 0 Not Supported..... default
- 1 Supported

4 8-Bit Bus Width Supported
- 0 Not Supported
- 1 Supported ..... **default**

3 4x Rate Supported
- 0 Not Supported
- 1 Supported ..... **default**

2 Reserved .....always reads 0

1 V-Link Split Bus
- 0 Disable..... default
- 1 Enable

0 8x Rate Supported
- 0 Not Supported..... default
- 1 Supported

Transfers Per

V-Link Mode	66MHz Cycle	Bits	Bus Usage	Rx48 Bit-4	Rx48 Bit-5	Rx48 Bit-1
0	4x	8	Bidirectional	0	0	0
1	8x	4+4	Split	1	0	1
2	8x	8	Bidirectional	1	0	0
3	4x	16	Bidirectional	0	1	0
4	8x	8+8	Split	1	1	1

Offset 49 – SB V-Link Capability (19h) ..... WC

7-6 Reserved .....always reads 0

5 16-bit Bus Width Supported by SB..... RO
- 0 Not Supported..... default
- 1 Supported

4 8-Bit Bus Width Supported by SB ..... RO
- 0 Not Supported
- 1 Supported ..... **default**

3 4x Rate Supported by SB..... RO
- 0 Not Supported
- 1 Supported ..... **default**

2 2x Rate Supported by SB..... RO
- 0 Not Supported..... default
- 1 Supported

1 Reserved .....always reads 0

0 8x Rate Supported by SB..... RO
- 0 Not Supported
- 1 Supported ..... **default**

Offset 4A – SB Downlink Status (88h) .....RO

7-4 DnCmd Max Request Depth (0=1 DnCmd).. def = 8
3-0 DnCmd Write Buffer Size (doublewords)..... def = 8

Offset 4B – SB Uplink Command (80h) .....RW

7-4 UpCmd Max Request Depth (0=1 UpCmd).. def = 8
Indicates the maximum allowable number of outstanding UPCMD requests
3-0 Reserved ..... always reads 0

Offset 4C – SB Uplink Command (82h).....RW

7-4 UpCmd P2C Write Buffer Size (max lines).. def = 8
3-0 UpCmd P2P Write Buffer Size (max lines).. def = 2

Offset 4D – SB V-Link Bus Timer (44h) .....RW

7-4 Timer for Normal Priority Requests from NB
0000 Immediate
0001 1*4 VCLKs
0010 2*4 VCLKs
0011 3*4 VCLKs
0100 4*4 VCLKs .....default
0101 5*4 VCLKs
0110 6*4 VCLKs
0111 7*4 VCLKs
1000 8*4 VCLKs
1001 16*4 VCLKs
1010 32*4 VCLKs
1011 64*4 VCLKs
11xx Own the bus for as long as there is a request

3-0 Timer for High Priority Requests from NB
0000 Immediate
0001 1*2 VCLKs
0010 2*2 VCLKs
0011 3*2 VCLKs
0100 4*2 VCLKs .....default
0101 5*2 VCLKs
0110 6*2 VCLKs
0111 7*2 VCLKs
1000 8*2 VCLKs
1001 16*2 VCLKs
1010 32*2 VCLKs
1011 64*2 VCLKs
11xx Own the bus for as long as there is a request

Offset 4E – CCA Master Priority (00h)..... RW

7 1394 High Priority
0 Low priority..... default
1 High priority
6 LAN / NIC High Priority
0 Low priority..... default
1 High priority
5 Reserved .....always reads 0
4 USB High Priority
0 Low priority..... default
1 High priority
3 Reserved .....always reads 0
2 IDE High Priority
0 Low priority..... default
1 High priority
1 AC97-ISA High Priority
0 Low priority..... default
1 High priority
0 PCI High Priority
0 Low priority..... default
1 High priority

Offset 4F – SB V-Link Misc Control (00h)..... RW

7 Upstream Command High Priority
0 Disable high priority up commands..... default
1 Enable high priority up commands
6-4 Reserved .....always reads 0
3 Up Strobe Dynamic Stop
0 Disable..... default
1 Enable
2-1 Reserved .....always reads 0
0 Down Cycle Wait for Up Cycle Write Flush (Except Down Cycle Post Write)
0 Disable..... default
1 Enable

Offset 57 – Bank 7 Ending (01h) ..... RO

DRAM Bank 7 Ending Address High (HA[31:24]) sent to the South Bridge. (See also Function 3 Rx47).

Offset 61 – C-ROM Shadow (00h) ..... RW

(same as Function 3 Rx80)

Offset 62 – D-ROM Shadow (00h) ..... RW

(same as Function 3 Rx81)

Offset 63 – F-ROM Shadow / Mem Hole / SMI (00h) ... RW

(same as Function 3 Rx82)

Offset 64 – E-ROM Shadow (00h)..... RW

(same as Function 3 Rx83)

PCI Bus Control

These registers are normally programmed once at system initialization time.

Offset 70 - PCI Buffer Control (00h) ..... RW

- **7 CPU to PCI Post-Write**
  - 0 Disable ..... default
  - 1 Enable
- **6 Reserved** ..... always reads 0
- **5-4 PCI Master to DRAM Prefetch**
  - 00 Always prefetch ..... default
  - x1 Never prefetch
  - 10 Prefetch only for Enhance command
- **3 Reserved** ..... always reads 0
- **2 PCI Master Read Buffering**
  - 0 Disable ..... default
  - 1 Enable
- **1 Delay Transaction**
  - 0 Disable ..... default
  - 1 Enable
- **0 Reserved** ..... always reads 0

Offset 71 - CPU to PCI Flow Control (48h) ..... RWC

- **7 Retry Status ..... RWC**
  - 0 No retry occurred ..... default
  - 1 Retry occurred
- **6 Retry Timeout Action**
  - 0 Retry forever (record status only)
  - 1 Flush buffer or return FFFFFFFFh for reads ..... default
- **5-4 Retry Count and Retry Backoff**
  - 00 Retry 2 times, backoff CPU ..... default
  - 01 Retry 16 times
  - 10 Retry 4 times
  - 11 Retry 64 times
- **3 PCI Burst**
  - 0 Disable
  - 1 Enable ..... default
- **2 Reserved** ..... always reads 0
- **1 Compatible Type#1 Configuration Cycles**
  - 0 Disable (fixed AD31) ..... default
  - 1 Enable
- **0 IDSEL Control**
  - 0 AD11, AD12 ..... default
  - 1 AD30, AD31

Offset 73 - PCI Master Control (00h) ..... RW

- **7 Reserved** ..... always reads 0
- **6 PCI Master 1-Wait-State Write**
  - 0 Zero wait state TRDY# response..... default
  - 1 One wait state TRDY# response
- **5 PCI Master 1-Wait-State Read**
  - 0 Zero wait state TRDY# response..... default
  - 1 One wait state TRDY# response
- **4 WSC#**
  - 0 Disable..... default
  - 1 Enable
- **3-1 Reserved** ..... always reads 0
- **0 PCI Master Broken Timer Enable**
  - 0 Disable..... default
  - 1 Enable. Force into arbitration when there is no FRAME# 16 PCICLK's after the grant.

Offset 75 - PCI Arbitration 1 (00h).....RW

7 Arbitration Mode
- 0 REQ-based (arbitrate at end of REQ#) ..default
- 1 Frame-based (arbitrate at FRAME# assertion)

6-4 CPU Latency

3 Reserved ..... always reads 0

2-0 PCI Master Bus Time-Out
(force into arbitration after a period of time)
- 000 Disable .....default
- 001 1x16 PCICLKs
- 010 2x16 PCICLKs
- 011 3x16 PCICLKs
- 100 4x16 PCICLKs
- ... ...
- 111 7x16 PCICLKs

Offset 76 - PCI Arbitration 2 (00h)..... RW

7 I/O Port 22 Access
- 0 CPU access to I/O address 22h is passed on to the PCI bus ..... default
- 1 CPU access to I/O address 22h is processed internally

6 Reserved .....always reads 0

5-4 Master Priority Rotation Control
- 00 Disable..... default
- 01 Grant to CPU after every PCI master grant
- 10 Grant to CPU after every 2 PCI master grants
- 11 Grant to CPU after every 3 PCI master grants

Setting 01: the CPU will always be granted access after the current bus master completes, no matter how many PCI masters are requesting.

Setting 10: if other PCI masters are requesting during the current PCI master grant, the highest priority master will get the bus after the current master completes, but the CPU will be guaranteed to get the bus after that master completes.

Setting 11: if other PCI masters are requesting, the highest priority will get the bus next, then the next highest priority will get the bus, then the CPU will get the bus.

In other words, with the above settings, even if multiple PCI masters are continuously requesting the bus, the CPU is guaranteed to get access after every master grant (01), after every other master grant (10) or after every third master grant (11).

3-2 Select REQn# to REQ4# mapping
- 00 REQ4#..... default
- 01 REQ0#
- 10 REQ1#
- 11 REQ2#

1 Reserved .....always reads 0

0 REQ4# is High Priority Master
- 0 Disable..... default
- 1 Enable

Graphics Aperture Control

Offset 85-84 – Graphics Aperture Size (0000h).....RW

15-12 Reserved ..... always reads 0

11-0 Graphics Aperture Size [31:20] ..... default = 00h

111100111111	4MB
111100111110	8MB
111100111100	16MB
111100111000	32MB
111100110000	64MB
111100100000	128MB
111100000000	256MB
111000000000	512MB
110000000000	1GB
100000000000	2GB <= Max supported
000000000000	4GB <= Do not program

In AGP 2.0 mode, only 4MB - 256MB are supported

Offset 88 – GART Base (00h).....RW

7-2 Reserved ..... always reads 0

1 GART Window Access

0 Disable .....default

1 Enable

0 Reserved ..... always reads 0

V-Link CKG Control

Offset B0 – V-Link CKG Control 1 (00h) ..... RW

7 Rise Time Duty Cyclc Control - V-Link #1 R-Port

6 Rise Time Duty Cyclc Control - V-Link #0 R-Port

5 Fall Time Duty Cyclc Control - V-Link #1 R-Port

4 Fall Time Duty Cyclc Control - V-Link #0 R-Port

3 Rise Time Duty Cyclc Control - V-Link #1 S-Port

2 Rise Time Duty Cyclc Control - V-Link #0 S-Port

1 Fall Time Duty Cyclc Control - V-Link #1 S-Port

0 Fall Time Duty Cyclc Control - V-Link #0 S-Port

Offset B1 – V-Link CKG Control 2 (00h) ..... RW

7-4 Reserved .....always reads 0

3 Rise Time Duty Cyclc Control - V-Link #1 D-Port

2 Rise Time Duty Cyclc Control - V-Link #0 D-Port

1 Fall Time Duty Cyclc Control - V-Link #1 D-Port

0 Fall Time Duty Cyclc Control - V-Link #0 D-Port

V-Link Compensation / Drive Control

Offset B4 – V-Link NB Compensation Control (00h) .... RW

- **7-5 V-Link Autocomp Output Value – High Drive** . RO
- **4 Reserved** ..... always reads 0
- **3-1 V-Link Autocomp Output Value – Low Drive** .. RO
- **0 Compensation Select**
  - 0 Auto Comp (use values in bits 7-5, 3-1) default
  - 1 Manual Comp (use values in RxB5, B6)

Offset B5 – V-Link NB Strobe Drive Control (00h) ..... RW

- **7-5 V-Link Strobe Pullup Manual Setting (High)**
- **4 Reserved** ..... always reads 0
- **3-1 V-Link Strobe Pulldown Manual Setting (Low)**
- **0 Reserved** ..... always reads 0

Offset B6 – V-Link NB Data Drive Control (00h) ..... RW

- **7-5 V-Link Data Pullup Manual Setting (High)**
- **4 Reserved** ..... always reads 0
- **3-1 V-Link Data Pulldown Manual Setting (Low)**
- **0 Reserved** ..... always reads 0

Offset B7 – V-Link NB Receive Strobe Delay (00h) ..... RW

- **7-2 Reserved** ..... always reads 0
- **1-0 NB V-Link Strobe Delay for Receiving**
  - 00 150 psec early ..... default
  - 01 No delay
  - 10 150 psec late
  - 11 300 psec late

VT8237 South Bridge:

Offset B8 – V-Link SB Compensation Control (00h) .... RW

- **7-5 V-Link Autocomp Output Value – High Drive** .RO
- **4-1 Reserved** ..... always reads 0
- **0 Compensation Select**
  - 0 Auto Comp (use values in bits 7-5) ..... default
  - 1 Manual Comp (use values in RxB9)

Offset B9 – V-Link SB Strobe Drive Control (00h) ..... RW

- **7-5 V-Link Strobe Pullup Manual Setting (High)**
- **4 Reserved** ..... always reads 0
- **3-1 V-Link Strobe Pulldown Manual Setting (Low)**
- **0 Reserved** ..... always reads 0

VT8233 South Bridge (VT8233, VT8233A):

Offset B8 – V-Link SB Compensation Control (00h) .... RW

- **7-6 V-Link Autocomp Output Value** ..... always reads 0
- **5 Pullup Compensation Selection**
  - 0 Auto Comp (use values in bits 7-6) ..... default
  - 1 Manual Comp (use values in bits 3-2)
- **4 Pulldown Compensation Selection**
  - 0 Auto Comp (use values in bits 7-6) ..... default
  - 1 Manual Comp (use values in bits 1-0)
- **3-2 Pullup Compensation Manual Setting** ..... def = 0
- **1-0 Pulldown Compensation Manual Setting** ..... def = 0

Offset B9 – V-Link SB Drive Control (00h) ..... RW

- **7-6 SB V-Link Strobe Pullup Manual Setting**
- **5-4 SB V-Link Strobe Pulldown Manual Setting**
- **3-1 Reserved** ..... always reads 0
- **0 SB V-Link Slew Rate Control**
  - 0 Disable ..... default
  - 1 Enable

DRAM Above 4G Support

Offset E4 – Low Top Address Low (00h) ..... RW

(same as Function 3 Rx84)

Offset E5 – Low Top Address High (FFh) ..... RW

(same as Function 3 Rx85)

Offset E6 – SMM / APIC Decoding (01h) ..... RW

(same as Function 3 Rx86)

Device 1 Registers – PCI-to-PCI Bridge

Device 1 Header Registers

All registers are located in PCI configuration space. They should be programmed using PCI configuration mechanism 1 through CF8 / CFC with bus number of 0 and function number equal to 0 and device number equal to one.

Device 1 Offset 1-0 - Vendor ID (1106h) ..... RO

15-0 ID Code (reads 1106h to identify VIA Technologies)

Device 1 Offset 3-2 - Device ID (B198h) ..... RO

15-0 ID Code (reads B198h to identify the North Bridge PCI-to-PCI Bridge device)

Device 1 Offset 5-4 – Command (0007h) ..... RW

15-10 Reserved ..... always reads 0

9 Fast Back-to-Back Cycle Enable ..... RO
- 0 Fast back-to-back transactions only allowed to the same agent ..... default
- 1 Fast back-to-back transactions allowed to different agents

8 SERR# Enable ..... RO
- 0 SERR# driver disabled ..... default
- 1 SERR# driver enabled

7 Address / Data Stepping ..... RO
- 0 Device never does stepping ..... default
- 1 Device always does stepping

6 Parity Error Response ..... RW
- 0 Ignore parity errors & continue ..... default
- 1 Take normal action on detected parity errors

5 Reserved ..... always reads 0

4 Memory Write and Invalidate Command ..... RO
- 0 Bus masters must use Mem Write ..... default
- 1 Bus masters may generate Mem Write & Inval

3 Special Cycle Monitoring ..... RO
- 0 Does not monitor special cycles ..... default
- 1 Monitors special cycles

2 Bus Master ..... RW
- 0 Never behaves as a bus master
- 1 Enable to operate as a bus master on the primary interface on behalf of a master on the secondary interface ..... default

1 Memory Space ..... RW
- 0 Does not respond to memory space
- 1 Enable memory space access ..... default

0 I/O Space ..... RW
- 0 Does not respond to I/O space
- 1 Enable I/O space access ..... default

Device 1 Offset 7-6 - Status (Primary Bus) (0230h) .... RWC

15 Detected Parity Error ..... always reads 0

14 Signaled System Error (SERR#) ..... always reads 0

13 Signaled Master Abort
- 0 No abort received ..... default
- 1 Transaction aborted by the master with Master-Abort (except Special Cycles) ..... write 1 to clear

12 Received Target Abort
- 0 No abort received ..... default
- 1 Transaction aborted by the target with Target-Abort ..... write 1 to clear

11 Signaled Target Abort ..... always reads 0

10-9 DEVSEL# Timing
- 00 Fast
- 01 Medium ..... always reads 01
- 10 Slow
- 11 Reserved

8 Data Parity Error Detected ..... always reads 0

7 Fast Back-to-Back Capable ..... always reads 0

6 User Definable Features ..... always reads 0

5 66MHz Capable ..... always reads 1

4 Supports New Capability list ..... always reads 1

3-0 Reserved ..... always reads 0

Device 1 Offset 8 - Revision ID (00h) ..... RO

7-0 Chip Revision Code (00=First Silicon)

Device 1 Offset 9 - Programming Interface (00h) ..... RO

This register is defined in different ways for each Base/Sub-Class Code value and is undefined for this type of device.

7-0 Interface Identifier ..... always reads 00

Device 1 Offset A - Sub Class Code (04h) ..... RO

7-0 Sub Class Code .reads 04 to indicate PCI-PCI Bridge

Device 1 Offset B - Base Class Code (06h) ..... RO

7-0 Base Class Code.. reads 06 to indicate Bridge Device

Device 1 Offset E - Header Type (01h) ..... RO

7-0 Header Type Code..... reads 01: PCI-PCI Bridge

Device 1 Offset 13-10 – Graphics Aperture Base (0000 0008h).....RW

This register is interpreted per the following definition if RxFD[1]=1 (AGP 2.0 registers enabled).

31-22 Programmable Base Address Bits ..... def=0
These bits behave as if hardwired to 0 if the corresponding AGP 3.0 Graphics Aperture Size register bit (Device 0 Function 0 Offset 94h) is 0.

31	30	29	28	-	-	27	26	25	24	23	22	(Base)
11	10	9	8	7	6	5	4	3	2	1	0	(Size)
RW	RW	RW	RW	0	0	RW	RW	RW	RW	RW	RW	4M
RW	RW	RW	RW	0	0	RW	RW	RW	RW	RW	0	8M
RW	RW	RW	RW	0	0	RW	RW	RW	RW	0	0	16M
RW	RW	RW	RW	0	0	RW	RW	RW	0	0	0	32M
RW	RW	RW	RW	0	0	RW	RW	0	0	0	0	64M
RW	RW	RW	RW	0	0	RW	0	0	0	0	0	128M
RW	RW	RW	RW	0	0	0	0	0	0	0	0	256M
RW	RW	RW	0	0	0	0	0	0	0	0	0	512M
RW	RW	0	0	0	0	0	0	0	0	0	0	1G
RW	0	0	0	0	0	0	0	0	0	0	0	2G-max
0	0	0	0	0	0	0	0	0	0	0	0	4G

21-4 Reserved ..... always reads 0
3 Prefetchable.....**always reads 1**
2-1 Type ..... always reads 0
0 Memory Space..... always reads 0

Device 1 Offset 18 - Primary Bus Number (00h).....RW

7-0 Primary Bus Number ..... default = 0
This register is read write, but internally the chip always uses bus 0 as the primary.

Device 1 Offset 19 - Secondary Bus Number (00h) .....RW

7-0 Secondary Bus Number..... default = 0
Note: AGP must use these bits to convert Type 1 to Type 0.

Device 1 Offset 1A - Subordinate Bus Number (00h) ....RW

7-0 Primary Bus Number..... default = 0
Note: AGP must use these bits to decide if Type 1 to Type 1 command passing is allowed.

Device 1 Offset 1C - I/O Base (F0h).....RW

7-4 I/O Base AD[15:12]..... default = 1111b
3-0 I/O Addressing Capability ..... default = 0

Device 1 Offset 1D - I/O Limit (00h).....RW

7-4 I/O Limit AD[15:12] ..... default = 0
3-0 I/O Addressing Capability ..... default = 0

Device 1 Offset 1F-1E - Secondary Status ..... RO

15-0 Secondary Status
Rx44[4] = 0: these bits read back 0000h
Rx44[4] = 1: these bits read back same as Rx7-6

Device 1 Offset 21-20 - Memory Base (FFF0h) ..... RW

15-4 Memory Base AD[31:20] ..... default = FFFh
3-0 Reserved .....always reads 0

Device 1 Offset 23-22 - Memory Limit (Inclusive) (0000h) RW

15-4 Memory Limit AD[31:20].....default = 0
3-0 Reserved .....always reads 0

Device 1 Offset 25-24 - Prefetchable Mem Base (FFF0h) RW

15-4 Prefetchable Memory Base AD[31:20]default = FFFh
3-0 Reserved .....always reads 0

Device 1 Offset 27-26 - Prefetchable Memory Limit (0000h) ..... RW

15-4 Prefetchable Memory Limit AD[31:20].. default = 0
3-0 Reserved .....always reads 0

Device 1 Offset 34 - Capability Pointer (70h)..... RO

Contains an offset from the start of configuration space.

7-0 AGP Capability List Pointer .....always reads 70h

Device 1 Device-Specific Registers

AGP Bus Control

Device 1 Offset 40 - CPU-to-AGP Flow Control 1 (00h) RW

7 CPU-AGP Post Write
- 0 Disable .....default
- 1 Enable

6 CPU-AGP One Wait State Burst Write
- 0 Disable .....default
- 1 Enable

5-4 Read Prefetch Control
- 00 Always prefetch .....default
- x1 Never prefetch
- 10 Prefetch only for Enhance command

3 Reserved ..... always reads 0

2 MDA Present on AGP
- 0 Forward MDA accesses to AGP .....default
- 1 Forward MDA accesses to PCI

Note: Forward despite IO / Memory Base / Limit

Note: MDA (Monochrome Display Adapter) addresses are memory addresses B0000h-B7FFFh and I/O addresses 3B4-3B5h, 3B8-3BAh and 3BFh (10-bit decode). 3BC-3BE are reserved for printers.

Note: If Rx3E bit-3 is 0, this bit is a don't care (MDA accesses are forwarded to the PCI bus).

1 AGP Master Read Caching
- 0 Disable .....default
- 1 Enable

0 AGP Delay Transaction
- 0 Disable .....default
- 1 Enable

Table 10. VGA/MDA Memory/IO Redirection

3E[3] VGA Pres.	40[2] MDA Pres.	VGA is on	MDA is on	Axxxx, B8xxx Access	B0000 -B7FFF Access	3Cx, 3Dx I/O	3Bx I/O
0	-	PCI	PCI	PCI	PCI	PCI	PCI
1	0	AGP	AGP	AGP	AGP	AGP	AGP
1	1	AGP	PCI	AGP	PCI	AGP	PCI

Device 1 Offset 41 - CPU-to-AGP Flow Control 2 (08h) RW

7 Retry Status
- 0 No retry occurred..... default
- 1 Retry Occurred .....**write 1 to clear**

6 Retry Timeout Action
- 0 No action taken except to record status ..... def
- 1 Flush buffer for write or return all 1s for read

5-4 Retry Count
- 00 Retry 2, backoff CPU ..... default
- 01 Retry 4, backoff CPU
- 10 Retry 16, backoff CPU
- 11 Retry 64, backoff CPU

3 CPU-to-AGP Bursting Timeout
- 0 Disable
- 1 Enable**..... default**

2 Reserved .....always reads 0

1 CPU-to-PCI/AGP Cycles Invalidate PCI/AGP Buffered Read Data
- 0 Disable..... default
- 1 Enable

0 Reserved .....always reads 0

Device 1 Offset 42 - AGP Master Control (00h) ..... RW

7 Reserved (Must Be Programmed to 1) .....def = 0

When this bit is set, the North Bridge will automatically resolve the problem of AGP master cycles being blocked by PCI Master Cycles.

6 AGP Master One Wait State Write
- 0 Disable..... default
- 1 Enable

5 AGP Master One Wait State Read
- 0 Disable..... default
- 1 Enable

4 Break Consecutive PCI Master Accesses
- 0 Disable..... default
- 1 Enable

3 Reserved .....always reads 0

2 Claim I/O R/W and Memory Read Cycles
- 0 Disable..... default
- 1 Enable

1 Claim Local APIC FEEx xxxx Cycles
- 0 Disable..... default
- 1 Enable

0 Snoop Write Enable 2T Rate, Support Host Side Snoop Cycles at 2T Rate
- 0 Disable..... default
- 1 Enable

Device 1 Offset 43 - AGP Master Latency Timer (22h) RW

7-4 Host to AGP Time slot
- 0 Disable (no timer)
- 1 16 GCLKs
- 2 32 GCLKs ..... default
- … …
- F 128 GCLKs

3-0 AGP Master Time Slot
- 0 Disable (no timer)
- 1 16 GCLKs
- 2 32 GCLKs ..... default
- … …
- F 128 GCLKs

Device 1 Offset 47-46 – PCI-to-PCI Bridge Device ID ... RW

15-0 PCI-to-PCI Bridge Device ID ..... default = 0000

Power Management

Device 1 Offset 70 – Capability ID (01h) ..... RO

7-0 Capability ID ..... always reads 01h

Device 1 Offset 71 – Next Pointer (00h) ..... RO

7-0 Next Pointer: Null ..... always reads 00h

Device 1 Offset 72 – Power Mgmt Capabilities 1 (02h) .. RO

7-0 Power Mgmt Capabilities ..... always reads 02h

Device 1 Offset 73 – Power Mgmt Capabilities 2 (00h) .. RO

7-0 Power Mgmt Capabilities ..... always reads 00h

Device 1 Offset 74 – Power Mgmt Ctrl/Status (00h)..... RW

7-2 Reserved ..... always reads 0

1-0 Power State
- 00 D0 ..... default
- 01 -reserved-
- 10 -reserved-
- 11 D3 Hot

Device 1 Offset 75 – Power Mgmt Status (00h)..... RO

7-0 Power Mgmt Status ..... default = 00

Device 1 Offset 76 – P2P Br. Support Extensions (00h) . RO

7-0 P2P Bridge Support Extensions ..... default = 00

Device 1 Offset 77 – Power Management Data (00h) ..... RO

7-0 Power Management Data ..... default = 00

ELECTRICAL SPECIFICATIONS

Absolute Maximum Ratings

Table 11. Absolute Maximum Ratings

Symbol	Parameter	Min	Max	Unit	Notes
T_C	Case operating temperature	0	85	°C	1
T_S	Storage temperature	–55	125	°C	1
V_{IN}	Input voltage	–0.5	V_{RAIL} + 10%	Volts	1, 2
V_{OUT}	Output voltage	–0.5	V_{RAIL} + 10%	Volts	1, 2

Note 1. Stress above the conditions listed may cause permanent damage to the device. Functional operation of this device should be restricted to the conditions described under operating conditions.

Note 2. V_{RAIL} is defined as the V_{CC} level of the respective rail. The CPU interface voltage is CPU dependent. AGP is 1.5V (4x transfer mode) or 0.8V (8x transfer mode). V-Link is 1.5V. Memory is 2.5V. Graphics / Display is 3.3V.

DC Characteristics

T_C = 0-85°C, V_{RAIL} = V_{CC} ±5%, V_{CORE} = 1.5V ±5%, GND=0V

Table 12. DC Characteristics

Symbol	Parameter	Min	Max	Unit	Condition
V_{IL}	Input Low Voltage	–0.50	0.8	V	
V_{IH}	Input High Voltage	2.0	V_{CC} + 0.5	V	
V_{OL}	Output Low Voltage	–	0.55	V	I_{OL} = 4.0mA
V_{OH}	Output High Voltage	2.4	–	V	I_{OH} = –1.0mA
I_{IL}	Input Leakage Current	–	±10	uA	0 < V_{IN} < V_{CC}
I_{OZ}	Tristate Leakage Current	–	±20	uA	0.55 < V_{OUT} < V_{CC}

MECHANICAL SPECIFICATIONS



Figure 5. Mechanical Specifications – 681-Pin HSBGA Ball Grid Array Package with Heat Spreader



Figure 6. Lead-Free Mechanical Specifications – 681-Pin HSBGA Ball Grid Array Package with Heat Spreader