

The FARM
Felix Annotated Reference Manual

John Skaller

May 2, 2016

Contents

1	Introduction	8
I	Gross Structure	9
2	Program structure	10
2.1	Parse Unit	10
2.2	AST	10
2.3	Grammar	11
2.4	Grammar syntax	11
3	Modules	12
3.1	Special procedure <code>flx_main</code>	12
3.2	Libraries	13
4	Lexicology	14
4.1	Comments	14
4.1.1	C++ comments	14
4.1.2	Nested C comments	14
4.2	Layout	15
4.3	File inclusion	15
4.4	fdoc files	15
4.4.1	Uncomments	15
4.4.2	<code>#line</code> directive	16
4.5	<code>#!</code> directive	16
4.6	Identifiers	16
4.6.1	Plain Identifiers	17
4.6.2	TeX Identifiers	17
4.7	Operator Identifiers	17
4.7.1	Special identifiers	18
4.8	Boolean Literals	18
4.9	Integer Literals	18
4.10	Floating point literals	19
4.11	String like literals	19

<i>CONTENTS</i>	2
4.11.1 Standard string literals	19
4.11.2 Raw strings	20
4.11.3 Null terminated strings	20
4.11.4 Perl interpolation strings	20
4.11.5 C format strings	21
5 Macro processing	25
5.1 Include Directive	25
5.2 Macro val	25
5.3 Macro for	26
5.4 Constant folding and conditional compilation	26
II Lookup	27
6 Classes	28
6.1 Class Statement	28
6.1.1 Qualified Names	28
6.1.2 Nested Classes	28
6.1.3 Private definitions	29
6.1.4 Single File Rule	29
6.1.5 Completeness Rule	29
6.1.6 Setwise Lookup	29
6.1.7 Top level module alias	29
6.2 Polymorphic Classes	30
6.2.1 Parametric Polymorphism	30
6.2.2 No Variables	30
6.2.3 Qualified Names	30
6.2.4 Polymorphic Members	31
6.3 Virtuals and instances	31
6.3.1 Default Definition	32
6.3.2 Matching polymorphic functions	33
6.4 Classes as Categories	33
6.5 Axioms, Lemmas and Theorems	34
6.5.1 Lemmas and Theorems	35
6.5.2 Reductions	36
7 General lookup	37
8 Overload Resolution	38
9 Lookup control directives	39
9.1 Open directive	39
9.2 Inherit directive	39
9.3 Rename directive	40
9.4 Use directive	40

<i>CONTENTS</i>	3
9.5 Export directives	40
III Type System	42
10 Type constructors	43
10.1 typedef	43
10.2 Tuples	43
10.2.1 Tuple projections	44
10.3 Records	44
10.3.1 Plain Record	44
10.3.2 Record projections	45
10.3.3 General record	45
10.3.4 Adding fields	46
10.3.5 Row Polymorphism	46
10.3.6 Interfaces	47
10.4 Structs	47
10.5 Sums	48
10.5.1 Unit sum	48
10.6 union	49
10.6.1 enum	50
10.6.2 caseno operator	50
10.7 variant	50
10.8 Array	51
10.8.1 Multi-arrays	51
11 Meta-typing	54
11.0.1 typedef fun	54
11.1 typematch	54
11.2 type sets	55
12 Abstract types	56
13 Polymorphism	57
IV Definitions	58
14 Variable Definitions	59
14.1 The <code>var</code> statement	59
14.1.1 Multiple variables	60
14.2 The <code>val</code> statement	60
14.2.1 Multiple values	61
15 Functions	62
15.1 Functions	62
15.2 Pre- and post-conditions	63

15.3	Higher order functions	63
15.4	Procedures	64
15.5	Generators	65
15.5.1	Yielding Generators	65
15.6	Constructors	66
15.7	Special function <code>apply</code>	67
15.8	Objects	67
V	Executable statements	69
15.9	Assignment	70
15.10	The <code>goto</code> statement and label <code>prefix</code>	70
15.10.1	<code>halt</code>	70
15.10.2	<code>try/catch/entry</code>	71
15.10.3	<code>goto-indirect/label_address</code>	71
15.10.4	Exchange of control	71
15.11	<code>match/endmatch</code>	72
15.12	<code>if/goto</code>	73
15.12.1	<code>if/return</code>	73
15.12.2	<code>if/call</code>	73
15.13	<code>if/do/elif/else/done</code>	73
15.14	<code>call</code>	74
15.15	procedure return	75
15.15.1	return from	75
15.15.2	<code>jump</code>	75
15.16	function return	75
15.16.1	<code>yield</code>	76
15.17	<code>spawn_fthread</code>	76
15.17.1	<code>read/write/broadcast schannel</code>	76
15.18	<code>spawn_pthread</code>	77
15.18.1	<code>read/write pchannel</code>	77
15.18.2	<code>exchange</code>	77
15.19	loops	77
15.19.1	<code>redo</code>	77
15.19.2	<code>break</code>	77
15.19.3	<code>continue</code>	78
15.19.4	<code>for/in/upto/downto/do/done</code>	78
15.19.5	<code>while/do/done</code>	78
15.19.6	<code>until loop</code>	78
15.19.7	<code>for/match/done</code>	79
15.19.8	<code>loop</code>	79
15.20	Assertions	79
15.21	<code>assert</code>	79
15.21.1	<code>axiom</code>	79
15.21.2	<code>lemma</code>	80
15.21.3	<code>theorem</code>	80

15.21.4 reduce	80
15.21.5 invariant	80
15.22 code	81
15.22.1 noreturn code	81
15.23 Service call	81
15.24 with/do/done	82
15.25 do/done	82
15.26 begin/end	82

VI Expressions 84

15.27 Chain forms	85
15.27.1 Pattern let	85
15.27.2 Function let	85
15.27.3 Match chain	85
15.27.4 conditional chain	86
15.28 Alternate conditional chain	86
15.29 Dollar application	86
15.30 Pipe application	86
15.31 Tuple cons constructor	87
15.32 N-ary tuple constructor	87
15.33 Logical implication	87
15.34 Logical disjunction	87
15.35 Logical conjunction	87
15.36 Logical negation	87
15.37 Comparisons	88
15.38 Name temporary	88
15.39 Schannel pipe operators	88
15.40 Right Arrows	88
15.41 Case literals	89
15.42 Bitwise or	89
15.43 Bitwise exclusive or	89
15.44 Bitwise and	90
15.45 Bitwise shifts	90
15.46 Addition	90
15.47 Subtraction	90
15.48 Multiplication	90
15.49 Division operators	90
15.50 Prefix operators	91
15.51 Fortran exponentiation	91
15.52 Felix exponentiation	91
15.53 Function composition	91
15.54 Dereference	91
15.54.1 Operator new	92
15.55 Whitespace application	92
15.55.1 General	92

15.55.2 Caseno operator	92
15.55.3 Likelyhood	92
15.56 Coercion operator	92
15.57 Suffixed name	93
15.58 Factors	93
15.58.1 Subscript	93
15.58.2 Subsstring	93
15.58.3 Copyfrom	93
15.58.4 Copyto	93
15.58.5 Reverse application	94
15.58.6 Reverse application with deref	94
15.58.7 Reverse application with addressing	94
15.58.8 Unit application	94
15.58.9 Addressing	94
15.58.10 C pointer	94
15.58.11 Label address	95
15.58.12 Macro freezer	95
15.58.13 Pattern variable	95
15.58.14 Parser argument	95
15.59 Qualified name	96
16 Atoms	97
16.1 Record expression	97
16.2 Alternate record expression	97
16.3 Variant type	97
16.4 Wildcard pattern	98
16.5 Ellipsis	98
16.6 Truth constants	98
16.7 callback expression	98
16.8 Lazy expression	98
16.9 Sequencing	98
16.10 Procedure of unit.	99
16.11 Grouping	99
16.12 Object extension	99
16.13 Conditional expression	99
VII Library	100
17 C bindings	101
17.1 Type bindings	101
17.2 Expression bindings	102
17.3 Function bindings	102
17.4 Floating insertions	102
17.5 Package requirements	102

18 Core Primitive Types	103
18.1 Boolean type	103
18.2 Integer types	103
18.2.1 Classification of integers	105
18.3 Floating point types	107
18.4 Complex types	107
18.5 Quaternion type	110
18.6 Char Type	110
18.6.1 ASCII classification functions	110
18.7 String Type	111
18.7.1 Equality and total ordering	111
18.7.2 Equality of <code>string</code> and <code>char</code>	111
18.7.3 Append to <code>string</code> object	111
18.7.4 Length of	
string	113
18.7.5 String concatenation	113
18.7.6 Repetition of <code>string</code> or <code>char</code>	113
18.7.7 Application of <code>string</code> to <code>string</code> or <code>int</code> is concatenation	113
18.7.8 Construct a char from first byte of a <code>string</code>	113
18.7.9 Constructors for <code>string</code>	113
18.7.10 Substrings	114
18.7.11 Map a string <code>char</code> by <code>char</code>	114
18.7.12 STL string functions	114
18.7.13 Construe <code>string</code> as set of <code>char</code>	116
18.7.14 Construe <code>string</code> as stream of <code>char</code>	116
18.7.15 Test if a string has given prefix or suffix	116
18.7.16 Trim off specified prefix or suffix or both	116
18.7.17 Strip characters from left, right, or both end of a string.	117
18.7.18 Justify string contents	117
18.8 Regexprs	117
19 Fibres and Schannels	118
19.1 Pipelines	118
19.1.1 Synchronouse pipelines	118
20 Asynchronous Events	119
21 Pre-emptive Threading	120
21.0.1 Json	120
21.0.2 Sqlite3	120

Chapter 1

Introduction

This reference is a guide to the Felix programming language. It is not the usual reference because Felix differs from other systems in that most of the grammar is part of the library, in user space. In principle then, separating the library from the core language is impossible: if anything the core language is defined by the compiler intermediate abstract machine, details of little interest to most programmers.

Furthermore even that characterisation is weak, because considerable functionality is actually embodied in the run time library. For example the compiler knows what a service request is, but it has no idea what an fthread is. It knows what a generator is, and it knows which generators perform yields, but it has no idea what an iterator is, despite the fact these are effectively a core language feature.

Therefore, our presentation cannot be complete, it cannot be precise, and it cannot replace actually reading the library code. Felix is a highly mutable language, major new features can often be introduced without touching the compiler.

For example a complete set of primitive types with their base operations cannot be presented, because, with a couple of exceptions there aren't any such type. Instead, most primitive types are introduced without knowledge of the compiler, by creating bindings to C++ in library code; these bindings defined the type name and some operations on the types in terms of C++.

Part I

Gross Structure

Chapter 2

Program structure

A Felix program consists of a nominated root parse unit and the transitive closure of units with respect to inclusion.

The behaviour of this system consists of the action of the initialisation code in each unit, performed in sequence within a given unit, with the order of action between units unspecified.

2.1 Parse Unit

A parse unit is a file augmented by prefixing specified import files to the front. These consist of a suite of grammar files defining the syntax and other files defining macros.

By convention syntax files have the extension `.fsyn`, and other import files have the extension `.flxh`.

With this augmentation all parse units in a program are independently parsed to produce an list of statements represented as abstract syntax, denoted an AST (even though it is a list of trees, not a single tree).

2.2 AST

The program consists of the concatenation of the ASTs of each parse unit, resulting in a single AST, which is then translated to a C++ translation unit by the compiler.

2.3 Grammar

The Felix grammar is part of the library. It is notionally prefixed to each file to be processed prior to any import files to specify the syntax with which the file is to be parsed and translated to an AST.

The grammar uses an augmented BNF like syntax with parse actions specified in R5RS Scheme.

The resulting S-expressions are translated to an intermediate form and then into an internal AST structure.

The parser is a scannerless GLR parser with significant extensions.

2.4 Grammar syntax

Not written yet. Browse the [grammar directory](#) for examples.

Chapter 3

Modules

Every Felix program is encapsulated in a module with the name being a mangle of the basename of the root unit. The mangling replaces characters in the file-name with other characters so that the module name is a valid ISO C identifier.

3.1 Special procedure `flx_main`

A program module may contain at most one top level procedure with no arguments, exported as `flx_main`. After initialisation code suspends or terminates, this procedure is invoked if it exists. It is the analogue of `main` in C++ however it is rarely used: side-effects of the root unit initialisation code are typically used instead.

A simple example:

```
println "Init";
var i,o = mk_ioschannel_pair[int]();
write (o,42);

export proc flx_main()
{
    println$ "main " + (read i).str;
    println$ "done ..";
}

println$ "Init done";
```

produces output:

```
Init
main 42
done ..
Init done
```

Note that `flx_main` must be exported to ensure that an `extern "C"` symbol is created by the linker.

3.2 Libraries

In Felix a library is a root unit together with its transitive closure with respect to inclusion, which does not contain a top level exported `flx_main`.

A program unit can be augmented by a set of libraries which are then considered as if included, but without an include directive being present.

Chapter 4

Lexicology

All Felix files are considered to be UTF-8 encoded Unicode.

Felix uses a scannerless parser, there are no keywords.

4.1 Comments

There are lexical commenting methods for *.flx files. Comments are treated as white space separators. For example

```
println$ f/**/x; // parsed as f x not fx
```

The two forms of lexical comments are exclusive, once the parser is scanning one kind of comment the other is not recognised.

4.1.1 C++ comments

C++ style comments consist of // followed by all the characters up to and including the next newline character.

4.1.2 Nested C comments

C style comments consist of the lead in sequence /* followed by all the characters up to and including the balancing exit sequence */. These comments can span multiple lines and can be nested. When scanning comments lead in and exit sequences are recognised as such even in strings.

4.2 Layout

Felix treats code points 0 through 32 (space) as whitespace which may be used freely between symbols. Whitespace is significant in strings, however, and new-line is a terminator for C++ style comments.

4.3 File inclusion

There is (deliberately) no support in the Felix language for lexical (physical) file inclusion. Inclusions are processed at the AST level instead, allowing files to be parsed independently of other files. However command line switches can be used to prepend files or sets of files to the command input file, in particular the grammar and some standard macros are notionally inserted.

4.4 fdoc files

As well as *.flx files, the Felix language processor can directly process *.fdoc files using a limited subset of available fdoc commands.

fdoc files are processed slightly differently to *.flx files. The translator begins treating the file in comment mode, so all text is ignored up to a Felix leadin code.

4.4.1 Uncomments

A felix uncomment switches to processing lines as Felix program code. It consists of the line @felix, and is terminated by any line starting with @.

```
@title This is an fdoc.
@h1 Fdocs are documents.
They can contain code:
@felix
var x = 1;
@
Which defines a variable and
@felix
println$ x;
@
which prints it.
```


4.4.2 #line directive

Felix provides support for programs that generate Felix code by allowing C style **#line** directives. Such a directive consists of the characters **#line** at the start of a line, followed by whitespace, a decimal number indicating the line number in the original source, and optionally whitespace followed by a filename in double quotes.

If the filename is present the parser original source filename is set to it. The line number sets the line number, 1 origin, so that the next source line will be taken to be obtained from the original source file at that line number.

Felix provides two standard programs which make use of this facility: **flx_tangle** and **flx_iscr** both of which are literate programming tools which extract source code from mixed code and comments.

In the event of a compilation error, Felix will specify that the error occurred at a location in the original source file, as indicated by **#line** directives. An example:

```
#line 42 "anerror.fdoc"
var x = error;
```

If this program is processed by Felix the error on the second line will be reported as an error on line 42 of the file **anerror.fdoc**.

4.5 #! directive

If the first line of an ***.flx** file starts with **#!** then the line is ignored. This allows a file on a Unix system marked executable to specify its natural translator so that the file may be run directly as a program. On Linux you should use:

```
#!/env /usr/local/lib/felix/felix-latest/host/bin/flx
```

assuming you have a standard install and have linked **felix-latest** to a directory containing an installed version of Felix such as

%usr/local/lib/felix/felix-2016.05.25%.

This is the standard way to refer to the most recent version of Felix installed on Unix systems. Note the path name to the translator on Unix systems must be an absolute path for security reasons.

4.6 Identifiers

[Library Reference](#)

Felix has three kinds of basic identifiers, plain identifiers, which are an enhanced variant of standard C identifiers, TeX identifiers, which are encodings of mathematical symbols in the style of TeX, and some ascii-art character sequences normally use for punctuation or operators which are also recognised as names.

4.6.1 Plain Identifiers

A plain identifier starts with a letter or underscore, then consists of a sequence of letters, digits, dash (-), apostrophy ('), has no more than one apostrophy or dash in a row, except at the end no dash is allowed, and any number of apostrophies.

```
Ab_cd1  a' b-x
```

Identifiers starting with underscore are reserved for the implementation.

A letter may be any Unicode character designated for use in an identifier by the ISO C++ standard. In practice, all high bit set octets are allowed. Identifiers are uniquely identified by their sequence of ISO-10646 (Unicode) code points, alternate encodings of the same glyph are distinct.

4.6.2 TeX Identifiers

A TeX identifier starts with a slash and is followed by a sequence of letters.

Here is a partial table of [TeX Symbols](#) recognised by the grammar as identifiers with undefined semantics but pre-assigned kind and precedence.

4.7 Operator Identifiers

Felix allows some operators to be used as an identifier. For example you can write:

```
fun +: int * int -> int = "$1+$2";
```

to define addition on int in C. Symbols recognised by the parser such as + are usually mapped to functions with the same name as the operator.⁴

These operators are recognised as identifiers by the parser in positions where an identifier is expected:

```
+ - * / % ^ ~
\& \ \^
&= = += -= *= /= %= ^= <<= >>=
< > == != <= >= << >>
```

4.7.1 Special identifiers

The special string literal with a "n" or "N" prefix is a way to encode an arbitrary sequence of characters as an identifier in a context where the parser might interpret it otherwise. It can be used, for example, to define special characters as functions. For example:

```
typedef fun n"@" (T:TYPE) : TYPE => cptr[T];
```

4.8 Boolean Literals

There are two literals of type `bool`, namely `true` and `false`.

4.9 Integer Literals

Library Reference

An plain integer literal consists of a sequence of digits, optionally separated by underscores. Each separating underscore must be between digits.

A prefixed integer literal is a plain integer literal or a plain integer literal prefixed by a radix specifier. The radix specifier is a zero followed by one of the letters `bB` for binary radix, `oO` for octal radix, optionally one may use `dD` for decimal radix, although this is the default, and `xX` for hexadecimal radix.

An underscore is permitted after the prefix.

The radix is the one specified by the prefix or decimal by default.

The digits of an integer consist of those permitted by the radix: `01` for binary, `01234567` for octal, `0123456789` for decimal, `0123456789abcdefABCDEF` for hex.

Note there are no negative integer literals.

A type suffix may be added to the end of a prefixed integer to designate a literal of a particular integer type, it has the form of an upper or lower case letter or pair of letters usually combined with a prefix or suffix `u` or `U` to designate an unsigned variant of the type. The allowed lower case suffices are:

```
t s l ll
ut us u ul ull
tu su lu llu
i8 i16 i32 i64
u8 u16 u32 u64
p d j
zu pu du ju
uz up ud uj
```

In addition, one or more letters may be upper case, except that `lL` and `Ll` are not permitted.

There is a table of the types [Table 18.1 Felix Integer Types](#).

Note the suffices do not entirely agree with C.

4.10 Floating point literals

Library Reference

Floating point literals follow ISO C89, except that underscores are allowed between digits, and a digit is required both before and after the decimal point if it is present.

The mantissa may be decimal, or hex, a hex mantissa uses a leading `0x` or `0X` prefix optionally followed by an underscore.

The exponent may designate a power of 10 using `E` or `e`, or a power of 2, using `P` or `p`.

A suffix may be `F`, `f`, `D`, `d`, `L` or `l`, designating floating type, double precision floating type, or long double precision floating type.

```
123.4
123_456.78
12.6E-5L
0xAf.bE6f
12.7p35
```

There is a table of the operators [Table 18.5 Floating Point Operators](#).

4.11 String like literals

Library Reference

4.11.1 Standard string literals

Generally we follow Python here. Felix allows strings to be delimited by; single quotes `'`, double quotes `"`, triped single quotes `'''` or tripled double quotes `"""`.

The single quote forms must be on a single line.

The triple quoted forms may span lines, and include embedded newline characters.

The complete list of special escapes is shown in table [Table 4.1 String Escapes](#).

Table 4.1: String Escapes

Basic		
Escape	Name	Decimal Code
<code>\a</code>	ASCII Bell	7
<code>\b</code>	ASCII Backspace	8
<code>\t</code>	ASCII Tab	9
<code>\n</code>	ASCII New Line	10
<code>\r</code>	ASCII Vertical Tab	11
<code>\f</code>	ASCII Form Feed	12
<code>\r</code>	ASCII Carriage Return	13
<code>\'</code>	ASCII Single Quote	39
<code>\"</code>	ASCII Double Quote	34
<code>\\</code>	ASCII Backslash	92
Numeric		
<code>\d999</code>	Decimal encoding	
<code>\o777</code>	Octal encoding	
<code>\xFF</code>	Hex encoding	
<code>\uFFFF</code>	UTF-8 encoding	
<code>\UFFFFFFFF</code>	UTF-8 encoding	

4.11.2 Raw strings

A prefix `"r"` or `"R"` on a double quoted string or triple double quoted string suppresses escape processing. This is called a raw string literal.

NOTE: single quoted string cannot be used, because this would clash with the use of single quotes/apostrophies in identifiers.

4.11.3 Null terminated strings

A prefix of `"c"` or `"C"` specifies a C NTBS (Nul terminated byte string) be generated instead of a C++ string. Such a string has type `+char` rather than `string`.

4.11.4 Perl interpolation strings

A literal prefixed by `"q"` or `"Q"` is a Perl interpolation string. Such strings are actually functions. Each occurrence of `$(varname)` in the string is replaced at run time by the value `"str varname"`. The type of the variable must provide an overload of `"str"` which returns a C++ string for this to work.

```
var x = 1;
var y = 3.2;
println$ q"x=$(x), y=$(y)";
```

4.11.5 C format strings

A literal prefixed by a "f" or "F" is a C format string.

Such strings are actually functions.

The string contains code such as "C format specifiers.

```
var x = 1;
var y = 3.2;
println$ f"x=%03d, y=%4.1f, s=%S" (x,y,"Hello");
```

Variable field width specifiers "*" are not permitted.

The additional format specification is supported and requires a Felix string argument.

If `vsprintf` is available on the local platform it is used to provide an implementation which cannot overrun. If it is not, `vsprintf` is used instead with a 1000 character buffer.

The argument types and code types are fully checked for type safety. There are some tables of accepted codes: [Table 4.2 C format codes: integer](#), [?? ??](#), [Table 4.4 C format codes: floating](#), [Table 4.5 C format codes: other](#).

Please see a suitable reference to learn how to use C format codes.

Table 4.2: C format codes: integer

Code	Type	Radix
hhd	tiny	decimal
hhi	tiny	decimal
hho	utiny	octal
hhx	utiny	hex
hhX	utiny	HEX
hd	short	decimal
hi	short	decimal
hu	ushort	decimal
ho	ushort	octal
hx	ushort	hex
hX	ushort	HEX
d	int	decimal
i	int	decimal
u	uint	decimal
o	uint	octal
x	uint	hex
X	uint	HEX
ld	long	decimal
li	long	decimal
lu	ulong	decimal
lo	ulong	octal
lx	ulong	hex
lX	ulong	HEX
lld	vlong	decimal
lli	vlong	decimal
llu	uvlong	decimal
llo	uvlong	octal
llx	uvlong	hex
llX	uvlong	HEX

Table 4.3: C format codes: special integer

Code	Type	Radix
zd	ssize	decimal
zi	ssize	decimal
zu	size	decimal
zo	size	octal
zx	size	hex
zX	size	HEX
jd	intmax	decimal
ji	intmax	decimal
ju	uintmax	decimal
jo	uintmax	octal
jx	uintmax	hex
jX	uintmax	HEX
td	ptrdiff	decimal
ti	ptrdiff	decimal
tu	uptrdiff	decimal
to	uptrdiff	octal
tx	uptrdiff	hex
tX	uptrdiff	HEX

Table 4.4: C format codes: floating

Code	Type	format
e	double	scientific
E	double	SCIENTIFIC
f	double	fixed
F	double	FIXED
g	double	general
G	double	GENERAL
a	double	hex
A	double	HEX
Le	ldouble	scientific
LE	ldouble	SCIENTIFIC
Lf	ldouble	fixed
LF	ldouble	FIXED
Lg	ldouble	general
LG	ldouble	GENERAL
La	ldouble	hex
LA	ldouble	HEX

Table 4.5: C format codes: other

Code	Type	
c	int (prints char)	
S	string	
s	&char	
p	address	hex
P	address	HEX

Chapter 5

Macro processing

[Library Syntax Reference](#)

[Compiler Semantics Reference](#)

5.1 Include Directive

An include directive has the syntax:

```
include "filename";  
include "dirname/filename";  
include "./filename";
```

where the filename is a Unix relative filename, may not have an extension, and may not begin with or contain `..` (two dots).

If the filename begins with `./` then the balance of the name is relative, a sibling of the including file, otherwise the name is searched for on an include path.

In either case, a search succeeds when it finds a file with the appropriate base path in the search directory with extension `.flx` or `.fdoc`. If both files exist the most recently changed one is used. If the time stamps are the same the choice is unspecified.

5.2 Macro val

The macro `val` statement is used to specify an identifier should be replaced by the defining expression wherever it occurs in an expression, type expression, or pattern.

```
macro val WIN32 = true;
macro val hitchhiker;
macro val a,b,c = 1,2,3;
```

5.3 Macro for

This statement allows a list of statements to be repeated with a sequence of replacements.

```
forall name in 1,2,3 do
  println$ name;
done
```

5.4 Constant folding and conditional compilation

[Compiler Semantics Reference](#)

Felix provides two core kinds of constant folding: folding of arithmetic, boolean, and string values, and deletion of code, either statements or expressions, which would become unreachable due to certain value of conditionals.

Basic operations on integer literals, namely addition, subtraction, negation, multiplication, division, and remainder are folded.

Strings are concatenated.

Boolean and, or, exclusive or, and negation, are evaluated.

False branches of if/then/else/endif expression and match expressions are eliminated.

False branches of if/do/elif/else/done are also eliminated.

By this mechanism of constant folding and elimination, Felix provides conditional compilation without the need for special constructions.

Part II

Lookup

Chapter 6

Classes

Syntax

6.1 Class Statement

The top level Felix module can contain submodules which are specified by a non-polymorphic class statement:

```
class classname { ... }
```

6.1.1 Qualified Names

The effect is to produce a qualified name to be used outside the class:

```
class classname { proc f () {} }  
classname::f ();
```

6.1.2 Nested Classes

Classes may be nested.

```
class A {  
  class B {  
    proc f () {}  
    f();  
  }  
  B::f();  
}  
A::B::f ();
```

6.1.3 Private definitions

A class may contain private definitions, if a symbol is marked private it is only visible in the scope class in which it is defined, including any nested classes:

```
class A {
  private proc f () {}
  class B {
    f(); // visible inside A
  }
  f(); // visible inside A
}
// A::f () fails, f is not visible outside A
```

6.1.4 Single File Rule

A class must be specified within a single file.

6.1.5 Completeness Rule

Classes are not extensible, a definition of a class with the same name in the same scope is not permitted.

6.1.6 Setwise Lookup

The body of a class forms a nested scope. Within a class all symbols defined in the class are visible, along with all those visible in the enclosing context.

```
var x = "Hello";
class A {
  proc f() { g(); } // g visible before defined
  proc g() { x = x + 1; } // use uninitialised variable!
  var x = 1;
}
```

Beware using uninitialised variables! The procedure `g` above uses `A::x` before it is initialised.

6.1.7 Top level module alias

The reserved name `root` may be used as a prefix for the top level module:

```
var x = 1;
class A { var x = root::x; }
```

6.2 Polymorphic Classes

6.2.1 Parametric Polymorphism

A class may be specified with one or more type variables. Such a class is said to be a polymorphic class.

```
class MakePair[T,U] {
  fun fwd_pair (x:T) (y:U) => x,y;
  fun rev_pair (x:T) (y:U) => x,y;
}
```

6.2.2 No Variables

Polymorphic classes may not directly contain variables, all members must be function or type definitions.

6.2.3 Qualified Names

Entities from a class can be specified from outside using a qualified name in which the class name is followed a square bracketed list of types instantiating the corresponding type variables:

```
var f = MakePair[int,string]::fwd_pair 42 "Hello";
var r = MakePair[int,string]::rev_pair 42 "Hello";
```

However one or more or even all the types can be omitted from the right end of the list if they can be deduced by overload resolution.

The square brackets are optional if they enclose an empty list.

```
f = MakePair[int,string]::fwd_pair 42 "Hello";
f = MakePair[int]::fwd_pair 42 "Hello";
f = MakePair[]::fwd_pair 42 "Hello";
f = MakePair::fwd_pair 42 "Hello";
```

It is also permitted to move the instance types across qualification boundaries:

```
f = MakePair[int,string]::fwd_pair 42 "Hello";
```

although this practice is not recommended.

From the outside, a class type variables are viewed as existential quantification. From inside however, the variable names are fixed types which happen to be unknown, that is they're to be considered as existentials.

This means they cannot be specified explicitly or implicitly inside the class:

```
class A[T] {
  fun f(x:T) => x,x;
  fun g(y:T) => f y; // correct
  // fun h(y:T) => f[T] y; // wrong
}
```

From inside the class the function `f` above is monomorphic, not polymorphic. Although `T` is not known, it is a fixed, invariant type.

6.2.4 Polymorphic Members

Functional members of a class may be polymorphic. This is independent of the class type parameters.

```
class A[T] {
  fun f[U] (x:T, y:U) => x,y;
  fun g(a:T) => f[T * T] (a,a);
}
```

In this case the function `f` has its own personal type variable `U` which is set in the call in `g` to `T * T` because its argument is a pair of `a` which has that type.

6.3 Virtuals and instances

A polymorphic class may contain functions or procedures marked `virtual`. In this case a definition is optional.

```
class A[T] {
  // non virtual function
  fun f(x:T) => x,x;

  // virtual function with definition
  virtual fun g (x:T) => f x;

  // virtual function without definition
  virtual fun h : T -> T * T;
}
```

If a virtual function without a definition from a class is used, it must be defined for the types for which it is used. This is done in an instance statement:


```

var a = 1; // int
var x = A[int]::h a; // h used for T=int

// instance defining h for int
instance A[int] {
  fun h(a:int) => a + 1, a - 1;
}

```

An instance can be defined anywhere in a non-functional scope provided the class being instantiated is visible.

In this case symbols in the instance definition are bound the context of the instance scope and its enclosing scope in the usual way.

It is not possible to directly access the definitions in an instance from outside the instance. Instead all access is diverted through the top level class being instantiated. Symbols are bound to the top level class member first to fix the type variables, then a matching instance is sought.

If there is no matching instance, the program fails with a diagnostic.

If there is more than one matching instance, the most specialised instance is used. If there is no most specialised instance, the use of the class member is ambiguous and the program fails with a diagnostic.

An instance must be not less specialised than the class it instantiated (that is, equally specialised or more specialised).

Instance specialisation is judged by the polymorphic subtyping rule which is implemented using unification algorithm.

A polymorphic type $S[T]$ parametrised by a type variable T is more specialised than a polymorphic type $A[U]$ is there if T may be replaced by a type expression containing U the result of which equals $S[T]$.

If S has more than one type variable, substitutions for each of them must be found. If A has more than one type variable, the substitutions involve all of these variables.

A specialisation $S1$ of A is strictly more specialised than a specialisation $S2$ of A if $S1$ is also strictly a specialisation of $S2$.

6.3.1 Default Definition

If a virtual function has a definition, it is called a *default definition*. On a use of a function with a default definition, if no matching instance is found, the default definition is specialised and used instead. Note that default definitions do not resolve ambiguity from overlapping instances.

6.3.2 Matching polymorphic functions

If a virtual function is polymorphic, the personal type variables of the function must not be specialised in an instance. The class type variables are resolved independently of the function type variables.

You may think of this as if the class type variables are resolved first by finding a uniquely matching instance, and then the function type variables are resolved in a second step (although in fact there is no coupling between the resolution).

6.4 Classes as Categories

A class may be thought of in a category theoretic sense.

A base category consists of objects which consists of a finite set of base types and all combinations thereof formed by the available set of type combinators such as tuples, records, function types, etc.

The arrows of this category consist of all the functions explicitly defined on these types, and all compositions thereof. This includes the identity functions implicitly defined by copying.

This is the category generated by the graph consisting of the defined functions, where paths in the graph are (reverse) function compositions. This is called the free category generated by the graph.

A class in the context of a base category generates an extension to that category by throwing in some additional types and arrows. The type variables are added to the set of base types, so that the set of combinations is extended. The functions are added to the set of digraph edges of the base generating graph, to add additional arrows.

This view of the role of a class is vital to understand semantic rules which correspond to the notion of a category generated by a graph with relations. The relations form a constraint. In category theory, the relations are generally equations relating the arrows which specify that certain function compositions are equal to others.

The freely generated category is sometimes called an initial algebra. When constraints are added a new category is formed by collapsing some sequences of arrows to a single arrow. There is a mapping called an epi-morphism which takes each arrow from the freely generated category to the target so that two distinct composites may map to the same arrow in the target.

Conversely, there is a reverse mapping from the arrows of the target category to sets of arrows of the freely generated one, forming another category called a quotient category. These two mappings are functions and together form an adjunction.

The purpose of this explanation is not merely for your entertainment. In most programming classes are intended to be constrained, that is, the instances are intended to have a certain behaviour.

Consider for example:

```
class Addable [T] {  
  virtual fun add: T * T -> T;  
}
```

Now consider the following instances:

```
instance Addable[uint] {  
  fun add (x:uint, y:uint) => x + y;  
}  
  
instance Addable[int] {  
  fun add (x:int, y:int) => x + y;  
}  
  
instance Addable[double] {  
  fun add (x:double, y:double) => x + y;  
}
```

These instances are good according to the specification, however the addition of `int` and `double` is unspecified because we may have overflow. Furthermore one may get a big surprise adding floating point representations of reals: if you add a big float to a small one the small one may be so small that the result is equal to the big one.

Basic laws of arithmetic are not obeyed by floating representations, in particular addition of floats is not associative!

It is usual to specify requirements in comments and the programmer must carefully check that instances obey the constraints specified for the class in these comments.

Felix, however, can do a bit better.

6.5 Axioms, Lemmas and Theorems

Felix allows some semantic constraints on class instances to be specified with explicit axioms. For example:

```

class Addable [T] {
  virtual fun add: T * T -> T;
  axiom associative (x:T, y:T, z:T):
    add (add (x,y), z) == add (x, add (y, z))
  ;
}

```

The axiom documents in a formal language the requirement that the addition operator defined in an instance must be associative. An axiom is similar to an ordinary boolean function which tests whether some condition is met or not. By applying an axiom to particular values we can check for non-conformance of instances.

However, in a categorical sense, an equational axiom plays precisely the role of a relation in the formation of a category with generators and relations. It is a vital part of practical specification of semantics.

We should note that not all constraints can be expressed as axioms in Felix. In particular since Felix only provides first order polymorphism, only equational predicates in Horn form can be used, that is, all the quantifiers must be (implicitly or explicitly) on the left of the formula. Interior quantifiers require second order polymorphism.

Note also that like most programming languages we use constructive mathematics which constrains the role of existentials to calculations. That is, it is not acceptable to assert that something exists because if it did not a contradiction would be derived. Indirect proof is not allowed in constructive mathematics.

Instead, one must prove something exists by actually constructing one! So for example given $a < b$ we know there exists a number x such that $a < x < b$. A proof of this by asserting that if no such x existed, then we would have a contradiction, is not allowed in constructive mathematics. Instead the proof is simply given by $x = (a + b)/2$. And of course .. the assertion is false for many types such as integers!

6.5.1 Lemmas and Theorems

Lemmas and theorems play the same role as axioms. The idea, however, is that lemmas and theorems can be derived from the axioms. A lemma is a simple rule which a good automatic theorem prover could derive, and which seems obvious to a human.

A theorem is a more difficult rule which would require a proof assistant with hints to derive a proof.

6.5.2 Reductions

A reduction is also an axiom, but it has an additional property. Instead of an equation, reductions use a directed equality:

```
reduce revrev[T] (x:list[T]):  
  rev (rev x) => x  
;
```

This reduction asserts that if you reverse a list twice you end up back where you started. But it does more: it give the compiler a hint that it is allowed to replace an expression which reverse a list twice with the list, removing the two reversing operations.

This is a particularly interesting example of the general rule that all theorems are nothing more than optimisations, in this case literally allowing the compiler to optimise a program. Note that it is only a hint!

Chapter 7

General lookup

By default Felix looks up symbols in nested scopes, starting with all symbols in the current scope and proceeding through its containing scope outwards until the outermost scope is reached.

Symbols are visible in the whole of a scope, both before and after their introduction.

A symbol lookup may properly find either a single non-function symbol, which is final, or a set of function symbols.

If the kind of symbol being sought is a function symbol, overload resolution is performed on the set of function signatures found in a scope. If a best match is found, that is final. If no match is found the search continues in the next outermost scope.

All other cases are in error.

Chapter 8

Overload Resolution

Blah.

Chapter 9

Lookup control directives

9.1 Open directive

The simple `open` directive may be used to make the symbols defined in a class visible in the scope containing the `open` directive.

```
class X { var x = 1; }  
open X;  
println$ x;
```

Names made visible by an `open` directive live in a weak scope under the current scope. Names in the weak scope may be hidden by definitions in the current scope without error.

```
class X { var x = 1; }  
open X;  
var x = 2;  
println$ x; // prints 2
```

The `open` directive is not transitive. The names it makes visible are only visible in the scope in which the `open` directive is written.

9.2 Inherit directive

The `inherit` directive allows all of the public symbols of a class to be included in another scope as if they were defined in that scope. This means such names inherited into a class can be accessed by qualification with the inheriting class name, and will be visible if that class is opened.

Inheriting is transitive.

If a name is inherited it will clash with a local definition.

```
class A { var a = 1; }
class B { inherit A; }
println$ B::a;
```

9.3 Rename directive

This directive is can be used to inherit a single symbol into a scope, possibly with a new name, and also to add an alias for a name in the current scope.

When applied to a function name all functions with that name are renamed.

```
class A {
  var a = 1;
  proc f() {}
  proc f(x:int) {}
}

class B {
  rename a = A::a;
  rename fun f = A::f;
}
```

The new name injected by a rename may be polymorphic:

```
class A { proc f[T] () {} }
class B { rename g[T] = A::f[T]; }
```

9.4 Use directive

This is a short form of the rename directive:

```
class A { var a = 1; }
class B { use A::a; use b = A::a; }
```

It cannot be applied to functions. The first form is equivalent to

```
use a = A::a;
```

Unlike the rename directive the new name cannot be polymorphic and is limited to a simple identifier.

9.5 Export directives

The `export` directives make the exported symbol a root of the symbol graph.

The functional `export` and forces it to be place in the generated code as an `extern "C"` symbol with the given name:

```
export fun f of (int) as "myf";  
export cfun f of (int) as "myf";  
export proc f of (int) as "myf";  
export cproc f of (int) as "myf";
```

Functions are exported by generating a wrapper around the Felix function. If the function is exported as `fun` or `proc` the C function generated requires a pointer to the thread frame as the first argument, if the `cfun` or `cproc` forms are used, the wrapper will not require the thread frame.

In the latter case, the Felix function must not require the thread frame.

A type may also be exported:

```
export type ( mystruct ) as "MyStruct";
```

This causes a C typedef to be emitted making the name `MyStruct` an alias to the Felix type. This is useful because Felix types can have unpredictable mangled names.

The word `export` optionally followed by a string may also be used as a prefix for any Felix function, generator, or procedure definition. If the string is omitted is taken as the symbol name. The effect is the same as if an export statement has been written.

Part III

Type System

Chapter 10

Type constructors

Syntax

10.1 typedef

The typedef statement is used to define an alias for a type. It does not create a new type.

```
typedef Int = int;
```

10.2 Tuples

Tuple types are well known: a tuple is just a Cartesian Product with components identified by position, starting at 0. The n-ary type combinator is infix `*` and the n-ary value constructor is infix `,:`

```
val tup : int * string * double = 1, "Hello", 4.2;
```

The 0-ary tuple type is denoted `1` or `unit` with sole value `()`:

```
val u : unit = ();
```

The 1-ary tuple of type `T` component value `v` is identified with the type `T` and has value `v`.

The individual components of a tuple may be accessed by a projection function. Felix uses an integer literal to denote this function.

```
var x = 1, "Hello";  
assert 0 x == 1; assert x.0 == 1;  
assert 1 x == "Hello"; assert x.1 == "Hello";
```

[There should be a way to name this function without application to a tuple!]

A pointer to a tuple is also in itself a tuple, namely the tuple of pointers to the individual components. This means if a tuple is addressable, so are the components.

```
var x = 1, "Hello";
val px = &x;
val pi = px.0; pi <-42;
val ps = px.1; ps <- "World";
assert x.0 == 42;
assert x.1 == "World";
```

In particular note:

```
var x = 1, "Hello";
&x.0 <- 42;
```

because the precedences make the grouping $(\&x).0$.

You cannot take the address of a tuple component because a projection of a value is a value.

Assignment to components of tuples stored in variables is supported but only to one level, for general access you must take a pointer and use the store-at-address operator $<-$.

10.2.1 Tuple projections

The projections of a tuple can also be written in an expanded form so that they may stand alone as functions:

```
var first = proj 0 of (int * string);
var a = 1, "Hello";
var one = a . first;
var two = a . proj 1 of (int * string);
```

10.3 Records

A record is similar to a tuple except the components are named and considered unordered up to duplication.

10.3.1 Plain Record

A plain record is one without duplicate fields. A plain record type is one without duplicate fields or a row variable. A record is constructed using a parenthesis en-

closed list of comma separated field assignments. An empty record is equivalent to an empty tuple.

```
typedef xy = (x:int, y:int);
var r : xy = (x=1,y=2);
```

10.3.2 Record projections

A component of a record may be accessed with a function called a record value projection, it is denoted by the name of the field.

```
var r (x=1,y=2);
println$ x r, r.y;
```

Record value projections can also be used as stand-alone functions. For example:

```
var r1 = list ((x=1,y=11),(x=2,y=22));
var xs = map (x of (x:int, y:int)) r1;
println$ xs; // list (1,2)
```

Records also have pointer projections, overloaded with the value projections: if the name of a field is applied to a pointer to a record, a pointer to the named component field is returned. This allows assignment and other mutators to be applied to record components.

```
var r =(x=1,y=2);
var px = &r.x; // means (&r).x
px <- 42;
r.&y <- 23;
println$ r.x, r.y; // (42,23)
```

Record pointer projects can also be used as stand-alone functions:

```
var prjx = x of (xy);
var prjpx = x of (&xy);
```

10.3.3 General record

Records may have duplicate fields. In this case, reading from left to right in a record literal, a duplicate field is hidden by a previous field of the same name, in a push down stack like fashion.

```
var r = (x=1,y=2,x="Hello");
println$ r._strr, r.x;
// ((x=1,x='Hello',y=2), 1)
```

Note that the generic function `_strr` displays the whole of the record including duplicate fields. However projections only find the left-most field.

10.3.4 Adding fields

Fields can be added to an existing record to construct a new record:

```
var r = (x=1,y=2);
var r2 = (a="one",b="two",x="newx" | r);
println$ r2._strr,r2,x;
// ((a='one',b='two',x='newx',x=1,y=2), newx)
```

Again, leftmost fields hide rightmost ones. You can also add two records with infix +:

```
var r = (a=1) + (b=2) + (a="hello");
println$ r._strr, r.a.str; // ((a=1,a='hello',b=2), 1)
```

The leftmost field with a given name dominates. Record addition by + is only applied if a user defined addition is not found for the argument types.

Currently, addition of fields of two records of the same type is not supported: it is likely the user intended to add corresponding field values rather than hide the fields in the right argument with those on the left.

10.3.5 Row Polymorphism

Felix provides a special record type called a *polyrecord* which supports row polymorphism with scoped labels in the style of Daan Leijen. The article is [here](#).

This allows a generic function to be written which accepts an argument which is or contains a value of a record type with more fields than required. Unlike subtyping, the extra fields, whilst inaccessible, are not lost and can be returned by the function. For example:

```
val circle = (x=0.0,y=0.0,r=1.0);
val square = (x=0.0,y=0.0,w=1.0,h=1.0);

fun move[T] (dx:double, dy:double) (shape: (x:double, y:double | T)) =>
  (x=shape.x+dx, y=shape.y+dy | (shape without x y))
;

var inc = 1.0,1.0;
println$ (move inc circle)._strr, (move inc square)._strr;
```

without operator

The `without` operator can be used to return a record with some fields removed. It works on values of record and polyrecord type. Note that because Felix uses scoped fields once a field is removed, the previous value of that field is exposed

if it exists, and can also be removed. This means it is correct and sometimes necessary to list a field more than once when using the `without` operator.

10.3.6 Interfaces

An interface is a special notation for a record type all of whose fields are functions or procedures.

```
interface fred {
  f: int -> int;
  g: int -> 0; // procedure
}

// equivalent to
typedef fred = (f: int -> int, g: int -> 0);
```

The primary use is for specifying the type of a Java like object.

10.4 Structs

A struct is a a nominally typed record, that is, it must be defined, and each definition specifies a distinct type.

```
struct S { x:int; y:int; };
var s : S = S (1,2);
println$ s.x,s.y;
```

A struct value can be constructed using the structure name as a function and passing a tuple of values corresponding by position to the fields of the struct.

A struct constructor can be used a first class function.

The field names are projection functions and can be applied to a struct value to extract the nominated component, or applied to a pointer to a struct to find a pointer to the nominated component.

The notation (may be changed soon)

```
var prjx = x of (S);
var prjpx = x of (&S);
```

can be used to refer to a projection in isolation, and a pointer projection in isolation, that is, as unapplied first class functions.

A struct may also contain function and procedure definitions:


```

struct A {
  x:int;
  y:int;
  fun get2x => 2 * self.x;
  fun get2y () => 2 * self.y;
  proc diag (d:int) { self.x <- d; self.y <-d; }
};

```

These functions are precisely equivalent to:

```

fun get2x (self:A) => 2 * self.x;
proc diag (self: &A) (d:int) { self.x <-d; self.y <-d; }

```

Note that for a function `self` is a value, for a procedure `@{self` is a pointer.

Because of these definitions, we can form object closures over a struct:

```

var a = A(1,2);
var g2y = a. get2y;
var di = a . diag;

```

Note we can't form a closure for `get2x` without an explicit wrapper, i.e. eta-expansion.

10.5 Sums

Sum types are the dual of tuples. They represent a sequence of possible cases, potentially with arguments. Case indices are 0 origin. Sum variables are decoded with a match which may also extract an argument value:

```

typedef num = int + long + double;
var x = (case 1 of num) 53L;
println$
  match x with
  | case 0 (i) => "int " + i.str
  | case 1 (l) => "long" + l.str
  | case 2 (d) => "double " + d.str
  endmatch
;

```

10.5.1 Unit sum

There is a family of special sum types equivalent to:

```
2 = 1 + 1
3 = 1 + 1 + 1
4 = 1 + 1 + 1
```

Recall type 1, or unit, is the type of the empty tuple. The type 2 is also known as bool, and represents two cases where `false` is an alias for `@{case 0 of 2}` and `@{true}` is an alias for `case 1 of 2`.

The type 0 or void, is the type of no values.

These types are called unit sums because they're a sum of a certain number of units.

Note carefully that:

```
x + (y + z), (x + y) + z, x + y + z
```

are three distinct types because operator `+` is not associative.

10.6 union

A union is the dual of a struct. It is a nominally typed version of a sum. Here for example is a list of integers:

```
union intlist {
  iEmpty ;
  iCons of int * intlist;
};
```

This alternative syntax is more commonly used and comes from ML family:

```
union intlist =
  | iEmpty
  | iCons of int * intlist
;
```

The fields of a union type are injections or type constructors. In effect they cast their argument to the type of the union, thus unifying heterogenous types into a single type.

Pattern matches are used to decode unions.

```

var x = iEmpty;
x = iCons (1, x);
x = iCons (2, x); // list of two integers

fun istr (x:intlist) =>
  match x with
  | #iEmpty => "end"
  | iCons (i, tail) => i.str + "," + istr tail
  endmatch
;

```

The first variant represents an empty list. The second variant says that a pair consisting of an int and a list can be considered as a list by applying the type constructor iCons to it.

Unlike product types, a sum may directly contain itself. This is because sum types are represented by pointers.

10.6.1 enum

A restricted kind of union, being a nominally typed version of a unit sum.

```

enum colour { red, green, blue }; // same as
enum colour = red, green, blue; // same as
union colour = red | green | blue;

```

The tag value of an enum can be set:

```

enum wsize = w8=8, w16=16, w32=32, w64=64;

```

10.6.2 caseno operator

The caseno operator can find the tag value of any sum type, the anonymous sum, union, enum or variant as an integer.

```

assert caseno w16 == 16;
assert caseno (case 1 of 2) == 1;

```

10.7 variant

Variants the sum type which are the dual of records. They used named injections like unions but are structurally typed.

```

typedef vars = union { Int of int ; Float of float; };

```

10.8 Array

Felix has various kinds of array. The term is abused and sometimes refers to the abstract concept, and sometimes the statically typed fixed length array described here.

An array is nothing but a tuple all of whose elements have the same type. It is convenient to use an exponential operator with a unit sum index to provide a compact notation:

```
int ^ 3 // array of 3 integers equivalent to
int * int * int
```

Therefore the value:

```
var a3 = 1,2,3;
```

is, in fact, an array. As for tuples an integer literal applied to an array value returns a component, however for arrays, an expression may be used as well:

```
var i = 1;
var y = a3 . i;
var z = a3 . proj i of (int^3);
```

The last form is equivalent to

```
var z = a .
  match i with
  | 0 => proj 0 of (int^3)
  | 1 => proj 1 of (int^3)
  | 2 => proj 2 of (int^3)
  | _ => throw error
endmatch
;
```

in other words there is a run time array bounds check equivalent to a match failure. Note that of course the actual generated code is optimised!

A run time check can be avoided by using the correct type of index:

```
var i = case 1 of 3;
var z = a . i; // no run time check
```

10.8.1 Multi-arrays

Whilst we introduced the exponential notation

```
B ^ J
```

as a mere shorthand, where J is a unit sum, in fact Felix allows the index to be any compact linear type.

A compact linear type is any combination of sums, products, and exponentials of unit sums. The type

```
3 * 4 * 5
```

for example is compact linear, and therefore Felix allows the array type

```
typedef matrix = double ^ (3 * 4 * 5)
```

Although this looks like the type

```
typedef array3 = double ^ 3 ^ 4 ^ 5
```

as suggested by the usual index laws, the latter is an array size 5 of arrays size 4 of arrays size 3 which can be used like:

```
var a : array3;  
var z = a . case 1 of 5 . case 1 of 4 . case 1 of 3;
```

where you will note that the projections are applied in the reverse order to the indices. On the other hand to use the first form we have instead:

```
var m : matrix;  
var z = a . (case 1 of 3, case 1 of 4, case 1 of 5);
```

The exponent here is a value of a compact linear type. It is a single tuple value! It is called a multi-index when applied to an array.

The advantage of this type is that there is an obvious encoding of the values shown in this psuedo code:

```
i * 3 * 4 + j * 3 + k
```

which is nothing more than a positional number notation where the base varies with position. That encoding clearly associates with the compact linear value as integer in the range 0 to 59, or, alternatively, an value of type 60. In other words the type is linear and compact.

Since clearly, given an integer in range 0 through 59 and this type we can decode the integer into a tuple, being the positional representation of the integer in this weird coding scheme, the type is clearly isomorphic to the subrange of integer.

Therefore Felix allows you to coerce an integer to a compact linear type with a run time check, and convert a compact linear type to an integer or a unitsum:

```
var i : int = ((case 1 of 3, case 1 of 4, case 1 of 5) :>> int);  
var j : 60 = ((case 1 of 3, case 1 of 4, case 1 of 5) :>> 60);  
var clt : 3 * 4 * 5 = (16 :>> 3 * 4 * 5);
```

Because we can do this we can now write a loop over a matrix with a single iterator:

```
for i in 60 do  
  println$ m . (i :>> 3 * 4 * 5);  
done
```

This is an advanced topic which will require an extensive explanation beyond the scope of this summary. However we will not that this facility provides a very high level feature known as polyadic array programming. In short this means that one may write routines which work on matrices of arbitrary dimension. You can of course do this in C by doing your own index calculations at run time and using casts, however Felix does these calculations for you based on the type so they're always correct.

Chapter 11

Meta-typing

Felix provides some facilities for meta-typing.

11.0.1 typedef fun

The notation

```
typedef fun diag (T:TYPE):TYPE=> T * T;  
var x: diag int = 1,2;
```

defines a type function (or functor). Given a type T, this function returns the type for a pair of T's. The identifier TYPE denotes the kind which is a category of all types.

Applications of type functions must be resolved during binding, since the result may influence overloading.

11.1 typematch

Felix has a facility to inspect and decode types at compile time.

```
typedef T = int * long;  
var x:  
  typematch T with  
  | A * B => A  
  | _ => int  
endmatch  
= 1  
;
```

As with type functions, type matches must be resolved during binding. If a type match fails, an error is issued and compilation halted. The wildcard type pattern `_` matches any type.

The real power of the type match comes when combined with a type function:

```
typedef fun promote (T:TYPE): TYPE =>
  typematch T with
  | #tiny => int
  | #short => int
  | #int => int
  | #long => long
  | #vlong => vlong
  endmatch
;
```

This functor does integral promotions of signed integer types corresponding to ISO C rules.

11.2 type sets

TBD

Chapter 12

Abstract types

Felix provides abstract types as demonstrated in this example.

```
class Rat {  
  type rat = new (num:int, den:int);  
  ctor rat (x:int, y:int) =>  
    let d = gcd (x,y) in  
    _make_rat (num=x/d, den=y/d)  
  ;  
  
  fun + (a:rat, b:rat) =>  
    let a = _repr_ a in  
    let b = _repr_ b in  
    _make_rat (  
      a.num * b.den + b.num * a.den,  
      a.den * b.den  
    )  
  ;  
}
```

Here, the abstract type `rat` is represented by a record of two integers, `num` and `den`, but this type is hidden.

Inside the class `Rat` the operator `_make_rat` casts the implementation value to an abstract value, and the operator `_repr_` casts the abstract value to its implementation.

These casts cannot be used outside the class, thereby hiding the implementation outside the class.

Chapter 13

Polymorphism

TBD

Part IV

Definitions

Chapter 14

Variable Definitions

Syntax

A definition is a statement which defines a name, but does not cause any observable behavior, or, a class statement, or, a `var` or `val` statement. The latter two exceptions define a name but may also have associated behaviour.

14.1 The `var` statement

The `var` statement is used to introduce a variable name and potential executable behaviour. It has one of three basic forms:

```
var x : int = 1;
var y : int;
var z = 1;
```

The first form specifies the type and an initialising expression which must be of the specified type.

The second form specifies a variable of the given type without an explicit initialiser, however the variable will be initialised anyhow with the default constructor for the underlying C++ type, although that constructor may be trivial.

The third form does not specify the type, it will be deduced from the initialiser.

If the initialiser has observable behaviour it will be observed if at all, when control passes through the variable statement.

If the variable introduced by the `var` statement is not used, the variable and its initialiser will be elided and any observable behaviour will be lost.

To be used means to have its address taken in a used expression, to occur in a used expression. A used expression is one which initialises a used variable, or,

is an argument to function or generator in a used expression, or an argument to a procedure through which control passes.

In other words, the variable is used if the behaviour of the program appears to depend on its value or its address.

The library procedure `C_hack::ignore` ensures the compiler believes a variable is used:

```
var x = expr;
C_hack::ignore x;
```

so that any side effects of `expr` will be seen. In general the argument to any primitive function, generator or procedure will be considered used if its containing entity is also considered used. In general this means there is a possible execution path from a root procedure of the program.

A variable may have its address taken:

```
var x = 1;
var px = &x;
```

it may be assigned a new value directly or indirectly:

```
x = 2;
px <- 3;
*px = 4;
```

A variable is said to name an object, not a value. This basically means it is associated with the address of a typed storage location.

14.1.1 Multiple variables

Multiple variables can be defined at once:

```
var m = 1,2;
var a,b = 1,2;
var c,d = m;
```

With this syntax, no type annotation may be given.

14.2 The `val` statement.

A `val` statement defines a name for an expression.

```
val x : int = 1;
val z = 1;
```

The value associated with a `val` symbol may be computed at any time between its definition and its use, and may differ between uses, if the initialising expression depends on variable state, such as a variable or call to a generator.

It is not an error to create such a dependence since either the value may, in fact, not change, or the change may not be significant.

Nevertheless the user must be warned to take care with the indeterminate evaluation time and use a `var` when there is any doubt.

Since a `val` simply names an expression, it is associated with a value not an object and cannot be addressed or assigned to. However this does NOT mean its value cannot change:

```
for var i in 0 upto 9 do
  val x = i;
  println$ x;
done
```

In this example, `x` isn't mutable but it does take on all the values 0 to 9 in succession. This is just a most obvious case: a less obvious one:

```
var i = 0;
val x = i;
println$ x;
++i;
println$ x;
```

which is clearly just an expansion of the the first two iteration of the previously given for loop. However in this case there is no assurance `x` will change after `i` is incremented because the compiler is free to replace any `val` definition with a `var` definition.

14.2.1 Multiple values

Multipls values can be defined at once:

```
val m = 1,2;
val a,b = 1,2;
val c,d = m;
```

With this syntax, no type annotation may be given.

Chapter 15

Functions

Syntax

15.1 Functions

A felix function definition takes one of three basic forms:

```
fun f (x:int) = { var y = x + x; return y + 1; }  
fun g (x:int) => x + x + 1;  
fun h : int -> int = | x => x + x + 1;
```

The first form is the most general, the body of the function contains executable statements and the result is returned by a return statement.

The second form is equivalent to a function in the first form whose body returns the RHS expression.

The third form specifies the function type then the body of a pattern match. It is equivalent to

```
fun h (a:int) = { return match a with | x => x + x + 1 endmatch; }
```

The first two forms also allow the return type to be specified:

```
fun f (x:int) : int = { var y = x + x; return y + 1; }  
fun g (x:int) :int => x + x + 1;
```

Functions may not have side effects.

All these function have a type:

```
D -> C
```

where D is the domain and C is the codomain: both would be `int` in the examples.

A function can be applied by the normal forward notation using juxtaposition or what is whimsically known as operator whitespace, or in reverse notation using operator dot:

```
f x
x.f
```

Such applications are equivalent. Both operators are left associative. Operator dot binds more tightly than whitespace so that

```
f x.g    // means
f (g x)
```

A special notation is used for application to the unit tuple:

```
#zero // means
zero ()
```

The intention is intended to suggest a constant since a pure function with unit argument must always return the same value.

This hash operator binds more tightly than operator dot so

```
#a.b // means
(#a).b
```

15.2 Pre- and post-conditions

A function using one of the first two forms may have pre-conditions, post-conditions, or both:

```
fun f1 (x:int when x > 0) => x + x + 1;
fun f2 (x:int) expect result > 1 => x + x + 1;
fun f3 (x:int when x > 0) expect result > 1 => x + x + 1;
fun f4 (x:int when x > 0) : int expect result > 1 => x + x + 1;
```

Pre- and pos-conditions are usually treated as boolean assertions which are checked at run time. The compiler may occasionally be able to prove a pre- or post-condition must hold and elide it.

The special identifier `result` is used to indicate the return value of the function.

15.3 Higher order functions

A function may be written like


```
fun hof (x:int) (y:int) : int = { return x + y; }
fun hof (x:int) (y:int) => x + y;
```

These are called higher order functions of arity 2. They have the type

```
int -> int -> int    // or equivalently
int -> (int -> int)  //since -> is right associative.
```

They are equivalent to

```
fun hof (x:int) : int -> int =
{
  fun inner (y:int) : int => x + y;
  return inner;
}
```

that is, a function which returns another function.

Such a function can be applied like

```
hof 1 2 // or equivalently
(hof 1) 2
```

since whitespace application is left associative.

15.4 Procedures

A function which returns control but no value is called a procedure. Procedures may have side effects.

```
fun show (x:int) : 0 = { println x; }
proc show (x:int) { println x; }
proc show (x:int) => println x;
```

The second form is a more convenient notation. The type 0 is also called `void` and denotes a type with no values.

A procedure may return with a simple return statement:

```
proc show (x:int) { println x; return; }
```

however one is assumed at the end of the procedure body.

Procedures can also have pre- and post-conditions.

A procedure may be called like an application, however it must be a whole statement since expressions of type `void` may not occur interior to an expression.

```
show 1;
1.show;
```

If a procedure accepts the unit argument, it may be elided:

```
proc f () => show 1;
f; // equivalent to
f ();
```

15.5 Generators

A generator is a special kind of function which is allowed to have side effects. It is defined similarly to a function, but using the binder `gen` instead of `fun`:

```
var seqno = 1;
gen seq () { var result = seqno; ++seqno; return result; }
```

When a generator is directly applied in an expression, the application is replaced by a fresh variable and the generator application is lifted out and assigned to the variable. For example:

```
fun twice (x:int) => x + x;
println$ twice #seq;
```

will always print an even number because it is equivalent to

```
var tmp = #seq;
println$ twice tmp;
```

Therefore even if `twice` is inlined we end up with the argument to `println` being `@{tmp+tmp}` and not `@{#seq}` which would print an odd number.

15.5.1 Yielding Generators

A generator may contain a `yield` statement:

```
gen fresh() {
  var x = 1;
  while x < 10 do
    yield x;
    ++x;
  done
  return x;
}
```

In order to use such a yielding generator, a closure of the generator must be stored in a variable. Then the generator may be called repeatedly.

```
var g = fresh;
for i in 1 upto 20 do
  println$ i, #g;
done
```

This will print pairs (1,1), (2,2) up to (10,10) then print (11,10), (12,10) up to (20,10).

The `yield` statement returns a value such that a subsequent call to a closure of the generator will resume execution after the `yield` statement. Therefore `yield` is a kind of cross between a `return` and a subroutine call.

If a generator executes a `return` statement, that is equivalent to yielding a value and setting the resume point back to the `return` statement, in other words `return expr`; is equivalent to

```
while true do yield expr; done
```

Yielding generators should not be called directly because they will always start at the beginning with a fresh copy of any local variables used to maintain state.

Function closures differ from generator closures in that the closures is cloned before every application to ensure that the initial state is fresh.

Yielding generators are primarily intended to implement iterators, that is, to provide lazy lists or streams.

15.6 Constructors

Felix provides a special notation which allows an identifier naming a type to return a value of that type:

```
typedef cart = dcomplex;
typedef polar = dcomplex;
ctor cart (x:double, y:double) => dcomplex (x,y);
ctor polar (r: double, theta: double) =>
  dcomplex (r * sin theta, r * cos theta)
;
var z = cart (20.0,15.0) + polar (25.8, 0.7 * pi);
```

The constructions are equivalent to

```
fun _ctor_cart (x:double, y:double) : cart => dcomplex (x,y);
fun _ctor_polar (r: double, theta: double): polar =>
  dcomplex (r * sin theta, r * cos theta)
;
```

When a type with a simple name is applied to a value, Felix tries to find a function with that name prefixed by `_ctor_` instead.

Note that Felix generates a constructor for `struct` and `cstruct` types automatically with argument type the product of the types of the structure fields.

15.7 Special function apply

When Felix finds an application

```
f a
```

where `f` is a value of type `F` which is not a function (or `C` function) type, Felix looks instead for a function named `apply` with argument of type:

```
F * A
```

where `A` is the type of `a`. For example

```
fun apply (x:string, y:string) => x + y; // concat
var x = "hello " "world"; // apply a string to a string
```

15.8 Objects

Felix provides an object system with syntax based on Java, and technology based on CLOS.

An object is a record of function closures, closed over the local scope of a constructor function that returns the record.

```
interface person_t {
  get_name: 1 -> string;
  set_age: int -> 0;
  set_job : string -> 0;
  get_job : 1 -> string;
}

object person (name:string, var age:int) implements person_t =
{
  var job = "unknown";
  method fun get_name () => name;
  method proc set_age (x:int) { age = x; }
  method fun get_job () => job;
  method proc set_job (x:string) { job = x; }
}

var john = person ("John", 42);
println$ #(john.name) + " is " + #(john.age).str;
```

The entity `person` is a function which when called with its argument of name and age returns a record of type `person_t` consisting of closures of the functions and procedures marked as `method` in its definition.

Since functions hide their local variables the object state is hidden and can only be accessed using the methods.

The **implements** clause is optional.

Objects provide an excellent way for a dynamically loaded shared library to export a set of functions, only the object function needs to be exported so it has a C name which can be linked to with **dlopen**.

Part V

Executable statements

15.9 Assignment

Syntax

15.10 The goto statement and label prefix

Felix statements may be prefixed by a label to which control may be transferred by a `goto` statement:

```
alabel:>
  dosomething;
  goto alabel;
```

The label must be visible from the `goto` statement.

There are two kinds of `gotos`. A local `goto` is a jump to a label in the same scope as the `goto` statement.

A non-local `goto` is a jump to any other visible label.

Non-local transfers of control may cross procedure boundaries. They may not cross function or generator boundaries.

The procedure or function containing the label must be active at the time of the control transfer.

A non-local `goto` may be wrapped in a procedure closure and passed to a procedure from which the `goto` target is not visible.

```
proc doit (err: 1 -> 0) { e; }

proc outer () {
  proc handler () { goto error; }
  doit (handler);
  return;

  error:> println$ error;
}
```

This is a valid way to handle errors. the code is correct because `outer` is active at the time that `handler` performs the control transfer.

15.10.1 halt

Stops the program with a diagnostic.

```
halt "Program complete";
```

15.10.2 try/catch/entry

The try/catch construction may only be user to wrap calls to C++ primitives, so as to catch exceptions.

```
proc mythrow 1 = "throw 0;";
try
  mythrow;
catch (x:int) =>
  println$ "Caughht integer " + x.str;
endtry
```

15.10.3 goto-indirect/label_address

The label-address operator captures the address of code at a nominated label.

The address has type LABEL and can be stored in a variable.

Provided the activation record of the procedure containing the label remains live, a subsequent @goto-indirect) can be used to jump to that location.

```
proc demo (selector:int) {
  var pos : LABEL =
    if selector == 1
    then label_address lab1
    else label_address lab2
    endif
  ;
  goto-indirect selector;
lab1:>
  println$ "Lab1"; return;
lab2:>
  println$ "Lab2"; return;
}
```

15.10.4 Exchange of control

Built on top of label addressing and indirect gotos, the **branch-and-link** instruction is conceptually the most fundamental control instruction. The library implementation is in


```

inline proc branch-and-link (target:&LABEL, save:&LABEL)
{
  save <- label_address next;
  goto-indirect *target;
  next:>
}

```

A good example is [here](#), which shows an example of coroutines.

15.11 match/endmatch

The form:

```

match expr with
| pattern1 => stmts1
| pattern2 => stmts2
...
endmatch

```

is an extension of the C switch statement. The patterns are composed of these forms:

```

(v1, v2, ... )      // tuple match
h!t                 // list match
h,,t                // tuple cons
Ctor                // const union or variant match
Ctor v              // nonconst union or variant match
(fld1=f1, fld2=f2, ...) // record match
pat as v            // assign variable to matched subexpression
pat when expr       // guarded match
pat1 | pat2         // match either pattern
999                 // integer match
"str"               // string match
lit1 .. lit2        // range match
-                   // wildcard match

```

The guarded match only matches the pattern if the guard expression is true.

```

match x with
| (x,y) when y != 0 => ...
endmatch

```

The tuple as list cons match is a form of row polymorphism where the first element of a tuple and the remaining elements considered as a tuple are matched.

A good example of this is found in the library [here](#) which allows printing a tuple of arbitrary number of components, indeed, this facility was implemented precisely to allow this definition in the library.

Record matches succeed with any record containing a superset of the specified fields.

As well as integer and string matches, a literal of any type with an equality and inequality operator can be matched. In addition, if there is a less than or equal operator `<=` an inclusive range match can be specified.

15.12 if/goto

The conditional goto is an abbreviation for the more verbose conditional:

```
if c goto lab; // equivalent to
if c do goto lab; done
```

15.12.1 if/return

The conditional return is an abbreviation for the more verbose conditional:

```
if c return; // equivalent to
if c do return; done
```

15.12.2 if/call

The conditional call is an abbreviation for the more verbose conditional:

```
if c call f x; // equivalent to
if c do call f x; done
```

15.13 if/do/elif/else/done

The procedural conditional branch is used to select a control path based on a boolean expression.

The `else` and `@{elif` clauses are optional.

```

if c1 do
  stmt1;
  stmt2;
elif c2 do
  stmt3;
  stmt4;
else
  stmt5;
  stmt6;
done

```

The `elif` clause saves writing a nested conditional. The above is equivalent to:

```

if c1 do
  stmt1;
  stmt2;
else
  if c2 do
    stmt3;
    stmt4;
  else
    stmt5;
    stmt6;
  done
done

```

One or more statements may be given in the selected control path.

A simple conditional is an abbreviation for a statement match:

```

if c do stmt1; stmt2; else stmt3; stmt4; done
// is equivalent to
match c with
| true => stmt1; stmt2;
| false => stmt3; stmt4;
endmatch;

```

15.14 call

The `call` statement is used to invoke a procedure.

```

proc p(x:int) { println$ x; }
call p 1;

```

The word `call` may be elided in a simple call:

```

p 1;

```

If the argument is of unit type; that is, it is the empty tuple, then the tuple may also be elided in a simple call:

```
proc f() { println$ "Hi"; }
call f (); // is equivalent to
f(); // is equivalent to
f;
```

15.15 procedure return

The procedural return is used to return control from a procedure to its caller.

A return is not required at the end of a procedure where control would otherwise appear to drop through, a return is assumed:

```
proc f() { println$ 1; }
// equivalent to
proc f() { println$ 1; return; }
```

15.15.1 return from

The return from statement allows control to be returned from an enclosing procedure, provided that procedure is active.

```
proc outer () {
  proc inner () {
    println$ "Inner";
    return from outer;
  }
  inner;
  println$ "Never executed";
}
```

15.15.2 jump

The procedural jump is an abbreviation for the more verbose sequence:

```
jump procedure arg; // is equivalent to
call procedure arg;
return;
```

15.16 function return

The functional return statement returns a value from a function.

```
fun f () : int = {
  return 1;
}
```

Control may not fall through the end of a function.

15.16.1 yield

The `yield` statement returns a value from a generator whilst retaining the current location so that execution may be resumed at the point after the `yield`.

For this to work a closure of the generator must be stored in a variable which is subsequently applied.

```
gen counter () = {
  var x = 0;
next_integer:>
  yield x;
  ++x;
  goto next_integer;
}

var counter1 = counter;
var zero = counter1 ();
var one = counter1 ();
println$ zero, one;
```

15.17 spawn_fthread

[Library Reference](#)

The `spawn_fthread` library function invokes the corresponding service call to schedule the initial continuation of a procedure taking a unit argument as an fthread (fibre).

The spawned fthread begins executing immediately. If control returns before yielding by a synchronous channel operation, the action is equivalent to calling the procedure.

Otherwise the spawned fthread is suspended when the first write, or the first unmatched read operation occurs.

15.17.1 read/write/broadcast schannel

[Library Reference](#)

15.18 spawn_pthread

[Library Reference](#)

15.18.1 read/write pchannel

[Library Reference](#)

15.18.2 exchange

15.19 loops

[Library Reference](#)

Felix has some low level and high level loop constructions.

The low level for, while, and repeat loops are equivalent to loops implemented with gotos.

The bodies of do loops do not constitute a scope, therefore any symbol defined in such a body is also visible in the surrounding code.

Low level loops may be labelled with a loop label which is used to allow break, continue, and redo statements to exit from any containing loop.

```
outer:for var i in 0 upto 9 do
  inner: for var j in 0 upto 9 do
    println$ i,j;
    if i == j do break inner; done
    if i * j > 60 do break outer; done
  done
done
```

15.19.1 redo

The redo statement causes control to jump to the start of the specified loop without incrementing the control variable.

15.19.2 break

The break statement causes control to jump past the end of the specified loop, terminating iteration.

15.19.3 continue

The continue statement causes the control variable to be incremented and tests and the next iteration commenced or the loop terminated.

15.19.4 for/in/upto/downto/do/done

A basic loop with an inclusive range.

```
// up
for var ti:int in 0 upto 9 do println$ ti; done
for var i in 0 upto 9 do println$ i; done
for i in 0 upto 9 do println$ i; done

// down
for var tj:int in 9 downto 0 do println$ j; done
for var j in 9 downto 0 do println$ j; done
for j in 0 upto 9 do println$ j; done
```

The start and end expressions must be of the same type.

If the control variable is defined in the loop with a type annotation, that type must agree with the control variable.

The type must support comparison with the equality operator == the less than or equals operator <= and increment with the pre increment procedure ++.

For loops over unsigned types cannot handle the empty case. For loops over signed types cannot span the whole range of the type.

The loop logic takes care to ensure the control variable is not incremented (resp. decremented) past the end (resp.start) value.

15.19.5 while/do/done

The while loop executes the body repeatedly whilst the control condition is true at the start of the loop body.

```
var i = 0;
while i < 10 do println$ i; ++i; done
```

15.19.6 until loop

The until loop executes the loop body repeatedly until the control condition is false at the start of the loop, it is equivalent o a while loop with a negated condition.

```
var i = 0;
until i == 9 do println$ i; ++i; done
```

15.19.7 for/match/done

TBD

15.19.8 loop

TBD

15.20 Assertions

[Library Reference](#)

15.21 assert

Ad hoc assertion throws an assertion exception if its argument is false.

```
assert x > 0;
```

15.21.1 axiom

An axiom is a relationship between functions, typically polymorphic, which is required to hold.

```
axiom squares (x:double) => x * x >= 0;
class addition[T]
{
  virtual add : T * T -> T;
  virtual == : T * T -> bool;

  axiom assoc (x:T, y:T, z:T) :
    add (add (x,y),z) == add (x, add (y,z))
  ;
}
```

In a class, an axiom is a specification constraining implementations of virtual function in instances.

Axioms are restricted to first order logic, that is, they may be polymorphic, but the universal quantification implied is always at the head.

Existential quantification can be provided in a constructive logic by actually constructing the requisite variable.

Second order logic, with quantifiers internal to the logic term, are not supported.

15.21.2 lemma

A lemma is similar to an axiom, except that it is easily derivable from axioms; in particular, a reasonable automatic theorem prover should be able to derive it.

15.21.3 theorem

A theorem is similar to a lemma, except that it is too hard to expect an automatic theorem prover to be able to derive it without hints or assistance.

There is currently no standard way to prove such hints.

15.21.4 reduce

A reduce statement specifies a term reduction and is logically equivalent to an axiom, lemma, or theorem, however it acts as an instruction to the compiler to attempt to actually apply the axiom.

The compiler may apply the axiom, but it may miss opportunities for application.

The set of reductions must be coherent and terminal, that is, after a finite number of reductions the final term must be unique and irreducible.

Application of reduction is extremely expensive and they should be used lightly.

```
reduce revrev[T] (x: list[T]) : rev (rev x) => x;
```

15.21.5 invariant

An invariant is an assertion which must hold on the state variables of an object, at the point after construction of the state is completed by the constructor function and just before the record of method closures is returned, and, at the start and end of every method invocation.

The invariant need not hold during execution of a method.

Felix inserts the a check on the invariant into the constructor function and into the post conditions of every procedure or generator method.

```

object f(var x:int, var y:int) =
{
  invariant y >= 0;
  method proc set_y (newy: int) => y = newy;
}

```

15.22 code

The code statement inserts C++ code literally into the current Felix code.

The code must be one or more C++ statements.

```
code 'cout << "hello";';
```

15.22.1 noreturn code

Similar to code, however noreturn code never returns.

```
noreturn code "throw 1;";
```

15.23 Service call

The service call statement calls the Felix system kernel to perform a specified operation.

It is equivalent to an OS kernel call.

The available operations include:

```

union svc_req_t =
/*0*/ | svc_yield
/*1*/ | svc_get_fthread      of &fthread      // CHANGED LAYOUT
/*2*/ | svc_read            of address
/*3*/ | svc_general         of &address      // CHANGED LAYOUT
/*4*/ | svc_reserved1
/*5*/ | svc_spawn_pthread   of fthread
/*6*/ | svc_spawn_detached  of fthread
/*7*/ | svc_sread           of _schannel * &gcaddress
/*8*/ | svc_swrite          of _schannel * &gcaddress
/*9*/ | svc_kill            of fthread
/*10*/ | svc_reserved2
/*11*/ | svc_multi_swrite   of _schannel * &gcaddress
/*12*/ | svc_schedule_detached of fthread
;

```

These operations are typically related to coroutine or thread scheduling. However `svc_general` is an unspecified operation, which is typically used to invoke the asynchronous I/O subsystem.

Service calls can only be issued from flat code, that is, from procedures, since they call the system by returning control, the system must reside exactly one return address up the machine stack at the point a service call is executed.

15.24 with/do/done

The `with/do/done` statement is used to define temporary variables which are accessible only in the `do/done` body of the statement.

It is the statement equivalent of the `let` expression.

```
var x = 1;
with var x = 2; do println$ x; done
assert x == 1;
```

15.25 do/done

The `do/done` statement has no semantics and merely acts as a way to make a sequence of statements appear as a single statement to the parser.

Jumps into `do/done` groups are therefore allowed, and any labels defined in a `do/done` group are visible in the enclosing context.

Any variables, functions, or other symbols defined in a `do/done` group are visible in the enclosing context.

```
do something; done
```

15.26 begin/end

The `begin/end` statement creates an anonymous procedure and then calls it. It therefore appears as a single statement to the parser, but it simulates a block as would be used in C. It is exactly equivalent to a brace enclosed procedure called by a terminating semi-colon.

```
begin
  var x = 1;
end
// equivalent to
{
  var x = 1;
};
```

Part VI

Expressions

Syntax

Expressions are listed in approximate order of precedence, starting with the weakest binding.

We will often exhibit expressions in the form

```
var x = expr;
```

so as to present a complete statement. The `x` is of no significance.

15.27 Chain forms

15.27.1 Pattern let

The traditional let binding of ML. The syntax is

```
var x = let pattern = expr1 in expr2; // equivalent to
var x = match expr1 with pattern => expr2 endmatch
```

```
var x = let a = 1 in a + 1; // equivalent to
var x = match 1 with a => a + 1 endmatch
```

15.27.2 Function let

A let form which makes a function available in the expression

```
var x =
  let fun f(y:int)=> y + 1 in
  f 42
;
```

15.27.3 Match chain

A variant on the terminated match which allows a second match to be chained onto the last branch without any `endmatch`.

```

var y = list (1,2);
var x =
  match y with
  | #Empty => "Empty"
  | _ =>
    match y with
    | h ! Empty => h.str
    | _ =>
      match y with
      | h1 ! h2 ! Empty => h1.str + "," + h2.str
      ;

println$ x;

```

15.27.4 conditional chain

A variant on the terminated if/then/elif/else allowing chaining.

```

var x =
  if c1 then r1
  elif c2 then r2 else
  if c3 then r3 else
  r4
;

```

15.28 Alternate conditional chain

```

var x = n / d unless d == 0 then 0;

```

15.29 Dollar application

A right associative low precedence forward apply operator taken from Haskell.

```

var x = str$ rev$ list$ 1,2,3;

```

15.30 Pipe application

A left associative low precedence reverse apply operator taken from C#.

```

var x = 1,2,3 |> list |> rev |> str;

```

15.31 Tuple cons constructor

A right associative cons operator for tuples. Allows concatenating an element to the head/front/left end of a tuple. Can also be used in a pattern match to recursively decode a tuple like a list.

```
var x = 3,4;
var y = 1 ,, 2 ,, x; // 1,2,3,4
```

15.32 N-ary tuple constructor

There is a non-associative n-ary tuple constructor consists of a sequence of expressions separated by commas.

```
var x = 1,2,3,4;
```

15.33 Logical implication

An operator for function `implies`.

```
var x = false implies true;
```

15.34 Logical disjunction

A chaining operator for function `lor`.

```
var x = true or false;
```

15.35 Logical conjunction

A chaining operator for function `land`.

```
var x = true and false;
```

15.36 Logical negation

A bool operator for function `lnot`.

15.37 Comparisons

Non-associative.

```
var x =
  a < b or
  a > b or
  a <= b or
  a >= b or
  a == b or
  a != b or
  1 in list(1,2,3)
  1 \in list (1,2,3)
;
```

15.38 Name temporary

Allows a subexpression to be named as a `val` by default or a `var`.

```
var x = a + (f y as z) + z; // equivalent to
val z = f y; var x = a + z + z;

var x = a + (f y as var k) + k; // equivalent to
var k = f y; var x = a + k + k;
```

Note that the `var` for ensures the subexpression is eagerly evaluated, before the containing expression.

15.39 Schannel pipe operators

Used to flow data through schannels from the source on the left to the sink on the right via processing units in between.

```
spawn_fthread$ source |-> filter |-> enhancer |-> sink;
```

This variant uses an iterator to stream data out of a data structure:

```
spawn_fthread$ list (1,2,3) >-> sink;
```

15.40 Right Arrows

Right associative arrow operators.

List cons operator.

```
var x = 1 ! 2 ! list (3,4);
```

Function types (type language only):

```
D -> C // Felix function
D --> C // C function pointer
```

15.41 Case literals

The case tag is only used in pattern matches. The sum or union type isn't required because it can be deduced from the match argument.

```
var a = match a with Some v => v | #None => 0;
```

The case constructor with integer caseno has two uses.

It creates a value of a sum type with no arguments:

```
var x = case 1 of 2; // aka true
```

or it is a function for a sum type variant with an argument:

```
var x = (case 1 of int + double) 4.2;
```

A case literal with a name instead of an integer constructs a variant instead:

```
typedef maybe = union { No; Yes of int; };
var x = (case Yes of maybe) 42;
```

The tuple projection function names a tuple projection:

```
typedef triple = int * long * string;
var snd = proj 1 of triple;
var y: int = snd (1, 2L, "3");
```

15.42 Bitwise or

Left associative.

```
var x = q  $\boxdot$  b;
```

15.43 Bitwise exclusive or

Left associative.

```
var x = q  $\boxdot^$  b;
```

15.44 Bitwise and

Left associative.

```
var x = q & b;
```

15.45 Bitwise shifts

Left associative.

```
var x = a << b; // left shift
var x = a >> b; // right shift
```

15.46 Addition

Chain operator. Non-associative for types. Left associative for expressions.

```
var x = a + b + c;
```

15.47 Subtraction

Left associative.

```
var x = a - b;
```

15.48 Multiplication

Chain operator. Non-associative for types. Left associative for expressions.

```
var x = a * b;
```

15.49 Division operators

Left associative. Not carefully: higher precedence than multiplication, unlike C!!

```
var x = a * b / c * d; // means
var x = a * (b / c) * d;

var x = a * b % c * d; // means
var x = a * (b % c) * d;
```

15.50 Prefix operators

```
var x = !a;
var x = -a; // negation
var x = ~a; // bitwise complement
```

15.51 Fortran exponentiation

Infix `**` is special syntax for function `@pow`. The left operand binds more tightly than `**` but the right operand binds as for prefixed operators or more tightly. Observe that:

```
var x = -a**-b; // means
var x = -(a**(-b));
```

preserving the usual mathematical syntax.

15.52 Felix exponentiation

Left associative. The right operand binds as deref operator or more tightly. Used for array notation in the type language.

```
var x = a ^ ix;
```

15.53 Function composition

Standard math notation. Left associative. Same precedence as exponentiation. Spelled `\circ`.

```
var x = f \circ g;
```

15.54 Dereference

For function `deref`.

```
var x = *p;
```

For builtin dereference operator:

```
var x = _deref p;
```

Note these usually have the same meaning however the function `deref` can be overloaded. If the overloaded definition is not to be circular it may use `_deref` when dereferencing pointers.

15.54.1 Operator new

Copies a value onto the heap and returns a pointer.

```
var px = new 42;
```

15.55 Whitespace application

Operator whitespace is used for applications.

15.55.1 General

```
var x = sin y;
```

15.55.2 Caseno operator

Returns the integer tag value of the value of an anonymous sum, union, or variant type.

```
var x = caseno true; // 1
var x = caseno (Some 43); // 1
```

15.55.3 Likelyhood

Indicates if a bool valued expression is likely or unlikely to be true. Used to generate the corresponding gcc optimisation hints, if available.

```
if likely (c) goto restart;
if unlikely (d) goto loopend;
```

15.56 Coercion operator

left associative. The right operand is a type.

```
var x = 1L :>> int; // cast
```

15.57 Suffixed name

The most general form of a name:

```
var x = qualified::name of int;
```

Used to name functions, with the right operand specifying the function argument type.

15.58 Factors

15.58.1 Subscript

Used for array and string subscripting. Calls function **subscript**. For strings, returns a character. If the subscript is out of range after adjustment of negative index, returns **char 0** and thus cannot fail.

```
var x = a . [ i ]; // i'th element
```

15.58.2 Subsstring

Calls function **substring**. Negative indices may be used to offset from end, i.e. -1 is the index of the last element. Out of range indices (past the end or before the start, after adjustment of negative indices) are clipped back to the end or start respectively.

```
var x = a . [ first to past];  
// past is one past the last element referred to
```

15.58.3 Copyfrom

Calls function **copyfrom**. Copies from designated index to end. Supports negative indices and range clipping for strings.

```
var x = a . [to past]; // from the first
```

15.58.4 Copyto

Calls function **copyto**. Supports negative indices and range clipping for strings.

```
var x = a . [to past]; // from the first
```

15.58.5 Reverse application

Left associative.

```
var x = y .f; // means
var x = f y;
```

15.58.6 Reverse application with deref

Left associative

```
var x = p *. k; // means
var x = (*p) . k;
```

15.58.7 Reverse application with addressing

Left associative

```
var x = v &. k; // means
var x = (&v) . k;
```

15.58.8 Unit application

Prefix operator applies argument to empty tuple.

```
var x = #f; // means
var x = f ();
```

15.58.9 Addressing

Finds the pointer address of a variable. Means pointer to in type language.

```
var x : int = 1;
var px : &int = &x;
// address of x
// type pointer to int
```

15.58.10 C pointer

Used in type language for pointer to type or NULL.

```
var px : @char = malloc (42);
```

Note that this symbol is also used in fdoc as a markup indicator. Please keep out of column 1, do not follow with a left brace.

15.58.11 Label address

Used to find the machine address in the code text of a label. Used with computed goto instruction.

```
proc f (a: int) {
  var target: LABEL =
    if a < 0 then label_address neg
    elif a > 0 then label_address pos
    else label_address zer
  ;
  goto-indirect target;
  pos:> println$ "pos"; return;
  neg:> println$ "neg"; return;
  zer:> println$ "zer"; return;
}
```

15.58.12 Macro freezer

Used to disable macro expansion of a symbol.

```
macro val fred = joe;
var x = fred + noexpand fred; // means
var x = joe + fred;
```

15.58.13 Pattern variable

Notation `v` Used in patterns to designate a val variable to be bound in the pattern matching.

```
var x =
  match y with
  | Some v => "Some " + v.str
  | #None => "None";
;
```

15.58.14 Parser argument

Notation `n}` for some integer `@{n}`. In user defined syntax designates the `n`'th term of a syntax production.

15.59 Qualified name

A name in Felix has the form:

```
class1 :: nested1 :: ... :: identifier [ type1, type2, ... ]
```

where the qualifiers and/or type list may be elided. This is the same as C++ except we use `[]` instead of `@{<>}` for template argument types.

Chapter 16

Atoms

16.1 Record expression

```
var x = (name="Hello", age=42);
```

16.2 Alternate record expression

```
var x =  
  struct {  
    var name = "Hello";  
    var age = 42;  
  }  
;
```

16.3 Variant type

Denotes a variant type.

```
var x :  
  union {  
    Cart of double * double;  
    Polar of double * double;  
  }  
;
```

16.4 Wildcard pattern

Used in a pattern match, matches anything.

```
var x = match a with _ => "anything";
```

16.5 Ellipsis

Used only in C bindings to denote varargs.

```
fun f: int * ... -> int;
```

16.6 Truth constants

```
false // alias for case 0 of 2
true  // alias for case 1 of 2
```

16.7 callback expression

??

```
callback [ x ]
```

16.8 Lazy expression

Function of unit.

```
var f = { expr };
var x = f ();
```

16.9 Sequencing

Function dependent on final expression.

```
var x = ( var y = 1; var z = y + y; z + 1 ); // equivalent to
var x = #{ var y = 1; var z = y + y; return z + 1; };
```

16.10 Procedure of unit.

```
var p = { println$ "Hello"; } // procedure
p ();

var f = { var y = 1; return y + y; }; // function
var x = f ();
```

16.11 Grouping

Parentheses are used for grouping.

```
var x = (1 + 2) * 3;
```

16.12 Object extension

```
var x = extend a,b with c end;
```

16.13 Conditional expression

```
var x =
  if c1 then a elif c2 then b else c endif
;
```

Part VII

Library

Chapter 17

C bindings

Felix is specifically designed to provide almost seamless integration with C and C++.

In particular, Felix and C++ can share types and functions, typically without executable glue.

However Felix has a stronger and stricter type system than C++ and a much better syntax, so binding specifications which lift C++ entities into Felix typically require some static glue.

17.1 Type bindings

In general, Felix requires all primitive types to be first class, that is, they must be default initialisable, copy constructible, assignable, and destructible. Assignment to a default initialised variable must have the same semantics as copy construction.

It is recommended C++ objects provide move constructors as Felix generated code uses pass by value extensively.

The Felix type system does not support C++ references in general, you should use pointers instead.

However, there is a special lvalue annotation for C++ functions returning lvalues that allows them to appear on the LHS of an assignment. Only primitives can be marked lvalue.

The Felix type system does not support either const or volatile. This has no impact when passing arguments to C++ functions. However it may be necessary to cast a pointer returned from a primitive function in order for the generated code to type check.

17.2 Expression bindings

TBD

17.3 Function bindings

TBD

17.4 Floating insertions

TBD

17.5 Package requirements

TBD

Chapter 18

Core Primitive Types

18.1 Boolean type

The type `bool` which is also called 2 provides the usual boolean logic values `false` and `true`. The name `bool` is actually an alias for type `unit` sum of two cases. The name `false` is an alternate name of the value `case 0 of 2` and the name `true` is an alternate name for the value `case 1 of 2`.

See `?? ??` for more information.

18.2 Integer types

[Library Reference](#)

There is a table of the types [Table 18.1 Felix Integer Types](#).

Note that all these types are distinct unlike C and C++. The types designated are not the complete set of available integer like types since not all have literal representations.

Signed integers are expected to be two's complement with one more negative value than positive value. Bitwise and, or, exclusive or, and complement operations do not apply with signed types.

The effect of overflow on signed types is unspecified.

Unsigned types use the standard representation. Bitwise operations may be applied to unsigned types. Basic arithmetic operations on unsigned types are all well defined as the result of the operation mathematically modulo the maximum value of the type plus one.

Table 18.1: Felix Integer Types

Felix	C	Suffix
Standard signed integers		
tiny	char	t
short	short	s
int	int	
long	long	l
vlong	long long	ll
Standard unsigned integers		
utiny	unsigned char	ut
ushort	unsigned short	us
uint	unsigned int	u
ulong	unsigned long	ul
uvlong	unsigned long long	ull
Exact signed integers		
int8	int8_t	i8
int16	int16_t	i16
int32	int32_t	i32
int64	int64_t	i64
Exact unsigned integers		
uint8	uint8_t	u8
uint16	uint16_t	u16
uint32	uint32_t	u32
uint64	uint64_t	u64
Weird ones		
size	size_t	uz
intptr	intptr_t	p
uintptr	uintptr_t	up
ptrdiff	ptrdiff_t	d
uptrdiff	uptrdiff_t	ud
intmax	intmax_t	j
uintmax	uintmax_t	uj
Addressing		
address	void*	
byte	unsigned char	

The maximum value of an unsigned type is one less than two raised to the power of the number of bits in the type. The number of bits is 8, 16, 32, or 64 or 128 for all unsigned types.

There is a table of the operators [Table 18.2 Integer Operators](#).

18.2.1 Classification of integers

Library Reference

Integer types can be grouped into sets. In Felix this can be done with a `typeset` construction. The defined typesets are show in [Table 18.3 Integer Typesets](#).

Fast integers correspond to the usual C distinct integer types.

Exact integers are aliases to fast integers of specified sizes, in Felix these are distinct types.

The weird integers are special purposes aliases to fast integers which have special uses, again in Felix these are distinct types.

- The type `ptrdiff` is a signed type intended to represent the difference between two pointers.
- The `size` type is for measuring the sizes of objects and number of elements in an array.
- The `intmax` and `uintmax` types are the largest available signed and unsigned integer types, respectively.
- Finally the `intptr` and `uintptr` types are the same size as a pointer and can be used for low level numerical operations on pointers either by a conversion or reinterpret cast. They're typically used for to pack extra data into the low bits of a pointer to a type with an alignment which ensures the low bits of the pointer are zero.

Typesets can be used to simplify specification of C function bindings by leveraging constrained polymorphism.

```
fun add[T in ints]: T * T -> T = "$1+$2";

// or equivalently
fun add[T : ints]: T * T -> T = "$1+$2";
```

A special form which implies a quantifier for every use also exists, by specifying a `!` followed by a typeset name. For example,

```
fun intsum: !ints * !ints -> long = "(long)($1+$2)";

// or equivalently
fun intsum[T:ints, U:ints] : T * U -> long = "(long)($1+$2)";
```

Table 18.2: Integer Operators

symbol	kind	type	semantics
All Integers			
<code>==</code>	infix-nassoc	$T * T \rightarrow \text{bool}$	equality
<code>!=</code>	infix-nassoc	$T * T \rightarrow \text{bool}$	inequality
<code><</code>	infix-nassoc	$T * T \rightarrow \text{bool}$	less
<code><=</code>	infix-nassoc	$T * T \rightarrow \text{bool}$	less or equal
<code>></code>	infix-nassoc	$T * T \rightarrow \text{bool}$	greater
<code>>=</code>	infix-nassoc	$T * T \rightarrow \text{bool}$	greater or equal
<code>+</code>	infix-lassoc	$T * T \rightarrow T$	addition
<code>-</code>	infix-lassoc	$T * T \rightarrow T$	subtraction
<code>*</code>	infix-lassoc	$T * T \rightarrow T$	multiplication
<code>/</code>	infix-lassoc	$T * T \rightarrow T$	quotient
<code>%</code>	infix-lassoc	$T * T \rightarrow T$	remainder
<code><<</code>	infix-lassoc	$T * T \rightarrow T$	multiplication by power of 2
<code>>></code>	infix-lassoc	$T * T \rightarrow T$	division by power of 2
<code>-</code>	prefix	$T \rightarrow T$	negation
<code>+</code>	prefix	$T \rightarrow T$	no op
<code>succ</code>	func	$T \rightarrow T$	successor
<code>pred</code>	func	$T \rightarrow T$	predecessor
Signed Integers			
<code>sgn</code>	func	$T \rightarrow T$	sign
<code>abs</code>	func	$T \rightarrow T$	absolute value
Unsigned Integers			
<code>\&</code>	infix-lassoc	$T * T \rightarrow T$	bitwise and
<code>\ </code>	infix-lassoc	$T * T \rightarrow T$	bitwise or
<code>\^</code>	infix-lassoc	$T * T \rightarrow T$	bitwise exclusive or
<code>~</code>	prefix	$T * T \rightarrow T$	bitwise complement
nassoc: non-associative			
lassoc: left associative			
func: function			
note prefix - maps to function <code>neg</code>			

Table 18.3: Integer Typesets

<code>fast_sints</code>	(tiny, short, int, long, vlong)
<code>exact_sints</code>	(int8,int16,int32,int64)
<code>fast_uints</code>	(utiny, ushort, uint, ulong,ulong)
<code>exact_uints</code>	(uint8,uint16,uint32,uint64)
<code>weird_sints</code>	(ptrdiff, ssize, intmax, intptr)
<code>weird_uints</code>	(size, uintmax, uintptr)
<code>sints</code>	<code>fast_sints</code> \cup <code>exact_sints</code> \cup <code>weird_sints</code>
<code>uints</code>	<code>fast_uints</code> \cup <code>exact_uints</code> \cup <code>weird_uints</code>
<code>fast_ints</code>	<code>fast_sints</code> \cup <code>fast_uints</code>
<code>exact_ints</code>	<code>exact_sints</code> \cup <code>exact_uints</code>
<code>ints</code>	<code>sints</code> \cup <code>uints</code>

Note `intsum` can add any different kinds of integers, returning a `long`.

Polymorphism with typeset constraints is *only* useful for C bindings because the constraints are not propagated. It simply saves writing out all the finite combinations when genericity in the C or C++ target code means the C code would be the same in each case.

18.3 Floating point types

Library Reference

There is a table of the operators [Table 18.5 Floating Point Operators](#), we also have [Table 18.4 Trig functions](#).

Felix also provides `FINFINITY`, `DINFINITY` and `LINFINITY` for positive infinity representation for `float`, `double` and `ldouble` types, respectively.

18.4 Complex types

There are three complex types, `fcomplex`, `dcomplex` and `lcomplex` corresponding to cartesian representation using a pair of `float`, `double` and `ldouble` values, respectively.

There is a table of the operators [Table 18.6 Complex Operators](#), we also have [Table 18.4 Trig functions](#).

Table 18.4: Trig functions

symbol	type	semantics
circular		
<code>sin</code>	<code>T -> T</code>	sine
<code>cos</code>	<code>T -> T</code>	cosine
<code>tan</code>	<code>T -> T</code>	tangent
<code>asin</code>	<code>T -> T</code>	arc (inverse) sine
<code>acos</code>	<code>T -> T</code>	arc (inverse) cosine
<code>atan</code>	<code>T -> T</code>	arc (inverse) tangent
hyperbolic		
<code>sinh</code>	<code>T -> T</code>	hyperbolic sine
<code>cosh</code>	<code>T -> T</code>	hyperbolic cosine
<code>tanh</code>	<code>T -> T</code>	hyperbolic tangent
<code>asinh</code>	<code>T -> T</code>	arc (inverse) hyperbolic sine
<code>acosh</code>	<code>T -> T</code>	arc (inverse) hyperbolic cosine
<code>atanh</code>	<code>T -> T</code>	arc (inverse) hyperbolic tangent
Note: Inverses return primary branch		

Table 18.5: Floating Point Operators

symbol	kind	type	semantics
<code>==</code>	infix-nassoc	<code>T * T -> bool</code>	equality
<code>!=</code>	infix-nassoc	<code>T * T -> bool</code>	inequality
<code><</code>	infix-nassoc	<code>T * T -> bool</code>	less
<code><=</code>	infix-nassoc	<code>T * T -> bool</code>	less or equal
<code>></code>	infix-nassoc	<code>T * T -> bool</code>	greater
<code>>=</code>	infix-nassoc	<code>T * T -> bool</code>	greater or equal
<code>+</code>	infix-nassoc	<code>T * T -> T</code>	addition
<code>-</code>	infix-nassoc	<code>T * T -> T</code>	subtraction
<code>*</code>	infix-nassoc	<code>T * T -> T</code>	multiplication
<code>/</code>	infix-nassoc	<code>T * T -> T</code>	quotient
<code>-</code>	prefix	<code>T -> T</code>	negation
<code>abs</code>	func	<code>T->T</code>	absolute value
<code>log10</code>	func	<code>T->T</code>	base 10 logarithm
<code>sqrt</code>	func	<code>T->T</code>	square root
<code>ceil</code>	func	<code>T->T</code>	ceiling
<code>floor</code>	func	<code>T->T</code>	floor
<code>trunc</code>	func	<code>T->T</code>	truncate
<code>embed</code>	func	<code>int->T</code>	embedding
nassoc: non-associative			
lassoc: left associative			
func: function			
note prefix <code>-</code> maps to function <code>neg</code>			

Table 18.6: Complex Operators

symbol	kind	type	semantics
<code>fcomplex</code>	ctor	<code>float * float -> fcomplex</code>	cartesian
<code>fcomplex</code>	ctor	<code>float -> fcomplex</code>	from real
<code>dcomplex</code>	ctor	<code>double * double -> dcomplex</code>	cartesian
<code>dcomplex</code>	ctor	<code>double -> dcomplex</code>	from real
<code>lcomplex</code>	ctor	<code>ldouble * ldouble -> lcomplex</code>	cartesian
<code>lcomplex</code>	ctor	<code>ldouble -> lcomplex</code>	from real
<code>==</code>	infix-nassoc	<code>T * T -> bool</code>	equality
<code>!=</code>	infix-nassoc	<code>T * T -> bool</code>	inequality
<code>+</code>	infix-lassoc	<code>T * T -> T</code>	addition
<code>-</code>	infix-lassoc	<code>T * T -> T</code>	subtraction
<code>*</code>	infix-lassoc	<code>T * T -> T</code>	multiplication
<code>/</code>	infix-lassoc	<code>T * T -> T</code>	quotient
<code>-</code>	prefix	<code>T -> T</code>	negation
<code>real</code>	func	<code>T->R</code>	real part
<code>imag</code>	func	<code>T->R</code>	imaginary part
<code>abs</code>	func	<code>T->R</code>	norm
<code>arg</code>	func	<code>T->R</code>	argument

nassoc: non-associative
 lassoc: left associative
 func: function
 ctor: constructor
 note prefix - maps to function `neg`

Table 18.7: Quaternion Operators

symbol	kind	type	semantics
<code>==</code>	infix-nassoc	<code>T * T -> bool</code>	equality
<code>!=</code>	infix-nassoc	<code>T * T -> bool</code>	inequality
<code>+</code>	infix-lassoc	<code>T * T -> T</code>	addition
<code>-</code>	infix-lassoc	<code>T * T -> T</code>	subtraction
<code>*</code>	infix-lassoc	<code>T * T -> T</code>	multiplication
<code>/</code>	infix-lassoc	<code>T * T -> T</code>	quotient
<code>-</code>	prefix	<code>T -> T</code>	negation
nassoc: non-associative			
lassoc: left associative			
func: function			
note prefix <code>-</code> maps to function <code>neg</code>			

18.5 Quaternion type

There is a table of the operators [Table 18.7 Quaternion Operators](#).

18.6 Char Type

Felix has a type `char` corresponding to C's `char`. There are no literals of type `char`, instead there is a function, also called `char` to construct a `char` from a string literal. If the string at least length 1, the first character is returned, if the string is empty the NUL char `\0x00` is returned.

An overload of the `char` function also accepts an `int` argument and constructs a `char` with the designated C code value which must be in the range 0 through 255.

The function `ord` extracts the C code value of a `char` as an `int` in the range 0 through 255.

We note that C code values were originally used for the ASCII character set. Strings of `char` may be used to represent ISO-10646 (Unicode) code points via the UTF-8 encoding method. ASCII characters in the range 0 through 127 agree with Unicode interpretation.

18.6.1 ASCII classification functions

There is a set of [Table 18.9 ASCII classification functions](#) used to test the ASCII class of char.

Table 18.8: ASCII charsets

symbol	definition
upper	ABCDEFGHIJKLMNOPQRSTUVWXYZ
lower	abcdefghijklmnopqrstuvwxyz
letters	upper + lower
digits	0123456789
alphanum	letters + digits
cidcont	alphanum+"_"
flxidcont	alphanum+"_'"
camlidcont	alphanum+"_'"
numeric	digits + ".eEdD_"

The library also provides character sets represents as strings, show in [Table 18.8 ASCII charsets](#)

18.7 String Type

18.7.1 Equality and total ordering

```
fun == (s:string, c:string): bool
fun < (s:string, c:string): bool
fun <= (s:string, c:string): bool
fun > (s:string, c:string): bool
fun >= (s:string, c:string): bool
```

18.7.2 Equality of string and char

```
fun == (s:string, c:char): bool
fun == (c:char, s:string): bool
fun != (s:string, c:char): bool
fun != (c:char, s:string): bool
```

18.7.3 Append to string object

```
proc += : &string * string
proc += : &string * +char
proc += : &string * char
```


Table 18.9: ASCII classification functions

symbol	type	semantics
ISO C functions		
<code>isupper</code>	<code>char -> bool</code>	A-Z
<code>islower</code>	<code>char -> bool</code>	a-z
<code>isalnum</code>	<code>char -> bool</code>	A-Za-z0-9
<code>isalpha</code>	<code>char -> bool</code>	A-Za-z
<code>isdigit</code>	<code>char -> bool</code>	0-9
<code>isxdigit</code>	<code>char -> bool</code>	0-9A-Za-z
<code>iscntrl</code>	<code>char -> bool</code>	0x0-0x1F
<code>isspace</code>	<code>char -> bool</code>	0x20
<code>isblank</code>	<code>char -> bool</code>	0x20,0x09
<code>isprint</code>	<code>char -> bool</code>	0x20-0x7e
<code>ispunct</code>	<code>char -> bool</code>	punctuation
Lexing functions		
<code>isidstart</code>	<code>char -> bool</code>	First char identifier
<code>iscamlidcont</code>	<code>char -> bool</code>	Ocaml, subsequent chars
<code>iscidcont</code>	<code>char -> bool</code>	C, subsequent chars
<code>isflxidcont</code>	<code>char -> bool</code>	Felix, subsequent chars
<code>isnumeric</code>	<code>char -> bool</code>	0-9+-.Ee
<code>isalphanum</code>	<code>char -> bool</code>	A-Za-z0-9
<code>isletter</code>	<code>char -> bool</code>	A-Za-z
<code>issq</code>	<code>char -> bool</code>	'
<code>isdq</code>	<code>char -> bool</code>	"
<code>isslosh</code>	<code>char -> bool</code>	\
<code>isnull</code>	<code>char -> bool</code>	0x0
<code>iseol</code>	<code>char -> bool</code>	\n LF: Unix, CR: Windows

18.7.4 Length of string

```
fun len: string -> size
```

18.7.5 String concatenation

```
fun + : string * string -> string
fun + : string * carray[char] -> string
fun + : string * char -> string
fun + : char * string -> string
fun + ( x:string, y: int):string
```

18.7.6 Repetition of string or char

```
fun * : string * int -> string
fun * : char * int -> string
```

18.7.7 Application of string to string or int is concatenation

```
fun apply (x:string, y:string):string
fun apply (x:string, y:int):string
```

18.7.8 Construct a char from first byte of a string

Returns nul char (code 0) if the string is empty.

```
ctor char (x:string)
```

18.7.9 Constructors for string

```
ctor string (c:char)
ctor string: +char
ctor string: +char * !ints
fun utf8: int -> string
```

18.7.10 Substrings

```
fun subscript: string * !ints -> char
fun copyfrom: string * !ints -> string
fun copyto: string * !ints -> string
fun substring: string * !ints * !ints -> string
fun subscript (x:string, gs:gslice[int]):string
proc store: &string * !ints * char
```

18.7.11 Map a string char by char

```
fun map (f:char->char) (var x:string): string = {
```

18.7.12 STL string functions

These come in two flavours: the standard C++ operations which return `stl_npos` on failure, and a more Felix like variant which uses an `@option` type.

```

const stl_npos: size

fun stl_find: string * string -> size
fun stl_find: string * string * size -> size
fun stl_find: string * +char -> size
fun stl_find: string * +char * size -> size
fun stl_find: string * char -> size
fun stl_find: string * char * size -> size

fun find (s:string, e:string) : opt[size]
fun find (s:string, e:string, i:size) : opt[size]
fun find (s:string, e:+char) : opt[size]
fun find (s:string, e:+char, i:size) : opt[size]
fun find (s:string, e:char) : opt[size]
fun find (s:string, e:char, i:size) : opt[size]

fun stl_rfind: string * string -> size
fun stl_rfind: string * string * size -> size
fun stl_rfind: string * +char -> size
fun stl_rfind: string * +char * size
fun stl_rfind: string * char -> size
fun stl_rfind: string * char * size -> size

fun rfind (s:string, e:string) : opt[size]
fun rfind (s:string, e:string, i:size) : opt[size]
fun rfind (s:string, e:+char) : opt[size]
fun rfind (s:string, e:+char, i:size) : opt[size]
fun rfind (s:string, e:char) : opt[size]
fun rfind (s:string, e:char, i:size) : opt[size]

fun stl_find_first_of: string * string -> size
fun stl_find_first_of: string * string * size -> size
fun stl_find_first_of: string * +char -> size
fun stl_find_first_of: string * +char * size -> size
fun stl_find_first_of: string * char -> size
fun stl_find_first_of: string * char * size -> size

fun find_first_of (s:string, e:string) : opt[size]
fun find_first_of (s:string, e:string, i:size) : opt[size]
fun find_first_of (s:string, e:+char) : opt[size]
fun find_first_of (s:string, e:+char, i:size) : opt[size]
fun find_first_of (s:string, e:char) : opt[size]
fun find_first_of (s:string, e:char, i:size) : opt[size]

fun stl_find_first_not_of: string * string -> size
fun stl_find_first_not_of: string * string * size -> size
fun stl_find_first_not_of: string * +char -> size
fun stl_find_first_not_of: string * +char * size -> size
fun stl_find_first_not_of: string * char -> size
fun stl_find_first_not_of: string * char * size -> size

fun find_first_not_of (s:string, e:string) : opt[size]
fun find_first_not_of (s:string, e:string, i:size) : opt[size]
fun find_first_not_of (s:string, e:+char) : opt[size]
fun find_first_not_of (s:string, e:+char, i:size) : opt[size]
fun find_first_not_of (s:string, e:char) : opt[size]

```

18.7.13 Construe string as set of char

```
instance Set[string, char] {
  fun \in (c:char, s:string) => stl_find (s,c) != stl_npos;
}
```

18.7.14 Construe string as stream of char

```
instance Iterable[string, char] {
  gen iterator(var x:string) () = {
    for var i in 0 upto x.len.int - 1 do yield Some (x[i]); done
    return None[char];
  }
}
inherit Streamable[string, char];
```

18.7.15 Test if a string has given prefix or suffix

```
fun prefix(arg:string, key:string)=
fun suffix (arg:string, key:string)
fun startswith (x:string) (e:string) : bool

// as above: slices are faster
fun endswith (x:string) (e:string) : bool

fun startswith (x:string) (e:char) : bool
fun endswith (x:string) (e:char) : bool
```

18.7.16 h2 Trim off specified prefix or suffix or both

```
fun ltrim (x:string) (e:string) : string
fun rtrim (x:string) (e:string) : string
fun trim (x:string) (e:string) : string
```

18.7.17 Strip characters from left, right, or both end of a string.

```
fun lstrip (x:string, e:string) : string
fun rstrip (x:string, e:string) : string
fun strip (x:string, e:string) : string
fun lstrip (x:string) : string
fun rstrip (x:string) : string
fun strip (x:string) : string
```

18.7.18 Justify string contents

```
fun ljust(x:string, width:int) : string
fun rjust(x:string, width:int) : string
```

18.8 Regexp

[Syntax](#)

[Combinators](#)

[Google Re2 Binding](#)

Chapter 19

Fibres and Schannels

19.1 Pipelines

19.1.1 Synchronouse pipelines

[Library](#) lah.

Chapter 20

Asynchronous Events

blah.

Chapter 21

Pre-emptive Threading

[Library](#)

21.0.1 Json

TBD

21.0.2 Sqlite3

BD