
PyNomo Documentation

Release 0.3.0

Ron Doerfler, Joe Marasco, Leif Roschier

October 31, 2015

1	Introduction	3
1.1	Background	3
2	Tutorial	5
2.1	Tutorial 1: Hello World	5
2.2	Tutorial 2: More complex example...	5
3	Installation	7
3.1	Python 2.7.x OSX Installation	7
3.2	Python 3.5 OSX Installation	8
3.3	Python 2.7.x Linux installation	8
3.4	Python 3 Linux installation	9
3.5	Python 2.7.x Windows installation	9
3.6	Python 3.5 Windows installation	9
3.7	Python 2.7.x Docker installation	10
3.8	Python 3 Docker installation	11
4	Big picture of nomograph construction	13
4.1	Axes	13
4.2	Blocks	13
4.3	Combination of blocks	14
4.4	Transformations	14
5	Axes	15
5.1	Axes by example	15
5.2	Common axis params	29
6	Blocks	33
6.1	Type 1	33
6.2	Type 2	36
6.3	Type 3	39
6.4	Type 4	42
6.5	Type 5	46
6.6	Type 6	52
6.7	Type 7	55
6.8	Type 8	57
6.9	Type 9	60
6.10	Type 10	63
7	Block alignment	67

8	Transformations	69
9	Top level parameters	71
9.1	Main params	71
10	Examples	73
10.1	Example: Amortized loan calculator	73
10.2	Example Photography exposure	77
11	Literature	89
11.1	List of relevant books	89
11.2	Sources in the web	89
11.3	Scientific articles	89
12	Appendix	91
12.1	Comparison of Nomogram to Computer Application	91
13	License	93

pyNomo is a python library for making nomographs (or nomograms) that are graphical calculators. Nomographs are defined as a python script that consists in most part of dictionaries.

INTRODUCTION

1.1 Background

Todo

Here what are nomographs, where they are good, some history,...

2.1 Tutorial 1: Hello World

Todo

Here simplest tutorial...

2.2 Tutorial 2: More complex example...

Todo

Here more complex tutorial... (15 minutes?)

INSTALLATION

pyNomo is a [python](#) library and thus requires working python installation on the computer. pyNomo stands on the shoulders of (read: requires) the python packages: [numpy](#), [scipy](#) and [pyx](#) that requires LaTeX-installation. From version > 0.3.0 pynomo is compatible both with python 2 and python 3.

For editing pyNomo scripts any text browser works but integrated development environment (IDE) for python can speed up developments. Good free IDE alternatives are for example [PyCharm community edition](#) and [spyder](#).

3.1 Python 2.7.x OSX Installation

In OSX [Macports](#) is an effective tool to manage open-source software. In the following a MacPorts environment is set for Python and pyNomo. *sudo* runs the commands as super-user and requires it's password to be given.

First install python 2.7

```
$ sudo port install python27
```

One can list available python versions on the system with command

```
$ sudo port select --list python
```

Select MacPorts python 2.7

```
$ sudo port select --set python python27
```

Install python package index tool (pip)

```
$ sudo port install py27-pip
```

and set it active

```
$ port select --set pip pip27
```

Now python environment should be correct to be run from /opt/local/Library/.... Now install other required packages.

```
$ sudo port install py27-numpy
$ sudo port install py27-scipy
$ sudo port install py27-pyx
$ sudo pip install pynomo
```

3.2 Python 3.5 OSX Installation

In OSX [Macports](#) is an effective tool to manage open-source software. In the following a MacPorts environment is set for Python and pyNomo. *sudo* runs the commands as super-user and requires it's password to be given.

First install python 3.5

```
$ sudo port install python35
```

One can list available python versions on the system with command

```
$ sudo port select --list python
```

Select MacPorts python 2.7

```
$ sudo port select --set python3 python35
```

Install python package index tool (pip)

```
$ sudo port install py35-pip
```

and set it active (this sets it system-wide, if you are using also python2, consider twice)

```
$ port select --set pip pip35
```

Now python environment should be correct to be run from /opt/local/Library/.... Now install other required packages.

```
$ sudo port install py35-numpy
$ sudo port install py35-scipy
$ sudo port install py35-scipy
$ sudo port install texlive
$ sudo port install texlive-fonts-recommended
```

If you set pip active in whole system, run:

```
$ sudo pip install pynomo
$ sudo pip install --allow-external pyx pyx
```

If not, check where pip is located and run for example (check your pip path)

```
$ sudo /opt/local/bin/pip install pynomo
$ sudo /opt/local/bin/pip install --allow-external pyx pyx
```

3.3 Python 2.7.x Linux installation

In [Debian](#) Linux distribution and in its [derivatives](#) (for example [Ubuntu](#) and [Raspbian](#)) pynomo can be installed using *apt-get* with the following commands. *sudo* runs the commands as super-user and requires it's password to be given.

```
$ sudo apt-get -y install python
$ sudo apt-get -y install python-pyx
$ sudo apt-get -y install python-pip
$ sudo apt-get -y install python-numpy
$ sudo apt-get -y install python-scipy
$ sudo pip install pynomo
```

3.4 Python 3 Linux installation

In [Debian](#) Linux distribution and in its [derivatives](#) (for example [Ubuntu](#) and [Raspbian](#)) `pynomo` can be installed using `apt-get` with the following commands. `sudo` runs the commands as super-user and requires it's password to be given.

```
$ sudo apt-get -y install python3
$ sudo apt-get -y install python3-pip
$ sudo apt-get -y install python3-numpy
$ sudo apt-get -y install python3-scipy
$ sudo apt-get -y install texlive-latex-base
$ sudo apt-get -y install texlive-fonts-recommended
$ sudo pip install pynomo
$ pip3 install --allow-external pyx pyx
$ pip3 install pynomo
```

3.5 Python 2.7.x Windows installation

1. Download and install [python 2.7.x](#) from www.python.org/downloads/ .
2. Download and install [MIKTeX LaTeX](#) -distribution from <http://miktex.org/download>.
3. Download and install [numpy](#) from sourceforge.net/projects/numpy.
4. Download and install [scipy](#) from sourceforge.net/projects/scipy.

`pyx` (python graphics package) installation is more tricky. Either

- Download `pyx 0.12.1` (python graphics package) from <http://sourceforge.net/projects/pyx/files/pyx/0.12.1/PyX-0.12.1.tar.gz/download>
- Uncompress the file `PyX-0.12.1.tar.gz` using for example `7-zip`.
- Open command prompt (cmd) and go to the uncompressed folder that contains file `setup.py`.
- run command `python setup.py install`

or cross your fingers and just run:

```
> pip install --allow-external pyx pyx
```

on command prompt with administrative rights.

Finally `pyNomo` is installed either by downloading installer from <http://sourceforge.net/projects/pynomo/> and by running it. Other choice to try is to run:

```
> pip install pynomo
```

on command line. Tedious, huh! If you find simpler Windows recipe, please email it to the maintainer of the project.

3.6 Python 3.5 Windows installation

1. Download and install [python 3.5.x](#) from www.python.org/downloads/ .
2. Download and install [MIKTeX LaTeX](#) -distribution from <http://miktex.org/download>.

3. Download and install [numpy](https://sourceforge.net/projects/numpy) from sourceforge.net/projects/numpy.
4. Download and install [scipy](https://sourceforge.net/projects/scipy) from sourceforge.net/projects/scipy.

pyx (python graphics package) installation is more tricky. Either

- Download [pyx 0.14](https://downloads.sourceforge.net/project/pyx/pyx/0.14/PyX-0.14.tar.gz) (python graphics package) from <https://downloads.sourceforge.net/project/pyx/pyx/0.14/PyX-0.14.tar.gz>
- Uncompress the file *PyX-0.14.tar.gz* using for example *7-zip*.
- Open command prompt (cmd) and go to the uncompressed folder that contains file *setup.py*.
- run command `python setup.py install`

or cross your fingers and just run:

```
> pip install --allow-external pyx pyx
```

on command prompt with administrative rights.

Finally `pyNomo` is installed either by downloading installer from <http://sourceforge.net/projects/pynomo/> and by running it. Other choice to try is to run:

```
> pip install pynomo
```

on command line. Tedious, huh! If you find simpler Windows recipe, please email it to the maintainer of the project.

3.7 Python 2.7.x Docker installation

[Docker](#) is a platform to create a sandboxed virtualized environments. In the following example *Dockerfile* a virtualized [Ubuntu](#) is created that has `pyNomo` installed with all requirements:

```
FROM ubuntu

# Install required packages:
# python, pyx, pip, numpy, scipy, pynomo and their requirements
RUN apt-get update
RUN apt-get -y upgrade
RUN DEBIAN_FRONTEND=noninteractive apt-get -y install python
RUN DEBIAN_FRONTEND=noninteractive apt-get -y install python-pyx
RUN DEBIAN_FRONTEND=noninteractive apt-get -y install python-pip
RUN DEBIAN_FRONTEND=noninteractive apt-get -y install python-numpy
RUN DEBIAN_FRONTEND=noninteractive apt-get -y install python-scipy
RUN DEBIAN_FRONTEND=noninteractive pip install pynomo

# Add /app directory and make it working dir
RUN mkdir -p /app
ADD . /app
WORKDIR /app

# Set the default command to execute -> "python my_pynomo_file.py"
CMD ["python", "my_pynomo_file.py"]
```

Docker container (environment) *my_pynomo_docker* is built in the directory */my_directory_path* that has the file *Dockerfile* with command

```
$ docker build -t my_pynomo_docker .
```

Once environment is built and *my_pynomo_file.py* is in directory */my_directory_path/pdf_py_dir/* one can run

```
$ docker run -i -v /my_directory_path/pdf_py_dir:/app my_pynomo_docker
```

that runs command `python my_pynomo_file.py` inside */app* directory of container that is mapped to directory */my_directory_path/pdf_py_dir* of the host system. That way a folder is used to share the script file and the generated pdf file between host system and the container (virtualized Linux environment).

3.8 Python 3 Docker installation

Docker is a platform to create a sandboxed virtualized environments. In the following example *Dockerfile* a virtualized **Ubuntu** is created that has pyNomo installed with all requirements:

```
FROM ubuntu

# Install required packages
RUN apt-get update && apt-get -y install -y \
    python3 \
    python3-pip \
    python3-numpy \
    python3-scipy \
    texlive-latex-base \
    texlive-fonts-recommended
RUN DEBIAN_FRONTEND=noninteractive pip3 install --allow-external pyx pyx

# Add our python app code to the image
RUN mkdir -p /app
ADD . /app
WORKDIR /app

CMD ["bash"]
```

Docker container (environment) *my_pynomo_docker* is built in the directory */my_directory_path* that has the file *Dockerfile* with command

```
$ docker build -t my_pynomo_docker .
```

Once environment is built and *my_pynomo_file.py* is in directory */my_directory_path/pdf_py_dir/* one can run

```
$ docker run -it -v /my_directory_path/pdf_py_dir:/app my_pynomo_docker
```

that opens terminal in */app* directory of container that is mapped to directory */my_directory_path/pdf_py_dir* of the host system. There one can run own scripts like:

```
$ python3 my_script.py
```

That way a folder is used to share the script file and the generated pdf file between host system and the container (virtualized Linux environment).

BIG PICTURE OF NOMOGRAPH CONSTRUCTION

Nomographs of PyNomo are constructed by writing a python script that defines the nomograph parameters and initializes class `Nomographer(parameters)` to build the nomograph.

Nomograph is constructed by defining axes that are used to build blocks. If there are more than one block, they are aligned with each other in order to construct the nomograph.

A simple example of pseudocode of typical PyNomo structure is the following:

```
from pynomo.nomographer import * # this loads the needed pynomo class
# define block 1
axis_params_1_for_block_1 = {...}
axis_params_2_for_block_1 = {...}
axis_params_3_for_block_1 = {...}
block_1 = {...}

# define block 2
axis_params_1_for_block_2 = {...}
axis_params_2_for_block_2 = {...}
axis_params_3_for_block_2 = {...}
block_2 = {...}

# define nomograph
main_params = { 'filename': 'filename_of_nomograph.pdf', # filename of output
                'block_params': [block_1, block_2],      # the blocks make the nomograph
                'transformations': [('scale paper',)],    # these make (projective) transformations for the canves
                }
# create nomograph
Nomographer(main_params)
```

It is to be noted that nomograph is defined as python dictionaries that constitute one main dictionary that is passed to `Nomographer` class.

4.1 Axes

A nomograph consist in simple terms of axes (or scales) that are positioned in a way to fulfil the equation to be graphed. Axes (or grids or graphs) are the leaves that build the tree of a nomograph. Defining axes and their appearance is major work in nomograph construction. Different possibilities are illustrated in Axes chapter.

4.2 Blocks

Blocks relate axes to each other. Each block fulfils some equation where axes are the variables. The following blocks below with corresponding equations are the core of PyNomo. These are

used as easy building blocks for nomograph construction. If these do not suffice one can build as complex nomograph as one wishes by using determinants in type 9.

Type 1	$F_1(u_1) + F_2(u_2) + F_3(u_3) = 0$
Type 2	$F_1(u_1) = F_2(u_2) F_3(u_3)$
Type 3	$F_1(u_1) + F_2(u_2) + \dots + F_N(u_N) = 0$
Type 4	$\frac{F_1(u_1)}{F_2(u_2)} = \frac{F_3(u_3)}{F_4(u_4)}$
Type 5	$F_1(v) = F_2(x, u)$
Type 6	$u = u$
Type 7	$\frac{1}{F_1(u_1)} + \frac{1}{F_2(u_2)} = \frac{1}{F_3(u_3)}$
Type 8	$y = F(u)$
Type 9	$\begin{vmatrix} F_1(u_1[, v_1]) & G_1(u_1[, v_1]) & H_1(u_1[, v_1]) \\ F_2(u_2[, v_2]) & G_2(u_2[, v_2]) & H_2(u_2[, v_2]) \\ F_3(u_3[, v_3]) & G_3(u_3[, v_3]) & H_3(u_3[, v_3]) \end{vmatrix} = 0$
Type 10	$F_1(u) + F_2(v) F_3(w) + F_4(w) = 0$

4.3 Combination of blocks

If a nomograph consists of many equations that are aligned, a compound nomograph is constructed. Chapter compound nomograph discusses block alignment in detail.

4.4 Transformations

Scales shall be transformed in order to use given space (paper) optimally. Chapter Transformations discusses transformations.


5.1 Axes by example

Axes are fundamental building blocks of nomographs. The following code uses minimal axis definition `N_params` that is rendered as a linear scale illustrated below. The range of values axis represents is defined with keywords `u_min` and `u_max`. `title` sets title string for the axis. Key part of the nomograph is the functional form of the axis. In the example below it is defined with keyword `function` and is given as a function. Different types of blocks assume different keywords of axis functions. For example types 1, 2 and 3 take keyword `function` but type 9 takes either `f`, `g`, `h` or `f_grid`, `g_grid`, `h_grid` keywords. So one have to define axis parameters compatible with the used block type. In the examples below Type 8 is used as block to taking axis definition because it is the simplest one.

5.1.1 Linear scale ('scale_type': 'linear')

Here we start with the simplest axis. It has by default scale `'scale_type': 'linear'` that is simple linear scale.

```
1 # ex_axes_1.py
2
3 import sys
4 sys.path.insert(0, "..")
5 from pynomo.nomographer import *
6
7 # axis definitions
8 N_params = {'u_min': 1.0,          # axis start value
9            'u_max': 10.0,         # axis stop value
10            'function': lambda u: u, # axis function
11            'title': 'u',          # axis titles
12            }
13
14 # block definitons defining one block of type 8
15 block_params = {'block_type': 'type_8',
16               'f_params': N_params,
17               'width': 5.0,
18               'height': 15.0,
19               }
20
21 # nomograph generation definitions
22 main_params = {'filename': 'ex_axes_1.pdf',
23               'paper_height': 15.0,
24               'paper_width': 5.0,
25               'block_params': [block_params],
26               'transformations': [('scale paper',)]
27               }
28
29 # actual code that builds the nomograph
30 Nomographer(main_params)
```




Because the example above looked little too busy or packed, we reduce the ticks by using only three different tick levels `'tick_levels':3` and two tick text levels `'tick_text_levels':2`. Tick side relative to the final drawing is set to left using `'tick_side':'left'`.

```
1 # ex_axes_2.py
2
3 N_params = {'u_min': 1.0,
4             'u_max': 10.0,
5             'function': lambda u: u,
6             'title': 'u',
7             'tick_levels': 3,      # <-
8             'tick_text_levels': 2, # <-
9             'tick_side': 'left',   # <-
10            }
11
12 block_params = {'block_type': 'type_8',
13                 'f_params': N_params,
14                 'width': 5.0,
15                 'height': 10.0,
16                }
17
18 main_params = {'filename': 'ex_axes_2.pdf',
19                'paper_height': 10.0,
20                'paper_width': 5.0,
```

```

21         'block_params': [block_params],
22         'transformations': [('scale paper',)]
23     }
24
25     Nomographer(main_params)

```




Title position can be shifted in both x- and y-directions. In the following we shift it using key-values 'title_x_shift':-1.0 and 'title_y_shift':0.5. Units are here centimeters.

```

1  # ex_axes_3.py
2
3  N_params = {'u_min': 1.0,
4              'u_max': 10.0,
5              'function': lambda u: u,
6              'title': 'u',
7              'tick_levels': 3,
8              'tick_text_levels': 2,
9              'tick_side': 'left',
10             'title_x_shift': -1.0, # <-
11             'title_y_shift': 0.5  # <-
12         }
13
14  block_params = {'block_type': 'type_8',
15                 'f_params': N_params,
16                 'width': 5.0,
17                 'height': 10.0,
18             }
19
20  main_params = {'filename': 'ex_axes_3.pdf',
21                'paper_height': 10.0,
22                'paper_width': 5.0,
23                'block_params': [block_params],
24                'transformations': [('scale paper',)]
25        }
26
27  Nomographer(main_params)

```



Sometimes single level of axis definitions is not enough. We might want to add more ticks in some additional range of the axis. Keyword 'extra_params' helps here. Value for this key is an array of dictionaries that modify given params in the given range set by `u_min` and `u_max`. In the following example we define additional ranges with more ticks in ranges 5.0..10.0 and 9.0..10.0. We also draw title this time to center using 'title_draw_center: True.

```


1  # ex_axes_4.py
2
3  N_params = {'u_min': 1.0,
4              'u_max': 10.0,
5              'function': lambda u: u,
6              'title': 'title',
7              'tick_levels': 2,
8              'tick_text_levels': 1,
9              'tick_side': 'left',
10             'title_draw_center': True,          # <-
11             'extra_params': [{ 'u_min': 5.0,    # <- range 1
12                               'u_max': 10.0,    # <-
13                               'tick_levels': 3,  # <-
14                               'tick_text_levels': 2, # <-
15                               },                # <-
16                               { 'u_min': 9.0,    # <- range 2
17                                 'u_max': 10.0,    # <-
18                                 'tick_levels': 4,  # <-
19                                 'tick_text_levels': 2, # <-
20                                 }                # <-
21                               ]                  # <-
22         }
23  block_params = {'block_type': 'type_8',
24                  'f_params': N_params,
25                  'width': 5.0,
26                  'height': 10.0,
27                  }
28  main_params = {'filename': 'ex_axes_4.pdf',
29                 'paper_height': 10.0,
30                 'paper_width': 5.0,
31                 'block_params': [block_params],
32                 'transformations': [('scale paper',)]

```

```

33     }
34     Nomographer(main_params)

```



Color can be used to tune visual appearance of the axis. In the following example we tune colors with self-explaining keywords 'axis_color', 'text_color' and 'title_color'. Additional titles are set by using keyword 'extra_titles' with value of an array of dictionaries that can take keywords 'dx' and 'dy' as relative position to main title. Value of keyword 'text' sets the title text and 'pyx_extra_defs' can be used to give additional parameters for pyx rendering that is only option in current release. In the example numbers are formatted to have one three digits before comma and one digit after comma using 'text_format': r"\$%3.1f\$".

```

1  # ex_axes_4_1.py
2
3  N_params = {'u_min': 1.0,
4             'u_max': 10.0,
5             'function': lambda u: u,
6             'title': 'title',
7             'tick_levels': 2,
8             'tick_text_levels': 1,
9             'tick_side': 'left',
10            'title_draw_center': True,
11            'text_format': r"$%3.1f$ ",          # <- format numbers as %3.1f
12            'axis_color': color.cmyk.Orange,
13            'text_color': color.cmyk.Plum,
14            'title_color': color.cmyk.Plum,
15            'extra_params': [{'u_min': 5.0,
16                             'u_max': 10.0,
17                             'tick_levels': 3,
18                             'tick_text_levels': 2,
19                             'axis_color': color.cmyk.Red,
20                             },
21                             {'u_min': 9.0,
22                              'u_max': 10.0,
23                              'tick_levels': 4,
24                              'tick_text_levels': 2,
25                              'axis_color': color.cmyk.Blue,


```

```

26         },
27     ],
28     'extra_titles': [{ 'dx': 1.0,                # <- 1st extra title
29                       'dy': 1.0,                # <-
30                       'text': 'extra title 1',    # <-
31                       'width': 5,               # <-
32                       'pyx_extra_defs': [color.rgb.red, text.size.tiny] # <-
33                     },
34                     { 'dx': 0.0,                # <- 2nd extra title
35                       'dy': 2.0,                # <-
36                       'text': 'extra title 2',    # <-
37                       'width': 5,               # <-
38                       'pyx_extra_defs': [color.rgb.green] # <-
39                     },
40                     { 'dx': -1.0,               # <- 3rd extra title
41                       'dy': 1.0,                # <-
42                       'text': r"extra \par title 3", # <- \par = newline
43                       'width': 5,               # <-
44                       'pyx_extra_defs': [color.rgb.blue] # <-
45                     }
46     ]
47 block_params = { 'block_type': 'type_8',
48                 'f_params': N_params,
49                 'width': 5.0,
50                 'height': 10.0,
51                 }
52 main_params = { 'filename': 'ex_axes_4_1.pdf',
53               'paper_height': 10.0,
54               'paper_width': 5.0,
55               'block_params': [block_params],
56               'transformations': [('scale paper',)]
57             }
58 Nomographer(main_params)

```

extra title 2



5.1.2 Manual point scale ('scale_type': 'manual point')

Sometimes axes have to be defined manually. One option is to use manual point scale type with 'scale_type': 'manual point' and define the points as a dict to keyword 'manual_axis_data'.

```

1 # ex_axes_5.py
2
3 N_params = {'u_min': 1.0,
4             'u_max': 10.0,
5             'function': lambda u: u,
6             'title': 'title',
7             'tick_levels': 2,
8             'tick_text_levels': 1,
9             'tick_side': 'left',
10            'title_draw_center': True,
11            'scale_type': 'manual point',      # <- use manual points
12            'manual_axis_data': {1.0: 'one',   # <- give point values as keys
13                                2.0: 'two',    # <- and texts as values
14                                3.0: 'three',
15                                3.1415: r'$\pi$',
16                                4.0: 'four',
17                                5.0: 'five',
18                                6.0: 'six',
19                                7.0: 'seven',
20                                8.0: 'eight',
21                                9.0: 'nine',
22                                10.0: 'ten'}
23
24 block_params = {'block_type': 'type_8',
25                 'f_params': N_params,
26                 'width': 5.0,
27                 'height': 10.0
28                }
29 main_params = {'filename': 'ex_axes_5.pdf',
30               'paper_height': 10.0,
31               'paper_width': 5.0,
32               'block_params': [block_params],
33               'transformations': [( 'scale paper',)]
34               }
35 Nomographer(main_params)

```

ten ·

nine ·

eight ·

seven ·

six ·

five ·

four ·

three π ·

two ·


one ·

title

5.1.3 Manual line scale ('scale_type': 'manual line')

Similarly other option is to use manual line scale type with 'scale_type': 'manual line' that draws main scale line and ticks. Drawn ticks are defined as a dict to keyword 'manual_axis_data' as above example.

```
1 # ex_axes_6.py
2
3 N_params = {'u_min': 1.0,
4             'u_max': 10.0,
5             'function': lambda u: u,
6             'title': 'title',
7             'tick_levels': 2,
8             'tick_text_levels': 1,
9             'tick_side': 'left',
10            'title_draw_center': True,
11            'scale_type': 'manual line',      # <-
12            'manual_axis_data': {1.0: 'one',
13                                2.0: 'two',
14                                3.0: 'three',
15                                3.1415: r'$\pi$',
16                                4.0: 'four',
17                                5.0: 'five',
18                                6.0: 'six',
19                                7.0: 'seven',
20                                8.0: 'eight',
21                                9.0: 'nine',
22                                10.0: 'ten'}
23        }
24 block_params = {'block_type': 'type_8',
25                 'f_params': N_params,
26                 'width': 5.0,
27                 'height': 10.0,
28                 }
29 main_params = {'filename': 'ex_axes_6.pdf',
30                'paper_height': 10.0,
31                'paper_width': 5.0,
32                'block_params': [block_params],
33                'transformations': [('scale paper',)]
34                }
35 Nomographer(main_params)
```



Combining manual lines and a linear scale.

```


1  # ex_axes_7.py
2
3  N_params = {'u_min': 1.0,
4              'u_max': 10.0,
5              'function': lambda u: u,
6              'title': 'title',
7              'tick_levels': 2,
8              'tick_text_levels': 1,
9              'tick_side': 'left',
10             'scale_type': 'manual line',
11             'manual_axis_data': {1.0: 'one',
12                                  2.0: 'two',
13                                  3.0: 'three',
14                                  3.1415: r'$\pi$',
15                                  4.0: 'four',
16                                  5.0: 'five',
17                                  6.0: 'six',
18                                  7.0: 'seven',
19                                  8.0: 'eight',
20                                  9.0: 'nine',
21                                  10.0: 'ten'},
22             'extra_params': [{'u_min': 1.0,
23                                'u_max': 10.0,
24                                'scale_type': 'linear',
25                                'tick_levels': 3,
26                                'tick_text_levels': 2,
27                                'tick_side': 'right',
28                                }]}
29
30  block_params = {'block_type': 'type_8',
31                  'f_params': N_params,
32                  'width': 5.0,
33                  'height': 10.0,
34                  }
35  main_params = {'filename': 'ex_axes_7.pdf',
36                 'paper_height': 10.0,
37                 'paper_width': 5.0,
38                 'block_params': [block_params],
39                 'transformations': [('scale paper',)]}

```

```

40     }
41     Nomographer(main_params)

```



5.1.4 Manual arrows ('scale_type': 'manual arrow')

Manual arrows can be used to point values in the scale using arrows.

```


1  # ex_axes_7_1.py
2
3  N_params = {'u_min': 1.0,
4             'u_max': 10.0,
5             'function': lambda u: u,
6             'title': r'\bf title',
7             'tick_levels': 2,
8             'tick_text_levels': 1,
9             'tick_side': 'left',
10            'scale_type': 'manual line',
11            'manual_axis_data': {1.0: 'one',
12                                2.0: 'two',
13                                3.0: 'three',
14                                3.1415: r'$\pi$',
15                                4.0: 'four',
16                                5.0: 'five',
17                                6.0: 'six',
18                                7.0: 'seven',
19                                8.0: 'eight',
20                                9.0: 'nine',
21                                10.0: 'ten'},
22            'extra_params': [{'u_min': 1.0,
23                              'u_max': 10.0,
24                              'scale_type': 'linear',
25                              'tick_levels': 3,
26                              'tick_text_levels': 2,
27                              'tick_side': 'right',
28                              'extra_angle': 90.0,
29                              'text_horizontal_align_center': True,
30                              'text_format': r"$$$2.1f$"}],

```

```

31         {'scale_type': 'manual arrow',          # <-
32          'manual_axis_data': {6.2830: r'$2\pi$',
33                               9.4245: r'$3\pi$'},
34          'arrow_color': color.cmyk.Sepia,
35          'arrow_length': 2.0,
36          'text_color': color.cmyk.Sepia,
37          }]
38     }
39     block_params = {'block_type': 'type_8',
40                    'f_params': N_params,
41                    'width': 5.0,
42                    'height': 10.0,
43                    }
44     main_params = {'filename': 'ex_axes_7_1.pdf',
45                   'paper_height': 10.0,
46                   'paper_width': 5.0,
47                   'block_params': [block_params],
48                   'transformations': [('scale paper',)]
49                   }
50     Nomographer(main_params)

```



5.1.5 Manual function ('function_x' and 'function_y')

If one wants to explicitly draw scale in xy-space, parameters 'function_x' and 'function_y' can be used in conjunction with block type 8. In the following example circular scale is drawn.

```


1  # ex_axes_8.py
2
3  N_params = {'u_min': 0.0,
4             'u_max': 300.0,
5             'function_x': lambda u: 3 * sin(u / 180.0 * pi),
6             'function_y': lambda u: 3 * cos(u / 180.0 * pi),
7             'title': 'u',
8             'tick_levels': 3,
9             'tick_text_levels': 1,
10            'title_x_shift': -0.5,

```

```

11     }
12     block_params = {'block_type': 'type_8',
13                     'f_params': N_params,
14                     'width': 5.0,
15                     'height': 15.0,
16                     }
17     main_params = {'filename': 'ex_axes_8.pdf',
18                   'paper_height': 10.0,
19                   'paper_width': 10.0,
20                   'block_params': [block_params],
21                   'transformations': [(('scale paper',))]}
22     }
23     Nomographer(main_params)

```



In the following we fine-tune the appearance of the scale. Tick lengths are explicitly given with params 'grid_length_x' (note name with bad logic), text sizes are tuned with params 'text_size_x' and distance of text to the scale is set using 'text_distance_x'. 'full_angle' parameter allows text to be drawn also upside down and text angle is rotated with 'extra_angle'.

```


1  # ex_axes_8_1.py
2
3  N_params = {'u_min': 0.0,
4              'u_max': 300.0,
5              'function_x': lambda u: 3 * sin(u / 180.0 * pi),
6              'function_y': lambda u: 3 * cos(u / 180.0 * pi),
7              'title': 'u',
8              'tick_levels': 3,
9              'tick_text_levels': 1,
10             'title_x_shift': -0.5,
11             'grid_length_0': 0.8/4,

```

```

12     'grid_length_1': 0.6/4,
13     'grid_length_2': 0.5/4,
14     'grid_length_3': 0.4/4,
15     'grid_length_4': 0.3/4,
16     'text_size_0': text.size.tiny,
17     'text_size_1': text.size.tiny,
18     'text_size_2': text.size.tiny,
19     'text_size_3': text.size.tiny,
20     'text_size_4': text.size.tiny,
21     'text_distance_0': 1.2/4,
22     'text_distance_1': 1.1/4,
23     'text_distance_2': 1.0/4,
24     'text_distance_3': 1.0/4,
25     'text_distance_4': 1.0/4,
26     'title_distance_center': 0.7,
27     'title_opposite_tick': True,
28     'title_draw_center': True,
29     'text_format': "$%3.1f$",
30     'full_angle': True,
31     'extra_angle': 90.0,
32     'text_horizontal_align_center': True,
33     'text_format': r"$%2.0f$",
34     'text_color': color.cmyk.Sepia,
35 }
36 block_params = {'block_type': 'type_8',
37                 'f_params': N_params,
38                 'width': 5.0,
39                 'height': 15.0,
40 }
41 main_params = {'filename': 'ex_axes_8_1.pdf',
42               'paper_height': 10.0,
43               'paper_width': 10.0,
44               'block_params': [block_params],
45               'transformations': [('scale paper',)]
46 }
47 Nomographer(main_params)


```



5.1.6 Linear scale ('scale_type': 'log')

Often one needs to use logarithmic functions in scales and 'scale_type': 'log' makes some optimizations for this kind of scale appearance.

```
1 # ex_axes_9.py
2
3 N_params = {'u_min': 1.0,
4             'u_max': 10000.0,
5             'function': lambda u: log(u),
6             'title': 'u',
7             'scale_type': 'log',
8             }
9 block_params = {'block_type': 'type_8',
10                'f_params': N_params,
11                'width': 5.0,
12                'height': 15.0,
13                }
14 main_params = {'filename': 'ex_axes_9.pdf',
15               'paper_height': 15.0,
16               'paper_width': 5.0,
17               'block_params': [block_params],
18               'transformations': [('scale paper',)]
19               }
20 Nomographer(main_params)
```

5.1.7 Smart scales ('scale_type': 'smart linear', 'scale_type': 'smart log')

Linear and log scales just plot ticks and texts as given with params 'tick_levels' and 'tick_text_levels'. Often this approach generates busy scales with overlapping texts and too dense ticks. Better approach is to use smart linear scales 'scale_type': 'smart linear' or smart log scales 'scale_type': 'smart log'. These scales check that tick and text distances does not go below given thresholds ('tick_distance_smart' and 'text_distance_smart'). TODO: example to use smart scales.

5.2 Common axis params

Table 5.1: Common axis params

parameter	default value	explanation
'ID'	'none'	String. To identify the axis.
'tag'	'none'	String. To align blocks w.r.t each other along axes with same tag.
'dtag'	'none'	String. To double-align blocks w.r.t each other along axes with same tag.
'title'	''	String. Axis title.
'title_x_shift'	0.0	Float. Title shift in x-direction.
'title_y_shift'	0.25	Float. Title shift in y-direction.
'scale_type'	'linear'	String. Scale type. Can be 'linear': linear scale. 'log': logarithmic scale. 'smart linear': linear scale with equal spacings. 'smart log': logarithmic scale with equal spacings, can also have negative values. 'manual point': Points and corresponding text positions are given manually in 'manual axis data'. No line is drawn. 'manual line': Ticks and corresponding text positions are given manually in 'manual axis data'.
'tick_levels'	4	Integer. How many levels (minor, minor-minor, etc.) of ticks are drawn. Largest effect to 'linear' scale.
'tick_text_levels'	'3'	Integer. How many levels (minor, minor-minor, etc.) of texts are drawn. Largest effect to 'linear' scale.
'tick_side'	'right'	String. Tick and text side in final paper. Can be: 'right' or 'left'
'reference'	False	Boolean. If axis is treated as reference line that is a turning point.
'reference_padding'	'0.2'	Float. Fraction of reference line over other lines.
'manual_axis_data'	{}	Dict. Manually set tick/point positions and text positions. Could be for example: {1: '1', 3.14: r'\$\pi\$', 5: '5', 7: 'seven', 10: '10'}
'title_draw_center'	False	Boolean. Title is drawn to center of line.
'title_distance_center'	'type_9'	String. To double-align blocks w.r.t each other along axes with same tag.
'title_opposite_tick'	True	Boolean. Title in opposite direction w.r.t ticks.
'align_func'	lambda u:u	func(u). function to align different scales.
'align_x_offset'	0.0	Float. If axis is aligned with other axis, this value x offsets final scale.
'align_y_offset'	0.0	Float. If axis is aligned with other axis, this value y offsets final scale.
'text_format'	r'%4.4g\$ '	String. Format for numbers in scale.

Continued on next page

Table 5.1 – continued from previous page

parameter	default value	explanation
'extra_params'	[{}, ...]	Array of Dicts. List of dictionary of params to be drawn additionally.
'text_distance_#'	x.x	Float. where # = 0, 1, 2, 3 or 4. Distance of text from scale line. Number corresponds to the level, where 0 is the major tick and 4 is the most minor ticks.
'grid_length_#'	x.x	Float. where # = 0, 1, 2, 3 or 4. Length of the tick. Number corresponds to the level, where 0 is the major tick and 4 is the most minor ticks.
'text_size_#'	x.x	Float. where # = 0, 1, 2, 3 or 4. Text size. For example: text.size.small, text.size.scriptsize or text.size.tiny. Number corresponds to the level, where 0 is the major tick and 4 is the most minor ticks.
'text_size_log_#'	x.x	Float. where # = 0, 1 or 2. Text size. For example: text.size.small, text.size.scriptsize or text.size.tiny. Number corresponds to the level, where 0 is the major tick and 2 is the most minor ticks.
'full_angle'	False	Boolean. If true, text can be upside down, otherwise +- 90 degrees from horizontal. Good for example for full circle scales.
'extra_angle'	0.0	Boolean. Title is drawn to center of line.
'title_draw_center'	False	Float. Angle to rotate tick text from horizontal along tick.
'text_horizontal_align_center'	False	Boolean. Aligns tick text horizontally to center. Good when text rotated 90 degrees.
'turn_relative'	False	Boolean. Side left or right is relative according to traveling of scale from min to max.
'arrow_size'	0.2	Float. Used with arrow scale.
'arrow_length'	1.0	Float. Used with arrow scale..
'arrow_color'	color.rgb.black	Color. Used with arrow scale.
'axis_color'	color.rgb.black	Color. Color of axis.
'text_color'	color.rgb.black	Color. Color of tick texts.
'extra_titles'	[]	Array. List of extra title dicts for scale. Could be i.e. [{"dx": 1.0, "dy": 1.0, "text": "extra title 1", "width": 5, "pyx_extra_defs": [color.rgb.red, text.size.Huge]}, {"text": "extra title 2"}].

Continued on next page

Table 5.1 – continued from previous page

parameter	default value	explanation
'base_start'	None	None/Float. Defines number with 'base_stop' (instead of 'u_min' or 'u_max') to find major tick decades.
'base_stop'	None	None/Float. Defines number with 'base_start' (instead of 'u_min' or 'u_max') to find major tick decades.
'tick_distance_smart'	.05	Float. Minimum distance between smart ticks.
'text_distance_smart'	.25	Float. Minimum distance between smart texts.

BLOCKS

Every block in pynomo represents some equation. The blocks and their functions are listed in the following table.

Type 1	$F_1(u_1) + F_2(u_2) + F_3(u_3) = 0$	Three parallel lines
Type 2	$F_1(u_1) = F_2(u_2)F_3(u_3)$	“N” or “Z”
Type 3	$F_1(u_1) + F_2(u_2) + \cdots + F_N(u_N) = 0$	N parallel lines
Type 4	$\frac{F_1(u_1)}{F_2(u_2)} = \frac{F_3(u_3)}{F_4(u_4)}$	“Proportion”
Type 5	$F_1(v) = F_2(x, u)$	“Contour”
Type 6	$u = u$	“Ladder”
Type 7	$\frac{1}{F_1(u_1)} + \frac{1}{F_2(u_2)} = \frac{1}{F_3(u_3)}$	“Angle”
Type 8	$y = F(u)$	“Single”
Type 9	$\begin{vmatrix} F_1(u_1[v_1]) & G_1(u_1[v_1]) & H_1(u_1[v_1]) \\ F_2(u_2[v_2]) & G_2(u_2[v_2]) & H_2(u_2[v_2]) \\ F_3(u_3[v_3]) & G_3(u_3[v_3]) & H_3(u_3[v_3]) \end{vmatrix} = 0$	“General”
Type 10	$F_1(u) + F_2(v)F_3(w) + F_4(w) = 0$	One curved line

6.1 Type 1

Type 1 is three parallel lines that have functional relationship:

$$F_1(u_1) + F_2(u_2) + F_3(u_3) = 0$$


Note, that this kind of function can be transformed to many forms by using type 8 that is a equation given in determinant form. Use of this nomograph is given by the following simple example.

6.1.1 Simple example

This simple example plots nomograph for equation:

$$u_1 + u_2 + u_3 = 0.$$

Generated nomograph



Source code of simple example of type 1

```

1  """
2      ex_type1_nomo_1.py
3
4      Simple nomogram of type 1: F1+F2+F3=0
5  """
6  import sys
7  sys.path.insert(0, "..")
8  #sys.path[:0] = [".."]
9  from pynomo.nomographer import *
10
11  N_params_1={
12      'u_min':0.0,
13      'u_max':10.0,
14      'function':lambda u:u,
15      'title':r'$u_1$',
16      'tick_levels':2,
17      'tick_text_levels':1,
18  }
19
20  N_params_2={
21      'u_min':0.0,
22      'u_max':10.0,
23      'function':lambda u:u,
24      'title':r'$u_2$',
25      'tick_levels':2,
26      'tick_text_levels':1,
27  }
28
29  N_params_3={
30      'u_min':0.0,
31      'u_max':-10.0,
32      'function':lambda u:u,
33      'title':r'$u_3$',

```

```

34     'tick_levels':2,
35     'tick_text_levels':1,
36     }
37
38
39 block_1_params={
40     'block_type':'type_1',
41     'width':10.0,
42     'height':10.0,
43     'f1_params':N_params_1,
44     'f2_params':N_params_2,
45     'f3_params':N_params_3,
46     'isopleth_values':[[6,2,'x']],
47     }
48
49 main_params={
50     'filename':'ex_type1_nomo_1.pdf',
51     'paper_height':10.0,
52     'paper_width':10.0,
53     'block_params':[block_1_params],
54     'transformations':[(('rotate',0.01),('scale paper',))],
55     'title_str':r'$u_1+u_2+u_3=0$',
56     'debug':False,
57     }
58 Nomographer(main_params)

```

6.1.2 Parameters for type 1

Axis parameters

Table 6.1: Specific axis parameters for type 1

parameter key	default value	type, explanation
'function'	—	func(u) . Function in equation For example lambda u: u
'u_min'	—	Float . Minimum value of function variable.
'u_max'	—	Float . Maximum value of function variable.

See *Common axis params* for other parameters.

Block parameters

Table 6.2: Specific block parameters for type 9

parameter	default value	explanation
'block_type'	'type_1'	String. This is type 1 block
'width'	10.0	Float. Block width (to be scaled)
'height'	10.0	Float. Block height (to be scaled)
'f1_params'	–	Axis params Dict. Axis params for function f1
'f2_params'	–	Axis params Dict. Axis params for function f2
'f3_params'	–	Axis params Dict. Axis params for function f3
'mirror_x'	False	Boolean. If x-axis is mirrored
'mirror_y'	False	Boolean. If y-axis is mirrored
'proportion'	1.0	Float. Factor for spacings between lines
'isopleth_values'	[[[]]]	** List of list of isopleth values.** Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, 0.1, 'x'], ['x', 0.2, 1.0]]</code>

General parameters

See [Main params](#) for top level main parameters.

6.2 Type 2

Type 1 is “N” or “Z” nomograph that have functional relationship:

$$F_1(u_1) = F_2(u_2)F_3(u_3)$$


Use of this nomograph is given by the following simple example.

6.2.1 Simple example

This simple example plots nomograph for equation:

$$u_1 = u_2 u_3$$

Generated nomograph



Source code of simple example of type 2

```

1  """
2      ex_type2_nomo_1.py
3
4      Simple nomogram of type 2: F1=F2*F3
5  """
6  import sys
7  sys.path.insert(0, "..")
8  from pynomo.nomographer import *
9
10 N_params_1={
11     'u_min':0.0,
12     'u_max':10.0,
13     'function':lambda u:u,
14     'title':r'$u_1$',
15     'tick_levels':3,
16     'tick_text_levels':1,
17 }
18
19 N_params_2={
20     'u_min':0.5,
21     'u_max':6.0,
22     'function':lambda u:u,
23     'title':r'$u_2$',
24     'tick_levels':3,
25     'tick_text_levels':2,
26     'scale_type':'linear smart',
27 }
28
29 N_params_3={
30     'u_min':0.0,
31     'u_max':10.0,
32     'function':lambda u:u,
33     'title':r'$u_3$',

```

```

34     'tick_levels':3,
35     'tick_text_levels':1,
36     }
37
38
39 block_1_params={
40     'block_type':'type_2',
41     'width':10.0,
42     'height':10.0,
43     'f1_params':N_params_1,
44     'f2_params':N_params_2,
45     'f3_params':N_params_3,
46     'isopleth_values':[[9,1.5,'x']],
47     }
48
49 main_params={
50     'filename':'ex_type2_nomo_1.pdf',
51     'paper_height':10.0,
52     'paper_width':10.0,
53     'block_params':[block_1_params],
54     'transformations':[(('rotate',0.01),('scale paper',))],
55     'title_str':r'$u_1=u_2\times u_3$'
56     }
57 Nomographer(main_params)

```

6.2.2 Parameters for type 2

Axis parameters

Table 6.3: Specific axis parameters for type 2

parameter key	default value	type, explanation
'function'	—	func(u) . Function in equation For example $\lambda u: u$
'u_min'	—	Float . Minimum value of function variable.
'u_max'	—	Float . Maximum value of function variable.

See *Common axis params* for other parameters.

Block parameters

Table 6.4: Specific block parameters for type 2

parameter	default value	explanation
'block_type'	'type_2'	String. This is type 2 block
'width'	10.0	Float. Block width (to be scaled)
'height'	10.0	Float. Block height (to be scaled)
'f1_params'	–	Axis params Dict. Axis params for function f1
'f2_params'	–	Axis params Dict. Axis params for function f2
'f3_params'	–	Axis params Dict. Axis params for function f3
'mirror_x'	False	Boolean. If x-axis is mirrored
'mirror_y'	False	Boolean. If y-axis is mirrored
'proportion'	1.0	Float. Factor for spacings between lines
'isopleth_values'	[[[]]]	** List of list of isopleth values.** Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, 0.1, 'x'], ['x', 0.2, 1.0]]</code>

General parameters

See [Main params](#) for top level main parameters.

6.3 Type 3

Type 3 has N parallel lines that have functional relationship:

$$F_1(u_1) + F_2(u_2) + \cdots + F_N(u_N) = 0$$


Use of this nomograph is given by the following simple example.

6.3.1 Simple example

This simple example plots nomograph for equation:

$$u_1 + u_2 + u_3 + u_4 + u_5 + u_6 = 0$$

Generated nomograph



Source code of simple example of type 2

```

1  """
2      ex_type3_nomo_1.py
3
4      Simple nomogram of type 3: F1+F2+...+FN=0
5      You should have received a copy of the GNU General Public License
6      along with this program. If not, see <http://www.gnu.org/licenses/>.
7  """
8  import sys
9  sys.path.insert(0, "..")
10 from pynomo.nomographer import *
11
12 N_params_1={
13     'u_min':0.0,
14     'u_max':10.0,
15     'function':lambda u:u,
16     'title':r'$u_1$',
17     'tick_levels':2,
18     'tick_text_levels':1,
19 }
20 N_params_2={

```

```

21     'u_min':0.0,
22     'u_max':10.0,
23     'function':lambda u:u,
24     'title':r'$u_2$',
25     'tick_levels':2,
26     'tick_text_levels':1,
27     }
28 N_params_3={
29     'u_min':0.0,
30     'u_max':10.0,
31     'function':lambda u:u,
32     'title':r'$u_3$',
33     'tick_levels':2,
34     'tick_text_levels':1,
35     }
36 N_params_4={
37     'u_min':0.0,
38     'u_max':10.0,
39     'function':lambda u:u,
40     'title':r'$u_4$',
41     'tick_levels':2,
42     'tick_text_levels':1,
43     }
44 N_params_5={
45     'u_min':0.0,
46     'u_max':10.0,
47     'function':lambda u:u,
48     'title':r'$u_5$',
49     'tick_levels':2,
50     'tick_text_levels':1,
51     }
52 N_params_6={
53     'u_min':-20.0,
54     'u_max':0.0,
55     'function':lambda u:u,
56     'title':r'$u_6$',
57     'tick_levels':2,
58     'tick_text_levels':1,
59     'tick_side':'right',
60     }
61
62 block_1_params={
63     'block_type':'type_3',
64     'width':10.0,
65     'height':10.0,
66     'f_params':[N_params_1,N_params_2,N_params_3,
67                 N_params_4,N_params_5,N_params_6],
68     'isopleth_values':[[3,2,1,0,3,'x']],
69     }
70
71 main_params={
72     'filename':'ex_type3_nomo_1.pdf',
73     'paper_height':20.0,
74     'paper_width':20.0,
75     'block_params':[block_1_params],
76     'transformations':[('rotate',0.01),('scale paper',)],
77     'title_str':r'$u_1+u_2+u_3+u_4+u_5+u_6=0$',
78     'title_y':21.0,
79     }
80 Nomographer(main_params)

```

6.3.2 Parameters for type 3

Axis parameters

Table 6.5: Specific axis parameters for type 3

parameter key	default value	type, explanation
'function'	–	func(u) . Function in equation For example <code>lambda u: u</code>
'u_min'	–	Float . Minimum value of function variable.
'u_max'	–	Float . Maximum value of function variable.

See *Common axis params* for other parameters.

Block parameters

Table 6.6: Specific block parameters for type 3

parameter	default value	explanation
'block_type'	'type_3'	String . This is type 3 block
'width'	10.0	Float . Block width (to be scaled)
'height'	10.0	Float . Block height (to be scaled)
'f_params'	–	List of Axis params Dict . List of Axis params.
'mirror_x'	False	Boolean . If x-axis is mirrored
'mirror_y'	False	Boolean . If y-axis is mirrored
'reference_padding'	0.2	Float . Additional length to reference axes.
'reference_titles'	[]	Array of Strings . List of reference line titles. For example <code>['\$R_1\$', '\$R_2\$', '\$R_3\$']</code> .
'reference_color'	<code>color.rgb.black</code>	Color . Color of reference lines.
'isopleth_values'	[[[]]]	** List of list of isopleth values.** Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, 'x', 0.7, 7.0, 9.0], [0.7, 0.8, 'x', 5.0, 4.44]]</code>

General parameters

See *Main params* for top level main parameters.

6.4 Type 4

Type 4 is proportion nomograph that have functional relationship:


$$\frac{F_1(u_1)}{F_2(u_2)} = \frac{F_3(u_3)}{F_4(u_4)}$$

6.4.1 Simple example

This simple example plots nomograph for equation:

$$u_1/u_2 = u_3/u_4$$

Generated nomograph



Source code of simple example of type 4

```

1  """
2      ex_type4_nomo_1.py
3
4      Simple nomogram of type 4: F1/F2=F3/F4
5  """
6  import sys
7  sys.path.insert(0, "..")
8  from pynomo.nomographer import *
9
10 N_params_1={
11     'u_min':1.0,
12     'u_max':10.0,
13     'function':lambda u:u,
14     'title':r'$u_1$',
15     'tick_levels':3,
16     'tick_text_levels':1,
17     'tick_side':'left',

```

```
18         }
19     N_params_2={
20         'u_min':1.0,
21         'u_max':10.0,
22         'function':lambda u:u,
23         'title':r'$u_2$',
24         'tick_levels':3,
25         'tick_text_levels':1,
26         'tick_side':'right',
27     }
28     N_params_3={
29         'u_min':1.0,
30         'u_max':10.0,
31         'function':lambda u:u,
32         'title':r'$u_3$',
33         'tick_levels':3,
34         'tick_text_levels':1,
35         'tick_side':'right',
36         'title_draw_center':True,
37         'title_opposite_tick':False,
38     }
39     N_params_4={
40         'u_min':1.0,
41         'u_max':10.0,
42         'function':lambda u:u,
43         'title':r'$u_4$',
44         'tick_levels':3,
45         'tick_text_levels':1,
46         'tick_side':'left',
47         'title_draw_center':True,
48         'title_opposite_tick':False,
49     }
50
51     block_1_params={
52         'block_type':'type_4',
53         'f1_params':N_params_1,
54         'f2_params':N_params_2,
55         'f3_params':N_params_3,
56         'f4_params':N_params_4,
57         'isopleth_values':[[7,6,2,'x']],
58     }
59
60     main_params={
61         'filename':'ex_type4_nomo_1.pdf',
62         'paper_height':10.0,
63         'paper_width':10.0,
64         'block_params':[block_1_params],
65         'transformations':[( 'rotate',0.01),('scale paper',)],
66         'title_str':r'$u_1/u_2=u_3/u_4$',
67         'title_y':8.0,
68     }
69     Nomographer(main_params)
```


6.4.2 Parameters for type 4

Axis parameters

Table 6.7: Specific axis parameters for type 4

parameter key	default value	type, explanation
'function'	–	func(u) . Function in equation For example <code>lambda u: u</code>
'u_min'	–	Float . Minimum value of function variable.
'u_max'	–	Float . Maximum value of function variable.

See *Common axis params* for other parameters.

Block parameters

Table 6.8: Specific block parameters for type 4

parameter	default value	explanation
'block_type'	'type_4'	String . This is type 4 block
'width'	10.0	Float . Block width (to be scaled)
'height'	10.0	Float . Block height (to be scaled)
'f1_params'	–	Axis params Dict . Axis params for function f1
'f2_params'	–	Axis params Dict . Axis params for function f2
'f3_params'	–	Axis params Dict . Axis params for function f3
'f4_params'	–	Axis params Dict . Axis params for function f4
'mirror_x'	False	Boolean . If x-axis is mirrored
'mirror_y'	False	Boolean . If y-axis is mirrored
'padding'	0.9	Float . How much axis extend w.r.t. width/height.
'float_axis'	'F1 or F2'	Strings . If given 'F1 or F2', then scaling is according to them, otherwise according to F3 and F4.
'reference_color'	<code>color.rgb.black</code>	Color . Color of reference lines.
'isopleth_values'	<code>[[[]]</code>	** List of list of isopleth values.** Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, 'x', 0.7, 0.5], [0.7, 0.8, 'x', 0.3]]</code>

General parameters

See *Main params* for top level main parameters.

6.5 Type 5

Type 5 is graphing block that has functional relationship:

$$F_1(u) = F_2(x, v).$$

This type of block is used commonly in nomographs that have an equation in form

$$f_a(a_1, a_2, a_3, \dots) = f_b(u, v)$$

and `math:f_b(u,v)` cannot be represented as line-nomograph. Typically equation above is written as pair of equations:

$$f_a(a_1, a_2, a_3, \dots) = x$$

and

$$f_b(u, v) = x.$$

This equation is written in form

$$F_1(u) = F_2(x, v).$$

in order to construct this contour block. In reality block consists of horizontal lines:

$$F_1(u) = y$$

and contour lines

$$F_2(x, v) = y,$$

where x and y are the coordinates of canvas. Coordinate x is reference with name `wd` in block parameters and it holds

$$x = f_{wd}(wd).$$

Note: Type 5 is a very complex (say stupid) way to make basic graphs. In the future versions of pynomo a more simple way for graphs will be implemented.

6.5.1 Simple example

In the following example

$$F_1(u) = u$$


and

$$F_2(wd, v) = wd + v.$$

Thus the original equation is

$$wd = u - v.$$

Generated nomograph



Source code of simple example of type 5

```

1  """
2      ex_type5_nomo_1.py
3
4      Simple nomogram of type 5.
5  """
6  import sys
7  sys.path.insert(0, "..")
8  from pynomo.nomographer import *
9
10
11
12  block_params={
13      'block_type': 'type_5',
14      'u_func': lambda u:u,
15      'v_func': lambda x,v:x+v,
16      'u_values':[1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0,9.0,10.0],
17      'v_values':[1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0,9.0,10.0],
18      'wd_tick_levels':2,
19      'wd_tick_text_levels':1,
20      'wd_tick_side':'right',
21      'wd_title':'wd = u-v',
22      'u_title':'u',
23      'v_title':'v',
24      'wd_title_opposite_tick':True,
25      'wd_title_distance_center':2.5,

```

```

26     'isopleth_values':[[6.5,7,'x']],
27 }
28
29
30 main_params={
31     'filename':'ex_type5_nomo_1.pdf',
32     'paper_height':10.0,
33     'paper_width':10.0,
34     'block_params':[block_params],
35     'transformations':[('rotate',0.01),('scale paper',)]
36 }
37
38 Nomographer(main_params)

```

6.5.2 Parameters for type 5

Axis parameters

No specific axis parameters. Everything is defined in block.

Block parameters

Table 6.9: Specific block parameters for type 4

parameter	default value	explanation
'block_type'	'type_5'	String. This is type 5 block.
'width'	10.0	Float. Block width (to be scaled)
'height'	10.0	Float. Block height (to be scaled)
'mirror_x'	False	Boolean. If x-axis is mirrored
'mirror_y'	False	Boolean. If y-axis is mirrored
'u_func'	–	func(u). u function. For example lambda u: u
'v_func'	–	func(u,v). v function. For example lambda x,v: x+v
'wd_func'	–	func(wd). wd func. For example lambda wd: wd
'wd_func_inv'	–	func(wd). Inverse of wd-func. For example lambda wd: wd
'u_values'	–	List of Floats. List of plotted u values. For example <i>[1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 8.0, 9.0, 10.0]</i> ’.
'u_tag'	'none'	String. To align blocks w.r.t each other along axes with same tag.
'u_title'	' '	String. Axis title.
'u_title_x_shift'	0.0	Float. Title shift in x-direction.
'u_title_y_shift'	0.25	Float. Title shift in y-direction.

Continued on next page

Table 6.9 – continued from previous page

parameter	default value	explanation
'u_scale_type'	'linear'	String. Scale type. Can be 'linear': linear scale. 'log': logarithmic scale. 'smart linear': linear scale with equal spacings. 'smart log': logarithmic scale with equal spacings, can also have negative values. 'manual point': Points and corresponding text positions are given manually in 'manual axis data'. No line is drawn. 'manual line': Ticks and corresponding text positions are given manually in 'manual axis data'.
'u_tick_levels'	4	Integer. How many levels (minor, minor-minor, etc.) of ticks are drawn. Largest effect to 'linear' scale.
'u_tick_text_levels'	'3'	Integer. How many levels (minor, minor-minor, etc.) of texts are drawn. Largest effect to 'linear' scale.
'u_tick_side'	'right'	String. Tick and text side in final paper. Can be: 'right' or 'left'
'u_reference'	False	Boolean. If axis is treated as reference line that is a turning point.
'u_reference_padding'	'0.2'	Float. Fraction of reference line over other lines.
'u_manual_axis_data'	{}	Dict. Manually set tick/point positions and text positions. Could be for example: <code>{1:'1', 3.14:r'\$\pi\$', 5:'5', 7:'seven', 10:'10'}</code>
'u_title_draw_center'	False	Boolean. Title is drawn to center of line.
'u_title_distance_center'	'type_9'	String. To double-align blocks w.r.t each other along axes with same tag.
'u_title_opposite_tick'	True	Boolean. Title in opposite direction w.r.t ticks.
'u_align_func'	lambda u:u	func(u). function to align different scales.
'u_align_x_offset'	0.0	Float. If axis is aligned with other axis, this value x offsets final scale.
'u_align_y_offset'	0.0	Float. If axis is aligned with other axis, this value y offsets final scale.
'u_text_format'	r'%4.4g\$ '	String. Format for numbers in scale.
'u_extra_params'	[{}], ...]	Array of Dicts. List of dictionary of params to be drawn additionally.
'u_text_distance_#'	x.x	Float. where # = 0, 1, 2, 3 or 4. Distance of text from scale line. Number corresponds to the level, where 0 is the major tick and 4 is the most minor ticks.

Continued on next page

Table 6.9 – continued from previous page

parameter	default value	explanation
'u_grid_length_#'	x.x	Float. where # = 0, 1, 2, 3 or 4. Length of the tick. Number corresponds to the level, where 0 is the major tick and 4 is the most minor ticks.
'u_text_size_#'	x.x	Float. where # = 0, 1, 2, 3 or 4. Text size. For example: <code>text.size.small</code> , <code>text.size.scriptsize</code> or <code>text.size.tiny</code> . Number corresponds to the level, where 0 is the major tick and 4 is the most minor ticks.
'u_text_size_log_#'	x.x	Float. where # = 0, 1 or 2. Text size. For example: <code>text.size.small</code> , <code>text.size.scriptsize</code> or <code>text.size.tiny</code> . Number corresponds to the level, where 0 is the major tick and 2 is the most minor ticks.
'u_full_angle'	False	Boolean. If true, text can be upside down, otherwise ± 90 degrees from horizontal. Good for example for full circle scales.
'u_extra_angle'	0.0	Boolean. Title is drawn to center of line.
'u_text_horizontal_align'	False	Boolean. Aligns tick text horizontally to center. Good when text rotated 90 degrees.
'u_axis_color'	<code>color.rgb.black</code>	Color. Color of axis.
'u_text_color'	<code>color.rgb.black</code>	Color. Color of tick texts.
'v_values'	–	List of Floats. List of plotted v values. For example <code>[1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 8.0, 9.0, 10.0]</code> .
'v_title'	''	String. Axis title.
'v_title_draw_center'	False	Boolean. Title is drawn to center of line.
'v_title_distance_center'	'type_9'	String. To double-align blocks w.r.t each other along axes with same tag.
'v_title_opposite_tick'	True	Boolean. Title in opposite direction w.r.t ticks.
'wd_tag'	'none'	String. To align blocks w.r.t each other along axes with same tag.
'wd_title'	''	String. Axis title.
'wd_title_x_shift'	0.0	Float. Title shift in x-direction.
'wd_title_y_shift'	0.25	Float. Title shift in y-direction.

Continued on next page

Table 6.9 – continued from previous page

parameter	default value	explanation
'wd_scale_type'	'linear'	String. Scale type. Can be 'linear': linear scale. 'log': logarithmic scale. 'smart linear': linear scale with equal spacings. 'smart log': logarithmic scale with equal spacings, can also have negative values. 'manual point': Points and corresponding text positions are given manually in 'manual axis data'. No line is drawn. 'manual line': Ticks and corresponding text positions are given manually in 'manual axis data'.
'wd_tick_levels'	4	Integer. How many levels (minor, minor-minor, etc.) of ticks are drawn. Largest effect to 'linear' scale.
'wd_tick_text_levels'	'3'	Integer. How many levels (minor, minor-minor, etc.) of texts are drawn. Largest effect to 'linear' scale.
'wd_tick_side'	'right'	String. Tick and text side in final paper. Can be: 'right' or 'left'
'wd_reference'	False	Boolean. If axis is treated as reference line that is a turning point.
'wd_reference_padding'	'0.2'	Float. Fraction of reference line over other lines.
'wd_manual_axis_data'	{}	Dict. Manually set tick/point positions and text positions. Could be for example: {1:'1', 3.14:r'\$\pi\$', 5:'5', 7:'seven', 10:'10'}
'wd_title_draw_center'	False	Boolean. Title is drawn to center of line.
'wd_title_distance_center_type'	'9'	String. To double-align blocks w.r.t each other along axes with same tag.
'wd_title_opposite_ticks'	True	Boolean. Title in opposite direction w.r.t ticks.
'wd_align_func'	lambda u:u	func(u). function to align different scales.
'wd_align_x_offset'	0.0	Float. If axis is aligned with other axis, this value x offsets final scale.
'wd_align_y_offset'	0.0	Float. If axis is aligned with other axis, this value y offsets final scale.
'wd_text_format'	r'%4.4g\$ '	String. Format for numbers in scale.
'wd_extra_params'	[{},...]	Array of Dicts. List of dictionary of params to be drawn additionally.
'wd_text_distance_#'	x.x	Float. where # = 0,1,2,3 or 4. Distance of text from scale line. Number corresponds to the level, where 0 is the major tick and 4 is the most minor ticks.

Continued on next page

Table 6.9 – continued from previous page

parameter	default value	explanation
'wd_grid_length_#'	x.x	Float. where # = 0, 1, 2, 3 or 4. Length of the tick. Number corresponds to the level, where 0 is the major tick and 4 is the most minor ticks.
'wd_text_size_#'	x.x	Float. where # = 0, 1, 2, 3 or 4. Text size. For example: text.size.small, text.size.scriptsize or text.size.tiny. Number corresponds to the level, where 0 is the major tick and 4 is the most minor ticks.
'wd_text_size_log_#'	x.x	Float. where # = 0, 1 or 2. Text size. For example: text.size.small, text.size.scriptsize or text.size.tiny. Number corresponds to the level, where 0 is the major tick and 2 is the most minor ticks.
'wd_full_angle'	False	Boolean. If true, text can be upside down, otherwise +/- 90 degrees from horizontal. Good for example for full circle scales.
'wd_extra_angle'	0.0	Boolean. Title is drawn to center of line.
'wd_text_horizontal_align'	center	Boolean. Aligns tick text horizontally to center. Good when text rotated 90 degrees.
'wd_axis_color'	color.rgb.black	Color. Color of axis.
'wd_text_color'	color.rgb.black	Color. Color of tick texts.
'isopleth_values'	[[[]]]	** List of list of isopleth values.** Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, 'x', 0.7], [0.7, 0.8, 'x']]</code>

General parameters

See [Main params](#) for top level main parameters.

6.6 Type 6

Type 6 is ladder nomograph:

$$u = u.$$

In practice this means that if one axis has for example y-position as

$$y = f_1(u)$$

and it was desirable to have

$$y = f_2(u)$$

in order to connect blocks together, one uses ladder to make the transformation.

Note: Ladders are not beautiful and should be used only when no other solution exist.


6.6.1 Simple example

This simple example plots nomograph for equation:

$$u = u,$$

where linear scale is converted to a logarithmic scale.

Generated nomograph



Source code of simple example of type6

```

1 """
2     ex_type6_nomo_1.py
3
4     Simple nomogram of type 6.
5 """
6 import sys
7 sys.path.insert(0, "..")
8 from pynomo.nomographer import *
9
10 N_params_1={
11     'u_min':1.0,
12     'u_max':10.0,
13     'function':lambda u:u*0.5,
14     'title':'u',
15     'tick_levels':3,

```

```

16     'tick_text_levels':2,
17     'tick_side':'left',
18 }
19
20 N_params_2={
21     'u_min':1.0,
22     'u_max':10.0,
23     'function':lambda u:log(u),
24     'title':'u',
25     'tick_levels':3,
26     'tick_text_levels':2,
27 }
28
29 block_params={
30     'block_type':'type_6',
31     'f1_params':N_params_1,
32     'f2_params':N_params_2,
33     'width':5.0,
34     'height':10.0,
35     'isopleth_values':[[2.2, 'x']],
36     #'curve_const':0.01
37 }
38
39 main_params={
40     'filename':'ex_type6_nomo_1.pdf',
41     'paper_height':10.0,
42     'paper_width':5.0,
43     'block_params':[block_params],
44     'transformations':[(('rotate',0.01),('scale paper',))],
45 }
46
47 Nomographer(main_params)

```

6.6.2 Parameters for type 6

Axis parameters

Table 6.10: Specific axis parameters for type 6

parameter key	default value	type, explanation
'function'	—	func(u) . Function in equation For example <code>lambda u: u</code>
'u_min'	—	Float . Minimum value of function variable.
'u_max'	—	Float . Maximum value of function variable.

See *Common axis params* for other parameters.

Block parameters

Table 6.11: Specific block parameters for type 6

parameter	default value	explanation
'block_type'	'type_6'	String. This is type 6 block.
'type'	'parallel'	String. Can be either 'parallel' or 'orthogonal'.
'x_empty'	0.2	Float. If orthogonal, how much fractional space before start of x-axis.
'y_empty'	0.2	Float. If orthogonal, how much fractional space before start of y-axis.
'curve_const'	0.0	Float. Sets the lenght of angle of Bezier curve. low value = straigh line, high value = curved line.
'width'	10.0	Float. Block width (to be scaled)
'height'	10.0	Float. Block height (to be scaled)
'f1_params'	–	Axis params Dict. Axis params for function f1
'f2_params'	–	Axis params Dict. Axis params for function f2
'mirror_x'	False	Boolean. If x-axis is mirrored
'mirror_y'	False	Boolean. If y-axis is mirrored
'ladder_color'	color.rgb.black	Color. Ladder color.
'isopleth_values'	[[[]]]	** List of list of isopleth values.** Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, 'x'], [0.7, 'x']]</code>

General parameters

See [Main params](#) for top level main parameters.

6.7 Type 7

Type 7 is “angle” nomograph that has functional relationship:


$$\frac{1}{F_1(u_1)} + \frac{1}{F_2(u_2)} = \frac{1}{F_3(u_3)}$$

6.7.1 Simple example

This simple example plots nomograph for equation:

$$1/u_1 + 1/u_2 = 1/u_3$$

Generated nomograph



Source code of simple example of type 2

6.7.2 Parameters for type 7

Axis parameters

Table 6.12: Specific axis parameters for type 7

parameter key	default value	type, explanation
'function'	–	func(u). Function in equation For example <code>lambda u: u</code>
'u_min'	–	Float. Minimum value of function variable.
'u_max'	–	Float. Maximum value of function variable.

See *Common axis params* for other parameters.

Block parameters

Table 6.13: Specific block parameters for type 7

parameter	default value	explanation
'block_type'	'type_4'	String. This is type 7 block
'width'	10.0	Float. Block width (to be scaled)
'height'	10.0	Float. Block height (to be scaled)
'f1_params'	–	Axis params Dict. Axis params for function f1
'f2_params'	–	Axis params Dict. Axis params for function f2
'f3_params'	–	Axis params Dict. Axis params for function f3
'mirror_x'	False	Boolean. If x-axis is mirrored
'mirror_y'	False	Boolean. If y-axis is mirrored
'angle_u'	45.0	Float. Angle between u1 and u3. Note: later transformations may alter the angle.
'angle_v'	45.0	Float. Angle between u2 and u3. Note: later transformations may alter the angle.
'isopleth_values'	[[[]]]	** List of list of isopleth values.** Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, 'x', 0.7], [0.7, 0.8, 'x']]</code>

General parameters

See [Main params](#) for top level main parameters.

6.8 Type 8

Type 8 is single nomograph:

$$y = F(u)$$

or

$$x = F_x(u),$$


$$y = F_y(u).$$

x and y are coordinates of canvas. Often this block is used for construction of dual-scales to existing scales.

6.8.1 Simple example

This simple example plots single vertical scale.

Generated nomograph



Source code of simple example of type 8

```
1 """
2     ex_type8_nomo_1.py
3
4     Simple nomogram of type 8.
5 """
6 import sys
7 sys.path.insert(0, "..")
8 from pynomo.nomographer import *
9
10 N_params_1={
11     'u_min':1.0,
12     'u_max':10.0,
13     'function':lambda u:u,
14     'title':'u',
15     'tick_levels':3,
16     'tick_text_levels':2,
17     'tick_side':'left',
18 }
19
20 block_params={
21     'block_type':'type_8',
22     'f_params':N_params_1,
23     'width':5.0,
24     'height':10.0,
25     'isopleth_values':[[5]]
26 }
27
28 main_params={
29     'filename':'ex_type8_nomo_1.pdf',
30     'paper_height':10.0,
31     'paper_width':5.0,
32     'block_params':[block_params],
33     'transformations':[]
34 }
35
36 Nomographer(main_params)
```

6.8.2 Parameters for type 8

Axis parameters

Table 6.14: Specific axis parameters for type 8

parameter key	default value	type, explanation
'function'	–	func(u) . Function in equation. For example <code>lambda u: u</code> .
'u_min'	–	Float . Minimum value of function variable.
'u_max'	–	Float . Maximum value of function variable.
'function_x'	–	func(u) . x-position in function. If used 'function_y' must be defined. For example <code>lambda u: u</code> .
'function_y'	–	func(u) . y-position in function. If used 'function_x' must be defined. Overrides 'function'. For example <code>lambda u: u</code> .

See [Common axis params](#) for other parameters.

Block parameters

Table 6.15: Specific block parameters for type 8

parameter	default value	explanation
'block_type'	'type_8'	String . This is type 8 block
'width'	10.0	Float . Block width (to be scaled)
'height'	10.0	Float . Block height (to be scaled)
'f1_params'	–	Axis params Dict . Axis params for function f1
'f2_params'	–	Axis params Dict . Axis params for function f2
'f3_params'	–	Axis params Dict . Axis params for function f3
'f4_params'	–	Axis params Dict . Axis params for function f4
'mirror_x'	False	Boolean . If x-axis is mirrored
'mirror_y'	False	Boolean . If y-axis is mirrored
'padding'	0.9	Float . How much axis extend w.r.t. width/height.
'float_axis'	'F1 or F2'	Strings . If given 'F1 or F2', then scaling is according to them, otherwise according to F3 and F4.
'reference_color'	<code>color.rgb.black</code>	Color . Color of reference lines.
'isopleth_values'	<code>[[[]]]</code>	** List of list of isopleth values.** Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, 'x', 0.7, 0.5], [0.7, 0.8, 'x', 0.3]]</code>

General parameters

See [Main params](#) for top level main parameters.

6.9 Type 9

Type 9 is “general determinant” nomograph that has functional relationship:

$$\begin{vmatrix} F_1(u_1[, v_1]) & G_1(u_1[, v_1]) & H_1(u_1[, v_1]) \\ F_2(u_2[, v_2]) & G_2(u_2[, v_2]) & H_2(u_2[, v_2]) \\ F_3(u_3[, v_3]) & G_3(u_3[, v_3]) & H_3(u_3[, v_3]) \end{vmatrix} = 0.$$


This is the basic building block for line nomographs. Notation $u[, v]$ is to be understood such that if v is defined, a grid is constructed for the row, otherwise a normal scale with variable u .

6.9.1 Simple example

This simple example plots nomograph for equation in determinant form:

$$\begin{vmatrix} 0 & u_1 & 1 \\ u_2 + 2 & 2v_2 + 5 & 1 \\ 4 & u_3 & 1 \end{vmatrix} = 0$$

Generated nomograph



Source code of simple example of type 9

```

1  """
2      ex_type9_nomo_1.py
3
4      Simple nomogram of type 9: determinant
5  """
6  import sys
7  sys.path.insert(0, "..")
8  from pynomo.nomographer import *
9
10 N_params_1={
11     'u_min':3.0,
12     'u_max':10.0,
13     'f':lambda u:0,
14     'g':lambda u:u,
15     'h':lambda u:1.0,
16     'title':r'$u_1$',
17     'scale_type':'linear',
18     'tick_levels':3,
19     'tick_text_levels':2,
20     'grid':False}
21
22 N_params_2={
23     'u_min':0.0, # for alignment
24     'u_max':1.0, # for alignment
25     'f_grid':lambda u,v:u+2.0,
26     'g_grid':lambda u,v:2*v+5.0,
27     'h_grid':lambda u,v:1.0,
28     'u_start':0.0,
29     'u_stop':1.0,
30     'v_start':0.0,
31     'v_stop':1.0,
32     'u_values':[0.0,0.25,0.5,0.75,1.0],
33     'v_values':[0.0,0.25,0.5,0.75,1.0],
34     'grid':True,
35     'text_prefix_u':r'$u_2$=',
36     'text_prefix_v':r'$v_2$=',
37 }
38
39 N_params_3={
40     'u_min':3.0,
41     'u_max':10.0,
42     'f':lambda u:4.0,
43     'g':lambda u:u,
44     'h':lambda u:1.0,
45     'title':r'$u_3$',
46     'scale_type':'linear',
47     'tick_levels':3,
48     'tick_text_levels':2,
49     'grid':False
50 }
51
52 block_params={
53     'block_type':'type_9',
54     'f1_params':N_params_1,
55     'f2_params':N_params_2,
56     'f3_params':N_params_3,
57     'transform_ini':False,
58     'isopleth_values':[[7,[0.75,0.5], 'x']]
59 }
60
61 main_params={
62     'filename':'ex_type9_nomo_1.pdf',
63     'paper_height':10.0,
64     'paper_width':10.0,
65     'block_params':[block_params],
66     'transformations':[('rotate',0.01),('scale paper',)]
67 }
68 Nomographer(main_params)

```

6.9.2 Parameters for type 9

Axis parameters

Table 6.16: Specific axis parameters for type 9 grid axis

parameter key	default value	type, explanation
'grid'	–	Bool. True because this is grid.
'f'	–	func(u,v). F function in determinant. For example <code>lambda u,v:u+v</code>
'g'	–	func(u,v). G function in determinant. For example <code>lambda u,v:u+v</code>
'h'	–	func(u,v). H function in determinant. For example <code>lambda u,v:u+v</code>
'u_start'	–	u start when drawing $v=\text{const}$ line
'u_stop'	–	u stop when drawing $v=\text{const}$ line
'v_start'	–	v start when drawing $u=\text{const}$ line
'v_stop'	–	v stop when drawing $u=\text{const}$ line
'u_values'	–	List of grid lines $u=\text{const}$. For example <code>[0.0,0.25,0.5,0.75,1.0]</code>
'v_values'	–	List of grid lines $v=\text{const}$. For example <code>“[0.0,0.25,0.5,0.75,1.0]”</code>
'text_prefix_u'	–	Text prefix for u before value
'text_prefix_v'	–	Text prefix for v before value
'v_texts_u_start'	False	If v-texts are in u start side
'v_texts_u_stop'	True	If v-texts are in u stop side
'u_texts_v_start'	False	If u-texts are in v start side
'u_texts_v_stop'	True	If u-texts are in v stop side
'u_line_color'	<code>color.rgb.black</code>	Color. u line color
'v_line_color'	<code>color.rgb.black</code>	Color. v line color
'u_text_color'	<code>color.rgb.black</code>	Color. u text color
'v_text_color'	<code>color.rgb.black</code>	Color. v text color
'text_distance'	0.25	Float. Text distance
'circles'	False	Boolean. If marker circles to crossings
'extra_params'	–	List of Dicts. List of params to be drawn.

See *Common axis params* for other parameters.

Block parameters

Table 6.17: Specific block parameters for type 9

parameter	default value	explanation
'block_type'	'type_9'	String. This is type 9 block
'width'	10.0	Float. Block width (to be scaled)
'height'	10.0	Float. Block height (to be scaled)
'f1_params'	–	Axis params Dict. Axis params for function f1
'f2_params'	–	Axis params Dict. Axis params for function f2
'f3_params'	–	Axis params Dict. Axis params for function f3
'mirror_x'	False	Boolean. If x-axis is mirrored
'mirror_y'	False	Boolean. If y-axis is mirrored
'transform_ini'	False	Boolean. If row 1 and row 3 end and start are to be transformed to be in rectangle corners. If True, be sure that 'u_min_trafo' and 'u_max_trafo' are defined.
'isopleth_values'	[[[]]]	** List of list of isopleth values.** Grid values are given with tuple (a,b) and are not solved. Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, (0.1, 0.2), 'x'], ['x', (0.1, 0.2), 1.0]]</code>

General parameters

See [Main params](#) for top level main parameters.

6.10 Type 10

Type 10 is nomograph that has one curved line. It has functional relationship:


$$F_1(u) + F_2(v)F_3(w) + F_4(w) = 0.$$

6.10.1 Simple example

This simple example plots nomograph for equation:

$$u + vw + w = 0.$$

Generated nomograph



Source code of simple example of type 10

```

1  """
2      ex_type10_nomo_1.py
3
4      Simple nomogram of type 7: F1(u)+F2(v)*F3(w)+F4(w)=0
5      along with this program. If not, see <http://www.gnu.org/licenses/>.
6  """
7  import sys
8  sys.path.insert(0, "..")
9  from pynomo.nomographer import *
10
11  N_params_1={
12      'u_min':-10.0,
13      'u_max':10.0,
14      'function':lambda u:u,
15      'title':r'$u$',
16      'tick_levels':3,
17      'tick_text_levels':2,
18  }
19
20  N_params_2={
21      'u_min':-10.0,
22      'u_max':10.0,
23      'function':lambda u:u,
24      'title':r'$v$',
25      'tick_levels':3,
26      'tick_text_levels':2,
27      'tick_side':'left',
28  }
29
30  N_params_3={
31      'u_min':0.3,
32      'u_max':4.0,
33      'function_3':lambda u:u,

```

```

34     'function_4': lambda u: u,
35     'title': r'$w$',
36     'tick_levels': 4,
37     'tick_text_levels': 3,
38     'scale_type': 'linear smart',
39     'title_draw_center': True,
40     }
41
42 block_1_params={
43     'block_type': 'type_10',
44     'width': 10.0,
45     'height': 10.0,
46     'f1_params': N_params_1,
47     'f2_params': N_params_2,
48     'f3_params': N_params_3,
49     'isopleth_values': [[6, -4, 'x']]
50 }
51
52 main_params={
53     'filename': 'ex_type10_nomo_1.pdf',
54     'paper_height': 10.0,
55     'paper_width': 10.0,
56     'block_params': [block_1_params],
57     'transformations': [('rotate', 0.01), ('scale paper',)],
58     'title_str': r'$u+vw+w=0$'
59 }
60 Nomographer(main_params)

```

6.10.2 Parameters for type 10

Axis parameters

Table 6.18: Specific axis parameters for type 10

parameter key	default value	type, explanation
'function'	—	func(u) . Function in the equation for F_1 and F_2 . For example <i>"lambda u : u"</i>
'function_3'	—	func(u) . Function in the equation for F_3 . For example <i>lambda u: u</i>
'function_4'	—	func(u) . Function in the equation for F_4 . For example <i>lambda u: u</i>
'u_min'	—	Float . Minimum value of function variable.
'u_max'	—	Float . Maximum value of function variable.

See *Common axis params* for other parameters.

Block parameters

Table 6.19: Specific block parameters for type 10

parameter	default value	explanation
'block_type'	'type_10'	String. This is type 10 block
'width'	10.0	Float. Block width (to be scaled)
'height'	10.0	Float. Block height (to be scaled)
'f1_params'	–	Axis params Dict. Axis params for function f1
'f2_params'	–	Axis params Dict. Axis params for function f2
'f3_params'	–	Axis params Dict. Axis params for function f3
'f4_params'	–	Axis params Dict. Axis params for function f4
'mirror_x'	False	Boolean. If x-axis is mirrored
'mirror_y'	False	Boolean. If y-axis is mirrored
'padding'	0.9	Float. How much axis extend w.r.t. width/height.
'float_axis'	'F1 or F2'	Strings. If given 'F1 or F2', then scaling is according to them, otherwise according to F3 and F4.
'reference_color'	color.rgb.black	Color. Color of reference lines.
'isopleth_values'	[[[]]]	** List of list of isopleth values.** Unknown values are given with strings, e.g. 'x'. An example: <code>[[0.8, 'x', 0.7, 0.5], [0.7, 0.8, 'x', 0.3]]</code>

General parameters

See [Main params](#) for top level main parameters.

BLOCK ALIGNMENT

Todo

Here discussion about block alignment, double alignment, tags, ...

TRANSFORMATIONS

Todo

Here discussion about transformations. Why and how they are made.

TOP LEVEL PARAMETERS

Main params define the top level properties of the nomograph. TODO: some explanations.

9.1 Main params

Table 9.1: General params

parameter	default value	explanation
'filename'	'pynomo_default.pdf'	String. Filename of generated file. .pdf and .eps formats supported.
'paper_height'	20.0	String. Height of paper (roughly, ticks and texts extend this).
'paper_width'	20.0	String. Width of paper (roughly, ticks and texts extend this).
'block_params'		Array of Blocks. List of blocks that make the nomograph.
'transformations'	[('rotate', 0.01), ('scale paper')]	Array of tuples. List of transformations to transform nomograph.
'title_str'	' '	String. Title string of nomograph.
'title_x'	paper_width/2.0	Float. Title x-position.
'title_y'	paper_height	Float. Title y-position.
'title_box_width'	paper_width/2.2	Float. Title box width.
'title_color'	'color.rgb.black'	Color. Title color.
'make_grid'	False	Boolean. If True, draws grid to help position texts, etc.
'pre_func'	None	func(context). PyX function(canvas) to draw under nomograph. Function definition could be:
'post_func'	None	func(context). PyX function(canvas) to draw over nomograph. Definiton same as for 'pre_func'.
'debug'	False	Boolean. If True, prints dicts of definions.
'extra_texts'	[]	List of Dicts defining texts. Defines extra texts. Could be for example:
'isopleth_params'	[{}]	List of Dicts. Defines appearance of isopleths. Could be for example:

EXAMPLES

In the following are listed examples to show nomographs possibilities. Also is explained the background for the cases and underlying math for the nomograph construction. Source code shows the implementation.

10.1 Example: Amortized loan calculator

10.1.1 Theory and background

This approach of constructing an amortized loan calculator is similar to one in Ref. [1]_ Equation for amortized loan [2]_ is:

$$\frac{a}{A} = \frac{\frac{p}{100 \times 12}}{1 - \frac{1}{(1 + \frac{p}{100 \times 12})^{12n}}},$$

where A is the amount of loan, a is monthly payment amount, p interest rate per year (monthly interest rate is taken as $p/12$)¹ and n is number of years for payment.

This equation of four variables is probably impossible to present with line and grid nomographs. For this reason a “Type 5” contour nomogram is constructed of the right hand side of the equation and left hand equation is just N-nomogram (Type 2). The two equations for nomogram construction are:

$$x = \frac{a}{A}$$

and

$$x = \frac{\frac{p}{100 \times 12}}{1 - \frac{1}{(1 + \frac{p}{100 \times 12})^{12n}}}.$$

In practice x is the x-coordinate of the canvas where nomogram is constructed.

Right hand side of equation

By defining coordinates x and y :

$$x = \frac{\frac{p}{100 \times 12}}{1 - \frac{1}{(1 + \frac{p}{100 \times 12})^{12n}}},$$

$y = 12n$, we may solve y in terms of x and n :

¹ http://en.wikipedia.org/wiki/Annual_percentage_rate#Does_not_represent_the_total_cost_of_borrowing

$$y = \frac{\log\left(\frac{x}{x - \frac{p}{100 \times 12}}\right)}{\log\left(1 + \frac{p}{100 \times 12}\right)}$$

The previous two equations are of correct form

$$y = f_1(v)$$

and

$$y = f_2(x, u)$$

for type 5 nomogram. For compressing time axis (y -axis), we transform $y \rightarrow \log y$ and find

$$y = \log\left(\frac{\log\left(\frac{x}{x - \frac{p}{100 \times 12}}\right)}{\log\left(1 + \frac{p}{100 \times 12}\right)}\right)$$

$$y = \log(12n).$$

Left hand side of equation

Left hand side of equation


$$x = \frac{a}{A}$$

is just N-nomogram

$$F_1(u_1) = F_2(u_2)F_3(u_3)$$

References

10.1.2 Generated nomograph



10.1.3 Source code

```

1  """
2      ex_amortized_loan.py
3
4      Amortized loan calculator
5  """
6  import sys
7  sys.path.insert(0, "..")
8  from pynomo.nomographer import *
9
10 # Type 5 contour

```

```

11 def f1(x,u):
12     return log(log(x/(x-u/(100.0*12.0)))/log(1+u/(100.0*12.0)))
13
14 block1_params={
15     'width':10.0,
16     'height':5.0,
17     'block_type':'type_5',
18     'u_func':lambda u:log(u*12.0),
19     'v_func':f1,
20     'u_values':[10.0,11.0,12.0,13.0,14.0,15.0,20.0,25.0,30.0,40.0,50.0,60.0],
21     'v_values':[1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0,9.0,10.0],
22     'wd_tag':'A',
23     'u_title':'years',
24     'v_title':r'interest rate = ',
25     'u_text_format':r"$%3.0f$ ",
26     'v_text_format':r"$%3.0f$ \%% ",
27     'isopleth_values':[[21,5,'x']]
28 }
29
30 # this is non-obvious trick to find bottom edge coordinates of the grid in order
31 # to align it with N nomogram
32 block1_dummy=Nomo_Block_Type_5(mirror_x=False)
33 block1_dummy.define_block(block1_params)
34 block1_dummy.set_block()
35
36 # Let's define the N-nomogram
37 N_params_3={
38     'u_min':block1_dummy.grid_box.params_wd['u_min'],
39     'u_max':block1_dummy.grid_box.params_wd['u_max'],
40     'function':lambda u:u,
41     'title':'',
42     'tag':'A',
43     'tick_side':'right',
44     'tick_levels':2,
45     'tick_text_levels':2,
46     'reference':False,
47     'tick_levels':0,
48     'tick_text_levels':0,
49     'title_draw_center':True
50 }
51 N_params_2={
52     'u_min':30.0,
53     'u_max':1000.0,
54     'function':lambda u:u,
55     'title':'Loan',
56     'tag':'none',
57     'tick_side':'left',
58     'tick_levels':4,
59     'tick_text_levels':3,
60     'title_draw_center':True,
61     #'text_format':r"$%3.0f$ ",
62     'scale_type':'linear smart',
63 }
64 N_params_1={
65     'u_min':0.2,
66     'u_max':3.0,
67     'function':lambda u:u,
68     'title':'monthly payment',
69     'tag':'none',
70     'tick_side':'right',
71     'tick_levels':3,
72     'tick_text_levels':2,
73     'title_draw_center':True
74 }
75
76 block2_params={
77     'block_type':'type_2',
78     'width':10.0,
79     'height':20.0,
80     'f1_params':N_params_1,
81     'f2_params':N_params_2,
82     'f3_params':N_params_3,

```



```

83     'isopleth_values':[['x',200,'x']]
84     }
85
86 main_params={
87     'filename':'amortized_loan.pdf',
88     'paper_height':20.0,
89     'paper_width':20.0,
90     'block_params':[block_1_params,block_2_params],
91     'transformations':[('rotate',0.01),('scale paper',)],
92     'title_str':r'Amortized loan calculator \copyright Leif Roschier 2009',
93     'title_x': 17,
94     'title_y': 21,
95     'title_box_width': 5
96     }
97 Nomographer(main_params)

```

10.2 Example Photography exposure

10.2.1 Theory and background

This example illustrates how exposure in photography depends on factors: latitude, time of day, day of year, weather, composition. It relates these to camera settings: film speed (e.g. ISO 100), aperture and shutter speed. The mathematical approach and model is taken from book written by V. Setälä. [\[1\]](#) This book illustrates the approach as nomographs but they are different compared with the one generated here. Book uses shadow length, but we break shadow length into time, date and latitude via solar zenith angle.

The basic equation in Setälä (pp.492-494) can be extracted and written as

$$FS - L - A - W + C + T = 0 \quad (10.1)$$

where parameters of (10.1) are listed below:

FS	Film speed	DIN value that equals $10 \log(S) + 1$, where S is ISO FILM speed
T	shutter time	$10 \log \left(\frac{t}{1/10} \right)$
A	aperture	$10 \log \left(\frac{N^2}{3.2^2} \right)$
L	shadow length (in steps)	two times (shadow length)/(person length) = $2 \arctan(\phi)$, where ϕ is solar zenith angle.
W	weather	Clear sky, Cumulus clouds: 0, Clear sky: 1, Sun through clouds: 3, Sky light gray: 6, Sky dark gray: 9, Thunder-clouds cover sky: 12
C	Composi-tion	Person under trees: -6, Inside forest : -4, Person in shadow of wall : -1, Person at open place; alley under trees : 2, Buildings; street : 5, Landscape and front matter : 7, Open landscape : 9, Snow landscape and front matter; beach : 11, Snow field; open sea : 13, Clouds : 15

It is to be noted that Setälä has stops ten times base-10 logarithmic. Today we think stops in base-2 logarithmic.

Shadow length

Calculation of shadow length as a function of day of year, time of day and latitude is according to [\[2\]](#). Following equations are used. For fractional year (without time information) we take

$$\gamma = (day - 1 + 0.5)2\pi/365.$$

For time offset (eqtime) we use equation (in minutes)

$$TO = 229.18(0.000075 + 0.001868 \cos(\gamma) - 0.032077 \sin(\gamma) - 0.014615 \cos(2\gamma) - 0.040849 \sin(2\gamma))$$

to calculate that error is below 17 minutes for time axis. We assume that sun is at highest point at noon and this is the error and approximation. We calculate stops in logarithmic scale and in this case we do not need very accurate equations for time. For declination we use equation

and for hour angle

$$ha = (60h + \overline{TO})/4 - 180.$$

Solar zenith angle (ϕ), latitude (LAT), declination (D) and hour angle (ha) are connected with equation:

$$\cos(\phi) = \sin(LAT)\sin(D) + \cos(LAT)\cos(D)\cos(ha).$$

This is in our desired form as a function of hour (h), day (day), latitude (LAT), solar zenith angle (ϕ):

$$\cos(\phi) = \sin(LAT)\sin(D(\gamma(day))) + \cos(LAT)\cos(D(\gamma(day)))\cos(ha(h)).$$

In practice illuminance of flat surface on earth depends on solar zenith angle as $\cos(\phi)$. Setälä uses shadow length that is easily measurable, but scales incorrectly, as value is proportional to $\tan(\phi)$. Also Setälä sums linear value with logarithmic ones as a practical approximation. To correct these assumptions, here we assume that values for shadow length 1 and 10 for Setälä are reasonable, and an equation that scales logarithmically is found:

$$L = 0.33766 - 13.656 \log_{10}(\cos(\phi))$$

that gives $L = 1$ for $\phi = 26.565 = \arctan(1/2)$ and $L = 10$ for $\phi = 78.69 = \arctan(10/2)$.

10.2.2 Construction of the nomograph

The presented equation is the following:

$$FS - \{0.33766 - 13.656 \log_{10}[\sin(LAT)\sin(D(\gamma(day))) + \cos(LAT)\cos(D(\gamma(day)))\cos(ha(h))]\} \\ - A - W + C + T = 0.$$

In order to construct the nomograph, we split the equation into four blocks and an additional block to present values as EV100.


Table 10.1: Main equation split into blocks for the nomograph.

Explanation	Type
$x_1 \equiv \cos(\phi) = \sin(LAT) \sin(D(\gamma(day))) + \cos(LAT) \cos(D(\gamma(day))) \cos(ha(h))$ <p>formed into determinant:</p> $\begin{vmatrix} 0 & \cos(\phi) & 1 \\ \frac{\cos(LAT) \cos(D(\gamma(day)))}{1 + (\cos(LAT) \cos(D(\gamma(day))))} & \frac{\sin(LAT) \sin(D(\gamma(day)))}{1 + (\cos(LAT) \cos(D(\gamma(day))))} & 1 \\ 1 & -\cos(ha(h)) & 1 \end{vmatrix} = 0$	Type 9
$C_1 \equiv L + W = 0.006918 - 13.656 \log_{10}(x_1) + W$ <p>split into two equations for contour construction:</p> $y_1 = C_1$ $y_1 = 0.006918 - 13.656 \log_{10}(x_1) + W$	Type 5
$C_2 \equiv L + W + C = C_1 + C$ <p>split into two equations for contour construction:</p> $y_2 = C_2$ $y_2 = C_1 + C$	Type 5
$C_2 = FS - A + T$ <p>equals</p> $C_2 - (10 \log_{10}(S) + 1.0) + 10 \log_{10} \left(\frac{N^2}{3.2^2} \right) - 10 \log_{10} \left(\frac{1/t_i}{1/10} \right) = 0,$ <p>where</p> $t_i \equiv 1/t$ <p>is inverse shutter time.</p>	Type 3
Continued on next page	

Table 10.1 – continued from previous page

Explanation	Type
<p>Additional EV100 scale by using relation</p> $C_2 = (-EV_{100} + 13.654)/0.3322$	Type 8
<p>Maximum focal length calculator according to equation</p> $t_i/f = FL$ <p>written as</p> $-10 \log_{10} \left(\frac{1/t_i}{1/10} \right) - 10 \log_{10} \left(\frac{f}{10} \right) - 10 \log_{10} (FL) = 0$ <p>in order to align correctly with previous equation. The values for the factor f are: DSLR (3/2), 35mm (1), DSLR image stabilization (3/8) and 35mm image stabilization (1/8).</p>	Type 1

10.2.3 Generated nomograph



10.2.4 Source code

```

1  """
2      ex_photo_exposure.py
3
4      Photograph exposure.
5  """
6  import sys
7  sys.path.insert(0, "..")
8  from pynomo.nomographer import *
9  """
10 functions for solartime taken from solareqns.pdf from
11 http://www.srrb.noaa.gov/highlights/sunrise/solareqns.PDF
12 """
13
14
15 # fractional year
16 def gamma(day):
17     return 2 * pi / 365.0 * (day - 1 + 0.5)
18 # equation of time
19
20
21 def eq_time(day):
22     gamma0 = gamma(day)
23     return 229.18 * (0.000075 + 0.001868 * cos(gamma0) - 0.032077 * sin(gamma0)\
24         - 0.014615 * cos(2 * gamma0) - 0.040849 * sin(2 * gamma0))

```

```
25
26 # mean correction, with constant correction we make less than 17 minutes error
27 # in time axis
28 temp_a = arange(0, 365.0, 0.1)
29 temp_b = eq_time(temp_a)
30 correction = mean(temp_b) # this is 0.0171885 minutes
31
32
33 # declination
34 def eq_declination(day):
35     g0 = gamma(day)
36     return 0.006918 - 0.399912 * cos(g0) + 0.070257 * sin(g0) - 0.006758 * cos(2 * g0)\
37           + 0.000907 * sin(2 * g0) - 0.002697 * cos(3 * g0) + 0.00148 * sin(3 * g0)
38
39
40 def f1(dummy):
41     return 0.0
42
43
44 def g1(fii):
45     return cos(fii*pi/180.0)
46
47
48 def f2(lat, day):
49     dec = eq_declination(day)
50     return (cos(lat * pi / 180.0) * cos(dec)) / (1.0 + (cos(lat * pi / 180.0) * cos(dec)))
51
52
53 def g2(lat, day):
54     dec = eq_declination(day) # in radians
55     return (sin(lat * pi / 180.0) * sin(dec)) / (1.0 + (cos(lat * pi / 180.0) * cos(dec)))
56
57
58 def f3(dummy):
59     return 1
60
61
62 def g3(h):
63     hr = (h * 60.0 + correction) / 4.0 - 180.0
64     return -1.0 * cos(hr * pi / 180.0)
65
66 days_in_month = (31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30, 31)
67 times1=[]
68 for idx in range(0, 12):
69     times1.append(sum(days_in_month[0:idx])+1)
70
71 time_titles = ['January', 'February', 'March', 'April', 'May', 'June',
72               'July', 'August', 'September', 'October', 'November', 'December']
73
74 phi_params = {'u_min': 0.0,
75               'u_max': 90.0,
76               'u_min_trafo': 0.0,
77               'u_max_trafo': 90.0,
78               'f': f1,
79               'g': g1,
80               'h': lambda u: 1.0,
81               'title': r'Solar zenith angle $\phi$',
82               'title_x_shift': 0.0,
83               'title_y_shift': 0.25,
84               'scale_type': 'linear smart',
85               'tick_levels': 4,
86               'tick_text_levels': 2,
87               'tick_side': 'right',
88               'tag': 'phi',
89               'grid': False,
90               }
91 time_params = {'u_min': 0.0,
92               'u_max': 23.0,
93               'u_min_trafo': 0.0,
94               'u_max_trafo': 12.0,
95               'f': f3,
96               'g': g3,
97               'h': lambda u: 1.0,
```

```

98         'title': r'Hour (h)',
99         'title_x_shift': 0.0,
100        'title_y_shift': 0.25,
101        'scale_type': 'linear',
102        'tick_levels': 2,
103        'tick_text_levels': 1,
104        'tick_side': 'right',
105        'tag': 'none',
106        'grid': False,
107    }
108    lat_day_params = {'ID': 'none', # to identify the axis
109                     'tag': 'none', # for aligning block wrt others
110                     'title': 'Grid',
111                     'title_x_shift': 0.0,
112                     'title_y_shift': 0.25,
113                     'title_distance_center': 0.5,
114                     'title_opposite_tick': True,
115                     'u_min': 20.0, # for alignment
116                     'u_max': 80.0, # for alignment
117                     'f_grid': f2,
118                     'g_grid': g2,
119                     'h_grid': lambda u, v: 1.0,
120                     'u_start': 30.0,
121                     'u_stop': 80.0,
122                     'v_start': times1[0], # day
123                     'v_stop': times1[-1],
124                     'u_values': [30.0, 40.0, 50.0, 60.0, 70.0, 80.0],
125                     'u_texts': ['30', '40', '50', 'Latitude = 60', '70', '80'],
126                     'v_values': times1,
127                     'v_texts': time_titles,
128                     'grid': True,
129                     'text_prefix_u': r'',
130                     'text_prefix_v': r'',
131                     'text_distance': 0.5,
132                     'v_texts_u_start': False,
133                     'v_texts_u_stop': True,
134                     'u_texts_v_start': False,
135                     'u_texts_v_stop': True,
136                 }
137    block_params = {'block_type': 'type_9',
138                   'f1_params': phi_params,
139                   'f2_params': lat_day_params,
140                   'f3_params': time_params,
141                   'transform_ini': True,
142                   'isopleth_values': [['x', [60, times1[4]], 14.0]]
143    }
144
145    # limiting functions are to avoid NaN in contour construction that uses optimization
146    def limit_xx(x):
147        x1 = x
148        return x1
149
150
151    def limit_x(x):
152        x1 = x
153        return x1
154
155    const_A = 0.33766
156    const_B = -13.656
157
158    block_params_weather = {'block_type': 'type_5',
159                           'u_func': lambda u: u,
160                           'v_func': lambda x, v: const_A + const_B * log10(limit_x(x)) + v,
161                           'u_values': [1.0, 25.0],
162                           'u_manual_axis_data': {1.0: '',
163                                                  25.0: ''},
164                           'v_values': [0.0, 1.0, 3.0, 6.0, 9.0, 12.0],
165                           'v_manual_axis_data': {0.0: ['Clear sky, Cumulus clouds',
166                                                         {'x_corr': 0.5,
167                                                          'y_corr': 0.0,
168                                                          'draw_line': False}],
169    }

```

```

170         1.0: 'Clear sky',
171         3.0: 'Sun through clouds',
172         6.0: 'Sky light gray',
173         9.0: 'Sky dark gray',
174         12.0: 'Thunder-clouds cover sky'},
175     'v_text_distance': 0.5,
176     'wd_tick_levels': 0,
177     'wd_tick_text_levels': 0,
178     'wd_tick_side': 'right',
179     'wd_title': '',
180     'manual_x_scale': True,
181     'x_min': 0.06,
182     'x_max': 0.99,
183     'u_title': '',
184     'v_title': '',
185     'wd_title_opposite_tick': True,
186     'wd_title_distance_center': 2.5,
187     'wd_align_func': lambda L: acos(limit_xx(10.0**((L - const_A) / const_B))) * 180.0 / pi, # phi as L
188     'wd_func': lambda L: 10.0**((L - const_A) / const_B), # x as L
189     'wd_func_inv': lambda x: const_A+const_B * log10(x), # L as x
190     'wd_tag': 'phi',
191     'mirror_y': True,
192     'mirror_x': False,
193     'width': 10.0,
194     'height': 10.0,
195     'u_scale_opposite': True,
196     'u_tag': 'AA',
197     'horizontal_guides': True,
198     'isopleth_values': [['x', 9.0, 'x']],
199 }
200 block_params_scene = {'block_type': 'type_5',
201     'u_func': lambda u: u,
202     'v_func': lambda x, v: x + v,
203     'u_values': [1.0, 25.0],
204     'u_manual_axis_data': {1.0: '',
205         25.0: ''},
206     'u_tag': 'AA',
207     'wd_tag': 'EV',
208     'v_values': [-4.0, -1.0, 2.0, 5.0, 7.0, 9.0, 11.0, 13.0, 15.0],
209     'v_manual_axis_data': {-6.0: 'Person under trees',
210         -4.0: 'Inside forest',
211         -1.0: 'Person in shadow of wall',
212         2.0: 'Person at open place; alley under trees',
213         5.0: 'Buildings; street',
214         7.0: 'Landscape and front matter',
215         9.0: 'Open landscape',
216         11.0: 'Snow landscape and front matter; beach',
217         13.0: 'Snow field; open sea',
218         15.0: 'Clouds',
219     },
220     'wd_tick_levels': 0,
221     'wd_tick_text_levels': 0,
222     'wd_tick_side': 'right',
223     'wd_title': '',
224     'u_title': '',
225     'v_title': '',
226     'wd_title_opposite_tick': True,
227     'wd_title_distance_center': 2.5,
228     'mirror_x': True,
229     'horizontal_guides': True,
230     'u_align_y_offset': -0.9,
231     'isopleth_values': [['x', 2.0, 'x']],
232 }
233 camera_params_1 = {'u_min': -10.0,
234     'u_max': 15.0,
235     'function': lambda u: u,
236     'title': 'r',
237     'tick_levels': 0,
238     'tick_text_levels': 0,
239     'tag': 'EV',
240 }
241 camera_params_2 = {'u_min': 10.0,

```



```

242     'u_max': 25600.0,
243     'function': lambda S: -(10 * log10(S) + 1.0),
244     'title': r'Film speed',
245     'manual_axis_data': {10.0: 'ISO 10',
246                          20.0: 'ISO 20',
247                          50.0: 'ISO 50',
248                          100.0: 'ISO 100',
249                          200.0: 'ISO 200',
250                          400.0: 'ISO 400',
251                          800.0: 'ISO 800',
252                          1600.0: 'ISO 1600',
253                          3200.0: 'ISO 3200',
254                          6400.0: 'ISO 6400',
255                          12800.0: 'ISO 12800',
256                          25600.0: 'ISO 25600',
257                      },
258     'scale_type': 'manual line'
259 }
260 camera_params_3 = {'u_min': 0.1,
261                   'u_max': 10000.0,
262                   'function': lambda t: -10 * log10((1.0 / t) / (1.0 / 10.0)) - 30,
263                   'manual_axis_data': {1/10.0: '10',
264                                         1/7.0: '7',
265                                         1/5.0: '5',
266                                         1/3.0: '3',
267                                         1/2.0: '2',
268                                         1.0: '1',
269                                         2.0: '1/2',
270                                         3.0: '1/3',
271                                         5.0: '1/5',
272                                         7.0: '1/7',
273                                         10.0: '1/10',
274                                         20.0: '1/20',
275                                         30.0: '1/30',
276                                         50.0: '1/50',
277                                         70.0: '1/70',
278                                         100.0: '1/100',
279                                         200.0: '1/200',
280                                         300.0: '1/300',
281                                         500.0: '1/500',
282                                         700.0: '1/700',
283                                         1000.0: '1/1000',
284                                         2000.0: '1/2000',
285                                         3000.0: '1/3000',
286                                         5000.0: '1/5000',
287                                         7000.0: '1/7000',
288                                         10000.0: '1/10000',
289                                     },
290                   'scale_type': 'manual line',
291                   'title': r't (s)',
292                   'text_format': r"%3.0f s",
293                   'tag': 'shutter',
294                   'tick_side': 'left',
295                   }
296 camera_params_4 = {'u_min': 1.0,
297                   'u_max': 22.0,
298                   'function': lambda N: 10 * log10((N / 3.2)**2) + 30,
299                   'manual_axis_data': {1.0: '$f$/1',
300                                         1.2: '$f$/1.2',
301                                         1.4: '$f$/1.4',
302                                         1.7: '$f$/1.7',
303                                         2.0: '$f$/2',
304                                         2.4: '$f$/2.4',
305                                         2.8: '$f$/2.8',
306                                         3.3: '$f$/3.3',
307                                         4.0: '$f$/4',
308                                         4.8: '$f$/4.8',
309                                         5.6: '$f$/5.6',
310                                         6.7: '$f$/6.7',
311                                         8.0: '$f$/8',
312                                         9.5: '$f$/9.5',
313                                         11.0: '$f$/11',

```

```

314             13.0 : '$f$/13',
315             16.0 : '$f$/16',
316             19.0 : '$f$/19',
317             22.0 : '$f$/22',
318         },
319         'scale_type': 'manual line',
320         'title': r'Aperture',
321     }
322 block_params_camera = {'block_type': 'type_3',
323                        'width': 10.0,
324                        'height': 10.0,
325                        'f_params': [camera_params_1, camera_params_2, camera_params_3,
326                                    camera_params_4],
327                        'mirror_x': True,
328                        'isopleth_values': [['x', 100.0, 'x', 4.0]],
329                        }
330
331
332 def old_EV(EV): # C2(EV100) in wiki
333     return (-EV + 13.654) / 0.3322
334
335 EV_para = {'tag': 'EV',
336            'u_min': 4.0,
337            'u_max': 19.0,
338            'function': lambda u: old_EV(u),
339            'title': r'EV$_{100}$',
340            'tick_levels': 1,
341            'tick_text_levels': 1,
342            'align_func': old_EV,
343            'title_x_shift': 0.5,
344            'tick_side': 'right',
345            }
346 EV_block = {'block_type': 'type_8',
347            'f_params': EV_para,
348            'isopleth_values': [['x']],
349            }
350 # maximum focal length
351 FL_t_para={'u_min': 0.1,
352            'u_max': 10000.0,
353            'function': lambda t:-10 * log10((1.0 / t) / (1.0 / 10.0)) - 30,
354            'scale_type': 'linear',
355            'tick_levels': 0,
356            'tick_text_levels': 0,
357            'title': r't (s)',
358            'text_format': r"1/%3.0f s",
359            'tag': 'shutter',
360            }
361 FL_factor_params_2 = {'u_min': 1.0/4.0,
362                       'u_max': 3.0/2.0,
363                       'function': lambda factor: -10 * log10(factor / 10.0) + 0,
364                       'title': r'Sensor, IS',
365                       'scale_type': 'manual point',
366                       'manual_axis_data': {1.0/(2.0/3.0): 'DSLR',
367                                           1.0/(1.0): '35mm',
368                                           1.0/(8.0/3.0): 'DSLR IS',
369                                           1.0/(4.0): '35mm IS',
370                                           },
371                       'tick_side': 'left',
372                       'text_size_manual': text.size.footnotesize, # pyx directive
373                       }
374 FL_fl_params = {'u_min': 20.0,
375                 'u_max': 1000.0,
376                 'function': lambda FL:-10 * log10(FL) + 30,
377                 'title': r'Max focal length',
378                 'tick_levels': 3,
379                 'tick_text_levels': 2,
380                 'tick_side': 'left',
381                 'scale_type': 'manual line',
382                 'manual_axis_data': {20.0: '20mm',
383                                     35.0: '35mm',
384                                     50.0: '50mm',
385                                     80.0: '80mm',

```

```

386         100.0: '100mm',
387         150.0: '150mm',
388         200.0: '200mm',
389         300.0: '300mm',
390         400.0: '400mm',
391         500.0: '500mm',
392         1000.0: '1000mm'}
393     }
394
395     FL_block_params = {'block_type': 'type_1',
396                       'width': 12.0,
397                       'height': 10.0,
398                       'f1_params': FL_t_para,
399                       'f2_params': FL_factor_params_2,
400                       'f3_params': FL_fl_params,
401                       'mirror_x': True,
402                       'proportion': 0.5,
403                       'isopleth_values': [['x', 1.0/(8.0/3.0), 'x']],
404                       }
405
406     main_params = {'filename': ['ex_photo_exposure.pdf', 'ex_photo_exposure.eps'],
407                  'paper_height': 35.0,
408                  'paper_width': 35.0,
409                  'block_params': [block_params, block_params_weather, block_params_scene,
410                                  block_params_camera, EV_block, FL_block_params],
411                  'transformations': [('rotate', 0.01), ('scale paper',)],
412                  'title_x': 7,
413                  'title_y': 34,
414                  'title_box_width': 10,
415                  'title_str': r'\LARGE Photography exposure (Setala 1940) \par \copyright Leif Roschier 2009 '
416                  }
417     Nomographer(main_params)

```


LITERATURE

11.1 List of relevant books

Todo

Here links to literature...

11.2 Sources in the web

Todo

Here links to web resources...

11.3 Scientific articles

Todo

Here links to peer-reviewed scientific articles related to nomography and some discussion why the link.

APPENDIX

12.1 Comparison of Nomogram to Computer Application

Characteristic	Computer	Nomogram
Hardware Requirements	Computer, specialized calculator, or smartphone	Any straightedge, pencil
Software Requirements	Application encapsulating the relevant relationships	Graphical representation of the relevant relationships
Infrastructure Requirements	Computing resources, perhaps Internet access; if smartphone, appropriate app	Ambient light
Energy Needs	Electrical outlet or batteries	Ambient light
Learning Curve	Knowing what to punch in, plus learning curve for software, hardware, and infrastructure	Knowing how to connect two points, and how to interpolate a point on a scale
Documentation	What documentation? Where?	Self-documenting
Tool Distribution	Likely Internet access	Single sheet of paper
Results Distribution	Need printer or Internet connection	Hand-carry or fax document
Cost	Variable	Cost of duplicating and transmitting a single page
Accuracy (decimal places)	As many as you want... if the software provides them	As many as you need... given the precision of the input
Speed: As fast as...	...your hardware	...you can draw a straight line
Sensitivity Analysis	Repeated data sets	Examination of graphic
Implicit Solution	Usually difficult or impossible	Automatic
Common Failure Mode	Punch in wrong numbers	Can't find glasses
Need to Calculate	None	None
Third World Use	Problematic depending on computing accessibility	Works so long as pencil and paper are available
GIGO Susceptibility	High; May be hard to detect	Garbage In is clearly documented
Permanence	Need a printer	Creates a written record as part of usage pattern

Continued on next page

Table 12.1 – continued from previous page

Characteristic	Computer	Nomogram
Trust Factor	Did the programmer get it right?	Did the nomographer get it right?
Communication	Single number output	Graphical interactivity
Pizzazz Factor	High: Very modern	Low: Old-fashioned slide-rule-like technology

CHAPTER THIRTEEN

LICENSE

PyNomo is open source and free software licensed under the GNU GPL Version 3.