

1 main — MIR Walkthrough

Purpose: TODO: Describe why this walkthrough exists

1.1 Source Context

```
fn main() {  
    let a = 42;  
    let mut b = &a;  
    b = &b;  
  
    assert!(*b == 42);  
}
```


1.2 Function Overview

- **Function:** main
- **Basic blocks:** 3
- **Return type:** ()
- **Notable properties:**
 - Contains panic path
 - Introduces borrows
 - Has conditional branches

1.3 Locals

Local	Type	Notes
0	()	Return place
1	i32	
2	&i32	
3	&&i32	
4	i32	
5	!	
6	&i32	

1.4 Control-Flow Overview



1.5 Basic Blocks

1.5.1 bb0 — entry

Entry point of the function.

MIR	Annotation
_1 = 42	Load constant
_2 = &_1	Shared borrow
_3 = &_2	Shared borrow

<code>_6 = copy_deref((*_3))</code>	
<code>_2 = _6</code>	Copy value
<code>_4 = (*_2)</code>	Copy value
<code>→ switch(move _4) [42→bb1; else→bb2]</code>	Branch on move _4

1.5.2 bb1 — return / success

Normal return path.

MIR	Annotation
<code>→ return</code>	Return from function

1.5.3 bb2 — panic path

Panic/diverging path.

MIR	Annotation
<code>→ _5 = panic([16 bytes])</code>	Call panic

1.6 Key Observations

TODO: Add bullet points summarizing what this MIR teaches

-
-

1.7 Takeaways

TODO: One or two sentences to generalize this example

