

# 1 main — MIR Walkthrough

**Purpose:** TODO: Describe why this walkthrough exists

## 1.1 Source Context

```
assert!(a + b == 4.7);  
  
let c:f64 = 3.5;  
let d:f64 = 1.2;  
  
assert!(c + d == 4.7);  
}
```


## 1.2 Function Overview

- **Function:** main
- **Basic blocks:** 5
- **Return type:** ()
- **Notable properties:**
  - Contains panic path
  - Has conditional branches

## 1.3 Locals

Local	Type	Notes
0	()	Return place
1	bool	
2	f32	
3	f32	
4	f32	
5	!	
6	bool	
7	f64	
8	f64	
9	f64	
10	!	

## 1.4 Control-Flow Overview



## 1.5 Basic Blocks

### 1.5.1 bb0 — entry

*Entry point of the function.*

MIR	Annotation
<code>_3 = 1080033280</code>	Load constant
<code>_4 = 1067030938</code>	Load constant
<code>_2 = move _3 + move _4</code>	Add operation
<code>_1 = move _2 == 1083598438</code>	Equal operation
<code>→ switch(move _1) [0→bb2; else→bb1]</code>	Branch on move _1

### 1.5.2 bb1 — branch point

MIR	Annotation
<code>_8 = 4615063718147915776</code>	Load constant
<code>_9 = 4608083138725491507</code>	Load constant
<code>_7 = move _8 + move _9</code>	Add operation
<code>_6 = move _7 == 4616977747989548237</code>	Equal operation
<code>→ switch(move _6) [0→bb4; else→bb3]</code>	Branch on move _6

### 1.5.3 bb2 — panic path

*Panic/diverging path.*

MIR	Annotation
<code>→ _5 = panic([16 bytes])</code>	Call panic

### 1.5.4 bb3 — return / success

*Normal return path.*

MIR	Annotation
<code>→ return</code>	Return from function

### 1.5.5 bb4 — panic path

*Panic/diverging path.*

MIR	Annotation
<code>→ _10 = panic([16 bytes])</code>	Call panic

## 1.6 Key Observations

TODO: Add bullet points summarizing what this MIR teaches

- 
- 

## 1.7 Takeaways

TODO: One or two sentences to generalize this example

