

1.	You are given a dummy headed doubly singly linked list containing an odd number of nodes (excluding the dummy head). Write a function that will place the node with minimum value at the middle of the linked list. The relative order of other elements will remain unchanged. <i>You are not allowed to change the value of any node or use any auxiliary data structures or create a separate list.</i> <table><tr><td>Input: dh↔5↔4↔3↔8↔6↔1↔2</td><td>Output: dh↔5↔4↔3↔1↔8↔6↔2 <i>[minimum value 1 is placed at the middle of the linked list]</i></td></tr></table>	Input: dh↔5↔4↔3↔8↔6↔1↔2	Output: dh↔5↔4↔3↔1↔8↔6↔2 <i>[minimum value 1 is placed at the middle of the linked list]</i>	[12]
Input: dh↔5↔4↔3↔8↔6↔1↔2	Output: dh↔5↔4↔3↔1↔8↔6↔2 <i>[minimum value 1 is placed at the middle of the linked list]</i>			
2.	Consider a 2D array with 7 rows and 15 columns. Determine the position of the 45 th element (zero-based index) when the array is traversed in row-major order.	[2]		
A. Row = 3, Column = 0 B. Row = 2, Column = 15 C. Row = 4, Column = 5 D. Row = 3, Column = 6				
3.	In an n×n two-dimensional array, how many elements satisfy the condition that the row index is smaller than or equal to the column index?	[2]		
A. n ² B. n(n-1)/2 C. n(n+1)/2 D. n/2				
4.	What is the time complexity of executing <i>the insert tail</i> operation m times to a dummy-headed doubly circular linked list containing n elements, where m<n?	[1]		
A. O(n) B. O(m) C. O(mn) D. O(n ²)				
5.	What is the time complexity of finding the tail of a singly circular linked list of n elements?	[1]		
A. O(1) B. O(logn) C. O(n) D. O(n ²)				