SPECIFICATION OF GAMMA-RAY BRACHYTHERAPY SOURCES



NCRP REPORT No. 41

SPECIFICATION OF GAMMA-RAY BRACHYTHERAPY SOURCES

Recommendations of the NATIONAL COUNCIL ON RADIATION PROTECTION AND MEASUREMENTS

Issued April 1, 1974
First Reprinting May 1, 1985

National Council on Radiation Protection and Measurements 7910 WOODMONT AVENUE / Bethesda, Md. 20814

Copyright © National Council on Radiation Protection and Measurements 1974

All rights reserved. This publication is protected by copyright. No part of this publication may be reproduced in any form or by any means, including photocopying, or utilized by any information storage and retrieval system without written permission from the copyright owner, except for brief quotation in critical articles or reviews.

Library of Congress Catalog Card Number 73-94306 International Standard Book Number 0-913392-23-5

Preface

This report of the National Council on Radiation Protection and Measurements (NCRP), successor to the National Committee on Radiation Protection and Measurements, is concerned with the specification of sealed sources of nuclides which emit gamma rays-sources useful in brachytherapy. The report resulted from the Council's belief that a single well-defined method for specifying the radionuclide in an encapsulated source would be advantageous for both the users and the suppliers of such sources. Presently, encapsulated radionuclides are being specified in terms of the activity of the radionuclide, in terms of the equivalent mass of radium, or in terms of the exposure rate at a specified distance from the source. This report examines each of these methods of specification and, on the basis of this examination, develops recommendations on the method of specification considered to be appropriate. Although the subject matter presented in this report is related to that found in NCRP Report No. 40, Protection Against Radiation From Brachytherapy Sources, this report's content is limited to the characteristics of the sources themselves rather than to a discussion of the way in which they may and should be used.

The present report was prepared by the Council's Scientific Committee 27 on Specification of Radium Substitutes. Serving on the Committee during the preparation of this report were:

MARVIN M. D. WILLIAMS, Chairman

11	cm	he	27.8
272	UIII	UE	70

Ivan M. Grotenhuis Antolin Raventos Robert J. Shalek

Consultants

John G. Beach
L. Thomas Dillman
Robert O. Gorson
John Hale
Robert Loevinger
Herbert M. Parker
Walter S. Snyder
Nagalingam Suntharalingam
Harold O. Wyckoff

The Council wishes to express its appreciation to the members and

iv / PREFACE

the consultants of the Committee for the time and effort devoted to the preparation of this report.

LAURISTON S. TAYLOR President, NCRP

Washington, D.C. December 15, 1973

Contents

Pre	eface	. ,												iii
1.	Introduct	ion	ι											1
2.	Present M													2
	2	.1	Spec	ifica	ition	in '	Tern	ns of	the	Act	ivity	of	the	
			Rad	ionu	elide	9								2
	2	.2	Spec	eifica	ition	in '	Γ erm	s of	the	Equi	vale	nt M	[ass	
			of R	adi	ım									3
	2	.3	Spec	eifice	ition	in I	lerm	s of	the l	Ехрс	sure	Rate	at	
			a Sr	ecif	ied I	Dista	nce							4
3.	Discussion	n												5
4.	Recomme	end	atior	18										6
ΑP	PENDIX A	4.	Data	a fo	r Se	elect	ed (Sam	ma-	Ray	Sou	ırces		8
ΑP	PENDIX E	3.	Defi	nitio	ons									Ć
Re	ferences													11
Th	e NCRP													12
NC	RP Report	s												18
	1													28

1. Introduction

Various encapsulated radionuclides that emit gamma rays (see Appendix A) are used in the same manner as, and frequently as substitutes for, radium sources in brachytherapy [1]. Except for radionuclides that emit low-energy gamma photons (approximately 0.1 MeV or less), the relative distribution of absorbed dose around such substitutes is frequently given with an accuracy sufficient for clinical purposes when the dose² distribution is calculated from available radium dosage tables [2, 3, 4, 5]. This is true for photons of energies greater than approximately 0.1 MeV because the inverse square relation rather than the attenuation of the radiation in tissue is the primary reason for dose rate reduction with distance. The dose distribution near the ends of the sources is uncertain for all radionuclides including radium. Because radium dosage tables have been available and used for many years, many radiation therapists wish to retain them to determine relative dose distribution produced by other radionuclides, provided this results in acceptable accuracy. However, calculation of absolute doses requires an appropriate quantitative specification of the particular brachytherapy source.

Suppliers of encapsulated radionuclides have used several methods to specify gamma-ray brachytherapy sources. The meaning, usefulness, and accuracy of the specification have not always been clear. A single well-defined method for specifying the sources would be advantageous for both the user and the supplier.

¹ Numbers in brackets indicate literature references listed on page 11.

²In this report the word "dose" is used as a synonym for the term "absorbed dose". Terms used in this report are defined in Appendix B.

2. Present Methods of Specification

Encapsulated gamma-ray therapy sources are being specified now in terms of activity of the radionuclide (usually in millicuries), in terms of the equivalent mass of radium (usually in milligrams), or in terms of the exposure rate at a specified distance in air from the source (usually in roentgens per hour at one meter).

2.1 Specification in Terms of the Activity of the Radionuclide

It often has been assumed that the exposure rate at any point in the vicinity of an encapsulated gamma-ray-emitting radionuclide, including radium, is proportional to the activity of the radionuclide and its specific gamma-ray constant.³ Although specification of gamma-ray brachytherapy sources in terms of activity has been and is being used, there are some problems associated with, and objections to, its use.

(1) The exposure rate may be reduced considerably because of self-attenuation in the radionuclide and attenuation in the wall of the container. These effects are taken into account when the mass of radium in a capsule is determined and in the selection of the numerical value of the specific gamma-ray constant for radium; also, they were taken into account when some radium dosage tables were calculated. Whether or

The International Commission on Radiation Units and Measurements has defined a new quantity, exposure rate constant, to replace specific gamma-ray constant [6]. The exposure rate constant includes the exposure rates from photons (of energies greater than a specified minimum) of the characteristic x rays and internal bremsstrahlung, in addition to the exposure rate from the gamma-rays. The specific gamma-ray constant includes only the latter. For encapsulated radio-nuclides the exposure rates from all three of these radiations will be modified by self-attenuation and by attenuation in the wall of the capsule; also, some low energy photons not included in the exposure rate constant may be important in dosage considerations. Hence, neither quantity may be entirely applicable to brachytherapy sources.

not these effects were taken into account when the activity of substituted radionuclides was determined has not always been specified. The filtration effect of the wall depends on the energies of the photons and the material and thickness of the wall of the capsule.

The exposure rate at a distance from the source may vary because the attenuation of the gamma rays in tissue from all radionuclides may not be the same due to differences in the energies of the photons.

Errors caused by these differences in attenuation are considered by some to be within acceptable limits for clinical purposes for a number of radionuclides [2, 3, 4, 5], but not by others [2, 7, 8].

- (2) There may be no standard source available for determining the activity of some radionuclides that may be used. The accuracy of the determination of the activity of such radionuclides may vary substantially from one supplier to another.
- (3) The activity of an encapsulated source can be determined by comparing the ionization produced by it with that from a standard source if the two sources are similarly encapsulated. If they are not similarly encapsulated, corrections will have to be made for the differences in self-attenuation and attenuation in the walls of the containers.
- (4) For clinical purposes the value of the exposure rate constant or the specific gamma-ray constant may not be entirely applicable or may not be known to a sufficient degree of accuracy for all radionuclides that may be used.

2.2 Specification in Terms of the Equivalent Mass of Radium

This method of specifying a radionuclide in a tube or needle would enable a therapist to use radium dosage tables. There are several reasons why this specification may not be satisfactory.

- (1) If the equivalent mass of radium of the substituted radionuclide is determined from the activity of the radionuclide and the ratio of the exposure rate constants or the specific gamma-ray constants of radium and the substituted radionuclide, the uncertainties discussed in Section 2.1 apply.
- (2) Occasionally the equivalent mass of radium has been determined with the same lead-walled ionization chamber used for radium comparisons. If the energies of the photons from the radium source and the substituted source are not the same, the chamber will respond differently to the two sources. Thus a one-milligram radium equivalent of the sub-

4 / 2. Present methods of specification

stituted source would not deliver the same dose in tissue as a one milligram source of radium.

2.3 Specification in Terms of the Exposure Rate at a Specified Distance

The International Commission on Radiation Units and Measurements recommends that high-activity gamma-beam sources, such as are used for gamma-beam therapy, be specified on the basis of an exposure rate at a stated reference point, defined as a point one meter from the front face of the source capsule [9]. A similar method would seem to be logical for specifying all encapsulated gamma-ray-emitting radionuclides used in therapy. Several attributes of the method are worthy of note.

- (1) The user is interested not in the activity of the encapsulated radionuclide but in the available exposure rates at distances of interest from the source. Such rates can be computed from the known exposure rate at a specified distance.
- (2) Methods of measuring exposure rates are well established [10]; such measurements can be made with an accuracy of about three percent and a precision of one percent or better.
- (3) The activity that a source appears to have, a specification which may be required by some regulatory agencies, can be determined by dividing the exposure rate at a specified distance from the source by that for a unit of activity of the radionuclide with the same filtration and at the same distance.
- (4) If it is desired to know an "effective" equivalent mass of radium (encapsulated in a container with a specified wall thickness) for a radionuclide in a source, it can be determined by dividing the exposure rate at a specified distance from the capsule by the exposure rate at the same distance from a unit mass of radium (in a capsule with the specified wall thickness). Such an "effective" equivalent mass of radium can be used to calculate dose around the capsule by the use of standard radium dosage tables, if such calculated dose is sufficiently accurate for clinical purposes.

3. Discussion

The determination of the exposure rate at a specified distance from the source is most appropriately made with an air-equivalent ionization chamber; the material and thickness of the wall of the chamber would have to be appropriate for the energy of the gamma rays emitted by the particular radionuclide. If the ionization chamber is calibrated with a gamma-ray source such as radium or cobalt-60, with a known exposure rate at a specified distance, a correction factor may be required for gamma rays of other energies. (The correction factor depends on such parameters as the gamma-ray attenuation in the wall, the ratio of the electron stopping power of the wall of the ionization chamber to that of air, and the ratio of mass-energy-attenuation coefficients of the wall and of the center electrode to that of air.) Usually the variation of this correction factor with photon energies of interest will not exceed two or three percent. An apparatus for determining the exposure rate for gamma-beam therapy sources has been recommended by the International Commission on Radiation Units and Measurements [9]; this apparatus might be adapted for measurements of exposure rates for gamma-ray brachytherapy sources.

4. Recommendations

The specification of gamma-ray brachytherapy sources should⁴ be in terms of the exposure rate at one meter from, and perpendicular to, the long axis of the source at its center. This exposure rate may be computed from a measurement made at any convenient distance meeting the requirements of item 2 of the enumeration set out below. The units in which a source strength is specified then become R m² h⁻¹, or any suitable multiple of this unit. It is recommended that the source be measured with an ionization chamber which has been calibrated over the energy range of the gamma photons to be measured. This calibration may be made either by use of a suitable gamma-ray standard, or by having the ionization chamber itself calibrated in suitable beams. These calibrations should be directly traceable to the exposure standards maintained by the National Bureau of Standards⁵.

The supplier shall furnish a certificate which gives, for each source, the half-life and purity of the radionuclide, the dimensions of the source, the composition and thickness of the encapsulating material, the conditions of the measurement, and other information that may be needed by the user.

The exposure rate shall be determined thus:

- (1) By the use of an ionization chamber
 - a. with air equivalent response (or if not air equivalent, a proper correction shall be made); and
 - b. with walls of proper thickness to establish electronic equilibrium.
- (2) The distance between the source and the ionization chamber shall be great enough that the source can be considered to be a point source and the chamber a point detector; this distance shall be stated in the certificate.

*NCRP recommendations are expressed in terms of "shall" and "should". Shall indicates a recommendation that is necessary or essential to meet current accepted standards. Should indicates an advisory recommendation that is to be applied when practicable.

⁶ In this context, "directly traccable" means that there should be not more than one intermediate step between the calibration of the working instrument and the calibration at the National Bureau of Standards.

- (3) If the attenuation of the radiation in air is greater than one percent, a correction for attenuation shall be made and this correction shall be described in the certificate.
- (4) The measurement shall not include radiation scattered from the surroundings.
- (5) The accuracy of the measurement should be within \pm 3 percent and shall be within \pm 5 percent (with 95 percent confidence limits).
- (6) The precision of the measurement should be within ± 1 percent and shall be within ± 2 percent (with 95 percent confidence limits).
- (7) The time and date of the measurement shall be stated in the certificate.

APPENDIX A

Data for Selected Gamma-Ray Sources*

Radionuclide	Half-Life	Gamma Photons	Specific Gamma-Ray Constant ^b	Exposure Rate Constant ^b	
3.2		MeV	R cm² h-1 m Ci-1	R m ² h ⁻¹ Ci ⁻¹	
Cesium-137	30.0 years	0.6616	3.226	0.3275	
Chromium-51	27.72 days	0.3200	0.1842	0.01842	
Cobalt-60	5.26 years	1.173-1.322	13.07	1.307	
Gold-198	2.698 days	0.4118-1.0880	2.327	0.2376	
Iodine-125	60.25 days	0.03548	0.04228	0.1326	
Iridium-192	74.2 days	0.1363-1.062	3.948	0.4002	
Radium-226 with daughters	1604.0 years	0.0465-2.440°	9.068d	1.015	
Tantalum-182	115.0 days	0.0427-1.453°	7.692	0.7815	

^{*} Reference 11.

^b The specific gamma-ray constants and exposure rate constants were calculated from the latest decay-scheme data by L. T. Dillman. Contributions to these values from gamma photons and x rays of energies less than 11.3 keV have not been included. Dr. Dillman is a member of NCRP Scientific Committee 33 from which this information had been requested.

Minimum and maximum values of gamma photons included in the calculation of specific gamma-ray constant and exposure rate constant.

^d This value differs from the currently accepted value of 8.25 for radium because the value of 9.068 was calculated for no filtration. The value of 8.25 is for a filter of 0.5 mm platinum and includes such secondary radiations as may be generated in the platinum filter.

APPENDIX B

Definitions

absorbed dose: The mean energy imparted by ionizing radiati , to matter per unit of mass of irradiated material at the place of interest. See rad.

absorbed dose rate: Absorbed dose per unit time.

accuracy: The degree of correctness with which a method of measuring yields the "true" value of a measured quantity [12].

activity: The number of spontaneous nuclear transformations occurring in a given quantity of a radionuclide per unit time. See curic.

attenuation: The reduction of exposure rate resulting from the interposition of matter.

air equivalent response: The response of an ionization chamber to photons is said to be "air equivalent" over some stipulated energy interval if the calibration factor for the chamber can be considered to be constant.

brachytherapy: A method of radiation therapy in which an encapsulated source or a group of such sources is utilized to deliver gamma or beta radiation at a distance up to a few centimeters either by surface, intracavitary, or interstitial application.

curic (Ci): The special unit of activity equal to a nuclear transformation rate of 3.7×10^{10} per second (exactly).

dose: See absorbed dose.

dose rate: See absorbed dose rate.

electronic equilibrium: Electronic equilibrium exists when the total ionization in a volume is equal to the total ionization that would be produced by the corpuscular emission originating in that volume.

encapsulated source: A radionuclide sealed in a container such as a tube or needle for use in brachytherapy, or in a container for use in a teletherapy machine.

exposure: A measure of the ionization produced in air by x or gamma radiation. It is the sum of the electrical charges on all of the ions of one sign produced in air, when all electrons liberated by photons in a volume element of air are completely stopped in air, divided by the mass of the air in the volume element. See roentgen.

exposure rate: The exposure per unit time.

exposure rate constant: This quantity is similar to "specific gamma-ray constant", but includes the exposure rates from photons (of energies greater than a specified minimum) of the characteristic x rays and internal bremsstrahlung, in addition to the exposure rate from the gamma rays. A specific unit of exposure rate constant is R m² h-1 Ci-1 or any convenient multiple of this.

million electron volts (MeV): Energy equal to that acquired by a particle with one electronic charge in passing through a potential difference of one million volts (one MV).

millicurie (mCi): One-thousandth of a curie.

10 / APPENDIX B

nuclide: A species of atom having specified numbers of neutrons and protons in its nucleus [6].

precision: The degree of reproducibility among several independent measurements of a quantity.

radionuclide: A nuclide which is radioactive.

rad: The special unit of absorbed dose, equal to 0.01 joule per kilogram.

roentgen (R): The special unit of exposure, equal to 2.58 × 10⁻⁴ coulomb per kilogram (exactly).

shall: Shall indicates a recommendation that is necessary or essential to meet current accepted standards.

should: Should indicates an advisory recommendation that is to be applied when practicable.

specific gamma-ray constant: The exposure rate produced by the unfiltered gamma rays from a point source of a defined activity of a radionuclide at a defined distance. A common form of specific gamma-ray constant is the exposure per millicurie-hour at one centimeter, which has the units R cm² h⁻¹ mCi⁻¹. (The value for radium, 8.25 R per mg h at 1 cm, is obtained with a filter of 0.5 millimeter of platinum.)

stopping power: The stopping power of a material for a charged particle of specific energy is the energy loss per unit length of path.

References

- National Council on Radiation Protection and Measurements, Protection Against Radiation from Brachytherapy Sources, NCRP Report No. 40 (National Council on Radiation Protection and Measurements, Washington, 1972)
- SHALEK, R. J. AND STOVALL, M., "Dosimetry in implant therapy," page 743 in Radiation Dosimetry, 2nd ed., Vol. III, Attix, F. H. and Tochilin, E., Eds. (Academic Press, New York, 1969)
- Hale, J., "The use of interstitial radium dose rate tables for other radioactive isotopes," Am. J. Roentgenol., Radium Therapy and Nucl. Med. 79, 49 (1958)
- GROTENHUIS, I. M., HILGER, M. T. J. AND WALZ, R. N., "Experimental comparison of radium, cesium-137, and cobalt-60 tissue doses," Radiology 86, 145 (1966)
- MERIDITH, W. J., GREEN, D. AND KAWASHIMA, K., "The attenuation and scattering in a phantom of gamma rays from some radionuclides used in mould and interstitial gamma-ray therapy," Brit. J. Radiol. 39, 280 (1966)
- International Commission on Radiation Units and Measurements, Radiation Quantities and Units, ICRU Report 19 (International Commission on Radiation Units and Measurements, Washington, 1971)
- Suntharalingam, N. and Gorson, R. O., Jefferson Medical College, Philadelphia, Pennsylvania. Private communication (1969)
- 8. Krishnaswamy, V., "Dose distribution about cesium-137 sources in tissue," Radiology 105, 181 (1972)
- International Commission on Radiation Units and Measurements, Specification of High Activity Gamma-Ray Sources, ICRU Report 18 (International Commission on Radiation Units and Measurements, Washington, 1970)
- International Commission on Radiation Units and Measurements, ICRU Report 10b. Physical Aspects of Irradiation, NBS Handbook 85 (U.S. Government Printing Office, Washington, 1964)
- DILLMAN, L. T., Ohio Wesleyan University, Delaware, Ohio and Health Physics Division, Oak Ridge National Laboratory, Oak Ridge, Tennessee, Private communication (1973)
- The International Dictionary of Physics and Electronics (D. Van Nostrand Company, Inc., Princeton, New Jersey, 1956)

The NCRP

The National Council on Radiation Protection and Measurements is a nonprofit corporation chartered by Congress in 1964 to:

- 1. Collect, analyze, develop, and disseminate in the public interest information and recommendations about (a) protection against radiation and (b) radiation measurements, quantities, and units, particularly those concerned with radiation protection;
- Provide a means by which organizations concerned with the scientific and related aspects of radiation protection and of radiation quantities, units, and measurements may cooperate for effective utilization of their combined resources, and to stimulate the work of such organizations;
- 3. Develop basic concepts about radiation quantities, units, and measurements, about the application of these concepts, and about radiation protection;
- 4. Cooperate with the International Commission on Radiological Protection, the International Commission on Radiation Units and Measurements, and other national and international organizations, governmental and private, concerned with radiation quantities, units, and measurements and with radiation protection.

The Council is the successor to the unincorporated association of scientists known as the National Committee on Radiation Protection and Measurements and was formed to carry on the work begun by the Committee.

The Council is made up of the members and the participants who serve on the fifty-three Scientific Committees of the Council. The Scientific Committees, composed of experts having detailed knowledge and competence in the particular area of the Committee's interest, draft proposed recommendations. These are then submitted to the full membership of the Council for careful review and approval before being published.

The following comprise the current officers and membership of the Council:

Officers

President Vice President Secretary and Treasurer Assistant Secretary Assistant Treasurer LAURISTON S. TAYLOR E. DALE TROUT W. ROGER NEY EUGENE R. FIDELL HAROLD O. WYCKOFF

Members

SEYMOUR ABRAHAMSON EDWARD L. ALPEN VICTOR P. BOND ROBERT L. BRENT A. BERTRAND BRILL REYNOLD F. BROWN WILLIAM W. BURR, JR. LEO K. BUSTAD MELVIN W. CARTER GEORGE W. CASARETT RANDALL S. CASWELL RICHARD H. CHAMBERLAIN ARTHUR B. CHILTON CYRIL L. COMAR JAMES F. CROW MERRILL EISENBUD THOMAS S. ELY DONALD C. FLECKENSTEIN RICHARD F. FOSTER HYMER L. FRIEDELL ROBERT O. GORSON ELLIS M. HALL WILLIAM T. HAM, JR. JOHN H. HARLEY ROBERT J. HASTERLIK JOHN W. HEALY JOHN M. HESLEP MARYLOU INGRAM GEORGE V. LEROY EDWARD B. LEWIS CHARLES W. MAYS ROGER O. McCLELLAN ROBERT W. MILLER

DADE W. MOELLER KARL Z. MORGAN RUSSELL H. MORGAN PAUL E. MORROW ROBERT D. MOSELEY, JR. JAMES V. NEEL ROBERT J. NELSEN PETER C. NOWELL HERBERT M. PARKER LESTER ROGERS HARALD H. ROSSI ROBERT E. ROWLAND WILLIAM L. RUSSELL JOHN H. RUST EUGENE L. SAENGER HARRY F. SCHULTE RAYMOND SELTSER WARREN K. SINCLAIR WALTER S. SNYDER LEWIS V. SPENCER J. NEWELL STANNARD JOHN B. STORER LAURISTON S. TAYLOR JOHN H. TOLAN E. DALE TROUT ARTHUR C. UPTON JOHN C. VILLFORTH GEORGE L. VOELZ NIEL WALD EDWARD W. WEBSTER GEORGE M. WILKENING HAROLD O. WYCKOFF

Honorary Members

Carl B. Braestrup Austin M. Brues Charles L. Dunham Paul C. Hodges Edith H. Quimby Shields Warren

14 / THE NCRP

Currently, the following Scientific Committees are actively engaged in formulating recommendations:

- SC-1: Basic Radiation Protection Criteria
- SC-7: Monitoring Methods and Instruments
- SC-9: Medical X- and Gamma-Ray Protection up to 10 meV (Structural Shielding Design)
- SC-11: Incineration of Radioactive Waste
- SC-14: Radiological Factors Affecting Decision Making in a Nuclear Attack
- SC-18: Standards and Measurements of Radioactivity for Radiological Use
- SC-22: Radiation Shielding for Particle Accelerators
- SC-23: Radiation Hazards Resulting from the Release of Radionuclides into the Environment
- SC-24: Radionuclides and Labeled Organic Compounds Incorporated in Genetic Material
- SC-25: Radiation Protection in the Use of Small Neutron Generators
- SC-26: High Energy X-Ray Dosimetry
- SC-28: Radiation Exposure from Consumer Products
- SC-30: Physical and Biological Properties of Radionuclides
- SC-31: Selected Occupational Exposure Problems Arising from Internal Emitters
- SC-32: Administered Radioactivity
- SC-33: Dose Calculations
- SC-34: Maximum Permissible Concentrations for Occupational and Non-Occupational Exposures
- SC-35: Environmental Radiation Measurements
- SC-36: Tritium Measurement Techniques for Laboratory and Environmental Use
- SC-37: Procedures for the Management of Contaminated Persons
- SC-38: Waste Disposal
- SC-39: Microwaves
- SC-40: Biological Aspects of Radiation Protection Criteria
- SC-41: Radiation Resulting from Nuclear Power Generation
- SC-42: Industrial Applications of X Rays and Sealed Sources
- SC-43: Natural Background Radiation
- SC-44: Radiation Associated with Medical Examinations
- SC-45: Radiation Received by Radiation Employees
- SC-46: Operational Radiation Safety
- SC-47: Instrumentation for the Determination of Dose Equivalent
- SC-48: Apportionment of Radiation Exposure
- SC-49: Radiation Protection Guidance for Paramedical Personnel
- SC-50: Surface Contamination
- SC-51: Radiation Protection in Pediatric Radiology and Nuclear Medicine
 Applied to Children
- SC-52: Conceptual Basis of Calculations of Dose Distributions
- SC-53: Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Radiation

In recognition of its responsibility to facilitate and stimulate cooperation among organizations concerned with the scientific and related aspects of radiation protection and measurement, the Council has created a category of NCRP Collaborating Organizations. Organizations or groups of organizations which are national or international in scope and are concerned with scientific problems involving radiation quantities, units, measurements and effects, or radiation protection may be admitted to collaborating status by the Council. The present Collaborating Organizations with which the NCRP maintains liaison are as follows:

American Academy of Dermatology American Association of Physicists in Medicine American College of Radiology American Dental Association American Industrial Hygiene Association American Insurance Association American Medical Association American Nuclear Society American Podiatry Association American Public Health Association American Radium Society American Roentgen Ray Society American Society of Radiologic Technologists American Veterinary Medical Association Association of University Radiologists Atomic Industrial Forum Defense Civil Preparedness Agency Genetics Society of America Health Physics Society Industrial Medical Association National Bureau of Standards National Electrical Manufacturers Association Radiation Research Society Radiological Society of North America Society of Nuclear Medicine United States Air Force United States Army United States Atomic Energy Commission United States Navy United States Public Health Service

The NCRP has found its relationships with these organizations to be extremely valuable to continued progress in its program.

The Council's activities are made possible by the voluntary contribution of the time and effort of its members and participants and the generous support of the following organizations:

Alfred P. Sloan Foundation American Academy of Dental Radiology American Academy of Dermatology American Association of Physicists in Medicine American Collège of Radiology American College of Radiology Foundation American Dental Association American Industrial Hygiene Association American Insurance Association American Medical Association American Mutual Insurance Alliance American Nuclear Society American Osteopathic College of Radiology American Podiatry Association American Public Health Association American Radium Society American Roentgen Ray Society American Society of Radiologic Technologists American Veterinary Medical Association American Veterinary Radiology Society Association of University Radiologists Atomic Industrial Forum Battelle Memorial Institute College of American Pathologists Defense Civil Preparedness Agency Edward Mallinckrodt, Jr. Foundation Environmental Protection Agency Genetics Society of America Health Physics Society Industrial Medical Association James Picker Foundation National Bureau of Standards National Electrical Manufacturers Association Radiation Research Society Radiological Society of North America Society of Nuclear Medicine United States Atomic Energy Commission United States Public Health Service

To all of these organizations the Council expresses its profound appreciation for their support.

Initial funds for publication of NCRP reports were provided by a

grant from the James Picker Foundation and for this the Council wishes to express its deep appreciation.

The NCRP seeks to promulgate information and recommendations based on leading scientific judgment on matters of radiation protection and measurement and to foster cooperation among organizations concerned with these matters. These efforts are intended to serve the public interest and the Council welcomes comments and suggestions on its reports or activities from those interested in its work.

NCRP Publications

NCRP publications are distributed by the NCRP Publications' office. Information on prices and how to order may be obtained by directing an inquiry to:

NCRP Publications 7910 Woodmont Ave, Suite 1016 Bethesda, Md. 20814

The currently available publications are listed below.

Proceedings of the Annual Meeting

No.			Title		
1	D 1' (D'. 1	ъ		- C 41	D.0

- 1 Perceptions of Risk, Proceedings of the Fifteenth Annual Meeting, Held on March 14-15, 1979 (Including Taylor Lecture No. 3) (1980)
- Quantitative Risk in Standards Setting, Proceedings of the Sixteenth Annual Meeting Held on April 2-3, 1980 (Including Taylor Lecture No. 4) (1981)
- 3 Critical Issues in Setting Radiation Dose Limits, Proceedings of the Seventeenth Annual Meeting, Held on April 8-9, 1981 (Including Taylor Lecture No. 5) (1982)
- 4 Radiation Protection and New Medical Diagnostic Procedures, Proceedings of the Eighteenth Annual Meeting, Held on April 6-7, 1982 (Including Taylor Lecture No. 6) (1983)
- 5 Environmental Radioactivity, Proceedings of the Nineteenth Annual Meeting, Held on April 6-7, 1983 (Including Taylor Lecture No. 7) (1983)
- Some Issues Important in Developing Basic Radiation Protection Recommendations, Proceedings of the Twentieth Annual Meeting, Held on April 4-5, 1984 (Including Taylor Lecture No. 8) (1985).

Symposium Proceedings

The Control of Exposure of the Public to Ionizing Radiation in the Event of Accident or Attack, Proceedings of a Symposium held April 27-29, 1981 (1982)

Lauriston S. Taylor Lectures

No.	Title and Author
1	The Squares of the Natural Numbers in Radiation Protec- tion by Herbert M. Parker (1977)
2	Why be Quantitative About Radiation Risk Estimates? by Sir Edward Pochin (1978)
3	Radiation Protection—Concepts and Trade Offs by Hymer L. Friedell (1979) [Available also in Perceptions of Risk, see above]
4	From "Quantity of Radiation" and "Dose" to "Exposure" and "Absorbed Dose"—An Historical Review by Harold O. Wyckoff (1980) [Available also in Quantitative Risks in Standards Setting, see above]
5	How Well Can We Assess Genetic Risk? Not Very by James F. Crow (1981) [Available also in Critical Issues in Setting Radiation Dose Limits, see above]
6	Ethics, Trade-offs and Medical Radiation by Eugene L. Saenger (1982) [Available also in Radiation Protection and New Medical Diagnostic Approaches, see above]
7	The Human Environment-Past, Present and Future by Merril Eisenbud (1983) [Available also in Environmental Radioactivity, see above]
8	Limitation and Assessment in Radiation Protection by Harald H. Rossi (1984) [Available also in Some Issues Important in Developing Basic Radiation Protection Rec- ommendations, see above]
	NCRP Reports
No.	Title
8	Control and Removal of Radioactive Contamination in Lab- oratories (1951)
9	Recommendations for Waste Disposal of Phosphorus-32 and Iodine-131 for Medical Users (1951)

Recommendations for the Disposal of Carbon-14 Wastes

Maximum Permissible Body Burdens and Maximum Permissible Concentrations of Radionuclides in Air and in Water for Occupational Exposure (1959) [Includes Ad-

Radioactive Waste Disposal in the Ocean (1954)

dendum 1 issued in August 1963]

12

16

22

20 / NCRP REPORTS

- 23 Measurement of Neutron Flux and Spectra for Physical and Biological Applications (1960)
- 25 Measurement of Absorbed Dose of Neutrons and Mixtures of Neutrons and Gamma Rays (1961)
- 27 Stopping Powers for Use with Cavity Chambers (1961)
- 30 Safe Handling of Radioactive Materials (1964)
- 32 Radiation Protection in Educational Institutions (1966)
- 33 Medical X-Ray and Gamma-Ray Protection for Energies Up to 10 MeV—Equipment Design and Use (1968)
- 35 Dental X-Ray Protection (1970)
- 36 Radiation Protection in Veterinary Medicine (1970)
- 37 Precautions in the Management of Patients Who Have Received Therapeutic Amounts of Radionuclides (1970)
- 38 Protection against Neutron Radiation (1971)
- 39 Basic Radiation Protection Criteria (1971)
- 40 Protection Against Radiation from Brachytherapy Sources (1972)
- 41 Specification of Gamma-Ray Brachytherapy Sources (1974)
- 42 Radiological Factors Affecting Decision-Making in a Nuclear Attack (1974)
- 43 Review of the Current State of Radiation Protection Philosophy (1975)
- 44 Krypton-85 in the Atmosphere—Accumulation, Biological Significance, and Control Technology (1975)
- 45 Natural Background Radiation in the United States (1975)
- 46 Alpha-Emitting Particles in Lungs (1975)
- 47 Tritium Measurement Techniques (1976)
- 48 Radiation Protection for Medical and Allied Health Personnel (1976)
- 49 Structural Shielding Design and Evaluation for Medical Use of X Rays and Gamma Rays of Energies Up to 10 MeV (1976)
- 50 Environmental Radiation Measurements (1976)
- 51 Radiation Protection Design Guidelines for 0.1–100 MeV Particle Accelerator Facilities (1977)
- 52 Cesium-137 From the Environment to Man: Metabolism and Dose (1977)
- 53 Review of NCRP Radiation Dose Limit for Embryo and Fetus in Occuptionally Exposed Women (1977)
- 54 Medical Radiation Exposure of Pregnant and Potentially Pregnant Women (1977)
- 55 Protection of the Thyroid Gland in the Event of Releases of

- Radioiodine (1977)
- 56 Radiation Exposure From Consumer Products and Miscellaneous Sources (1977)
- 57 Instrumentation and Monitoring Methods for Radiation Protection (1978)
- 58 A Handbook of Radioactivity Measurements Procedures (1978)
- 59 Operational Radiation Safety Program (1978)
- 60 Physical, Chemical, and Biological Properties of Radiocerium Relevant to Radiation Protection Guidelines (1978)
- Radiation Safety Training Criteria for Industrial Radiography (1978)
- 62 Tritium in the Environment (1979)
- 63 Tritium and Other Radionuclide Labeled Organic Compounds Incorporated in Genetic Material (1979)
- Influence of Dose and Its Distribution in Time on Dose-Response Relationships for Low-LET Radiations (1980)
- 65 Management of Persons Accidentally Contaminated with Radionuclides (1980)
- 66 Mammography (1980)
- 67 Radiofrequency Electromagnetic Fields—Properties, Quantities and Units, Biophysical Interaction, and Measurements (1981)
- 68 Radiation Protection in Pediatric Radiology (1981)
- 69 Dosimetry of X-Ray and Gamma-Ray Beams for Radiation Therapy in the Energy Range 10 keV to 50 MeV (1981)
- 70 Nuclear Medicine-Factors Influencing the Choice and Use of Radionuclides in Diagnosis and Therapy (1982)
- 71 Operational Radiation Safety—Training (1983)
- 72 Radiation Protection and Measurement for Low Voltage Neutron Generators (1983)
- 73 Protection in Nuclear Medicine and Ultrasound Diagnostic Procedures in Children (1983)
- 74 Biological Effects of Ultrasound: Mechanisms and Clinical Implications (1983)
- 75 Iodine-129: Evaluation of Releases from Nuclear Power Generation (1983)
- 76 Radiological Assessment: Predicting the Transport, Bioaccumulation, and Uptake by Man of Radionuclides Released to the Environment (1984)
- 77 Exposures from the Uranium Series with Emphasis on Radon and its Daughters (1984)

22 / NCRP REPORTS

- 78 Evaluation of Occupational and Environmental Exposures to Radon and Radon Daughters in the United States (1984)
- 79 Neutron Contamination from Medical Electron Accelerators (1984)
- 80 Induction of Thyroid Cancer by Ionizing Radiation (1985)

Other Documents

The following documents of the NCRP were published outside of the NCRP Reports series:

- "Blood Counts, Statement of the National Committee on Radiation Protection," Radiology 63, 428 (1954)
- "Statements on Maximum Permissible Dose from Television Receivers and Maximum Permissible Dose to the Skin of the Whole Body," Am. J. Roentgenol., Radium Ther. and Nucl. Med. 84, 152 (1960) and Radiology 75, 122 (1960)
- X-Ray Protection Standards for Home Television Receivers, Interim Statement of the National Council on Radiation Protection and Measurements (National Council on Radiation Protection and Measurements, Washington, 1968)
- Specification of Units of Natural Uranium and Natural Thorium (National Council on Radiation Protection and Measurements, Washington, 1973)
- NCRP Statement on Dose Limit for Neutrons (National Council on Radiation Protection and Measurements, Washington, 1980)
- Krypton-85 in the Atmosphere—With Specific Reference to the Public Health Significance of the Proposed Controlled Release at Three Mile Island (National Council on Radiation Protection and Measurements, Washington, 1980)
- Preliminary Evaluation of Criteria For the Disposal of Transuranic Contaminated Waste (National Council on Radiation Protection and Measurements, Bethesda, Md, 1982)
- Control of Air Emissions of Radionuclides (National Council on Radiation Protection and Measurements, Bethesda, Md, 1984)

Copies of the statements published in journals may be consulted in libraries. A limited number of copies of the remaining documents listed above are available for distribution by NCRP Publications.

INDEX

Absorbed dose 9 Absorbed dose rate 9 Accuracy 9 Accuracy of measurements 3, 4, 7 Activity 2, 3, 4, 9 Determined by ionization methods 3 Determined from exposure rate at a	Exposure 9 Exposure rate 2, 3, 4, 5, 9 Exposure rate at a distance of one meter, recommended method of determination 6, 7 Exposure rate constant 2, 3, 8, 9
specified distance 4 Specification required by some regulatory agencies 4	Gold-198 8
Air-equivalent response 9	ICRU apparatus for exposure rate mea- surements 5
Attenuation 1, 2, 3, 9	lodine-125 8
	Ionization chambers 3, 5, 6
Brachytherapy 9	Air-equivalent 5
Brachytherapy gamma-ray sources 1, 5, 6,	Calibration of 5, 6
8 Data for selected sources 8	Correction factors for 5
Dita for selected sources g	For determining activity 3 For determining equivalent mass of
Certificate to be furnished by supplier 6	radium 3
Cesium-137 8	For determining exposure rates 5
Chromium-51 8	Lead-walled 3
Cobalt-60 5, 8	Material and thickness of wall of 5
Curie (Ci) 9	Recommended by ICRU 5 With air-equivalent response 6
Definitions 9, 10	Iridium-192 8
Dose 1, 4, 9	
Absolute 1	Methods of specifying radionuclide
Absorbed 1 From radium dosage tables 1, 3, 4	sources 1, 2, 3, 4, 6 Millicurie (mCi) 9
Near ends of sources 1	Million electron volts (MeV) 9
Dose rate 9	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	Nuclide 10
Electronic equilibrium 9	D :: 4 # 10
Encapsulated source 9 Equivalent mass of radium 2, 3, 4	Precision 4, 7, 10 Purity of radionuclide 6
Determined by activity and ratio of	I unity of factoride o
specific gamina-ray constants (or ex-	Rad 10
posure rate constants) 3	.Radionuclide 10
Determined by ionization methods 3	Radium (Radium-226) 1, 2, 3, 5, 8
Determined from exposure rate at a	Radium dosage tables 1, 2, 3, 4
specified distance 4	Recommendations 6, 7

24 / INDEX

References 11 Roentgen (R) 10

Shall 6, 10
Should 6, 10
Specific gamma-ray constant 2, 3, 10
Specification in terms of the activity of
the radionuclide 2

Specification in terms of the equivalent mass of radium 2, 3 Specification in terms of the exposure rate at a specified distance 2, 4 Stopping power 5, 10

Tantalum-182 8