GREATER VALUE IN 2 NUMBER

```
#include<stdio.h>
int main()
{
 int f,s;
 printf("Enter first number\n");
 scanf("%d",&f);
 printf("Enter second number\n");
 scanf("%d",&s);
 if(f>s)
 {
  printf("first no is greater");
 }
 if(f<s)
 {
  printf("second no is greater");
 }
 if(f==s)
 {
  printf("both are equal");
 }
}
```

GREATER VALUE IN THREE NUMBER

```
#include<stdio.h>
int main()
{
 int a,b,c;
 printf("Enter first number\n");
 scanf("%d",&a);
 printf("Enter second number\n");
 scanf("%d",&b);
 printf("Enter third number\n");
 scanf("%d",&c);
 if(a>b&&a>c)
 {
  printf("%d is greater",a);
 }
 if(b>a&&b>c)
 {
  printf("%d is greater",b);
 }
 if(c>a&&c>b)
 {
  printf("%d is greater",c);
 }
}
```

CHECK GIVEN NUMBER IS POSITIVE OR NEGATIVE OR ZERO

```
#include<stdio.h>
int main()
{
 int no;
 printf("Enter any number\n");
 scanf("%d",&no);
 if(no>0)
 {
  printf("no is positive");
 }
 if(no<0)
 {
  printf("no is negative");
 }
 if(no==0)
 {
  printf("no is zero");
 }
}
```

SHOW RESULT ACCORDING TO PERCENT

```
#include<stdio.h>
int main()
{
 float p;
 printf("Enter your percent\n");
 scanf("%f",&p);
 if(p<=100&&p>=60)
 {
  printf("First division");
 }
 if(p<60&&p>=45)
 {
  printf("Second division");
 }
 if(p<45&&p>=33)
 {
  printf("Third division");
 }
 if(p<33)
 {
  printf("Fail");
 }
}
```

EVEN ODD PROGRAM

```
#include<stdio.h>
int main()
{
 int no;
 printf("Enter any number\n");
 scanf("%d",&no);
 if(no%2==0)
 {
  printf("Even");
 }
 else
 {
  printf("Odd");
 }
}
```

VOTING PROGRAM

```
#include<stdio.h>
int main()
{
 int age;
 printf("Enter your age\n");
 scanf("%d",&age);
 if(age>=18)
 {
  printf("You are eligible for
voting");
 }
 else
 {
  printf("You are not eligible for
voting");
 }
}
```

CONSONENT OR VOWEL PROGRAM

```
#include<stdio.h>
int main()
{
 char ch;
 printf("Enter any alphabet\n");
 scanf("%c",&ch);

 if(ch=='a'||ch=='e'||ch=='i'||ch=='o'||
ch=='u')
 {
  printf("Vowel");
 }
 else
 {
 printf("Consonent");
 }
}
```

LOGIN PROGRAM

```
#include<stdio.h>
#include<string.h>
int main()
{
 char
u[200]="easy@gmail.com",p[200]=
"12345";
 char u1[200],p1[200];
 printf("Enter username\n");
 scanf("%s",&u1);
 printf("Enter password\n");
 scanf("%s",&p1);

if(strcmp(u,u1)==0&&strcmp(p,p1)
==0)
 {
 printf("Login Successful");
 }
 else
 {
 printf("Wrong username or
password");
 }

}
```

CHECK ALPHABET IS UPPERCASE OR LOWERCASE

```
#include<stdio.h>
#include<string.h>
int main()
{
 char ch;
 printf("Enter any alphabet\n");
 scanf("%c",&ch);
 if(ch>=65&&ch<=90)
 {
 printf("Uppercase");
 }
 else
 {
 printf("Lowercase");
 }


}
```

INPUT THREE ANGLE OF TRIANGLE AND CHECK TRIANGLE IS VALID OR NOT

```
#include<stdio.h>
#include<string.h>
int main()
{
 float a1,a2,a3;
 printf("Enter first angle\n");
 scanf("%f",&a1);
 printf("Enter second angle\n");
 scanf("%f",&a2);
 printf("Enter third angle\n");
 scanf("%f",&a3);
 if((a1+a2+a3)==180)
 {
 printf("Triangle is valid");
 }
 else
 {
 printf("Triangle is not valid");
 }

}
```

CALCULATE PROFIT AND LOSS

```
#include<stdio.h>
#include<string.h>
int main()
{
 float sp,cp,profit,loss;
 printf("Enter cost price\n");
 scanf("%f",&cp);
 printf("Enter selling price\n");
 scanf("%f",&sp);
 if(sp>cp)
 {
 profit=sp-cp;
 printf("Profit is %f rupee",profit);
 }
 else
 {
 loss=cp-sp;
 printf("Loss is %f rupee",loss);
 }

}
```

SHOW RESULT ACCORDING TO PERCENT USING IF ELSE

```
#include<stdio.h>
int main()
{
 float p;
 printf("Enter your percent\n");
 scanf("%f",&p);
 if(p>=60)
 {
  printf("First division");
 }
 else if(p>=45)
 {
  printf("Second division");
 }
 else if(p>=33)
 {
  printf("Third division");
 }
 else
 {
  printf("Fail");
 }
}
```

GREATER VALUE IN THREE NUMBER USING IF ELSE STATEMENT

```
#include<stdio.h>
int main()
{
 int a,b,c;
 printf("Enter first number\n");
 scanf("%d",&a);
 printf("Enter second number\n");
 scanf("%d",&b);
 printf("Enter third number\n");
 scanf("%d",&c);
 if(a>b&&a>c)
 {
  printf("%d is greater",a);
 }
 else if(b>a&&b>c)
 {
  printf("%d is greater",b);
 }
 else
 {
  printf("%d is greater",c);
 }
}
```

CHECK GIVEN CHARACTER IS ALPHABET OR DIGIT OR SPECIAL SYMBOL

```
#include<stdio.h>
int main()
{
 char ch;
 printf("Enter any character\n");
 scanf("%c",&ch);
 if(ch>=65&&ch<=97||
ch>=97&&ch<=122)
 {
 printf("It is alphabet");
 }
 else if(ch>=48&&ch<=57)
 {
 printf("It is digit");
 }
 else
 {
 printf("It is special symbol");
 }
}
```

GREATER VALUE IN THREE NUMBER USING IF ELSE STATEMENT

```
#include<stdio.h>
int main()
{
 int a,b,c;
 printf("Enter first number\n");
 scanf("%d",&a);
 printf("Enter second number\n");
 scanf("%d",&b);
 printf("Enter third number\n");
 scanf("%d",&c);
 if(a>b&&a>c)
 {
  printf("%d is greater",a);
 }
 else if(b>a&&b>c)
 {
  printf("%d is greater",b);
 }
 else
 {
  printf("%d is greater",c);
 }
}
```