

USACO Notebook

Benq

January 5, 2018

Contents

1 (0) Contest	2		
1.1 (0) C++ Template	2		
1.2 (0) FastScanner	2		
1.3 (0) Troubleshoot	3		
1.4 (6) Pragma Optimization	4		
2 (2) Data Structures	4		
2.1 (2) Range Queries, No Update	4		
2.1.1 (2) Prefix Sums	4		
2.1.2 (3) Range Minimum Query	4		
2.2 (2) STL	4		
2.2.1 (2) Coordinate Compression	4		
2.2.2 (2) Map Customization	4		
2.2.3 (3) Minimum Deque	5		
2.3 (3) Range Queries, Point Update	5		
2.3.1 (3) Binary Indexed Tree	5		
2.3.2 (3) SegTree Demo	5		
2.3.3 (3) SegTree	5		
2.3.4 (4) Sparse SegTree	6		
2.3.5 (5) Basic Persistent SegTree	6		
2.4 (4) 2D Range Queries	7		
2.4.1 (4) 2D BIT	7		
2.4.2 (4) 2D Demo	7		
2.4.3 (4) 2D SegBIT	7		
2.4.4 (4) 2D SegTree	8		
2.4.5 (4) Merge-Sort Tree	8		
2.5 (4) BBST	8		
2.5.1 (4) Treap	8		
2.5.2 (5) Link-Cut Tree	9		
2.5.3 (5) Splay Tree	10		
2.6 (4) Range Queries, Range Update	11		
2.6.1 (4) BIT with Range Update	11		
2.6.2 (4) Lazy SegTree Demo	11		
2.6.3 (4) Lazy SegTree	12		
2.6.4 (5) Lazy Persistent SegTree	12		
3 (2) Graphs	13		
3.1 (2) Searching Demo	13		
3.1.1 (2) BFS on Grid	13		
3.1.2 (2) DFS on Graph	13		
3.2 (3) Shortest Path	14		
3.2.1 (3) Bellman-Ford	14		
3.2.2 (3) Dijkstra	14		
3.2.3 (3) Floyd-Warshall	14		
3.3 (3) TopoSort + Related	15		
		3.3.1 (3) Topological Sort	15
		3.3.2 (4) Kosaraju	15
		3.3.3 (4) Tarjan BCC	15
		3.3.4 (4) Tarjan SCC	16
		3.4 (6) Euler Tour	16
4 (2) Paradigms	17		
4.1 (2) Binary Search	17		
4.2 (2) Interval Cover	17		
4.3 (4) Discrete Logarithm	17		
4.4 (4) Ternary Search	18		
5 (3) Dynamic Programming	18		
5.1 (3) Distinct Subsequences	18		
5.2 (3) Knapsack	18		
5.3 (3) Longest Common Subsequence	18		
5.4 (3) Longest Increasing Subsequence	18		
5.5 (4) Divide Conquer	19		
5.6 (4) Traveling Salesman	19		
6 (3) Strings	19		
6.1 (3) Hashing	19		
6.2 (4) String Searching	20		
6.2.1 (4) Aho-Corasick	20		
6.2.2 (4) Bitset Trie	21		
6.2.3 (4) Z	21		
6.3 (4) Suffix Array	21		
6.4 (5) Manacher	22		
7 (3) Trees	22		
7.1 (3) Kruskal	22		
7.2 (4) Tree Queries	23		
7.2.1 (4) Centroid Decomposition	23		
7.2.2 (4) Heavy Light Set	23		
7.2.3 (4) Heavy-Light Decomposition	23		
7.2.4 (4) LCA Demo	24		
7.2.5 (4) LCA with Binary Jumps	24		
7.2.6 (4) LCA with RMQ	25		
7.3 (5) Tree Diameter	25		
8 (4) Flows	25		
8.1 (5) Dinic	25		
8.2 (5) Flows Demo	26		
8.3 (5) Push-Relabel	26		
8.4 (6) MinCostFlow	27		

9	(4) Geometry	28
9.1	(4) Convex Hull	28
9.2	(4) MaxCollinear	28
9.3	(4) Pair Operators	28
9.4	(5) Line Segment Intersection	29
9.5	(5) Polygon Area	30
9.6	(6) 3D Geometry	30
9.7	(6) Circles	30
9.8	(6) Closest Pair	30
9.9	(6) Point in Polygon	31
10	(4) Math	31
10.1	(4) Matrix	31
10.1.1	(4) Matrix Exponentiation	31
10.1.2	(6) Linear Equation Solver	32
10.2	(4) Number Theory	32
10.2.1	(4) Eratosthenes' Sieve	32
10.2.2	(5) Chinese Remainder Theorem	33
10.2.3	(5) Combinations Basic	33
10.2.4	(5) Combinations Plus	34
10.2.5	(5) Phi	34
10.3	(6) Polynomials	34
10.3.1	(6) Base Conversion	34
10.3.2	(6) FFT	35
10.3.3	(6) NTT	35
11	(6) Sqrt Decomposition	36
11.1	(6) Mo	36

1 (0) Contest

1.1 (0) C++ Template

```

/**
 * Sources: various
 */

#include <bits/stdc++.h>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/assoc_container.hpp>

using namespace std;
using namespace __gnu_pbds;

typedef long long ll;
typedef vector<int> vi;
typedef pair<int, int> pii;
template <class T> using Tree = tree<T, null_type,
    less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

#define FOR(i, a, b) for (int i=a; i<(b); i++)
#define FOR(i, a) for (int i=0; i<(a); i++)
#define FORd(i,a,b) for (int i = (b)-1; i >= a; i--)
#define FORd(i,a) for (int i = (a)-1; i >= 0; i--)

#define sz(x) (int)(x).size()
#define mp make_pair

```

```

#define pb push_back
#define f first
#define s second
#define lb lower_bound
#define ub upper_bound
#define all(x) x.begin(), x.end()

const int MOD = 1000000007;

int main() {
    ios_base::sync_with_stdio(0);cin.tie(0);

}

// read!read!read!read!read!read!read!
// ll vs. int!

```

1.2 (0) FastScanner

```

/**
 * Source: Matt Fontaine
 */

class FastScanner {
    private InputStream stream;
    private byte[] buf = new byte[1024];
    private int curChar;
    private int numChars;

    public FastScanner(InputStream stream) {
        this.stream = stream;
    }

    int read() {
        if (numChars == -1)
            throw new InputMismatchException();
        if (curChar >= numChars) {
            curChar = 0;
            try {
                numChars = stream.read(buf);
            } catch (IOException e) {
                throw new InputMismatchException();
            }
            if (numChars <= 0) return -1;
        }
        return buf[curChar++];
    }

    boolean isSpaceChar(int c) {
        return c == ' ' || c == '\n' || c == '\r' || c
            == '\t' || c == -1;
    }

    boolean isEndline(int c) {
        return c == '\n' || c == '\r' || c == -1;
    }

    public int nextInt() {
        return Integer.parseInt(next());
    }
}

```

```

public long nextLong() {
    return Long.parseLong(next());
}

public double nextDouble() {
    return Double.parseDouble(next());
}

public String next() {
    int c = read();
    while (isSpaceChar(c)) c = read();
    StringBuilder res = new StringBuilder();
    do {
        res.appendCodePoint(c);
        c = read();
    } while (!isSpaceChar(c));
    return res.toString();
}

public String nextLine() {
    int c = read();
    while (isEndline(c))
        c = read();
    StringBuilder res = new StringBuilder();
    do {
        res.appendCodePoint(c);
        c = read();
    } while (!isEndline(c));
    return res.toString();
}
}

```

1.3 (0) Troubleshoot

Source: *KACTL*

Pre-submit:

- Write a few simple test cases, if sample is not enough.
- Are time limits close? If so, generate max cases.
- Is the memory usage fine?
- Could anything overflow?
- Make sure to submit the right file.

Wrong answer:

- Print your solution! Print debug output, as well.
- Are you clearing all datastructures between test cases?
- Can your algorithm handle the whole range of input?
- Read the full problem statement again.
- Do you handle all corner cases correctly?
- Have you understood the problem correctly?
- Any uninitialized variables?

- Any overflows?
- Confusing N and M, i and j, etc.?
- Are you sure your algorithm works?
- What special cases have you not thought of?
- Are you sure the STL functions you use work as you think?
- Add some assertions, maybe resubmit.
- Create some testcases to run your algorithm on.
- Go through the algorithm for a simple case.
- Go through this list again.
- Explain your algorithm to a team mate.
- Ask the team mate to look at your code.
- Go for a small walk, e.g. to the toilet.
- Is your output format correct? (including whitespace)
- Rewrite your solution from the start or let a team mate do it.

Runtime error:

- Have you tested all corner cases locally?
- Any uninitialized variables?
- Are you reading or writing outside the range of any vector?
- Any assertions that might fail?
- Any possible division by 0? (mod 0 for example)
- Any possible infinite recursion?
- Invalidated pointers or iterators?
- Are you using too much memory?
- Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:

- Do you have any possible infinite loops?
- What is the complexity of your algorithm?
- Are you copying a lot of unnecessary data? (References)
- How big is the input and output? (consider scanf)
- Avoid vector, map. (use arrays/unordered map)
- What do your team mates think about your algorithm?

Memory limit exceeded:

- What is the max amount of memory your algorithm should need?
- Are you clearing all data structures between test cases?

1.4 (6) Pragma Optimization

```
/**
 * Source: Misc solutions to CF Nagini
 * Description: 106 operations are ok!
 * Passes the occasional disgusting CF task
 * Also see "Welcome home, Chtholly"
 */

#pragma GCC optimize ("O3")
#pragma GCC target ("sse4")

// template

int q, mx[100001], mn[100001];

int main() {
    ios_base::sync_with_stdio(0); cin.tie(0); cout.tie(0);
    cin >> q;
    FOR(i,100001) mx[i] = -MOD, mn[i] = MOD;
    FOR(i,q) {
        int t,l,r,k; cin >> t >> l >> r;
        r -= 1;

        auto a = mx+1, b = mn+1;
        if (t == 1) {
            cin >> k;
            if (k > 0) FOR(j,r) b[j] = min(b[j],k);
            else FOR(j,r) a[j] = max(a[j],k);
        } else {
            ll ans = 0;
            FOR(j,r) if (a[j] != -MOD && b[j] != MOD)
                ans += b[j]-a[j];
            cout << ans << "\n";
        }
    }
}
```

2 (2) Data Structures

2.1 (2) Range Queries, No Update

2.1.1 (2) Prefix Sums

```
/**
 * Description: Calculates rectangle sums in constant
 *             time
 */

template<class T, int SZ> struct sums {
    ll sum[SZ][SZ];
    sums () { memset(sum,0,sizeof sum); }
    void init() {
        FOR(i,1,SZ) FOR(j,1,SZ)
            sum[i][j] +=
                sum[i][j-1]+sum[i-1][j]-sum[i-1][j-1];
    }
    ll get(int X1, int X2, int Y1, int Y2) {
        return sum[X2][Y2]-sum[X1-1][Y2]
```

```
        -sum[X2][Y1-1]+sum[X1-1][Y1-1];
    }
};
```

2.1.2 (3) Range Minimum Query

```
/**
 * Description: Supports 1D range minimum query in
 *             constant time.
 * Verification: Problem Tournament from IOI 2012:
 *             http://wcipeg.com/problem/ioi1223
 * Source code: https://pastebin.com/ChpniVZL
 */

template<class T, int SZ> struct RMQ {
    T stor[SZ][32-__builtin_clz(SZ)];

    T comb(T a, T b) {
        return min(a,b);
    }

    void build(vector<T>& x) {
        FOR(i,sz(x)) stor[i][0] = x[i];
        FOR(j,1,32-__builtin_clz(SZ))
            FOR(i,SZ-(1<<(j-1)))
                stor[i][j] =
                    comb(stor[i][j-1],stor[i+(1<<(j-1))][j-1]);
    }

    T query(int l, int r) {
        int x = 31-__builtin_clz(r-l+1);
        return comb(stor[l][x],stor[r-(1<<x)+1][x]);
    }
};
```

2.2 (2) STL

2.2.1 (2) Coordinate Compression

```
/**
 * Description: Demonstrates use of map
 */

void compress(vi& x) {
    map<int,int> m; for (int i: x) m[i] = 0;
    int co = 0; for (auto& a: m) a.s = co++;
    for (int& i: x) i = m[i];
}

int main() {
    vi x = {2,4,3,6}; compress(x);
    // now x={0,2,1,3}
}
```

2.2.2 (2) Map Customization

```

/**
 * Description: Define your own comparator / hash
 * function
 * Source: StackOverflow
 */

struct cmp {
    bool operator()(const int& l, const int& r) const {
        return l > r;
    }
};

struct hsh {
    size_t operator()(const pii& k) const {
        return k.f^k.s; // bad, but you get the point
    }
};

set<int,cmp> s;
map<int,int,cmp> m;
unordered_map<pii,int,hsh> u;

```

2.2.3 (3) Minimum Deque

```

struct MinDeque {
    int lo = 0, hi = -1;
    deque<pii> d;

    void ins(int x) { // add to back
        while (sz(d) && d.back().f >= x) d.pop_back();
        d.pb({x,++hi});
    }

    void del() { // delete from front
        if (d.front().s == lo++) d.pop_front();
    }

    int get() {
        return sz(d) ? d.front().f : MOD;
    }
};

```

2.3 (3) Range Queries, Point Update

2.3.1 (3) Binary Indexed Tree

```

/**
 * Description: 1D range sum query with point update
 * Verification: SPOJ Fenwick
 */

template<class T, int SZ> struct BIT {
    T bit[SZ+1];

    BIT() { memset(bit,0,sizeof bit); }

    void upd(int k, T val) { // add val to index k

```

```

        for( ;k <= SZ; k += (k&-k)) bit[k] += val;
    }

    T query(int k) {
        T temp = 0;
        for (;k > 0;k -= (k&-k)) temp += bit[k];
        return temp;
    }

    T query(int l, int r) { return
        query(r)-query(l-1); } // range query [l,r]
};

```

2.3.2 (3) SegTree Demo

```

// SPOJ fenwick

BIT<ll,1000000> B;
// Seg<ll,1<<20> B;

int main() {
    int N; cin >> N;
    FOR(i,1,N+1) {
        int x; cin >> x;
        B.upd(i,x);
    }
    int q; cin >> q;
    FOR(i,q) {
        char c; int a, b;
        cin >> c >> a >> b;
        if (c == 'q') cout << B.query(a,b) << "\n";
        else B.upd(a,b);
    }
}

```

2.3.3 (3) SegTree

```

/**
 * Source: http://codeforces.com/blog/entry/18051
 * Description: 1D point update, range query
 * Verification: SPOJ Fenwick
 */

template<class T, int SZ> struct Seg {
    T seg[2*SZ], MN = 0;

    Seg() {
        memset(seg,0,sizeof seg);
    }

    T comb(T a, T b) { return a+b; } // easily change
        this to min or max

    void upd(int p, T value) { // set value at
        position p
        for (seg[p += SZ] = value; p > 1; p >>= 1)
            seg[p>>1] = comb(seg[p],seg[p^1]);
    }
}

```

```

void build() {
    FORd(i,SZ) seg[i] = comb(seg[2*i],seg[2*i+1]);
}

T query(int l, int r) { // sum on interval [l, r]
    T res = MN; r++;
    for (l += SZ, r += SZ; l < r; l >>= 1, r >>= 1) {
        if (l&1) res = comb(res,seg[l++]);
        if (r&1) res = comb(res,seg[--r]);
    }
    return res;
}
};

```

2.3.4 (4) Sparse SegTree

```

/**
 * Source: Own
 */

const int SZ = 1<<20;

struct node {
    ll val = 0;
    node* c[2];

    void upd(int ind, int v, int L = 0, int R = SZ-1)
        { // add v
        if (L == ind && R == ind) { val += v; return; }

        int M = (L+R)/2;
        if (ind <= M) {
            if (!c[0]) c[0] = new node();
            c[0]->upd(ind,v,L,M);
        } else {
            if (!c[1]) c[1] = new node();
            c[1]->upd(ind,v,M+1,R);
        }

        val = 0;
        if (c[0]) val += c[0]->val;
        if (c[1]) val += c[1]->val;
    }

    ll query(int low, int high, int L = 0, int R = SZ-1) { // query sum of segment
        if (low <= L && R <= high) return val;
        if (high < L || R < low) return 0;

        int M = (L+R)/2;
        ll t = 0;
        if (c[0]) t += c[0]->query(low,high,L,M);
        if (c[1]) t += c[1]->query(low,high,M+1,R);
        return t;
    }

    void UPD(int ind, node* c0, node* c1, int L = 0, int R = SZ-1) { // for 2D segtree
        if (L != R) {

```

```

            int M = (L+R)/2;
            if (ind <= M) {
                if (!c[0]) c[0] = new node();
                c[0]->UPD(ind,c0 ? c0->c[0] : NULL,c1 ? c1->c[0] : NULL,L,M);
            } else {
                if (!c[1]) c[1] = new node();
                c[1]->UPD(ind,c0 ? c0->c[1] : NULL,c1 ? c1->c[1] : NULL,M+1,R);
            }
        }
        val = 0;
        if (c0) val += c0->val;
        if (c1) val += c1->val;
    }
};

```

2.3.5 (5) Basic Persistent SegTree

```

/**
 * Description: persistent segtree node without lazy updates
 * Verification: Codeforces Problem 893F - Subtree Minimum Query
 * Implementation:
 *   http://codeforces.com/contest/893/submission/32652140
 */

struct Node {
    int val = 0;
    Node* c[2];

    Node* copy() {
        Node* x = new Node(); *x = *this;
        return x;
    }

    int query(int low, int high, int L, int R) {
        if (low <= L && R <= high) return val;
        if (R < low || high < L) return MOD;
        int M = (L+R)/2;
        return min(c[0]->query(low,high,L,M), c[1]->query(low,high,M+1,R));
    }

    Node* upd(int ind, int v, int L, int R) {
        if (R < ind || ind < L) return this;
        Node* x = copy();

        if (ind <= L && R <= ind) {
            x->val += v;
            return x;
        }

        int M = (L+R)/2;
        x->c[0] = x->c[0]->upd(ind,v,L,M);
        x->c[1] = x->c[1]->upd(ind,v,M+1,R);
        x->val = min(x->c[0]->val,x->c[1]->val);

        return x;
    }

```

```

}

void build(vi& arr, int L, int R) {
    if (L == R) {
        if (L < (int)arr.size()) val = arr[L];
        else val = 0;
        return;
    }
    int M = (L+R)/2;
    c[0] = new Node();
    c[0]->build(arr,L,M);
    c[1] = new Node();
    c[1]->build(arr,M+1,R);
    val = min(c[0]->val,c[1]->val);
}
};

```

2.4 (4) 2D Range Queries

2.4.1 (4) 2D BIT

```

/**
 * Description: Uses same principle as 1D BIT
 * Supports point update & range query
 * Range update is also possible
 * Verification: SPOJ matsum
 */

template<class T, int SZ> struct BIT2D {
    T bit[SZ+1][SZ+1];
    void upd(int X, int Y, T val) {
        for (; X <= SZ; X += (X&-X))
            for (int Y1 = Y; Y1 <= SZ; Y1 += (Y1&-Y1))
                bit[X][Y1] += val;
    }
    T query(int X, int Y) {
        T ans = 0;
        for (; X > 0; X -= (X&-X))
            for (int Y1 = Y; Y1 > 0; Y1 -= (Y1&-Y1))
                ans += bit[X][Y1];
        return ans;
    }
    T query(int X1, int X2, int Y1, int Y2) {
        return query(X2,Y2)-query(X1-1,Y2)
            -query(X2,Y1-1)+query(X1-1,Y1-1);
    }
};

int T;

int main() {
    ios_base::sync_with_stdio(0);cin.tie(0);
    cin >> T;
    FOR(i,T) {
        int N; cin >> N;
        BIT2D<ll,1024> B = BIT2D<ll,1024>();
        while (1) {
            string c; cin >> c;
            if (c == "SET") {
                int x, y,num; cin >> x >> y >> num;

```

```

                x++, y++;
                B.upd(x,y,num-B.query(x,x,y,y));
            } else if (c == "SUM") {
                int x1, y1, x2, y2; cin >> x1 >> y1 >>
                    x2 >> y2;
                x1 ++, y1 ++, x2 ++, y2++;
                cout << B.query(x1,x2,y1,y2) << "\n";
            } else break;
        }
    }
}

```

2.4.2 (4) 2D Demo

```

Node n; // SegBIT

int main() {
    n.upd(5,7,2);
    n.upd(3,2,20);
    n.upd(5,8,200);
    cout << n.query(3,5,2,7) << "\n"; // 22
}

```

2.4.3 (4) 2D SegBIT

```

/**
 * Source: USACO Mowing the Field
 * Description: array of sparse 1D segtrees
 */

const int SZ = 1<<17;

struct SegBit {
    node seg[SZ+1];

    SegBit() {
        FOR(i,SZ+1) seg[i] = node();
    }

    void upd(int x, int y, int v) { // add v
        for (x++; x <= SZ; x += (x&-x)) seg[x].upd(y,v);
    }

    int query(int x, int y1, int y2) {
        int ret = 0;
        for (; x > 0; x -= (x&-x)) ret +=
            seg[x].query(y1,y2);
        return ret;
    }

    int query(int x1, int x2, int y1, int y2) { //
        // query sum of rectangle
        return query(x2+1,y1,y2)-query(x1,y1,y2);
    }
};

```

2.4.4 (4) 2D SegTree

```
/**
 * Source: USACO Mowing the Field
 * Description: sparse segtree of sparse 1D segtrees
 */

const int SZ = 1<<17;

struct Node {
    node seg;
    Node* c[2];

    void upd(int x, int y, int v, int L = 0, int R =
        SZ-1) { // add v
        if (L == x && R == x) {
            seg.upd(y,v);
            return;
        }

        int M = (L+R)/2;
        if (x <= M) {
            if (!c[0]) c[0] = new Node();
            c[0]->upd(x,y,v,L,M);
        } else {
            if (!c[1]) c[1] = new Node();
            c[1]->upd(x,y,v,M+1,R);
        }

        seg.UPD(y,c[0] ? &c[0]->seg : NULL,c[1] ?
            &c[1]->seg : NULL);
    }

    int query(int x1, int x2, int y1, int y2, int L =
        0, int R = SZ-1) { // query sum of rectangle
        if (x1 <= L && R <= x2) return
            seg.query(y1,y2);
        if (x2 < L || R < x1) return 0;

        int M = (L+R)/2, t = 0;
        if (c[0]) t += c[0]->query(x1,x2,y1,y2,L,M);
        if (c[1]) t += c[1]->query(x1,x2,y1,y2,M+1,R);
        return t;
    }
};
```

2.4.5 (4) Merge-Sort Tree

```
/**
 * Description: Similar to 2D segtree, less memory
 * For more complex queries use a customized treap
 * Verification:
 *   http://codeforces.com/contest/785/submission/33953058
 */

template<int SZ> struct mstree {
    Tree<pii> val[SZ+1]; // for offline queries use
        vector with binary search instead
};
```

```
void upd(int x, int y, int t = 1) { //
    x-coordinate between 1 and SZ inclusive
    for (int X = x; X <= SZ; X += X&-X) {
        if (t == 1) val[X].insert({y,x});
        else val[X].erase({y,x});
    }
}

int query(int x, int y) {
    int t = 0;
    for (;x > 0; x -= x&-x) t +=
        val[x].order_of_key({y,MOD});
    return t;
}

int query(int lox, int hix, int loy, int hiy) { //
    query number of elements within a rectangle
    return query(hix,hiy)-query(lox-1,hiy)
        -query(hix,loy-1)+query(lox-1,loy-1);
}
};
```

2.5 (4) BBST

2.5.1 (4) Treap

```
/*
 * Sources: various
 * Description: Easiest BBST
 * Verification: http://www.spoj.com/problems/ORDERSET/
 */

struct tnode {
    int val, pri, sz;
    tnode *c[2];

    tnode (int v) {
        val = v, sz = 1, pri = rand()+(rand()<<15);
        c[0] = c[1] = NULL;
    }

    void inOrder(bool f = 0) {
        if (c[0]) c[0]->inOrder();
        cout << val << " ";
        if (c[1]) c[1]->inOrder();
        if (f) cout << "\n-----\n";
    }

    void recalc() {
        sz = 1+(c[0]?c[0]->sz:0)+(c[1]?c[1]->sz:0);
    }
};

pair<tnode*,tnode*> split(tnode* t, int v) { // >= v
    goes to the right
    if (!t) return {t,t};

    if (v <= t->val) {
        auto p = split(t->c[0], v);
        t->c[0] = p.s; t->recalc();
    }
}
```



```

        return {p.f, t};
    } else {
        auto p = split(t->c[1], v);
        t->c[1] = p.f; t->recalc();
        return {t, p.s};
    }
}

pair<tnode*, tnode*> split_by_order(tnode* t, int v) {
    if (!t) return {t, t};
    int tmp = t->c[0]?t->c[0]->sz:0;
    if (v <= tmp) {
        auto p = split_by_order(t->c[0], v);
        t->c[0] = p.s; t->recalc();
        return {p.f, t};
    } else {
        auto p = split_by_order(t->c[1], v-tmp-1);
        t->c[1] = p.f; t->recalc();
        return {t, p.s};
    }
}

tnode* merge(tnode* l, tnode* r) {
    if (!l) return r;
    if (!r) return l;

    if (l->pri > r->pri) {
        l->c[1] = merge(l->c[1], r);
        l->recalc();
        return l;
    } else {
        r->c[0] = merge(l, r->c[0]);
        r->recalc();
        return r;
    }
}

tnode* ins(tnode* x, int v) { // insert value v
    auto a = split(x, v);
    auto b = split(a.s, v+1);
    return merge(a.f, merge(new tnode(v), b.s));
}

tnode* del(tnode* x, int v) { // delete all values
    equal to v
    auto a = split(x, v), b = split(a.s, v+1);
    return merge(a.f, b.s);
}

tnode *root;

int order_of_key(int x) {
    auto a = split(root, x);
    int t = a.f?a.f->sz:0;
    root = merge(a.f, a.s);
    return t;
}

int find_by_order(int x) {
    auto a = split_by_order(root, x);
    auto b = split_by_order(a.f, x-1);
    int t = b.s->val;

```

```

        root = merge(merge(b.f, b.s), a.s);
        return t;
    }

int main() {
    ios_base::sync_with_stdio(0); cin.tie(0);

    int Q; cin >> Q;
    FOR(i, Q) {
        char c; int d; cin >> c >> d;
        if (c == 'I') root = ins(root, d);
        else if (c == 'D') root = del(root, d);
        else if (c == 'K') {
            if (!root || root->sz < d) cout
                << "invalid\n";
            else cout << find_by_order(d) <<
                "\n";
        } else cout << order_of_key(d) << "\n";
    }
}

```

2.5.2 (5) Link-Cut Tree

```

/**
 * Source: Dhruv Rohatgi
 * Usage: USACO Camp - The Applicant
 */

template<int SZ> struct LCT {
    int p[SZ], pp[SZ], c[SZ][2], sum[SZ];

    LCT () {
        FOR(i, 1, SZ) sum[i] = 1;
        memset(p, 0, sizeof p);
        memset(pp, 0, sizeof pp);
        memset(c, 0, sizeof c);
    }

    int getDir(int x, int y) {
        return c[x][0] == y ? 0 : 1;
    }

    void setLink(int x, int y, int d) {
        c[x][d] = y, p[y] = x;
    }

    void rotate(int y, int d) {
        int x = c[y][d], z = p[y];
        setLink(y, c[x][d^1], d);
        setLink(x, y, d^1);
        setLink(z, x, getDir(z, y));

        sum[x] = sum[y];
        sum[y] = sum[c[y][0]] + sum[c[y][1]] + 1;
        pp[x] = pp[y]; pp[y] = 0;
    }

    void splay(int x) {
        while (p[x]) {
            int y = p[x], z = p[y];

```

```

        int dy = getDir(y,x), dz = getDir(z,y);
        if (!z) rotate(y,dy);
        else if (dy == dz) rotate(z,dz),
            rotate(y,dy);
        else rotate(y,dy), rotate(z,dz);
    }
}

void dis(int v, int d) {
    p[c[v][d]] = 0, pp[c[v][d]] = v;
    sum[v] -= sum[c[v][d]];
    c[v][d] = 0;
}

void con(int v, int d) {
    c[pp[v]][d] = v;
    sum[pp[v]] += sum[v];
    p[v] = pp[v], pp[v] = 0;
}

void access(int v) {
    // v is brought to the root of auxiliary tree
    // modify preferred paths

    splay(v);
    dis(v,1);

    while (pp[v]) {
        int w = pp[v]; splay(w);
        dis(w,1), con(v,1);
        splay(v);
    }
}

int find_root(int v) {
    access(v);
    while (c[v][0]) v = c[v][0];
    access(v);
    return v;
}

int find_depth(int v) {
    access(v);
    return sum[c[v][0]];
}

void cut(int v) {
    // cut link between v and par[v]
    access(v);
    pp[c[v][0]] = p[c[v][0]] = 0; // fix
    sum[v] -= sum[c[v][0]];
    c[v][0] = 0;
}

void link(int v, int w) {
    // v, which is root of another tree, is now
    // child of w
    access(v), access(w);
    pp[w] = v; con(w,0);
}

int anc(int v, int num) {

```

```

    if (find_depth(v) < num) return 0;
    access(v);
    v = c[v][0];

    while (1) {
        if (sum[c[v][1]] >= num) v = c[v][1];
        else if (sum[c[v][1]]+1 == num) return v;
        else num -= (sum[c[v][1]]+1), v = c[v][0];
    }
}

void print(int x) {
    FOR(i,1,x+1) cout << i << " " << find_root(i)
        << " " << find_depth(i) << " " << anc(i,2)
        << "\n";
    cout << "\n";
}

};

LCT<100001> L;

int main() {
    L.link(2,1); L.link(3,1); L.link(4,1); L.link(5,4);
    L.link(10,4); L.link(7,6); L.link(8,7);
    L.link(9,8);
    L.print(10);

    L.cut(4); L.link(4,8);
    L.print(10);
}

```

2.5.3 (5) Splay Tree

```

/*
 * Description: based off treap code
 */

struct snode {
    int val;
    snode *p, *c[2];
    snode (int v) {
        val = v;
        c[0] = c[1] = p = NULL;
    }
    void inOrder(bool f = 0) {
        if (c[0]) c[0]->inOrder();
        cout << val << " ";
        if (c[1]) c[1]->inOrder();
        if (f) cout << "\n-----\n";
    }
};

void setLink(snode* x, snode* y, int d) {
    if (x) x->c[d] = y;
    if (y) y->p = x;
}

int getDir(snode* x, snode* y) {
    if (!x) return -1;
    return x->c[0] == y ? 0 : 1;
}

```

```

}

void rot(snode* x, int d) {
    snode *y = x->c[d], *z = x->p;
    setLink(x, y->c[d^1], d);
    setLink(y, x, d^1);
    setLink(z, y, getDir(z, x));
}

snode* splay(snode* x) {
    while (x && x->p) {
        snode* y = x->p, *z = y->p;
        int dy = getDir(y, x), dz = getDir(z, y);
        if (!z) rot(y, dy);
        else if (dy == dz) rot(z, dz), rot(y, dy);
        else rot(y, dy), rot(z, dz);
    }
    return x;
}

pair<snode*,snode*> find(snode *cur, int v) { // x.f
    is result, x.s is lowest
    if (!cur) return {cur,cur};
    pair<snode*,snode*> x;
    if (cur->val >= v) {
        x = find(cur->c[0],v);
        if (!x.f) x.f = cur;
    } else x = find(cur->c[1],v);
    if (!x.s) x.s = cur;
    return x;
}

snode* getmx(snode* x) {
    return x->c[1]?getmx(x->c[1]):x;
}

pair<snode*,snode*> split(snode* x, int v) {
    if (!x) return {x,x};
    auto y = find(x,v); y.s = splay(y.s);
    if (!y.f) return {y.s,NULL};

    y.f = splay(y.f);
    auto z = y.f->c[0]; setLink(y.f,NULL,0),
        setLink(NULL,z,0);
    return {z,y.f};
}

snode* merge(snode* x, snode* y) {
    if (!x) return y;
    x = splay(getmx(x));
    setLink(x,y,1);
    return x;
}

snode* ins(snode* x, int v) { // insert value v
    auto a = split(x,v);
    return merge(merge(a.f, new snode(v)),a.s);
}

snode* del(snode* x, int v) { // delete all values
    equal to v
    auto a = split(x,v), b = split(a.s,v+1);

```

```

        return merge(a.f,b.s);
    }

    snode* root;

```

2.6 (4) Range Queries, Range Update

2.6.1 (4) BIT with Range Update

```

/**
 * Source: GeeksForGeeks?
 * Description: 1D range update, range query
 * Alternative to lazy segment tree
 */

// BIT template

template<class T, int SZ> struct BITrange {
    BIT<T,SZ> bit[2]; // sums piecewise linear
    functions

    void upd(int hi, T val) {
        bit[1].upd(1,val), bit[1].upd(hi+1,-val);
        bit[0].upd(hi+1,hi*val);
    }

    void upd(int lo, int hi, T val) { upd(lo-1,-val),
        upd(hi,val); }

    T query(int x) { return
        bit[1].query(x)*x+bit[0].query(x); }
    T query(int x, int y) { return
        query(y)-query(x-1); }
};

```

2.6.2 (4) Lazy SegTree Demo

```

// SPOJ horrible

int main() {
    int T; cin >> T;
    FOR(i,T) {
        BITrange<ll,100000> B = BITrange<ll,100000>();
        // LazySegTree<ll,1<<17>
        int N, C; cin >> N >> C;
        FOR(j,C) {
            int t; cin >> t;
            if (t == 0) {
                int p,q,v; cin >> p >> q >> v;
                B.upd(p,q,v);
            } else {
                int p,q; cin >> p >> q;
                cout << B.query(p,q) << "\n"; // qsum
            }
        }
    }
}

```

2.6.3 (4) Lazy SegTree

```
/**
 * Description: 1D range update, range query
 * Verification: SPOJ Horrible
 */

const ll INF = 1e18; // setting this to MOD can be
                    disastrous :(

template<class T, int SZ> struct LazySegTree {
    T sum[2*SZ], mn[2*SZ], lazy[2*SZ]; // set SZ to a
    power of 2

    LazySegTree() {
        memset (sum,0,sizeof sum);
        memset (mn,0,sizeof mn);
        memset (lazy,0,sizeof lazy);
    }

    void push(int ind, int L, int R) {
        sum[ind] += (R-L+1)*lazy[ind];
        mn[ind] += lazy[ind];
        if (L != R) lazy[2*ind] += lazy[ind],
            lazy[2*ind+1] += lazy[ind];
        lazy[ind] = 0;
    }

    void pull(int ind) {
        sum[ind] = sum[2*ind]+sum[2*ind+1];
        mn[ind] = min(mn[2*ind],mn[2*ind+1]);
    }

    void build() {
        FORd(i,SZ) pull(i);
    }

    T qsum(int lo, int hi, int ind = 1, int L = 0, int
        R = SZ-1) {
        if (lo > R || L > hi) return 0;
        if (lo <= L && R <= hi) return sum[ind];

        int M = (L+R)/2;
        return qsum(lo,hi,2*ind,L,M) +
            qsum(lo,hi,2*ind+1,M+1,R);
    }

    T qmin(int lo, int hi, int ind = 1, int L = 0, int
        R = SZ-1) {
        if (lo > R || L > hi) return INF;
        if (lo <= L && R <= hi) return mn[ind];

        int M = (L+R)/2;
        return min(qmin(lo,hi,2*ind,L,M),
            qmin(lo,hi,2*ind+1,M+1,R));
    }

    void upd(int lo, int hi, ll inc, int ind = 1, int
        L = 0, int R = SZ-1) {
```

```
        push(ind,L,R);
        if (hi < L || R < lo) return;
        if (lo <= L && R <= hi) {
            lazy[ind] = inc;
            push(ind,L,R);
            return;
        }

        int M = (L+R)/2;
        upd(lo,hi,inc,2*ind,L,M);
        upd(lo,hi,inc,2*ind+1,M+1,R);
        pull(ind);
    }
};
```

2.6.4 (5) Lazy Persistent SegTree

```
/**
 * Source:
 * http://codeforces.com/blog/entry/47108?#comment-315047
 * Description: Node + lazy updatess
 */

struct node {
    int val = 0, lazy = 0;
    node* c[2];

    node* copy() {
        node* x = new node(); *x = *this;
        return x;
    }

    void push() {
        if (!lazy) return;
        FOR(i,2) if (c[i]) {
            c[i] = new node(*c[i]);
            c[i]->lazy += lazy;
        }
        lazy = 0;
    }

    int query(int low, int high, int L, int R) {
        if (low <= L && R <= high) return val;
        if (R < low || high < L) return MOD;
        int M = (L+R)/2;
        return lazy+min(c[0]->query(low,high,L,M),
            c[1]->query(low,high,M+1,R));
    }

    node* upd(int low, int high, int v, int L, int R) {
        if (R < low || high < L) return this;
        node* x = copy();
        if (low <= L && R <= high) {
            x->lazy += v, x->val += v;
            return x;
        }
        push();

        int M = (L+R)/2;
        x->c[0] = x->c[0]->upd(low,high,v,L,M);
```

```

x->c[1] = x->c[1]->upd(low,high,v,M+1,R);
x->val = min(x->c[0]->val,x->c[1]->val);

return x;
}

void build(vi& arr, int L, int R) {
    if (L == R) {
        if (L < sz(arr)) val = arr[L];
        else val = 0;
        return;
    }
    int M = (L+R)/2;
    c[0] = new node();
    c[0]->build(arr,L,M);
    c[1] = new node();
    c[1]->build(arr,M+1,R);
    val = min(c[0]->val,c[1]->val);
}

};

template<int SZ> struct pers {
    node* loc[SZ+1]; // stores location of root after
                    // ith update
    int nex = 1;

    pers() { loc[0] = new node(); }

    void upd(int low, int high, int val) {
        loc[nex] =
            loc[nex-1]->upd(low,high,val,0,SZ-1);
        nex++;
    }
    void build(vi& arr) {
        loc[0]->build(arr,0,SZ-1);
    }
    int query(int ti, int low, int high) {
        return loc[ti]->query(low,high,0,SZ-1);
    }
}

};

pers<8> p;

int main() {
    vi arr = {1,7,2,3,5,9,4,6};
    p.build(arr);

    p.upd(1,2,2); // 1 9 4 3 5 9 4 6

    FOR(i,8) {
        FOR(j,i,8) cout << p.query(1,i,j) << " ";
        cout << "\n";
    }
    cout << "\n";

    p.upd(4,7,5); // 1 9 4 3 10 14 9 11
    FOR(i,8) {
        FOR(j,i,8) cout << p.query(2,i,j) << " ";
        cout << "\n";
    }
    cout << "\n";
}

```

```

FOR(i,8) {
    FOR(j,i,8) cout << p.query(1,i,j) << " ";
    cout << "\n";
}
cout << "\n";
}

```

3 (2) Graphs

3.1 (2) Searching Demo

3.1.1 (2) BFS on Grid

```

/**
 * Note: Use xdir and ydir
 */

int xdir[4] = {0,1,0,-1}, ydir[4] = {1,0,-1,0};
int dist[21][21];
queue<pii> todo;

void process(pii x) {
    FOR(i,4) {
        pii y = {x.f+xdir[i],x.s+ydir[i]};
        if (y.f < 0 || y.f > 20 || y.s < 0 ||
            y.s > 20) continue; // ignore this
                                // point if it's outside of grid
        if (dist[y.f][y.s] == MOD) { // test
            // whether point has been visited or
            // not
            dist[y.f][y.s] = dist[x.f][x.s]+1;
            todo.push(y); // push point to queue
        }
    }
}

int main() {
    FOR(i,21) FOR(j,21) dist[i][j] = MOD;
    dist[10][10] = 0; todo.push({10,10}); //
    // initialize queue, distances
    while (todo.size()) {
        process(todo.front());
        todo.pop(); // pop point from queue
    }
    cout << dist[4][5]; // 11
}

```

3.1.2 (2) DFS on Graph

```

/**
 * Classic
 */

int n, visit[100001];
vi adj[100001];

void dfs(int node) {

```

```

    if (visit[node]) return;
    visit[node] = 1;
    for (int i: adj[node]) dfs(i);
    cout << node << "\n";
    // do stuff
}

int main() {
    cin >> n;
    FOR(i,n-1) {
        int a,b; cin >> a >> b;
        adj[a].pb(b);
        adj[b].pb(a);
    }
    dfs(1);
}

```

3.2 (3) Shortest Path

3.2.1 (3) Bellman-Ford

```

/**
 * Usage: https://open.kattis.com/problems/shortestpath3
 * Description: can be useful with linear programming
 * Constraints of the form  $x_i - x_j < k$ 
 */

const ll INF = 1e18;

int n,m,q,s,bad[1000];
vector<pair<pii,int>> edge;
ll dist[1000];

void solve() {
    edge.clear();
    FOR(i,n) dist[i] = INF, bad[i] = 0;
    dist[s] = 0;
    FOR(i,m) {
        int u,v,w; cin >> u >> v >> w;
        edge.pb({u,v,w});
    }
    FOR(i,n) for (auto a: edge) if (dist[a.f.f] < INF)
        dist[a.f.s] = min(dist[a.f.s],
            dist[a.f.f]+a.s);
    for (auto a: edge) if (dist[a.f.f] < INF) if
        (dist[a.f.s] > dist[a.f.f]+a.s) bad[a.f.s] = 1;
    FOR(i,n) for (auto a: edge) if (bad[a.f.f])
        bad[a.f.s] = 1;

    FOR(i,q) {
        int x; cin >> x;
        if (bad[x]) cout << "-Infinity\n";
        else if (dist[x] == INF) cout <<
            "Impossible\n";
        else cout << dist[x] << "\n";
    }
    cout << "\n";
}

```

3.2.2 (3) Dijkstra

```

/**
 * Description: shortest path!
 * Works with negative edge weights (aka SPFA?)
 */

template<int SZ> struct Dijkstra {
    int dist[SZ];
    vector<pii> adj[SZ];
    priority_queue<pii,vector<pii>,greater<pii>> q;

    void gen() {
        fill_n(dist,SZ,MOD); dist[0] = 0;

        q.push({0,0});
        while (q.size()) {
            pii x = q.top(); q.pop();
            if (dist[x.s] < x.f) continue;
            for (pii y: adj[x.s]) if (x.f+y.s <
                dist[y.f]) {
                dist[y.f] = x.f+y.s;
                q.push({dist[y.f],y.f});
            }
        }
    }
};

Dijkstra<100> D;

int main() {
    FOR(i,100) FOR(j,100) if (rand() % 10 == 0)
        D.adj[i].pb({j,rand() % 10+1});
    D.gen();
    FOR(i,100) cout << D.dist[i] << "\n";
}

```

3.2.3 (3) Floyd-Warshall

```

/**
 * Usage: https://open.kattis.com/problems/allpairspath
 */

const ll INF = 1e18;

int n,m,q; // vertices, edges, queries
ll dist[150][150], bad[150][150];

void solve() {
    FOR(i,n) FOR(j,n) dist[i][j] = INF, bad[i][j] = 0;
    FOR(i,n) dist[i][i] = 0;
    FOR(i,m) {
        int u,v,w; cin >> u >> v >> w;
        dist[u][v] = min(dist[u][v],(ll)w);
    }
    FOR(k,n) FOR(i,n) FOR(j,n) if (dist[i][k] != INF
        && dist[k][j] != INF)
        dist[i][j] =
            min(dist[i][j],dist[i][k]+dist[k][j]);
}

```

```

FOR(k,n) FOR(i,n) FOR(j,n) if (dist[i][k] != INF
    && dist[k][j] != INF)
    if (dist[i][j] > dist[i][k]+dist[k][j])
        bad[i][j] = 1;

FOR(k,n) FOR(i,n) FOR(j,n) {
    if (dist[i][k] < INF && bad[k][j]) bad[i][j] =
        1;
    if (bad[i][k] && dist[k][j] < INF) bad[i][j] =
        1;
}

FOR(i,q) {
    int u,v; cin >> u >> v;
    if (bad[u][v]) cout << "-Infinity\n";
    else if (dist[u][v] == INF) cout <<
        "Impossible\n";
    else cout << dist[u][v] << "\n";
}
cout << "\n";
}

```

3.3 (3) TopoSort + Related

3.3.1 (3) Topological Sort

```

/**
 * Description: sorts vertices such that if there
 * exists an edge x->y, then x goes before y
 */

int N,M, in[100001];
vi res, adj[100001];

void topo() {
    queue<int> todo;
    FOR(i,1,N+1) if (in[i] == 0) todo.push(i);
    while (sz(todo)) {
        int x = todo.front(); todo.pop();
        res.pb(x);
        for (int i: adj[x]) {
            in[i]--;
            if (!in[i]) todo.push(i);
        }
    }
}

int main() {
    cin >> N >> M;
    FOR(i,M) {
        int x,y; cin >> x >> y;
        adj[x].pb(y), in[y]++;
    }
    topo();
    for (int i: res) cout << i << " ";
}

```

3.3.2 (4) Kosaraju

```

/**
 * Source: Wikipedia
 * Description: generates SCC in topological order
 * Verification: SPOJ capcity
 */

template<int SZ> struct scc {
    vi adj[SZ], radj[SZ], todo;
    int N, comp[SZ];
    bitset<SZ> visit;

    void dfs(int v) {
        visit[v] = 1;
        for (int w: adj[v]) if (!visit[w]) dfs(w);
        todo.pb(v);
    }

    void dfs2(int v, int val) {
        comp[v] = val;
        for (int w: radj[v]) if (!comp[w]) dfs2(w,val);
    }

    void addEdge(int a, int b) {
        adj[a].pb(b), radj[b].pb(a);
    }

    void genSCC() {
        FOR(i,1,N+1) comp[i] = visit[i] = 0;
        FOR(i,1,N+1) if (!visit[i]) dfs(i);
        reverse(all(todo)); // topsort
        for (int i: todo) if (!comp[i]) dfs2(i,i);
    }
};

```

3.3.3 (4) Tarjan BCC

```

/**
 * Source:
 * http://www.geeksforgeeks.org/biconnected-components/
 * Some corrections!
 * Verification: USACO December 2017, Push a Box
 * Code: https://pastebin.com/yUWuzTH8
 */

template<int SZ> struct BCC {
    int N, ti = 0;
    vi adj[SZ];
    int disc[SZ], low[SZ], comp[SZ], par[SZ];
    vector<vector<pii>> fin;
    vector<pii> st;

    void addEdge(int u, int v) {
        adj[u].pb(v), adj[v].pb(u);
    }

    void BCCutil(int u) {
        disc[u] = low[u] = ti++;
    }
};

```

```

int child = 0;

for (int i: adj[u]) if (i != par[u]) {
    if (disc[i] == -1) {
        child++; par[i] = u;
        st.pb({u,i});
        BCCutil(i);
        low[u] = min(low[u],low[i]);

        if ((disc[u] == 0 && child > 1) ||
            (disc[u] != 0 && disc[u] <=
             low[i])) { // articulation point!
            vector<pii> tmp;
            while (st.back() != mp(u,i))
                tmp.pb(st.back()),
                st.pop_back();
            tmp.pb(st.back(), st.pop_back());
            fin.pb(tmp);
        }
    } else if (disc[i] < disc[u]) {
        low[u] = min(low[u],disc[i]);
        st.pb({u,i});
    }
}

}

void bcc() {
    FOR(i,1,N+1) par[i] = disc[i] = low[i] = -1;
    FOR(i,1,N+1) if (disc[i] == -1) {
        BCCutil(i);
        if (sz(st)) fin.pb(st);
        st.clear();
    }
}

};

```

3.3.4 (4) Tarjan SCC

```

/**
 * Source: See BCC template
 * Description: generates SCC in reverse topological
 *              order
 */

template<int SZ> struct scc {
    int N, ti = 0;
    vi adj[SZ], st, fin;
    int disc[SZ], low[SZ], comp[SZ];
    bitset<SZ> inStack;

    void addEdge(int u, int v) {
        adj[u].pb(v);
    }

    void SCCutil(int u) {
        disc[u] = low[u] = ti++;
        st.pb(u); inStack[u] = 1;

        for (int i: adj[u]) {
            if (disc[i] == -1) {

```

```

                SCCutil(i);
                low[u] = min(low[u],low[i]);
            } else if (inStack[i]) {
                low[u] = min(low[u],disc[i]);
            }
        }

        if (disc[u] == low[u]) {
            while (st.back() != u) {
                comp[st.back()] = u;
                inStack[st.back()] = 0;
                st.pop_back();
            }
            comp[u] = u; inStack[u] = 0; st.pop_back();
            fin.pb(u);
        }
    }

    void genSCC() {
        FOR(i,1,N+1) disc[i] = low[i] = -1;
        FOR(i,1,N+1) if (disc[i] == -1) SCCutil(i);
    }
};

```

3.4 (6) Euler Tour

```

/**
 * Description: extra log factor
 * Usage: https://open.kattis.com/problems/eulerianpath
 */

vi circuit;
multiset<int> adj[10000], adj1[10000];
int N,M, out[10000], in[10000];

void find_circuit(int x) { // directed graph, possible
    that resulting circuit is not valid
    while (adj[x].size()) {
        int j = *adj[x].begin();
        adj[x].erase(adj[x].begin());
        find_circuit(j);
    }
    circuit.pb(x);
}

int a,b,start;

void solve() {
    FOR(i,N) {
        adj[i].clear(), adj1[i].clear();
        out[i] = in[i] = 0;
    }
    circuit.clear();
    FOR(i,M) {
        cin >> a >> b;
        adj[a].insert(b), adj1[a].insert(b);
        out[a] ++, in[b] ++;
    }
    start = a;
    FOR(i,N) if (out[i]-in[i] == 1) start = i;

```



```

find_circuit(start);
reverse(circuit.begin(),circuit.end());

if (circuit.size() != M+1) {
    cout << "Impossible\n";
    return;
}

FOR(i,M) {
    if (adj1[circuit[i]].find(circuit[i+1]) ==
        adj1[circuit[i]].end()) {
        cout << "Impossible\n";
        return;
    }
    int t = circuit[i];
    adj1[t].erase(adj1[t].find(circuit[i+1]));
}
FOR(i,M+1) cout << circuit[i] << " ";
cout << "\n";
}

```

4 (2) Paradigms

4.1 (2) Binary Search

```

/**
 * Description: Basic example of binary search
 * Guess the Number
 * https://open.kattis.com/problems/guess
 */

int main() {
    int lo = 1, hi = 1000;
    while (1) {
        int mid = (lo+hi)/2;
        cout << mid << endl;
        string res; cin >> res;
        if (res == "correct") return 0;
        else if (res == "lower") hi = mid-1;
        else lo = mid+1;
    }
}

```

4.2 (2) Interval Cover

```

/**
 * Usage: https://open.kattis.com/problems/intervalcover
 * Description: Example of greedy algorithm
 */

double A,B,cur;
vector<pair<pdd,int>> in;
int N,nex;
vi ans;

void solve() {

```

```

    nex = 0; ans.clear();
    cin >> N; in.resize(N);
    FOR(i,N) {
        cin >> in[i].f.f >> in[i].f.s;
        in[i].s = i;
    }

    sort(all(in));
    pair<double,int> mx = {-DBL_MAX,-1};

    while (nex < in.size() && in[nex].f.f <= A) {
        mx = max(mx,{in[nex].f.s,in[nex].s});
        nex++;
    }
    if (nex == 0) {
        cout << "impossible\n";
        return;
    }
    ans.pb(mx.s);

    while (mx.f < B) {
        cur = mx.f;
        while (nex < in.size() && in[nex].f.f <= cur) {
            mx = max(mx,{in[nex].f.s,in[nex].s});
            nex++;
        }
        if (mx.f == cur) {
            cout << "impossible\n";
            return;
        }
        ans.pb(mx.s);
    }
    cout << ans.size() << "\n";
    for (int i: ans) cout << i << " ";
    cout << "\n";
}

```

4.3 (4) Discrete Logarithm

```

/**
 * Description: find k such that primitive^k=x
 * meet in the middle, O(sqrt(MOD))
 * Source: Own
 * Verification: PA 2006 - Professor Laugh's Numbers
 */

const int BLOCK = 32000;

int primitive = 5, invy[BLOCK];
unordered_map<int,int> u;

ll po (ll b, ll p) {
    return !p?1:po(b*b%MOD,p/2)*(p&1?b:1)%MOD;
}

ll inv (ll b) { return po(b,MOD-2); }

ll query(int x) {
    FOR(i,BLOCK) if (u.count(x*invy[i]%MOD))
        return i*BLOCK+u[x*invy[i]%MOD];
}

```

```

        return -1;
    }

    int main() {
        ll cur = 1;
        FOR(i,BLOCK) {
            u[cur] = i;
            cur = primitive*cur%MOD;
        }
        ll t = 1;
        FOR(i,BLOCK) {
            invy[i] = inv(t);
            t = t*cur%MOD;
        }
        ll x; cin >> x;
        cout << query(x) << "\n";
    }

```

4.4 (4) Ternary Search

```

/**
 * Description: use on functions which are strictly
 *             decreasing then strictly increasing
 */

double eval(double x) {
    return (x-5)*(x-5);
}

double ternary(double l, double r) {
    if (abs(r-l) <= 1e-9) return (l+r)/2;
    double l1 = (2*l+r)/3, r1 = (l+2*r)/3;
    return eval(l1) < eval(r1) ? ternary(l,r1) :
        ternary(l1,r);
}

// ternary(-100,100) = 5

```

5 (3) Dynamic Programming

5.1 (3) Distinct Subsequences

```

/**
 * Description: DP eliminates overcounting
 */

int distinct(string S) {
    vi tot(26);
    int ans = 1;
    for (char c: S) {
        int t = (ans-tot[c-'A']+MOD)%MOD;
        tot[c-'A'] = (tot[c-'A']+t)%MOD;
        ans = (ans+t)%MOD;
    }
    return ans;
}

```

5.2 (3) Knapsack

// <https://open.kattis.com/problems/knapsack>

```

double C;
int n,v[2000],w[2000],dp[2001][2001];

void solve() {
    FOR(i,n) cin >> v[i] >> w[i];
    FOR(i,n) {
        FOR(j,C+1) dp[i+1][j] = dp[i][j];
        FOR(j,C+1) if (w[i]+j <= C) dp[i+1][w[i]+j] =
            max(dp[i+1][w[i]+j],dp[i][j]+v[i]);
    }

    vi ans;
    int x = C;
    FORd(i,n) if (dp[i][x] != dp[i+1][x]) x -= w[i],
        ans.pb(i);

    cout << ans.size() << "\n";
    for (int i: ans) cout << i << " ";
    cout << "\n";
}

```

5.3 (3) Longest Common Subsequence

```

/**
 * Description: Classic DP example
 */

int dp[1001][1001];
string a,b;

int main() {
    cin >> a >> b;
    FOR(i,sz(a)) FOR(j,b.sz(b)) {
        dp[i+1][j+1] = max(dp[i+1][j],dp[i][j+1]);
        if (a[i] == b[j]) dp[i+1][j+1] =
            max(dp[i+1][j+1],dp[i][j]+1);
    }
    cout << dp[sz(a)][sz(b)];
}

```

5.4 (3) Longest Increasing Subsequence

```

/**
 * Description: DP with Binary Search
 */

vi bes = {0};
int n;

void ad(int x) {
    int lo = 0, hi = sz(bes)-1;
    while (lo < hi) {
        int mid = (lo+hi+1)/2;

```

```

        if (bes[mid] < x) lo = mid;
        else hi = mid-1;
    }
    if (lo == sz(bes)-1) bes.pb(0);
    bes[lo+1] = x;
}

int main() {
    cin >> n;
    FOR(i,n) {
        int x; cin >> x;
        ad(x);
    }
    cout << sz(bes)-1;
}

```

5.5 (4) Divide Conquer

```

/**
 * Source: Own
 * Usage: CEOI 2004 Two Sawmills
 */

void divi(int lo, int hi, int L, int R) {
    if (lo > hi) return;

    int mid = (lo+hi)/2;
    pair<ll,int> tmp = {1e18,-1};
    FOR(i,max(mid+1,L),R+1) tmp =
        min(tmp,{calc(0,mid)+calc(mid+1,i)+calc(i+1,n),i});
    ans = min(ans,tmp.f);

    divi(lo,mid-1,L,tmp.s);
    divi(mid+1,hi,tmp.s,R);
}

```

5.6 (4) Traveling Salesman

```

/**
 * Description: Bitset DP example
 * Solves TSP for small N
 */

const int MX = 15;

int N, dp[MX][1<<MX], dist[MX][MX];

int solve() {
    FOR(i,N) FOR(j,1<<N) dp[i][j] = MOD;

    dp[0][1] = 0;
    FOR(j,1<<N) FOR(i,N) if (j&(1<<i))
        FOR(k,N) if (!(j&(1<<k)))
            dp[k][j^(1<<k)] =
                min(dp[k][j^(1<<k)],dp[i][j]+dist[i][k]);

    int ans = MOD;
}

```

```

    FOR(j,1,N) ans =
        min(ans,dp[j][(1<<N)-1]+dist[j][0]);
    return ans;
}

int main() {
    int T; cin >> T;
    FOR(i,T) {
        cin >> N; N++;
        FOR(j,N) FOR(k,N) if (j != k) cin >>
            dist[j][k];
        cout << solve() << "\n";
    }
}

```

6 (3) Strings

6.1 (3) Hashing

```

/**
 * Source: own
 * Description: Pairs reduce frequency of collision
 * Verification: Dec 17 Plat 1
 */

typedef pair<ll, ll> pll;

template<class T> pair<T,T> operator+(const pair<T,T>&
    l, const pair<T,T>& r) {
    return {(l.f+r.f)%MOD,(l.s+r.s)%MOD};
}

template<class T> pair<T,T> operator-(const pair<T,T>&
    l, const pair<T,T>& r) {
    return {(l.f-r.f+MOD)%MOD,(l.s-r.s+MOD)%MOD};
}

template<class T> pair<T,T> operator*(const pair<T,T>&
    l, const T& r) {
    return {l.f*r%MOD,l.s*r%MOD};
}

template<class T> pair<T,T> operator*(const pair<T,T>&
    l, const pair<T,T>& r) {
    return {l.f*r.f%MOD,l.s*r.s%MOD};
}

struct hsh {
    string S;
    vector<pll> po, ipo, cum;
    pll base = mp(948392576,573928192);

    ll modpow(ll b, ll p) {
        return !p?1:modpow(b*b%MOD,p/2)*(p&1?b:1)%MOD;
    }

    ll inv(ll x) {
        return modpow(x,MOD-2);
    }
}

```

```

void gen(string _S) {
    S = _S;
    po.resize(sz(S)), ipo.resize(sz(S)),
    cum.resize(sz(S)+1);
    po[0] = ipo[0] = {1,1};
    FOR(i,1,sz(S)) {
        po[i] = po[i-1]*base;
        ipo[i] = {inv(po[i].f),inv(po[i].s)};
    }
    FOR(i,sz(S)) cum[i+1] =
        cum[i]+po[i]*(1ll)(S[i]-'a'+1);
}

pll get(int l, int r) {
    return ipo[l]*(cum[r+1]-cum[l]);
}

};

int lcp(hsh& a, hsh& b) { // can be used to generate a
    suffix array
    int lo = 0, hi = min(sz(a.S),sz(b.S));
    while (lo < hi) {
        int mid = (lo+hi+1)/2;
        if (a.get(0,mid-1) == b.get(0,mid-1)) lo = mid;
        else hi = mid-1;
    }
    return lo;
}

int main() {
    string _S = "abacaba";
    hsh h; h.gen(_S);
    FOR(i,sz(_S)) FOR(j,i,sz(_S)) cout << i << " " <<
        j << " " << h.get(i,j).f << " " <<
        h.get(i,j).s << "\n";

    hsh H; H.gen("abadaba");
    cout << lcp(h,H);
}

```

6.2 (4) String Searching

6.2.1 (4) Aho-Corasick

```

/**
 * Source: https://ideone.com/0cMjZJ
 * Usage:
 * https://open.kattis.com/problems/stringmultimatching
 */

template<int SZ> struct Aho {
    int link[SZ], dict[SZ], sz = 1, num = 0;
    vector<pii> ind[SZ];
    map<char,int> to[SZ];
    vi oc[SZ];
    queue<int> q;

    Aho() {
        memset(link,0,sizeof link);

```

```

        memset(dict,0,sizeof dict);
    }

    void add(string s) {
        int v = 0;
        for(auto c: s) {
            if (!to[v].count(c)) to[v][c] = sz++;
            v = to[v][c];
        }
        dict[v] = v; ind[v].pb({++num,sz(s)});
    }

    void push_links() {
        link[0] = -1; q.push(0);
        while (sz(q)) {
            int v = q.front(); q.pop();
            for (auto it: to[v]) {
                char c = it.f; int u = it.s, j =
                    link[v];
                while (j != -1 && !to[j].count(c)) j =
                    link[j];
                if (j != -1) {
                    link[u] = to[j][c];
                    if (!dict[u]) dict[u] =
                        dict[link[u]];
                }
                q.push(u);
            }
        }
    }

    void process(int pos, int cur) {
        cur = dict[cur];
        while (cur) {
            for (auto a: ind[cur])
                oc[a.f].pb(pos-a.s+1);
            cur = dict[link[cur]];
        }
    }

    int nex(int pos, int cur, char c) {
        while (cur != -1 && !to[cur].count(c)) cur =
            link[cur];
        if (cur == -1) cur = 0;
        else cur = to[cur][c];
        process(pos, cur);
        return cur;
    }
};

Aho<100001> A;

int n;

void solve() {
    A = Aho<100001>();
    cin >> n;
    FOR(i,n) {
        string pat; getline(cin,pat); if (!i)
            getline(cin,pat);
        A.add(pat);
    }
}

```

6.2.2 (4) Bitset Trie

6.2.3 (4) Z

```

vi ans(N); ans[0] = N;
while (s[1+ans[1]] == s[ans[1]]) ans[1] ++;

int L = 1, R = ans[1];
FOR(i,2,N) {
    if (i <= R) ans[i] = min(R-i+1,ans[i-L]);
    while (s[i+ans[i]] == s[ans[i]]) ans[i] ++;
    if (i+ans[i]-1 > R) L = i, R = i+ans[i]-1;
}
return ans;
}

vi get(string a, string b) { // find prefixes of a in b
    string s = a+"@"+b;
    vi t = z(s);
    return vi(t.begin()+a.length()+1,t.end());
}

int main() {
    vi x = z("abcababcbabcaba");
    for (int i: x) cout << i << " ";
    cout << "\n";

    x = get("abcab","uwetrabcerabcb");
    for (int i: x) cout << i << " ";
}

```

6.3 (4) Suffix Array

21

```

    bucket(1), bucket(0);
}*/

suffix_array(string _str) {
    str = _str; N = sz(str);
    P.pb(vi(N)); L.resize(N);
    FOR(i,N) P[0][i] = str[i];

    for (int stp = 1, cnt = 1; cnt < N; stp ++,
        cnt *= 2) {
        P.pb(vi(N));
        FOR(i,N) L[i] = {P[stp-1][i], i+cnt < N ?
            P[stp-1][i+cnt] : -1, i};
        sort(all(L));
        // bucket_sort();
        FOR(i,N) {
            if (i && mp(L[i][0], L[i][1]) ==
                mp(L[i-1][0], L[i-1][1]))
                P[stp][L[i][2]] = P[stp][L[i-1][2]];
            else P[stp][L[i][2]] = i;
        }

        idx.resize(N);
        FOR(i, sz(P.back())) idx[P.back()[i]] = i;
    }

    int lcp(int x, int y) {
        int res = 0;
        if (x == y) return N-x;
        for (int k = sz(P) - 1; k >= 0 && x < N && y <
            N; k--) {
            if (P[k][x] == P[k][y]) {
                x += 1 << k;
                y += 1 << k;
                res += 1 << k;
            }
        }
        return res;
    }
};

```

6.4 (5) Manacher

```

/**
 * Source: http://codeforces.com/blog/entry/12143
 * Description: Calculates length of largest palindrome
               centered at each character of string
 * Verification: http://www.spoj.com/problems/MSUBSTR/
 */

vi manacher(string s) {
    string s1 = "@#";
    for (char c: s) s1 += c, s1 += "#";
    s1[s1.length()-1] = '&';

    vi ans(s1.length()-1);
    int lo = 0, hi = 0;
    FOR(i, 1, s1.length()-1) {
        ans[i] = min(hi-i, ans[hi-i+lo]);
    }
}

```

```

    while (s1[i-ans[i]-1] == s1[i+ans[i]+1])
        ans[i] ++;
    if (i+ans[i] > hi) lo = i-ans[i], hi =
        i+ans[i];
}

ans.erase(ans.begin());
FOR(i, sz(ans)) if ((i&1) == (ans[i]&1)) ans[i] ++;
// adjust lengths
return ans;
}

int main() {
    int T; cin >> T;
    FOR(i, T) {
        pii bes = {0, 0};
        string s; cin >> s;
        vi t = manacher(s);
        for (int i: t) {
            if (i > bes.f) bes = {i, 1};
            else if (i == bes.f) bes.s++;
        }
        cout << bes.f << " " << bes.s << "\n";
    }
}

```

7 (3) Trees

7.1 (3) Kruskal

```

/**
 * Source: own
 * Description: computes the minimum spanning tree in
               O(ElogE) time
 * Verification: USACO superbull
 */

template<int SZ> struct DSU {
    int par[SZ], sz[SZ];
    DSU() {
        FOR(i, SZ) par[i] = i, sz[i] = 1;
    }

    int get(int x) { // path compression
        if (par[x] != x) par[x] = get(par[x]);
        return par[x];
    }

    bool unite(int x, int y) { // union-by-rank
        x = get(x), y = get(y);
        if (x == y) return 0;
        if (sz[x] < sz[y]) swap(x, y);
        sz[x] += sz[y], par[y] = x;
        return 1;
    }
};

int ans = 0; // total weight of MST
vector<pair<int, pii>> edge;

```

```

DSU<100> D;

void kruskal() {
    sort(all(edge));
    for (auto a: edge) if (D.unite(a.s.f,a.s.s))
        ans += a.f; // edge is in MST
}

```

7.2 (4) Tree Queries

7.2.1 (4) Centroid Decomposition

```

/**
 * Source: own
 * Verification Problem: Ciel and Commander
 *   (http://codeforces.com/contest/321/problem/C)
 * Code:
 *   http://codeforces.com/contest/321/submission/33952270
 */

const int MX = 100001;

int N, visit[MX], sub[MX], par[MX];
vi adj[MX];

void dfs (int no) {
    sub[no] = 1;
    for (int i: adj[no]) if (!visit[i] && i !=
        par[no]) {
        par[i] = no;
        dfs(i);
        sub[no] += sub[i];
    }
}

int get_centroid(int x) {
    par[x] = 0;
    dfs(x);
    int sz = sub[x];
    while (1) {
        pii mx = {0,0};
        for (int i: adj[x]) if (!visit[i] && i !=
            par[x]) mx = max(mx,{sub[i],i});
        if (mx.f*2 > sz) x = mx.s;
        else return x;
    }
}

void solve (int x) {
    x = get_centroid(x); visit[x] = 1;
    // do stuff
    cout << x << "\n";
    for (int i: adj[x]) if (!visit[i]) solve(i);
}

int main() {
    cin >> N;
    FOR(i,N-1) {
        int a,b; cin >> a >> b;

```

```

        adj[a].pb(b), adj[b].pb(a);
    }
    solve(1);
}

```

7.2.2 (4) Heavy Light Set

```

/**
 * Description: offline subtree queries in  $O(N \log^2 N)$ 
 * Verification: January Easy 2018 - Shubham & Tree 1
 */

const int MX = 200001;

struct HeavyLightSet {
    int loc[MX], sub[MX], par[MX], val[MX];
    vi child[MX];
    map<int,int> dat[MX];

    void comb(int a, int b) {
        int A = loc[a], B = loc[b];
        if (sz(dat[A]) < sz(dat[B])) swap(a,b),
            swap(A,B);
        for (auto& x: dat[B]) dat[A][x.f] += x.s;
        dat[B].clear(); loc[b] = A;
    }

    void process(int ind) {
        sub[ind] = 1; loc[ind] = ind;
        dat[ind][val[ind]]++;
        for (int i: child[ind]) {
            process(i);
            comb(i,ind);
            sub[ind] += sub[i];
        }
        // now do stuff with values
    }
};

```

7.2.3 (4) Heavy-Light Decomposition

```

/**
 * Source: http://codeforces.com/blog/entry/22072
 * Verification: USACO Grass Planting
 */

// insert LazySegTree Template

vector<vi> graph;

template <int V> struct HeavyLight { // sum queries,
    sum updates
    int parent[V], heavy[V], depth[V];
    int root[V], treePos[V];
    LazySegTree<V> tree;

    void init() {
        int n = graph.size();

```

```

FOR(i,1,n+1) heavy[i] = -1;
parent[1] = -1, depth[1] = 0;
dfs(1);
for (int i = 1, currentPos = 0; i <= n; ++i)
    if (parent[i] == -1 || heavy[parent[i]]
        != i)
        for (int j = i; j != -1; j =
            heavy[j]) {
            root[j] = i;
            treePos[j] = currentPos++;
        }
}

int dfs(int v) {
    int size = 1, maxSubtree = 0;
    for (auto u : graph[v]) if (u != parent[v]) {
        parent[u] = v;
        depth[u] = depth[v] + 1;
        int subtree = dfs(u);
        if (subtree > maxSubtree) heavy[v] = u,
            maxSubtree = subtree;
        size += subtree;
    }
    return size;
}

template <class BinaryOperation>
void processPath(int u, int v, BinaryOperation op)
{
    for (; root[u] != root[v]; v =
        parent[root[v]]) {
        if (depth[root[u]] > depth[root[v]])
            swap(u, v);
        op(treePos[root[v]], treePos[v]);
    }
    if (depth[u] > depth[v]) swap(u, v);
    op(treePos[u]+1, treePos[v]); // assumes
        values are stored in edges, not vertices
}

void modifyPath(int u, int v, int value) {
    processPath(u, v, [this, &value](int l, int r) {
        tree.upd(l, r, value); });
}

ll queryPath(int u, int v) {
    ll res = 0;
    processPath(u, v, [this, &res](int l, int r) {
        res += tree.qsum(l, r); });
    return res;
}

HeavyLight<1<<17> H;
int N,M;

int main() {
    cin >> N >> M;
    graph.resize(N+1);
    FOR(i,N+1) {
        int a,b; cin >> a >> b;
        graph[a].pb(b), graph[b].pb(a);

```

```

    }
    H.init();
    FOR(i,M) {
        char c; int A,B;
        cin >> c >> A >> B;
        if (c == 'P') H.modifyPath(A,B,1);
        else cout << H.queryPath(A,B) << "\n";
    }
}

```

7.2.4 (4) LCA Demo

```

// RMQ2 L;

int Q;

int main() {
    cin >> L.V >> Q >> L.R;
    FOR(i,L.V-1) {
        int u,v; cin >> u >> v;
        L.addEdge(u,v);
    }
    L.construct();

    FOR(i,Q) {
        int u,v; cin >> u >> v;
        cout << L.lca(u,v) << "\n";
    }
}

```

7.2.5 (4) LCA with Binary Jumps

```

/**
 * Source: USACO Camp
 * Verification: Debug the Bugs
 */

const int MAXN = 100001, MAXK = 17;

struct LCA {
    int V, R;
    vi edges[MAXN];
    int parK[MAXK][MAXN];
    int depth[MAXN];

    void addEdge(int u, int v) {
        edges[u].pb(v), edges[v].pb(u);
    }

    void dfs(int u, int prev){
        parK[0][u] = prev;
        depth[u] = depth[prev]+1;
        for (int v: edges[u]) if (v != prev) dfs(v, u);
    }

    void construct() {
        dfs(R, 0);
        FOR(k,1,MAXK) FOR(i,1,V+1)

```



```

        parK[k][i] = parK[k-1][parK[k-1][i]];
    }

    int lca(int u, int v){
        if (depth[u] < depth[v]) swap(u,v);

        FORd(k,MAXK) if (depth[u] >= depth[v]+(1<<k))
            u = parK[k][u];
        FORd(k,MAXK) if (parK[k][u] != parK[k][v]) u =
            parK[k][u], v = parK[k][v];

        if(u != v) u = parK[0][u], v = parK[0][v];
        return u;
    }

    int dist(int u, int v) {
        return depth[u]+depth[v]-2*depth[lca(u,v)];
    }
};

```

7.2.6 (4) LCA with RMQ

```

/**
 * Description: Euler Tour LCA w/ O(1) query
 * Source: own
 * Verification: Debug the Bugs
 */

const int MAXN = 100001, MAXK = 18;

struct RMQ2 {
    vi edges[MAXN];
    pii rmq[MAXK][2*MAXN];
    int depth[MAXN], pos[MAXN];

    int N, R, nex = 0;

    void addEdge(int u, int v) {
        edges[u].pb(v), edges[v].pb(u);
    }

    void dfs(int u, int prev){
        pos[u] = nex; depth[u] = depth[prev]+1;
        rmq[0][nex++] = {depth[u],u};
        for (int v: edges[u]) if (v != prev) {
            dfs(v, u);
            rmq[0][nex++] = {depth[u],u};
        }
    }

    void construct() {
        dfs(R, 0);
        FOR(k,1,MAXK) FOR(i,nex) if (i+(1<<(k-1)) <
            nex) rmq[k][i] =
            min(rmq[k-1][i],rmq[k-1][i+(1<<(k-1))]);
    }

    int lca(int u, int v){
        u = pos[u], v = pos[v];
        if (u > v) swap(u,v);

```

```

        int x = 31-__builtin_clz(v-u+1);
        return min(rmq[x][u],rmq[x][v-(1<<x)+1]).s;
    }

    int dist(int u, int v) {
        return depth[u]+depth[v]-2*depth[lca(u,v)];
    }
};

```

7.3 (5) Tree Diameter

```

/**
 * Might not be obvious why this works!
 * Verification: http://www.spoj.com/problems/PT07Z/
 */

const int MX = 10001;

int n, dist[MX];
vi adj[MX];

void dfs(int cur, int pre) {
    for (int i: adj[cur]) if (i != pre) {
        dist[i] = dist[cur]+1;
        dfs(i,cur);
    }
}

void dfs(int cur) {
    memset(dist,0,sizeof dist);
    dfs(cur,-1);
}

int treeDiameter() {
    dfs(1);
    int bes = 0; FOR(i,1,n+1) if (dist[i] > dist[bes])
        bes = i;
    dfs(bes); FOR(i,1,n+1) if (dist[i] > dist[bes])
        bes = i;
    return dist[bes];
}

int main() {
    cin >> n;
    FOR(i,n-1) {
        int a, b; cin >> a >> b;
        adj[a].pb(b), adj[b].pb(a);
    }
    cout << treeDiameter();
}

```

8 (4) Flows

8.1 (5) Dinic

```

/**
 * Source: GeeksForGeeks

```

```

* Verification: Problem Fashion
  (https://csacademy.com/contest/rmi-2017-day-1/task/fashion/)
* Code: https://pastebin.com/VJxTvEg1
*/

struct Edge {
    int v;
    ll flow, C;
    int rev;
};

template<int SZ> struct Dinic {
    int level[SZ], start[SZ];
    vector<Edge> adj[SZ];

    void addEdge(int u, int v, int C) {
        Edge a{v, 0, C, sz(adj[v])};
        Edge b{u, 0, 0, sz(adj[u])};
        adj[u].pb(a), adj[v].pb(b);
    }

    bool BFS(int s, int t) {
        FOR(i,SZ) level[i] = -1;
        level[s] = 0;

        queue<int> q; q.push(s);
        while (!q.empty()) {
            int u = q.front(); q.pop();
            for (auto e: adj[u])
                if (level[e.v] < 0 && e.flow < e.C) {
                    level[e.v] = level[u] + 1;
                    q.push(e.v);
                }
        }

        return level[t] >= 0;
    }

    ll sendFlow(int u, ll flow, int t) {
        if (u == t) return flow;

        for ( ; start[u] < sz(adj[u]); start[u]++) {
            Edge &e = adj[u][start[u]];

            if (level[e.v] == level[u]+1 && e.flow <
                e.C) {
                ll curr_flow = min(flow, e.C - e.flow);
                ll temp_flow = sendFlow(e.v, curr_flow,
                    t);

                if (temp_flow > 0) {
                    e.flow += temp_flow;
                    adj[e.v][e.rev].flow -= temp_flow;
                    return temp_flow;
                }
            }
        }

        return 0;
    }

    ll maxFlow(int s, int t) {

```

```

        if (s == t) return -1;
        ll total = 0;

        while (BFS(s, t)) {
            FOR(i,SZ) start[i] = 0;
            while (ll flow = sendFlow(s, INT_MAX, t))
                total += flow;
        }

        return total;
    }
};

```

8.2 (5) Flows Demo

```

/**
 * Description: SPOJ fastflow
 * Verify Dinic, Push-Relabel
 */

int N,M;
PushRelabel<5001> D; // or Dinic

int main() {
    cin >> N >> M;
    FOR(i,M) {
        int a,b,c; cin >> a >> b >> c;
        D.addEdge(a,b,c);
        D.addEdge(b,a,c);
    }
    cout << D.maxFlow(1,N);
}

```

8.3 (5) Push-Relabel

```

/**
 * Source: http://codeforces.com/blog/entry/14378
 * Verification: SPOJ fastflow
 */

struct Edge {
    int v;
    ll flow, C;
    int rev;
};

template <int SZ> struct PushRelabel {
    vector<Edge> adj[SZ];
    ll excess[SZ];
    int dist[SZ], count[SZ+1], b = 0;
    bool active[SZ];
    vi B[SZ];

    void addEdge(int u, int v, int C) {
        Edge a{v, 0, C, sz(adj[v])};
        Edge b{u, 0, 0, sz(adj[u])};
        adj[u].pb(a), adj[v].pb(b);
    }

```

```

}

void enqueue (int v) {
    if (!active[v] && excess[v] > 0 && dist[v] <
        SZ) {
        active[v] = 1;
        B[dist[v]].pb(v);
        b = max(b, dist[v]);
    }
}

void push (int v, Edge &e) {
    ll amt = min(excess[v], e.C-e.flow);
    if (dist[v] == dist[e.v]+1 && amt > 0) {
        e.flow += amt, adj[e.v][e.rev].flow -= amt;
        excess[e.v] += amt, excess[v] -= amt;
        enqueue(e.v);
    }
}

void gap (int k) {
    FOR(v,SZ) if (dist[v] >= k) {
        count[dist[v]] --;
        dist[v] = SZ;
        count[dist[v]] ++;
        enqueue(v);
    }
}

void relabel (int v) {
    count[dist[v]] --; dist[v] = SZ;
    for (auto e: adj[v]) if (e.C > e.flow) dist[v]
        = min(dist[v], dist[e.v] + 1);
    count[dist[v]] ++;
    enqueue(v);
}

void discharge(int v) {
    for (auto &e: adj[v]) {
        if (excess[v] > 0) push(v,e);
        else break;
    }
    if (excess[v] > 0) {
        if (count[dist[v]] == 1) gap(dist[v]);
        else relabel(v);
    }
}

ll maxFlow (int s, int t) {
    for (auto &e: adj[s]) excess[s] += e.C;

    count[0] = SZ;
    enqueue(s); active[t] = 1;

    while (b >= 0) {
        if (sz(B[b])) {
            int v = B[b].back(); B[b].pop_back();
            active[v] = 0; discharge(v);
        } else b--;
    }
    return excess[t];
}

```

```
};
```

8.4 (6) MinCostFlow

```

/**
 * Source: GeeksForGeeks
 */

struct Edge {
    int v, flow, C, rev, cost;
};

template<int SZ> struct mcf {
    pii pre[SZ];
    int cost[SZ], num[SZ], SC, SNC;
    ll flo, ans, ccost;
    vector<Edge> adj[SZ];

    void addEdge(int u, int v, int C, int cost) {
        Edge a{v, 0, C, sz(adj[v]), cost};
        Edge b{u, 0, 0, sz(adj[u]), -cost};
        adj[u].pb(a), adj[v].pb(b);
    }

    void reweight() {
        FOR(i,SZ) {
            for (auto& p: adj[i]) p.cost +=
                cost[i]-cost[p.v];
        }
    }

    bool spfa() {
        FOR(i,SZ) cost[i] = MOD, num[i] = 0;
        cost[SC] = 0, num[SC] = MOD;
        priority_queue<pii,vector<pii>,greater<pii>>
            todo; todo.push({0,SC});

        while (todo.size()) {
            pii x = todo.top(); todo.pop();
            if (x.f > cost[x.s]) continue;
            for (auto a: adj[x.s]) if (x.f+a.cost <
                cost[a.v] && a.flow < a.C) {
                pre[a.v] = {x.s,a.rev};
                cost[a.v] = x.f+a.cost;
                num[a.v] = min(a.C-a.flow,num[x.s]);
                todo.push({cost[a.v],a.v});
            }
        }

        ccost += cost[SNC];
        return num[SNC] > 0;
    }

    void backtrack() {
        flo += num[SNC], ans += (ll)num[SNC]*ccost;
        for (int x = SNC; x != SC; x = pre[x].f) {
            adj[x][pre[x].s].flow -= num[SNC];
            int t = adj[x][pre[x].s].rev;
            adj[pre[x].f][t].flow += num[SNC];
        }
    }
}

```

```

}

pii mincostflow(int sc, int snc) {
    SC = sc, SNC = snc;
    flo = ans = ccost = 0;

    spfa();
    while (1) {
        reweight();
        if (!spfa()) return {flo, ans};
        backtrack();
    }
}

};

mcf<100> m;

int main() {
    m.addEdge(0, 1, 16, 5);
    m.addEdge(1, 2, 13, 7);
    m.addEdge(1, 2, 13, 8);

    pii x = m.mincostflow(0, 2);
    cout << x.f << " " << x.s;
}

```

9 (4) Geometry

9.1 (4) Convex Hull

```

/**
 * Source: Wikibooks
 * Usage: https://open.kattis.com/problems/convexhull
 */

ll cross(pii O, pii A, pii B) {
    return
        (ll)(A.f-O.f)*(B.s-O.s)-(ll)(A.s-O.s)*(B.f-O.f);
}

vector<pii> convex_hull(vector<pii> P) {
    sort(P.begin(), P.end());
    P.erase(unique(P.begin(), P.end()), P.end());
    if (P.size() == 1) return P;

    int n = P.size();

    vector<pii> bot = {P[0]};
    FOR(i, 1, n) {
        while (bot.size() > 1 &&
            cross(bot[bot.size()-2], bot.back(), P[i])
            <= 0) bot.pop_back();
        bot.pb(P[i]);
    }
    bot.pop_back();

    vector<pii> up = {P[n-1]};
    FORd(i, n-1) {

```

```

        while (up.size() > 1 && cross(up[up.size()-2],
            up.back(), P[i]) <= 0) up.pop_back();
        up.pb(P[i]);
    }
    up.pop_back();

    bot.insert(bot.end(), all(up));
    return bot;
}

int main() {
    int n;
    while (cin >> n) {
        if (n == 0) break;
        vector<pii> P(n); FOR(i, n) cin >> P[i].f >>
            P[i].s;
        vector<pii> hull = convex_hull(P);

        cout << hull.size() << "\n";
        for (auto a: hull) cout << a.f << " " << a.s
            << "\n";
    }
}

```

9.2 (4) MaxCollinear

```

/**
 * Source: own
 * Usage: https://open.kattis.com/problems/maxcollinear
 */

int n, mx, ans;
map<pair<pii, int>, int> m;
pii p[1000];

pair<pii, int> getline(pii a, pii b) {
    pii z = {b.f-a.f, b.s-a.s};
    swap(z.f, z.s); z.f *= -1;
    int g = __gcd(z.f, z.s); z.f /= g, z.s /= g;
    if (z.f < 0 || (z.f == 0 && z.s < 0)) z.f *= -1,
        z.s *= -1;
    return {z, z.f*a.f+z.s*a.s};
}

void solve() {
    mx = ans = 0; m.clear();
    FOR(i, n) cin >> p[i].f >> p[i].s;
    FOR(i, n) FOR(j, i+1, n) m[getline(p[i], p[j])] ++;

    for (auto a: m) mx = max(mx, a.s);
    FOR(i, 1, n+1) if (i*(i-1)/2 <= mx) ans = i;
    cout << ans << "\n";
}

```

9.3 (4) Pair Operators

```

/**

```

```

* Source: own
*/

template<class T> pair<T,T> operator+(const pair<T,T>&
    l, const pair<T,T>& r) {
    return {l.f+r.f,l.s+r.s};
}

template<class T> pair<T,T> operator-(const pair<T,T>&
    l, const pair<T,T>& r) {
    return {l.f-r.f,l.s-r.s};
}

template<class T> pair<T,T> operator*(const pair<T,T>&
    l, T r) {
    return {l.f*r,l.s*r};
}

template<class T> pair<T,T> operator/(const pair<T,T>&
    l, T r) {
    return {l.f/r,l.s/r};
}

template<class T> double mag(pair<T,T> p) {
    return sqrt(p.f*p.f+p.s*p.s);
}

template<class T> pair<T,T> operator*(const pair<T,T>&
    l, const pair<T,T>& r) {
    // l.f+l.s*i, r.f+r.s*i
    return {l.f*r.f-l.s*r.s,l.s*r.f+l.f*r.s};
}

template<class T> pair<T,T> operator/(const pair<T,T>&
    l, const pair<T,T>& r) {
    // l.f+l.s*i, r.f+r.s*i
    pair<T,T> z =
        {r.f/(r.f*r.f+r.s*r.s),-r.s/(r.f*r.f+r.s*r.s)};
    return l*z;
}

template<class T> double area(pair<T,T> a, pair<T,T>
    b, pair<T,T> c) {
    b = b-a, c = c-a;
    return (b.f*c.s-b.s*c.f)/2;
}

template<class T> double dist(pair<T,T> l, pair<T,T>
    r) {
    return mag(r-l);
}

template<class T> double dist(pair<T,T> o, pair<T,T>
    x, pair<T,T> d) { // signed distance
    return 2*area(o,x,x+d)/mag(d);
}

```

9.4 (5) Line Segment Intersection

```
/**
```

```

* Source:
    https://open.kattis.com/problems/segmentintersection
* If numbers are small enough, fractions are
    recommended.
*/

typedef pair<double,double> pdd;

pii A,B,C,D;

pdd operator*(int x, pdd y) {
    return {x*y.f,x*y.s};
}

pdd operator/(pdd y, int x) {
    return {y.f/x,y.s/x};
}

pdd operator+(pdd l, pdd r) {
    return {l.f+r.f,l.s+r.s};
}

int sgn(pii a, pii b, pii c) {
    return (b.s-a.s)*(c.f-a.f)-(b.f-a.f)*(c.s-a.s);
}

pdd get(pii a, pii b, pii c, pii d) {
    return (abs(sgn(a,b,c))*d+abs(sgn(a,b,d))*c)
        /(abs(sgn(a,b,c))+abs(sgn(a,b,d)));
}

void solve() {
    cin >> A.f >> A.s >> B.f >> B.s >> C.f >> C.s >>
        D.f >> D.s;
    if (A > B) swap(A,B);
    if (C > D) swap(C,D);
    int a1 = sgn(A,B,C), a2 = sgn(A,B,D);
    if (a1 > a2) swap(a1,a2);
    if (!(a1 <= 0 && a2 >= 0)) {
        cout << "none\n";
        return;
    }
    if (a1 == 0 && a2 == 0) {
        if (sgn(A,C,D) != 0) {
            cout << "none\n";
            return;
        }
        pii x1 = max(A,C), x2 = min(B,D);
        if (x1 > x2) cout << "none\n";
        else if (x1 == x2) cout << (double)x1.f << " "
            << (double)x1.s << "\n";
        else cout << (double)x1.f << " " <<
            (double)x1.s << " " << (double)x2.f << " "
            << (double)x2.s << "\n";
        return;
    }
    pdd z = get(A,B,C,D);
    if (mp((double)A.f,(double)A.s) <= z && z <=
        mp((double)B.f,(double)B.s)) cout << z.f << "
        " << z.s << "\n";
    else cout << "none\n";
}

```

```
int main() {
    int n; cin >> n;
    cout << fixed << setprecision(2);
    FOR(i,n) solve();
}
```

9.5 (5) Polygon Area

```
/**
 * Description: Shoelace Formula
 * Usage: https://open.kattis.com/problems/polygonarea
 */

double area(vector<pii> v) {
    double x = 0;
    FOR(i,sz(v)) {
        int j = (i+1)%sz(v);
        x += (1l)v[i].f*v[j].s;
        x -= (1l)v[j].f*v[i].s;
    }
    return abs(x)/2;
}
```

9.6 (6) 3D Geometry

```
/**
 * Description: Basic 3D Geometry
 * Usage: AMPPZ 2011 Cross Spider
 */

typedef vector<ll> vl;

typedef long double ld;

int n;
vector<vl> cur;

vl operator-(vl a, vl b) {
    vl c(sz(a)); FOR(i,sz(a)) c[i] = a[i]-b[i];
    return c;
}

bool ismult(vl b, vl c) {
    if ((1d)b[0]*c[1] != (1d)b[1]*c[0]) return 0;
    if ((1d)b[0]*c[2] != (1d)b[2]*c[0]) return 0;
    if ((1d)b[2]*c[1] != (1d)b[1]*c[2]) return 0;
    return 1;
}

bool collinear(vl a, vl b, vl c) {
    b = b-a, c = c-a;
    return ismult(b,c);
}

vl cross(vl a, vl b) {
    return {a[1]*b[2]-a[2]*b[1],
```

```
        a[2]*b[0]-a[0]*b[2],
        a[0]*b[1]-a[1]*b[0]};
}

bool coplanar(vl a, vl b, vl c, vl d) {
    b = b-a, c = c-a, d = d-a;
    return ismult(cross(b,c),cross(b,d));
}
```

9.7 (6) Circles

```
/**
 * Source: Own
 * Usage:
 * https://codeforces.com/tournaments/s8thqrnQL2YPK7XQt/L
 */

typedef complex<double> cd;
typedef pair<cd,double> circle;

cd intersect(circle a, circle b, int x = 0) {
    double d = sqrt(norm(a.f-b.f));
    double co = (a.s*a.s+d*d-b.s*b.s)/(2*a.s*d);
    double theta = acos(co);

    cd tmp = (b.f-a.f)/d;
    if (x == 0) return a.f+tmp*a.s*polar(1.0,theta);
    return a.f+tmp*a.s*polar(1.0,-theta);
}

double arc(circle x, cd a, cd b) {
    cd d = (a-x.f)/(b-x.f);
    return x.s*acos(d.real());
}

bool on (circle x, cd y) {
    return norm(y-x.f) == x.s*x.s;
}

int main() {
    cout << intersect({0,2},{1,1}) << "\n";
    cout << arc({0,1},cd(1,0),cd(0,1)) << "\n";
    cout << on({0,1},1) << "\n";
}
```

9.8 (6) Closest Pair

```
/**
 * Source: GeeksForGeeks
 * Description: Nlog^2N, can be improved
 * Use: https://open.kattis.com/problems/closestpair2
 */

pair<double,pair<pdd,pdd>> MN = {INF,{0,0},{0,0}};

int n;
```

```

bool cmp(pdd a, pdd b) {
    return a.s < b.s;
}

double dist(pdd a, pdd b) {
    b.f -= a.f, b.s -= a.s;
    return sqrt(b.f*b.f+b.s*b.s);
}

pair<double,pair<pdd,pdd>> strip(vector<pdd> v, double
    di) {
    pair<double,pair<pdd,pdd>> ans = MN;
    FOR(i,v.size()) FOR(j,i+1,v.size()) {
        if (v[i].s+di <= v[j].s) break;
        ans = min(ans,{dist(v[i],v[j]),{v[i],v[j]}});
    }
    return ans;
}

pair<double,pair<pdd,pdd>> bes (vector<pdd> v) {
    if (v.size() == 1) return MN;
    int M = v.size()/2;
    vector<pdd> v1(v.begin(),v.begin()+M),
        v2(v.begin()+M,v.end());
    auto a = bes(v1), b = bes(v2);
    double di = min(a.f,b.f);

    vector<pdd> V;
    FOR(i,v.size()) if (v[i].f > v[M].f-di && v[i].f <
        v[M].f+di) V.pb(v[i]);
    sort(V.begin(),V.end(),cmp);

    auto z = strip(V,di);
    return min(min(a,b),z);
}

int main() {
    cout << fixed << setprecision(2);
    while (cin >> n) {
        if (n == 0) break;
        vector<pdd> v(n);
        FOR(i,n) cin >> v[i].f >> v[i].s;
        sort(v.begin(),v.end());
        auto a = bes(v);
        cout << a.s.f.f << " " << a.s.f.s << " " <<
            a.s.s.f << " " << a.s.s.s << "\n";
    }
}

```

9.9 (6) Point in Polygon

```

/**
 * Source: own
 * Usage:
 *   https://open.kattis.com/problems/pointinpolygon
 */

int n,m;
pii p[1000];

```

```

int area(pii x, pii y, pii z) {
    return (y.f-x.f)*(z.s-x.s)-(y.s-x.s)*(z.f-x.f);
}

bool on(pii x, pii y, pii z) {
    if (area(x,y,z) != 0) return 0;
    return min(x,y) <= z && z <= max(x,y);
}

double get(pii x, pii y, int z) {
    return double((z-x.s)*y.f+(y.s-z)*x.f)/(y.s-x.s);
}

void test(pii z) {
    int ans = 0;
    FOR(i,n) {
        pii x = p[i], y = p[(i+1)%n];
        if (on(x,y,z)) {
            cout << "on\n";
            return;
        }
        if (x.s > y.s) swap(x,y);
        if (x.s <= z.s && y.s > z.s) {
            double t = get(x,y,z.s);
            if (t > z.f) ans++;
        }
    }
    if (ans % 2 == 1) cout << "in\n";
    else cout << "out\n";
}

void solve() {
    FOR(i,n) cin >> p[i].f >> p[i].s;
    cin >> m;
    FOR(i,m) {
        pii z; cin >> z.f >> z.s;
        test(z);
    }
}

```

10 (4) Math

10.1 (4) Matrix

10.1.1 (4) Matrix Exponentiation

```

/**
 * Source: KACTL
 * Verification: https://dmoj.ca/problem/si17c1p5
 */

template<int SZ> struct mat {
    array<array<ll,SZ>,SZ> d;

    mat() {
        FOR(i,SZ) FOR(j,SZ) d[i][j] = 0;
    }

    mat operator+(const mat& m) {

```

```

    mat<SZ> a;
    FOR(i,SZ) FOR(j,SZ) a.d[i][j] =
        (d[i][j]+m.d[i][j]) % MOD;
    return a;
}

mat operator*(const mat& m) {
    mat<SZ> a;
    FOR(i,SZ) FOR(j,SZ) FOR(k,SZ)
        a.d[i][k] = (a.d[i][k]+d[i][j]*m.d[j][k]) %
            MOD;
    return a;
}

mat operator^(ll p) {
    mat<SZ> a, b(*this);
    FOR(i,SZ) a.d[i][i] = 1;

    while (p) {
        if (p&1) a = a*b;
        b = b*b;
        p /= 2;
    }

    return a;
}

void print() {
    FOR(i,SZ) {
        FOR(j,SZ) cout << d[i][j] << " ";
        cout << "\n";
    }
    cout << "-----\n";
}

};

/*
mat<2> x; x.d[0][0] = 1, x.d[1][0] = 2, x.d[1][1] = 1,
    x.d[0][1] = 3;
mat<2> y = x*x;
mat<2> z = x^5;
x.print(), y.print(), z.print();
*/

```

10.1.2 (6) Linear Equation Solver

```

/**
 * Description: Gaussian Elimination
 * Usage:
 *   https://open.kattis.com/problems/equationsolverplus
 */

```

```

typedef long double ld;
typedef vector<vector<ld>> mat;

```

```

ld EPS = 1e-10;
int n;

```

```

void elim(mat& a, int i, int j, int k) {
    ld t = a[k][i];

```

```

    FOR(ind,n+1) a[k][ind] -= t*a[j][ind];
}

void prin(mat& a) {
    FOR(i,n) {
        FOR(j,n+1) cout << a[i][j] << " ";
        cout << "\n";
    }
    cout << "----\n";
}

void solve() {
    mat a(n); FOR(i,n) a[i].resize(n+1);
    FOR(i,n) FOR(j,n) cin >> a[i][j];
    FOR(i,n) cin >> a[i][n];
    int done[n]; FOR(i,n) done[i] = -1;

    FOR(i,n) {
        FOR(j,n) if (done[j] == -1 && abs(a[j][i]) >
            EPS) {
            ld t = a[j][i];
            FOR(k,n+1) a[j][k] /= t;

            FOR(k,n) if (j != k) elim(a,i,j,k);
            done[j] = i; break;
        }
    }

    int num = 0;
    FOR(i,n) if (done[i] == -1) {
        num++;
        if (abs(a[i][n]) > EPS) {
            cout << "inconsistent\n";
            return;
        }
    }

    ld ans[n]; FOR(i,n) ans[i] =
        numeric_limits<double>::max();
    FOR(i,n) if (done[i] != -1) {
        bool bad = 0;
        FOR(j,n) if (j != done[i] && abs(a[i][j]) >
            EPS) {
            bad = 1;
            break;
        }
        if (!bad) ans[done[i]] = a[i][n];
    }

    FOR(i,n) {
        if (ans[i] != numeric_limits<double>::max())
            cout << ans[i];
        else cout << "?";
        cout << " ";
    }
    cout << "\n";
}

```

10.2 (4) Number Theory

10.2.1 (4) Eratosthenes' Sieve


```

/**
 * Source: KACTL?
 * https://open.kattis.com/problems/primesieve
 */

template<int SZ> struct Sieve {
    bitset<SZ+1> comp;
    Sieve() {
        for (int i = 2; i*i <= SZ; ++i) if (!comp[i]) {
            for (int j = i*i; j <= SZ; j += i) comp[j] = 1;
        }
    }
    bool isprime(int x) {
        if (x == 1) return 0;
        return !comp[x];
    }
};

```

10.2.2 (5) Chinese Remainder Theorem

```

/**
 * Source: Own
 * Usage: Kattis generalchineseremainder
 */

ll n,m,a,b;
map<ll,pii> M;
bool bad;

ll inv(ll a, ll b) { // 0 < a < b, gcd(a,b) = 1
    a %= b;
    if (a <= 1) return a;
    ll i = inv(b%a,a);
    ll tmp = -((b/a)*i+((b%a)*i)/a) % b;
    while (tmp < 0) tmp += b;
    return tmp;
}

ll naive(ll n, ll m, ll a, ll b) {
    ll x = (a-b)*inv(m,n) % n;
    ll ans = (m*x+b) % (m*n);
    while (ans < 0) ans += (m*n);
    return ans;
}

void process(ll a, ll n) {
    vector<pii> z;
    for (int i = 2; i*i <= n; ++i) if (n % i == 0) {
        int co = 0;
        while (n % i == 0) n /= i, co++;
        z.pb({i,co});
    }
    if (n != 1) z.pb({n,1});
    for (auto A: z) {
        if (M.count(A.f)) {
            pii p1 = M[A.f];
            pii p2 = {A.s,a%(ll)pow(A.f,A.s)};
            if (p1 > p2) swap(p1,p2);
            if (p2.s%(ll)pow(A.f,p1.f) != p1.s) bad = 1;
        }
    }
}

```

```

        M[A.f] = p2;
    } else M[A.f] = {A.s,a%(ll)pow(A.f,A.s)};
}

ll po(ll b, ll p) {
    ll z = 1;
    FOR(i,p) z *= b;
    return z;
}

void solve() {
    bad = 0, M.clear();
    long long aa,nn,bb,mm; cin >> aa >> nn >> bb >> mm;
    a = aa, n = nn, b = bb, m = mm;
    process(a,n), process(b,m);
    if (bad) {
        cout << "no solution\n";
        return;
    }
    ll a1 = 0, a2 = 1;
    for (auto& x: M) {
        a1 = naive(a2,po(x.f,x.s.f),a1,x.s.s);
        a2 *= po(x.f,x.s.f);
    }
    cout << (ll)a1 << " " << (ll)a2 << "\n";
}

int main() {
    int T; cin >> T;
    FOR(i,T) solve();
}

```

10.2.3 (5) Combinations Basic

```

/**
 * Source: Own
 * MOD is a large prime
 */

template<int SZ> struct Combo {
    ll fac[SZ+1], ifac[SZ+1];

    Combo() {
        fac[0] = ifac[0] = 1;
        FOR(i,1,SZ+1) {
            fac[i] = i*fac[i-1] % MOD;
            ifac[i] = inv(fac[i]);
        }
    }

    ll po (ll b, ll p) {
        return !p?1:po(b*b%MOD,p/2)*(p&1?b:1)%MOD;
    }

    ll inv (ll b) { return po(b,MOD-2); }

    ll comb(ll a, ll b) {
        if (a < b) return 0;
        ll tmp = fac[a]*ifac[b] % MOD;
    }
}

```

```

    tmp = tmp*ifac[a-b] % MOD;
    return tmp;
}
};

```

10.2.4 (5) Combinations Plus

```

/**
 * Description: Extends combo to a power of a prime
 * Verification: https://dmoj.ca/problem/tle17c4p5
 */

typedef pair<ll,ll> pll;

template<int SZ> struct ComboExtended {
    pll fac[SZ+1], ifac[SZ+1], mod;
    ll MOD = 1;

    void init(pll _mod) { // prime, power
        mod = _mod; FOR(i,mod.s) MOD *= mod.f;

        fac[0] = ifac[0] = {1,0};
        FOR(i,1,SZ+1) {
            fac[i] = fac[i-1];
            int I = i, z = 0;
            while (I % mod.f == 0) I /= mod.f, z++;
            fac[i].f = fac[i].f*I%MOD; fac[i].s += z;
            ifac[i] = {inv(fac[i].f,MOD),fac[i].s};
        }

        ll inv(ll a, ll b) { // 0 < a < b, gcd(a,b) = 1
            a %= b;
            if (a <= 1) return a;
            ll i = inv(b%a,a);
            ll tmp = -((b/a)*i+((b%a)*i)/a) % b;
            while (tmp < 0) tmp += b;
            return tmp;
        }

        ll comb(ll a, ll b) {
            if (a < b) return 0;
            ll tmp = (fac[a].f*ifac[b].f%MOD)*ifac[a-b].f
                % MOD;
            ll z = fac[a].s-fac[b].s-fac[a-b].s;
            if (z >= mod.s) return 0;
            FOR(i,z) tmp = tmp*mod.f % MOD;
            return tmp;
        }
    };
};

```

10.2.5 (5) Phi

```

/**
 * Observation: number of operations needed s.t.
 *              phi(phi(...phi(n)...))=1
 * is 0(log n).

```

```

* Euler's theorem:  $a^{\phi(p)} \equiv 1 \pmod{p}$ ,
  gcd(a,p)=1
* Verification: CF Power Tower
*/

```

```

int phi(int x) {
    if (x == 1) return 1;
    int X = x;

    vi pri;
    for (int i = 2; i*i <= x; ++i) if (x % i == 0) {
        while (x % i == 0) x /= i;
        pri.pb(i);
    }

    if (x > 1) pri.pb(x);
    for (int i: pri) { X /= i; X *= i-1; }
    return X;
}

```

10.3 (6) Polynomials

10.3.1 (6) Base Conversion

```

/**
 * Description: NTT Application
 * Usage: 2017 VT HSPC - Alien Codebreaking
 */

// NTT template

struct Base {
    vl po10[21];
    const int base = 27;

    Base() {
        po10[0] = {10};
        FOR(i,1,21) {
            po10[i] = NTT::conv(po10[i-1],po10[i-1]);
            normalize(po10[i]);
        }
    }

    void normalize(vl& x) {
        FOR(i,sz(x)) if (x[i] >= base) {
            if (i == sz(x)-1) x.pb(0);
            x[i+1] += x[i]/base;
            x[i] %= base;
        }
        while (sz(x) && !x.back()) x.pop_back();
    }

    vl convert(vl in) {
        if (sz(in) == 1) return in;
        vl l =
            convert(vl(in.begin(),in.begin()+sz(in)/2));
        vl r =
            convert(vl(in.begin()+sz(in)/2,in.end()));

        r = NTT::conv(r,po10[get(sz(in))-1]);
    }
}

```

```

        normalize(r);

        int z = max(sz(l),sz(r));
        r.resize(z);
        FOR(i,sz(l)) r[i] += l[i];
        normalize(r);
        return r;
    }
};

Base B;

int main() {
    FOR(i,10) FOR(j,10) FOR(k,10) {
        vl z = {k,j,i};
        vl o = B.transform(z);
        for (ll x: o) cout << x << " ";
        cout << "\n";
    }
}

```

10.3.2 (6) FFT

```

/**
 * Sources: KACTL, https://pastebin.com/3Tnj5mRu
 * Verification: SPOJ polymul
 */

typedef complex<double> cd;
typedef vector<cd> vcd;
typedef vector<ll> vl;

int get(int s) {
    return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
}

namespace FFT {
    vcd fft(vcd& a) {
        int n = a.size(), x = get(n);
        vcd res, RES(n), roots(n);
        FOR(i,n) roots[i] =
            cd(cos(2*M_PI*i/n),sin(2*M_PI*i/n));

        res = a;
        FOR(i,1,x+1) {
            int inc = n>>i;
            FOR(j,inc) for (int k = 0; k < n; k += inc)
            {
                int t = 2*k%n+j;
                RES[k+j] = res[t]+roots[k]*res[t+inc];
            }
            swap(res,RES);
        }

        return res;
    }

    vcd fft_rev(vcd& a) {
        vcd res = fft(a);
        FOR(i,sz(res)) res[i] /= a.size();
    }
}

```

```

        reverse(res.begin() + 1, res.end());
        return res;
    }

    vcd brute(vcd& a, vcd& b) {
        vcd c(sz(a)+sz(b)-1);
        FOR(i,sz(a)) FOR(j,sz(b)) c[i+j] += a[i]*b[j];
        return c;
    }

    vcd conv(vcd a, vcd b) {
        int s = sz(a)+sz(b)-1, L = get(s), n = 1<<L;
        if (s <= 0) return {};
        if (s <= 200) return brute(a,b);

        a.resize(n); a = fft(a);
        b.resize(n); b = fft(b);

        FOR(i,n) a[i] *= b[i];
        a = fft_rev(a);

        a.resize(s);
        return a;
    }

    vl convll(vl a, vl b) {
        vcd A(sz(a)); FOR(i,sz(a)) A[i] = a[i];
        vcd B(sz(b)); FOR(i,sz(b)) B[i] = b[i];
        vcd X = conv(A,B);
        vl x(sz(X)); FOR(i,sz(X)) x[i] =
            round(X[i].real());
        return x;
    }
}

int main() {
    int T; cin >> T;
    FOR(i,T) {
        int N; cin >> N;
        vl a(N+1), b(N+1);
        FOR(j,N+1) cin >> a[N-j];
        FOR(j,N+1) cin >> b[N-j];
        vl x = FFT::convll(a,b);
        FORd(j,sz(x)) cout << x[j] << " ";
        cout << "\n";
    }
}

```

10.3.3 (6) NTT

```

/**
 * Description: Use if you are working with
 *              non-negative integers
 * Verification:
 *              http://codeforces.com/contest/632/submission/33953285
 */

typedef vector<ll> vl;

int get(int s) {

```

```

    return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
}

namespace NTT {
    const ll mod = (119 << 23) + 1, root = 3; // =
        998244353
    // For p < 2^30 there is also e.g. (5 << 25, 3),
        (7 << 26, 3),
    // (479 << 21, 3) and (483 << 21, 5). The last two
        are > 10^9.

    ll modpow(ll b, ll p) { return
        !p?1:modpow(b*b%mod,p/2)*(p&1?b:1)%mod; }

    ll inv (ll b) { return modpow(b,mod-2); }

    vl ntt(vl& a) {
        int n = a.size(), x = get(n);
        vl res, RES(n), roots(n);
        roots[0] = 1, roots[1] =
            modpow(root, (mod-1)/n);
        FOR(i,2,n) roots[i] = roots[i-1]*roots[1] %
            mod;

        res = a;
        FOR(i,1,x+1) {
            int inc = n>>i;
            FOR(j,inc) for (int k = 0; k < n; k += inc)
                {
                    int t = 2*k%n+j;
                    RES[k+j] = (res[t]+roots[k]*res[t+inc])
                        % mod;
                }
            swap(res,RES);
        }

        return res;
    }

    vl ntt_rev(vl& a) {
        vl res = ntt(a);
        ll in = inv(a.size());
        FOR(i,sz(res)) res[i] = res[i]*in % mod;
        reverse(res.begin() + 1, res.end());
        return res;
    }

    vl brute(vl& a, vl& b) {
        vl c(sz(a)+sz(b)-1);
        FOR(i,sz(a)) FOR(j,sz(b)) c[i+j] =
            (c[i+j]+a[i]*b[j])%mod;
        return c;
    }

    vl conv(vl a, vl b) {
        int s = sz(a)+sz(b)-1, L = get(s), n = 1<<L;
        if (s <= 0) return {};
        if (s <= 200) return brute(a,b);

        a.resize(n); a = ntt(a);
        b.resize(n); b = ntt(b);

```

```

        FOR(i,n) a[i] = a[i]*b[i] % mod;
        a = ntt_rev(a);

        a.resize(s);
        return a;
    }
}

int main() {
    vl X = NTT::conv({1,2,3,4,5,6,7,8},
        {1,2,3,4,5,6,7,8});
    for (auto a: X) cout << a << "\n";
}

```

11 (6) Sqrt Decomposition

11.1 (6) Mo

```

/**
 * Source: Codeforces
 * Description: Answers queries offline in (N+Q)sqrt(N)
 * Also see Mo's on trees
 */

int block = 300; // set ~sqrt(N)

bool cmp(vi a, vi b) {
    if (a[0]/block != b[0]/block) return a[0] < b[0];
    return a[1] < b[1];
}

```