

USACO Notebook

Ben Qi

October 13, 2018

Contents

| | |
|---|----------|
| 1 Contest | 2 |
| 1.1 C++ Template | 2 |
| 1.2 FastScanner | 3 |
| 1.3 Troubleshooting | 3 |
| 1.4 io | 4 |
| 2 Sorting And Searching (2) | 5 |
| 2.1 Interval Cover | 5 |
| 2.2 Binary Search | 5 |
| 3 Data Structures (2) | 5 |
| 3.1 Set | 5 |
| 3.1.1 Coordinate Compression | 5 |
| 3.1.2 Map Comparator | 5 |
| 3.1.3 Unordered Map | 5 |
| 4 Graphs Easy (2) | 6 |
| 4.1 Traversal | 6 |
| 4.1.1 BFS on Grid | 6 |
| 4.1.2 DFS | 6 |
| 4.2 Shortest Path (3) | 6 |
| 4.2.1 Bellman-Ford | 6 |
| 4.2.2 Dijkstra | 7 |
| 4.2.3 Floyd-Warshall | 7 |
| 4.3 Topological Sort (3) | 7 |
| 4.4 MST (3) | 8 |
| 4.4.1 DSU | 8 |
| 4.4.2 Kruskal | 8 |
| 5 Algorithm Design (2) | 8 |
| 5.1 Minimum Deque (3) | 8 |
| 5.2 Ternary Search (4) | 8 |
| 6 Range Queries (2) | 9 |
| 6.1 Static Array Queries | 9 |
| 6.1.1 Prefix Sums | 9 |
| 6.1.2 Range Minimum Query (3) | 9 |
| 6.1.3 Wavelet Tree (6) | 9 |
| 6.2 1D Range Queries (3) | 9 |
| 6.2.1 BIT | 9 |
| 6.2.2 SegTree | 10 |
| 6.2.3 BITrange (4) | 10 |
| 6.2.4 LazySegTree (4) | 10 |
| 6.2.5 Sparse SegTree (4) | 11 |
| 6.2.6 SegTreeBeats (6) | 11 |

| | |
|--|-----------|
| 6.3 2D Range Queries (4) | 12 |
| 6.3.1 2D BIT | 12 |
| 6.3.2 2D SegBIT | 12 |
| 6.3.3 2D SegTree | 13 |
| 6.3.4 Merge-Sort Tree | 13 |
| 6.4 BBST (4) | 13 |
| 6.4.1 Treap | 13 |
| 6.4.2 Link-Cut Tree (5) | 14 |
| 6.4.3 Splay Tree (5) | 15 |
| 6.5 Lazy PST (5) | 15 |
| 7 DP (3) | 16 |
| 7.1 Examples | 16 |
| 7.1.1 Distinct Subsequences | 16 |
| 7.1.2 Knapsack | 16 |
| 7.1.3 Longest Common Subsequence | 17 |
| 7.1.4 Longest Increasing Subsequence | 17 |
| 7.1.5 Traveling Salesman (4) | 17 |
| 7.2 Divide And Conquer (4) | 17 |
| 7.3 SOS DP (5) | 17 |
| 8 Strings (3) | 17 |
| 8.1 Hashing | 17 |
| 8.2 Bitset Trie (4) | 18 |
| 8.3 String Searching (4) | 18 |
| 8.3.1 Aho-Corasick | 18 |
| 8.3.2 Manacher | 19 |
| 8.3.3 Minimum Rotation | 19 |
| 8.3.4 Palindromic Tree | 19 |
| 8.3.5 Z | 20 |
| 8.4 Suffix Array (4) | 20 |
| 8.4.1 suffixArray | 20 |
| 8.4.2 reverseBW (6) | 21 |
| 9 Trees (4) | 21 |
| 9.1 TreeDiameter | 21 |
| 9.2 Queries | 21 |
| 9.2.1 HeavyLightSet | 21 |
| 9.2.2 LCA with Binary Jumps | 21 |
| 9.2.3 LCA with RMQ | 22 |
| 9.3 Advanced | 22 |
| 9.3.1 CentroidDecomp | 22 |
| 9.3.2 HLD | 23 |

| | |
|---------------------------------------|-----------|
| 10 Math (4) | 24 |
| 10.1 Number Theory | 24 |
| 10.1.1 factor1 | 24 |
| 10.1.2 rpm | 24 |
| 10.1.3 sieve | 24 |
| 10.1.4 combo (5) | 25 |
| 10.1.5 crt (6) | 25 |
| 10.1.6 factor2 (6) | 25 |
| 10.1.7 order (6) | 26 |
| 10.2 Matrix | 26 |
| 10.2.1 matrix | 26 |
| 10.2.2 matInv (6) | 27 |
| 10.3 Operators | 27 |
| 10.3.1 bigint | 27 |
| 10.3.2 exprParse | 31 |
| 10.3.3 frac | 32 |
| 10.3.4 modOp | 33 |
| 10.3.5 pairOp | 33 |
| 10.3.6 vecOp | 33 |
| 10.4 Polynomials (6) | 34 |
| 10.4.1 FFT | 34 |
| 10.4.2 FFTand | 34 |
| 10.4.3 FFTmod | 35 |
| 10.4.4 FWHT | 36 |
| 10.4.5 NTT | 36 |
| 10.4.6 linRec | 37 |
| 11 Graphs Hard (4) | 37 |
| 11.1 SCC | 37 |
| 11.1.1 2SAT | 37 |
| 11.1.2 Kosaraju | 38 |
| 11.2 Flows | 38 |
| 11.2.1 Dinic (5) | 38 |
| 11.2.2 Push-Relabel (5) | 39 |
| 11.2.3 MinCostFlow (6) | 39 |
| 11.3 Tarjan BCC | 40 |
| 11.4 Euler Tour (6) | 41 |
| 11.5 EdgeColor (6) | 41 |
| 12 Geometry (4) | 42 |
| 12.1 Techniques | 42 |
| 12.1.1 ComplexOp | 42 |
| 12.1.2 Polygon Area | 43 |
| 12.1.3 Point in Polygon (5) | 43 |
| 12.1.4 3D Geometry (6) | 43 |
| 12.1.5 Circles (6) | 43 |
| 12.1.6 ClosestPair (6) | 44 |
| 12.2 Sweep Line | 44 |
| 12.2.1 Angular Sort | 44 |
| 12.2.2 Convex Hull | 44 |
| 12.2.3 Max Rectangle | 45 |
| 12.2.4 LineContainer (6) | 45 |
| 12.3 Delaunay | 45 |
| 12.4 Max Collinear | 46 |

| | |
|-------------------------------|-----------|
| 13 Additional (4) | 46 |
| 13.1 Mo | 46 |
| 13.2 Misc | 47 |
| 13.2.1 discreteLog | 47 |
| 13.2.2 queryConnect | 47 |

1 Contest

1.1 C++ Template

```

#pragma GCC optimize ("O3")
#pragma GCC target ("sse4")

#include <bits/stdc++.h>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/rope>

using namespace std;
using namespace __gnu_pbds;
using namespace __gnu_cxx;

typedef long long ll;
typedef long double ld;
typedef complex<ld> cd;

typedef pair<int, int> pi;
typedef pair<ll,ll> pl;
typedef pair<ld,ld> pd;

typedef vector<int> vi;
typedef vector<ld> vd;
typedef vector<ll> vl;
typedef vector<pi> vpi;
typedef vector<pl> vpl;
typedef vector<cd> vcd;

template <class T> using Tree = tree<T, null_type,
    less<T>,
    rb_tree_tag,tree_order_statistics_node_update>;

#define FOR(i, a, b) for (int i=a; i<(b); i++)
#define FOR(i, a) for (int i=0; i<(a); i++)
#define FORd(i,a,b) for (int i = (b)-1; i >= a; i--)
#define FORd(i,a) for (int i = (a)-1; i >= 0; i--)

#define sz(x) (int)(x).size()
#define mp make_pair
#define pb push_back
#define f first
#define s second
#define lb lower_bound
#define ub upper_bound
#define all(x) x.begin(), x.end()

const int MOD = 1000000007;
const ll INF = 1e18;
const int MX = 100001;

int main() {

```

```

}

/*
 * (Actually read this pls)
 * Rlly bad errors: int overflow, array bounds
 * Less bad errors: special cases (n=1?), set tle
 * Common sense: do smth instead of nothing
 */

```

1.2 FastScanner

```

/**
 * Source: Matt Fontaine
 */

class FastScanner {
    private InputStream stream;
    private byte[] buf = new byte[1024];
    private int curChar;
    private int numChars;

    public FastScanner(InputStream stream) {
        this.stream = stream;
    }

    int read() {
        if (numChars == -1)
            throw new InputMismatchException();
        if (curChar >= numChars) {
            curChar = 0;
            try {
                numChars = stream.read(buf);
            } catch (IOException e) {
                throw new InputMismatchException();
            }
            if (numChars <= 0) return -1;
        }
        return buf[curChar++];
    }

    boolean isSpaceChar(int c) {
        return c == ' ' || c == '\n' || c == '\r' || c
            == '\t' || c == -1;
    }

    boolean isEndline(int c) {
        return c == '\n' || c == '\r' || c == -1;
    }

    public int nextInt() {
        return Integer.parseInt(next());
    }

    public long nextLong() {
        return Long.parseLong(next());
    }

    public double nextDouble() {
        return Double.parseDouble(next());
    }
}

```

```

public String next() {
    int c = read();
    while (isSpaceChar(c)) c = read();
    StringBuilder res = new StringBuilder();
    do {
        res.appendCodePoint(c);
        c = read();
    } while (!isSpaceChar(c));
    return res.toString();
}

public String nextLine() {
    int c = read();
    while (isEndline(c))
        c = read();
    StringBuilder res = new StringBuilder();
    do {
        res.appendCodePoint(c);
        c = read();
    } while (!isEndline(c));
    return res.toString();
}
}

```

1.3 Troubleshooting

Source: KACTL

Pre-submit:

- Write a few simple test cases, if sample is not enough.
- Are time limits close? If so, generate max cases.
- Is the memory usage fine?
- Could anything overflow?
- Make sure to submit the right file.

Wrong answer:

- Print your solution! Print debug output, as well.
- Are you clearing all datastructures between test cases?
- Can your algorithm handle the whole range of input?
- Read the full problem statement again.
- Do you handle all corner cases correctly?
- Have you understood the problem correctly?
- Any uninitialized variables?
- Any overflows?
- Confusing N and M, i and j, etc.?
- Are you sure your algorithm works?

- What special cases have you not thought of?
- Are you sure the STL functions you use work as you think?
- Add some assertions, maybe resubmit.
- Create some testcases to run your algorithm on.
- Go through the algorithm for a simple case.
- Go through this list again.
- Explain your algorithm to a team mate.
- Ask the team mate to look at your code.
- Go for a small walk, e.g. to the toilet.
- Is your output format correct? (including whitespace)
- Rewrite your solution from the start or let a team mate do it.

Runtime error:

- Have you tested all corner cases locally?
- Any uninitialized variables?
- Are you reading or writing outside the range of any vector?
- Any assertions that might fail?
- Any possible division by 0? (mod 0 for example)
- Any possible infinite recursion?
- Invalidated pointers or iterators?
- Are you using too much memory?
- Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:

- Do you have any possible infinite loops?
- What is the complexity of your algorithm?
- Are you copying a lot of unnecessary data? (References)
- How big is the input and output? (consider scanf)
- Avoid vector, map. (use arrays/unordered map)
- What do your team mates think about your algorithm?

Memory limit exceeded:

- What is the max amount of memory your algorithm should need?
- Are you clearing all data structures between test cases?

1.4 io

```

/**
 * Description: more convenient functions for input /
 *             output
 *             * experimentation with C++11 features
 */

namespace io {
    template<typename Test, template<typename...>
        class Ref>
    struct is_specialization : std::false_type {};

    template<template<typename...> class Ref,
        typename... Args>
    struct is_specialization<Ref<Args...>, Ref>:
        std::true_type {};
    // https://stackoverflow.com/questions/16337610
    // /how-to-know-if-a-type-is-
    // a-specialization-of-stdvector

    void setIn(string s) {
        freopen(s.c_str(),"r",stdin); }
    void setOut(string s) {
        freopen(s.c_str(),"w",stdout); }
    void setIO(string s = "") {
        ios_base::sync_with_stdio(0); cin.tie(0);
        if (sz(s)) { setIn(s+".in"), setOut(s+".out");
        }
    }

    // INPUT

    // double input seems slow on CF
    void re(double& x) { string t; cin >> t; x =
        stod(t); }
    void re(ld& x) { string t; cin >> t; x = stold(t);
    }
    template<class T> void re(T& x) { cin >> x; }
    template<class Arg, class... Args> void re(Arg&
        first, Args&... rest) {
        re(first); re(rest...);
    }
    template<class T1, class T2> istream&
        operator>>(istream& is, pair<T1,T2>& p) {
        is >> p.f >> p.s; return is;
    }
    template<class T> istream& operator>>(istream& is,
        vector<T>& a) {
        FOR(i,sz(a)) is >> a[i];
        return is;
    }

    // OUTPUT

    template<class T> void pr(const T& x) { cout << x
        << '\n'; }
    template<class Arg, class... Args> void pr(const
        Arg& first, const Args&... rest) {
        cout << first << ' '; pr(rest...);
    }

```

```

template<class T1, class T2> ostream&
operator<<(ostream& os, const pair<T1,T2>& a) {
    os << '{' << a.f << ", " << a.s << '}'; return
    os;
}
template<class T> ostream& operator<<(ostream& os,
    const vector<T>& a) {
    os << '{';
    FOR(i,sz(a)) {
        if (i) {
            os << ", ";
            if (is_specialization<T,
                vector::value> os << '\n';
        }
        os << a[i];
    }
    os << '}';
    return os;
}
}

using namespace io;

```

2 Sorting And Searching (2)

2.1 Interval Cover

```

/**
 * Description: Example of greedy algorithm
 * Verification:
 *   https://open.kattis.com/problems/intervalcover
 *   actually, you need to account for A=B and add
 *   epsilons but w/e
 */

vi solve(double A, double B, vector<pair<pd,int>> in)
{ // cover [A,B] with intervals from in
    pair<double,int> mx = {A,-1};
    vi ans;
    int nex = 0;

    sort(all(in));
    while (mx.f < B) {
        double cur = mx.f;
        while (nex < sz(in) && in[nex].f.f <= cur)
            mx = max(mx, {in[nex].f.s, in[nex].s}), nex++;
        if (mx.f == cur) return {};
        ans.pb(mx.s);
    }

    return ans;
}

```

2.2 Binary Search

```

/**
 * Description: Basic example of binary search

```

```

* Guess the Number
* https://open.kattis.com/problems/guess
*/

```

```

void binarySearch() {
    int lo = 1, hi = 1000;
    while (1) {
        int mid = (lo+hi)/2;
        cout << mid << endl;
        string res; cin >> res;
        if (res == "correct") return 0;
        else if (res == "lower") hi = mid-1;
        else lo = mid+1;
    }
}

```

3 Data Structures (2)

3.1 Set

3.1.1 Coordinate Compression

```

/**
 * Description: Demonstrates use of map
 * Verification: POI 12 - The Bus
 */

template<int B> void compress(vector<array<int,B>>& x,
    int ind) {
    map<int,int> m;
    for (auto& a: x) m[a[ind]] = 0;
    int co = 0; for (auto& a: m) a.s = co++;
    for (auto& a: x) a[ind] = m[a[ind]];
}

```

3.1.2 Map Comparator

```

/**
 * Source: StackOverflow
 */

struct cmp {
    bool operator()(const int& l, const int& r) const {
        return l > r;
    }
};

set<int,cmp> s;
map<int,int,cmp> m;

```

3.1.3 Unordered Map

```

/**
 * Description: faster than standard unordered map
 * Source: http://codeforces.com/blog/entry/62393

```

```

* Verification:
  http://codeforces.com/contest/966/problem/E
  * normal unordered map gets TLE
*/

struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM =
            chrono::steady_clock::now()
                .time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
};

template<class T> using um = unordered_map<ll, T,
    custom_hash>;
template<class T> using ht = gp_hash_table<ll, T,
    custom_hash>;

template<class T> T get(ht<T>& u, ll x) {
    if (u.find(x) == u.end()) return 0;
    return u[x];
}

```

4 Graphs Easy (2)

4.1 Traversal

4.1.1 BFS on Grid

```

/**
 * Note: Use xdir and ydir
 */

int xdir[4] = {0,1,0,-1}, ydir[4] = {1,0,-1,0};
int dist[21][21];
queue<pi> todo;

void process(pi x) {
    FOR(i,4) {
        pi y = {x.f+xdir[i],x.s+ydir[i]};
        if (y.f < 0 || y.f > 20 || y.s < 0 ||
            y.s > 20) continue; // ignore this
            point if it's outside of grid
        if (dist[y.f][y.s] == MOD) { // test
            whether point has been visited or
            not
            dist[y.f][y.s] = dist[x.f][x.s]+1;
            todo.push(y); // push point to queue
        }
    }
}

```

```

}

int main() {
    FOR(i,21) FOR(j,21) dist[i][j] = MOD;
    dist[10][10] = 0; todo.push({10,10}); //
        initialize queue, distances
    while (todo.size()) {
        process(todo.front());
        todo.pop(); // pop point from queue
    }
    cout << dist[4][5]; // 11
}

```

4.1.2 DFS

```

int n, visit[MX];
vi adj[MX];

void dfs(int node) {
    if (visit[node]) return;
    visit[node] = 1;
    for (int i: adj[node]) dfs(i);
    cout << node << "\n";
    // do stuff
}

int main() {
    cin >> n;
    FOR(i,n-1) {
        int a,b; cin >> a >> b;
        adj[a].pb(b), adj[b].pb(a);
    }
    dfs(1);
}

```

4.2 Shortest Path (3)

4.2.1 Bellman-Ford

```

/**
 * Description: Shortest Path w/ negative edge weights
 * Can be useful with linear programming
 * Constraints of the form  $x_i - x_j < k$ 
 * Verification:
   https://open.kattis.com/problems/shortestpath3
 */

int n,m,q,s,bad[1000];
vector<pair<pi,int>> edge;
ll dist[1000];

void solve() {
    edge.clear();
    FOR(i,n) dist[i] = INF, bad[i] = 0;
    dist[s] = 0;
    FOR(i,m) {
        int u,v,w; cin >> u >> v >> w;
    }
}

```

```

        edge.pb({u,v},w});
    }
    FOR(i,n) for (auto a: edge) if (dist[a.f.f] < INF)
        dist[a.f.s] = min(dist[a.f.s],
            dist[a.f.f]+a.s);
    for (auto a: edge) if (dist[a.f.f] < INF) if
        (dist[a.f.s] > dist[a.f.f]+a.s) bad[a.f.s] = 1;
    FOR(i,n) for (auto a: edge) if (bad[a.f.f])
        bad[a.f.s] = 1;

    FOR(i,q) {
        int x; cin >> x;
        if (bad[x]) cout << "-Infinity\n";
        else if (dist[x] == INF) cout <<
            "Impossible\n";
        else cout << dist[x] << "\n";
    }
    cout << "\n";
}

```

4.2.2 Dijkstra

```

/**
 * Description: shortest path!
 * Works with negative edge weights (aka SPFA?)
 */

template<class T> using pqg =
    priority_queue<T,vector<T>,greater<T>>;

template<class T> T poll(pqg<T>& x) {
    T y = x.top(); x.pop();
    return y;
}

template<int SZ> struct Dijkstra {
    ll dist[SZ];
    vpi adj[SZ];
    pqg<pl> q;

    void addEdge(int A, int B, int C) {
        adj[A].pb({B,C}), adj[B].pb({A,C});
    }

    void gen(int st) {
        fill_n(dist,SZ,INF);
        q = pqg<pl>(); q.push({dist[st] = 0,st});
        while (sz(q)) {
            auto x = poll(q);
            if (dist[x.s] < x.f) continue;
            for (auto y: adj[x.s]) if (x.f+y.s <
                dist[y.f])
                q.push({dist[y.f] =
                    x.f+y.s,y.f});
        }
    }
};

```

4.2.3 Floyd-Warshall

```

/**
 * Description: All-Pairs Shortest Path
 * Verification:
 *   https://open.kattis.com/problems/allpairspath
 */

int n,m,q; // vertices, edges, queries
ll dist[150][150], bad[150][150];

void solve() {
    FOR(i,n) FOR(j,n) dist[i][j] = INF, bad[i][j] = 0;
    FOR(i,n) dist[i][i] = 0;
    FOR(i,m) {
        int u,v,w; cin >> u >> v >> w;
        dist[u][v] = min(dist[u][v],(ll)w);
    }
    FOR(k,n) FOR(i,n) FOR(j,n) if (dist[i][k] != INF
        && dist[k][j] != INF)
        dist[i][j] =
            min(dist[i][j],dist[i][k]+dist[k][j]);

    FOR(k,n) FOR(i,n) FOR(j,n) if (dist[i][k] != INF
        && dist[k][j] != INF)
        if (dist[i][j] > dist[i][k]+dist[k][j])
            bad[i][j] = 1;

    FOR(k,n) FOR(i,n) FOR(j,n) {
        if (dist[i][k] < INF && bad[k][j]) bad[i][j] =
            1;
        if (bad[i][k] && dist[k][j] < INF) bad[i][j] =
            1;
    }

    FOR(i,q) {
        int u,v; cin >> u >> v;
        if (bad[u][v]) cout << "-Infinity\n";
        else if (dist[u][v] == INF) cout <<
            "Impossible\n";
        else cout << dist[u][v] << "\n";
    }
    cout << "\n";
}

```

4.3 Topological Sort (3)

```

/**
 * Description: sorts vertices such that if there
 *   exists an edge x->y, then x goes before y
 */

template<int SZ> struct Topo {
    int N, in[SZ];
    vi res, adj[SZ];

    void addEdge(int x, int y) {
        adj[x].pb(y), in[y] ++;
    }
}

```

```

void sort() {
    queue<int> todo;
    FOR(i,1,N+1) if (in[i] == 0) todo.push(i);
    while (sz(todo)) {
        int x = todo.front(); todo.pop();
        res.pb(x);
        for (int i: adj[x]) {
            in[i]--;
            if (!in[i]) todo.push(i);
        }
    }
}
};

```

4.4 MST (3)

4.4.1 DSU

```

/**
 * Description: Disjoint Set Union
 * Verification: USACO superbull
 */

template<int SZ> struct DSU {
    int par[SZ], sz[SZ];
    DSU() {
        FOR(i,SZ) par[i] = i, sz[i] = 1;
    }

    int get(int x) { // path compression
        if (par[x] != x) par[x] = get(par[x]);
        return par[x];
    }

    bool unite(int x, int y) { // union-by-rank
        x = get(x), y = get(y);
        if (x == y) return 0;
        if (sz[x] < sz[y]) swap(x,y);
        sz[x] += sz[y], par[y] = x;
        return 1;
    }
};

```

4.4.2 Kruskal

```

/**
 * Description: computes the minimum spanning tree in
 *              O(ElogE) time
 * Verification: USACO superbull
 */

ll kruskal(vector<array<int,3>> edge) {
    DSU<MX> D;
    sort(all(edge));
    ll ans = 0;
    for (auto a: edge) if (D.unite(a[1],a[2])) ans +=
        a[0]; // edge is in MST
}

```

```

return ans;
}

```

5 Algorithm Design (2)

5.1 Minimum Deque (3)

```

/**
 * Source: own
 * Verification: Jan 18 Lifeguards
 */

struct MinDeque {
    int lo = 0, hi = -1;
    deque<pi> d;

    void ins(int x) { // add to back
        while (sz(d) && d.back().f >= x) d.pop_back();
        d.pb({x,++hi});
    }

    void del() { // delete from front
        if (d.front().s == lo++) d.pop_front();
    }

    int get() {
        return sz(d) ? d.front().f : MOD;
    }
};

```

5.2 Ternary Search (4)

```

/**
 * Description: use on functions which are strictly
 *              decreasing then strictly increasing
 */

double eval(double x) {
    return (x-5)*(x-5);
}

double ternary(double l, double r) {
    if (abs(r-l) <= 1e-9) return (l+r)/2;
    double l1 = (2*l+r)/3, r1 = (l+2*r)/3;
    return eval(l1) < eval(r1) ? ternary(l,r1) :
        ternary(l1,r);
}

// ternary(-100,100) = 5

```

6 Range Queries (2)

6.1 Static Array Queries

6.1.1 Prefix Sums

```
/**
 * Description: Calculates rectangle sums in constant
 *             time
 * Verification: POI 16 Ticket Inspector
 */

template<class T, int SZ> struct sums {
    T sum[SZ][SZ];
    sums () { memset(sum,0,sizeof sum); }
    void init() {
        FOR(i,1,SZ) FOR(j,1,SZ)
            sum[i][j] += sum[i][j-1]
            +sum[i-1][j]-sum[i-1][j-1];
    }
    T get(int X1, int X2, int Y1, int Y2) {
        return sum[X2][Y2]-sum[X1-1][Y2]
            -sum[X2][Y1-1]+sum[X1-1][Y1-1];
    }
};
```

6.1.2 Range Minimum Query (3)

```
/**
 * Description: Supports 1D range minimum query in
 *             constant time.
 * Verification: Problem Tournament from IOI 2012:
 *             http://wcipeg.com/problem/ioi1223
 * Source code: https://pastebin.com/ChpniVZL
 */

template<class T, int SZ> struct RMQ {
    T stor[SZ][32-__builtin_clz(SZ)];

    T comb(T a, T b) {
        return min(a,b);
    }

    void build(vector<T>& x) {
        FOR(i,sz(x)) stor[i][0] = x[i];
        FOR(j,1,32-__builtin_clz(SZ))
            FOR(i,SZ-(1<<(j-1)))
                stor[i][j] = comb(stor[i][j-1],
                    stor[i+(1<<(j-1))][j-1]);
    }

    T query(int l, int r) {
        int x = 31-__builtin_clz(r-l+1);
        return comb(stor[l][x],stor[r-(1<<x)+1][x]);
    }
};
```

6.1.3 Wavelet Tree (6)

```
/**
 * Description: Segment tree on values instead of
 *             indices
 * Verification: http://www.spoj.com/problems/MKTHNUM/
 */

template<int SZ> struct wavelet {
    vi mapl[2*SZ], mapr[2*SZ], val[2*SZ];

    void build(int ind = 1, int L = 0, int R = SZ-1) {
        // build a wavelet tree
        if (ind == 1) { FOR(i,N) val[ind].pb(i); }

        if (L < R) {
            int M = (L+R)/2;
            for (int i: val[ind]) {
                val[2*ind+(A[i] > M)].pb(i);
                mapl[ind].pb(sz(val[2*ind])-1);
                mapr[ind].pb(sz(val[2*ind+1])-1);
            }
            build(2*ind,L,M);
            build(2*ind+1,M+1,R);
        }
    }

    int getl(int ind, int x) { return x < 0 ? -1 :
        mapl[ind][x]; }

    int getr(int ind, int x) { return x < 0 ? -1 :
        mapr[ind][x]; }

    int query(int lind, int rind, int k, int ind = 1,
        int L = 0, int R = SZ-1) { // how many <= mid
        with index <= r
        if (L == R) return L;

        int M = (L+R)/2;
        int t = getl(ind,rind)-getl(ind,lind-1);
        if (t >= k) return query(getl(ind,lind-1)+1,
            getl(ind,rind),k,2*ind,L,M);
        return query(getr(ind,lind-1)+1,
            getr(ind,rind),k-t,2*ind+1,M+1,R);
    }
};
```

6.2 1D Range Queries (3)

6.2.1 BIT

```
/**
 * Description: 1D range sum query with point update
 * Verification: SPOJ Fenwick
 */

template<class T, int SZ> struct BIT {
    T bit[SZ+1];
```

```

BIT() { memset(bit,0,sizeof bit); }

void upd(int k, T val) { // add val to index k
    for( ;k <= SZ; k += (k&-k)) bit[k] += val;
}

T query(int k) {
    T temp = 0;
    for (;k > 0;k -= (k&-k)) temp += bit[k];
    return temp;
}

T query(int l, int r) { return
    query(r)-query(l-1); } // range query [l,r]
};

```

6.2.2 SegTree

```

/*
* Source: http://codeforces.com/blog/entry/18051
* Description: 1D point update, range query
* Verification: SPOJ Fenwick
*/

template<class T, int SZ> struct Seg {
    T seg[2*SZ], MN = 0;

    Seg() {
        memset(seg,0,sizeof seg);
    }

    T comb(T a, T b) { return a+b; } // easily change
        this to min or max

    void upd(int p, T value) { // set value at
        position p
        for (seg[p += SZ] = value; p > 1; p >>= 1)
            seg[p>>1] = comb(seg[(p|1)^1],seg[p|1]); //
            non-commutative operations
    }

    void build() {
        FORd(i,SZ) seg[i] = comb(seg[2*i],seg[2*i+1]);
    }

    T query(int l, int r) { // sum on interval [l, r]
        T res1 = MN, res2 = MN; r++;
        for (l += SZ, r += SZ; l < r; l >>= 1, r >>=
            1) {
            if (l&1) res1 = comb(res1,seg[l++]);
            if (r&1) res2 = comb(seg[--r],res2);
        }
        return comb(res1,res2);
    }
};

```

6.2.3 BITrange (4)

```

/**

```

```

* Source: GeeksForGeeks?
* Description: 1D range update, range query
* Alternative to lazy segment tree
*/

template<class T, int SZ> struct BITrange {
    BIT<T,SZ> bit[2]; // sums piecewise linear
        functions

    void upd(int hi, T val) {
        bit[1].upd(1,val), bit[1].upd(hi+1,-val);
        bit[0].upd(hi+1,hi*val);
    }

    void upd(int lo, int hi, T val) { upd(lo-1,-val),
        upd(hi,val); }

    T query(int x) { return
        bit[1].query(x)*x+bit[0].query(x); }

    T query(int x, int y) { return
        query(y)-query(x-1); }
};

```

6.2.4 LazySegTree (4)

```

/**
* Description: 1D range update, range query
* Verification: SPOJ Horrible
*/

template<class T, int SZ> struct LazySegTree {
    T sum[2*SZ], mn[2*SZ], lazy[2*SZ]; // set SZ to a
        power of 2

    LazySegTree() {
        memset (sum,0,sizeof sum);
        memset (mn,0,sizeof mn);
        memset (lazy,0,sizeof lazy);
    }

    void push(int ind, int L, int R) {
        sum[ind] += (R-L+1)*lazy[ind];
        mn[ind] += lazy[ind];
        if (L != R) lazy[2*ind] += lazy[ind],
            lazy[2*ind+1] += lazy[ind];
        lazy[ind] = 0;
    }

    void pull(int ind) {
        sum[ind] = sum[2*ind]+sum[2*ind+1];
        mn[ind] = min(mn[2*ind],mn[2*ind+1]);
    }

    void build() {
        FORd(i,SZ) pull(i);
    }

    T qsum(int lo, int hi, int ind = 1, int L = 0, int
        R = SZ-1) {
        push(ind,L,R);
        if (lo > R || L > hi) return 0;

```

```

    if (lo <= L && R <= hi) return sum[ind];

    int M = (L+R)/2;
    return qsum(lo,hi,2*ind,L,M) +
           qsum(lo,hi,2*ind+1,M+1,R);
}

T qmin(int lo, int hi, int ind = 1, int L = 0, int
      R = SZ-1) {
    push(ind,L,R);
    if (lo > R || L > hi) return INF;
    if (lo <= L && R <= hi) return mn[ind];

    int M = (L+R)/2;
    return min(qmin(lo,hi,2*ind,L,M),
              qmin(lo,hi,2*ind+1,M+1,R));
}

void upd(int lo, int hi, ll inc, int ind = 1, int
      L = 0, int R = SZ-1) {
    push(ind,L,R);
    if (hi < L || R < lo) return;
    if (lo <= L && R <= hi) {
        lazy[ind] = inc;
        push(ind,L,R);
        return;
    }

    int M = (L+R)/2;
    upd(lo,hi,inc,2*ind,L,M);
    upd(lo,hi,inc,2*ind+1,M+1,R);
    pull(ind);
}
};

```

6.2.5 Sparse SegTree (4)

```

/**
 * Source: Own
 */

const int SZ = 1<<20;

template<class T> struct node {
    T val;
    node<T>* c[2];

    node() {
        val = 0;
        c[0] = c[1] = NULL;
    }

    void upd(int ind, T v, int L = 0, int R = SZ-1) {
        // add v
        if (L == ind && R == ind) { val += v; return; }

        int M = (L+R)/2;
        if (ind <= M) {
            if (!c[0]) c[0] = new node();
            c[0]->upd(ind,v,L,M);

```

```

        } else {
            if (!c[1]) c[1] = new node();
            c[1]->upd(ind,v,M+1,R);
        }

        val = 0;
        if (c[0]) val += c[0]->val;
        if (c[1]) val += c[1]->val;
    }

    T query(int low, int high, int L = 0, int R =
          SZ-1) { // query sum of segment
        if (low <= L && R <= high) return val;
        if (high < L || R < low) return 0;

        int M = (L+R)/2;
        T t = 0;
        if (c[0]) t += c[0]->query(low,high,L,M);
        if (c[1]) t += c[1]->query(low,high,M+1,R);
        return t;
    }

    void UPD(int ind, node* c0, node* c1, int L = 0,
          int R = SZ-1) { // for 2D segtree
        if (L != R) {
            int M = (L+R)/2;
            if (ind <= M) {
                if (!c[0]) c[0] = new node();
                c[0]->UPD(ind,c0 ? c0->c[0] : NULL,c1 ?
                    c1->c[0] : NULL,L,M);
            } else {
                if (!c[1]) c[1] = new node();
                c[1]->UPD(ind,c0 ? c0->c[1] : NULL,c1 ?
                    c1->c[1] : NULL,M+1,R);
            }
        }

        val = 0;
        if (c0) val += c0->val;
        if (c1) val += c1->val;
    }
};

```

6.2.6 SegTreeBeats (6)

```

/**
 * Description: Interval min modifications
 * Verification:
 *   http://acm.hdu.edu.cn/showproblem.php?pid=5306
 */

template<int SZ> struct SegTreeBeats {
    int N;
    ll sum[2*SZ];
    int mx[2][2*SZ], maxCnt[2*SZ];

    void pull(int ind) {
        mx[0][ind] = max(mx[0][2*ind],mx[0][2*ind+1]);
        mx[1][ind] = max(mx[1][2*ind],mx[1][2*ind+1]);
        maxCnt[ind] = 0;
    }

```

```

FOR(i,2) {
    if (mx[0][2*ind^i] == mx[0][ind])
        maxCnt[ind] += maxCnt[2*ind^i];
    else mx[1][ind] =
        max(mx[1][ind], mx[0][2*ind^i]);
}

sum[ind] = sum[2*ind] + sum[2*ind+1];
}

void build(vi& a, int ind = 1, int L = 0, int R =
-1) {
    if (R == -1) R += N;
    if (L == R) {
        mx[0][ind] = sum[ind] = a[L];
        maxCnt[ind] = 1; mx[1][ind] = -1;
        return;
    }

    int M = (L+R)/2;
    build(a, 2*ind, L, M); build(a, 2*ind+1, M+1, R);
    pull(ind);
}

void push(int ind, int L, int R) {
    if (L == R) return;
    FOR(i,2)
        if (mx[0][2*ind^i] > mx[0][ind]) {
            sum[2*ind^i] -= (1ll)maxCnt[2*ind^i]*
                (mx[0][2*ind^i] - mx[0][ind]);
            mx[0][2*ind^i] = mx[0][ind];
        }
}

void upd(int x, int y, int t, int ind = 1, int L =
0, int R = -1) { // set a_i = min(a_i, t)
    if (R == -1) R += N;
    if (R < x || y < L || mx[0][ind] <= t) return;
    push(ind, L, R);
    if (x <= L && R <= y && mx[1][ind] < t) {
        sum[ind] -= (1ll)maxCnt[ind]*(mx[0][ind] - t);
        mx[0][ind] = t;
        return;
    }
    if (L == R) return;
    int M = (L+R)/2;
    upd(x, y, t, 2*ind, L, M);
    upd(x, y, t, 2*ind+1, M+1, R); pull(ind);
}

11 qsum(int x, int y, int ind = 1, int L = 0, int
R = -1) {
    if (R == -1) R += N;
    if (R < x || y < L) return 0;
    push(ind, L, R);
    if (x <= L && R <= y) return sum[ind];

    int M = (L+R)/2;
    return
        qsum(x, y, 2*ind, L, M) + qsum(x, y, 2*ind+1, M+1, R);
}

```

```

int qmax(int x, int y, int ind = 1, int L = 0, int
R = -1) {
    if (R == -1) R += N;
    if (R < x || y < L) return -1;
    push(ind, L, R);
    if (x <= L && R <= y) return mx[0][ind];

    int M = (L+R)/2;
    return max(qmax(x, y, 2*ind, L, M),
        qmax(x, y, 2*ind+1, M+1, R));
}
};

```

6.3 2D Range Queries (4)

6.3.1 2D BIT

```

/**
 * Description:
 *   * Supports point update & rectangle query
 *   * can be extended to rectangle update
 *   * can also use with unordered map
 * Verification: SPOJ matsum
 */

// struct BIT

template<class T, int SZ> struct BIT2D {
    BIT<T, SZ> bit[SZ+1];
    void upd(int X, int Y, T val) {
        for (; X <= SZ; X += (X&-X)) bit[X].upd(Y, val);
    }
    T query(int X, int Y) {
        T ans = 0;
        for (; X > 0; X -= (X&-X)) ans +=
            bit[X].query(Y);
        return ans;
    }
    T query(int X1, int X2, int Y1, int Y2) {
        return query(X2, Y2) - query(X1-1, Y2)
            - query(X2, Y1-1) + query(X1-1, Y1-1);
    }
};

```

6.3.2 2D SegBIT

```

/**
 * Source: USACO Mowing the Field
 * Dependency: Sparse SegTree
 */

const int SZ = 1<<17;

template<class T> struct SegBit {
    node<T> seg[SZ+1];

    SegBit() {
        FOR(i, SZ+1) seg[i] = node<T>();
    }
};

```

```

}

void upd(int x, int y, int v) { // add v
    for (x++; x <= SZ; x += (x&-x)) seg[x].upd(y,v);
}

T query(int x, int y1, int y2) {
    T ret = 0;
    for (; x > 0; x -= (x&-x)) ret +=
        seg[x].query(y1,y2);
    return ret;
}

T query(int x1, int x2, int y1, int y2) { // query
    sum of rectangle
    return query(x2+1,y1,y2)-query(x1,y1,y2);
}
};

```

6.3.3 2D SegTree

```

/**
 * Source: USACO Mowing the Field
 * Dependency: Sparse SegTree
 */

const int SZ = 1<<17;

template<class T> struct Node {
    node<T> seg;
    Node* c[2];

    void upd(int x, int y, T v, int L = 0, int R =
        SZ-1) { // add v
        if (L == x && R == x) {
            seg.upd(y,v);
            return;
        }

        int M = (L+R)/2;
        if (x <= M) {
            if (!c[0]) c[0] = new Node();
            c[0]->upd(x,y,v,L,M);
        } else {
            if (!c[1]) c[1] = new Node();
            c[1]->upd(x,y,v,M+1,R);
        }

        seg.UPD(y,c[0] ? &c[0]->seg : NULL,c[1] ?
            &c[1]->seg : NULL);
    }

    T query(int x1, int x2, int y1, int y2, int L = 0,
        int R = SZ-1) { // query sum of rectangle
        if (x1 <= L && R <= x2) return
            seg.query(y1,y2);
        if (x2 < L || R < x1) return 0;

        int M = (L+R)/2;
        T t = 0;

```

```

        if (c[0]) t += c[0]->query(x1,x2,y1,y2,L,M);
        if (c[1]) t += c[1]->query(x1,x2,y1,y2,M+1,R);
        return t;
    }
};

```

6.3.4 Merge-Sort Tree

```

/**
 * Description: Similar to 2D segtree, less memory
 * For more complex queries use a customized treap
 * Verification:
 *   http://codeforces.com/contest/785/submission/33953058
 */

template<int SZ> struct mstree {
    Tree<pi> val[SZ+1]; // for offline queries use
        vector with binary search instead

    void upd(int x, int y, int t = 1) { //
        x-coordinate between 1 and SZ inclusive
        for (int X = x; X <= SZ; X += X&-X) {
            if (t == 1) val[X].insert({y,x});
            else val[X].erase({y,x});
        }
    }

    int query(int x, int y) {
        int t = 0;
        for (; x > 0; x -= x&-x) t +=
            val[x].order_of_key({y,MOD});
        return t;
    }

    int query(int lox, int hix, int loy, int hiy) { //
        query number of elements within a rectangle
        return query(hix,hiy)-query(lox-1,hiy)
            -query(hix,loy-1)+query(lox-1,loy-1);
    }
};

```

6.4 BBST (4)

6.4.1 Treap

```

/*
 * Source:
 *   https://cp-algorithms.com/data_structures/treap.html
 * + others
 * Description: Easiest BBST
 * Verification: http://www.spoj.com/problems/ORDERSET/
 */

namespace treap {
    typedef struct tnode* pt;

    struct tnode {
        int pri, val; pt c[2]; // essential

```

```

int sz; ll sum; // for range queries

tnode (int _val) {
    pri = rand()+(rand()<<15); val = _val; c[0]
        = c[1] = NULL;
    sz = 1; sum = val;
}
};

int getsz(pt x) { return x?x->sz:0; }
ll getsum(pt x) { return x?x->sum:0; }

void trav(pt x, vi& v) {
    if (!x) return;
    trav(x->c[0],v); v.pb(x->val); trav(x->c[1],v);
}

pt recalc(pt x) {
    x->sz = 1+getsz(x->c[0])+getsz(x->c[1]);
    x->sum =
        x->val+getsum(x->c[0])+getsum(x->c[1]);
    return x;
}

pair<pt,pt> split(pt t, int v) { // >= v goes to
    the right
    if (!t) return {t,t};
    if (t->val >= v) {
        auto p = split(t->c[0], v); t->c[0] = p.s;
        return {p.f, recalc(t)};
    } else {
        auto p = split(t->c[1], v); t->c[1] = p.f;
        return {recalc(t), p.s};
    }
}

pair<pt,pt> splitsz(pt t, int sz) {
    if (!t) return {t,t};
    if (getsz(t->c[0]) >= sz) {
        auto p = splitsz(t->c[0], sz); t->c[0] =
            p.s;
        return {p.f, recalc(t)};
    } else {
        auto p = splitsz(t->c[1],
            sz-getsz(t->c[0])-1); t->c[1] = p.f;
        return {recalc(t), p.s};
    }
}

pt merge(pt l, pt r) {
    if (!l || !r) return l ? l : r;
    pt t;
    if (l->pri > r->pri) l->c[1] =
        merge(l->c[1],r), t = l;
    else r->c[0] = merge(l,r->c[0]), t = r;
    return recalc(t);
}

pt ins(pt x, int v) { // insert v
    auto a = split(x,v), b = split(a.s,v+1);
    return merge(a.f,merge(new tnode(v),b.s));
}

```

```

pt del(pt x, int v) { // delete v
    auto a = split(x,v), b = split(a.s,v+1);
    return merge(a.f,b.s);
}
}

```

```
using namespace treap;
```

6.4.2 Link-Cut Tree (5)

```

/**
 * Sources: Dhruv Rohatgi,
 *           https://sites.google.com/site/kc97ble
 *           /container/splay-tree/splaytree-cpp-3
 * Verification: SPOJ DYNACON1, DYNALCA
 */

using namespace splayTree;

template<int SZ> struct LCT {
    ps S[SZ];
    LCT () { FOR(i,SZ) S[i] = new snode(i); }

    void dis(ps x, int d) {
        ps y = x->c[d];
        if (x) x->c[d] = NULL, recalc(x);
        if (y) y->p = NULL, y->pp = x;
    }

    void con(ps x, int d) { setLink(x->pp,x,d); x->pp
        = NULL; }

    void setPref(ps x) { splay(x->pp), dis(x->pp,1),
        con(x,1); splay(x); }

    ps access(ps x) { // x is brought to the root of
        auxiliary tree
        dis(splay(x),1);
        while (x->pp) setPref(x);
        return x;
    }

    ////////// UPDATES

    ps makeRoot(ps v) { access(v)->flip = 1; return
        access(v); }

    void link(ps v, ps w) {
        access(w)->pp = makeRoot(v);
        con(w,0);
    }

    void cut(ps x) { // cut link between x and its
        parent
        ps y = access(x)->c[0];
        dis(x,0); y->pp = NULL;
    }

    ////////// QUERIES

```

```

int getDepth(ps v) { access(v); return
    getsz(v->c[0]); }

int getRoot(ps v) { return
    getExtreme(access(v),0)->id; }

int lca(ps x, ps y) {
    ps root = getExtreme(access(y),0);

    dis(splay(x),1);
    auto z = getExtreme(x,0);
    if (z == root) return x->val;
    splay(x);

    while (x->pp) {
        auto z = getExtreme(splay(x->pp),0);
        if (z == root) return x->pp->val;
        setPref(x);
    }

    return -1;
}
};

```

6.4.3 Splay Tree (5)

```

/**
 * Description: Treap alternative
 * Sources: see LCT
 */

namespace splayTree {
    typedef struct snode* ps;

    struct snode {
        int val; ps p, pp, c[2]; // essential
        int sz; // # nodes in subtree
        bool flip; // range flip

        snode (int _val) {
            val = _val; c[0] = c[1] = p = pp = NULL;
            sz = 1; flip = 0;
        }
    };

    int getsz(ps x) { return x?x->sz:0; }
    int getDir(ps x, ps y) { return x?(x->c[1] ==
        y):-1; }

    void trav(ps x, vi& v) {
        if (!x) return;
        trav(x->c[0],v); v.pb(x->val); trav(x->c[1],v);
    }

    ps recalc(ps x) {
        x->sz = 1+getsz(x->c[0])+getsz(x->c[1]);
        return x;
    }
}

```

```

void setLink(ps x, ps y, int d) { // x propagated
    if (x) x->c[d] = y, recalc(x);
    if (y) y->p = x;
}

void prop(ps x) {
    if (!x || !x->flip) return;
    swap(x->c[0],x->c[1]);
    if (x->c[0]) x->c[0]->flip ^= 1;
    if (x->c[1]) x->c[1]->flip ^= 1;
    x->flip = 0;
}

void pushDown(ps x) {
    if (!x) return;
    if (x->p) pushDown(x->p);
    prop(x);
}

void rot(ps x, int d) { // precondition: x &
    parents propagated
    snode *y = x->c[d], *z = x->p;
    prop(y);
    setLink(x, y->c[d^1], d);
    setLink(y, x, d^1);
    setLink(z, y, getDir(z, x));
    y->pp = x->pp; x->pp = NULL;
}

ps splay(ps x) {
    pushDown(x);
    while (x && x->p) {
        ps y = x->p, z = y->p;
        int dy = getDir(y, x), dz = getDir(z, y);
        if (!z) rot(y, dy);
        else if (dy == dz) rot(z, dz), rot(y, dy);
        else rot(y, dy), rot(z, dz);
    }
    return x;
}

ps getExtreme(ps x, int d) { // get leftmost or
    rightmost node
    prop(x);
    if (x->c[d]) return getExtreme(x->c[d],d);
    return splay(x);
}
}

```

using namespace splayTree;

6.5 Lazy PST (5)

```

/**
 * Description: persistent segtree with lazy updates
 * Sources: CF, Franklyn Wang
 */

template<class T, int SZ> struct pseg {
    static const int LIMIT = 10000000;

```

```

int l[LIMIT], r[LIMIT], nex = 0;
T val[LIMIT], lazy[LIMIT];

//// HELPER
int copy(int cur) {
    int x = nex++;
    val[x] = val[cur], l[x] = l[cur], r[x] =
        r[cur], lazy[x] = lazy[cur];
    return x;
}
T comb(T a, T b) { return min(a,b); }
void pull(int x) { val[x] =
    comb(val[l[x]],val[r[x]]); }
void push(int cur, int L, int R) {
    if (!lazy[cur]) return;
    if (L != R) {
        l[cur] = copy(l[cur]);
        val[l[cur]] += lazy[cur];
        lazy[l[cur]] += lazy[cur];

        r[cur] = copy(r[cur]);
        val[r[cur]] += lazy[cur];
        lazy[r[cur]] += lazy[cur];
    }
    lazy[cur] = 0;
}

//// IMPORTANT
T query(int cur, int lo, int hi, int L, int R) {
    if (lo <= L && R <= hi) return val[cur];
    if (R < lo || hi < L) return INF;
    int M = (L+R)/2;
    return lazy[cur]+comb(query(l[cur],lo,hi,L,M),
        query(r[cur],lo,hi,M+1,R));
}
int upd(int cur, int lo, int hi, T v, int L, int
    R) {
    if (R < lo || hi < L) return cur;

    int x = copy(cur);
    if (lo <= L && R <= hi) { val[x] += v, lazy[x]
        += v; return x; }
    push(x,L,R);

    int M = (L+R)/2;
    l[x] = upd(l[x],lo,hi,v,L,M), r[x] =
        upd(r[x],lo,hi,v,M+1,R);
    pull(x); return x;
}
int build(vector<T>& arr, int L, int R) {
    int cur = nex++;
    if (L == R) {
        if (L < sz(arr)) val[cur] = arr[L];
        return cur;
    }

    int M = (L+R)/2;
    l[cur] = build(arr,L,M), r[cur] =
        build(arr,M+1,R);
    pull(cur); return cur;
}

```

```

//// PUBLIC
vi loc;
void upd(int lo, int hi, T v) {
    loc.pb(upd(loc.back(),lo,hi,v,0,SZ-1)); }
T query(int ti, int lo, int hi) { return
    query(loc[ti],lo,hi,0,SZ-1); }
void build(vector<T>& arr) {
    loc.pb(build(arr,0,SZ-1)); }
};

```

7 DP (3)

7.1 Examples

7.1.1 Distinct Subsequences

```

/**
 * Description: DP eliminates overcounting
 * Verification: https://cses.fi/problemset/task/1149/
 */

using namespace modOp;

int distinct(string S) {
    vi tot(26);
    int ans = 1;
    for (char c: S) {
        int t = sub(ans,tot[c-'a']);
        AD(tot[c-'a'],t), AD(ans,t);
    }
    return ans;
}

```

7.1.2 Knapsack

```

/**
 * Description: solves knapsack in pseudo-polynomial
 *             time
 * Verification:
 *             https://open.kattis.com/problems/knapsack
 */

const int MX = 2001;

vi solve(int cap, vi v, vi w) {
    int dp[MX][MX]; FOR(i,cap+1) dp[0][i] = 0;

    FOR(i,sz(v)) {
        FOR(j,cap+1) dp[i+1][j] = dp[i][j];
        FOR(j,cap+1) if (w[i]+j <= cap)
            dp[i+1][w[i]+j] =
                max(dp[i+1][w[i]+j],dp[i][j]+v[i]);
    }

    vi ans;
    FORd(i,sz(v)) if (dp[i][cap] != dp[i+1][cap]) cap
        -= w[i], ans.pb(i);
}

```



```
    return ans;
}
```

7.1.3 Longest Common Subsequence

```
/**
 * Description: Classic DP example
 * Verification:
 *   https://pcs.cs.cloud.vt.edu/problems/224
 */

int lcs(string a, string b) {
    vi dp(sz(b)+1);
    for (char c: a) {
        FORd(i,sz(b)) if (b[i] == c) dp[i+1] =
            dp[i]+1;
        FOR(i,sz(b)) dp[i+1] = max(dp[i+1],dp[i]);
    }
    return dp[sz(b)];
}
```

7.1.4 Longest Increasing Subsequence

```
/**
 * Description: DP with Binary Search
 */

vi bes = {INT_MIN}; // last term of increasing
sequence with i terms

void ad(int x) { // add terms of sequence one by one
    int lo = lb(all(bes),x)-bes.begin();
    if (lo == sz(bes)) bes.pb(0);
    bes[lo] = x; // sz(bes)-1 is your current answer
}
```

7.1.5 Traveling Salesman (4)

```
/**
 * Description: Bitset DP example
 * Solves TSP for small N
 */

const int MX = 15;

int N, dp[MX][1<<MX], dist[MX][MX];

int solve() {
    FOR(i,N) FOR(j,1<<N) dp[i][j] = MOD;

    dp[0][1] = 0;
    FOR(j,1<<N) FOR(i,N) if (j&(1<<i))
        FOR(k,N) if (!(j&(1<<k)))
            dp[k][j^(1<<k)] = min(dp[k][j^(1<<k)],
                dp[i][j]+dist[i][k]);
}
```

```
int ans = MOD;
FOR(j,1,N) ans =
    min(ans,dp[j][((1<<N)-1)+dist[j][0]]);
return ans;
}
```

7.2 Divide And Conquer (4)

```
/**
 * Source: Own
 * Verification: CEOI 2004 Two Sawmills
 */

void divide(int lo, int hi, int L, int R) {
    if (lo > hi) return;

    int mid = (lo+hi)/2;
    pair<ll,int> tmp = {1e18,-1};
    FOR(i,max(mid+1,L),R+1)
        tmp = min(tmp,{calc(0,mid)+calc(mid+1,i)
            +calc(i+1,n),i});
    ans = min(ans,tmp.f);

    divide(lo,mid-1,L,tmp.s);
    divide(mid+1,hi,tmp.s,R);
}
```

7.3 SOS DP (5)

```
/**
 * Description: if you add one to dp[i]
 * it adds one to dp[j] for all j such that j&i = i
 */

void sos (vi& dp, int x = 1) { // x = -1 reverses
    int SZ = 31-__builtin_clz(sz(dp));
    FOR(i,SZ) FOR(j,1<<SZ) if (j&(1<<i))
        dp[j^(1<<i)] += x*dp[j];
}
```

8 Strings (3)

8.1 Hashing

```
/**
 * Source: own
 * Description: Pairs reduce frequency of collision
 * Verification: Dec 17 Plat 1
 */

using namespace pairOp;

struct hsh {
    static const int tmp =
        chrono::high_resolution_clock::now()
```

```

        .time_since_epoch().count());
string S;
vpi pows, ipows, cum;
pi base = mp(948392576,tmp%MOD), invbase; //
    probably want to randomize base

hsh() {}
hsh(string s) { gen(s); }

void gen(string _S) {
    invbase = {inv(base.f),inv(base.s)};
    S = _S; pows.resize(sz(S)),
        ipows.resize(sz(S)), cum.resize(sz(S)+1);

    pows[0] = ipows[0] = {1,1};
    FOR(i,1,sz(S)) pows[i] = pows[i-1]*base,
        ipows[i] = ipows[i-1]*invbase;
    FOR(i,sz(S)) cum[i+1] =
        cum[i]+pows[i]*(int)(S[i]-'a'+1);
}

pi get(int l, int r) { return
    ipows[l]*(cum[r+1]-cum[l]); }

int lcp(hsh& b) {
    int lo = 0, hi = min(sz(S),sz(b.S));
    while (lo < hi) {
        int mid = (lo+hi+1)/2;
        if (cum[mid] == b.cum[mid]) lo = mid;
        else hi = mid-1;
    }
    return lo;
}
};

```

8.2 Bitset Trie (4)

```

/**
 * Source: Algorithms Gym
 * Verification: January Easy 2018 - Shubham and
 * Subarray Xor
 */

template<int MX> struct tri {
    static const int MXBIT = 60;
    int trie[MX][2], nex = 0; // easily changed to
        character
    int sz[MX];

    tri() {
        memset(trie,0,sizeof trie);
    }

    void ins(ll x, int a = 1) { // insert or delete
        int cur = 0; sz[cur] += a;
        FORd(i,MXBIT) {
            int t = (x&(1LL<<i))>>i;
            if (!trie[cur][t]) trie[cur][t] = ++nex;
            cur = trie[cur][t];
            sz[cur] += a;
        }
    }
};

```

```

    }
}

ll test(ll x) { // compute max xor
    if (sz[0] == 0) return -INF;
    int cur = 0;
    FORd(i,MXBIT) {
        int t = ((x&(1LL<<i))>>i) ^ 1;
        if (!trie[cur][t] || !sz[trie[cur][t]]) t
            ^= 1;
        cur = trie[cur][t];
        if (t) x ^= (1LL<<i);
    }
    return x;
}
};

```

8.3 String Searching (4)

8.3.1 Aho-Corasick

```

/**
 * Source: https://ideone.com/0cMjZJ
 * Verification: Kattis stringmultimatching
 */

template<int SZ> struct AhoCorasick {
    int link[SZ], dict[SZ], sz = 1, num = 0;
    vpi ind[SZ];
    map<char,int> to[SZ];
    vi oc[SZ];
    queue<int> q;

    AhoCorasick() {
        memset(link,0,sizeof link);
        memset(dict,0,sizeof dict);
    }

    void add(string s) {
        int v = 0;
        for(auto c: s) {
            if (!to[v].count(c)) to[v][c] = sz++;
            v = to[v][c];
        }
        dict[v] = v; ind[v].pb({++num,sz(s)});
    }

    void pushLinks() {
        link[0] = -1; q.push(0);
        while (sz(q)) {
            int v = q.front(); q.pop();
            for (auto it: to[v]) {
                char c = it.f; int u = it.s, j =
                    link[v];
                while (j != -1 && !to[j].count(c)) j =
                    link[j];
                if (j != -1) {
                    link[u] = to[j][c];
                    if (!dict[u]) dict[u] =
                        dict[link[u]];
                }
            }
        }
    }
};

```

```

    }
    q.push(u);
}
}
}

void process(int pos, int cur) { // process matches
    cur = dict[cur];
    while (cur) {
        for (auto a: ind[cur])
            oc[a.f].pb(pos-a.s+1);
        cur = dict[link[cur]];
    }

    int nex(int pos, int cur, char c) {
        // get position after adding character
        // speed up with memoization
        while (cur != -1 && !to[cur].count(c)) cur =
            link[cur];
        if (cur == -1) cur = 0;
        else cur = to[cur][c];
        process(pos, cur);
        return cur;
    }
};

```

8.3.2 Manacher

```

/**
 * Source: http://codeforces.com/blog/entry/12143
 * Description: Calculates length of largest palindrome
 *              centered at each character of string
 * Verification: http://www.spoj.com/problems/MSUBSTR/
 */

vi manacher(string s) {
    string s1 = "@";
    for (char c: s) s1 += c, s1 += "#";
    s1[s1.length()-1] = '&';

    vi ans(s1.length()-1);
    int lo = 0, hi = 0;
    FOR(i, 1, s1.length()-1) {
        if (i != 1) ans[i] = min(hi-i, ans[hi-i+lo]);
        while (s1[i-ans[i]-1] == s1[i+ans[i]+1])
            ans[i] ++;
        if (i+ans[i] > hi) lo = i-ans[i], hi =
            i+ans[i];
    }

    ans.erase(ans.begin());
    FOR(i, sz(ans)) if ((i&1) == (ans[i]&1)) ans[i] ++;
    // adjust lengths
    return ans;
}

// vi v = manacher("abacaba"); cout << v;

```

8.3.3 Minimum Rotation

```

/**
 * Source: KACTL
 * Unused
 */

int min_rotation(string s) {
    int a=0, N=sz(s); s += s;
    FOR(b, N) FOR(i, N) {
        if (a+i == b || s[a+i] < s[b+i]) {b +=
            max(0, i-1); break;}
        if (s[a+i] > s[b+i]) {a = b; break;}
    }
    return a;
}

```

8.3.4 Palindromic Tree

```

/**
 * Source: http://codeforces.com/blog/entry/13959
 * Verification:
 *           https://oj.uz/problem/view/API014\_palindrome
 */

template<int SZ> struct palTree {
    static const int sigma = 26;

    int s[SZ], len[SZ], link[SZ], to[SZ][sigma],
        oc[SZ];
    int n, last, sz;

    palTree() {
        s[n++] = -1;
        link[0] = 1;
        len[1] = -1;
        sz = 2;
    }

    int get_link(int v) {
        while(s[n-len[v]-2] != s[n-1]) v = link[v];
        return v;
    }

    void add_letter(int c) {
        s[n++] = c;
        last = get_link(last);
        if (!to[last][c]) {
            len[sz] = len[last]+2;
            link[sz] = to[get_link(link[last])][c];
            to[last][c] = sz++;
        }
        last = to[last][c];
        oc[last] ++;
    }

    void prop() { // number of occurrences of each
        palindrome
        vpi v;
    }
}

```

```

    FOR(i,2,sz) v.pb({len[i],i});
    sort(all(v)); reverse(all(v));
    for (auto a: v) oc[link[a.s]] += oc[a.s];
}
};

```

8.3.5 Z

```

/**
 * Source: http://codeforces.com/blog/entry/3107
 * Description: similar to KMP
 * Verification: POI 12 Template
 */

vi z(string s) {
    int N = sz(s); s += '#';
    vi ans(N); ans[0] = N;
    while (s[1+ans[1]] == s[ans[1]]) ans[1] ++;

    int L = 1, R = ans[1];
    FOR(i,2,N) {
        if (i <= R) ans[i] = min(R-i+1,ans[i-L]);
        while (s[i+ans[i]] == s[ans[i]]) ans[i] ++;
        if (i+ans[i]-1 > R) L = i, R = i+ans[i]-1;
    }
    return ans;
}

vi get(string a, string b) { // find prefixes of a in b
    string s = a+"@"+b;
    vi t = z(s);
    return vi(t.begin()+sz(a)+1,t.end());
}

```

8.4 Suffix Array (4)

8.4.1 suffixArray

```

/**
 * Sources: SuprDewd, KACTL, majk
 * Task: https://open.kattis.com/problems/suffixsorting
 * Verification: USACO December 2017: Standing out from the herd:
 * http://usaco.org/index.php?page=viewproblem2&cpid=768
 * Code to Verify: https://pastebin.com/y2Z9FYr6
 */

struct suffixArray {
    int N;
    vi idx;
    string str;

    void compress(vi& v) {
        vi V = v; sort(all(V));
        V.erase(unique(all(V)),V.end());
        for (int& i: v) i = lb(all(V),i)-V.begin()+1;
    }
}

```

```

vi a, A, L, cum;

void initVar(string _str) {
    str = _str; N = sz(str);
    a.resize(N);
    A.resize(N); FOR(i,N) A[i] = str[i];
    compress(A); A2.resize(N);
    L.resize(N); FOR(i,N) L[i] = i; L2.resize(N);
    cum.resize(N+1);
}

int get(int x) { return x >= N ? 0 : A[x]; }

void sort_by(int x) { // stable sort elements in a
    by b
    fill(all(cum),0); FOR(i,N) cum[get(i+x)] ++;
    int sum = 0; FOR(i,N+1) cum[i] = (sum += cum[i], sum-cum[i]);

    vi L2(N);
    for (int i: L) L2[cum[get(i+x)]++] = i;
    swap(L,L2);
}

void init(string _str) {
    initVar(_str);

    for (int cnt = 1; cnt < N; cnt <= 1) {
        vi A2(N);

        sort_by(cnt), sort_by(0);

        FOR(i,N) {
            if (i == 0) A2[L[i]] = 1;
            else A2[L[i]] = A2[L[i-1]]+
                (mp(get(L[i]),get(L[i]+cnt)) !=
                 mp(get(L[i-1]),get(L[i-1]+cnt)));
        }

        swap(A,A2);
    }

    FOR(i,N) a[A[i]-1] = i;
}

vi lcp() { // KACTL
    int n = sz(str), h = 0;
    vi inv(n), res(n);
    FOR(i,N) inv[a[i]] = i;
    FOR(i,N) if (inv[i]) {
        int p0 = a[inv[i] - 1];
        while (max(i,p0)+h < N &&
                str[i+h] == str[p0+h]) h++;
        res[inv[i]] = h;
        if (h) h--;
    }
    return res;
}
};

```

8.4.2 reverseBW (6)

```
/**
 * Description: Reverse Burrows-Wheeler
 * Verification: https://cses.fi/problemset/task/1113/
 */

string reverseBW(string s) {
    vector<pair<char,int>> v;
    int nex[sz(s)];

    FOR(i,sz(s)) v.pb({s[i],i});
    sort(all(v));
    FOR(i,sz(v)) nex[i] = v[i].s;

    int cur = nex[0];
    string ret;
    while (cur != 0) {
        ret += v[cur].f;
        cur = nex[cur];
    }
    return ret;
}
```

9 Trees (4)

9.1 TreeDiameter

```
/**
 * Might not be obvious why this works!
 * Verification: http://www.spoj.com/problems/PT07Z/
 */

struct TreeDiameter {
    int n, dist[MX], pre[MX];
    vi adj[MX];

    void addEdge(int a, int b) {
        adj[a].pb(b), adj[b].pb(a);
    }

    void dfs(int cur) {
        for (int i: adj[cur]) if (i != pre[cur]) {
            pre[i] = cur;
            dist[i] = dist[cur]+1;
            dfs(i);
        }
    }

    void genDist(int cur) {
        memset(dist,0,sizeof dist);
        pre[cur] = -1;
        dfs(cur);
    }

    int diameterLength() {
        genDist(1);
```

```
        int bes = 0; FOR(i,1,n+1) if (dist[i] >
            dist[bes]) bes = i;
        genDist(bes); FOR(i,1,n+1) if (dist[i] >
            dist[bes]) bes = i;
        return dist[bes];
    }

    vi genCenter() {
        int t = diameterLength();
        int bes = 0; FOR(i,1,n+1) if (dist[i] >
            dist[bes]) bes = i;

        FOR(i,t/2) bes = pre[bes];
        if (t&1) return {bes,pre[bes]};
        return {bes};
    }
};
```

9.2 Queries

9.2.1 HeavyLightSet

```
/**
 * Description: offline subtree queries in  $O(N \log^2 N)$ 
 * To verify: January Easy 2018 - Shubham & Tree 1
 */

struct HeavyLightSet {
    int val[MX];
    vi child[MX];
    map<int,int> dat[MX];

    void comb(int a, int b) {
        bool swa = 0;
        if (sz(dat[a]) < sz(dat[b])) swap(a,b), swa = 1;
        for (auto& x: dat[b]) dat[a][x.f] += x.s;
        dat[b].clear();
        if (swa) swap(dat[a],dat[b]);
    }

    void process(int ind) {
        dat[ind][val[ind]] ++;
        for (int i: child[ind]) {
            process(i);
            comb(ind,i);
        }
        // now do stuff with values
    }
};
```

9.2.2 LCA with Binary Jumps

```
/**
 * Source: USACO Camp
 * Verification: Debug the Bugs
 */
```

```

template<int SZ> struct LCA {
    const int MAXK = 32-__builtin_clz(SZ);

    int N, R = 1; // vertices from 1 to N, R = root
    vi adj[SZ];
    int par[32-__builtin_clz(SZ)][SZ], depth[SZ];

    void addEdge(int u, int v) {
        adj[u].pb(v), adj[v].pb(u);
    }

    void dfs(int u, int prev){
        par[0][u] = prev;
        depth[u] = depth[prev]+1;
        for (int v: adj[u]) if (v != prev) dfs(v, u);
    }

    void init(int _N) {
        N = _N;
        dfs(R, 0);
        FOR(k,1,MAXK) FOR(i,1,N+1)
            par[k][i] = par[k-1][par[k-1][i]];
    }

    int lca(int u, int v){
        if (depth[u] < depth[v]) swap(u,v);

        FORd(k,MAXK) if (depth[u] >= depth[v]+(1<<k))
            u = par[k][u];
        FORd(k,MAXK) if (par[k][u] != par[k][v]) u =
            par[k][u], v = par[k][v];

        if(u != v) u = par[0][u], v = par[0][v];
        return u;
    }

    int dist(int u, int v) {
        return depth[u]+depth[v]-2*depth[lca(u,v)];
    }
};

```

9.2.3 LCA with RMQ

```

/**
 * Description: Euler Tour LCA w/ O(1) query
 * Source: own
 * Verification: Debug the Bugs
 * Dependency: Range Minimum Query
 */

```

```

template<int SZ> struct LCA {
    vi adj[SZ];
    RMQ<pi,2*SZ> r;
    vpi tmp;
    int depth[SZ], pos[SZ];

    int N, R = 1;

    void addEdge(int u, int v) {
        adj[u].pb(v), adj[v].pb(u);
    }

```

```

    }

    void dfs(int u, int prev){
        pos[u] = sz(tmp); depth[u] = depth[prev]+1;
        tmp.pb({depth[u],u});
        for (int v: adj[u]) if (v != prev) {
            dfs(v, u);
            tmp.pb({depth[u],u});
        }
    }

    void init(int _N) {
        N = _N;
        dfs(R, 0);
        r.build(tmp);
    }

    int lca(int u, int v){
        u = pos[u], v = pos[v];
        if (u > v) swap(u,v);
        return r.query(u,v).s;
    }

    int dist(int u, int v) {
        return depth[u]+depth[v]-2*depth[lca(u,v)];
    }
};

```

9.3 Advanced

9.3.1 CentroidDecomp

```

/**
 * Source: own
 * Verification:
 *   https://codeforces.com/contest/342/problem/E
 * Description: can support tree path queries and
 *               updates
 */

```

```

template<int SZ> struct CentroidDecomp {
    bool done[SZ];
    int sub[SZ], par[SZ], ans[SZ];
    vi dist[SZ], adj[SZ], ANS[SZ];
    pi cen[SZ];

    void addEdge(int a, int b) { adj[a].pb(b),
        adj[b].pb(a); }

    void dfs (int no) {
        sub[no] = 1;
        for (int i: adj[no]) if (!done[i] && i !=
            par[no]) {
                par[i] = no;
                dfs(i);
                sub[no] += sub[i];
            }
    }

    void genDist(int par, int no) {

```

```

    for (int i: adj[no]) if (!done[i] && i != par)
    {
        cen[i] = cen[no];
        dist[i].pb(dist[no].back()+1);
        genDist(no,i);
    }
}

int getCentroid(int x) {
    par[x] = 0; dfs(x);
    int sz = sub[x];
    while (1) {
        pi mx = {0,0};
        for (int i: adj[x]) if (!done[i] && i !=
            par[x]) mx = max(mx,{sub[i],i});
        if (mx.f*2 > sz) x = mx.s;
        else return x;
    }
}

void solve (int x) { // call solve(1) to initialize
    x = getCentroid(x); done[x] = 1;
    dist[x].pb(0);
    for (int i: adj[x]) if (!done[i]) {
        cen[i] = {x,sz(ANS[x])};
        dist[i].pb(1);
        genDist(x,i);
        ANS[x].pb(0);
    }
    for (int i: adj[x]) if (!done[i]) solve(i);
}

void upd(int v) {
    pi V = {v,-1};
    for (int ind = sz(dist[v])-1; V.f; V =
        cen[V.f], ind --) {
        ans[V.f] ++;
        if (V.s != -1) ANS[V.f][V.s] ++;
    }
}

int query(int v) {
    pi V = {v,-1}; int ret = 0;
    for (int ind = sz(dist[v])-1; V.f; V =
        cen[V.f], ind --) {
        ret += ans[V.f];
        if (V.s != -1) ret -= ANS[V.f][V.s];
    }
    return ret;
}
};

```

9.3.2 HLD

```

/**
 * Description: Heavy Light Decomposition
 * Source: http://codeforces.com/blog/entry/22072
 * Verification: USACO Grass Planting
 */

```

```

// struct LazySegTree

vector<vi> graph;

template <int V> struct HLD { // sum queries, sum
    updates
    int parent[V], heavy[V], depth[V];
    int root[V], treePos[V];
    LazySegTree<V> tree;

    void init() {
        int n = sz(graph)-1;
        FOR(i,1,n+1) heavy[i] = -1;
        parent[1] = -1, depth[1] = 0;
        dfs(1);
        for (int i = 1, currentPos = 0; i <= n; ++i)
            if (parent[i] == -1 || heavy[parent[i]]
                != i)
                for (int j = i; j != -1; j =
                    heavy[j]) {
                        root[j] = i;
                        treePos[j] = currentPos++;
                    }
    }

    int dfs(int v) {
        int size = 1, maxSubtree = 0;
        for (auto u : graph[v]) if (u != parent[v]) {
            parent[u] = v;
            depth[u] = depth[v] + 1;
            int subtree = dfs(u);
            if (subtree > maxSubtree) heavy[v] = u,
                maxSubtree = subtree;
            size += subtree;
        }
        return size;
    }

    template <class BinaryOperation>
    void processPath(int u, int v, BinaryOperation op)
    {
        for (; root[u] != root[v]; v =
            parent[root[v]]) {
            if (depth[root[u]] > depth[root[v]])
                swap(u, v);
            op(treePos[root[v]], treePos[v]);
        }
        if (depth[u] > depth[v]) swap(u, v);
        op(treePos[u]+1, treePos[v]); // assumes
            values are stored in edges, not vertices
    }

    void modifyPath(int u, int v, int value) { // add
        one to vertices along path
        processPath(u, v, [this, &value](int l, int r)
            { tree.upd(l, r, value); });
    }

    ll queryPath(int u, int v) { // query sum of path
        ll res = 0;
        processPath(u, v, [this, &res](int l, int r) {
            res += tree.qsum(l, r); });
    }
}

```

```

        return res;
    }
};

```

10 Math (4)

10.1 Number Theory

10.1.1 factor1

```

/**
 * Description: factors N in O(sqrtN) time
 */
namespace factor1 {
    vpl factor(ll x) { // x <= 1014 is fine
        vpl pri;

        for (int i = 2; i*i <= x; ++i) if (x % i == 0) {
            int t = 0;
            while (x % i == 0) x /= i, t++;
            pri.pb({i,t});
        }

        if (x > 1) pri.pb({x,1});
        return pri;
    }

    ll phi(ll x) {
        for (auto a: factor(x)) x /= a.f, x *= a.f-1;
        return x;
    }

    void trav(vpl& v, vl& V, int ind, ll cur) {
        if (ind == sz(v)) V.pb(cur);
        else {
            ll mul = 1;
            FOR(i,v[ind].s+1) {
                trav(v,V,ind+1,cur*mul);
                mul *= v[ind].f;
            }
        }
    }

    vl getDivi(ll x) {
        vpl v = factor(x); vl V;
        trav(v,V,0,1);
        sort(all(V));
        return V;
    }
}

using namespace factor1;

```

10.1.2 rpm

```

/**
 * Description: Russian Peasant Multiplication
 * multiply two 64-bit integers mod another if
 * 128-bit is not available
 * Source: KACTL
 */

typedef unsigned long long ull;

namespace rpm {
    const int bits = 14; // if all numbers are less
                        // than 2k, set bits = 64-k
    const ull po = (ull)1<<bits;

    ull mod_mul(ull a, ull b, ull &c) { // return
        (__int128(a)*b) % c;
        ull x = 0;
        for (; b >>= bits, a = (a << bits) % c)
            x = (x + (a * (b & (po - 1))) % c) % c;
        return x;
    }

    ull mod_pow(ull a, ull b, ull mod) {
        if (b == 0) return 1;
        ull res = mod_pow(a, b / 2, mod);
        res = mod_mul(res, res, mod);
        if (b & 1) return mod_mul(res, a, mod);
        return res;
    }
}

```

```
using namespace rpm;
```

10.1.3 sieve

```

/**
 * Verification:
 * https://open.kattis.com/problems/primesieve
 */

template<int SZ> struct sieve {
    bitset<SZ> comp;
    vl pr;
    // int sp[SZ];

    sieve() {
        for (int i = 2; i*i <= SZ; ++i) if
            (!comp[i])
                for (int j = i*i; j <= SZ; j +=
                    i) comp[j] = 1;
        FOR(i,2,SZ) if (!comp[i]) pr.pb(i);

        /*FOR(i,2,SZ) { // O(N) sieve
            if (sp[i] == 0) { sp[i] = i;
                pr.pb(i); }
            for (int p : pr) {
                if (p > sp[i] || i*p >=
                    SZ) break;
                sp[i*p] = p;
            }
        }
    }
}

```



```

        }*/
    }
};

```

10.1.4 combo (5)

```

/**
 * Description: extends Combo to all natural numbers
 * Verification: https://dmoj.ca/problem/tle17c4p5
 */

using namespace modOp;
using namespace factor1;

template<int SZ> struct combo {
    int MOD, fac[SZ+1], ifac[SZ+1];
    vpl factors;
    vi cnt[SZ+1];

    int mul_mod(int a, int b) { return (ll)a*b%MOD; }

    void init(ll _MOD) {
        MOD = _MOD; factors = factor(MOD);
        cnt[0].resize(sz(factors));

        fac[0] = ifac[0] = 1;
        FOR(i,1,SZ+1) {
            cnt[i] = cnt[i-1];

            int I = i;
            FOR(j,sz(factors))
                while (I % factors[j].f == 0)
                    I /= factors[j].f, cnt[i][j] ++;

            fac[i] = mul_mod(I,fac[i-1]), ifac[i] =
                inv(fac[i],MOD);
        }

        ll comb(ll a, ll b) {
            if (a < b || b < 0) return 0;
            ll tmp =
                mul_mod(mul_mod(fac[a],ifac[b]),ifac[a-b]);
            FOR(i,sz(factors)) {
                int t = cnt[a][i]-cnt[a-b][i]-cnt[b][i];
                tmp = mul_mod(tmp,po(factors[i].f,t));
            }
            return tmp;
        }
    };
};

```

10.1.5 crt (6)

```

/**
 * Description: Chinese Remainder Theorem
 * Verification: Kattis generalchineseremainder
 */

```

```

using namespace modOp;

pl solve(pl a, pl b) {
    ll g = __gcd(a.s,b.s), l = a.s*b.s/g;
    if ((b.f-a.f) % g != 0) return {-1,-1};
    ll A = a.s/g, B = b.s/g;
    ll mul = (b.f-a.f)/g*invGeneral(A%B,B) % B;
    return {(mul*a.s+a.f)%l+1}%l,1};
}

```

10.1.6 factor2 (6)

```

/**
 * Source: KACTL
 * Description: Factors integers up to 260
 * Usage: https://www.spoj.com/problems/FACT0/
 *
 * https://codeforces.com/contest/1033/submission/44009089
 * is probably faster
 */

using namespace rpm;

namespace factor2 {
    Sieve<1<<20> S = Sieve<1<<20>(); // should
    take care of all primes up to n1/3

    bool prime(ll p) { // miller-rabin
        if (p == 2) return true;
        if (p == 1 || p % 2 == 0) return false;
        ll s = p - 1;
        while (s % 2 == 0) s /= 2;
        FOR(i,15) {
            ll a = rand() % (p - 1) + 1, tmp
                = s;
            ll mod = mod_pow(a, tmp, p);
            while (tmp != p - 1 && mod != 1
                && mod != p - 1) {
                mod = mod_mul(mod, mod,
                    p);
                tmp *= 2;
            }
            if (mod != p - 1 && tmp % 2 ==
                0) return false;
        }
        return true;
    }

    ll f(ll a, ll n, ll &has) { return (mod_mul(a,
        a, n) + has) % n; }

    vpl factor2(ll d) {
        vpl res;

        vi& pr = S.pr;
        for (int i = 0; i < sz(pr) &&
            pr[i]*pr[i] <= d; i++) if (d %
            pr[i] == 0) {
            int co = 0;

```

```

        while (d % pr[i] == 0) d /=
            pr[i], co ++;
        res.pb({pr[i],co});
    }

    if (d > 1) { // d is now a product of
        at most 2 primes.
        if (prime(d)) res.pb({d,1});
        else while (1) {
            ll has = rand() % 2321 +
                47;
            ll x = 2, y = 2, c = 1;
            for (; c == 1; c =
                __gcd((y > x ? y - x
                    : x - y), d)) {
                x = f(x, d, has);
                y = f(y, d,
                    has), d, has);
            }
            if (c != d) {
                d /= c; if (d > c)
                    swap(d,c);
                if (c == d)
                    res.pb({c,2});
                else res.pb({c,1}),
                    res.pb({d,1});
                break;
            }
        }
    }

    return res;
}
}

```

10.1.7 order (6)

```

/** Notes:
 * number of operations needed s.t.
 *      phi(phi(...phi(n)...))=1
 * is  $O(\log n)$ .
 * Euler's theorem:  $a^{\phi(p)} \equiv 1 \pmod p$ ,
 *      gcd(a,p)=1
 */

using namespace RPM;
using namespace factor1;

ll order(ll x, ll p) {
    if (__gcd(x,p) != 1) return 0;
    ll P = phi(p);
    auto a = fac(P);

    for (auto t: a) while (P % t.f == 0 &&
        mod_pow(x,P/t.f,p) == 1) P /= t.f;
    return P;
}

```

10.2 Matrix

10.2.1 matrix

```

/**
 * Source: KACTL
 * Verification: https://dmoj.ca/problem/si17c1p5
 */

using namespace modOp;

struct mat {
    int** d;
    int a, b;

    mat() { a = b = 0; }

    mat(int _a, int _b) {
        a = _a, b = _b;
        d = new int*[a];
        FOR(i,a) {
            d[i] = new int[b];
            FOR(j,b) d[i][j] = 0;
        }
    }

    mat (vector<vi> v) : mat(sz(v),sz(v[0])) {
        FOR(i,a) FOR(j,b) d[i][j] = v[i][j];
    }

    void print() {
        FOR(i,a) {
            FOR(j,b) cout << d[i][j] << " ";
            cout << "\n";
        }
        cout << "-----\n";
    }

    mat operator+(const mat& m) {
        mat r(a,b);
        FOR(i,a) FOR(j,b) r.d[i][j] =
            ad(d[i][j],m.d[i][j]);
        return r;
    }

    mat operator*(const mat& m) {
        mat r(a,m.b);
        FOR(i,a) FOR(j,b) FOR(k,m.b)
            AD(r.d[i][k],mul(d[i][j],m.d[j][k]));
        return r;
    }

    mat operator^(ll p) {
        mat r(a,a), base(*this);
        FOR(i,a) r.d[i][i] = 1;

        while (p) {
            if (p&1) r = r*base;
            base = base*base;
            p /= 2;
        }
    }
}

```

```

        return r;
    }
};

```

10.2.2 matInv (6)

```

/*
 * Description: Calculates determinant mod a prime via
 *              gaussian elimination
 * Verification: SPOJ MIFF
 */

// struct mat

namespace matInv {
    void elim(mat& m, int col, int a, int b) { //
        column, todo row
        int x = m.d[b][col];
        FOR(i,col,m.b) SUB(m.d[b][i],mul(x,m.d[a][i]));
    }

    ll gauss(mat& m) { // determinant of 1000x1000
        matrix in ~1s
        int prod = 1, nex = 0;

        FOR(i,m.a) {
            int row = -1;
            FOR(j,nex,m.a) if (m.d[j][i] != 0) { row =
                j; break; }
            if (row == -1) { prod = 0; continue; }
            if (row != nex) MUL(prod,MOD-1),
                swap(m.d[row],m.d[nex]);

            MUL(prod,m.d[nex][i]);
            int x = inv(m.d[nex][i]);
            FOR(k,i,m.b) MUL(m.d[nex][k],x);

            FOR(k,m.a) if (k != nex) elim(m,i,nex,k);
            nex ++;
        }

        return prod;
    }

    ll numSpan(mat m) { // Kirchhoff's theorem
        mat res(m.a-1,m.a-1);
        FOR(i,m.a) FOR(j,i+1,m.a) {
            if (i) {
                AD(res.d[i-1][i-1],m.d[i][j]);
                SUB(res.d[i-1][j-1],m.d[i][j]);
                SUB(res.d[j-1][i-1],m.d[i][j]);
            }
            AD(res.d[j-1][j-1],m.d[i][j]);
        }
        return gauss(res);
    }

    mat inv(mat m) {
        mat x(m.a,2*m.a);

```

```

        FOR(i,m.a) FOR(j,m.a) x.d[i][j] = m.d[i][j];
        FOR(i,m.a) x.d[i][i+m.a] = 1;

```

```

        if (gauss(x) == 0) return mat(0,0);

```

```

        mat r(m.a,m.a);
        FOR(i,m.a) FOR(j,m.a) r.d[i][j] =
            x.d[i][j+m.a];
        return r;
    }
}

```

10.3 Operators

10.3.1 bigint

```

/**
 * Source: https://github.com/indy256/codelibrary/blob/master/cpp/numbertheory/bigint.cpp
 */

namespace bigint {
    // base and base_digits must be consistent
    constexpr int base = 1000000000;
    constexpr int base_digits = 9;

    struct bigint {
        // value == 0 is represented by empty z
        vector<int> z; // digits

        // sign == 1 <==> value >= 0
        // sign == -1 <==> value < 0
        int sign;

        bigint() : sign(1) {}

        bigint(long long v) {
            *this = v;
        }

        bigint &operator=(long long v) {
            sign = v < 0 ? -1 : 1;
            v *= sign;
            z.clear();
            for (; v > 0; v = v / base)
                z.push_back((int) (v % base));
            return *this;
        }

        bigint(const string &s) {
            read(s);
        }

        bigint &operator+=(const bigint &other) {
            if (sign == other.sign) {
                for (int i = 0, carry = 0; i <
                    other.z.size() || carry; ++i) {
                    if (i == z.size())
                        z.push_back(0);

```

```

        z[i] += carry + (i < other.z.size()
            ? other.z[i] : 0);
        carry = z[i] >= base;
        if (carry)
            z[i] -= base;
    }
} else if (other != 0 /* prevent infinite
loop */) {
    *this -= -other;
}
return *this;
}

friend bigint operator+(bigint a, const bigint
    &b) {
    return a += b;
}

bigint &operator--(const bigint &other) {
    if (sign == other.sign) {
        if (sign == 1 && *this >= other || sign
            == -1 && *this <= other) {
            for (int i = 0, carry = 0; i <
                other.z.size() || carry; ++i) {
                z[i] -= carry + (i <
                    other.z.size() ? other.z[i]
                    : 0);
                carry = z[i] < 0;
                if (carry)
                    z[i] += base;
            }
            trim();
        } else {
            *this = other - *this;
            this->sign = -this->sign;
        }
    } else {
        *this += -other;
    }
    return *this;
}

friend bigint
operator-(bigint a, const bigint &b) {
    return a -= b;
}

bigint &operator*=(int v) {
    if (v < 0)
        sign = -sign, v = -v;
    for (int i = 0, carry = 0; i < z.size() ||
        carry; ++i) {
        if (i == z.size())
            z.push_back(0);
        long long cur = (long long) z[i] * v +
            carry;
        carry = (int) (cur / base);
        z[i] = (int) (cur % base);
    }
    trim();
    return *this;
}

```

```

}

bigint operator*(int v) const {
    return bigint(*this) *= v;
}

friend pair<bigint, bigint> divmod(const
    bigint &a1, const bigint &b1) {
    int norm = base / (b1.z.back() + 1);
    bigint a = a1.abs() * norm;
    bigint b = b1.abs() * norm;
    bigint q, r;
    q.z.resize(a.z.size());

    for (int i = (int) a.z.size() - 1; i >= 0;
        i--) {
        r *= base;
        r += a.z[i];
        int s1 = b.z.size() < r.z.size() ?
            r.z[b.z.size()] : 0;
        int s2 = b.z.size() - 1 < r.z.size() ?
            r.z[b.z.size() - 1] : 0;
        int d = (int) (((long long) s1 * base +
            s2) / b.z.back());
        r -= b * d;
        while (r < 0)
            r += b, --d;
        q.z[i] = d;
    }

    q.sign = a1.sign * b1.sign;
    r.sign = a1.sign;
    q.trim();
    r.trim();
    return {q, r / norm};
}

friend bigint sqrt(const bigint &a1) {
    bigint a = a1;
    while (a.z.empty() || a.z.size() % 2 == 1)
        a.z.push_back(0);

    int n = a.z.size();

    int firstDigit = (int) ::sqrt((double)
        a.z[n - 1] * base + a.z[n - 2]);
    int norm = base / (firstDigit + 1);
    a *= norm;
    a *= norm;
    while (a.z.empty() || a.z.size() % 2 == 1)
        a.z.push_back(0);

    bigint r = (long long) a.z[n - 1] * base +
        a.z[n - 2];
    firstDigit = (int) ::sqrt((double) a.z[n -
        1] * base + a.z[n - 2]);
    int q = firstDigit;
    bigint res;

    for (int j = n / 2 - 1; j >= 0; j--) {
        for (; --q) {

```

```

        bigint r1 = (r - (res * 2 * base +
            q) * q) * base * base +
            (j > 0 ? (long long)
                a.z[2 * j - 1] * base
                + a.z[2 * j - 2] : 0);
        if (r1 >= 0) {
            r = r1;
            break;
        }
    }
    res *= base;
    res += q;

    if (j > 0) {
        int d1 = res.z.size() + 2 <
            r.z.size() ? r.z[res.z.size() +
                2] : 0;
        int d2 = res.z.size() + 1 <
            r.z.size() ? r.z[res.z.size() +
                1] : 0;
        int d3 = res.z.size() < r.z.size() ?
            r.z[res.z.size()] : 0;
        q = (int) (((long long) d1 * base *
            base + (long long) d2 * base +
            d3) / (firstDigit * 2));
    }

    res.trim();
    return res / norm;
}

bigint operator/(const bigint &v) const {
    return divmod(*this, v).first;
}

bigint operator%(const bigint &v) const {
    return divmod(*this, v).second;
}

bigint &operator/=(int v) {
    if (v < 0)
        sign = -sign, v = -v;
    for (int i = (int) z.size() - 1, rem = 0; i
        >= 0; --i) {
        long long cur = z[i] + rem * (long
            long) base;
        z[i] = (int) (cur / v);
        rem = (int) (cur % v);
    }
    trim();
    return *this;
}

bigint operator/(int v) const {
    return bigint(*this) /= v;
}

int operator%(int v) const {
    if (v < 0)
        v = -v;
    int m = 0;

```

```

        for (int i = (int) z.size() - 1; i >= 0;
            --i)
            m = (int) ((z[i] + m * (long long)
                base) % v);
        return m * sign;
    }

    bigint &operator*=(const bigint &v) {
        *this = *this * v;
        return *this;
    }

    bigint &operator/=(const bigint &v) {
        *this = *this / v;
        return *this;
    }

    bool operator<(const bigint &v) const {
        if (sign != v.sign)
            return sign < v.sign;
        if (z.size() != v.z.size())
            return z.size() * sign < v.z.size() *
                v.sign;
        for (int i = (int) z.size() - 1; i >= 0;
            i--)
            if (z[i] != v.z[i])
                return z[i] * sign < v.z[i] * sign;
        return false;
    }

    bool operator>(const bigint &v) const {
        return v < *this;
    }

    bool operator<=(const bigint &v) const {
        return !(v < *this);
    }

    bool operator>=(const bigint &v) const {
        return !(*this < v);
    }

    bool operator==(const bigint &v) const {
        return !(*this < v) && !(v < *this);
    }

    bool operator!=(const bigint &v) const {
        return *this < v || v < *this;
    }

    void trim() {
        while (!z.empty() && z.back() == 0)
            z.pop_back();
        if (z.empty())
            sign = 1;
    }

    bool isZero() const {
        return z.empty();
    }

    friend bigint operator-(bigint v) {

```

```

    if (!v.z.empty())
        v.sign = -v.sign;
    return v;
}

bigint abs() const {
    return sign == 1 ? *this : -*this;
}

long long longValue() const {
    long long res = 0;
    for (int i = (int) z.size() - 1; i >= 0; i--)
        res = res * base + z[i];
    return res * sign;
}

friend bigint gcd(const bigint &a, const
    bigint &b) {
    return b.isZero() ? a : gcd(b, a % b);
}

friend bigint lcm(const bigint &a, const
    bigint &b) {
    return a / gcd(a, b) * b;
}

void read(const string &s) {
    sign = 1;
    z.clear();
    int pos = 0;
    while (pos < s.size() && (s[pos] == '-' ||
        s[pos] == '+')) {
        if (s[pos] == '-')
            sign = -sign;
        ++pos;
    }
    for (int i = (int) s.size() - 1; i >= pos;
        i -= base_digits) {
        int x = 0;
        for (int j = max(pos, i - base_digits +
            1); j <= i; j++)
            x = x * 10 + s[j] - '0';
        z.push_back(x);
    }
    trim();
}

friend istream &operator>>(istream &stream,
    bigint &v) {
    string s;
    stream >> s;
    v.read(s);
    return stream;
}

friend ostream &operator<<(ostream &stream,
    const bigint &v) {
    if (v.sign == -1)
        stream << '-';
    stream << (v.z.empty() ? 0 : v.z.back());

```

```

    for (int i = (int) v.z.size() - 2; i >= 0;
        --i)
        stream << setw(base_digits) <<
            setfill('0') << v.z[i];
    return stream;
}

static vector<int> convert_base(const
    vector<int> &a, int old_digits, int
    new_digits) {
    vector<long long> p(max(old_digits,
        new_digits) + 1);
    p[0] = 1;
    for (int i = 1; i < p.size(); i++)
        p[i] = p[i - 1] * 10;
    vector<int> res;
    long long cur = 0;
    int cur_digits = 0;
    for (int v : a) {
        cur += v * p[cur_digits];
        cur_digits += old_digits;
        while (cur_digits >= new_digits) {
            res.push_back(int(cur %
                p[new_digits]));
            cur /= p[new_digits];
            cur_digits -= new_digits;
        }
    }
    res.push_back((int) cur);
    while (!res.empty() && res.back() == 0)
        res.pop_back();
    return res;
}

typedef vector<long long> vll;

static vll karatsubaMultiply(const vll &a,
    const vll &b) {
    int n = a.size();
    vll res(n + n);
    if (n <= 32) {
        for (int i = 0; i < n; i++)
            for (int j = 0; j < n; j++)
                res[i + j] += a[i] * b[j];
        return res;
    }

    int k = n >> 1;
    vll a1(a.begin(), a.begin() + k);
    vll a2(a.begin() + k, a.end());
    vll b1(b.begin(), b.begin() + k);
    vll b2(b.begin() + k, b.end());

    vll a1b1 = karatsubaMultiply(a1, b1);
    vll a2b2 = karatsubaMultiply(a2, b2);

    for (int i = 0; i < k; i++)
        a2[i] += a1[i];
    for (int i = 0; i < k; i++)
        b2[i] += b1[i];

    vll r = karatsubaMultiply(a2, b2);

```

```

    for (int i = 0; i < a1b1.size(); i++)
        r[i] -= a1b1[i];
    for (int i = 0; i < a2b2.size(); i++)
        r[i] -= a2b2[i];

    for (int i = 0; i < r.size(); i++)
        res[i + k] += r[i];
    for (int i = 0; i < a1b1.size(); i++)
        res[i] += a1b1[i];
    for (int i = 0; i < a2b2.size(); i++)
        res[i + n] += a2b2[i];
    return res;
}

bigint operator*(const bigint &v) const {
    vector<int> a6 = convert_base(this->z,
        base_digits, 6);
    vector<int> b6 = convert_base(v.z,
        base_digits, 6);
    vll a(a6.begin(), a6.end());
    vll b(b6.begin(), b6.end());
    while (a.size() < b.size())
        a.push_back(0);
    while (b.size() < a.size())
        b.push_back(0);
    while (a.size() & (a.size() - 1))
        a.push_back(0), b.push_back(0);
    vll c = karatsubaMultiply(a, b);
    bigint res;
    res.sign = sign * v.sign;
    for (int i = 0, carry = 0; i < c.size();
        i++) {
        long long cur = c[i] + carry;
        res.z.push_back((int) (cur % 1000000));
        carry = (int) (cur / 1000000);
    }
    res.z = convert_base(res.z, 6, base_digits);
    res.trim();
    return res;
}

};

bigint random_bigint(int n) {
    string s;
    for (int i = 0; i < n; i++) {
        s += rand() % 10 + '0';
    }
    return bigint(s);
}

// random tests
void bigintTest() {
    bigint x = bigint("120");
    bigint y = bigint("5");
    cout << x / y << endl;

    for (int i = 0; i < 1000; i++) {
        int n = rand() % 100 + 1;
        bigint a = random_bigint(n);
        bigint res = sqrt(a);
        bigint xx = res * res;

```

```

        bigint yy = (res + 1) * (res + 1);

        if (xx > a || yy <= a) {
            cout << i << endl;
            cout << a << " " << res << endl;
            break;
        }

        int m = rand() % n + 1;
        bigint b = random_bigint(m) + 1;
        res = a / b;
        xx = res * b;
        yy = b * (res + 1);

        if (xx > a || yy <= a) {
            cout << i << endl;
            cout << a << " " << b << " " << res <<
                endl;
            break;
        }
    }
}

bigint a = random_bigint(10000);
bigint b = random_bigint(2000);
clock_t start = clock();
bigint c = a / b;
printf("time=%.3lfsec\n", (clock() - start) *
    1. / CLOCKS_PER_SEC);
}
}

using namespace bigint;

```

10.3.2 exprParse

```

/**
 * Description: Evaluates mod expression with
 *               parentheses, or returns -1 if it is invalid
 * Usage: IPSC 2018 I1 :((((
 */

namespace exprParse {
    string expr;
    int ind; // reset to 0 every time

    int eval(char c, int x, int y) {
        switch(c) {
            case '+': return (x+y)%MOD;
            case '-': return (x-y+MOD)%MOD;
            case '*': return (1ll)x*y%MOD;
            default: exit(5);
        }
    }

    int pri(char c) {
        switch (c) {
            case '+': return 0;
            case '-': return 0;
            case '*': return 1;
            default: exit(5);
        }
    }
}

```

```

    }
}

int process(vi& num, vector<char>& op) {
    if (sz(num) < 2 || sz(op) < 1) return -1;
    int y = num.back(); num.pop_back();
    int x = num.back(); num.pop_back();
    char c = op.back(); op.pop_back();
    num.pb(eval(c,x,y));
    return 0;
}

int finish(int& state, vi& num, vector<char>& op) {
    if (state != 0) return -1;
    while (sz(op)) {
        int t = process(num,op);
        if (t == -1) return -1;
    }
    if (sz(num) != 1) return -1;
    return num[0];
}

int eval(int cur = 0) {
    vi num;
    vector<char> op;

    int state = -1;
    while (ind < sz(expr)) {
        if (expr[ind] == ')') {
            ind++;
            if (cur == 0) return -1;
            return finish(state,num,op);
        } else if (expr[ind] == '(') {
            ind++;
            num.pb(eval(1)); if (num.back() == -1)
                return -1;
            if (state == 0) return -1;
            state = 0;
        } else if (isdigit(expr[ind])) {
            int val = 0;
            while (ind < sz(expr) &&
                isdigit(expr[ind])) {
                val = (10LL*val+(expr[ind]-'0')) %
                    MOD;
                ind++;
            }
            num.pb(val);
            if (state == 0) return -1;
            state = 0;
        } else {
            while (sz(op) && pri(op.back()) >=
                pri(expr[ind])) {
                int t = process(num,op);
                if (t == -1) return -1;
            }
            op.pb(expr[ind]);
            if (state != 0) return -1;
            state = 1;
            ind++;
        }
    }
}

```

```

        if (cur == 1) return -1; // parentheses don't
            match up
        if (ind != sz(expr)) return -1;
        return finish(state,num,op);
    }
}

```

using namespace exprParse;

10.3.3 frac

```

/**
 * Source: https://martin-thoma.com/fractions-in-cpp/
 * Verification: TopCoder MinimizeAbsoluteDifferenceDiv1
 */

namespace frac {
    struct frac {
        ll n,d;
        frac() { n = 0, d = 1; }
        frac(ll _n, ll _d) {
            n = _n, d = _d;
            ll g = __gcd(n,d);
            n /= g, d /= g;
            if (d < 0) n *= -1, d *= -1;
        }
    };

    frac abs(frac F) { return frac(abs(F.n),F.d); }

    bool operator<(const frac& l, const frac& r) {
        return l.n*r.d < r.n*l.d; }
    bool operator==(const frac& l, const frac& r) {
        return l.n == r.n && l.d == r.d; }
    bool operator!=(const frac& l, const frac& r) {
        return !(l == r); }

    frac operator+(const frac& l, const frac& r) {
        return frac(l.n*r.d+r.n*l.d,l.d*r.d); }
    frac operator-(const frac& l, const frac& r) {
        return frac(l.n*r.d-r.n*l.d,l.d*r.d); }
    frac operator*(const frac& l, const frac& r) {
        return frac(l.n*r.n,l.d*r.d); }
    frac operator*(const frac& l, int r) { return
        l*frac(r,1); }
    frac operator*(int r, const frac& l) { return l*r;
    }

    frac operator/(const frac& l, const frac& r) {
        return l*frac(r.d,r.n); }
    frac operator/(const frac& l, const int& r) {
        return l/frac(r,1); }
    frac operator/(const int& l, const frac& r) {
        return frac(l,1)/r; }

    frac operator+=(frac& l, const frac& r) { return l
        = l+r; }
    frac operator-=(frac& l, const frac& r) { return l
        = l-r; }

    template<class T> frac operator*=(frac& l, const
        T& r) { return l = l*r; }
}

```



```

template<class T> frac operator/=(frac& l, const
    T& r) { return l = l/r; }

ostream& operator<<(ostream &strm, const frac &a) {
    strm << a.n;
    if (a.d != 1) strm << "/" << a.d;
    return strm;
}
}

using namespace frac;

```

10.3.4 modOp

```

/**
 * Description: Basic operations with modular arithmetic
 */

```

```

namespace modOp {
    int ad(int a, int b, int mod = MOD) { return
        (a+b)%mod; }
    int sub(int a, int b, int mod = MOD) { return
        (a-b+mod)%mod; }
    int mul(int a, int b, int mod = MOD) { return
        (ll)a*b%mod; }

    int AD(int& a, int b, int mod = MOD) { return a =
        ad(a,b,mod); }
    int SUB(int& a, int b, int mod = MOD) { return a =
        sub(a,b,mod); }
    int MUL(int& a, int b, int mod = MOD) { return a =
        mul(a,b,mod); }

    int po (int b, int p, int mod = MOD) { return
        !p?1:mul(po(mul(b,b,mod),p/2,mod),p&1?b:1,mod);
    }
    int inv (int b, int mod = MOD) { return
        po(b,mod-2,mod); }

    int invGeneral(ll a, ll b) { // 0 < a < b,
        gcd(a,b) = 1
        a %= b;
        if (a <= 1) return a;
        ll i = inv(b%a,a);
        ll tmp = -((b/a)*i+((b%a)*i)/a) % b;
        if (tmp < 0) tmp += b;
        return tmp;
    }
}

using namespace modOp;

```

10.3.5 pairOp

```

/**
 * Description: modular arithmetic with pairs
 * use for hashing
 */

```

```
using namespace modOp;
```

```

namespace pairOp {
    template<class T> T operator+=(T& l, const T& r) {
        return l = l+r; }
    template<class T> T operator--=(T& l, const T& r) {
        return l = l-r; }
    template<class T> T operator*=(T& l, const T& r) {
        return l = l*r; }

    pi operator+(const pi& l, const pi& r) {
        return {ad(l.f,r.f),ad(l.s,r.s)}; }
    pi operator-(const pi& l, const pi& r) {
        return {sub(l.f,r.f),sub(l.s,r.s)}; }
    pi operator*(const pi& l, const pi& r) {
        return {mul(l.f,r.f),mul(l.s,r.s)}; }
    pi operator*(const pi& l, const int& r) {
        return l*pi(r,r); }
    pi operator*(const int& r, const pi& l) {
        return l*r; }
    pi operator*=(pi& l, const int& r) { return l
        = l*r; }
}

```

```
using namespace pairOp;
```

10.3.6 vecOp

```

/**
 * Description: modular arithmetic with vectors
 * use for NTT
 */

```

```
using namespace modOp;
```

```

namespace vecOp {
    template<class T> T operator+=(T& l, const T& r) {
        return l = l+r; }
    template<class T> T operator--=(T& l, const T& r) {
        return l = l-r; }
    template<class T> T operator*=(T& l, const T& r) {
        return l = l*r; }

    vi operator+(const vi& l, const vi& r) {
        vi res(max(sz(l),sz(r)));
        FOR(i,sz(l)) res[i] = l[i];
        FOR(i,sz(r)) AD(res[i],r[i]);
        return res;
    }
    vi operator-(const vi& l, const vi& r) {
        vi res(max(sz(l),sz(r)));
        FOR(i,sz(l)) res[i] = l[i];
        FOR(i,sz(r)) SUB(res[i],r[i]);
        return res;
    }
    vi operator*(const vi& l, const vi& r) {
        if (min(sz(l),sz(r)) == 0) return {};
        vi x(sz(l)+sz(r)-1);

```

```

    FOR(i,sz(l)) FOR(j,sz(r))
        AD(x[i+j],mul(l[i],r[j]));
    return x;
}
vi operator*(const vi& l, const int& r) {
    vi L = l;
    for (int& i: L) MUL(i,r);
    return L;
}
vi operator*(const int& l, const vi& r) { return
    r*l; }
vi operator*=(vi& l, const int& r) { return l =
    l*r; }

vi rem(vi a, vi b) {
    while (sz(b) && b.back() == 0) b.pop_back();
    assert(sz(b)); b *= inv(b.back());
    while (sz(a) >= sz(b)) {
        int k = a.back();
        FOR(i,sz(b))
            SUB(a[sz(a)-sz(b)+i],mul(k,b[i]));
        while (sz(a) && a.back() == 0) a.pop_back();
    }
    return a;
}

vi interpolate(vpi v) {
    vi ret;
    FOR(i,sz(v)) {
        vi prod = {1};
        int todiv = 1;
        FOR(j,sz(v)) if (i != j) {
            MUL(todiv,sub(v[i].f,v[j].f));
            vi tmp = {sub(0,v[j].f),1};
            prod *= tmp;
        }
        ret += prod*mul(inv(todiv),v[i].s);
    }
    return ret;
}
}

using namespace vecOp;

```

10.4 Polynomials (6)

10.4.1 FFT

```

/**
 * Sources: KACTL, https://pastebin.com/3Tnj5mRu
 * Verification: SPOJ polymul, CSA manhattan
 */

namespace FFT {
    int get(int s) {
        return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
    }

    vcd fft(vcd& a) {
        int n = sz(a), x = get(n);

```

```

        vcd res, RES(n), roots(n);
        FOR(i,n) roots[i] =
            cd(cos(2*M_PI*i/n),sin(2*M_PI*i/n));

        res = a;
        FOR(i,1,x+1) {
            int inc = n>>i;
            FOR(j,inc) for (int k = 0; k < n; k += inc)
                {
                    int t = 2*k%n+j;
                    RES[k+j] = res[t]+roots[k]*res[t+inc];
                }
            swap(res,RES);
        }

        return res;
    }

    vcd fft_rev(vcd& a) {
        vcd res = fft(a);
        FOR(i,sz(res)) res[i] /= sz(a);
        reverse(res.begin() + 1, res.end());
        return res;
    }

    vcd brute(vcd& a, vcd& b) {
        vcd c(sz(a)+sz(b)-1);
        FOR(i,sz(a)) FOR(j,sz(b)) c[i+j] += a[i]*b[j];
        return c;
    }

    vcd conv(vcd a, vcd b) {
        int s = sz(a)+sz(b)-1, L = get(s), n = 1<<L;
        if (s <= 0) return {};
        if (s <= 200) return brute(a,b);

        a.resize(n); a = fft(a);
        b.resize(n); b = fft(b);

        FOR(i,n) a[i] *= b[i];
        a = fft_rev(a);

        a.resize(s);
        return a;
    }

    vl convll(vl a, vl b) {
        vcd A(sz(a)); FOR(i,sz(a)) A[i] = a[i];
        vcd B(sz(b)); FOR(i,sz(b)) B[i] = b[i];
        vcd X = conv(A,B);
        vl x(sz(X)); FOR(i,sz(X)) x[i] =
            round(X[i].real());
        return x;
    }
}

```

10.4.2 FFTand

```

/**
 * Description: Similar to FWHT

```

* Source: CSA - FFT And Variations
*/

```
namespace FFTand {
    int get(int s) {
        return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
    }

    vd andConv(vd P, bool inv = 0) {
        for (int len = 1; 2 * len <= sz(P); len <= 1)
        {
            for (int i = 0; i < sz(P); i += 2 * len) {
                for (int j = 0; j < len; j++) {
                    double u = P[i + j];
                    double v = P[i + len + j];

                    if (!inv) {
                        P[i + j] = v;
                        P[i + len + j] = u + v;
                    } else {
                        P[i + j] = -u + v;
                        P[i + len + j] = u;
                    }
                }
            }
        }

        return P;
    }

    vd conv(vd a, vd b) {
        int s = max(sz(a), sz(b)), L = get(s), n = 1 << L;
        if (s <= 0) return {};

        a.resize(n); a = andConv(a);
        b.resize(n); b = andConv(b);

        FOR(i, n) a[i] = a[i] * b[i];
        a = andConv(a, 1);
        return a;
    }

    vd orConv(vd a, vd b) {
        int s = max(sz(a), sz(b)), L = get(s), n = 1 << L;
        if (s <= 0) return {};

        a.resize(n); reverse(all(a)); a = andConv(a);
        b.resize(n); reverse(all(b)); b = andConv(b);

        FOR(i, n) a[i] = a[i] * b[i];
        a = andConv(a, 1);
        reverse(all(a));

        return a;
    }

    vl orConv(vl a, vl b) {
        vd A; for (ll x: a) A.pb(x);
        vd B; for (ll x: b) B.pb(x);
        vd c = orConv(A, B);
        vl C; for (double x: c) C.pb(round(x));
        return C;
    }
}
```

```
}

vl conv(vl a, vl b) {
    vd A; for (ll x: a) A.pb(x);
    vd B; for (ll x: b) B.pb(x);
    vd c = conv(A, B);
    vl C; for (double x: c) C.pb(round(x));
    return C;
}
}
```

10.4.3 FFTmod

/*
Description: Allows multiplication of polynomials in
general moduli.
Verification:
<http://codeforces.com/contest/960/submission/37085144>
*/

```
namespace FFTmod {
    int get(int s) {
        return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
    }

    void fft(vcd& a, bool inv){
        int n = sz(a), j = 0;
        vcd roots(n/2);
        FOR(i, 1, n) {
            int bit = (n >> 1);
            while (j >= bit){
                j -= bit;
                bit >>= 1;
            }
            j += bit;
            if (i < j) swap(a[i], a[j]);
        }

        ld ang = 2 * M_PI / n * (inv ? -1 : 1);
        FOR(i, n/2) roots[i] = cd(cos(ang * i), sin(ang * i));

        for (int i=2; i<=n; i<=1){
            int step = n / i;
            for(int j=0; j<n; j+=i){
                for(int k=0; k<i/2; k++){
                    cd u = a[j+k], v =
                        a[j+k+i/2] *
                        roots[step * k];
                    a[j+k] = u+v;
                    a[j+k+i/2] = u-v;
                }
            }
        }

        if (inv) FOR(i, n) a[i] /= n;
    }

    vl conv(vl a, vl b, ll mod){
        int s = sz(a)+sz(b)-1, L = get(s), n = 1 << L;
```

```

vcd v1(n), v2(n), r1(n), r2(n);
FOR(i,sz(a)) v1[i] = cd(a[i] >> 15, a[i] &
    32767);
FOR(i,sz(b)) v2[i] = cd(b[i] >> 15, b[i] &
    32767);
fft(v1, 0); fft(v2, 0);

FOR(i,n) {
    int j = (i ? (n - i) : i);
    cd ans1 = (v1[i] + conj(v1[j])) *
        cd(0.5, 0);
    cd ans2 = (v1[i] - conj(v1[j])) * cd(0,
        -0.5);
    cd ans3 = (v2[i] + conj(v2[j])) *
        cd(0.5, 0);
    cd ans4 = (v2[i] - conj(v2[j])) * cd(0,
        -0.5);
    r1[i] = (ans1 * ans3) + (ans1 * ans4) *
        cd(0, 1);
    r2[i] = (ans2 * ans3) + (ans2 * ans4) *
        cd(0, 1);
}
fft(r1, 1); fft(r2, 1);
v1 ret(n);
FOR(i,n) {
    ll av = (ll)round(r1[i].real());
    ll bv = (ll)round(r1[i].imag()) +
        (ll)round(r2[i].real());
    ll cv = (ll)round(r2[i].imag());
    av %= mod, bv %= mod, cv %= mod;
    ret[i] = (av << 30) + (bv << 15) + cv;
    ret[i] %= mod; ret[i] += mod; ret[i] %=
        mod;
}
ret.resize(s);
return ret;
}
}

```

```
using namespace FFTmod;
```

10.4.4 FWHT

```

/**
 * Description: FWHT, similar to FFT
 * Source: CSA - FFT And Variations
 * Verification: HackerRank XOR Subsequence
 */

namespace FWHT {
    int get(int s) {
        return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
    }

    vd fwht(vd P) {
        for (int len = 1; 2 * len <= sz(P); len <= 1)
            {
                for (int i = 0; i < sz(P); i += 2 * len) {
                    for (int j = 0; j < len; j++) {

```

```

                        double u = P[i + j];
                        double v = P[i + len + j];
                        P[i + j] = u+v;
                        P[i + len + j] = u-v;
                    }
                }
            }

        return P;
    }

    vd fwht_rev(vd& a) {
        vd res = fwht(a);
        FOR(i,sz(res)) res[i] /= sz(a);
        return res;
    }

    vd conv(vd a, vd b) {
        int s = max(sz(a),sz(b)), L = get(s), n = 1<<L;
        if (s <= 0) return {};

        a.resize(n); a = fwht(a);
        b.resize(n); b = fwht(b);

        FOR(i,n) a[i] = a[i]*b[i];
        a = fwht_rev(a);
        return a;
    }

    vl conv(vl a, vl b) {
        vd A; for (ll x: a) A.pb(x);
        vd B; for (ll x: b) B.pb(x);
        vd c = conv(A,B);
        vl C; for (double x: c) C.pb(round(x));
        return C;
    }
}

```

10.4.5 NTT

```

/**
 * Description: Use if you are working with
 *               non-negative integers
 * Usage: http://codeforces.com/contest/632/problem/E
 * Faster? https://oj.uz/submission/66171
 */

using namespace VecOp;

const int MOD = (119 << 23) + 1, root = 3; // =
    998244353
// For p < 2^30 there is also e.g. (5 << 25, 3), (7 <<
    26, 3),
// (479 << 21, 3) and (483 << 21, 5). The last two are
    > 10^9.

namespace NTT {
    int get(int s) {
        return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
    }
}

```

```

vi ntt(vi& a) {
    int n = sz(a), x = get(n);
    vi res, RES(n), roots(n);
    roots[0] = 1, roots[1] = po(root, (MOD-1)/n);
    FOR(i, 2, n) roots[i] = mul(roots[i-1], roots[1]);

    res = a;
    FOR(i, 1, x+1) {
        int inc = n>>i;
        FOR(j, inc) for (int k = 0; k < n; k += inc)
            {
                int t = 2*k%n+j;
                RES[k+j] =
                    ad(res[t], mul(roots[k], res[t+inc]));
            }
        swap(res, RES);
    }

    return res;
}

vi ntt_rev(vi& a) {
    vi res = ntt(a);
    ll in = inv(sz(a));
    FOR(i, sz(res)) MUL(res[i], in);
    reverse(res.begin() + 1, res.end());
    return res;
}

vi conv(vi a, vi b) {
    int s = sz(a)+sz(b)-1, L = get(s), n = 1<<L;
    if (s <= 0) return {};
    if (s <= 200) return a*b;

    a.resize(n); a = ntt(a);
    b.resize(n); b = ntt(b);

    FOR(i, n) MUL(a[i], b[i]);

    a = ntt_rev(a);
    a.resize(s);
    return a;
}

```

10.4.6 linRec

```

/**
 * Description: Berlekamp-Massey Algo
 * Tutorial: http://codeforces.com/blog/entry/61306
 * Usage: http://codeforces.com/contest/506/problem/E
 */

```

```

using namespace VecOp;

struct linRec {
    vector<vi> seq;
    vi x, fail, delta, des;

```

```

    linRec (vi _x) {
        x = _x; seq.pb({}); int best = 0;

        FOR(i, sz(x)) {
            delta.pb(mul(-1, x[i]));
            FOR(j, sz(seq.back()))
                AD(delta[i], mul(x[i-j-1], seq.back()[j]));
            if (delta[i] == 0) continue;

            fail.pb(i); if (sz(seq) == 1) {
                seq.pb(vi(i+1)); continue; }

            int k =
                mul(mul(-1, delta[i]), inv(delta[fail[best]]));
            vi cur(i-fail[best]-1); cur.pb(mul(-1, k));
            for (auto a: seq[best]) cur.pb(mul(a, k));

            cur += seq.back();
            if (i-fail[best]+sz(seq[best]) >=
                sz(seq.back())) best = sz(seq)-1;
            // take fail vector with smallest size

            seq.pb(cur);
        }

        FORd(i, sz(seq.back()))
            des.pb(mul(-1, seq.back()[i]));
        des.pb(1);
    }

    vi getPo(int n) {
        if (n == 0) return {1};
        vi x = getPo(n/2); x = rem(x*x, des);
        if (n&1) {
            vi v = {0, 1};
            x = rem(x*v, des);
        }
        return x;
    }

    int get(int n) {
        vi t = getPo(n);
        int ANS = 0;
        FOR(i, sz(t)) AD(ANS, mul(t[i], x[i]));
        return ANS;
    }
};

```

11 Graphs Hard (4)

11.1 SCC

11.1.1 2SAT

```

/*
 * Verification: https://www.spoj.com/problems/BUGLIFE/
 * Also useful: at most one
 *
 * (http://codeforces.com/contest/1007/submission/40284510)

```

```

*/

template<int SZ> struct twosat {
    scc<2*SZ> S;
    int N;

    void OR(int x, int y) { S.addEdge(x^1,y);
        S.addEdge(y^1,x); }

    int tmp[2*SZ];
    bitset<SZ> ans;

    bool solve() {
        S.N = 2*N; S.genSCC();
        for (int i = 0; i < 2*N; i += 2) if (S.comp[i]
            == S.comp[i^1]) return 0;
        reverse(all(S.allComp));
        for (int i: S.allComp) if (tmp[i] == 0)
            tmp[i] = 1, tmp[S.comp[i^1]] = -1;
        FOR(i,N) if (tmp[S.comp[2*i]] == 1) ans[i]
            = 1;
        return 1;
    }
};

```

11.1.2 Kosaraju

```

/**
 * Source: Wikipedia
 * Description: generates SCC in topological order
 * Verification: POI 8 peaceful commission
 */

template<int SZ> struct scc {
    vi adj[SZ], radj[SZ], todo, allComp;
    int N, comp[SZ];
    bitset<SZ> visit;

    void dfs(int v) {
        visit[v] = 1;
        for (int w: adj[v]) if (!visit[w]) dfs(w);
        todo.pb(v);
    }

    void dfs2(int v, int val) {
        comp[v] = val;
        for (int w: radj[v]) if (comp[w] == -1)
            dfs2(w, val);
    }

    void addEdge(int a, int b) { adj[a].pb(b),
        radj[b].pb(a); }

    void genSCC() {
        FOR(i,N) comp[i] = -1, visit[i] = 0;
        FOR(i,N) if (!visit[i]) dfs(i);
        reverse(all(todo)); // toposort
        for (int i: todo) if (comp[i] == -1)
            dfs2(i,i), allComp.pb(i);
    }
};

```

```
};
```

11.2 Flows

11.2.1 Dinic (5)

```

/**
 * Source: GeeksForGeeks
 * Verification: Problem Fashion (RMI 2017 Day 1)
 * capode: https://pastebin.com/VJxTvEg1
 */

template<int SZ> struct Dinic {
    struct Edge {
        int v;
        ll flow, cap;
        int rev;
    };

    vector<Edge> adj[SZ];

    void addEdge(int u, int v, ll cap) {
        Edge a{v, 0, cap, sz(adj[v])};
        Edge b{u, 0, 0, sz(adj[u])};
        adj[u].pb(a), adj[v].pb(b);
    }

    int level[SZ], st[SZ];

    bool bfs(int s, int t) {
        FOR(i,SZ) level[i] = -1, st[i] = 0;
        level[s] = 0;

        queue<int> q; q.push(s);
        while (sz(q)) {
            int u = q.front(); q.pop();
            for (auto e: adj[u])
                if (level[e.v] < 0 && e.flow < e.cap) {
                    level[e.v] = level[u] + 1;
                    q.push(e.v);
                }
        }

        return level[t] >= 0;
    }

    ll sendFlow(int s, int t, ll flow) {
        if (s == t) return flow;

        for (; st[s] < sz(adj[s]); st[s]++) {
            Edge &e = adj[s][st[s]];

            if (level[e.v] != level[s]+1 || e.flow ==
                e.cap) continue;
            ll temp_flow = sendFlow(e.v, t, min(flow,
                e.cap - e.flow));

            if (temp_flow > 0) {
                e.flow += temp_flow;
                adj[e.v][e.rev].flow -= temp_flow;
            }
        }
    }
};

```

```

        return temp_flow;
    }
}

return 0;
}

ll maxFlow(int s, int t) {
    if (s == t) return -1;
    ll total = 0;
    while (bfs(s, t)) while (ll flow = sendFlow(s,
        t, INT_MAX)) total += flow;
    return total;
}
};

```

11.2.2 Push-Relabel (5)

```

/**
 * Source: http://codeforces.com/blog/entry/14378
 * Verification: SPOJ fastflow
 */

struct Edge {
    int v;
    ll flow, C;
    int rev;
};

template<int SZ> struct PushRelabel {
    vector<Edge> adj[SZ];
    ll excess[SZ];
    int dist[SZ], count[SZ+1], b = 0;
    bool active[SZ];
    vi B[SZ];

    void addEdge(int u, int v, ll C) {
        Edge a{v, 0, C, sz(adj[v])};
        Edge b{u, 0, 0, sz(adj[u])};
        adj[u].pb(a), adj[v].pb(b);
    }

    void enqueue (int v) {
        if (!active[v] && excess[v] > 0 && dist[v] <
            SZ) {
            active[v] = 1;
            B[dist[v]].pb(v);
            b = max(b, dist[v]);
        }
    }

    void push (int v, Edge &e) {
        ll amt = min(excess[v], e.C-e.flow);
        if (dist[v] == dist[e.v]+1 && amt > 0) {
            e.flow += amt, adj[e.v][e.rev].flow -= amt;
            excess[e.v] += amt, excess[v] -= amt;
            enqueue(e.v);
        }
    }
};

```

```

void gap (int k) {
    FOR(v,SZ) if (dist[v] >= k) {
        count[dist[v]] --;
        dist[v] = SZ;
        count[dist[v]] ++;
        enqueue(v);
    }
}

void relabel (int v) {
    count[dist[v]] --; dist[v] = SZ;
    for (auto e: adj[v]) if (e.C > e.flow) dist[v]
        = min(dist[v], dist[e.v] + 1);
    count[dist[v]] ++;
    enqueue(v);
}

void discharge(int v) {
    for (auto &e: adj[v]) {
        if (excess[v] > 0) push(v,e);
        else break;
    }
    if (excess[v] > 0) {
        if (count[dist[v]] == 1) gap(dist[v]);
        else relabel(v);
    }
}

ll maxFlow (int s, int t) {
    for (auto &e: adj[s]) excess[s] += e.C;

    count[0] = SZ;
    enqueue(s); active[t] = 1;

    while (b >= 0) {
        if (sz(B[b])) {
            int v = B[b].back(); B[b].pop_back();
            active[v] = 0; discharge(v);
        } else b--;
    }
    return excess[t];
}
};

```

11.2.3 MinCostFlow (6)

```

/**
 * Source: GeeksForGeeks
 */

struct Edge {
    int v, flow, C, rev, cost;
};

template<int SZ> struct mcf {
    pi pre[SZ];
    int cost[SZ], num[SZ], SC, SNC;
    ll flo, ans, ccost;
    vector<Edge> adj[SZ];
};

```

```

void addEdge(int u, int v, int C, int cost) {
    Edge a{v, 0, C, sz(adj[v]), cost};
    Edge b{u, 0, 0, sz(adj[u]), -cost};
    adj[u].pb(a), adj[v].pb(b);
}

void reweight() {
    FOR(i,SZ) {
        for (auto& p: adj[i]) p.cost +=
            cost[i]-cost[p.v];
    }
}

bool spfa() {
    FOR(i,SZ) cost[i] = MOD, num[i] = 0;
    cost[SC] = 0, num[SC] = MOD;
    priority_queue<pi,vpi,greater<pi>> todo;
    todo.push({0,SC});

    while (todo.size()) {
        pi x = todo.top(); todo.pop();
        if (x.f > cost[x.s]) continue;
        for (auto a: adj[x.s]) if (x.f+a.cost <
            cost[a.v] && a.flow < a.C) {
            pre[a.v] = {x.s,a.rev};
            cost[a.v] = x.f+a.cost;
            num[a.v] = min(a.C-a.flow,num[x.s]);
            todo.push({cost[a.v],a.v});
        }
    }

    ccost += cost[SNC];
    return num[SNC] > 0;
}

void backtrack() {
    flo += num[SNC], ans += (ll)num[SNC]*ccost;
    for (int x = SNC; x != SC; x = pre[x].f) {
        adj[x][pre[x].s].flow -= num[SNC];
        int t = adj[x][pre[x].s].rev;
        adj[pre[x].f][t].flow += num[SNC];
    }
}

pi mincostflow(int sc, int snc) {
    SC = sc, SNC = snc;
    flo = ans = ccost = 0;

    spfa();
    while (1) {
        reweight();
        if (!spfa()) return {flo,ans};
        backtrack();
    }
}

};

mcf<100> m;

int main() {
    m.addEdge(0, 1, 16, 5);
    m.addEdge(1, 2, 13, 7);

```

```

    m.addEdge(1, 2, 13, 8);

    pi x = m.mincostflow(0,2);
    cout << x.f << " " << x.s;
}

```

11.3 Tarjan BCC

```

/**
 * Source: GeeksForGeeks (corrected)
 * Verification: USACO December 2017, Push a Box
 * Code: https://pastebin.com/yUWuzTH8
 */

template<int SZ> struct BCC {
    int N;
    vi adj[SZ];
    vector<vpi> fin;

    void addEdge(int u, int v) { adj[u].pb(v),
        adj[v].pb(u); }

    int ti = 0, disc[SZ], low[SZ], comp[SZ], par[SZ];
    vpi st;

    void BCCutil(int u, bool root = 0) {
        disc[u] = low[u] = ti++;
        int child = 0;

        for (int i: adj[u]) if (i != par[u])
            if (disc[i] == -1) {
                child++; par[i] = u;
                st.pb({u,i});
                BCCutil(i);
                low[u] = min(low[u],low[i]);

                if ((root && child > 1) || (!root &&
                    disc[u] <= low[i])) { //
                    articulation point!
                    vpi tmp;
                    while (st.back() != mp(u,i))
                        tmp.pb(st.back()),
                        st.pop_back();
                    tmp.pb(st.back()), st.pop_back();
                    fin.pb(tmp);
                }
            } else if (disc[i] < disc[u]) {
                low[u] = min(low[u],disc[i]);
                st.pb({u,i});
            }
    }

    void bcc(int _N) {
        N = _N;
        FOR(i,1,N+1) par[i] = disc[i] = low[i] = -1;
        FOR(i,1,N+1) if (disc[i] == -1) {
            BCCutil(i,1);
            if (sz(st)) fin.pb(st);
            st.clear();
        }
    }
}

```



```

    }
};

```

11.4 Euler Tour (6)

```

/**
 * Description: extra log factor
 * Verification:
 *   https://open.kattis.com/problems/eulerianpath
 */

struct Euler {
    vi circuit;
    multiset<int> adj[MX], ADJ[MX];
    int N,M, out[MX], in[MX];

    void find_circuit(int x) { // directed graph,
        // possible that resulting circuit is not valid
        while (sz(adj[x])) {
            int j = *adj[x].begin();
            adj[x].erase(adj[x].begin());
            find_circuit(j);
        }
        circuit.pb(x);
    }

    int a,b,start;

    vi solve() {
        FOR(i,N) {
            adj[i].clear(), ADJ[i].clear();
            out[i] = in[i] = 0;
        }
        circuit.clear();
        FOR(i,M) {
            cin >> a >> b; // add edges
            adj[a].insert(b), ADJ[a].insert(b);
            out[a] ++, in[b] ++;
        }
        start = a;
        FOR(i,N) if (out[i]-in[i] == 1) start = i;

        find_circuit(start);
        reverse(all(circuit));

        if (sz(circuit) != M+1) return {};

        FOR(i,M) { // verify that circuit is valid
            if (ADJ[circuit[i]].find(circuit[i+1]) ==
                ADJ[circuit[i]].end()) return {};
            int t = circuit[i];
            ADJ[t].erase(ADJ[t].find(circuit[i+1]));
        }

        return circuit;
    }
};

```

11.5 EdgeColor (6)

```

/**
 * Description:
 *   https://en.m.wikipedia.org/wiki/Vizing%27s_theorem
 * Usage:
 *   https://open.kattis.com/problems/gamescheduling
 */

template<int SZ> struct EdgeColor {
    int n, adjVert[SZ][SZ], adjCol[SZ][SZ];
    int deg[SZ], maxDeg;

    EdgeColor(int _n) {
        n = _n; maxDeg = 0;
        FOR(i,n) {
            deg[i] = 0;
            FOR(j,n) adjVert[i][j] = adjCol[i][j] = -1;
        }
    }

    void delEdge(int x, int y) {
        if (adjVert[x][y] == -1) return;
        int C = adjVert[x][y];
        adjCol[x][C] = adjCol[y][C] = adjVert[x][y] =
            adjVert[y][x] = -1;
    }

    void setEdge(int x, int y, int c) { // delete
        // previous value if it had one
        delEdge(x,y); assert(adjCol[x][c] == -1 &&
            adjCol[y][c] == -1);
        adjVert[x][y] = adjVert[y][x] = c,
        adjCol[x][c] = y, adjCol[y][c] = x;
    }

    void shiftPath(int x, vi p) {
        FORd(i,sz(p)) setEdge(x,p[i],notAdj[p[i]]);
    }

    vi getPath(int st, int c0, int c1) {
        vi res = {st};
        for (int nex = 0; ; nex ^= 1) {
            int c = (nex == 0 ? c0 : c1);
            if (adjCol[res.back()][c] == -1) return res;
            res.pb(adjCol[res.back()][c]);
        }
    }

    void flipPath(vi p, int c0, int c1) {
        FOR(i,sz(p)-1) delEdge(p[i],p[i+1]);
        FOR(i,sz(p)-1) {
            if (i&1) setEdge(p[i],p[i+1],c0);
            else setEdge(p[i],p[i+1],c1);
        }
    }

    int notAdj[SZ];

    void addEdge(int x, int y) {
        maxDeg = max(maxDeg,max(++deg[x],++deg[y]));
    }
};

```

```

// generate a color which is not adjacent to
// each vertex
FOR(i,n) {
    FOR(j,maxDeg+1) if (adjCol[i][j] == -1) {
        notAdj[i] = j;
        break;
    }
}

vi nex(n);
FOR(i,n) if (adjVert[x][i] != -1) nex[i] =
    adjCol[x][notAdj[i]];
nex[y] = adjCol[x][notAdj[y]];

// generate sequence of neighbors
vi vis(n), seq = {y};
while (seq.back() != -1 && !vis[seq.back()]) {
    vis[seq.back()] = 1;
    seq.pb(nex[seq.back()]);
}

// case 1: easy
if (seq.back() == -1) {
    seq.pop_back(), shiftPath(x,seq);
    return;
}

// separate into path and cycle
int ind = 0; while (seq[ind] != seq.back())
    ind ++;
seq.pop_back();
vi path = vi(seq.begin(),seq.begin()+ind);
vi cyc = vi(seq.begin()+ind,seq.end());
int c0 = notAdj[x], c1 = notAdj[cyc.back()];

// case based on a/b path
vi p = getPath(cyc.back(),c0,c1);
if (p.back() != path.back()) {
    if (p.back() == x) { p.pop_back(),
        delEdge(x,p.back()); }
    flipPath(p,c0,c1);
    notAdj[seq.back()] = c0; shiftPath(x,seq);
} else {
    reverse(all(p));
    flipPath(p,c0,c1);
    notAdj[path.back()] = c0; shiftPath(x,path);
}
}
};

```

12 Geometry (4)

12.1 Techniques

12.1.1 ComplexOp

```

/**
 * Description: Easy Geo

```

```

* Source: http://codeforces.com/blog/entry/22175
*/

namespace ComplexOp {
    template<class T> istream& operator>> (istream&
        is, complex<T>& p) {
        T value;
        is >> value; p.real(value);
        is >> value; p.imag(value);
        return is;
    }

    bool operator<(const cd& a, const cd& b) {
        if (a.real() != b.real()) return a.real() <
            b.real();
        return a.imag() < b.imag();
    }
    bool operator>(const cd& a, const cd& b) {
        if (a.real() != b.real()) return a.real() >
            b.real();
        return a.imag() > b.imag();
    }
    bool operator<=(const cd& a, const cd& b) { return
        a < b || a == b; }
    bool operator>=(const cd& a, const cd& b) { return
        a > b || a == b; }
    cd max(const cd& a, const cd& b) { return a>b?a:b;
    }
    cd min(const cd& a, const cd& b) { return a<b?a:b;
    }

    ld cross(cd a, cd b) { return (conj(a)*b).imag(); }
    ld area(cd a, cd b, cd c) { return cross(b-a,c-a);
    }
    ld dot(cd a, cd b) { return (conj(a)*b).real(); }

    cd reflect(cd p, cd a, cd b) { return
        a+conj((p-a)/(b-a))*(b-a); }
    cd proj(cd p, cd a, cd b) { return
        (p+reflect(p,a,b))/(ld)2; }

    cd line(cd a, cd b, cd c, cd d) {
        ld x = area(a,b,c), y = area(a,b,d);
        return (x*d-y*c)/(x-y);
    }

    vcd segment(cd A, cd B, cd C, cd D) { // kattis
        segmentintersection
        if (A > B) swap(A,B);
        if (C > D) swap(C,D);

        ld a1 = area(A,B,C), a2 = area(A,B,D);
        if (a1 > a2) swap(a1,a2);
        if (!(a1 <= 0 && a2 >= 0)) return {};

        if (a1 == 0 && a2 == 0) {
            if (area(A,C,D) != 0) return {};
            cd x1 = max(A,C), x2 = min(B,D);
            if (x1 > x2) return {};
            if (x1 == x2) return {x1};
            return {x1,x2};
        }
    }
}

```

```

        cd z = line(A,B,C,D);
        if (A <= z && z <= B) return {z};
        return {};
    }
}

```

12.1.2 Polygon Area

```

/**
 * Description: Shoelace Formula
 * Verification:
 *   https://open.kattis.com/problems/polygonarea
 */

ld area(vector<cd> v) {
    ld x = 0;
    FOR(i,sz(v)) {
        int j = (i+1)%sz(v);
        x += (ld)v[i].real()*v[j].imag();
        x -= (ld)v[j].real()*v[i].imag();
    }
    return abs(x)/2;
}

```

12.1.3 Point in Polygon (5)

```

/**
 * Source: own
 * Verification:
 *   https://open.kattis.com/problems/pointinpolygon
 */

int n,m;
pi p[1000];

int area(pi x, pi y, pi z) {
    return (y.f-x.f)*(z.s-x.s)-(y.s-x.s)*(z.f-x.f);
}

bool on(pi x, pi y, pi z) {
    if (area(x,y,z) != 0) return 0;
    return min(x,y) <= z && z <= max(x,y);
}

double get(pi x, pi y, int z) {
    return double((z-x.s)*y.f+(y.s-z)*x.f)/(y.s-x.s);
}

string test(pi z) {
    int ans = 0;
    FOR(i,n) {
        pi x = p[i], y = p[(i+1)%n];
        if (on(x,y,z)) return "on";
        if (x.s > y.s) swap(x,y);
        if (x.s <= z.s && y.s > z.s) {
            double t = get(x,y,z.s);
            if (t > z.f) ans++;
        }
    }
}

```

```

    }
}
if (ans % 2 == 1) return "in";
return "out";
}

```

12.1.4 3D Geometry (6)

```

/**
 * Description: Basic 3D Geometry
 * Verification: AMPPZ 2011 Cross Spider
 */

int n;
vector<vl> cur;

vl operator-(vl a, vl b) {
    vl c(sz(a)); FOR(i,sz(a)) c[i] = a[i]-b[i];
    return c;
}

bool ismult(vl b, vl c) {
    if ((ld)b[0]*c[1] != (ld)b[1]*c[0]) return 0;
    if ((ld)b[0]*c[2] != (ld)b[2]*c[0]) return 0;
    if ((ld)b[2]*c[1] != (ld)b[1]*c[2]) return 0;
    return 1;
}

bool collinear(vl a, vl b, vl c) {
    b = b-a, c = c-a;
    return ismult(b,c);
}

vl cross(vl a, vl b) {
    return {a[1]*b[2]-a[2]*b[1],
            a[2]*b[0]-a[0]*b[2],
            a[0]*b[1]-a[1]*b[0]};
}

bool coplanar(vl a, vl b, vl c, vl d) {
    b = b-a, c = c-a, d = d-a;
    return ismult(cross(b,c),cross(b,d));
}

```

12.1.5 Circles (6)

```

/**
 * Source: Own
 * Verification:
 *   https://codefights.com/tournaments/s8thqrnQL2YPK7XQt/L
 */

typedef pair<cd,ld> circle;

cd intersect(circle a, circle b, int x = 0) {
    ld d = sqrt(norm(a.f-b.f));
    ld co = (a.s*a.s+d*d-b.s*b.s)/(2*a.s*d);
    ld theta = acos(co);
}

```

```

    cd tmp = (b.f-a.f)/d;
    if (x == 0) return
        a.f+tmp*a.s*polar((ld)1.0,theta);
    return a.f+tmp*a.s*polar((ld)1.0,-theta);
}

ld arc(circle x, cd a, cd b) {
    cd d = (a-x.f)/(b-x.f);
    return x.s*acos(d.real());
}

bool on (circle x, cd y) {
    return norm(y-x.f) == x.s*x.s;
}

```

12.1.6 ClosestPair (6)

```

/**
 * Description: O(NlogN) line sweep to find two closest
 *             points
 * Source: Own
 * Verification:
 *             https://open.kattis.com/problems/closestpair2
 */

ld dist(pd a, pd b) {
    return sqrt(pow(a.f-b.f,2)+pow(a.s-b.s,2));
}

pair<pd,pd> solve(vector<pd> v) {
    pair<ld,pair<pd,pd>> bes; bes.f = INF;

    set<pd> S;
    int ind = 0;

    sort(all(v));
    FOR(i,sz(v)) {
        if (i && v[i] == v[i-1]) return {v[i],v[i]};

        while (v[i].f-v[ind].f >= bes.f) {
            S.erase({v[ind].s,v[ind].f});
            ind++;
        }

        for (auto it = S.upper_bound({v[i].s-bes.f,INF});
             it != S.end() && it->f < v[i].s+bes.f;
             it = next(it)) {
            pd t = {it->s,it->f};
            bes = min(bes,{dist(t,v[i]),{t,v[i]}});
        }

        S.insert({v[i].s,v[i].f});
    }

    return bes.s;
}

```

12.2 Sweep Line

12.2.1 Angular Sort

```

/**
 * Description: Use when atan2 does not suffice
 */

int half(pi x) { return mp(x.s,x.f) > mp(0,0); }

ll area(pi a, pi b) { return (ll)a.f*b.s-(ll)a.s*b.f; }

ll area(pi a, pi b, pi c) {
    b.f -= a.f, b.s -= a.s;
    c.f -= a.f, c.s -= a.s;
    return area(b,c);
}

bool cmp(pi a, pi b) {
    int A = half(a), B = half(b);
    if (A != B) return A < B;
    return area(a,b) > 0;
}

```

12.2.2 Convex Hull

```

/**
 * Source: Wikibooks
 * Verification:
 *             https://open.kattis.com/problems/convexhull
 */

ll cross(pi O, pi A, pi B) {
    return (ll)(A.f-O.f)*(B.s-O.s)
        - (ll)(A.s-O.s)*(B.f-O.f);
}

vpi convex_hull(vpi P) {
    sort(all(P)); P.erase(unique(all(P)),P.end());
    int n = sz(P);
    if (n == 1) return P;

    vpi bot = {P[0]};
    FOR(i,1,n) {
        while (sz(bot) > 1 && cross(bot[sz(bot)-2],
            bot.back(), P[i]) <= 0) bot.pop_back();
        bot.pb(P[i]);
    }
    bot.pop_back();

    vpi up = {P[n-1]};
    FORd(i,n-1) {
        while (sz(up) > 1 && cross(up[sz(up)-2],
            up.back(), P[i]) <= 0) up.pop_back();
        up.pb(P[i]);
    }
    up.pop_back();

    bot.insert(bot.end(),all(up));
    return bot;
}

```

}

12.2.3 Max Rectangle

```
/**
 * Description: Computes size of max rectangle in grid
 *              w/ obstacles
 * Verification: https://cses.fi/problemset/task/1147/
 */

int n,m,cur[1000];
char g[1000][1000];
ll ans = 0;

void solve(int x) {
    vi nex[m+1];
    FOR(i,n) nex[cur[i]-x].pb(i);

    DSU<1000> D = DSU<1000>();
    FORd(i,m+1) for (int a: nex[i]) {
        D.par[a] = a;
        if (a > 0 && D.par[a-1] != -1) D.unite(a,a-1);
        if (a < n-1 && D.par[a+1] != -1)
            D.unite(a,a+1);
        ans = max(ans,i*(ll)D.sz[D.get(a)]);
    }
}

int solve() {
    FOR(i,n) cur[i] = m;
    FORd(j,m) {
        FOR(i,n) if (g[i][j] == '*') cur[i] = j; //
        obstacle
        solve(j);
    }
    return ans;
}
```

12.2.4 LineContainer (6)

```
/**
 * Source: KACTL
 * Verification: CSA Squared Ends
 */

bool Q;
struct Line {
    mutable ll k, m, p; // slope, y-intercept,
    last optimal x
    bool operator<(const Line& o) const {
        return Q ? p < o.p : k < o.k;
    }
};

struct LineContainer : multiset<Line> {
    const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        if (b < 0) a *= -1, b *= -1;
```

```
        if (a >= 0) return a/b;
        return -((-a+b-1)/b);
    }

    // updates x->p, determines if y is unneeded
    bool isect(iterator x, iterator y) {
        if (y == end()) { x->p = inf; return 0;
        }
        if (x->k == y->k) x->p = x->m > y->m ?
            inf : -inf;
        else x->p = div(y->m - x->m, x->k -
            y->k);
        return x->p >= y->p;
    }

    void add(ll k, ll m) {
        auto z = insert({k, m, 0}), y = z++, x
            = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y))
            isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p
            >= y->p) isect(x, erase(y));
    }

    ll query(ll x) { // gives max value
        assert(!empty());
        Q = 1; auto l = *lb({0,0,x}); Q = 0;
        return l.k * x + l.m;
    }
};
```

12.3 Delaunay

```
/*
 * Bowyer-Watson  $O(n^2 \log n)$ 
 * Verification: Panda Preserve
 */

namespace Delaunay {
    // stay with __int128 for better precision, if
    // possible
    ld cross(cd b, cd c) { return (conj(b)*c).imag(); }
    ld cross(cd a, cd b, cd c) { return
        cross(b-a,c-a); }

    bool inCircle (cd a, cd b, cd c, cd d) {
        a -= d, b -= d, c -= d;
        ld x = norm(a)*cross(b,c)+norm(b)*cross(c,a)
            +norm(c)*cross(a,b);
        if (cross(a,b,c) < 0) x *= -1;
        return x > 0;
    }

    vector<array<int,3>> triangulate(vcd v) {
        // works with cyclic quads
        // not when all points are collinear!
        // creates super-triangle, adjusts as necessary
```

```

v.pb(cd(-1e5,-1e5)); v.pb(cd(1e5,0));
v.pb(cd(0,1e5));

vector<array<int,3>> ret;
ret.pb({sz(v)-3,sz(v)-2,sz(v)-1});

FOR(i,sz(v)-3) {
    map<pi,int> m;
    vector<array<int,3>> tmp;
    for (auto a: ret) {
        if
            (inCircle(v[a[0]],v[a[1]],v[a[2]],v[i]))
            m[{a[0],a[1]}] ++, m[{a[1],a[2]}]
            ++, m[{a[0],a[2]}] ++;
        else tmp.pb(a);
    }
    for (auto a: m) if (a.s == 1) {
        array<int,3> x = {a.f.f,a.f.s,i};
        sort(all(x));
        tmp.pb(x);
    }
    ret = tmp;
}
vector<array<int,3>> tmp;
for (auto a: ret) if (a[2] < sz(v)-3)
    tmp.pb(a);
return tmp;
}

void print(vcd x) { // produces asymptote code
    cout << "[asy]\n";
    cout << "pair[] A = {";
    bool done = 0;
    for (auto a: x) {
        if (done) cout << ",";
        cout << a; done = 1;
    }
    cout << "};\n";

    cout << "for (int i = 0; i < " << sz(x) << ";
    ++i) {\n\tdot(A[i]);\n}\n";

    for (auto b: triangulate(x)) cout << "draw(A["
    << b[0] << "]--A[" << b[1] << "]--A[" <<
    b[2] << "]--cycle);\n";
    cout << "[/asy]\n";
}
};

```

12.4 Max Collinear

```

/**
 * Source: own
 * Verification:
 *   https://open.kattis.com/problems/maxcollinear
 */

int n, mx, ans;
map<pair<pi,int>,int> m;
pi p[1000];

```

```

pair<pi,int> getline(pi a, pi b) {
    pi z = {b.f-a.f,b.s-a.s};
    swap(z.f,z.s); z.f *= -1;
    int g = __gcd(z.f,z.s); z.f /= g, z.s /= g;
    if (z.f < 0 || (z.f == 0 && z.s < 0)) z.f *= -1,
        z.s *= -1;
    return {z,z.f*a.f+z.s*a.s};
}

void solve() {
    mx = ans = 0; m.clear();
    FOR(i,n) cin >> p[i].f >> p[i].s;
    FOR(i,n) FOR(j,i+1,n) m[getline(p[i],p[j])] ++;

    for (auto a: m) mx = max(mx,a.s);
    FOR(i,1,n+1) if (i*(i-1)/2 <= mx) ans = i;
    cout << ans << "\n";
}

```

13 Additional (4)

13.1 Mo

```

/**
 * Source: Codeforces
 * Description: Answers queries offline in (N+Q)sqrt(N)
 * Also see Mo's on trees
 */

int N, Q, A[MX], ans[MX], oc[MX];
vector<array<int,3>> todo;

bool cmp(array<int,3> a, array<int,3> b) { // sort
    queries
    if (a[0]/sqrt(N) != b[0]/sqrt(N)) return a[0] <
        b[0];
    return a[1] < b[1];
}

int l = 0, r = -1, cans = 0;

void ad(int x, int y = 1) {
    x = A[x];
    // if condition: cans --;
    oc[x] += y;
    // if condition: cans ++;
}

int answer(int L, int R) { // adjust interval
    while (l > L) ad(--l);
    while (r < R) ad(++r);
    while (l < L) ad(l++, -1);
    while (r > R) ad(r--, -1);
    return cans;
}

```

13.2 Misc

13.2.1 discreteLog

```

/**
 * Description: find k such that primitive^k=x
 *             * meet in the middle: O(sqrt(MOD))
 * Source: Own
 * Verification: PA 2006 - Professor Laugh's Numbers
 */

using namespace modOp;

struct discreteLog {
    int mod, root, block;
    vi invy;
    unordered_map<int,int> u;

    int query(int x) {
        FOR(i,block) {
            int X = mul(x,invy[i],mod);
            if (u.count(X)) return
                i*block+u[X];
        }
        return -1;
    }

    void gen(int _mod, int _root) {
        mod = _mod, root = _root, u.clear();

        block = sqrt(mod)+1;
        int cur = 1;
        FOR(i,block) u[cur] = i,
            MUL(cur,root,mod);
        cur = inv(cur,mod);

        invy.resize(block);
        invy[0] = 1; FOR(i,1,block) invy[i] =
            mul(cur,invy[i-1],mod);
    }
};

```

13.2.2 queryConnect

```

/**
 * Description: For each pair of points, calculates the
 *             first time when they are connected
 * Verification:
 *             https://oj.uz/problem/view/COCI18\_pictionary
 */

// struct DSU

template<int SZ> struct queryConnect {
    int n,q; // vertices, edges, # queries
    vpi ed; // edges

    pi p[SZ]; // connectivity queries
    int l[SZ],r[SZ]; // left and right bounds for
        answer

```

```

vi tri[SZ];

bool left() {
    FOR(i,sz(ed)+1) tri[i].clear();
    bool ok = 0;
    FOR(i,q) if (l[i] != r[i]) {
        tri[(l[i]+r[i])/2].pb(i);
        ok = 1;
    }
    return ok;
}

void test() {
    DSU<SZ> D = DSU<SZ>();
    FOR(i,sz(ed)+1) {
        if (i) D.unite(ed[i-1].f,ed[i-1].s);
        for (int x: tri[i]) {
            if (D.get(p[x].f) == D.get(p[x].s))
                r[x] = i;
            else l[x] = i+1;
        }
    }
}

void solve() {
    FOR(i,q) l[i] = 0, r[i] = sz(ed)+1;
    while (left()) test();
}
};

```
