

USACO Notebook

Benq

February 15, 2018

Contents

1 Contest	2	5.2 Shortest Path (3)	6	7.4.3 2D SegTree	14
1.1 C++ Template	2	5.2.1 Bellman-Ford	6	7.4.4 Merge-Sort Tree	14
1.2 FastScanner	2	5.2.2 Dijkstra	7	7.5 BBST (4)	15
1.3 Troubleshooting	3	5.2.3 Floyd-Warshall	7	7.5.1 Link-Cut Tree (5)	15
2 Sorting And Searching (2)	4	5.3 Topological Sort (3)	7	7.5.2 Splay Tree (5)	16
2.1 Interval Cover	4	5.4 Kruskal (3)	8	7.5.3 Treap	17
2.2 Binary Search	4	6 Algorithm Design (2)	8	7.6 Persistent Queries (5)	18
3 Data Structures (2)	4	6.1 Minimum Deque (3)	8	7.6.1 Basic Persistent SegTree	18
3.1 Set	4	6.2 Ternary Search (4)	8	7.6.2 Lazy Persistent SegTree	18
3.1.1 Coordinate Compression	4	7 Range Queries (2)	8	7.6.3 Low-Memory Persistent Seg- ment Tree	19
3.1.2 Map Customization	4	7.1 Demos (3)	8	8 Trees (4)	20
4 DP (3)	5	7.1.1 2D Demo (4)	8	8.1 Tree Diameter (5)	20
4.1 Divide And Conquer (4)	5	7.1.2 BBST Demo (4)	9	8.2 Queries (4)	20
4.2 Examples	5	7.1.3 Point Update Demo	9	8.2.1 Heavy-Light Set	20
4.2.1 Distinct Subsequences	5	7.1.4 Range Update Demo (4)	9	8.2.2 LCA Demo	20
4.2.2 Knapsack	5	7.2 Static Array Queries	9	8.2.3 LCA with Binary Jumps	21
4.2.3 Longest Common Subsequence	5	7.2.1 Prefix Sums	9	8.3 Advanced (4)	21
4.2.4 Longest Increasing Subse- quence	5	7.2.2 Range Minimum Query (3)	10	8.3.1 Centroid Decomposition	21
4.2.5 Traveling Salesman (4)	6	7.2.3 Wavelet Tree (6)	10	8.3.2 Heavy-Light Decomposition	21
5 Graphs Easy (2)	6	7.3 1D Range Queries (3)	10	9 Math (4)	22
5.1 Traversal	6	7.3.1 BIT with Range Update (4)	10	9.1 Number Theory	22
5.1.1 BFS on Grid	6	7.3.2 Binary Indexed Tree	11	9.1.1 CRT (5)	22
5.1.2 DFS on Graph	6	7.3.3 Lazy SegTree (4)	11	9.1.2 Eratosthenes' Sieve	23
		7.3.4 SegTree Beats (6)	11	9.1.3 Phi	23
		7.3.5 SegTree	12	9.2 Combinatorics (5)	23
		7.3.6 Sparse SegTree (4)	13	9.2.1 Combo Basic	23
		7.4 2D Range Queries (4)	13	9.2.2 Combo Plus	23
		7.4.1 2D BIT	13	9.3 Matrices	24
		7.4.2 2D SegBIT	14		

9.3.1	Gaussian Elimination (6)	24
9.3.2	Matrix Exponentiation	24
9.4	FFT	25
9.4.1	And Convolution	25
9.4.2	Base Conversion	26
9.4.3	FFT	26
9.4.4	NTT	27
9.4.5	XOR Convolution	27
10	Graphs Hard (4)	28
10.1	Kosaraju	28
10.2	Euler Tour (6)	28
10.3	Flows	29
10.3.1	Dinic (5)	29
10.3.2	Flows Demo	30
10.3.3	MinCostFlow (6)	30
10.3.4	Push-Relabel (5)	30
10.4	Tarjan BCC	31
11	Geometry (4)	32
11.1	Techniques	32
11.1.1	3D Geometry (6)	32
11.1.2	Circles	32
11.1.3	Line Segment Intersection (5)	32
11.1.4	Pair Operators	33
11.1.5	Point in Polygon (5)	33
11.1.6	Polygon Area	34
11.2	Sweep Line	34
11.2.1	Closest Pair (6)	34
11.2.2	Convex Hull	34
11.3	Max Collinear	35
12	Strings (3)	35
12.1	Bitset Trie (4)	35
12.2	Hashing	35
12.3	Z (4)	36
12.3.1	Aho-Corasick	36
12.3.2	Manacher (5)	37
12.3.3	Minimum Rotation	37
12.3.4	Z	37
12.4	Suffix Array (4)	38
12.4.1	Wheeler (6)	38

12.4.2	Suffix Array	38
13	Additional (4)	39
13.1	Mo (6)	39
13.2	Misc	39
13.2.1	Discrete Logarithm	39
13.2.2	Pragma Optimization (6)	39

1 Contest

1.1 C++ Template

```

/**
 * Sources: various
 */

#include <bits/stdc++.h>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/assoc_container.hpp>

using namespace std;
using namespace __gnu_pbds;

typedef long long ll;
typedef vector<int> vi;
typedef pair<int, int> pii;
template <class T> using Tree = tree<T,
    null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

#define FOR(i, a, b) for (int i=a; i<(b); i++)
#define FOR(i, a) for (int i=0; i<(a); i++)
#define FORd(i,a,b) for (int i = (b)-1; i >=
    a; i--)
#define FORd(i,a) for (int i = (a)-1; i >= 0;
    i--)

#define sz(x) (int)(x).size()
#define mp make_pair
#define pb push_back
#define f first
#define s second
#define lb lower_bound

```

```

#define ub upper_bound
#define all(x) x.begin(), x.end()

const int MOD = 1000000007;

int main() {
    ios_base::sync_with_stdio(0);cin.tie(0);
}

```

```

// read!read!read!read!read!read!read!
// ll vs. int!

```

1.2 FastScanner

```

/**
 * Source: Matt Fontaine
 */

class FastScanner {
    private InputStream stream;
    private byte[] buf = new byte[1024];
    private int curChar;
    private int numChars;

    public FastScanner(InputStream stream) {
        this.stream = stream;
    }

    int read() {
        if (numChars == -1)
            throw new InputMismatchException();
        if (curChar >= numChars) {
            curChar = 0;
            try {
                numChars = stream.read(buf);
            } catch (IOException e) {
                throw new
                    InputMismatchException();
            }
            if (numChars <= 0) return -1;
        }
        return buf[curChar++];
    }
}

```

```

boolean isSpaceChar(int c) {
    return c == ' ' || c == '\n' || c ==
           '\r' || c == '\t' || c == -1;
}

boolean isEndline(int c) {
    return c == '\n' || c == '\r' || c ==
           -1;
}

public int nextInt() {
    return Integer.parseInt(next());
}

public long nextLong() {
    return Long.parseLong(next());
}

public double nextDouble() {
    return Double.parseDouble(next());
}

public String next() {
    int c = read();
    while (isSpaceChar(c)) c = read();
    StringBuilder res = new
        StringBuilder();
    do {
        res.appendCodePoint(c);
        c = read();
    } while (!isSpaceChar(c));
    return res.toString();
}

public String nextLine() {
    int c = read();
    while (isEndline(c))
        c = read();
    StringBuilder res = new
        StringBuilder();
    do {
        res.appendCodePoint(c);
        c = read();
    } while (!isEndline(c));

```

```

        return res.toString();
    }
}

```

1.3 Troubleshooting

Source: KACTL

Pre-submit:

- Write a few simple test cases, if sample is not enough.
- Are time limits close? If so, generate max cases.
- Is the memory usage fine?
- Could anything overflow?
- Make sure to submit the right file.

Wrong answer:

- Print your solution! Print debug output, as well.
- Are you clearing all datastructures between test cases?
- Can your algorithm handle the whole range of input?
- Read the full problem statement again.
- Do you handle all corner cases correctly?
- Have you understood the problem correctly?
- Any uninitialized variables?
- Any overflows?
- Confusing N and M, i and j, etc.?
- Are you sure your algorithm works?

- What special cases have you not thought of?
- Are you sure the STL functions you use work as you think?
- Add some assertions, maybe resubmit.
- Create some testcases to run your algorithm on.
- Go through the algorithm for a simple case.
- Go through this list again.
- Explain your algorithm to a team mate.
- Ask the team mate to look at your code.
- Go for a small walk, e.g. to the toilet.
- Is your output format correct? (including whitespace)
- Rewrite your solution from the start or let a team mate do it.

Runtime error:

- Have you tested all corner cases locally?
- Any uninitialized variables?
- Are you reading or writing outside the range of any vector?
- Any assertions that might fail?
- Any possible division by 0? (mod 0 for example)
- Any possible infinite recursion?
- Invalidated pointers or iterators?
- Are you using too much memory?
- Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:

- Do you have any possible infinite loops?

- What is the complexity of your algorithm?
- Are you copying a lot of unnecessary data? (References)
- How big is the input and output? (consider scanf)
- Avoid vector, map. (use arrays/unordered map)
- What do your team mates think about your algorithm?

Memory limit exceeded:

- What is the max amount of memory your algorithm should need?
- Are you clearing all data structures between test cases?

2 Sorting And Searching (2)

2.1 Interval Cover

```
/**
 * Usage:
 *   https://open.kattis.com/problems/intervalcover
 * Description: Example of greedy algorithm
 */
```

```
double A,B,cur;
vector<pair<pdd,int>> in;
int N,nex;
vi ans;
```

```
void solve() {
    nex = 0; ans.clear();
    cin >> N; in.resize(N);
    FOR(i,N) {
        cin >> in[i].f.f >> in[i].f.s;
        in[i].s = i;
    }
}
```

```
sort(all(in));
pair<double,int> mx = {-DBL_MAX,-1};

while (nex < in.size() && in[nex].f.f <=
    A) {
    mx = max(mx,{in[nex].f.s,in[nex].s});
    nex++;
}
if (nex == 0) {
    cout << "impossible\n";
    return;
}
ans.pb(mx.s);

while (mx.f < B) {
    cur = mx.f;
    while (nex < in.size() && in[nex].f.f
        <= cur) {
        mx =
            max(mx,{in[nex].f.s,in[nex].s});
        nex++;
    }
    if (mx.f == cur) {
        cout << "impossible\n";
        return;
    }
    ans.pb(mx.s);
}
cout << ans.size() << "\n";
for (int i: ans) cout << i << " ";
cout << "\n";
}
```

2.2 Binary Search

```
/**
 * Description: Basic example of binary search
 * Guess the Number
 * https://open.kattis.com/problems/guess
 */

int main() {
```

```
    int lo = 1, hi = 1000;
    while (1) {
        int mid = (lo+hi)/2;
        cout << mid << endl;
        string res; cin >> res;
        if (res == "correct") return 0;
        else if (res == "lower") hi = mid-1;
        else lo = mid+1;
    }
}
```

3 Data Structures (2)

3.1 Set

3.1.1 Coordinate Compression

```
/**
 * Description: Demonstrates use of map
 * Verification: POI 12 - The Bus
 */

void compress(vector<array<int,3>>& x, int
    ind) {
    map<int,int> m;
    for (auto& a: x) m[a[ind]] = 0;
    int co = 0; for (auto& a: m) a.s = co++;
    for (auto& a: x) a[ind] = m[a[ind]];
}
```

3.1.2 Map Customization

```
/**
 * Description: Define your own comparator /
 * hash function
 * Source: StackOverflow
 */

struct cmp {
    bool operator()(const int& l, const int&
        r) const {
```

```

        return l > r;
    }
};

struct hsh {
    size_t operator()(const pii& k) const {
        return k.f^k.s; // bad, but you get
                        the point
    }
};

set<int,cmp> s;
map<int,int,cmp> m;
unordered_map<pii,int,hsh> u;

```

4 DP (3)

4.1 Divide And Conquer (4)

```

/**
 * Source: Own
 * Usage: CEOI 2004 Two Sawmills
 */

void divi(int lo, int hi, int L, int R) {
    if (lo > hi) return;

    int mid = (lo+hi)/2;
    pair<ll,int> tmp = {1e18,-1};
    FOR(i,max(mid+1,L),R+1) tmp =
        min(tmp,{calc(0,mid)+calc(mid+1,i)+calc(i+1,n,i)});
    ans = min(ans,tmp.f);

    divi(lo,mid-1,L,tmp.s);
    divi(mid+1,hi,tmp.s,R);
}

```

4.2 Examples

4.2.1 Distinct Subsequences

```

/**
 * Description: DP eliminates overcounting
 */

int distinct(string S) {
    vi tot(26);
    int ans = 1;
    for (char c: S) {
        int t = (ans-tot[c-'A']+MOD)%MOD;
        tot[c-'A'] = (tot[c-'A']+t)%MOD;
        ans = (ans+t)%MOD;
    }
    return ans;
}

```

4.2.2 Knapsack

```

// https://open.kattis.com/problems/knapsack

double C;
int n,v[2000],w[2000],dp[2001][2001];

void solve() {
    FOR(i,n) cin >> v[i] >> w[i];
    FOR(i,n) {
        FOR(j,C+1) dp[i+1][j] = dp[i][j];
        FOR(j,C+1) if (w[i]+j <= C)
            dp[i+1][w[i]+j] =
                max(dp[i+1][w[i]+j],dp[i][j]+v[i]);
    }

    vi ans;
    int x = C;
    FORd(i,n) if (dp[i][x] != dp[i+1][x]) x -=
        w[i], ans.pb(i);

    cout << ans.size() << "\n";
    for (int i: ans) cout << i << " ";
    cout << "\n";
}

```

4.2.3 Longest Common Subsequence

```

/**
 * Description: Classic DP example
 */

int dp[1001][1001];
string a,b;

int main() {
    cin >> a >> b;
    FOR(i,sz(a)) FOR(j,b.sz(b)) {
        dp[i+1][j+1] =
            max(dp[i+1][j],dp[i][j+1]);
        if (a[i] == b[j]) dp[i+1][j+1] =
            max(dp[i+1][j+1],dp[i][j]+1);
    }
    cout << dp[sz(a)][sz(b)];
}

```

4.2.4 Longest Increasing Subsequence

```

/**
 * Description: DP with Binary Search
 */

vi bes = {0};
int n;

void ad(int x) {
    int lo = 0, hi = sz(bes)-1;
    while (lo < hi) {
        int mid = (lo+hi+1)/2;
        if (bes[mid] < x) lo = mid;
        else hi = mid-1;
    }
    if (lo == sz(bes)-1) bes.pb(0);
    bes[lo+1] = x;
}

int main() {
    cin >> n;
    FOR(i,n) {

```

```

    int x; cin >> x;
    ad(x);
}
cout << sz(bes)-1;
}

```

4.2.5 Traveling Salesman (4)

```

/**
 * Description: Bitset DP example
 * Solves TSP for small N
 */

const int MX = 15;

int N, dp[MX][1<<MX], dist[MX][MX];

int solve() {
    FOR(i,N) FOR(j,1<<N) dp[i][j] = MOD;

    dp[0][1] = 0;
    FOR(j,1<<N) FOR(i,N) if (j&(1<<i))
        FOR(k,N) if (!(j&(1<<k)))
            dp[k][j^(1<<k)] =
                min(dp[k][j^(1<<k)], dp[i][j]+dist[i][k]);

    int ans = MOD;
    FOR(j,1,N) ans =
        min(ans, dp[j][(1<<N)-1]+dist[j][0]);
    return ans;
}

int main() {
    int T; cin >> T;
    FOR(i,T) {
        cin >> N; N++;
        FOR(j,N) FOR(k,N) if (j != k) cin
            >> dist[j][k];
        cout << solve() << "\n";
    }
}

```

5 Graphs Easy (2)

5.1 Traversal

5.1.1 BFS on Grid

```

/**
 * Note: Use xdir and ydir
 */

int xdir[4] = {0,1,0,-1}, ydir[4] =
    {1,0,-1,0};
int dist[21][21];
queue<pii> todo;

void process(pii x) {
    FOR(i,4) {
        pii y =
            {x.f+xdir[i],x.s+ydir[i]};
        if (y.f < 0 || y.f > 20 || y.s
            < 0 || y.s > 20) continue;
        // ignore this point if
        // it's outside of grid
        if (dist[y.f][y.s] == MOD) { //
            test whether point has been
            visited or not
            dist[y.f][y.s] =
                dist[x.f][x.s]+1;
            todo.push(y); // push point
            to queue
        }
    }
}

int main() {
    FOR(i,21) FOR(j,21) dist[i][j] = MOD;
    dist[10][10] = 0; todo.push({10,10});
    // initialize queue, distances
    while (todo.size()) {
        process(todo.front());
        todo.pop(); // pop point from queue
    }
    cout << dist[4][5]; // 11
}

```

5.1.2 DFS on Graph

```

/**
 * Classic
 */

int n, visit[100001];
vi adj[100001];

void dfs(int node) {
    if (visit[node]) return;
    visit[node] = 1;
    for (int i: adj[node]) dfs(i);
    cout << node << "\n";
    // do stuff
}

int main() {
    cin >> n;
    FOR(i,n-1) {
        int a,b; cin >> a >> b;
        adj[a].pb(b);
        adj[b].pb(a);
    }
    dfs(1);
}

```

5.2 Shortest Path (3)

5.2.1 Bellman-Ford

```

/**
 * Usage:
 *   https://open.kattis.com/problems/shortestpath3
 * Description: can be useful with linear
 * programming
 * Constraints of the form x_i-x_j<k
 */

const ll INF = 1e18;

int n,m,q,s,bad[1000];

```

```
vector<pair<pii,int>> edge;
ll dist[1000];

void solve() {
    edge.clear();
    FOR(i,n) dist[i] = INF, bad[i] = 0;
    dist[s] = 0;
    FOR(i,m) {
        int u,v,w; cin >> u >> v >> w;
        edge.pb({u,v},w});
    }
    FOR(i,n) for (auto a: edge) if
        (dist[a.f.f] < INF) dist[a.f.s] =
        min(dist[a.f.s], dist[a.f.f]+a.s);
    for (auto a: edge) if (dist[a.f.f] < INF)
        if (dist[a.f.s] > dist[a.f.f]+a.s)
            bad[a.f.s] = 1;
    FOR(i,n) for (auto a: edge) if
        (bad[a.f.f]) bad[a.f.s] = 1;

    FOR(i,q) {
        int x; cin >> x;
        if (bad[x]) cout << "-Infinity\n";
        else if (dist[x] == INF) cout <<
            "Impossible\n";
        else cout << dist[x] << "\n";
    }
    cout << "\n";
}
```

5.2.2 Dijkstra

```
/**
 * Description: shortest path!
 * Works with negative edge weights (aka SPFA?)
 */

template<int SZ> struct Dijkstra {
    int dist[SZ];
    vector<pii> adj[SZ];
    priority_queue<pii,vector<pii>,greater<pii>>
        q;
```

```
void gen() {
    fill_n(dist,SZ,MOD); dist[0] = 0;

    q.push({0,0});
    while (q.size()) {
        pii x = q.top(); q.pop();
        if (dist[x.s] < x.f) continue;
        for (pii y: adj[x.s]) if
            (x.f+y.s < dist[y.f]) {
                dist[y.f] = x.f+y.s;
                q.push({dist[y.f],y.f});
            }
    }
}

Dijkstra<100> D;

int main() {
    FOR(i,100) FOR(j,100) if (rand() % 10
        == 0) D.adj[i].pb({j,rand() %
        10+1});
    D.gen();
    FOR(i,100) cout << D.dist[i] << "\n";
}
```

5.2.3 Floyd-Warshall

```
/**
 * Usage:
 * https://open.kattis.com/problems/allpairspath
 */

const ll INF = 1e18;

int n,m,q; // vertices, edges, queries
ll dist[150][150], bad[150][150];

void solve() {
    FOR(i,n) FOR(j,n) dist[i][j] = INF,
        bad[i][j] = 0;
    FOR(i,n) dist[i][i] = 0;
    FOR(i,m) {
```

```
int u,v,w; cin >> u >> v >> w;
    dist[u][v] = min(dist[u][v],(ll)w);
}
FOR(k,n) FOR(i,n) FOR(j,n) if (dist[i][k]
    != INF && dist[k][j] != INF)
    dist[i][j] =
        min(dist[i][j],dist[i][k]+dist[k][j]);

FOR(k,n) FOR(i,n) FOR(j,n) if (dist[i][k]
    != INF && dist[k][j] != INF)
    if (dist[i][j] > dist[i][k]+dist[k][j])
        bad[i][j] = 1;

FOR(k,n) FOR(i,n) FOR(j,n) {
    if (dist[i][k] < INF && bad[k][j])
        bad[i][j] = 1;
    if (bad[i][k] && dist[k][j] < INF)
        bad[i][j] = 1;
}

FOR(i,q) {
    int u,v; cin >> u >> v;
    if (bad[u][v]) cout << "-Infinity\n";
    else if (dist[u][v] == INF) cout <<
        "Impossible\n";
    else cout << dist[u][v] << "\n";
}
cout << "\n";
}
```

5.3 Topological Sort (3)

```
/**
 * Description: sorts vertices such that if
 * there exists an edge x->y, then x goes
 * before y
 */

int N,M, in[100001];
vi res, adj[100001];

void topo() {
    queue<int> todo;
```

```

FOR(i,1,N+1) if (in[i] == 0) todo.push(i);
while (sz(todo)) {
    int x = todo.front(); todo.pop();
    res.pb(x);
    for (int i: adj[x]) {
        in[i]--;
        if (!in[i]) todo.push(i);
    }
}

int main() {
    cin >> N >> M;
    FOR(i,M) {
        int x,y; cin >> x >> y;
        adj[x].pb(y), in[y]++;
    }
    topo();
    for (int i: res) cout << i << " ";
}

```

5.4 Kruskal (3)

```

/**
 * Source: own
 * Description: computes the minimum spanning
 *              tree in O(ElogE) time
 * Verification: USACO superbull
 */

template<int SZ> struct DSU {
    int par[SZ], sz[SZ];
    DSU() {
        FOR(i,SZ) par[i] = i, sz[i] = 1;
    }

    int get(int x) { // path compression
        if (par[x] != x) par[x] = get(par[x]);
        return par[x];
    }

    bool unite(int x, int y) { // union-by-rank
        x = get(x), y = get(y);

```

```

        if (x == y) return 0;
        if (sz[x] < sz[y]) swap(x,y);
        sz[x] += sz[y], par[y] = x;
        return 1;
    }
};

int ans = 0; // total weight of MST
vector<pair<int,pii>> edge;

DSU<100> D;

void kruskal() {
    sort(all(edge));
    for (auto a: edge) if
        (D.unite(a.s.f,a.s.s)) ans += a.f;
    // edge is in MST
}

```

6 Algorithm Design (2)

6.1 Minimum Deque (3)

```

/**
 * Source: own
 * Verification: Jan 18 Lifeguards
 */

struct MinDeque {
    int lo = 0, hi = -1;
    deque<pii> d;

    void ins(int x) { // add to back
        while (sz(d) && d.back().f >= x)
            d.pop_back();
        d.pb({x,++hi});
    }

    void del() { // delete from front
        if (d.front().s == lo++) d.pop_front();
    }
}

```

```

int get() {
    return sz(d) ? d.front().f : MOD;
}
};

```

6.2 Ternary Search (4)

```

/**
 * Description: use on functions which are
 *              strictly decreasing then strictly
 *              increasing
 */

double eval(double x) {
    return (x-5)*(x-5);
}

double ternary(double l, double r) {
    if (abs(r-l) <= 1e-9) return (l+r)/2;
    double l1 = (2*l+r)/3, r1 = (l+2*r)/3;
    return eval(l1) < eval(r1) ? ternary(l,r1)
        : ternary(l1,r);
}

// ternary(-100,100) = 5

```

7 Range Queries (2)

7.1 Demos (3)

7.1.1 2D Demo (4)

```

/**
 * Link: http://www.spoj.com/problems/MATSUM/
 *       (modified)
 * Description: Use with 2D BIT, 2D SegBIT, 2D
 *              SegTree
 */

int main() {

```



```

BIT2D<int,1024> B = BIT2D<int,1024>();
Node<int> S = Node<int>();

FOR(i,100000) {
    int c = rand()%1;
    if (c == 0) {
        int x = rand() % SZ, y = rand() %
            SZ, num = rand() % 100;
        S.upd(x,y,num);
        x++, y++;
        B.upd(x,y,num);
    } else if (c == 1) {
        int x1 = rand() % SZ, y1 = rand() %
            SZ, x2 = rand() % SZ, y2 =
            rand() % SZ;
        if (x1 > x2) swap(x1,x2);
        if (y1 > y2) swap(y1,y2);
        int a = S.query(x1,x2,y1,y2);
        x1 ++, y1 ++, x2 ++, y2 ++;
        int b = B.query(x1,x2,y1,y2);
        assert(a == b);
    } else break;
}
}

```

7.1.2 BBST Demo (4)

```

/**
 * Link: http://www.spoj.com/problems/ORDERSET/
 * Description: Use with treap, splay tree
 */

int main() {
    int Q; cin >> Q;
    FOR(i,Q) {
        char c; int d; cin >> c >> d;
        if (c == 'I') root =
            ins(root,d);
        else if (c == 'D') root =
            del(root,d);
        else if (c == 'K') {
            if (!root || root->sz <
                d) cout <<

```

```

        "invalid\n";
    else cout <<
        find_by_order(d) <<
        "\n";
    } else cout << order_of_key(d)
        << "\n";
    }
}

```

7.1.3 Point Update Demo

```

/**
 * Link: http://www.spoj.com/problems/FENTREE/
 * Description: Use with SegTree, BIT, Sparse
 *              SegTree
 */

Seg<ll,1<<20> B;

int main() {
    int N; cin >> N;
    FOR(i,1,N+1) {
        int x; cin >> x;
        B.upd(i,x);
    }
    int q; cin >> q;
    FOR(i,q) {
        char c; int a, b;
        cin >> c >> a >> b;
        if (c == 'q') cout << B.query(a,b)
            << "\n";
        else B.upd(a,b);
    }
}

```

7.1.4 Range Update Demo (4)

```

/**
 * Link: http://www.spoj.com/problems/HORRIBLE/
 * Description: Use with range BIT, lazy
 *              segtree

```

```

*/

int main() {
    int T; cin >> T;
    FOR(i,T) {
        LazySegTree<ll,1<<17> B =
            LazySegTree<ll,1<<17>();
        int N, C; cin >> N >> C;
        FOR(j,C) {
            int t; cin >> t;
            if (t == 0) {
                int p,q,v; cin >> p >> q >> v;
                B.upd(p,q,v);
            } else {
                int p,q; cin >> p >> q;
                cout << B.qsum(p,q) << "\n";
            }
        }
    }
}

```

7.2 Static Array Queries

7.2.1 Prefix Sums

```

/**
 * Description: Calculates rectangle sums in
 *              constant time
 * Verification: POI 16 Ticket Inspector
 */

template<class T, int SZ> struct sums {
    T sum[SZ][SZ];
    sums () { memset(sum,0,sizeof sum); }
    void init() {
        FOR(i,1,SZ) FOR(j,1,SZ)
            sum[i][j] +=
                sum[i][j-1]+sum[i-1][j]-sum[i-1][j-1];
    }
    T get(int X1, int X2, int Y1, int Y2) {
        return sum[X2][Y2]-sum[X1-1][Y2]
            -sum[X2][Y1-1]+sum[X1-1][Y1-1];
    }
}

```

```
};
```

7.2.2 Range Minimum Query (3)

```
/**
 * Description: Supports 1D range minimum
 *              query in constant time.
 * Verification: Problem Tournament from IOI
 *               2012: http://wcipeg.com/problem/ioi1223
 * Source code: https://pastebin.com/ChpniVZL
 */

template<class T, int SZ> struct RMQ {
    T stor[SZ][32-__builtin_clz(SZ)];

    T comb(T a, T b) {
        return min(a,b);
    }

    void build(vector<T>& x) {
        FOR(i,sz(x)) stor[i][0] = x[i];
        FOR(j,1,32-__builtin_clz(SZ))
            FOR(i,SZ-(1<<(j-1)))
                stor[i][j] =
                    comb(stor[i][j-1],stor[i+(1<<(j-1))][j-1]);
    }

    T query(int l, int r) {
        int x = 31-__builtin_clz(r-l+1);
        return
            comb(stor[l][x],stor[r-(1<<x)+1][x]);
    }
};
```

7.2.3 Wavelet Tree (6)

```
/**
 * Description: Segment tree on values instead
 *              of indices
 * Verification:
 *               http://www.spoj.com/problems/MKTHNUM/
```

```
*/

int N,Q, A[100000];
map<int,int> m;
vi revm;

void input() {
    cin >> N >> Q;
    FOR(i,N) cin >> A[i];
}

void compress() {
    FOR(i,N) m[A[i]] = 0;
    int nex = 0;
    for (auto& a: m) {
        a.s = nex++;
        revm.pb(a.f);
    }
    FOR(i,N) A[i] = m[A[i]];
}

template<int SZ> struct wavelet {
    vi mapl[2*SZ], mapr[2*SZ], val[2*SZ];

    void build(int ind = 1, int L = 0, int R =
        SZ-1) { // build a wavelet tree
        if (ind == 1) { FOR(i,N)
            val[ind].pb(i); }

        if (L < R) {
            int M = (L+R)/2;
            for (int i: val[ind]) {
                val[2*ind+(A[i] > M)].pb(i);
                mapl[ind].pb(sz(val[2*ind])-1);
                mapr[ind].pb(sz(val[2*ind+1])-1);
            }
            build(2*ind,L,M);
            build(2*ind+1,M+1,R);
        }
    }

    int getl(int ind, int x) { return x < 0 ?
        -1 : mapl[ind][x]; }
```

```
int getr(int ind, int x) { return x < 0 ?
    -1 : mapr[ind][x]; }

int query(int lind, int rind, int k, int
    ind = 1, int L = 0, int R = SZ-1) { //
    how many <= mid with index <= r
    if (L == R) return L;

    int M = (L+R)/2;
    int t =
        getl(ind,rind)-getl(ind,lind-1);
    if (t >= k) return
        query(getl(ind,lind-1)+1,
            getl(ind,rind),k,2*ind,L
        );
    return query(getr(ind,lind-1)+1,
        getr(ind,rind),k-t,2*ind+1,M+1,R);
}

};

wavelet<1<<17> w;

int main() {
    input();
    compress();
    w.build();

    FOR(i,Q) {
        int l,r,k; cin >> l >> r >> k;
        cout << revm[w.query(l-1,r-1,k)] <<
            "\n";
    }
}
```

7.3 1D Range Queries (3)

7.3.1 BIT with Range Update (4)

```
/**
 * Source: GeeksForGeeks?
 * Description: 1D range update, range query
 * Alternative to lazy segment tree
 */
```

```
// BIT template

template<class T, int SZ> struct BITrange {
    BIT<T,SZ> bit[2]; // sums piecewise linear
                      functions

    void upd(int hi, T val) {
        bit[1].upd(1,val),
        bit[1].upd(hi+1,-val);
        bit[0].upd(hi+1,hi*val);
    }

    void upd(int lo, int hi, T val) {
        upd(lo-1,-val), upd(hi,val); }

    T query(int x) { return
        bit[1].query(x)*x+bit[0].query(x); }
    T query(int x, int y) { return
        query(y)-query(x-1); }
};
```

7.3.2 Binary Indexed Tree

```
/**
 * Description: 1D range sum query with point
 * update
 * Verification: SPOJ Fenwick
 */

template<class T, int SZ> struct BIT {
    T bit[SZ+1];

    BIT() { memset(bit,0,sizeof bit); }

    void upd(int k, T val) { // add val to
        index k
        for( ;k <= SZ; k += (k&-k)) bit[k] +=
            val;
    }

    T query(int k) {
        T temp = 0;
        for ( ;k > 0; k -= (k&-k)) temp +=
            bit[k];
    }
};
```

```
        return temp;
    }
    T query(int l, int r) { return
        query(r)-query(l-1); } // range query
        [l,r]
};
```

7.3.3 Lazy SegTree (4)

```
/**
 * Description: 1D range update, range query
 * Verification: SPOJ Horrible
 */

const ll INF = 1e18; // setting this to MOD
                    can be disastrous :(

template<class T, int SZ> struct LazySegTree {
    T sum[2*SZ], mn[2*SZ], lazy[2*SZ]; // set
    SZ to a power of 2

    LazySegTree() {
        memset (sum,0,sizeof sum);
        memset (mn,0,sizeof mn);
        memset (lazy,0,sizeof lazy);
    }

    void push(int ind, int L, int R) {
        sum[ind] += (R-L+1)*lazy[ind];
        mn[ind] += lazy[ind];
        if (L != R) lazy[2*ind] += lazy[ind],
            lazy[2*ind+1] += lazy[ind];
        lazy[ind] = 0;
    }

    void pull(int ind) {
        sum[ind] = sum[2*ind]+sum[2*ind+1];
        mn[ind] = min(mn[2*ind],mn[2*ind+1]);
    }

    void build() {
        FORd(i,SZ) pull(i);
    }
};
```

```
T qsum(int lo, int hi, int ind = 1, int L
    = 0, int R = SZ-1) {
    push(ind,L,R);
    if (lo > R || L > hi) return 0;
    if (lo <= L && R <= hi) return
        sum[ind];

    int M = (L+R)/2;
    return qsum(lo,hi,2*ind,L,M) +
        qsum(lo,hi,2*ind+1,M+1,R);
}

T qmin(int lo, int hi, int ind = 1, int L
    = 0, int R = SZ-1) {
    push(ind,L,R);
    if (lo > R || L > hi) return INF;
    if (lo <= L && R <= hi) return mn[ind];

    int M = (L+R)/2;
    return min(qmin(lo,hi,2*ind,L,M),
        qmin(lo,hi,2*ind+1,M+1,R));
}

void upd(int lo, int hi, ll inc, int ind =
    1, int L = 0, int R = SZ-1) {
    push(ind,L,R);
    if (hi < L || R < lo) return;
    if (lo <= L && R <= hi) {
        lazy[ind] = inc;
        push(ind,L,R);
        return;
    }

    int M = (L+R)/2;
    upd(lo,hi,inc,2*ind,L,M);
    upd(lo,hi,inc,2*ind+1,M+1,R);
    pull(ind);
}
};
```

7.3.4 SegTree Beats (6)

```

/**
 * Description: Interval min modifications
 * Verification:
 *   http://acm.hdu.edu.cn/showproblem.php?pid=5306
 */

const int MX = 1<<20;

int N,M, a[MX];

struct Seg {
    ll sum[2*MX];
    int mx1[2*MX], mx2[2*MX], maxCnt[2*MX];

    void pull(int ind) {
        mx1[ind] =
            max(mx1[2*ind],mx1[2*ind+1]);
        mx2[ind] =
            max(mx2[2*ind],mx2[2*ind+1]);
        maxCnt[ind] = 0;

        if (mx1[2*ind] == mx1[ind])
            maxCnt[ind] += maxCnt[2*ind];
        else mx2[ind] =
            max(mx2[ind],mx1[2*ind]);

        if (mx1[2*ind+1] == mx1[ind])
            maxCnt[ind] += maxCnt[2*ind+1];
        else mx2[ind] =
            max(mx2[ind],mx1[2*ind+1]);

        sum[ind] = sum[2*ind]+sum[2*ind+1];
    }

    void build(int ind = 1, int L = 0, int R =
        N-1) {
        if (L == R) {
            mx1[ind] = sum[ind] = a[L];
            maxCnt[ind] = 1;
            mx2[ind] = -1;
            return;
        }

        int M = (L+R)/2;
        build(2*ind,L,M); build(2*ind+1,M+1,R);

```

```

        pull(ind);
    }

    void push(int ind, int L, int R) {
        if (L == R) return;
        if (mx1[2*ind] > mx1[ind]) {
            sum[2*ind] -=
                (ll)maxCnt[2*ind]*(mx1[2*ind]-mx1[ind]);
            mx1[2*ind] = mx1[ind];
        }
        if (mx1[2*ind+1] > mx1[ind]) {
            sum[2*ind+1] -=
                (ll)maxCnt[2*ind+1]*(mx1[2*ind+1]-mx1[ind]);
            mx1[2*ind+1] = mx1[ind];
        }
    }

    void modify(int x, int y, int t, int ind =
        1, int L = 0, int R = N-1) {
        if (R < x || y < L || mx1[ind] <= t)
            return;
        push(ind,L,R);
        if (x <= L && R <= y && mx2[ind] < t) {
            sum[ind] -=
                (ll)maxCnt[ind]*(mx1[ind]-t);
            mx1[ind] = t;
            return;
        }
        if (L == R) return;
        int M = (L+R)/2;
        modify(x,y,t,2*ind,L,M);
        modify(x,y,t,2*ind+1,M+1,R);
        pull(ind);
    }

    ll qsum(int x, int y, int ind = 1, int L =
        0, int R = N-1) {
        if (R < x || y < L) return 0;
        push(ind,L,R);
        if (x <= L && R <= y) return sum[ind];

        int M = (L+R)/2;
        return
            qsum(x,y,2*ind,L,M)+qsum(x,y,2*ind+1,M+1,R);
    }

```

```

    int qmax(int x, int y, int ind = 1, int L
        = 0, int R = N-1) {
        if (R < x || y < L) return -1;
        push(ind,L,R);
        if (x <= L && R <= y) return mx1[ind];

        int M = (L+R)/2;
        return
            max(qmax(x,y,2*ind,L,M),qmax(x,y,2*ind+1,M));
    }

    void solve() {
        cin >> N >> M;
        FOR(i,N) cin >> a[i];
        S.build();

        FOR(i,M) {
            int t; cin >> t;
            if (t == 0) {
                int x,y,z; cin >> x >> y >> z;
                S.modify(x-1,y-1,z);
            } else if (t == 1) {
                int x,y; cin >> x >> y;
                cout << S.qmax(x-1,y-1) << "\n";
            } else {
                int x,y; cin >> x >> y;
                cout << S.qsum(x-1,y-1) << "\n";
            }
        }
    }
}

```

7.3.5 SegTree

```

/**
 * Source:
 *   http://codeforces.com/blog/entry/18051
 * Description: 1D point update, range query
 * Verification: SPOJ Fenwick
 */

```

```

template<class T, int SZ> struct Seg {
    T seg[2*SZ], MN = 0;

    Seg() {
        memset(seg,0,sizeof seg);
    }

    T comb(T a, T b) { return a+b; } // easily
        change this to min or max

    void upd(int p, T value) { // set value at
        position p
        for (seg[p += SZ] = value; p > 1; p
            >>= 1)
            seg[p>>1] =
                comb(seg[(p|1)^1],seg[p|1]);
        // non-commutative operations
    }

    void build() {
        FORd(i,SZ) seg[i] =
            comb(seg[2*i],seg[2*i+1]);
    }

    T query(int l, int r) { // sum on interval
        [l, r]
        T res1 = MN, res2 = MN; r++;
        for (l += SZ, r += SZ; l < r; l >>= 1,
            r >>= 1) {
            if (l&1) res1 = comb(res1,seg[l++]);
            if (r&1) res2 = comb(seg[--r],res2);
        }
        return comb(res1,res2);
    }
};

```

7.3.6 Sparse SegTree (4)

```

/**
 * Source: Own
 */

```

```

const int SZ = 1<<20;

template<class T> struct node {
    T val;
    node<T>* c[2];

    node() {
        val = 0;
        c[0] = c[1] = NULL;
    }

    void upd(int ind, T v, int L = 0, int R =
        SZ-1) { // add v
        if (L == ind && R == ind) { val += v;
            return; }

        int M = (L+R)/2;
        if (ind <= M) {
            if (!c[0]) c[0] = new node();
            c[0]->upd(ind,v,L,M);
        } else {
            if (!c[1]) c[1] = new node();
            c[1]->upd(ind,v,M+1,R);
        }

        val = 0;
        if (c[0]) val += c[0]->val;
        if (c[1]) val += c[1]->val;
    }

    T query(int low, int high, int L = 0, int
        R = SZ-1) { // query sum of segment
        if (low <= L && R <= high) return val;
        if (high < L || R < low) return 0;

        int M = (L+R)/2;
        T t = 0;
        if (c[0]) t +=
            c[0]->query(low,high,L,M);
        if (c[1]) t +=
            c[1]->query(low,high,M+1,R);
        return t;
    }
}

```

```

void UPD(int ind, node* c0, node* c1, int
    L = 0, int R = SZ-1) { // for 2D
    segtree
    if (L != R) {
        int M = (L+R)/2;
        if (ind <= M) {
            if (!c[0]) c[0] = new node();
            c[0]->UPD(ind,c0 ? c0->c[0] :
                NULL,c1 ? c1->c[0] :
                NULL,L,M);
        } else {
            if (!c[1]) c[1] = new node();
            c[1]->UPD(ind,c0 ? c0->c[1] :
                NULL,c1 ? c1->c[1] :
                NULL,M+1,R);
        }
    }
    val = 0;
    if (c0) val += c0->val;
    if (c1) val += c1->val;
}
};

```

7.4 2D Range Queries (4)

7.4.1 2D BIT

```

/**
 * Description: Supports point update & range
    query, can be extended to range update
 * Verification: SPOJ matsum
 * Dependency: Binary indexed tree
 */

```

```

template<class T, int SZ> struct BIT2D {
    BIT<T,SZ> bit[SZ+1];
    void upd(int X, int Y, T val) {
        for (; X <= SZ; X += (X&-X))
            bit[X].upd(Y,val);
    }

    T query(int X, int Y) {
        T ans = 0;

```

```

        for (; X > 0; X -= (X&-X)) ans +=
            bit[X].query(Y);
        return ans;
    }
    T query(int X1, int X2, int Y1, int Y2) {
        return query(X2,Y2)-query(X1-1,Y2)
            -query(X2,Y1-1)+query(X1-1,Y1-1);
    }
};

int main() {
    int T; cin >> T;
    FOR(i,T) {
        int N; cin >> N;
        BIT2D<ll,1024> B = BIT2D<ll,1024>();
        while (1) {
            string c; cin >> c;
            if (c == "SET") {
                int x, y,num; cin >> x >> y
                    >> num;
                x++, y++;
                B.upd(x,y,num-B.query(x,x,y,y));
            } else if (c == "SUM") {
                int x1, y1, x2, y2; cin >>
                    x1 >> y1 >> x2 >> y2;
                x1 ++, y1 ++, x2 ++, y2++;
                cout <<
                    B.query(x1,x2,y1,y2) <<
                    "\n";
            } else break;
        }
    }
}

```

7.4.2 2D SegBIT

```

/**
 * Source: USACO Mowing the Field
 * Dependency: Sparse SegTree
 */

```

```
const int SZ = 1<<17;
```

```

template<class T> struct SegBit {
    node<T> seg[SZ+1];

    SegBit() {
        FOR(i,SZ+1) seg[i] = node<T>();
    }

    void upd(int x, int y, int v) { // add v
        for (x++;x <= SZ; x += (x&-x))
            seg[x].upd(y,v);
    }

    T query(int x, int y1, int y2) {
        T ret = 0;
        for (;x > 0; x -= (x&-x)) ret +=
            seg[x].query(y1,y2);
        return ret;
    }

    T query(int x1, int x2, int y1, int y2) {
        // query sum of rectangle
        return
            query(x2+1,y1,y2)-query(x1,y1,y2);
    }
};

```

7.4.3 2D SegTree

```

/**
 * Source: USACO Mowing the Field
 * Dependency: Sparse SegTree
 */

```

```
const int SZ = 1<<17;
```

```

template<class T> struct Node {
    node<T> seg;
    Node* c[2];

    void upd(int x, int y, T v, int L = 0, int
        R = SZ-1) { // add v
        if (L == x && R == x) {
            seg.upd(y,v);

```

```

            return;
        }

        int M = (L+R)/2;
        if (x <= M) {
            if (!c[0]) c[0] = new Node();
            c[0]->upd(x,y,v,L,M);
        } else {
            if (!c[1]) c[1] = new Node();
            c[1]->upd(x,y,v,M+1,R);
        }

        seg.UPD(y,c[0] ? &c[0]->seg :
            NULL,c[1] ? &c[1]->seg : NULL);
    }

    T query(int x1, int x2, int y1, int y2,
        int L = 0, int R = SZ-1) { // query
        sum of rectangle
        if (x1 <= L && R <= x2) return
            seg.query(y1,y2);
        if (x2 < L || R < x1) return 0;

        int M = (L+R)/2;
        T t = 0;
        if (c[0]) t +=
            c[0]->query(x1,x2,y1,y2,L,M);
        if (c[1]) t +=
            c[1]->query(x1,x2,y1,y2,M+1,R);
        return t;
    }
};

```

7.4.4 Merge-Sort Tree

```

/**
 * Description: Similar to 2D segtree, less
 * memory
 * For more complex queries use a customized
 * treap
 * Verification:
 * http://codeforces.com/contest/785/submission/3395
 */

```

```

template<int SZ> struct mstree {
    Tree<pii> val[SZ+1]; // for offline
    queries use vector with binary search
    instead

    void upd(int x, int y, int t = 1) { //
        x-coordinate between 1 and SZ inclusive
        for (int X = x; X <= SZ; X += X&-X) {
            if (t == 1) val[X].insert({y,x});
            else val[X].erase({y,x});
        }
    }

    int query(int x, int y) {
        int t = 0;
        for (;x > 0; x -= x&-x) t +=
            val[x].order_of_key({y,MOD});
        return t;
    }

    int query(int lox, int hix, int loy, int
        hiy) { // query number of elements
        within a rectangle
        return query(hix,hiy)-query(lox-1,hiy)
            -query(hix,loy-1)+query(lox-1,loy-1);
    }
};

```

7.5 BBST (4)

7.5.1 Link-Cut Tree (5)

```

/**
 * Source: Dhruv Rohatgi
 * Usage: USACO Camp - The Applicant
 */

template<int SZ> struct LCT {
    int p[SZ], pp[SZ], c[SZ][2], sum[SZ];

    LCT () {
        FOR(i,1,SZ) sum[i] = 1;
    }

```

```

        memset(p,0,sizeof p);
        memset(pp,0,sizeof pp);
        memset(c,0,sizeof c);
    }

    int getDir(int x, int y) {
        return c[x][0] == y ? 0 : 1;
    }

    void setLink(int x, int y, int d) {
        c[x][d] = y, p[y] = x;
    }

    void rotate(int y, int d) {
        int x = c[y][d], z = p[y];
        setLink(y,c[x][d^1],d);
        setLink(x,y,d^1);
        setLink(z,x,getDir(z,y));

        sum[x] = sum[y];
        sum[y] = sum[c[y][0]]+sum[c[y][1]]+1;
        pp[x] = pp[y]; pp[y] = 0;
    }

    void splay(int x) {
        while (p[x]) {
            int y = p[x], z = p[y];
            int dy = getDir(y,x), dz =
                getDir(z,y);
            if (!z) rotate(y,dy);
            else if (dy == dz) rotate(z,dz),
                rotate(y,dy);
            else rotate(y,dy), rotate(z,dz);
        }
    }

    void dis(int v, int d) {
        p[c[v][d]] = 0, pp[c[v][d]] = v;
        sum[v] -= sum[c[v][d]];
        c[v][d] = 0;
    }

    void con(int v, int d) {
        c[pp[v]][d] = v;
        sum[pp[v]] += sum[v];
    }

```

```

        p[v] = pp[v], pp[v] = 0;
    }

    void access(int v) {
        // v is brought to the root of
        auxiliary tree
        // modify preferred paths

        splay(v);
        dis(v,1);

        while (pp[v]) {
            int w = pp[v]; splay(w);
            dis(w,1), con(v,1);
            splay(v);
        }
    }

    int find_root(int v) {
        access(v);
        while (c[v][0]) v = c[v][0];
        access(v);
        return v;
    }

    int find_depth(int v) {
        access(v);
        return sum[c[v][0]];
    }

    void cut(int v) {
        // cut link between v and par[v]
        access(v);
        pp[c[v][0]] = p[c[v][0]] = 0; // fix
        sum[v] -= sum[c[v][0]];
        c[v][0] = 0;
    }

    void link(int v, int w) {
        // v, which is root of another tree,
        is now child of w
        access(v), access(w);
        pp[w] = v; con(w,0);
    }

```

```

int anc(int v, int num) {
    if (find_depth(v) < num) return 0;
    access(v);
    v = c[v][0];

    while (1) {
        if (sum[c[v][1]] >= num) v =
            c[v][1];
        else if (sum[c[v][1]]+1 == num)
            return v;
        else num -= (sum[c[v][1]]+1), v =
            c[v][0];
    }

    void print(int x) {
        FOR(i,1,x+1) cout << i << " " <<
            find_root(i) << " " <<
            find_depth(i) << " " << anc(i,2)
            << "\n";
        cout << "\n";
    }
};

LCT<100001> L;

int main() {
    L.link(2,1); L.link(3,1); L.link(4,1);
    L.link(5,4);
    L.link(10,4); L.link(7,6); L.link(8,7);
    L.link(9,8);
    L.print(10);

    L.cut(4); L.link(4,8);
    L.print(10);
}

```

7.5.2 Splay Tree (5)

```

/*
* Description: Based off treap code
* Source:
https://sites.google.com/site/kc97ble/container/splay-tree/splaytree-cpp-3

```

```

* Verification:
http://www.spoj.com/problems/ORDERSET/
*/

struct snode {
    int val, sz;
    snode *p, *c[2];

    snode(int v) {
        val = v, sz = 1;
        c[0] = c[1] = p = NULL;
    }

    void inOrder(bool f = 0) {
        if (c[0]) c[0]->inOrder();
        cout << val << " ";
        if (c[1]) c[1]->inOrder();
        if (f) cout << "\n-----\n";
    }

    void recalc() {
        sz =
            1+(c[0]?c[0]->sz:0)+(c[1]?c[1]->sz:0);
    }
};

void setLink(snode* x, snode* y, int d) {
    if (x) x->c[d] = y, x->recalc();
    if (y) y->p = x;
}

snode* unLink(snode* x, int d) {
    snode* y = x->c[d];
    x->c[d] = NULL; x->recalc();
    if (y) y->p = NULL;
    return y;
}

int getDir(snode* x, snode* y) {
    if (!x) return -1;
    return x->c[0] == y ? 0 : 1;
}

void rot(snode* x, int d) {
    snode *y = x->c[d], *z = x->p;

```

```

    setLink(x, y->c[d^1], d);
    setLink(y, x, d^1);
    setLink(z, y, getDir(z, x));
}

snode* splay(snode* x) {
    while (x && x->p) {
        snode* y = x->p, *z = y->p;
        int dy = getDir(y, x), dz = getDir(z, y);
        if (!z) rot(y, dy);
        else if (dy == dz) rot(z, dz), rot(y, dy);
        else rot(y, dy), rot(z, dz);
    }
    return x;
}

snode* find(snode *cur, int v) {
    if (!cur) return cur;
    snode* x;
    if (cur->val >= v) x = find(cur->c[0], v);
    else x = find(cur->c[1], v);
    return x?x:cur;
}

snode* getmx(snode* x) {
    return x->c[1]?getmx(x->c[1]):x;
}

pair<snode*,snode*> split(snode* x, int v) {
    if (!x) return {x,x};
    snode* y = find(x,v); y = splay(y);
    if (y->val >= v) return {unLink(y,0),y};
    else return {y,unLink(y,1)};
}

snode* find_by_order(snode* x, int v) {
    int tmp = x->c[0]?x->c[0]->sz:0;
    if (v < tmp) return
        find_by_order(x->c[0], v);
    else if (v == tmp) return x;
    else return find_by_order(x->c[1], v-tmp-1);
}

```



```

pair<snode*,snode*> split_by_order(snode* x,
    int v) { // left subtree has v elements
    if (!x) return {x,x};
    if (v == x->sz) return {x,NULL};
    snode* y = find_by_order(x,v); y =
        splay(y);
    return {unLink(y,0),y};
}

snode* merge(snode* x, snode* y) {
    if (!x) return y;
    x = splay(getmx(x));
    setLink(x,y,1);
    return x;
}

// same as treap

snode* ins(snode* x, int v) { // insert value
    v
    auto a = split(x,v);
    auto b = split(a.s,v+1);
    return merge(a.f,merge(new snode(v),b.s));
}

snode* del(snode* x, int v) { // delete all
    values equal to v
    auto a = split(x,v), b = split(a.s,v+1);
    return merge(a.f,b.s);
}

snode* root;

int order_of_key(int x) {
    auto a = split(root,x);
    int t = a.f?a.f->sz:0;
    root = merge(a.f,a.s);
    return t;
}

int find_by_order(int x) {
    auto a = split_by_order(root,x);
    auto b = split_by_order(a.f,x-1);
    int t = b.s->val;
    root = merge(merge(b.f,b.s),a.s);
}

```

```

    return t;
}

7.5.3 Treap

/*
 * Sources: various
 * Description: Easiest BBST
 * Verification:
 *   http://www.spoj.com/problems/ORDERSET/
 */

struct tnode {
    int val, pri, sz;
    tnode *c[2];

    tnode (int v) {
        val = v, sz = 1, pri =
            rand()+(rand()<<15);
        c[0] = c[1] = NULL;
    }

    void inOrder(bool f = 0) {
        if (c[0]) c[0]->inOrder();
        cout << val << " ";
        if (c[1]) c[1]->inOrder();
        if (f) cout << "\n-----\n";
    }

    void recalc() {
        sz =
            1+(c[0]?c[0]->sz:0)+(c[1]?c[1]->sz:0);
    }
};

pair<tnode*,tnode*> split(tnode* t, int v) {
    // >= v goes to the right
    if (!t) return {t,t};

    if (v <= t->val) {
        auto p = split(t->c[0], v);
        t->c[0] = p.s; t->recalc();
        return {p.f, t};
    }
}

```

```

    } else {
        auto p = split(t->c[1], v);
        t->c[1] = p.f; t->recalc();
        return {t, p.s};
    }
}

pair<tnode*,tnode*> split_by_order(tnode* t,
    int v) {
    if (!t) return {t,t};
    int tmp = t->c[0]?t->c[0]->sz:0;
    if (v <= tmp) {
        auto p = split_by_order(t->c[0], v);
        t->c[0] = p.s; t->recalc();
        return {p.f, t};
    } else {
        auto p = split_by_order(t->c[1],
            v-tmp-1);
        t->c[1] = p.f; t->recalc();
        return {t, p.s};
    }
}

tnode* merge(tnode* l, tnode* r) {
    if (!l) return r;
    if (!r) return l;

    if (l->pri > r->pri) {
        l->c[1] = merge(l->c[1],r);
        l->recalc();
        return l;
    } else {
        r->c[0] = merge(l,r->c[0]);
        r->recalc();
        return r;
    }
}

tnode* ins(tnode* x, int v) { // insert value
    v
    auto a = split(x,v);
    auto b = split(a.s,v+1);
    return merge(a.f,merge(new tnode(v),b.s));
}

```

```

tnode* del(tnode* x, int v) { // delete all
    values equal to v
    auto a = split(x,v), b = split(a.s,v+1);
    return merge(a.f,b.s);
}

tnode *root;

int order_of_key(int x) {
    auto a = split(root,x);
    int t = a.f?a.f->sz:0;
    root = merge(a.f,a.s);
    return t;
}

int find_by_order(int x) {
    auto a = split_by_order(root,x);
    auto b = split_by_order(a.f,x-1);
    int t = b.s->val;
    root = merge(merge(b.f,b.s),a.s);
    return t;
}

```

7.6 Persistent Queries (5)

7.6.1 Basic Persistent SegTree

```

/**
 * Description: persistent segtree node
 *              without lazy updates
 * Verification: Codeforces Problem 893F -
 *              Subtree Minimum Query
 * Implementation:
 *              http://codeforces.com/contest/893/submission/32652140
 */

struct Node {
    int val = 0;
    Node* c[2];

    Node* copy() {
        Node* x = new Node(); *x = *this;
        return x;
    }
}

```

```

}

int query(int low, int high, int L, int R)
{
    if (low <= L && R <= high) return val;
    if (R < low || high < L) return MOD;
    int M = (L+R)/2;
    return min(c[0]->query(low,high,L,M),
               c[1]->query(low,high,M+1,R));
}

Node* upd(int ind, int v, int L, int R) {
    if (R < ind || ind < L) return this;
    Node* x = copy();

    if (ind <= L && R <= ind) {
        x->val += v;
        return x;
    }

    int M = (L+R)/2;
    x->c[0] = x->c[0]->upd(ind,v,L,M);
    x->c[1] = x->c[1]->upd(ind,v,M+1,R);
    x->val =
        min(x->c[0]->val,x->c[1]->val);

    return x;
}

void build(vi& arr, int L, int R) {
    if (L == R) {
        if (L < (int)arr.size()) val =
            arr[L];
        else val = 0;
        return;
    }
    int M = (L+R)/2;
    c[0] = new Node();
    c[0]->build(arr,L,M);
    c[1] = new Node();
    c[1]->build(arr,M+1,R);
    val = min(c[0]->val,c[1]->val);
}
};

```

```

template<int SZ> struct pers {
    Node* loc[SZ+1]; // stores location of
                     // root after ith update
    int nex = 1;

    pers() { loc[0] = new Node(); }

    void upd(int ind, int val) {
        loc[nex] =
            loc[nex-1]->upd(ind,val,0,SZ-1);
        nex++;
    }

    void build(vi& arr) {
        loc[0]->build(arr,0,SZ-1);
    }

    int query(int ti, int low, int high) {
        return loc[ti]->query(low,high,0,SZ-1);
    }
};

```

7.6.2 Lazy Persistent SegTree

```

/**
 * Source:
 * http://codeforces.com/blog/entry/47108?#comment-3
 * Description: Node + lazy updates
 */

struct node {
    int val = 0, lazy = 0;
    node* c[2];

    node* copy() {
        node* x = new node(); *x = *this;
        return x;
    }

    void push() {
        if (!lazy) return;
        FOR(i,2) if (c[i]) {
            c[i] = new node(*c[i]);
            c[i]->lazy += lazy;
        }
    }
}

```

```

    lazy = 0;
}

int query(int low, int high, int L, int R)
{
    if (low <= L && R <= high) return val;
    if (R < low || high < L) return MOD;
    int M = (L+R)/2;
    return
        lazy+min(c[0]->query(low,high,L,M),
                c[1]->query(low,high,M+1,R));
}

node* upd(int low, int high, int v, int L,
    int R) {
    if (R < low || high < L) return this;
    node* x = copy();
    if (low <= L && R <= high) {
        x->lazy += v, x->val += v;
        return x;
    }
    push();

    int M = (L+R)/2;
    x->c[0] = x->c[0]->upd(low,high,v,L,M);
    x->c[1] =
        x->c[1]->upd(low,high,v,M+1,R);
    x->val =
        min(x->c[0]->val,x->c[1]->val);

    return x;
}

void build(vi& arr, int L, int R) {
    if (L == R) {
        if (L < sz(arr)) val = arr[L];
        else val = 0;
        return;
    }
    int M = (L+R)/2;
    c[0] = new node();
    c[0]->build(arr,L,M);
    c[1] = new node();
    c[1]->build(arr,M+1,R);
    val = min(c[0]->val,c[1]->val);
}

```

```

    }
};

template<int SZ> struct pers {
    node* loc[SZ+1]; // stores location of
                    // root after ith update
    int nex = 1;

    pers() { loc[0] = new node(); }

    void upd(int low, int high, int val) {
        loc[nex] =
            loc[nex-1]->upd(low,high,val,0,SZ-1);
        nex++;
    }

    void build(vi& arr) {
        loc[0]->build(arr,0,SZ-1);
    }

    int query(int ti, int low, int high) {
        return loc[ti]->query(low,high,0,SZ-1);
    }
};

pers<8> p;

int main() {
    vi arr = {1,7,2,3,5,9,4,6};
    p.build(arr);

    p.upd(1,2,2); // 1 9 4 3 5 9 4 6

    FOR(i,8) {
        FOR(j,i,8) cout << p.query(1,i,j) << "
            ";
        cout << "\n";
    }
    cout << "\n";

    p.upd(4,7,5); // 1 9 4 3 10 14 9 11
    FOR(i,8) {
        FOR(j,i,8) cout << p.query(2,i,j) << "
            ";
        cout << "\n";
    }
    cout << "\n";
}

```

```

    FOR(i,8) {
        FOR(j,i,8) cout << p.query(1,i,j) << "
            ";
        cout << "\n";
    }
    cout << "\n";
}

```

7.6.3 Low-Memory Persistent Segment Tree

```

//uses about 34 MB
const int MAXN = 100100;
int N = 100000;
struct Node {
    ll val;
} SEG[20*MAXN];
int e = 0;
int LFT[20*MAXN], RGT[20*MAXN];

int roots[MAXN];

int build(int l = 0, int r = N - 1) {
    //build from L to R inclusive.
    int x = ++e;
    if (l == r){
        SEG[x].val = 0;
        LFT[x] = -1;
        RGT[x] = -1;
        return x;
    }
    int mid = (l + r)/2;
    LFT[x] = build(l, mid);
    RGT[x] = build(mid + 1, r);
    return x;
}

int upd(int cur, int pos, int set, int l = 0,
    int r = N - 1) {
    //set a[pos] = set in the root cur
    if (r < pos || pos < l) return cur;
    int x = ++e;
}

```

```

//we're creating a new node
if (l == r){
    SEG[x].val = set;
    return x;
}
int m = (l+r)/2;
LFT[x] = upd(LFT[cur], pos, set, l, m);
RGT[x] = upd(RGT[cur], pos, set, m +
    1, r);
SEG[x].val = SEG[LFT[x]].val +
    SEG[RGT[x]].val;
return x;
}

ll query(int cur, int L, int R, int l = 0,
    int r = N - 1){
    if (r < L || R < l) return 0LL;
    int m = (l + r)/2;
    if (L <= l && r <= R) return
        SEG[cur].val;
    return query(LFT[cur], L, R, l, m) +
        query(RGT[cur], L, R, m + 1, r);
}

```

8 Trees (4)

8.1 Tree Diameter (5)

```

/**
 * Might not be obvious why this works!
 * Verification:
 *   http://www.spoj.com/problems/PT07Z/
 */

const int MX = 10001;

int n, dist[MX];
vi adj[MX];

void dfs(int cur, int pre) {
    for (int i: adj[cur]) if (i != pre) {
        dist[i] = dist[cur]+1;

```

```

        dfs(i,cur);
    }
}

void dfs(int cur) {
    memset(dist,0,sizeof dist);
    dfs(cur,-1);
}

int treeDiameter() {
    dfs(1);
    int bes = 0; FOR(i,1,n+1) if (dist[i] >
        dist[bes]) bes = i;
    dfs(bes); FOR(i,1,n+1) if (dist[i] >
        dist[bes]) bes = i;
    return dist[bes];
}

int main() {
    cin >> n;
    FOR(i,n-1) {
        int a, b; cin >> a >> b;
        adj[a].pb(b), adj[b].pb(a);
    }
    cout << treeDiameter();
}

```

8.2 Queries (4)

8.2.1 Heavy-Light Set

```

/**
 * Description: offline subtree queries in
 *    $O(N \log^2 N)$ 
 * Verification: January Easy 2018 - Shubham &
 *   Tree 1
 */

const int MX = 200001;

struct HeavyLightSet {
    int loc[MX], sub[MX], par[MX], val[MX];
    vi child[MX];

```

```

    map<int,int> dat[MX];

    void comb(int a, int b) {
        int A = loc[a], B = loc[b];
        if (sz(dat[A]) < sz(dat[B]))
            swap(a,b), swap(A,B);
        for (auto& x: dat[B]) dat[A][x.f] +=
            x.s;
        dat[B].clear(); loc[b] = A;
    }

    void process(int ind) {
        sub[ind] = 1; loc[ind] = ind;
        dat[ind][val[ind]] ++;
        for (int i: child[ind]) {
            process(i);
            comb(i,ind);
            sub[ind] += sub[i];
        }
        // now do stuff with values
    }
};

```

8.2.2 LCA Demo

```

/**
 * Debug the Bugs
 * Description: Use for both LCA's
 */

LCA L;

int Q;

int main() {
    cin >> L.V >> Q >> L.R;
    FOR(i,L.V-1) {
        int u,v; cin >> u >> v;
        L.addEdge(u,v);
    }
    L.construct();

    FOR(i,Q) {

```

```

    int u,v; cin >> u >> v;
    cout << L.lca(u,v) << "\n";
}
}

```

8.2.3 LCA with Binary Jumps

```

/**
 * Source: USACO Camp
 * Verification: Debug the Bugs
 */

const int MAXN = 100001, MAXK = 17;

struct LCA {
    int V, R;
    vi edges[MAXN];
    int parK[MAXK][MAXN];
    int depth[MAXN];

    void addEdge(int u, int v) {
        edges[u].pb(v), edges[v].pb(u);
    }

    void dfs(int u, int prev){
        parK[0][u] = prev;
        depth[u] = depth[prev]+1;
        for (int v: edges[u]) if (v != prev)
            dfs(v, u);
    }

    void construct() {
        dfs(R, 0);
        FOR(k,1,MAXK) FOR(i,1,V+1)
            parK[k][i] =
                parK[k-1][parK[k-1][i]];
    }

    int lca(int u, int v){
        if (depth[u] < depth[v]) swap(u,v);

        FORd(k,MAXK) if (depth[u] >=
            depth[v]+(1<<k)) u = parK[k][u];

```

```

        FORd(k,MAXK) if (parK[k][u] !=
            parK[k][v]) u = parK[k][u], v =
            parK[k][v];

        if(u != v) u = parK[0][u], v =
            parK[0][v];
        return u;
    }

    int dist(int u, int v) {
        return
            depth[u]+depth[v]-2*depth[lca(u,v)];
    }
};

```

8.3 Advanced (4)

8.3.1 Centroid Decomposition

```

/**
 * Source: own
 * Verification Problem: Ciel and Commander
 *   (http://codeforces.com/contest/321/problem/C)
 * Code:
 *   http://codeforces.com/contest/321/submission/33952270
 */

const int MX = 100001;

int N, visit[MX], sub[MX], par[MX];
vi adj[MX];

void dfs (int no) {
    sub[no] = 1;
    for (int i: adj[no]) if (!visit[i] && i !=
        par[no]) {
        par[i] = no;
        dfs(i);
        sub[no] += sub[i];
    }
}

int get_centroid(int x) {

```

```

    par[x] = 0;
    dfs(x);
    int sz = sub[x];
    while (1) {
        pii mx = {0,0};
        for (int i: adj[x]) if (!visit[i] && i
            != par[x]) mx = max(mx,{sub[i],i});
        if (mx.f*2 > sz) x = mx.s;
        else return x;
    }
}

void solve (int x) {
    x = get_centroid(x); visit[x] = 1;
    // do stuff
    cout << x << "\n";
    for (int i: adj[x]) if (!visit[i])
        solve(i);
}

int main() {
    cin >> N;
    FOR(i,N-1) {
        int a,b; cin >> a >> b;
        adj[a].pb(b), adj[b].pb(a);
    }
    solve(1);
}

```

8.3.2 Heavy-Light Decomposition

```

/**
 * Source:
 *   http://codeforces.com/blog/entry/22072
 * Dependency: Lazy SegTree
 * Verification: USACO Grass Planting
 */

vector<vi> graph;

template <int V> struct HeavyLight { // sum
    queries, sum updates
    int parent[V], heavy[V], depth[V];

```

```

int root[V], treePos[V];
LazySegTree<V> tree;

void init() {
    int n = graph.size();
    FOR(i,1,n+1) heavy[i] = -1;
    parent[1] = -1, depth[1] = 0;
    dfs(1);
    for (int i = 1, currentPos = 0; i <=
        n; ++i)
        if (parent[i] == -1 ||
            heavy[parent[i]] != i)
            for (int j = i; j != -1;
                j = heavy[j]) {
                root[j] = i;
                treePos[j] =
                    currentPos++;
            }
}

int dfs(int v) {
    int size = 1, maxSubtree = 0;
    for (auto u : graph[v]) if (u !=
        parent[v]) {
        parent[u] = v;
        depth[u] = depth[v] + 1;
        int subtree = dfs(u);
        if (subtree > maxSubtree) heavy[v]
            = u, maxSubtree = subtree;
        size += subtree;
    }
    return size;
}

template <class BinaryOperation>
void processPath(int u, int v,
    BinaryOperation op) {
    for (; root[u] != root[v]; v =
        parent[root[v]]) {
        if (depth[root[u]] >
            depth[root[v]]) swap(u, v);
        op(treePos[root[v]], treePos[v]);
    }
    if (depth[u] > depth[v]) swap(u, v);

```

```

        op(treePos[u]+1, treePos[v]); //
            assumes values are stored in
            edges, not vertices
    }

    void modifyPath(int u, int v, int value) {
        processPath(u, v, [this, &value](int
            l, int r) { tree.upd(l, r, value);
        });
    }

    ll queryPath(int u, int v) {
        ll res = 0;
        processPath(u, v, [this, &res](int l,
            int r) { res += tree.qsum(l, r);
        });
        return res;
    }
};

HeavyLight<1<<17> H;
int N,M;

int main() {
    cin >> N >> M;
    graph.resize(N+1);
    FOR(i,N-1) {
        int a,b; cin >> a >> b;
        graph[a].pb(b), graph[b].pb(a);
    }
    H.init();
    FOR(i,M) {
        char c; int A,B;
        cin >> c >> A >> B;
        if (c == 'P') H.modifyPath(A,B,1);
        else cout << H.queryPath(A,B) <<
            "\n";
    }
}

```

9 Math (4)

9.1 Number Theory

9.1.1 CRT (5)

```

/**
 * Source: Own
 * Verification:
 *   * Kattis generalchineseremainder
 *   * POI 9 Rhyme
 */

typedef pair<ll,ll> pll;

struct CRT {
    ll n,m,a,b;
    map<ll,pii> M;
    bool bad;

    ll inv(ll a, ll b) { // 0 < a < b,
        gcd(a,b) = 1
        a %= b;
        if (a <= 1) return a;
        ll i = inv(b%a,a);
        ll tmp = -((b/a)*i+((b%a)*i)/a) % b;
        while (tmp < 0) tmp += b;
        return tmp;
    }

    ll naive(ll n, ll m, ll a, ll b) {
        ll x = (a-b)*inv(m,n) % n;
        ll ans = (m*x+b) % (m*n);
        while (ans < 0) ans += (m*n);
        return ans;
    }

    void process(ll a, ll n) {
        vector<pii> z;
        for (int i = 2; i*i <= n; ++i) if (n %
            i == 0) {
            int co = 0;
            while (n % i == 0) n /= i, co++;
            z.pb({i,co});
        }
    }
}

```

```

    }
    if (n != 1) z.pb({n,1});
    for (auto A: z) {
        if (M.count(A.f)) {
            pii p1 = M[A.f];
            pii p2 =
                {A.s,a%(1l)pow(A.f,A.s)};
            if (p1 > p2) swap(p1,p2);
            if (p2.s%(1l)pow(A.f,p1.f) !=
                p1.s) bad = 1;
            M[A.f] = p2;
        } else M[A.f] =
            {A.s,a%(1l)pow(A.f,A.s)};
    }
}

ll po(ll b, ll p) {
    ll z = 1;
    FOR(i,p) z *= b;
    return z;
}

pll solve(ll aa, ll nn, ll bb, ll mm) {
    bad = 0, M.clear();
    a = aa, n = nn, b = bb, m = mm;
    process(a,n), process(b,m);
    if (bad) {
        cout << "NIE";
        exit(0);
    }
    ll a1 = 0, a2 = 1;
    for (auto& x: M) {
        a1 =
            naive(a2,po(x.f,x.s.f),a1,x.s.s);
        a2 *= po(x.f,x.s.f);
    }
    return {a1,a2};
}
};

```

9.1.2 Eratosthenes' Sieve

```
/**
```

```

* Source: KACTL?
* https://open.kattis.com/problems/primesieve
*/

template<int SZ> struct Sieve {
    bitset<SZ+1> comp;
    Sieve() {
        for (int i = 2; i*i <= SZ; ++i) if
            (!comp[i]) {
                for (int j = i*i; j <= SZ; j += i)
                    comp[j] = 1;
            }
    }
    bool isprime(int x) {
        if (x == 1) return 0;
        return !comp[x];
    }
};

```

9.1.3 Phi

```

/**
 * Observation: number of operations needed
 * s.t.
 *
 *         phi(phi(...phi(n)...))=1
 * is O(log n).
 * Euler's theorem:  $a^{\phi(p)} \equiv 1 \pmod{p}$ , gcd(a,p)=1
 * Verification: CF Power Tower
 */

int phi(int x) {
    if (x == 1) return 1;
    int X = x;

    vi pri;
    for (int i = 2; i*i <= x; ++i) if (x % i
        == 0) {
            while (x % i == 0) x /= i;
            pri.pb(i);
        }

    if (x > 1) pri.pb(x);

```

```

    for (int i: pri) { X /= i; X *= i-1; }
    return X;
}

```

9.2 Combinatorics (5)

9.2.1 Combo Basic

```

/**
 * Source: Own
 * MOD is a large prime
 */

template<int SZ> struct Combo {
    ll fac[SZ+1], ifac[SZ+1];

    Combo() {
        fac[0] = ifac[0] = 1;
        FOR(i,1,SZ+1) {
            fac[i] = i*fac[i-1] % MOD;
            ifac[i] = inv(fac[i]);
        }
    }

    ll po (ll b, ll p) {
        return
            !p?1:po(b*b%MOD,p/2)*(p&1?b:1)%MOD;
    }

    ll inv (ll b) { return po(b,MOD-2); }

    ll comb(ll a, ll b) {
        if (a < b) return 0;
        ll tmp = fac[a]*ifac[b] % MOD;
        tmp = tmp*ifac[a-b] % MOD;
        return tmp;
    }
};

```

9.2.2 Combo Plus

```

/**
 * Description: Extends combo to a power of a
 *             prime
 * Verification:
 *             https://dmoj.ca/problem/tle17c4p5
 */

typedef pair<ll,ll> pll;

template<int SZ> struct ComboExtended {
    pll fac[SZ+1], ifac[SZ+1], mod;
    ll MOD = 1;

    void init(pll _mod) { // prime, power
        mod = _mod; FOR(i,mod.s) MOD *= mod.f;

        fac[0] = ifac[0] = {1,0};
        FOR(i,1,SZ+1) {
            fac[i] = fac[i-1];
            int I = i, z = 0;
            while (I % mod.f == 0) I /= mod.f,
                z++;
            fac[i].f = fac[i].f*I%MOD; fac[i].s
                += z;
            ifac[i] =
                {inv(fac[i].f,MOD),fac[i].s};
        }
    }

    ll inv(ll a, ll b) { // 0 < a < b,
        gcd(a,b) = 1
        a %= b;
        if (a <= 1) return a;
        ll i = inv(b%a,a);
        ll tmp = -((b/a)*i+((b%a)*i)/a) % b;
        while (tmp < 0) tmp += b;
        return tmp;
    }

    ll comb(ll a, ll b) {
        if (a < b) return 0;
        ll tmp =
            (fac[a].f*ifac[b].f%MOD)*ifac[a-b].f
            % MOD;
        ll z = fac[a].s-fac[b].s-fac[a-b].s;

```

```

        if (z >= mod.s) return 0;
        FOR(i,z) tmp = tmp*mod.f % MOD;
        return tmp;
    }
};

```

9.3 Matrices

9.3.1 Gaussian Elimination (6)

```

/**
 * Description: Gaussian Elimination
 * Usage:
 *             https://open.kattis.com/problems/equationsolverplus
 */

typedef long double ld;
typedef vector<vector<ld>> mat;

ld EPS = 1e-10;
int n;

void elim(mat& a, int i, int j, int k) {
    ld t = a[k][i];
    FOR(ind,n+1) a[k][ind] -= t*a[j][ind];
}

void prin(mat& a) {
    FOR(i,n) {
        FOR(j,n+1) cout << a[i][j] << " ";
        cout << "\n";
    }
    cout << "----\n";
}

void solve() {
    mat a(n); FOR(i,n) a[i].resize(n+1);
    FOR(i,n) FOR(j,n) cin >> a[i][j];
    FOR(i,n) cin >> a[i][n];
    int done[n]; FOR(i,n) done[i] = -1;

    FOR(i,n) {

```

```

        FOR(j,n) if (done[j] == -1 &&
            abs(a[j][i]) > EPS) {
            ld t = a[j][i];
            FOR(k,n+1) a[j][k] /= t;

            FOR(k,n) if (j != k) elim(a,i,j,k);
            done[j] = i; break;
        }
    }

    int num = 0;
    FOR(i,n) if (done[i] == -1) {
        num++;
        if (abs(a[i][n]) > EPS) {
            cout << "inconsistent\n";
            return;
        }
    }
    ld ans[n]; FOR(i,n) ans[i] =
        numeric_limits<double>::max();
    FOR(i,n) if (done[i] != -1) {
        bool bad = 0;
        FOR(j,n) if (j != done[i] &&
            abs(a[i][j]) > EPS) {
            bad = 1;
            break;
        }
        if (!bad) ans[done[i]] = a[i][n];
    }
    FOR(i,n) {
        if (ans[i] !=
            numeric_limits<double>::max())
            cout << ans[i];
        else cout << "?";
        cout << " ";
    }
    cout << "\n";
}

```

9.3.2 Matrix Exponentiation

```

/**
 * Source: KACTL

```



```

* Verification:
  https://dmoj.ca/problem/si17c1p5
*/

template<int SZ> struct mat {
    array<array<ll,SZ>,SZ> d;

    mat() {
        FOR(i,SZ) FOR(j,SZ) d[i][j] = 0;
    }

    mat operator+(const mat& m) {
        mat<SZ> a;
        FOR(i,SZ) FOR(j,SZ) a.d[i][j] =
            (d[i][j]+m.d[i][j]) % MOD;
        return a;
    }

    mat operator*(const mat& m) {
        mat<SZ> a;
        FOR(i,SZ) FOR(j,SZ) FOR(k,SZ)
            a.d[i][k] =
                (a.d[i][k]+d[i][j]*m.d[j][k])
                % MOD;
        return a;
    }

    mat operator^(ll p) {
        mat<SZ> a, b(*this);
        FOR(i,SZ) a.d[i][i] = 1;

        while (p) {
            if (p&1) a = a*b;
            b = b*b;
            p /= 2;
        }

        return a;
    }

    void print() {
        FOR(i,SZ) {
            FOR(j,SZ) cout << d[i][j] << " ";
            cout << "\n";
        }
    }
}

```

```

        cout << "-----\n";
    }
};

/*
mat<2> x; x.d[0][0] = 1, x.d[1][0] = 2,
x.d[1][1] = 1, x.d[0][1] = 3;
mat<2> y = x*x;
mat<2> z = x^5;
x.print(), y.print(), z.print();
*/

```

9.4 FFT

9.4.1 And Convolution

```

/**
 * Description: Similar to FWHT
 * Source: CSA - FFT And Variations
 */

typedef vector<double> vd;
typedef vector<ll> vl;

int get(int s) {
    return s > 1 ? 32 - __builtin_clz(s - 1) :
        0;
}

namespace andConv {
    vd andConv(vd P, bool inv = 0) {
        for (int len = 1; 2 * len <= sz(P);
            len <= 1) {
            for (int i = 0; i < sz(P); i += 2 *
                len) {
                for (int j = 0; j < len; j++) {
                    double u = P[i + j];
                    double v = P[i + len + j];

                    if (!inv) {
                        P[i + j] = u + v;
                        P[i + len + j] = u - v;
                    } else {

```

```

                        P[i + j] = -u + v;
                        P[i + len + j] = u;
                    }
                }
            }
        }

        return P;
    }
}

vd conv(vd a, vd b) {
    int s = max(sz(a),sz(b)), L = get(s),
        n = 1<<L;
    if (s <= 0) return {};

    a.resize(n); a = andConv(a);
    b.resize(n); b = andConv(b);

    FOR(i,n) a[i] = a[i]*b[i];
    a = andConv(a,1);
    return a;
}

vd orConv(vd a, vd b) {
    int s = max(sz(a),sz(b)), L = get(s),
        n = 1<<L;
    if (s <= 0) return {};

    a.resize(n); reverse(all(a)); a =
        andConv(a);
    b.resize(n); reverse(all(b)); b =
        andConv(b);

    FOR(i,n) a[i] = a[i]*b[i];
    a = andConv(a,1);
    reverse(all(a));

    return a;
}

vl orConv(vl a, vl b) {
    vd A; for (ll x: a) A.pb(x);
    vd B; for (ll x: b) B.pb(x);
    vd c = orConv(A,B);
    vl C; for (double x: c) C.pb(round(x));
}

```

```

    return C;
}

vl conv(vl a, vl b) {
    vd A; for (ll x: a) A.pb(x);
    vd B; for (ll x: b) B.pb(x);
    vd c = conv(A,B);
    vl C; for (double x: c) C.pb(round(x));
    return C;
}
}

```

9.4.2 Base Conversion

```

/**
 * Description: NTT Application
 * Usage: 2017 VT HSPC - Alien Codebreaking
 */

// NTT template

struct Base {
    vl po10[21];
    const int base = 27;

    Base() {
        po10[0] = {10};
        FOR(i,1,21) {
            po10[i] =
                NTT::conv(po10[i-1],po10[i-1]);
            normalize(po10[i]);
        }
    }

    void normalize(vl& x) {
        FOR(i,sz(x)) if (x[i] >= base) {
            if (i == sz(x)-1) x.pb(0);
            x[i+1] += x[i]/base;
            x[i] %= base;
        }
        while (sz(x) && !x.back())
            x.pop_back();
    }
}

```

```

vl convert(vl in) {
    if (sz(in) == 1) return in;
    vl l =
        convert(vl(in.begin(),in.begin()+sz(in)/2));
    vl r =
        convert(vl(in.begin()+sz(in)/2,in.end()));

    r = NTT::conv(r,po10[get(sz(in))-1]);
    normalize(r);

    int z = max(sz(l),sz(r));
    r.resize(z);
    FOR(i,sz(l)) r[i] += l[i];
    normalize(r);
    return r;
}

};

Base B;

int main() {
    FOR(i,10) FOR(j,10) FOR(k,10) {
        vl z = {k,j,i};
        vl o = B.transform(z);
        for (ll x: o) cout << x << " ";
        cout << "\n";
    }
}

```

9.4.3 FFT

```

/**
 * Sources: KACTL,
 *           https://pastebin.com/3Tnj5mRu
 * Verification: SPOJ polymul
 */

typedef complex<double> cd;
typedef vector<cd> vcd;
typedef vector<ll> vl;

int get(int s) {

```

```

    return s > 1 ? 32 - __builtin_clz(s - 1) :
        0;
}

namespace FFT {
    vcd fft(vcd& a) {
        int n = a.size(), x = get(n);
        vcd res, RES(n), roots(n);
        FOR(i,n) roots[i] =
            cd(cos(2*M_PI*i/n),sin(2*M_PI*i/n));

        res = a;
        FOR(i,1,x+1) {
            int inc = n>>i;
            FOR(j,inc) for (int k = 0; k < n; k
                += inc) {
                int t = 2*k%n+j;
                RES[k+j] =
                    res[t]+roots[k]*res[t+inc];
            }
            swap(res,RES);
        }

        return res;
    }

    vcd fft_rev(vcd& a) {
        vcd res = fft(a);
        FOR(i,sz(res)) res[i] /= a.size();
        reverse(res.begin() + 1, res.end());
        return res;
    }

    vcd brute(vcd& a, vcd& b) {
        vcd c(sz(a)+sz(b)-1);
        FOR(i,sz(a)) FOR(j,sz(b)) c[i+j] +=
            a[i]*b[j];
        return c;
    }

    vcd conv(vcd a, vcd b) {
        int s = sz(a)+sz(b)-1, L = get(s), n =
            1<<L;
        if (s <= 0) return {};
        if (s <= 200) return brute(a,b);

```

```

    a.resize(n); a = fft(a);
    b.resize(n); b = fft(b);

    FOR(i,n) a[i] *= b[i];
    a = fft_rev(a);

    a.resize(s);
    return a;
}

vl convll(vl a, vl b) {
    vcd A(sz(a)); FOR(i,sz(a)) A[i] = a[i];
    vcd B(sz(b)); FOR(i,sz(b)) B[i] = b[i];
    vcd X = conv(A,B);
    vl x(sz(X)); FOR(i,sz(X)) x[i] =
        round(X[i].real());
    return x;
}

int main() {
    int T; cin >> T;
    FOR(i,T) {
        int N; cin >> N;
        vl a(N+1), b(N+1);
        FOR(j,N+1) cin >> a[N-j];
        FOR(j,N+1) cin >> b[N-j];
        vl x = FFT::convll(a,b);
        FORd(j,sz(x)) cout << x[j] << " ";
        cout << "\n";
    }
}

```

9.4.4 NTT

```

/**
 * Description: Use if you are working with
 *              non-negative integers
 * Verification:
 *              http://codeforces.com/contest/632/submission/33953285
 */

```

```

typedef vector<ll> vl;

int get(int s) {
    return s > 1 ? 32 - __builtin_clz(s - 1) :
        0;
}

namespace NTT {
    const ll mod = (119 << 23) + 1, root = 3;
    // = 998244353
    // For p < 2^30 there is also e.g. (5 <<
    // 25, 3), (7 << 26, 3),
    // (479 << 21, 3) and (483 << 21, 5). The
    // last two are > 10^9.

    ll modpow(ll b, ll p) { return
        !p?1:modpow(b*b%mod,p/2)*(p&1?b:1)%mod;
    }

    ll inv (ll b) { return modpow(b,mod-2); }

    vl ntt(vl& a) {
        int n = a.size(), x = get(n);
        vl res, RES(n), roots(n);
        roots[0] = 1, roots[1] =
            modpow(root, (mod-1)/n);
        FOR(i,2,n) roots[i] =
            roots[i-1]*roots[1] % mod;

        res = a;
        FOR(i,1,x+1) {
            int inc = n>>i;
            FOR(j,inc) for (int k = 0; k < n; k
                += inc) {
                int t = 2*k%n+j;
                RES[k+j] =
                    (res[t]+roots[k]*res[t+inc])
                    % mod;
            }
            swap(res,RES);
        }

        return res;
    }
}

```

```

vl ntt_rev(vl& a) {
    vl res = ntt(a);
    ll in = inv(a.size());
    FOR(i,sz(res)) res[i] = res[i]*in %
        mod;
    reverse(res.begin() + 1, res.end());
    return res;
}

vl brute(vl& a, vl& b) {
    vl c(sz(a)+sz(b)-1);
    FOR(i,sz(a)) FOR(j,sz(b)) c[i+j] =
        (c[i+j]+a[i]*b[j])%mod;
    return c;
}

vl conv(vl a, vl b) {
    int s = sz(a)+sz(b)-1, L = get(s), n =
        1<<L;
    if (s <= 0) return {};
    if (s <= 200) return brute(a,b);

    a.resize(n); a = ntt(a);
    b.resize(n); b = ntt(b);

    FOR(i,n) a[i] = a[i]*b[i] % mod;
    a = ntt_rev(a);

    a.resize(s);
    return a;
}

int main() {
    vl X = NTT::conv({1,2,3,4,5,6,7,8},
        {1,2,3,4,5,6,7,8});
    for (auto a: X) cout << a << "\n";
}

```

9.4.5 XOR Convolution

```

/**
 * Description: FWHT, similar to FFT

```

```

* Source:
https://csacademy.com/blog/fast-fourier-transform-and-variations-of-it
* Verification:
https://www.hackerrank.com/challenges/xor-subsequence/problem
*/

typedef vector<double> vd;
typedef vector<ll> vl;

int get(int s) {
    return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
}

namespace FWHT {
    vd fwht(vd P) {
        for (int len = 1; 2 * len <= sz(P);
             len <= 1) {
            for (int i = 0; i < sz(P); i += 2 * len) {
                for (int j = 0; j < len; j++) {
                    double u = P[i + j];
                    double v = P[i + len + j];
                    P[i + j] = u+v;
                    P[i + len + j] = u-v;
                }
            }
        }

        return P;
    }

    vd fwht_rev(vd& a) {
        vd res = fwht(a);
        FOR(i,sz(res)) res[i] /= a.size();
        return res;
    }

    vd conv(vd a, vd b) {
        int s = max(sz(a),sz(b)), L = get(s),
            n = 1<<L;
        if (s <= 0) return {};
        a.resize(n); a = fwht(a);

```

```

        b.resize(n); b = fwht(b);
        FOR(i,n) a[i] = a[i]*b[i];
        a = fwht_rev(a);
        return a;
    }

    vl conv(vl a, vl b) {
        vd A; for (ll x: a) A.pb(x);
        vd B; for (ll x: b) B.pb(x);
        vd c = conv(A,B);
        vl C; for (double x: c) C.pb(round(x));
        return C;
    }
}

```

10 Graphs Hard (4)

10.1 Kosaraju

```

/**
 * Source: Wikipedia
 * Description: generates SCC in topological
                order, support for 2-SAT
 * Verification: POI 8 peaceful commission
 */

int rev(int x) {
    return x&1?x+1:x-1;
}

template<int SZ> struct scc {
    vi adj[SZ], radj[SZ], todo, allComp;
    int N, comp[SZ];
    bitset<SZ> visit;

    void dfs(int v) {
        visit[v] = 1;
        for (int w: adj[v]) if (!visit[w])
            dfs(w);
        todo.pb(v);
    }
}

```

```

void dfs2(int v, int val) {
    comp[v] = val;
    for (int w: radj[v]) if (!comp[w])
        dfs2(w,val);
}

void addEdge(int a, int b) {
    adj[a].pb(b), radj[b].pb(a);
}

void genSCC() {
    FOR(i,1,N+1) comp[i] = visit[i] = 0;
    FOR(i,1,N+1) if (!visit[i]) dfs(i);
    reverse(all(todo)); // toposort
    for (int i: todo) if (!comp[i]) {
        dfs2(i,i);
        allComp.pb(i);
    }
}

int tmp[SZ];
bitset<SZ> ans;

bool twosat() {
    for (int i = 1; i <= N; i += 2) if
        (comp[i] == comp[rev(i)]) return 0;
    reverse(all(allComp));
    for (int i: allComp) if (tmp[i] == 0) {
        tmp[i] = 1;
        tmp[comp[rev(i)]] = -1;
    }
    FOR(i,1,N+1) if (tmp[comp[i]] == 1)
        ans[i] = 1;
    return 1;
}
};

```

10.2 Euler Tour (6)

```

/**
 * Description: extra log factor

```

```

* Usage:
https://open.kattis.com/problems/eulerianpath
*/

vi circuit;
multiset<int> adj[10000], adj1[10000];
int N,M, out[10000], in[10000];

void find_circuit(int x) { // directed graph,
    possible that resulting circuit is not
    valid
    while (adj[x].size()) {
        int j = *adj[x].begin();
        adj[x].erase(adj[x].begin());
        find_circuit(j);
    }
    circuit.pb(x);
}

int a,b,start;

void solve() {
    FOR(i,N) {
        adj[i].clear(), adj1[i].clear();
        out[i] = in[i] = 0;
    }
    circuit.clear();
    FOR(i,M) {
        cin >> a >> b;
        adj[a].insert(b), adj1[a].insert(b);
        out[a] ++, in[b] ++;
    }
    start = a;
    FOR(i,N) if (out[i]-in[i] == 1) start = i;

    find_circuit(start);
    reverse(circuit.begin(),circuit.end());

    if (circuit.size() != M+1) {
        cout << "Impossible\n";
        return;
    }

    FOR(i,M) {

```

```

        if
            (adj1[circuit[i]].find(circuit[i+1])
             == adj1[circuit[i]].end()) {
                cout << "Impossible\n";
                return;
            }
            int t = circuit[i];
            adj1[t].erase(adj1[t].find(circuit[i+1]));
        }
        FOR(i,M+1) cout << circuit[i] << " ";
        cout << "\n";
    }
}

```

10.3 Flows

10.3.1 Dinic (5)

```

/**
 * Source: GeeksForGeeks
 * Verification: Problem Fashion (RMI 2017 Day
 * 1)
 * Code: https://pastebin.com/VJxTvEg1
 */

struct Edge {
    int v;
    ll flow, C;
    int rev;
};

template<int SZ> struct Dinic {
    int level[SZ], start[SZ];
    vector<Edge> adj[SZ];

    void addEdge(int u, int v, int C) {
        Edge a{v, 0, C, sz(adj[v])};
        Edge b{u, 0, 0, sz(adj[u])};
        adj[u].pb(a), adj[v].pb(b);
    }

    bool BFS(int s, int t) {
        FOR(i,SZ) level[i] = -1;
        level[s] = 0;

```

```

        queue<int> q; q.push(s);
        while (!q.empty()) {
            int u = q.front(); q.pop();
            for (auto e: adj[u])
                if (level[e.v] < 0 && e.flow <
                    e.C) {
                    level[e.v] = level[u] + 1;
                    q.push(e.v);
                }
        }

        return level[t] >= 0;
    }

    ll sendFlow(int u, ll flow, int t) {
        if (u == t) return flow;

        for ( ; start[u] < sz(adj[u]);
              start[u] ++ ) {
            Edge &e = adj[u][start[u]];

            if (level[e.v] == level[u]+1 &&
                e.flow < e.C) {
                ll curr_flow = min(flow, e.C -
                                     e.flow);
                ll temp_flow = sendFlow(e.v,
                                         curr_flow, t);

                if (temp_flow > 0) {
                    e.flow += temp_flow;
                    adj[e.v][e.rev].flow -=
                        temp_flow;
                    return temp_flow;
                }
            }
        }

        return 0;
    }

    ll maxFlow(int s, int t) {
        if (s == t) return -1;
        ll total = 0;

```

```

while (BFS(s, t)) {
    FOR(i,SZ) start[i] = 0;
    while (ll flow = sendFlow(s,
        INT_MAX, t)) total += flow;
}

return total;
}
};

```

10.3.2 Flows Demo

```

/**
 * Link: http://www.spoj.com/problems/FASTFLOW/
 * Use with Dinic, Push-Relabel
 */

int N,M;
PushRelabel<5001> D;

int main() {
    cin >> N >> M;
    FOR(i,M) {
        int a,b,c; cin >> a >> b >> c;
        D.addEdge(a,b,c);
        D.addEdge(b,a,c);
    }
    cout << D.maxFlow(1,N);
}

```

10.3.3 MinCostFlow (6)

```

/**
 * Source: GeeksForGeeks
 */

struct Edge {
    int v, flow, C, rev, cost;
};

template<int SZ> struct mcf {

```

```

    pii pre[SZ];
    int cost[SZ], num[SZ], SC, SNC;
    ll flo, ans, ccost;
    vector<Edge> adj[SZ];

    void addEdge(int u, int v, int C, int
        cost) {
        Edge a{v, 0, C, sz(adj[v]), cost};
        Edge b{u, 0, 0, sz(adj[u]), -cost};
        adj[u].pb(a), adj[v].pb(b);
    }

    void reweight() {
        FOR(i,SZ) {
            for (auto& p: adj[i]) p.cost +=
                cost[i]-cost[p.v];
        }
    }

    bool spfa() {
        FOR(i,SZ) cost[i] = MOD, num[i] = 0;
        cost[SC] = 0, num[SC] = MOD;
        priority_queue<pii,vector<pii>,greater<pii>>
            todo; todo.push({0,SC});

        while (todo.size()) {
            pii x = todo.top(); todo.pop();
            if (x.f > cost[x.s]) continue;
            for (auto a: adj[x.s]) if
                (x.f+a.cost < cost[a.v] &&
                 a.flow < a.C) {
                pre[a.v] = {x.s,a.rev};
                cost[a.v] = x.f+a.cost;
                num[a.v] =
                    min(a.C-a.flow,num[x.s]);
                todo.push({cost[a.v],a.v});
            }
        }

        ccost += cost[SNC];
        return num[SNC] > 0;
    }

    void backtrack() {

```

```

        flo += num[SNC], ans +=
            (ll)num[SNC]*ccost;
        for (int x = SNC; x != SC; x =
            pre[x].f) {
            adj[x][pre[x].s].flow -= num[SNC];
            int t = adj[x][pre[x].s].rev;
            adj[pre[x].f][t].flow += num[SNC];
        }
    }

    pii mincostflow(int sc, int snc) {
        SC = sc, SNC = snc;
        flo = ans = ccost = 0;

        spfa();
        while (1) {
            reweight();
            if (!spfa()) return {flo,ans};
            backtrack();
        }
    }
};

mcf<100> m;

int main() {
    m.addEdge(0, 1, 16, 5);
    m.addEdge(1, 2, 13, 7);
    m.addEdge(1, 2, 13, 8);

    pii x = m.mincostflow(0,2);
    cout << x.f << " " << x.s;
}

```

10.3.4 Push-Relabel (5)

```

/**
 * Source:
 * http://codeforces.com/blog/entry/14378
 * Verification: SPOJ fastflow
 */

struct Edge {

```

```

int v;
ll flow, C;
int rev;
};

template <int SZ> struct PushRelabel {
    vector<Edge> adj[SZ];
    ll excess[SZ];
    int dist[SZ], count[SZ+1], b = 0;
    bool active[SZ];
    vi B[SZ];

    void addEdge(int u, int v, int C) {
        Edge a{v, 0, C, sz(adj[v])};
        Edge b{u, 0, 0, sz(adj[u])};
        adj[u].pb(a), adj[v].pb(b);
    }

    void enqueue (int v) {
        if (!active[v] && excess[v] > 0 &&
            dist[v] < SZ) {
            active[v] = 1;
            B[dist[v]].pb(v);
            b = max(b, dist[v]);
        }
    }

    void push (int v, Edge &e) {
        ll amt = min(excess[v], e.C-e.flow);
        if (dist[v] == dist[e.v]+1 && amt > 0)
        {
            e.flow += amt, adj[e.v][e.rev].flow
                -= amt;
            excess[e.v] += amt, excess[v] -=
                amt;
            enqueue(e.v);
        }
    }

    void gap (int k) {
        FOR(v,SZ) if (dist[v] >= k) {
            count[dist[v]] --;
            dist[v] = SZ;
            count[dist[v]] ++;
            enqueue(v);

```

```

        }
    }

    void relabel (int v) {
        count[dist[v]] --; dist[v] = SZ;
        for (auto e: adj[v]) if (e.C > e.flow)
            dist[v] = min(dist[v], dist[e.v] +
                1);
        count[dist[v]] ++;
        enqueue(v);
    }

    void discharge(int v) {
        for (auto &e: adj[v]) {
            if (excess[v] > 0) push(v,e);
            else break;
        }
        if (excess[v] > 0) {
            if (count[dist[v]] == 1)
                gap(dist[v]);
            else relabel(v);
        }
    }

    ll maxFlow (int s, int t) {
        for (auto &e: adj[s]) excess[s] += e.C;

        count[0] = SZ;
        enqueue(s); active[t] = 1;

        while (b >= 0) {
            if (sz(B[b])) {
                int v = B[b].back();
                B[b].pop_back();
                active[v] = 0; discharge(v);
            } else b--;
        }
        return excess[t];
    }
};

```

10.4 Tarjan BCC

```

/**
 * Source:
 *   http://www.geeksforgeeks.org/biconnected-component
 * Some corrections!
 * Verification: USACO December 2017, Push a
 *   Box
 * Code: https://pastebin.com/yUWuzTH8
 */

template<int SZ> struct BCC {
    int N, ti = 0;
    vi adj[SZ];
    int disc[SZ], low[SZ], comp[SZ], par[SZ];
    vector<vector<pii>> fin;
    vector<pii> st;

    void addEdge(int u, int v) {
        adj[u].pb(v), adj[v].pb(u);
    }

    void BCCutil(int u) {
        disc[u] = low[u] = ti++;
        int child = 0;

        for (int i: adj[u]) if (i != par[u]) {
            if (disc[i] == -1) {
                child ++; par[i] = u;
                st.pb({u,i});
                BCCutil(i);
                low[u] = min(low[u],low[i]);

                if ((disc[u] == 0 && child > 1)
                    || (disc[u] != 0 && disc[u]
                        <= low[i])) { //
                    articulation point!
                    vector<pii> tmp;
                    while (st.back() !=
                        mp(u,i))
                        tmp.pb(st.back()),
                            st.pop_back();
                    tmp.pb(st.back()),
                        st.pop_back();
                    fin.pb(tmp);
                }
            } else if (disc[i] < disc[u]) {

```

```

        low[u] = min(low[u],disc[i]);
        st.pb({u,i});
    }
}

void bcc() {
    FOR(i,1,N+1) par[i] = disc[i] = low[i]
        = -1;
    FOR(i,1,N+1) if (disc[i] == -1) {
        BCCutil(i);
        if (sz(st)) fin.pb(st);
        st.clear();
    }
}
};

```

11 Geometry (4)

11.1 Techniques

11.1.1 3D Geometry (6)

```

/**
 * Description: Basic 3D Geometry
 * Usage: AMPPZ 2011 Cross Spider
 */

typedef vector<ll> vl;

typedef long double ld;

int n;
vector<vl> cur;

vl operator-(vl a, vl b) {
    vl c(sz(a)); FOR(i,sz(a)) c[i] = a[i]-b[i];
    return c;
}

bool ismult(vl b, vl c) {

```

```

    if ((ld)b[0]*c[1] != (ld)b[1]*c[0]) return
        0;
    if ((ld)b[0]*c[2] != (ld)b[2]*c[0]) return
        0;
    if ((ld)b[2]*c[1] != (ld)b[1]*c[2]) return
        0;
    return 1;
}

bool collinear(vl a, vl b, vl c) {
    b = b-a, c = c-a;
    return ismult(b,c);
}

vl cross(vl a, vl b) {
    return {a[1]*b[2]-a[2]*b[1],
            a[2]*b[0]-a[0]*b[2],
            a[0]*b[1]-a[1]*b[0]};
}

bool coplanar(vl a, vl b, vl c, vl d) {
    b = b-a, c = c-a, d = d-a;
    return ismult(cross(b,c),cross(b,d));
}

```

11.1.2 Circles

```

/**
 * Source: Own
 * Usage:
 *   https://codefights.com/tournaments/s8thqrnQL2YPK7XQt/L
 */

typedef complex<double> cd;
typedef pair<cd,double> circle;

cd intersect(circle a, circle b, int x = 0) {
    double d = sqrt(norm(a.f-b.f));
    double co =
        (a.s*a.s+d*d-b.s*b.s)/(2*a.s*d);
    double theta = acos(co);

    cd tmp = (b.f-a.f)/d;

```

```

    if (x == 0) return
        a.f+tmp*a.s*polar(1.0,theta);
    return a.f+tmp*a.s*polar(1.0,-theta);
}

double arc(circle x, cd a, cd b) {
    cd d = (a-x.f)/(b-x.f);
    return x.s*acos(d.real());
}

bool on (circle x, cd y) {
    return norm(y-x.f) == x.s*x.s;
}

int main() {
    cout << intersect({0,2},{1,1}) << "\n";
    cout << arc({0,1},cd(1,0),cd(0,1)) << "\n";
    cout << on({0,1},1) << "\n";
}

```

11.1.3 Line Segment Intersection (5)

```

/**
 * Source:
 *   https://open.kattis.com/problems/segmentintersect
 * If numbers are small enough, fractions are
 * recommended.
 */

typedef pair<double,double> pdd;
pii A,B,C,D;

pdd operator*(int x, pdd y) {
    return {x*y.f,x*y.s};
}

pdd operator/(pdd y, int x) {
    return {y.f/x,y.s/x};
}

pdd operator+(pdd l, pdd r) {
    return {l.f+r.f,l.s+r.s};
}

```



```

}

int sgn(pii a, pii b, pii c) {
    return
        (b.s-a.s)*(c.f-a.f)-(b.f-a.f)*(c.s-a.s);
}

pdd get(pii a, pii b, pii c, pii d) {
    return
        (abs(sgn(a,b,c))*d+abs(sgn(a,b,d))*c)
        /(abs(sgn(a,b,c))+abs(sgn(a,b,d)));
}

void solve() {
    cin >> A.f >> A.s >> B.f >> B.s >> C.f >>
        C.s >> D.f >> D.s;
    if (A > B) swap(A,B);
    if (C > D) swap(C,D);
    int a1 = sgn(A,B,C), a2 = sgn(A,B,D);
    if (a1 > a2) swap(a1,a2);
    if (!(a1 <= 0 && a2 >= 0)) {
        cout << "none\n";
        return;
    }
    if (a1 == 0 && a2 == 0) {
        if (sgn(A,C,D) != 0) {
            cout << "none\n";
            return;
        }
        pii x1 = max(A,C), x2 = min(B,D);
        if (x1 > x2) cout << "none\n";
        else if (x1 == x2) cout <<
            (double)x1.f << " " <<
            (double)x1.s << "\n";
        else cout << (double)x1.f << " " <<
            (double)x1.s << " " <<
            (double)x2.f << " " <<
            (double)x2.s << "\n";
        return;
    }
    pdd z = get(A,B,C,D);
    if (mp((double)A.f,(double)A.s) <= z && z
        <= mp((double)B.f,(double)B.s)) cout
        << z.f << " " << z.s << "\n";
    else cout << "none\n";
}

```

```

}

int main() {
    int n; cin >> n;
    cout << fixed << setprecision(2);
    FOR(i,n) solve();
}



---


11.1.4 Pair Operators



---


/**
 * Source: own
 */

template<class T> pair<T,T> operator+(const
    pair<T,T>& l, const pair<T,T>& r) {
    return {l.f+r.f,l.s+r.s};
}

template<class T> pair<T,T> operator-(const
    pair<T,T>& l, const pair<T,T>& r) {
    return {l.f-r.f,l.s-r.s};
}

template<class T> pair<T,T> operator*(const
    pair<T,T>& l, T r) {
    return {l.f*r,l.s*r};
}

template<class T> pair<T,T> operator/(const
    pair<T,T>& l, T r) {
    return {l.f/r,l.s/r};
}

template<class T> double mag(pair<T,T> p) {
    return sqrt(p.f*p.f+p.s*p.s);
}

template<class T> pair<T,T> operator*(const
    pair<T,T>& l, const pair<T,T>& r) {
    // l.f+l.s*i, r.f+r.s*i
    return {l.f*r.f-l.s*r.s,l.s*r.f+l.f*r.s};
}

```

```

template<class T> pair<T,T> operator/(const
    pair<T,T>& l, const pair<T,T>& r) {
    // l.f+l.s*i, r.f+r.s*i
    pair<T,T> z =
        {r.f/(r.f*r.f+r.s*r.s),-r.s/(r.f*r.f+r.s*r.s)};
    return l*z;
}

template<class T> double area(pair<T,T> a,
    pair<T,T> b, pair<T,T> c) {
    b = b-a, c = c-a;
    return (b.f*c.s-b.s*c.f)/2;
}

template<class T> double dist(pair<T,T> l,
    pair<T,T> r) {
    return mag(r-l);
}

template<class T> double dist(pair<T,T> o,
    pair<T,T> x, pair<T,T> d) { // signed
    distance
    return 2*area(o,x,x+d)/mag(d);
}

```

11.1.5 Point in Polygon (5)

```

/**
 * Source: own
 * Usage:
 *   https://open.kattis.com/problems/pointinpolygon
 */

int n,m;
pii p[1000];

int area(pii x, pii y, pii z) {
    return
        (y.f-x.f)*(z.s-x.s)-(y.s-x.s)*(z.f-x.f);
}

bool on(pii x, pii y, pii z) {

```

```

    if (area(x,y,z) != 0) return 0;
    return min(x,y) <= z && z <= max(x,y);
}

double get(pii x, pii y, int z) {
    return
        double((z-x.s)*y.f+(y.s-z)*x.f)/(y.s-x.s);
}

void test(pii z) {
    int ans = 0;
    FOR(i,n) {
        pii x = p[i], y = p[(i+1)%n];
        if (on(x,y,z)) {
            cout << "on\n";
            return;
        }
        if (x.s > y.s) swap(x,y);
        if (x.s <= z.s && y.s > z.s) {
            double t = get(x,y,z.s);
            if (t > z.f) ans++;
        }
    }
    if (ans % 2 == 1) cout << "in\n";
    else cout << "out\n";
}

void solve() {
    FOR(i,n) cin >> p[i].f >> p[i].s;
    cin >> m;
    FOR(i,m) {
        pii z; cin >> z.f >> z.s;
        test(z);
    }
}

```

11.1.6 Polygon Area

```

/**
 * Description: Shoelace Formula
 * Usage:
 *   https://open.kattis.com/problems/polygonarea
 */

```

```

double area(vector<pii> v) {
    double x = 0;
    FOR(i,sz(v)) {
        int j = (i+1)%sz(v);
        x += (ll)v[i].f*v[j].s;
        x -= (ll)v[j].f*v[i].s;
    }
    return abs(x)/2;
}

```

11.2 Sweep Line

11.2.1 Closest Pair (6)

```

/**
 * Source: GeeksForGeeks
 * Description: Nlog^2N, can be improved
 * Use:
 *   https://open.kattis.com/problems/closestpair2
 */

pair<double,pair<pdd,pdd>> MN =
    {INF,{0,0},{0,0}};

int n;

bool cmp(pdd a, pdd b) {
    return a.s < b.s;
}

double dist(pdd a, pdd b) {
    b.f -= a.f, b.s -= a.s;
    return sqrt(b.f*b.f+b.s*b.s);
}

```

```

pair<double,pair<pdd,pdd>> strip(vector<pdd>
    v, double di) {
    pair<double,pair<pdd,pdd>> ans = MN;
    FOR(i,v.size()) FOR(j,i+1,v.size()) {
        if (v[i].s+di <= v[j].s) break;
        ans =
            min(ans,{dist(v[i],v[j]),{v[i],v[j]}});
    }
}

```

```

    }
    return ans;
}

pair<double,pair<pdd,pdd>> bes (vector<pdd>
    v) {
    if (v.size() == 1) return MN;
    int M = v.size()/2;
    vector<pdd> v1(v.begin(),v.begin()+M),
        v2(v.begin()+M,v.end());
    auto a = bes(v1), b = bes(v2);
    double di = min(a.f,b.f);

    vector<pdd> V;
    FOR(i,v.size()) if (v[i].f > v[M].f-di &&
        v[i].f < v[M].f+di) V.pb(v[i]);
    sort(V.begin(),V.end(),cmp);

    auto z = strip(V,di);
    return min(min(a,b),z);
}

int main() {
    cout << fixed << setprecision(2);
    while (cin >> n) {
        if (n == 0) break;
        vector<pdd> v(n);
        FOR(i,n) cin >> v[i].f >> v[i].s;
        sort(v.begin(),v.end());
        auto a = bes(v);
        cout << a.s.f.f << " " << a.s.f.s
            << " " << a.s.s.f << " " <<
            a.s.s.s << "\n";
    }
}

```

11.2.2 Convex Hull

```

/**
 * Source: Wikibooks
 * Usage:
 *   https://open.kattis.com/problems/convexhull
 */

```

```

11 cross(pii O, pii A, pii B) {
    return
        (11)(A.f-O.f)*(B.s-O.s)-(11)(A.s-O.s)*(B.f-O.f)}
}

vector<pii> convex_hull(vector<pii> P) {
    sort(P.begin(),P.end());
    P.erase(unique(P.begin(),P.end()),P.end());
    if (P.size() == 1) return P;

    int n = P.size();

    vector<pii> bot = {P[0]};
    FOR(i,1,n) {
        while (bot.size() > 1 &&
            cross(bot[bot.size()-2],
                bot.back(), P[i]) <= 0)
            bot.pop_back();
        bot.pb(P[i]);
    }
    bot.pop_back();

    vector<pii> up = {P[n-1]};
    FORd(i,n-1) {
        while (up.size() > 1 &&
            cross(up[up.size()-2], up.back(),
                P[i]) <= 0) up.pop_back();
        up.pb(P[i]);
    }
    up.pop_back();

    bot.insert(bot.end(),all(up));
    return bot;
}

int main() {
    int n;
    while (cin >> n) {
        if (n == 0) break;
        vector<pii> P(n); FOR(i,n) cin >>
            P[i].f >> P[i].s;
        vector<pii> hull = convex_hull(P);

        cout << hull.size() << "\n";
    }
}

```

```

        for (auto a: hull) cout << a.f << " "
            << a.s << "\n";
    }
}

11.3 Max Collinear

/**
 * Source: own
 * Usage:
 *   https://open.kattis.com/problems/maxcollinear
 */

int n, mx, ans;
map<pair<pii,int>,int> m;
pii p[1000];

pair<pii,int> getline(pii a, pii b) {
    pii z = {b.f-a.f,b.s-a.s};
    swap(z.f,z.s); z.f *= -1;
    int g = __gcd(z.f,z.s); z.f /= g, z.s /= g;
    if (z.f < 0 || (z.f == 0 && z.s < 0)) z.f
        *= -1, z.s *= -1;
    return {z,z.f*a.f+z.s*a.s};
}

void solve() {
    mx = ans = 0; m.clear();
    FOR(i,n) cin >> p[i].f >> p[i].s;
    FOR(i,n) FOR(j,i+1,n)
        m[getline(p[i],p[j])] ++;

    for (auto a: m) mx = max(mx,a.s);
    FOR(i,1,n+1) if (i*(i-1)/2 <= mx) ans = i;
    cout << ans << "\n";
}

```

12 Strings (3)

12.1 Bitset Trie (4)

```

/**
 * Source: Algorithms Gym
 * Verification: January Easy 2018 - Shubham
 *   and Subarray Xor
 */

template<int MX> struct tri {
    int nex = 0, ans = 0;
    int trie[MX][2]; // easily changed to
        character

    tri() {
        memset(trie,0,sizeof trie);
    }

    void ins(int x) {
        int cur = 0;
        FORd(i,30) {
            int t = (x&(1<<i))>>i;
            if (!trie[cur][t]) trie[cur][t] =
                ++nex;
            cur = trie[cur][t];
        }

    void test(int x) {
        int cur = 0;
        FORd(i,30) {
            int t = ((x&(1<<i))>>i) ^ 1;
            if (!trie[cur][t]) t ^= 1;
            cur = trie[cur][t];
            if (t) x ^= (1<<i);
        }
        ans = max(ans,x);
    }
};

```

12.2 Hashing

```

/**
 * Source: own

```

```

* Description: Pairs reduce frequency of
  collision
* Verification: Dec 17 Plat 1
*/

typedef pair<ll, ll> pll;

template<class T> pair<T,T> operator+(const
pair<T,T>& l, const pair<T,T>& r) {
  return {(l.f+r.f)%MOD, (l.s+r.s)%MOD};
}

template<class T> pair<T,T> operator-(const
pair<T,T>& l, const pair<T,T>& r) {
  return
    {(l.f-r.f+MOD)%MOD, (l.s-r.s+MOD)%MOD};
}

template<class T> pair<T,T> operator*(const
pair<T,T>& l, const T& r) {
  return {l.f*r%MOD, l.s*r%MOD};
}

template<class T> pair<T,T> operator*(const
pair<T,T>& l, const pair<T,T>& r) {
  return {l.f*r.f%MOD, l.s*r.s%MOD};
}

struct hsh {
  string S;
  vector<pll> po, ipo, cum;
  pll base = mp(948392576, 573928192);

  ll modpow(ll b, ll p) {
    return
      !p?1:modpow(b*b%MOD, p/2)*(p&1?b:1)%MOD;
  }

  ll inv(ll x) {
    return modpow(x, MOD-2);
  }

  void gen(string _S) {
    S = _S;

```

```

    po.resize(sz(S)), ipo.resize(sz(S)),
      cum.resize(sz(S)+1);
    po[0] = ipo[0] = {1,1};
    FOR(i,1,sz(S)) {
      po[i] = po[i-1]*base;
      ipo[i] =
        {inv(po[i].f), inv(po[i].s)};
    }
    FOR(i,sz(S)) cum[i+1] =
      cum[i]+po[i]*(ll)(S[i]-'a'+1);
  }

  pll get(int l, int r) {
    return ipo[l]*(cum[r+1]-cum[l]);
  }
};

int lcp(hsh& a, hsh& b) { // can be used to
  generate a suffix array
  int lo = 0, hi = min(sz(a.S), sz(b.S));
  while (lo < hi) {
    int mid = (lo+hi+1)/2;
    if (a.get(0, mid-1) == b.get(0, mid-1))
      lo = mid;
    else hi = mid-1;
  }
  return lo;
}

int main() {
  string _S = "abacaba";
  hsh h; h.gen(_S);
  FOR(i,sz(_S)) FOR(j,i,sz(_S)) cout << i <<
    " " << j << " " << h.get(i,j).f << " "
    << h.get(i,j).s << "\n";

  hsh H; H.gen("abadaba");
  cout << lcp(h,H);
}

```

12.3 Z (4)

12.3.1 Aho-Corasick

```

/**
 * Source: https://ideone.com/0cMjZJ
 * Usage:
 *   https://open.kattis.com/problems/stringmultimatc
 */

template<int SZ> struct Aho {
  int link[SZ], dict[SZ], sz = 1, num = 0;
  vector<pii> ind[SZ];
  map<char,int> to[SZ];
  vi oc[SZ];
  queue<int> q;

  Aho() {
    memset(link,0,sizeof link);
    memset(dict,0,sizeof dict);
  }

  void add(string s) {
    int v = 0;
    for(auto c: s) {
      if (!to[v].count(c)) to[v][c] =
        sz++;
      v = to[v][c];
    }
    dict[v] = v; ind[v].pb({++num, sz(s)});
  }

  void push_links() {
    link[0] = -1; q.push(0);
    while (sz(q)) {
      int v = q.front(); q.pop();
      for (auto it: to[v]) {
        char c = it.f; int u = it.s, j
          = link[v];
        while (j != -1 &&
          !to[j].count(c)) j =
          link[j];
        if (j != -1) {
          link[u] = to[j][c];
          if (!dict[u]) dict[u] =
            dict[link[u]];
        }
        q.push(u);
      }
    }
  }
};

```

```

    }
}

void process(int pos, int cur) {
    cur = dict[cur];
    while (cur) {
        for (auto a: ind[cur])
            oc[a.f].pb(pos-a.s+1);
        cur = dict[link[cur]];
    }
}

int nex(int pos, int cur, char c) {
    while (cur != -1 && !to[cur].count(c))
        cur = link[cur];
    if (cur == -1) cur = 0;
    else cur = to[cur][c];
    process(pos, cur);
    return cur;
}

};

Aho<100001> A;

int n;

void solve() {
    A = Aho<100001>();
    cin >> n;
    FOR(i,n) {
        string pat; getline(cin,pat); if (!i)
            getline(cin,pat);
        A.add(pat);
    }
    A.push_links();

    string t; getline(cin,t);
    int cur = 0;
    FOR(i,sz(t)) cur = A.nex(i,cur,t[i]);
    FOR(i,1,n+1) {
        for (int j: A.oc[i]) cout << j << " ";
        cout << "\n";
    }
}

```

12.3.2 Manacher (5)

```

/**
 * Source:
 *   http://codeforces.com/blog/entry/12143
 * Description: Calculates length of largest
 *               palindrome centered at each character of
 *               string
 * Verification:
 *   http://www.spoj.com/problems/MSUBSTR/
 */

vi manacher(string s) {
    string s1 = "@";
    for (char c: s) s1 += c, s1 += "#";
    s1[s1.length()-1] = '&#39;#39;;

    vi ans(s1.length()-1);
    int lo = 0, hi = 0;
    FOR(i,1,s1.length()-1) {
        ans[i] = min(hi-i,ans[hi-i+lo]);
        while (s1[i-ans[i]-1] ==
                s1[i+ans[i]+1]) ans[i] ++;
        if (i+ans[i] > hi) lo = i-ans[i], hi =
            i+ans[i];
    }

    ans.erase(ans.begin());
    FOR(i,sz(ans)) if ((i&1) == (ans[i]&1))
        ans[i] ++; // adjust lengths
    return ans;
}

int main() {
    int T; cin >> T;
    FOR(i,T) {
        pii bes = {0,0};
        string s; cin >> s;
        vi t = manacher(s);
        for (int i: t) {
            if (i > bes.f) bes = {i,1};
            else if (i == bes.f) bes.s++;
        }
        cout << bes.f << " " << bes.s << "\n";
    }
}

```

```

}

```

12.3.3 Minimum Rotation

```

/**
 * Source: KACTL
 * Unused
 */

int min_rotation(string s) {
    int a=0, N=sz(s); s += s;
    FOR(b,N) FOR(i,N) {
        if (a+i == b || s[a+i] <
            s[b+i]) {b += max(0, i-1);
                    break;}
        if (s[a+i] > s[b+i]) {a = b;
                              break;}
    }
    return a;
}

```

12.3.4 Z

```

/**
 * Source:
 *   http://codeforces.com/blog/entry/3107
 * Description: similar to KMP
 * Verification: POI 12 Template
 */

vi z(string s) {
    int N = s.length(); s += '#';
    vi ans(N); ans[0] = N;
    while (s[1+ans[1]] == s[ans[1]]) ans[1] ++;

    int L = 1, R = ans[1];
    FOR(i,2,N) {
        if (i <= R) ans[i] =
            min(R-i+1,ans[i-L]);
        while (s[i+ans[i]] == s[ans[i]])
            ans[i] ++;
    }
}

```

```

        if (i+ans[i]-1 > R) L = i, R =
            i+ans[i]-1;
    }
    return ans;
}

vi get(string a, string b) { // find prefixes
    of a in b
    string s = a+"@"+b;
    vi t = z(s);
    return vi(t.begin()+a.length()+1,t.end());
}

int main() {
    vi x = z("abcababcbabcaba");
    for (int i: x) cout << i << " ";
    cout << "\n";

    x = get("abcab","uwetrabcerabcb");
    for (int i: x) cout << i << " ";
}

```

12.4 Suffix Array (4)

12.4.1 Wheeler (6)

```

/**
 * Verification:
 *   https://cses.fi/problemset/task/1113/
 */

string transform(string s) {
    vector<pair<char,int>> v;
    int nex[sz(s)];

    FOR(i,sz(s)) v.pb({s[i],i});
    sort(all(v));
    FOR(i,sz(v)) nex[i] = v[i].s;

    int cur = nex[0];
    string ret;
    while (cur != 0) {
        ret += v[cur].f;

```

```

        cur = nex[cur];
    }
    return ret;
}

```

12.4.2 Suffix Array

```

/**
 * Source: SuprDewd CP Course
 * Task:
 *   https://open.kattis.com/problems/suffixsorting
 * KACTL version is slightly faster
 * Verification: USACO December 2017: Standing
 *   out from the herd:
 *   http://usaco.org/index.php?page=viewproblem2&cpid=768
 * Code to Verify:
 *   https://pastebin.com/y2Z9FYr6
 */

struct suffix_array {
    int N;
    vector<vi> P;
    vector<array<int,3>> L;
    vi idx;
    string str;

    /*void bucket(int ind) {
        int mn = MOD, mx = -MOD;

        for (auto a: L) mn = min(mn,a[ind]),
            mx = max(mx,a[ind]);
        vector<array<int,3>> tmp[mx-mn+1];
        FORd(i,sz(L))
            tmp[L[i][ind]-mn].pb(L[i]);

        int nex = 0;
        FOR(i,mx-mn+1) for (auto a: tmp[i])
            L[nex++] = a;
    }

    void bucket_sort() {
        bucket(1), bucket(0);
    }*/

```

```

suffix_array(string _str) {
    str = _str; N = sz(str);
    P.pb(vi(N)); L.resize(N);
    FOR(i,N) P[0][i] = str[i];

    for (int stp = 1, cnt = 1; cnt < N;
        stp ++, cnt *= 2) {
        P.pb(vi(N));
        FOR(i,N) L[i] = {P[stp-1][i],i+cnt
            < N ? P[stp-1][i+cnt] : -1,i};
        sort(all(L));
        // bucket_sort();
        FOR(i,N) {
            if (i && mp(L[i][0],L[i][1]) ==
                mp(L[i-1][0],L[i-1][1]))
                P[stp][L[i][2]] =
                    P[stp][L[i-1][2]];
            else P[stp][L[i][2]] = i;
        }

        idx.resize(N);
        FOR(i,sz(P.back())) idx[P.back()[i]] =
            i;
    }

    int lcp(int x, int y) {
        int res = 0;
        if (x == y) return N-x;
        for (int k = sz(P) - 1; k >= 0 && x <
            N && y < N; k--) {
            if (P[k][x] == P[k][y]) {
                x += 1 << k;
                y += 1 << k;
                res += 1 << k;
            }
        }
        return res;
    }
};

```

13 Additional (4)

13.1 Mo (6)

```
/**
 * Source: Codeforces
 * Description: Answers queries offline in
 *             (N+Q)sqrt(N)
 * Also see Mo's on trees
 */

int block = 300; // set ~sqrt(N)

bool cmp(vi a, vi b) {
    if (a[0]/block != b[0]/block) return a[0]
        < b[0];
    return a[1] < b[1];
}
```

13.2 Misc

13.2.1 Discrete Logarithm

```
/**
 * Description: find k such that primitive^k=x
 * meet in the middle, O(sqrt(MOD))
 * Source: Own
 * Verification: PA 2006 - Professor Laugh's
 *              Numbers
 */

const int BLOCK = 32000;
```

```
int primitive = 5, invy[BLOCK];
unordered_map<int,int> u;

ll po (ll b, ll p) {
    return !p?1:po(b*b%MOD,p/2)*(p&1?b:1)%MOD;
}

ll inv (ll b) { return po(b,MOD-2); }

ll query(int x) {
    FOR(i,BLOCK) if
        (u.count(x*invy[i]%MOD))
        return i*BLOCK+u[x*invy[i]%MOD];
    return -1;
}

int main() {
    ll cur = 1;
    FOR(i,BLOCK) {
        u[cur] = i;
        cur = primitive*cur%MOD;
    }
    ll t = 1;
    FOR(i,BLOCK) {
        invy[i] = inv(t);
        t = t*cur%MOD;
    }
    ll x; cin >> x;
    cout << query(x) << "\n";
}
```

13.2.2 Pragma Optimization (6)

```
/**
```

```
 * Source: Misc solutions to CF Nagini
 * Description: 107 operations are ok!
 * Passes the occasional disgusting CF task
 * Also see "Welcome home, Chtholly"
 */

#pragma GCC optimize ("O3")
#pragma GCC target ("sse4")

// template

int q, mx[100001], mn[100001];

int main() {
    ios_base::sync_with_stdio(0);cin.tie(0);cout.tie(0);
    cin >> q;
    FOR(i,100001) mx[i] = -MOD, mn[i] = MOD;
    FOR(i,q) {
        int t,l,r,k; cin >> t >> l >> r;
        r -= l;

        auto a = mx+l, b = mn+l;
        if (t == 1) {
            cin >> k;
            if (k > 0) FOR(j,r) b[j] =
                min(b[j],k);
            else FOR(j,r) a[j] = max(a[j],k);
        } else {
            ll ans = 0;
            FOR(j,r) if (a[j] != -MOD && b[j]
                != MOD) ans += b[j]-a[j];
            cout << ans << "\n";
        }
    }
}
```
