

USACO Notebook: Complete

Benq

April 2, 2018

Contents

1	Contest	2
1.1	C++ Template	2
1.2	FastScanner	2
1.3	Troubleshooting	3
2	Sorting And Searching (2)	4
2.1	Interval Cover	4
2.2	Binary Search	4
3	Data Structures (2)	4
3.1	Set	4
3.1.1	Coordinate Compression	4
3.1.2	Map Customization	5
4	Graphs Easy (2)	5
4.1	Traversal	5
4.1.1	BFS on Grid	5
4.1.2	DFS on Graph	5
4.2	Shortest Path (3)	5
4.2.1	Bellman-Ford	5
4.2.2	Dijkstra	6
4.2.3	Floyd-Warshall	6
4.3	Topological Sort (3)	6
4.4	Kruskal (3)	7
5	Algorithm Design (2)	7
5.1	Minimum Deque (3)	7
5.2	Ternary Search (4)	7
6	Range Queries (2)	8
6.1	Static Array Queries	8
6.1.1	Prefix Sums	8
6.1.2	Range Minimum Query (3)	8
6.1.3	Wavelet Tree (6)	8
6.2	Demos (3)	9
6.2.1	Point Update Demo	9
6.2.2	2D Demo (4)	9
6.2.3	BBST Demo (4)	9
6.2.4	Range Update Demo (4)	9
6.3	1D Range Queries (3)	10
6.3.1	Binary Indexed Tree	10
6.3.2	SegTree	10
6.3.3	BIT with Range Update (4)	10

6.3.4	Lazy SegTree (4)	10
6.3.5	Sparse SegTree (4)	11
6.3.6	SegTree Beats (6)	12
6.4	2D Range Queries (4)	13
6.4.1	2D BIT	13
6.4.2	2D SegBIT	13
6.4.3	2D SegTree	13
6.4.4	Merge-Sort Tree	14
6.5	BBST (4)	14
6.5.1	Treap	14
6.5.2	Link-Cut Tree (5)	15
6.5.3	Splay Tree (5)	16
6.6	Persistent Queries (5)	17
6.6.1	Basic PST	17
6.6.2	Lazy PST	18
6.6.3	Low-Memory Basic PST	19
7	DP (3)	19
7.1	Examples	19
7.1.1	Knapsack	19
7.1.2	Longest Common Subsequence	19
7.1.3	Longest Increasing Subsequence	19
7.1.4	String Removals	20
7.1.5	Traveling Salesman (4)	20
7.2	Divide And Conquer (4)	20
8	Strings (3)	20
8.1	Hashing	20
8.2	Bitset Trie (4)	21
8.3	String Searching (4)	21
8.3.1	Aho-Corasick	21
8.3.2	Manacher	22
8.3.3	Minimum Rotation	23
8.3.4	Z	23
8.4	Suffix Array (4)	23
8.4.1	Suffix Array	23
8.4.2	Reverse Burrows-Wheeler (6)	24
8.5	Z (5)	24
8.5.1	Manacher	24
9	Trees (4)	24
9.1	Tree Diameter	24
9.2	Queries	25
9.2.1	Heavy-Light Set	25
9.2.2	LCA Demo	25
9.2.3	LCA with Binary Jumps	25
9.2.4	LCA with RMQ	26
9.3	Advanced	26
9.3.1	Centroid Decomposition	26
9.3.2	Heavy-Light Decomposition	27
10	Math (4)	27
10.1	Number Theory	27
10.1.1	Eratosthenes' Sieve	27
10.1.2	ModPow	27
10.1.3	Phi	28
10.1.4	Chinese Remainder Theorem (5)	28

10.2	Matrices	28
10.2.1	Matrix	28
10.2.2	Matrix Inverse (6)	29
10.3	Combinatorics (5)	29
10.3.1	Combo Basic	29
10.3.2	Combo Plus	30
10.4	FFT (6)	30
10.4.1	NTT	30
10.5	Polynomials (6)	31
10.5.1	And Convolution	31
10.5.2	Base Conversion	31
10.5.3	FFT	32
10.5.4	Interpolation	33
10.5.5	NTT	33
10.5.6	XOR Convolution	34
11	Graphs Hard (4)	34
11.1	Kosaraju	34
11.2	Flows	35
11.2.1	Edmonds-Karp	35
11.2.2	Flows Demo	35
11.2.3	Dinic (5)	35
11.2.4	Push-Relabel (5)	36
11.2.5	MinCostFlow (6)	37
11.3	Tarjan BCC	37
11.4	Euler Tour (6)	38
12	Geometry (4)	38
12.1	Techniques	38
12.1.1	Pair Operators	38
12.1.2	Polygon Area	39
12.1.3	Line Segment Intersection (5)	39
12.1.4	Point in Polygon (5)	40
12.1.5	3D Geometry (6)	40
12.1.6	Circles (6)	40
12.2	Sweep Line	41
12.2.1	Convex Hull	41
12.2.2	Closest Pair (6)	41
12.2.3	LineContainer (6)	42
12.3	Max Collinear	42
13	Additional (4)	42
13.1	Mo	42
13.2	Misc	43
13.2.1	Discrete Logarithm	43
13.3	Pragma Optimization (6)	43

1 Contest

1.1 C++ Template

```
#include <bits/stdc++.h>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/assoc_container.hpp>

using namespace std;
```

```
using namespace __gnu_pbds;

typedef long long ll;
typedef long double ld;
typedef complex<ld> cd;

typedef pair<int, int> pi;
typedef pair<ll,ll> pl;
typedef pair<double,double> pd;

typedef vector<int> vi;
typedef vector<ll> vl;
typedef vector<pi> vpi;

template <class T> using Tree = tree<T, null_type,
    less<T>,
    rb_tree_tag,tree_order_statistics_node_update>;

#define FOR(i, a, b) for (int i=a; i<(b); i++)
#define FOR(i, a) for (int i=0; i<(a); i++)
#define FORd(i,a,b) for (int i = (b)-1; i >= a; i--)
#define FORd(i,a) for (int i = (a)-1; i >= 0; i--)

#define sz(x) (int)(x).size()
#define mp make_pair
#define pb push_back
#define f first
#define s second
#define lb lower_bound
#define ub upper_bound
#define all(x) x.begin(), x.end()

const int MOD = 1000000007;
const ll INF = 1e18;
const int MX = 100001;

int main() {
    ios_base::sync_with_stdio(0); cin.tie(0);
}

// read the question correctly (is y a vowel?)
// look out for SPECIAL CASES (n=1?) and overflow (ll
// vs int?)
```

1.2 FastScanner

```
/**
 * Source: Matt Fontaine
 */

class FastScanner {
    private InputStream stream;
    private byte[] buf = new byte[1024];
    private int curChar;
    private int numChars;

    public FastScanner(InputStream stream) {
        this.stream = stream;
    }
}
```

```

int read() {
    if (numChars == -1)
        throw new InputMismatchException();
    if (curChar >= numChars) {
        curChar = 0;
        try {
            numChars = stream.read(buf);
        } catch (IOException e) {
            throw new InputMismatchException();
        }
        if (numChars <= 0) return -1;
    }
    return buf[curChar++];
}

boolean isSpaceChar(int c) {
    return c == ' ' || c == '\n' || c == '\r' || c
        == '\t' || c == -1;
}

boolean isEndline(int c) {
    return c == '\n' || c == '\r' || c == -1;
}

public int nextInt() {
    return Integer.parseInt(next());
}

public long nextLong() {
    return Long.parseLong(next());
}

public double nextDouble() {
    return Double.parseDouble(next());
}

public String next() {
    int c = read();
    while (isSpaceChar(c)) c = read();
    StringBuilder res = new StringBuilder();
    do {
        res.appendCodePoint(c);
        c = read();
    } while (!isSpaceChar(c));
    return res.toString();
}

public String nextLine() {
    int c = read();
    while (isEndline(c))
        c = read();
    StringBuilder res = new StringBuilder();
    do {
        res.appendCodePoint(c);
        c = read();
    } while (!isEndline(c));
    return res.toString();
}
}

```

1.3 Troubleshooting

Source: KACTL

Pre-submit:

- Write a few simple test cases, if sample is not enough.
- Are time limits close? If so, generate max cases.
- Is the memory usage fine?
- Could anything overflow?
- Make sure to submit the right file.

Wrong answer:

- Print your solution! Print debug output, as well.
 - Are you clearing all datastructures between test cases?
 - Can your algorithm handle the whole range of input?
 - Read the full problem statement again.
 - Do you handle all corner cases correctly?
 - Have you understood the problem correctly?
 - Any uninitialized variables?
 - Any overflows?
 - Confusing N and M, i and j, etc.?
 - Are you sure your algorithm works?
 - What special cases have you not thought of?
 - Are you sure the STL functions you use work as you think?
 - Add some assertions, maybe resubmit.
 - Create some testcases to run your algorithm on.
 - Go through the algorithm for a simple case.
 - Go through this list again.
 - Explain your algorithm to a team mate.
 - Ask the team mate to look at your code.
 - Go for a small walk, e.g. to the toilet.
 - Is your output format correct? (including whitespace)
 - Rewrite your solution from the start or let a team mate do it.
- Runtime error:
- Have you tested all corner cases locally?
 - Any uninitialized variables?

- Are you reading or writing outside the range of any vector?
- Any assertions that might fail?
- Any possible division by 0? (mod 0 for example)
- Any possible infinite recursion?
- Invalidated pointers or iterators?
- Are you using too much memory?
- Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:

- Do you have any possible infinite loops?
- What is the complexity of your algorithm?
- Are you copying a lot of unnecessary data? (References)
- How big is the input and output? (consider scanf)
- Avoid vector, map. (use arrays/unordered map)
- What do your team mates think about your algorithm?

Memory limit exceeded:

- What is the max amount of memory your algorithm should need?
- Are you clearing all data structures between test cases?

2 Sorting And Searching (2)

2.1 Interval Cover

```
/**
 * Usage: https://open.kattis.com/problems/intervalcover
 * Description: Example of greedy algorithm
 */

double A,B,cur;
vector<pair<pdd,int>> in;
int N,nex;
vi ans;

void solve() {
    nex = 0; ans.clear();
    cin >> N; in.resize(N);
    FOR(i,N) {
        cin >> in[i].f.f >> in[i].f.s;
        in[i].s = i;
    }

    sort(all(in));
    pair<double,int> mx = {-DBL_MAX,-1};
```

```
while (nex < in.size() && in[nex].f.f <= A) {
    mx = max(mx,{in[nex].f.s,in[nex].s});
    nex++;
}
if (nex == 0) {
    cout << "impossible\n";
    return;
}
ans.pb(mx.s);

while (mx.f < B) {
    cur = mx.f;
    while (nex < in.size() && in[nex].f.f <= cur) {
        mx = max(mx,{in[nex].f.s,in[nex].s});
        nex++;
    }
    if (mx.f == cur) {
        cout << "impossible\n";
        return;
    }
    ans.pb(mx.s);
}
cout << ans.size() << "\n";
for (int i: ans) cout << i << " ";
cout << "\n";
}
```

2.2 Binary Search

```
/**
 * Description: Basic example of binary search
 * Guess the Number
 * https://open.kattis.com/problems/guess
 */

int main() {
    int lo = 1, hi = 1000;
    while (1) {
        int mid = (lo+hi)/2;
        cout << mid << endl;
        string res; cin >> res;
        if (res == "correct") return 0;
        else if (res == "lower") hi = mid-1;
        else lo = mid+1;
    }
}
```

3 Data Structures (2)

3.1 Set

3.1.1 Coordinate Compression

```
/**
 * Description: Demonstrates use of map
 * Verification: POI 12 - The Bus
 */
```

```
void compress(vector<array<int,3>>& x, int ind) {
    map<int,int> m;
    for (auto& a: x) m[a[ind]] = 0;
    int co = 0; for (auto& a: m) a.s = co++;
    for (auto& a: x) a[ind] = m[a[ind]];
}
```

3.1.2 Map Customization

```
/**
 * Description: Define your own comparator / hash
 *              function
 * Source: StackOverflow
 */

struct cmp {
    bool operator()(const int& l, const int& r) const {
        return l > r;
    }
};

struct hsh {
    size_t operator()(const pi& k) const {
        return k.f^k.s; // bad, but you get the point
    }
};

set<int,cmp> s;
map<int,int,cmp> m;
unordered_map<pi,int,hsh> u;
```

4 Graphs Easy (2)

4.1 Traversal

4.1.1 BFS on Grid

```
/**
 * Note: Use xdir and ydir
 */

int xdir[4] = {0,1,0,-1}, ydir[4] = {1,0,-1,0};
int dist[21][21];
queue<pi> todo;

void process(pi x) {
    FOR(i,4) {
        pi y = {x.f+xdir[i],x.s+ydir[i]};
        if (y.f < 0 || y.f > 20 || y.s < 0 ||
            y.s > 20) continue; // ignore this
                                // point if it's outside of grid
        if (dist[y.f][y.s] == MOD) { // test
            whether point has been visited or
            not
            dist[y.f][y.s] = dist[x.f][x.s]+1;
            todo.push(y); // push point to queue
        }
    }
}
```

```
    }
}

int main() {
    FOR(i,21) FOR(j,21) dist[i][j] = MOD;
    dist[10][10] = 0; todo.push({10,10}); //
        initialize queue, distances
    while (todo.size()) {
        process(todo.front());
        todo.pop(); // pop point from queue
    }
    cout << dist[4][5]; // 11
}
```

4.1.2 DFS on Graph

```
/**
 * Classic
 */

int n, visit[100001];
vi adj[100001];

void dfs(int node) {
    if (visit[node]) return;
    visit[node] = 1;
    for (int i: adj[node]) dfs(i);
    cout << node << "\n";
    // do stuff
}

int main() {
    cin >> n;
    FOR(i,n-1) {
        int a,b; cin >> a >> b;
        adj[a].pb(b);
        adj[b].pb(a);
    }
    dfs(1);
}
```

4.2 Shortest Path (3)

4.2.1 Bellman-Ford

```
/**
 * Usage: https://open.kattis.com/problems/shortestpath3
 * Description: can be useful with linear programming
 * Constraints of the form  $x_i - x_j < k$ 
 */

const ll INF = 1e18;

int n,m,q,s,bad[1000];
vector<pair<pi,int>> edge;
ll dist[1000];
```

```

void solve() {
    edge.clear();
    FOR(i,n) dist[i] = INF, bad[i] = 0;
    dist[s] = 0;
    FOR(i,m) {
        int u,v,w; cin >> u >> v >> w;
        edge.pb({u,v,w});
    }
    FOR(i,n) for (auto a: edge) if (dist[a.f.f] < INF)
        dist[a.f.s] = min(dist[a.f.s],
            dist[a.f.f]+a.s);
    for (auto a: edge) if (dist[a.f.f] < INF) if
        (dist[a.f.s] > dist[a.f.f]+a.s) bad[a.f.s] = 1;
    FOR(i,n) for (auto a: edge) if (bad[a.f.f])
        bad[a.f.s] = 1;

    FOR(i,q) {
        int x; cin >> x;
        if (bad[x]) cout << "-Infinity\n";
        else if (dist[x] == INF) cout <<
            "Impossible\n";
        else cout << dist[x] << "\n";
    }
    cout << "\n";
}

```

4.2.2 Dijkstra

```

/**
 * Description: shortest path!
 * Works with negative edge weights (aka SPFA?)
 */

template<int SZ> struct Dijkstra {
    int dist[SZ];
    vector<pi> adj[SZ];
    priority_queue<pi,vector<pi>,greater<pi>> q;

    void gen() {
        fill_n(dist,SZ,MOD); dist[0] = 0;

        q.push({0,0});
        while (q.size()) {
            pi x = q.top(); q.pop();
            if (dist[x.s] < x.f) continue;
            for (pi y: adj[x.s]) if (x.f+y.s <
                dist[y.f]) {
                dist[y.f] = x.f+y.s;
                q.push({dist[y.f],y.f});
            }
        }
    }
};

```

Dijkstra<100> D;

```

int main() {
    FOR(i,100) FOR(j,100) if (rand() % 10 == 0)
        D.adj[i].pb({j,rand() % 10+1});
}

```

```

D.gen();
FOR(i,100) cout << D.dist[i] << "\n";
}

```

4.2.3 Floyd-Warshall

```

/**
 * Usage: https://open.kattis.com/problems/allpairspath
 */

const ll INF = 1e18;

int n,m,q; // vertices, edges, queries
ll dist[150][150], bad[150][150];

void solve() {
    FOR(i,n) FOR(j,n) dist[i][j] = INF, bad[i][j] = 0;
    FOR(i,n) dist[i][i] = 0;
    FOR(i,m) {
        int u,v,w; cin >> u >> v >> w;
        dist[u][v] = min(dist[u][v],(ll)w);
    }
    FOR(k,n) FOR(i,n) FOR(j,n) if (dist[i][k] != INF
        && dist[k][j] != INF)
        dist[i][j] =
            min(dist[i][j],dist[i][k]+dist[k][j]);

    FOR(k,n) FOR(i,n) FOR(j,n) if (dist[i][k] != INF
        && dist[k][j] != INF)
        if (dist[i][j] > dist[i][k]+dist[k][j])
            bad[i][j] = 1;

    FOR(k,n) FOR(i,n) FOR(j,n) {
        if (dist[i][k] < INF && bad[k][j]) bad[i][j] =
            1;
        if (bad[i][k] && dist[k][j] < INF) bad[i][j] =
            1;
    }

    FOR(i,q) {
        int u,v; cin >> u >> v;
        if (bad[u][v]) cout << "-Infinity\n";
        else if (dist[u][v] == INF) cout <<
            "Impossible\n";
        else cout << dist[u][v] << "\n";
    }
    cout << "\n";
}

```

4.3 Topological Sort (3)

```

/**
 * Description: sorts vertices such that if there
 * exists an edge x->y, then x goes before y
 */

int N,M, in[100001];
vi res, adj[100001];

```

```

void topo() {
    queue<int> todo;
    FOR(i,1,N+1) if (in[i] == 0) todo.push(i);
    while (sz(todo)) {
        int x = todo.front(); todo.pop();
        res.pb(x);
        for (int i: adj[x]) {
            in[i]--;
            if (!in[i]) todo.push(i);
        }
    }
}

int main() {
    cin >> N >> M;
    FOR(i,M) {
        int x,y; cin >> x >> y;
        adj[x].pb(y), in[y]++;
    }
    topo();
    for (int i: res) cout << i << " ";
}

```

4.4 Kruskal (3)

```

/**
 * Source: own
 * Description: computes the minimum spanning tree in
 *              O(ElogE) time
 * Verification: USACO superbull
 */

template<int SZ> struct DSU {
    int par[SZ], sz[SZ];
    DSU() {
        FOR(i,SZ) par[i] = i, sz[i] = 1;
    }

    int get(int x) { // path compression
        if (par[x] != x) par[x] = get(par[x]);
        return par[x];
    }

    bool unite(int x, int y) { // union-by-rank
        x = get(x), y = get(y);
        if (x == y) return 0;
        if (sz[x] < sz[y]) swap(x,y);
        sz[x] += sz[y], par[y] = x;
        return 1;
    }
};

int ans = 0; // total weight of MST
vector<pair<int,pi>> edge;

DSU<100> D;

void kruskal() {
    sort(all(edge));

```

```

        for (auto a: edge) if (D.unite(a.s.f,a.s.s))
            ans += a.f; // edge is in MST
    }

```

5 Algorithm Design (2)

5.1 Minimum Deque (3)

```

/**
 * Source: own
 * Verification: Jan 18 Lifeguards
 */

struct MinDeque {
    int lo = 0, hi = -1;
    deque<pi> d;

    void ins(int x) { // add to back
        while (sz(d) && d.back().f >= x) d.pop_back();
        d.pb({x,++hi});
    }

    void del() { // delete from front
        if (d.front().s == lo++) d.pop_front();
    }

    int get() {
        return sz(d) ? d.front().f : MOD;
    }
};

```

5.2 Ternary Search (4)

```

/**
 * Description: use on functions which are strictly
 *              decreasing then strictly increasing
 */

double eval(double x) {
    return (x-5)*(x-5);
}

double ternary(double l, double r) {
    if (abs(r-l) <= 1e-9) return (l+r)/2;
    double l1 = (2*l+r)/3, r1 = (l+2*r)/3;
    return eval(l1) < eval(r1) ? ternary(l,r1) :
        ternary(l1,r);
}

// ternary(-100,100) = 5

```

6 Range Queries (2)

6.1 Static Array Queries

6.1.1 Prefix Sums

```
/**
 * Description: Calculates rectangle sums in constant
 *             time
 * Verification: POI 16 Ticket Inspector
 */

template<class T, int SZ> struct sums {
    T sum[SZ][SZ];
    sums () { memset(sum,0,sizeof sum); }
    void init() {
        FOR(i,1,SZ) FOR(j,1,SZ)
            sum[i][j] += sum[i][j-1]
            +sum[i-1][j]-sum[i-1][j-1];
    }
    T get(int X1, int X2, int Y1, int Y2) {
        return sum[X2][Y2]-sum[X1-1][Y2]
            -sum[X2][Y1-1]+sum[X1-1][Y1-1];
    }
};
```

6.1.2 Range Minimum Query (3)

```
/**
 * Description: Supports 1D range minimum query in
 *             constant time.
 * Verification: Problem Tournament from IOI 2012:
 *             http://wcipeg.com/problem/ioi1223
 * Source code: https://pastebin.com/ChpniVZL
 */

template<class T, int SZ> struct RMQ {
    T stor[SZ][32-__builtin_clz(SZ)];

    T comb(T a, T b) {
        return min(a,b);
    }

    void build(vector<T>& x) {
        FOR(i,sz(x)) stor[i][0] = x[i];
        FOR(j,1,32-__builtin_clz(SZ))
            FOR(i,SZ-(1<<(j-1)))
                stor[i][j] = comb(stor[i][j-1],
                    stor[i+(1<<(j-1))][j-1]);
    }

    T query(int l, int r) {
        int x = 31-__builtin_clz(r-l+1);
        return comb(stor[l][x],stor[r-(1<<x)+1][x]);
    }
};
```

6.1.3 Wavelet Tree (6)

```
/**
 * Description: Segment tree on values instead of
 *             indices
 * Verification: http://www.spoj.com/problems/MKTHNUM/
 */

int N,Q, A[100000];
map<int,int> m;
vi revm;

void input() {
    cin >> N >> Q;
    FOR(i,N) cin >> A[i];
}

void compress() {
    FOR(i,N) m[A[i]] = 0;
    int nex = 0;
    for (auto& a: m) {
        a.s = nex++;
        revm.pb(a.f);
    }
    FOR(i,N) A[i] = m[A[i]];
}

template<int SZ> struct wavelet {
    vi mapl[2*SZ], mapr[2*SZ], val[2*SZ];

    void build(int ind = 1, int L = 0, int R = SZ-1) {
        // build a wavelet tree
        if (ind == 1) { FOR(i,N) val[ind].pb(i); }

        if (L < R) {
            int M = (L+R)/2;
            for (int i: val[ind]) {
                val[2*ind+(A[i] > M)].pb(i);
                mapl[ind].pb(sz(val[2*ind])-1);
                mapr[ind].pb(sz(val[2*ind+1])-1);
            }
            build(2*ind,L,M);
            build(2*ind+1,M+1,R);
        }
    }

    int getl(int ind, int x) { return x < 0 ? -1 :
        mapl[ind][x]; }

    int getr(int ind, int x) { return x < 0 ? -1 :
        mapr[ind][x]; }

    int query(int lind, int rind, int k, int ind = 1,
        int L = 0, int R = SZ-1) { // how many <= mid
        with index <= r
        if (L == R) return L;

        int M = (L+R)/2;
        int t = getl(ind,rind)-getl(ind,lind-1);
        if (t >= k) return query(getl(ind,lind-1)+1,
            getl(ind,rind),k,2*ind,L,M);
    }
};
```



```

        return query(getr(ind,lind-1)+1,
                    getr(ind,rind),k-t,2*ind+1,M+1,R);
    }
};

wavelet<1<<17> w;

int main() {
    input();
    compress();
    w.build();

    FOR(i,Q) {
        int l,r,k; cin >> l >> r >> k;
        cout << revm[w.query(l-1,r-1,k)] << "\n";
    }
}

```

6.2 Demos (3)

6.2.1 Point Update Demo

```

/**
 * Link: http://www.spoj.com/problems/FENTREE/
 * Description: Use with SegTree, BIT, Sparse SegTree
 */

Seg<11,1<<20> B;

int main() {
    int N; cin >> N;
    FOR(i,1,N+1) {
        int x; cin >> x;
        B.upd(i,x);
    }
    int q; cin >> q;
    FOR(i,q) {
        char c; int a, b;
        cin >> c >> a >> b;
        if (c == 'q') cout << B.query(a,b) << "\n";
        else B.upd(a,b);
    }
}

```

6.2.2 2D Demo (4)

```

/**
 * Link: http://www.spoj.com/problems/MATSUM/ (modified)
 * Description: Use with 2D BIT, 2D SegBIT, 2D SegTree
 */

int main() {
    BIT2D<int,1024> B = BIT2D<int,1024>();
    Node<int> S = Node<int>();

    FOR(i,100000) {
        int c = rand()&1;
        if (c == 0) {

```

```

            int x = rand() % SZ, y = rand() % SZ, num =
                rand() % 100;
            S.upd(x,y,num);
            x++, y++;
            B.upd(x,y,num);
        } else if (c == 1) {
            int x1 = rand() % SZ, y1 = rand() % SZ, x2
                = rand() % SZ, y2 = rand() % SZ;
            if (x1 > x2) swap(x1,x2);
            if (y1 > y2) swap(y1,y2);
            int a = S.query(x1,x2,y1,y2);
            x1 ++, y1 ++, x2 ++, y2 ++;
            int b = B.query(x1,x2,y1,y2);
            assert(a == b);
        } else break;
    }
}

```

6.2.3 BBST Demo (4)

```

/**
 * Link: http://www.spoj.com/problems/ORDERSET/
 * Description: Use with treap, splay tree
 */

int main() {
    int Q; cin >> Q;
    FOR(i,Q) {
        char c; int d; cin >> c >> d;
        if (c == 'I') root = ins(root,d);
        else if (c == 'D') root = del(root,d);
        else if (c == 'K') {
            if (!root || root->sz < d) cout
                << "invalid\n";
            else cout << find_by_order(d) <<
                "\n";
        } else cout << order_of_key(d) << "\n";
    }
}

```

6.2.4 Range Update Demo (4)

```

/**
 * Link: http://www.spoj.com/problems/HORRIBLE/
 * Description: Use with range BIT, lazy segtree
 */

int main() {
    int T; cin >> T;
    FOR(i,T) {
        LazySegTree<11,1<<17> B =
            LazySegTree<11,1<<17>();
        int N, C; cin >> N >> C;
        FOR(j,C) {
            int t; cin >> t;
            if (t == 0) {
                int p,q,v; cin >> p >> q >> v;
                B.upd(p,q,v);

```

```

    } else {
        int p,q; cin >> p >> q;
        cout << B.qsum(p,q) << "\n";
    }
}
}
}
}

```

6.3 1D Range Queries (3)

6.3.1 Binary Indexed Tree

```

/**
 * Description: 1D range sum query with point update
 * Verification: SPOJ Fenwick
 */

```

```

template<class T, int SZ> struct BIT {
    T bit[SZ+1];

    BIT() { memset(bit,0,sizeof bit); }

    void upd(int k, T val) { // add val to index k
        for( ;k <= SZ; k += (k&-k)) bit[k] += val;
    }

    T query(int k) {
        T temp = 0;
        for (;k > 0;k -= (k&-k)) temp += bit[k];
        return temp;
    }

    T query(int l, int r) { return
        query(r)-query(l-1); } // range query [l,r]
};

```

6.3.2 SegTree

```

/**
 * Source: http://codeforces.com/blog/entry/18051
 * Description: 1D point update, range query
 * Verification: SPOJ Fenwick
 */

```

```

template<class T, int SZ> struct Seg {
    T seg[2*SZ], MN = 0;

    Seg() {
        memset(seg,0,sizeof seg);
    }

    T comb(T a, T b) { return a+b; } // easily change
        this to min or max

    void upd(int p, T value) { // set value at
        position p
        for (seg[p += SZ] = value; p > 1; p >>= 1)
            seg[p>>1] = comb(seg[(p|1)^1],seg[p|1]); //
            non-commutative operations
    }
}

```

```

}

void build() {
    FORd(i,SZ) seg[i] = comb(seg[2*i],seg[2*i+1]);
}

T query(int l, int r) { // sum on interval [l, r]
    T res1 = MN, res2 = MN; r++;
    for (l += SZ, r += SZ; l < r; l >>= 1, r >>=
        1) {
        if (l&1) res1 = comb(res1,seg[l++]);
        if (r&1) res2 = comb(seg[--r],res2);
    }
    return comb(res1,res2);
}
};

```

6.3.3 BIT with Range Update (4)

```

/**
 * Source: GeeksForGeeks?
 * Description: 1D range update, range query
 * Alternative to lazy segment tree
 */

```

// BIT template

```

template<class T, int SZ> struct BITrange {
    BIT<T,SZ> bit[2]; // sums piecewise linear
        functions

    void upd(int hi, T val) {
        bit[1].upd(1,val), bit[1].upd(hi+1,-val);
        bit[0].upd(hi+1,hi*val);
    }

    void upd(int lo, int hi, T val) { upd(lo-1,-val),
        upd(hi,val); }

    T query(int x) { return
        bit[1].query(x)*x+bit[0].query(x); }

    T query(int x, int y) { return
        query(y)-query(x-1); }
};

```

6.3.4 Lazy SegTree (4)

```

/**
 * Description: 1D range update, range query
 * Verification: SPOJ Horrible
 */

```

```

const ll INF = 1e18; // setting this to MOD can be
    disastrous :(

template<class T, int SZ> struct LazySegTree {
    T sum[2*SZ], mn[2*SZ], lazy[2*SZ]; // set SZ to a
        power of 2
}

```

```

LazySegTree() {
    memset (sum,0,sizeof sum);
    memset (mn,0,sizeof mn);
    memset (lazy,0,sizeof lazy);
}

void push(int ind, int L, int R) {
    sum[ind] += (R-L+1)*lazy[ind];
    mn[ind] += lazy[ind];
    if (L != R) lazy[2*ind] += lazy[ind],
        lazy[2*ind+1] += lazy[ind];
    lazy[ind] = 0;
}

void pull(int ind) {
    sum[ind] = sum[2*ind]+sum[2*ind+1];
    mn[ind] = min(mn[2*ind],mn[2*ind+1]);
}

void build() {
    FORd(i,SZ) pull(i);
}

T qsum(int lo, int hi, int ind = 1, int L = 0, int
    R = SZ-1) {
    push(ind,L,R);
    if (lo > R || L > hi) return 0;
    if (lo <= L && R <= hi) return sum[ind];

    int M = (L+R)/2;
    return qsum(lo,hi,2*ind,L,M) +
        qsum(lo,hi,2*ind+1,M+1,R);
}

T qmin(int lo, int hi, int ind = 1, int L = 0, int
    R = SZ-1) {
    push(ind,L,R);
    if (lo > R || L > hi) return INF;
    if (lo <= L && R <= hi) return mn[ind];

    int M = (L+R)/2;
    return min(qmin(lo,hi,2*ind,L,M),
        qmin(lo,hi,2*ind+1,M+1,R));
}

void upd(int lo, int hi, ll inc, int ind = 1, int
    L = 0, int R = SZ-1) {
    push(ind,L,R);
    if (hi < L || R < lo) return;
    if (lo <= L && R <= hi) {
        lazy[ind] = inc;
        push(ind,L,R);
        return;
    }

    int M = (L+R)/2;
    upd(lo,hi,inc,2*ind,L,M);
    upd(lo,hi,inc,2*ind+1,M+1,R);
    pull(ind);
}
};

```

6.3.5 Sparse SegTree (4)

```

/**
 * Source: Own
 */

const int SZ = 1<<20;

template<class T> struct node {
    T val;
    node<T>* c[2];

    node() {
        val = 0;
        c[0] = c[1] = NULL;
    }

    void upd(int ind, T v, int L = 0, int R = SZ-1) {
        // add v
        if (L == ind && R == ind) { val += v; return; }

        int M = (L+R)/2;
        if (ind <= M) {
            if (!c[0]) c[0] = new node();
            c[0]->upd(ind,v,L,M);
        } else {
            if (!c[1]) c[1] = new node();
            c[1]->upd(ind,v,M+1,R);
        }

        val = 0;
        if (c[0]) val += c[0]->val;
        if (c[1]) val += c[1]->val;
    }

    T query(int low, int high, int L = 0, int R =
        SZ-1) { // query sum of segment
        if (low <= L && R <= high) return val;
        if (high < L || R < low) return 0;

        int M = (L+R)/2;
        T t = 0;
        if (c[0]) t += c[0]->query(low,high,L,M);
        if (c[1]) t += c[1]->query(low,high,M+1,R);
        return t;
    }

    void UPD(int ind, node* c0, node* c1, int L = 0,
        int R = SZ-1) { // for 2D segtree
        if (L != R) {
            int M = (L+R)/2;
            if (ind <= M) {
                if (!c[0]) c[0] = new node();
                c[0]->UPD(ind,c0 ? c0->c[0] : NULL,c1 ?
                    c1->c[0] : NULL,L,M);
            } else {
                if (!c[1]) c[1] = new node();
                c[1]->UPD(ind,c0 ? c0->c[1] : NULL,c1 ?
                    c1->c[1] : NULL,M+1,R);
            }
        }
    }
};

```

```

    val = 0;
    if (c0) val += c0->val;
    if (c1) val += c1->val;
}
};

```

6.3.6 SegTree Beats (6)

```

/**
 * Description: Interval min modifications
 * Verification:
 *   http://acm.hdu.edu.cn/showproblem.php?pid=5306
 */

const int MX = 1<<20;

int N,M, a[MX];

struct Seg {
    ll sum[2*MX];
    int mx1[2*MX], mx2[2*MX], maxCnt[2*MX];

    void pull(int ind) {
        mx1[ind] = max(mx1[2*ind],mx1[2*ind+1]);
        mx2[ind] = max(mx2[2*ind],mx2[2*ind+1]);
        maxCnt[ind] = 0;

        if (mx1[2*ind] == mx1[ind]) maxCnt[ind] +=
            maxCnt[2*ind];
        else mx2[ind] = max(mx2[ind],mx1[2*ind]);

        if (mx1[2*ind+1] == mx1[ind]) maxCnt[ind] +=
            maxCnt[2*ind+1];
        else mx2[ind] = max(mx2[ind],mx1[2*ind+1]);

        sum[ind] = sum[2*ind]+sum[2*ind+1];
    }

    void build(int ind = 1, int L = 0, int R = N-1) {
        if (L == R) {
            mx1[ind] = sum[ind] = a[L];
            maxCnt[ind] = 1;
            mx2[ind] = -1;
            return;
        }

        int M = (L+R)/2;
        build(2*ind,L,M); build(2*ind+1,M+1,R);
        pull(ind);
    }

    void push(int ind, int L, int R) {
        if (L == R) return;
        if (mx1[2*ind] > mx1[ind]) {
            sum[2*ind] -=
                (ll)maxCnt[2*ind]*(mx1[2*ind]-mx1[ind]);
            mx1[2*ind] = mx1[ind];
        }
        if (mx1[2*ind+1] > mx1[ind]) {

```

```

            sum[2*ind+1] -=
                (ll)maxCnt[2*ind+1]*(mx1[2*ind+1]-mx1[ind]);
            mx1[2*ind+1] = mx1[ind];
        }
    }

    void modify(int x, int y, int t, int ind = 1, int
        L = 0, int R = N-1) {
        if (R < x || y < L || mx1[ind] <= t) return;
        push(ind,L,R);
        if (x <= L && R <= y && mx2[ind] < t) {
            sum[ind] -= (ll)maxCnt[ind]*(mx1[ind]-t);
            mx1[ind] = t;
            return;
        }
        if (L == R) return;
        int M = (L+R)/2;
        modify(x,y,t,2*ind,L,M);
        modify(x,y,t,2*ind+1,M+1,R);
        pull(ind);
    }

    ll qsum(int x, int y, int ind = 1, int L = 0, int
        R = N-1) {
        if (R < x || y < L) return 0;
        push(ind,L,R);
        if (x <= L && R <= y) return sum[ind];

        int M = (L+R)/2;
        return
            qsum(x,y,2*ind,L,M)+qsum(x,y,2*ind+1,M+1,R);
    }

    int qmax(int x, int y, int ind = 1, int L = 0, int
        R = N-1) {
        if (R < x || y < L) return -1;
        push(ind,L,R);
        if (x <= L && R <= y) return mx1[ind];

        int M = (L+R)/2;
        return
            max(qmax(x,y,2*ind,L,M),qmax(x,y,2*ind+1,M+1,R));
    }
};

Seg S = Seg();

void solve() {
    cin >> N >> M;
    FOR(i,N) cin >> a[i];
    S.build();

    FOR(i,M) {
        int t; cin >> t;
        if (t == 0) {
            int x,y,z; cin >> x >> y >> z;
            S.modify(x-1,y-1,z);
        } else if (t == 1) {
            int x,y; cin >> x >> y;
            cout << S.qmax(x-1,y-1) << "\n";
        } else {
            int x,y; cin >> x >> y;

```

```

        cout << S.qsum(x-1,y-1) << "\n";
    }
}

```

6.4 2D Range Queries (4)

6.4.1 2D BIT

```

/**
 * Description: Supports point update & range query,
 *              can be extended to range update
 * Verification: SPOJ matsum
 * Dependency: Binary indexed tree
 */

template<class T, int SZ> struct BIT2D {
    BIT<T,SZ> bit[SZ+1];
    void upd(int X, int Y, T val) {
        for (; X <= SZ; X += (X&-X)) bit[X].upd(Y,val);
    }
    T query(int X, int Y) {
        T ans = 0;
        for (; X > 0; X -= (X&-X)) ans +=
            bit[X].query(Y);
        return ans;
    }
    T query(int X1, int X2, int Y1, int Y2) {
        return query(X2,Y2)-query(X1-1,Y2)
            -query(X2,Y1-1)+query(X1-1,Y1-1);
    }
};

int main() {
    int T; cin >> T;
    FOR(i,T) {
        int N; cin >> N;
        BIT2D<ll,1024> B = BIT2D<ll,1024>();
        while (1) {
            string c; cin >> c;
            if (c == "SET") {
                int x, y,num; cin >> x >> y >> num;
                x++, y++;
                B.upd(x,y,num-B.query(x,x,y,y));
            } else if (c == "SUM") {
                int x1, y1, x2, y2; cin >> x1 >> y1
                    >> x2 >> y2;
                x1 ++, y1 ++, x2 ++, y2++;
                cout << B.query(x1,x2,y1,y2) << "\n";
            } else break;
        }
    }
}

```

6.4.2 2D SegBIT

```

/**
 * Source: USACO Mowing the Field

```

```

 * Dependency: Sparse SegTree
 */

```

```
const int SZ = 1<<17;
```

```

template<class T> struct SegBit {
    node<T> seg[SZ+1];

    SegBit() {
        FOR(i,SZ+1) seg[i] = node<T>();
    }

    void upd(int x, int y, int v) { // add v
        for (x++;x <= SZ; x += (x&-x)) seg[x].upd(y,v);
    }

    T query(int x, int y1, int y2) {
        T ret = 0;
        for (;x > 0; x -= (x&-x)) ret +=
            seg[x].query(y1,y2);
        return ret;
    }

    T query(int x1, int x2, int y1, int y2) { // query
        sum of rectangle
        return query(x2+1,y1,y2)-query(x1,y1,y2);
    }
};

```

6.4.3 2D SegTree

```

/**
 * Source: USACO Mowing the Field
 * Dependency: Sparse SegTree
 */

const int SZ = 1<<17;

template<class T> struct Node {
    node<T> seg;
    Node* c[2];

    void upd(int x, int y, T v, int L = 0, int R =
        SZ-1) { // add v
        if (L == x && R == x) {
            seg.upd(y,v);
            return;
        }

        int M = (L+R)/2;
        if (x <= M) {
            if (!c[0]) c[0] = new Node();
            c[0]->upd(x,y,v,L,M);
        } else {
            if (!c[1]) c[1] = new Node();
            c[1]->upd(x,y,v,M+1,R);
        }

        seg.UPD(y,c[0] ? &c[0]->seg : NULL,c[1] ?
            &c[1]->seg : NULL);
    }
}

```

```

}

T query(int x1, int x2, int y1, int y2, int L = 0,
        int R = SZ-1) { // query sum of rectangle
    if (x1 <= L && R <= x2) return
        seg.query(y1,y2);
    if (x2 < L || R < x1) return 0;

    int M = (L+R)/2;
    T t = 0;
    if (c[0]) t += c[0]->query(x1,x2,y1,y2,L,M);
    if (c[1]) t += c[1]->query(x1,x2,y1,y2,M+1,R);
    return t;
}
};

```

6.4.4 Merge-Sort Tree

```

/**
 * Description: Similar to 2D segtree, less memory
 * For more complex queries use a customized treap
 * Verification:
 *   http://codeforces.com/contest/785/submission/33953058
 */

template<int SZ> struct mstree {
    Tree<pi> val[SZ+1]; // for offline queries use
                        // vector with binary search instead

    void upd(int x, int y, int t = 1) { //
        x-coordinate between 1 and SZ inclusive
        for (int X = x; X <= SZ; X += X&-X) {
            if (t == 1) val[X].insert({y,x});
            else val[X].erase({y,x});
        }
    }

    int query(int x, int y) {
        int t = 0;
        for (;x > 0; x -= x&-x) t +=
            val[x].order_of_key({y,MOD});
        return t;
    }

    int query(int lox, int hix, int loy, int hiy) { //
        query number of elements within a rectangle
        return query(hix,hiy)-query(lox-1,hiy)
            -query(hix,loy-1)+query(lox-1,loy-1);
    }
};

```

6.5 BBST (4)

6.5.1 Treap

```

/*
 * Sources: various
 * Description: Easiest BBST

```

```

 * Verification: http://www.spoj.com/problems/ORDERSET/
 */

struct tnode {
    int val, pri, sz;
    tnode *c[2];

    tnode (int v) {
        val = v, sz = 1, pri = rand()+(rand()<<15);
        c[0] = c[1] = NULL;
    }

    void inOrder(bool f = 0) {
        if (c[0]) c[0]->inOrder();
        cout << val << " ";
        if (c[1]) c[1]->inOrder();
        if (f) cout << "\n-----\n";
    }

    void recalc() {
        sz = 1+(c[0]?c[0]->sz:0)+(c[1]?c[1]->sz:0);
    }
};

pair<tnode*,tnode*> split(tnode* t, int v) { // >= v
    goes to the right
    if (!t) return {t,t};

    if (v <= t->val) {
        auto p = split(t->c[0], v);
        t->c[0] = p.s; t->recalc();
        return {p.f, t};
    } else {
        auto p = split(t->c[1], v);
        t->c[1] = p.f; t->recalc();
        return {t, p.s};
    }
}

pair<tnode*,tnode*> split_by_order(tnode* t, int v) {
    if (!t) return {t,t};
    int tmp = t->c[0]?t->c[0]->sz:0;
    if (v <= tmp) {
        auto p = split_by_order(t->c[0], v);
        t->c[0] = p.s; t->recalc();
        return {p.f, t};
    } else {
        auto p = split_by_order(t->c[1], v-tmp-1);
        t->c[1] = p.f; t->recalc();
        return {t, p.s};
    }
}

tnode* merge(tnode* l, tnode* r) {
    if (!l) return r;
    if (!r) return l;

    if (l->pri > r->pri) {
        l->c[1] = merge(l->c[1],r);
        l->recalc();
        return l;
    } else {

```

```

        r->c[0] = merge(l,r->c[0]);
        r->recalc();
        return r;
    }
}

tnode* ins(tnode* x, int v) { // insert value v
    auto a = split(x,v);
    auto b = split(a.s,v+1);
    return merge(a.f,merge(new tnode(v),b.s));
}

tnode* del(tnode* x, int v) { // delete all values
    equal to v
    auto a = split(x,v), b = split(a.s,v+1);
    return merge(a.f,b.s);
}

tnode *root;

int order_of_key(int x) {
    auto a = split(root,x);
    int t = a.f?a.f->sz:0;
    root = merge(a.f,a.s);
    return t;
}

int find_by_order(int x) {
    auto a = split_by_order(root,x);
    auto b = split_by_order(a.f,x-1);
    int t = b.s->val;
    root = merge(merge(b.f,b.s),a.s);
    return t;
}

```

6.5.2 Link-Cut Tree (5)

```

/**
 * Source: Dhruv Rohatgi
 * Usage: USACO Camp - The Applicant
 */

template<int SZ> struct LCT {
    int p[SZ], pp[SZ], c[SZ][2], sum[SZ];

    LCT () {
        FOR(i,1,SZ) sum[i] = 1;
        memset(p,0,sizeof p);
        memset(pp,0,sizeof pp);
        memset(c,0,sizeof c);
    }

    int getDir(int x, int y) {
        return c[x][0] == y ? 0 : 1;
    }

    void setLink(int x, int y, int d) {
        c[x][d] = y, p[y] = x;
    }
}

```

```

void rotate(int y, int d) {
    int x = c[y][d], z = p[y];
    setLink(y,c[x][d^1],d);
    setLink(x,y,d^1);
    setLink(z,x,getYDir(z,y));

    sum[x] = sum[y];
    sum[y] = sum[c[y][0]]+sum[c[y][1]]+1;
    pp[x] = pp[y]; pp[y] = 0;
}

void splay(int x) {
    while (p[x]) {
        int y = p[x], z = p[y];
        int dy = getYDir(y,x), dz = getYDir(z,y);
        if (!z) rotate(y,dy);
        else if (dy == dz) rotate(z,dz),
            rotate(y,dy);
        else rotate(y,dy), rotate(z,dz);
    }
}

void dis(int v, int d) {
    p[c[v][d]] = 0, pp[c[v][d]] = v;
    sum[v] -= sum[c[v][d]];
    c[v][d] = 0;
}

void con(int v, int d) {
    c[pp[v]][d] = v;
    sum[pp[v]] += sum[v];
    p[v] = pp[v], pp[v] = 0;
}

void access(int v) {
    // v is brought to the root of auxiliary tree
    // modify preferred paths

    splay(v);
    dis(v,1);

    while (pp[v]) {
        int w = pp[v]; splay(w);
        dis(w,1), con(v,1);
        splay(v);
    }
}

int find_root(int v) {
    access(v);
    while (c[v][0]) v = c[v][0];
    access(v);
    return v;
}

int find_depth(int v) {
    access(v);
    return sum[c[v][0]];
}

void cut(int v) {
    // cut link between v and par[v]
}

```

```

    access(v);
    pp[c[v][0]] = p[c[v][0]] = 0; // fix
    sum[v] -= sum[c[v][0]];
    c[v][0] = 0;
}

void link(int v, int w) {
    // v, which is root of another tree, is now
    // child of w
    access(v), access(w);
    pp[w] = v; con(w,0);
}

int anc(int v, int num) {
    if (find_depth(v) < num) return 0;
    access(v);
    v = c[v][0];

    while (1) {
        if (sum[c[v][1]] >= num) v = c[v][1];
        else if (sum[c[v][1]]+1 == num) return v;
        else num -= (sum[c[v][1]]+1), v = c[v][0];
    }
}

void print(int x) {
    FOR(i,1,x+1) cout << i << " " << find_root(i)
        << " " << find_depth(i) << " " << anc(i,2)
        << "\n";
    cout << "\n";
}

};

LCT<100001> L;

int main() {
    L.link(2,1); L.link(3,1); L.link(4,1); L.link(5,4);
    L.link(10,4); L.link(7,6); L.link(8,7);
    L.link(9,8);
    L.print(10);

    L.cut(4); L.link(4,8);
    L.print(10);
}

```

6.5.3 Splay Tree (5)

```

/*
 * Description: Based off treap code
 * Source: https://sites.google.com/site/kc97ble
 *           /container/splay-tree/splaytree-cpp-3
 * Verification: http://www.spoj.com/problems/ORDERSET/
 */

struct snode {
    int val, sz;
    snode *p, *c[2];

    snode(int v) {
        val = v, sz = 1;
    }
}

```

```

    c[0] = c[1] = p = NULL;
}

void inOrder(bool f = 0) {
    if (c[0]) c[0]->inOrder();
    cout << val << " ";
    if (c[1]) c[1]->inOrder();
    if (f) cout << "\n-----\n";
}

void recalc() {
    sz = 1+(c[0]?c[0]->sz:0)+(c[1]?c[1]->sz:0);
}

};

void setLink(snode* x, snode* y, int d) {
    if (x) x->c[d] = y, x->recalc();
    if (y) y->p = x;
}

snode* unLink(snode* x, int d) {
    snode* y = x->c[d];
    x->c[d] = NULL; x->recalc();
    if (y) y->p = NULL;
    return y;
}

int getDir(snode* x, snode* y) {
    if (!x) return -1;
    return x->c[0] == y ? 0 : 1;
}

void rot(snode* x, int d) {
    snode *y = x->c[d], *z = x->p;
    setLink(x, y->c[d^1], d);
    setLink(y, x, d^1);
    setLink(z, y, getDir(z, x));
}

snode* splay(snode* x) {
    while (x && x->p) {
        snode* y = x->p, *z = y->p;
        int dy = getDir(y, x), dz = getDir(z, y);
        if (!z) rot(y, dy);
        else if (dy == dz) rot(z, dz), rot(y, dy);
        else rot(y, dy), rot(z, dz);
    }
    return x;
}

snode* find(snode* cur, int v) {
    if (!cur) return cur;
    snode* x;
    if (cur->val >= v) x = find(cur->c[0], v);
    else x = find(cur->c[1], v);
    return x?x:cur;
}

snode* getmx(snode* x) {
    return x->c[1]?getmx(x->c[1]):x;
}

```



```

pair<snode*,snode*> split(snode* x, int v) {
    if (!x) return {x,x};
    snode* y = find(x,v); y = splay(y);
    if (y->val >= v) return {unLink(y,0),y};
    else return {y,unLink(y,1)};
}

snode* find_by_order(snode* x, int v) {
    int tmp = x->c[0]?x->c[0]->sz:0;
    if (v < tmp) return find_by_order(x->c[0],v);
    else if (v == tmp) return x;
    else return find_by_order(x->c[1],v-tmp-1);
}

pair<snode*,snode*> split_by_order(snode* x, int v) {
    // left subtree has v elements
    if (!x) return {x,x};
    if (v == x->sz) return {x,NULL};
    snode* y = find_by_order(x,v); y = splay(y);
    return {unLink(y,0),y};
}

snode* merge(snode* x, snode* y) {
    if (!x) return y;
    x = splay(getmx(x));
    setLink(x,y,1);
    return x;
}

// same as treap

snode* ins(snode* x, int v) { // insert value v
    auto a = split(x,v);
    auto b = split(a.s,v+1);
    return merge(a.f,merge(new snode(v),b.s));
}

snode* del(snode* x, int v) { // delete all values
    equal to v
    auto a = split(x,v), b = split(a.s,v+1);
    return merge(a.f,b.s);
}

snode* root;

int order_of_key(int x) {
    auto a = split(root,x);
    int t = a.f?a.f->sz:0;
    root = merge(a.f,a.s);
    return t;
}

int find_by_order(int x) {
    auto a = split_by_order(root,x);
    auto b = split_by_order(a.f,x-1);
    int t = b.s->val;
    root = merge(merge(b.f,b.s),a.s);
    return t;
}

```

6.6 Persistent Queries (5)

6.6.1 Basic PST

```

/**
 * Description: persistent segtree node without lazy
 *             updates
 * Verification: Codeforces Problem 893F - Subtree
 *               Minimum Query
 * Implementation:
 *               http://codeforces.com/contest/893/submission/32652140
 */

struct Node {
    int val = 0;
    Node* c[2];

    Node* copy() {
        Node* x = new Node(); *x = *this;
        return x;
    }

    int query(int low, int high, int L, int R) {
        if (low <= L && R <= high) return val;
        if (R < low || high < L) return MOD;
        int M = (L+R)/2;
        return min(c[0]->query(low,high,L,M),
                  c[1]->query(low,high,M+1,R));
    }

    Node* upd(int ind, int v, int L, int R) {
        if (R < ind || ind < L) return this;
        Node* x = copy();

        if (ind <= L && R <= ind) {
            x->val += v;
            return x;
        }

        int M = (L+R)/2;
        x->c[0] = x->c[0]->upd(ind,v,L,M);
        x->c[1] = x->c[1]->upd(ind,v,M+1,R);
        x->val = min(x->c[0]->val,x->c[1]->val);

        return x;
    }

    void build(vi& arr, int L, int R) {
        if (L == R) {
            if (L < (int)arr.size()) val = arr[L];
            else val = 0;
            return;
        }
        int M = (L+R)/2;
        c[0] = new Node();
        c[0]->build(arr,L,M);
        c[1] = new Node();
        c[1]->build(arr,M+1,R);
        val = min(c[0]->val,c[1]->val);
    }
};

```

```
template<int SZ> struct pers {
    Node* loc[SZ+1]; // stores location of root after
                    ith update
    int nex = 1;

    pers() { loc[0] = new Node(); }

    void upd(int ind, int val) {
        loc[nex] = loc[nex-1]->upd(ind,val,0,SZ-1);
        nex++;
    }
    void build(vi& arr) {
        loc[0]->build(arr,0,SZ-1);
    }
    int query(int ti, int low, int high) {
        return loc[ti]->query(low,high,0,SZ-1);
    }
};
```

6.6.2 Lazy PST

```
/**
 * Source:
 * http://codeforces.com/blog/entry/47108?#comment-315047
 * Description: Node + lazy updates
 */

struct node {
    int val = 0, lazy = 0;
    node* c[2];

    node* copy() {
        node* x = new node(); *x = *this;
        return x;
    }

    void push() {
        if (!lazy) return;
        FOR(i,2) if (c[i]) {
            c[i] = new node(*c[i]);
            c[i]->lazy += lazy;
        }
        lazy = 0;
    }

    int query(int low, int high, int L, int R) {
        if (low <= L && R <= high) return val;
        if (R < low || high < L) return MOD;
        int M = (L+R)/2;
        return lazy+min(c[0]->query(low,high,L,M),
                       c[1]->query(low,high,M+1,R));
    }

    node* upd(int low, int high, int v, int L, int R) {
        if (R < low || high < L) return this;
        node* x = copy();
        if (low <= L && R <= high) {
            x->lazy += v, x->val += v;
            return x;
        }
    }
};
```

```
    }
    push();

    int M = (L+R)/2;
    x->c[0] = x->c[0]->upd(low,high,v,L,M);
    x->c[1] = x->c[1]->upd(low,high,v,M+1,R);
    x->val = min(x->c[0]->val,x->c[1]->val);

    return x;
}

void build(vi& arr, int L, int R) {
    if (L == R) {
        if (L < sz(arr)) val = arr[L];
        else val = 0;
        return;
    }
    int M = (L+R)/2;
    c[0] = new node();
    c[0]->build(arr,L,M);
    c[1] = new node();
    c[1]->build(arr,M+1,R);
    val = min(c[0]->val,c[1]->val);
}

};

template<int SZ> struct pers {
    node* loc[SZ+1]; // stores location of root after
                    ith update
    int nex = 1;

    pers() { loc[0] = new node(); }

    void upd(int low, int high, int val) {
        loc[nex] =
            loc[nex-1]->upd(low,high,val,0,SZ-1);
        nex++;
    }
    void build(vi& arr) {
        loc[0]->build(arr,0,SZ-1);
    }
    int query(int ti, int low, int high) {
        return loc[ti]->query(low,high,0,SZ-1);
    }
};

pers<8> p;

int main() {
    vi arr = {1,7,2,3,5,9,4,6};
    p.build(arr);

    p.upd(1,2,2); // 1 9 4 3 5 9 4 6

    FOR(i,8) {
        FOR(j,i,8) cout << p.query(1,i,j) << " ";
        cout << "\n";
    }
    cout << "\n";

    p.upd(4,7,5); // 1 9 4 3 10 14 9 11
    FOR(i,8) {
```

```

    FOR(j,i,8) cout << p.query(2,i,j) << " ";
    cout << "\n";
}
cout << "\n";

FOR(i,8) {
    FOR(j,i,8) cout << p.query(1,i,j) << " ";
    cout << "\n";
}
cout << "\n";
}

```

6.6.3 Low-Memory Basic PST

```

//uses about 34 MB
const int MAXN = 100100;
int N = 100000;
struct Node {
    ll val;
} SEG[20*MAXN];
int e = 0;
int LFT[20*MAXN], RGT[20*MAXN];

int roots[MAXN];

int build(int l = 0, int r = N - 1) {
    //build from L to R inclusive.
    int x = ++e;
    if (l == r){
        SEG[x].val = 0;
        LFT[x] = -1;
        RGT[x] = -1;
        return x;
    }
    int mid = (l + r)/2;
    LFT[x] = build(l, mid);
    RGT[x] = build(mid + 1, r);
    return x;
}

int upd(int cur, int pos, int set, int l = 0, int r =
N - 1) {
    //set a[pos] = set in the root cur
    if (r < pos || pos < l) return cur;
    int x = ++e;
    //we're creating a new node
    if (l == r){
        SEG[x].val = set;
        return x;
    }
    int m = (l+r)/2;
    LFT[x] = upd(LFT[cur], pos, set, l, m);
    RGT[x] = upd(RGT[cur], pos, set, m + 1, r);
    SEG[x].val = SEG[LFT[x]].val + SEG[RGT[x]].val;
    return x;
}

ll query(int cur, int L, int R, int l = 0, int r = N -
1){
    if (r < L || R < l) return 0LL;

```

```

    int m = (l + r)/2;
    if (L <= l && r <= R) return SEG[cur].val;
    return query(LFT[cur], L, R, l, m) +
        query(RGT[cur], L, R, m + 1, r);
}

```

7 DP (3)

7.1 Examples

7.1.1 Knapsack

// <https://open.kattis.com/problems/knapsack>

```

double C;
int n,v[2000],w[2000],dp[2001][2001];

void solve() {
    FOR(i,n) cin >> v[i] >> w[i];
    FOR(i,n) {
        FOR(j,C+1) dp[i+1][j] = dp[i][j];
        FOR(j,C+1) if (w[i]+j <= C) dp[i+1][w[i]+j] =
            max(dp[i+1][w[i]+j],dp[i][j]+v[i]);
    }

    vi ans;
    int x = C;
    FORd(i,n) if (dp[i][x] != dp[i+1][x]) x -= w[i],
        ans.pb(i);

    cout << ans.size() << "\n";
    for (int i: ans) cout << i << " ";
    cout << "\n";
}

```

7.1.2 Longest Common Subsequence

```

/**
 * Description: Classic DP example
 */

int dp[1001][1001];
string a,b;

int main() {
    cin >> a >> b;
    FOR(i,sz(a)) FOR(j,b.sz(b)) {
        dp[i+1][j+1] = max(dp[i+1][j],dp[i][j+1]);
        if (a[i] == b[j]) dp[i+1][j+1] =
            max(dp[i+1][j+1],dp[i][j]+1);
    }
    cout << dp[sz(a)][sz(b)];
}

```

7.1.3 Longest Increasing Subsequence

```

/**
 * Description: DP with Binary Search
 */

vi bes = {0};
int n;

void ad(int x) {
    int lo = 0, hi = sz(bes)-1;
    while (lo < hi) {
        int mid = (lo+hi+1)/2;
        if (bes[mid] < x) lo = mid;
        else hi = mid-1;
    }
    if (lo == sz(bes)-1) bes.pb(0);
    bes[lo+1] = x;
}

int main() {
    cin >> n;
    FOR(i,n) {
        int x; cin >> x;
        ad(x);
    }
    cout << sz(bes)-1;
}

```

7.1.4 String Removals

```

/**
 * Description: DP eliminates overcounting
 * Verification: https://cses.fi/problemset/task/1149/
 */

int distinct(string S) {
    vi tot(26);
    int ans = 1;
    for (char c: S) {
        int t = (ans-tot[c-'a']+MOD)%MOD;
        tot[c-'a'] = (tot[c-'a']+t)%MOD;
        ans = (ans+t)%MOD;
    }
    return ans;
}

```

7.1.5 Traveling Salesman (4)

```

/**
 * Description: Bitset DP example
 * Solves TSP for small N
 */

const int MX = 15;

int N, dp[MX][1<<MX], dist[MX][MX];

int solve() {

```

```

    FOR(i,N) FOR(j,1<<N) dp[i][j] = MOD;

    dp[0][1] = 0;
    FOR(j,1<<N) FOR(i,N) if (j&(1<<i))
        FOR(k,N) if (!(j&(1<<k)))
            dp[k][j^(1<<k)] = min(dp[k][j^(1<<k)],
                                   dp[i][j]+dist[i][k]);

    int ans = MOD;
    FOR(j,1,N) ans =
        min(ans,dp[j][((1<<N)-1)+dist[j][0]]);
    return ans;
}

int main() {
    int T; cin >> T;
    FOR(i,T) {
        cin >> N; N++;
        FOR(j,N) FOR(k,N) if (j != k) cin >>
            dist[j][k];
        cout << solve() << "\n";
    }
}

```

7.2 Divide And Conquer (4)

```

/**
 * Source: Own
 * Usage: CEOI 2004 Two Sawmills
 */

void divi(int lo, int hi, int L, int R) {
    if (lo > hi) return;

    int mid = (lo+hi)/2;
    pair<ll,int> tmp = {1e18,-1};
    FOR(i,max(mid+1,L),R+1)
        tmp = min(tmp,{calc(0,mid)+calc(mid+1,i)
                        +calc(i+1,n),i});
    ans = min(ans,tmp.f);

    divi(lo,mid-1,L,tmp.s);
    divi(mid+1,hi,tmp.s,R);
}

```

8 Strings (3)

8.1 Hashing

```

/**
 * Source: own
 * Description: Pairs reduce frequency of collision
 * Verification: Dec 17 Plat 1
 */

template<class T> pair<T,T> operator+(const pair<T,T>&
    l, const pair<T,T>& r) {

```

```

    return {(l.f+r.f)%MOD,(l.s+r.s)%MOD};
}

template<class T> pair<T,T> operator-(const pair<T,T>&
l, const pair<T,T>& r) {
    return {(l.f-r.f+MOD)%MOD,(l.s-r.s+MOD)%MOD};
}

template<class T> pair<T,T> operator*(const pair<T,T>&
l, const T& r) {
    return {l.f*r%MOD,l.s*r%MOD};
}

template<class T> pair<T,T> operator*(const pair<T,T>&
l, const pair<T,T>& r) {
    return {l.f*r.f%MOD,l.s*r.s%MOD};
}

struct hsh {
    string S;
    vector<pl> po, ipo, cum;
    pl base = mp(948392576,573928192), invbase =
        mp(499499562,829828935);

    ll modpow(ll b, ll p) {
        return !p?1:modpow(b*b%MOD,p/2)*(p&1?b:1)%MOD;
    }

    ll inv(ll x) {
        return modpow(x,MOD-2);
    }

    void gen(string _S) {
        S = _S;
        po.resize(sz(S)), ipo.resize(sz(S)),
            cum.resize(sz(S)+1);
        po[0] = ipo[0] = {1,1};
        FOR(i,1,sz(S)) {
            po[i] = po[i-1]*base;
            ipo[i] = ipo[i-1]*invbase;
        }
        FOR(i,sz(S)) cum[i+1] =
            cum[i]+po[i]*(ll)(S[i]-'a'+1);
    }

    pl get(int l, int r) {
        return ipo[l]*(cum[r+1]-cum[l]);
    }
};

int lcp(hsh& a, hsh& b) { // can be used to generate a
    suffix array
    int lo = 0, hi = min(sz(a.S),sz(b.S));
    while (lo < hi) {
        int mid = (lo+hi+1)/2;
        if (a.get(0,mid-1) == b.get(0,mid-1)) lo = mid;
        else hi = mid-1;
    }
    return lo;
}

int main() {

```

```

    string _S = "abacaba";
    hsh h; h.gen(_S);
    FOR(i,sz(_S)) FOR(j,i,sz(_S)) cout << i << " " <<
        j << " " << h.get(i,j).f << " " <<
        h.get(i,j).s << "\n";

    hsh H; H.gen("abadaba");
    cout << lcp(h,H);
}

```

8.2 Bitset Trie (4)

```

/**
 * Source: Algorithms Gym
 * Verification: January Easy 2018 - Shubham and
 * Subarray Xor
 */

template<int MX> struct tri {
    int nex = 0, ans = 0;
    int trie[MX][2]; // easily changed to character

    tri() {
        memset(trie,0,sizeof trie);
    }

    void ins(int x) {
        int cur = 0;
        FORd(i,30) {
            int t = (x&(1<<i))>>i;
            if (!trie[cur][t]) trie[cur][t] = ++nex;
            cur = trie[cur][t];
        }
    }

    void test(int x) {
        int cur = 0;
        FORd(i,30) {
            int t = ((x&(1<<i))>>i) ^ 1;
            if (!trie[cur][t]) t ^= 1;
            cur = trie[cur][t];
            if (t) x ^= (1<<i);
        }
        ans = max(ans,x);
    }
};

```

8.3 String Searching (4)

8.3.1 Aho-Corasick

```

/**
 * Source: https://ideone.com/0cMjZJ
 * Usage: Kattis stringmultimatching
 */

template<int SZ> struct Aho {
    int link[SZ], dict[SZ], sz = 1, num = 0;

```

```

vpi ind[SZ];
map<char,int> to[SZ];
vi oc[SZ];
queue<int> q;

Aho() {
    memset(link,0,sizeof link);
    memset(dict,0,sizeof dict);
}

void add(string s) {
    int v = 0;
    for(auto c: s) {
        if (!to[v].count(c)) to[v][c] = sz++;
        v = to[v][c];
    }
    dict[v] = v; ind[v].pb(++num,sz(s));
}

void push_links() {
    link[0] = -1; q.push(0);
    while (sz(q)) {
        int v = q.front(); q.pop();
        for (auto it: to[v]) {
            char c = it.f; int u = it.s, j =
                link[v];
            while (j != -1 && !to[j].count(c)) j =
                link[j];
            if (j != -1) {
                link[u] = to[j][c];
                if (!dict[u]) dict[u] =
                    dict[link[u]];
            }
            q.push(u);
        }
    }
}

void process(int pos, int cur) {
    cur = dict[cur];
    while (cur) {
        for (auto a: ind[cur])
            oc[a.f].pb(pos-a.s+1);
        cur = dict[link[cur]];
    }
}

int nex(int pos, int cur, char c) {
    while (cur != -1 && !to[cur].count(c)) cur =
        link[cur];
    if (cur == -1) cur = 0;
    else cur = to[cur][c];
    process(pos, cur);
    return cur;
}

};

Aho<100001> A;

int n;

void solve() {

```

```

A = Aho<100001>();
cin >> n;
FOR(i,n) {
    string pat; getline(cin,pat); if (!i)
        getline(cin,pat);
    A.add(pat);
}
A.push_links();

string t; getline(cin,t);
int cur = 0;
FOR(i,sz(t)) cur = A.nex(i,cur,t[i]);
FOR(i,1,n+1) {
    for (int j: A.oc[i]) cout << j << " ";
    cout << "\n";
}
}

```

8.3.2 Manacher

```

/**
 * Source: http://codeforces.com/blog/entry/12143
 * Description: Calculates length of largest palindrome
                centered at each character of string
 * Verification: http://www.spoj.com/problems/MSUBSTR/
 */

vi manacher(string s) {
    string s1 = "@";
    for (char c: s) s1 += c, s1 += "#";
    s1[s1.length()-1] = '&';

    vi ans(s1.length()-1);
    int lo = 0, hi = 0;
    FOR(i,1,s1.length()-1) {
        ans[i] = min(hi-i,ans[hi-i+lo]);
        while (s1[i-ans[i]-1] == s1[i+ans[i]+1])
            ans[i]++;
        if (i+ans[i] > hi) lo = i-ans[i], hi =
            i+ans[i];
    }

    ans.erase(ans.begin());
    FOR(i,sz(ans)) if ((i&1) == (ans[i]&1)) ans[i]++;
    // adjust lengths
    return ans;
}

int main() {
    int T; cin >> T;
    FOR(i,T) {
        pii bes = {0,0};
        string s; cin >> s;
        vi t = manacher(s);
        for (int i: t) {
            if (i > bes.f) bes = {i,1};
            else if (i == bes.f) bes.s++;
        }
        cout << bes.f << " " << bes.s << "\n";
    }
}

```

}

8.3.3 Minimum Rotation

```
/**
 * Source: KACTL
 * Unused
 */

int min_rotation(string s) {
    int a=0, N=sz(s); s += s;
    FOR(b,N) FOR(i,N) {
        if (a+i == b || s[a+i] < s[b+i]) {b +=
            max(0, i-1); break;}
        if (s[a+i] > s[b+i]) { a = b; break; }
    }
    return a;
}
```

8.3.4 Z

```
/**
 * Source: http://codeforces.com/blog/entry/3107
 * Description: similar to KMP
 * Verification: POI 12 Template
 */

vi z(string s) {
    int N = s.length(); s += '#';
    vi ans(N); ans[0] = N;
    while (s[1+ans[1]] == s[ans[1]]) ans[1] ++;

    int L = 1, R = ans[1];
    FOR(i,2,N) {
        if (i <= R) ans[i] = min(R-i+1,ans[i-L]);
        while (s[i+ans[i]] == s[ans[i]]) ans[i] ++;
        if (i+ans[i]-1 > R) L = i, R = i+ans[i]-1;
    }
    return ans;
}

vi get(string a, string b) { // find prefixes of a in b
    string s = a+"@"+b;
    vi t = z(s);
    return vi(t.begin()+a.length()+1,t.end());
}

int main() {
    vi x = z("abcababcbabcaba");
    for (int i: x) cout << i << " ";
    cout << "\n";

    x = get("abcab","uwetrabcerabcb");
    for (int i: x) cout << i << " ";
}
```

8.4 Suffix Array (4)

8.4.1 Suffix Array

```
/**
 * Source: SuprDewd CP Course
 * Task: https://open.kattis.com/problems/suffixsorting
 * KACTL version is slightly faster
 * Verification: USACO December 2017: Standing out from
    the herd:
    http://usaco.org/index.php?page=viewproblem2&cpid=768
 * Code to Verify: https://pastebin.com/y2Z9FYr6
 */

struct suffix_array {
    int N;
    vector<vi> P;
    vector<array<int,3>> L;
    vi idx;
    string str;

    /*void bucket(int ind) {
        int mn = MOD, mx = -MOD;

        for (auto a: L) mn = min(mn,a[ind]), mx =
            max(mx,a[ind]);
        vector<array<int,3>> tmp[mx-mn+1];
        FORd(i,sz(L)) tmp[L[i][ind]-mn].pb(L[i]);

        int nex = 0;
        FOR(i,mx-mn+1) for (auto a: tmp[i]) L[nex++] =
            a;
    }

    void bucket_sort() {
        bucket(1), bucket(0);
    }*/

    suffix_array(string _str) {
        str = _str; N = sz(str);
        P.pb(vi(N)); L.resize(N);
        FOR(i,N) P[0][i] = str[i];

        for (int stp = 1, cnt = 1; cnt < N; stp ++,
            cnt *= 2) {
            P.pb(vi(N));
            FOR(i,N) L[i] = {P[stp-1][i],i+cnt < N ?
                P[stp-1][i+cnt] : -1,i};
            sort(all(L)); // bucket_sort();
            FOR(i,N) {
                if (i && mp(L[i][0],L[i][1]) ==
                    mp(L[i-1][0],L[i-1][1]))
                    P[stp][L[i][2]] = P[stp][L[i-1][2]];
                else P[stp][L[i][2]] = i;
            }
        }

        idx.resize(N);
        FOR(i,sz(P.back())) idx[P.back()[i]] = i;
    }
}
```

```

int lcp(int x, int y) {
    int res = 0;
    if (x == y) return N-x;
    for (int k = sz(P) - 1; k >= 0 && x < N && y <
        N; k--) {
        if (P[k][x] == P[k][y]) {
            x += 1 << k;
            y += 1 << k;
            res += 1 << k;
        }
    }
    return res;
}
};

```

8.4.2 Reverse Burrows-Wheeler (6)

```

/**
 * Verification: https://cses.fi/problemset/task/1113/
 */

string transform(string s) {
    vector<pair<char,int>> v;
    int nex[sz(s)];

    FOR(i,sz(s)) v.pb({s[i],i});
    sort(all(v));
    FOR(i,sz(v)) nex[i] = v[i].s;

    int cur = nex[0];
    string ret;
    while (cur != 0) {
        ret += v[cur].f;
        cur = nex[cur];
    }
    return ret;
}

```

8.5 Z (5)

8.5.1 Manacher

```

/**
 * Source: http://codeforces.com/blog/entry/12143
 * Description: Calculates length of largest palindrome
 *               centered at each character of string
 * Verification: http://www.spoj.com/problems/MSUBSTR/
 */

vi manacher(string s) {
    string s1 = "@";
    for (char c: s) s1 += c, s1 += "#";
    s1[s1.length()-1] = '&';

    vi ans(s1.length()-1);
    int lo = 0, hi = 0;
    FOR(i,1,s1.length()-1) {
        ans[i] = min(hi-i,ans[hi-i+lo]);
    }
}

```

```

while (s1[i-ans[i]-1] == s1[i+ans[i]+1])
    ans[i] ++;
if (i+ans[i] > hi) lo = i-ans[i], hi =
    i+ans[i];
}

ans.erase(ans.begin());
FOR(i,sz(ans)) if ((i&1) == (ans[i]&1)) ans[i] ++;
// adjust lengths
return ans;
}

int main() {
    int T; cin >> T;
    FOR(i,T) {
        pi bes = {0,0};
        string s; cin >> s;
        vi t = manacher(s);
        for (int i: t) {
            if (i > bes.f) bes = {i,1};
            else if (i == bes.f) bes.s++;
        }
        cout << bes.f << " " << bes.s << "\n";
    }
}

```

9 Trees (4)

9.1 Tree Diameter

```

/**
 * Might not be obvious why this works!
 * Verification: http://www.spoj.com/problems/PT07Z/
 */

int n, dist[MX], pre[MX];
vi adj[MX];

void dfs(int cur) {
    for (int i: adj[cur]) if (i != pre[cur]) {
        pre[i] = cur;
        dist[i] = dist[cur]+1;
        dfs(i);
    }
}

void genDist(int cur) {
    memset(dist,0,sizeof dist);
    pre[cur] = -1;
    dfs(cur);
}

int treeDiameter() {
    genDist(1);
    int bes = 0; FOR(i,1,n+1) if (dist[i] > dist[bes])
        bes = i;
    genDist(bes); FOR(i,1,n+1) if (dist[i] >
        dist[bes]) bes = i;
    return dist[bes];
}

```



```

}

vi genCenter() {
    int t = treeDiameter();
    int bes = 0; FOR(i,1,n+1) if (dist[i] > dist[bes])
        bes = i;

    FOR(i,t/2) bes = pre[bes];
    if (t&1) return {bes,pre[bes]};
    return {bes};
}

int main() {
    cin >> n;
    FOR(i,n-1) {
        int a, b; cin >> a >> b;
        adj[a].pb(b), adj[b].pb(a);
    }
    vi x = genCenter();
    for (int i: x) cout << i << " ";
}

```

9.2 Queries

9.2.1 Heavy-Light Set

```

/**
 * Description: offline subtree queries in  $O(N \log^2 N)$ 
 * To verify: January Easy 2018 - Shubham & Tree 1
 */

const int MX = 200001;

struct HeavyLightSet {
    int val[MX];
    vi child[MX];
    map<int,int> dat[MX];

    void comb(int a, int b) {
        bool swa = 0;
        if (sz(dat[a]) < sz(dat[b])) swap(a,b), swa = 1;
        for (auto& x: dat[b]) dat[a][x.f] += x.s;
        dat[b].clear();
        if (swa) swap(dat[a],dat[b]);
    }

    void process(int ind) {
        dat[ind][val[ind]]++;
        for (int i: child[ind]) {
            process(i);
            comb(i,ind);
        }
        // now do stuff with values
    }
};

```

9.2.2 LCA Demo

```

/**
 * Debug the Bugs
 * Description: Use for both LCA's
 */

LCA L;

int Q;

int main() {
    cin >> L.V >> Q >> L.R;
    FOR(i,L.V-1) {
        int u,v; cin >> u >> v;
        L.addEdge(u,v);
    }
    L.construct();

    FOR(i,Q) {
        int u,v; cin >> u >> v;
        cout << L.lca(u,v) << "\n";
    }
}

```

9.2.3 LCA with Binary Jumps

```

/**
 * Source: USACO Camp
 * Verification: Debug the Bugs
 */

const int MAXN = 100001, MAXK = 17;

struct LCA {
    int V, R;
    vi edges[MAXN];
    int parK[MAXK][MAXN];
    int depth[MAXN];

    void addEdge(int u, int v) {
        edges[u].pb(v), edges[v].pb(u);
    }

    void dfs(int u, int prev){
        parK[0][u] = prev;
        depth[u] = depth[prev]+1;
        for (int v: edges[u]) if (v != prev) dfs(v, u);
    }

    void construct() {
        dfs(R, 0);
        FOR(k,1,MAXK) FOR(i,1,V+1)
            parK[k][i] = parK[k-1][parK[k-1][i]];
    }

    int lca(int u, int v){
        if (depth[u] < depth[v]) swap(u,v);
    }
}

```

```

FORd(k,MAXK) if (depth[u] >= depth[v]+(1<<k))
    u = parK[k][u];
FORd(k,MAXK) if (parK[k][u] != parK[k][v]) u =
    parK[k][u], v = parK[k][v];

if(u != v) u = parK[0][u], v = parK[0][v];
return u;
}

int dist(int u, int v) {
    return depth[u]+depth[v]-2*depth[lca(u,v)];
}
};

```

9.2.4 LCA with RMQ

```

/**
 * Description: Euler Tour LCA w/ O(1) query
 * Source: own
 * Verification: Debug the Bugs
 * Dependency: Range Minimum Query
 */

const int MAXN = 100001;

struct LCA {
    vi edges[MAXN];
    RMQ<pi,2*MAXN> r;
    vector<pi> tmp;
    int depth[MAXN], pos[MAXN];

    int V, R;

    void addEdge(int u, int v) {
        edges[u].pb(v), edges[v].pb(u);
    }

    void dfs(int u, int prev){
        pos[u] = sz(tmp); depth[u] = depth[prev]+1;
        tmp.pb({depth[u],u});
        for (int v: edges[u]) if (v != prev) {
            dfs(v, u);
            tmp.pb({depth[u],u});
        }
    }

    void construct() {
        dfs(R, 0);
        r.build(tmp);
    }

    int lca(int u, int v){
        u = pos[u], v = pos[v];
        if (u > v) swap(u,v);
        return r.query(u,v).s;
    }

    int dist(int u, int v) {
        return depth[u]+depth[v]-2*depth[lca(u,v)];
    }
}

```

```
};
```

9.3 Advanced

9.3.1 Centroid Decomposition

```

/**
 * Source: own
 * Verification Problem: Ciel and Commander
 *   (http://codeforces.com/contest/321/problem/C)
 * Code:
 *   (http://codeforces.com/contest/321/submission/33952270)
 */

const int MX = 100001;

int N, visit[MX], sub[MX], par[MX];
vi adj[MX];

void dfs (int no) {
    sub[no] = 1;
    for (int i: adj[no]) if (!visit[i] && i !=
        par[no]) {
        par[i] = no;
        dfs(i);
        sub[no] += sub[i];
    }
}

int get_centroid(int x) {
    par[x] = 0;
    dfs(x);
    int sz = sub[x];
    while (1) {
        pi mx = {0,0};
        for (int i: adj[x]) if (!visit[i] && i !=
            par[x]) mx = max(mx,{sub[i],i});
        if (mx.f*2 > sz) x = mx.s;
        else return x;
    }
}

void solve (int x) {
    x = get_centroid(x); visit[x] = 1;
    // do stuff
    cout << x << "\n";
    for (int i: adj[x]) if (!visit[i]) solve(i);
}

int main() {
    cin >> N;
    FOR(i,N-1) {
        int a,b; cin >> a >> b;
        adj[a].pb(b), adj[b].pb(a);
    }
    solve(1);
}

```

9.3.2 Heavy-Light Decomposition

```

/**
 * Source: http://codeforces.com/blog/entry/22072
 * Dependency: Lazy SegTree
 * Verification: USACO Grass Planting
 */

vector<vi> graph;

template <int V> struct HeavyLight { // sum queries,
    sum updates
    int parent[V], heavy[V], depth[V];
    int root[V], treePos[V];
    LazySegTree<V> tree;

    void init() {
        int n = graph.size();
        FOR(i,1,n+1) heavy[i] = -1;
        parent[1] = -1, depth[1] = 0;
        dfs(1);
        for (int i = 1, currentPos = 0; i <= n; ++i)
            if (parent[i] == -1 || heavy[parent[i]]
                != i)
                for (int j = i; j != -1; j =
                    heavy[j]) {
                    root[j] = i;
                    treePos[j] = currentPos++;
                }
    }

    int dfs(int v) {
        int size = 1, maxSubtree = 0;
        for (auto u : graph[v]) if (u != parent[v]) {
            parent[u] = v;
            depth[u] = depth[v] + 1;
            int subtree = dfs(u);
            if (subtree > maxSubtree) heavy[v] = u,
                maxSubtree = subtree;
            size += subtree;
        }
        return size;
    }

    template <class BinaryOperation>
    void processPath(int u, int v, BinaryOperation op)
    {
        for (; root[u] != root[v]; v =
            parent[root[v]]) {
            if (depth[root[u]] > depth[root[v]])
                swap(u, v);
            op(treePos[root[v]], treePos[v]);
        }
        if (depth[u] > depth[v]) swap(u, v);
        op(treePos[u]+1, treePos[v]); // assumes
            values are stored in edges, not vertices
    }

    void modifyPath(int u, int v, int value) {
        processPath(u, v, [this, &value](int l, int r)
            { tree.upd(l, r, value); });
    }
}

```

```

}

ll queryPath(int u, int v) {
    ll res = 0;
    processPath(u, v, [this, &res](int l, int r) {
        res += tree.qsum(l, r); });
    return res;
}

};

HeavyLight<1<<17> H;
int N,M;

int main() {
    cin >> N >> M;
    graph.resize(N+1);
    FOR(i,N-1) {
        int a,b; cin >> a >> b;
        graph[a].pb(b), graph[b].pb(a);
    }
    H.init();
    FOR(i,M) {
        char c; int A,B;
        cin >> c >> A >> B;
        if (c == 'P') H.modifyPath(A,B,1);
        else cout << H.queryPath(A,B) << "\n";
    }
}

```

10 Math (4)

10.1 Number Theory

10.1.1 Eratosthenes' Sieve

```

/**
 * Source: KACTL?
 * https://open.kattis.com/problems/primesieve
 */

template<int SZ> struct Sieve {
    bitset<SZ+1> comp;
    Sieve() {
        for (int i = 2; i*i <= SZ; ++i) if (!comp[i]) {
            for (int j = i*i; j <= SZ; j += i) comp[j]
                = 1;
        }
    }
    bool isprime(int x) {
        if (x == 1) return 0;
        return !comp[x];
    }
};

```

10.1.2 ModPow

```

ll po (ll b, ll p) { return
    !p?1:po(b*b%MOD,p/2)*(p&1?b:1)%MOD; }
ll inv (ll b) { return po(b,MOD-2); }

```

10.1.3 Phi

```

/**
 * Observation: number of operations needed s.t.
 *              phi(phi(...phi(n)...))=1
 * is O(log n).
 * Euler's theorem:  $a^{\phi(p)} \equiv 1 \pmod{p}$ ,
 * gcd(a,p)=1
 * Verification: CF Power Tower
 */

int phi(int x) {
    if (x == 1) return 1;
    int X = x;

    vi pri;
    for (int i = 2; i*i <= x; ++i) if (x % i == 0) {
        while (x % i == 0) x /= i;
        pri.pb(i);
    }

    if (x > 1) pri.pb(x);
    for (int i: pri) { X /= i; X *= i-1; }
    return X;
}

```

10.1.4 Chinese Remainder Theorem (5)

```

/**
 * Source: Own
 * Verification:
 *   * Kattis generalchineseremainder
 *   * POI 9 Rhyme
 */

struct CRT {
    ll n,m,a,b;
    map<ll,pi> M;
    bool bad;

    ll inv(ll a, ll b) { // 0 < a < b, gcd(a,b) = 1
        a %= b;
        if (a <= 1) return a;
        ll i = inv(b%a,a);
        ll tmp = -((b/a)*i+((b%a)*i)/a) % b;
        while (tmp < 0) tmp += b;
        return tmp;
    }

    ll naive(ll n, ll m, ll a, ll b) {
        ll x = (a-b)*inv(m,n) % n;
        ll ans = (m*x+b) % (m*n);
        while (ans < 0) ans += (m*n);
        return ans;
    }
}

```

```

}

void process(ll a, ll n) {
    vector<pi> z;
    for (int i = 2; i*i <= n; ++i) if (n % i == 0)
        {
            int co = 0;
            while (n % i == 0) n /= i, co++;
            z.pb({i,co});
        }
    if (n != 1) z.pb({n,1});
    for (auto A: z) {
        if (M.count(A.f)) {
            pi p1 = M[A.f];
            pi p2 = {A.s,a%(ll)pow(A.f,A.s)};
            if (p1 > p2) swap(p1,p2);
            if (p2.s%(ll)pow(A.f,p1.f) != p1.s) bad
                = 1;
            M[A.f] = p2;
        } else M[A.f] = {A.s,a%(ll)pow(A.f,A.s)};
    }
}

ll po(ll b, ll p) {
    ll z = 1;
    FOR(i,p) z *= b;
    return z;
}

pl solve(ll aa, ll nn, ll bb, ll mm) {
    bad = 0, M.clear();
    a = aa, n = nn, b = bb, m = mm;
    process(a,n), process(b,m);
    if (bad) {
        cout << "NIE";
        exit(0);
    }
    ll a1 = 0, a2 = 1;
    for (auto& x: M) {
        a1 = naive(a2,po(x.f,x.s.f),a1,x.s.s);
        a2 *= po(x.f,x.s.f);
    }
    return {a1,a2};
}
};

```

10.2 Matrices

10.2.1 Matrix

```

/**
 * Source: KACTL
 * Verification: https://dmoj.ca/problem/si17c1p5
 */

struct mat {
    int** d;
    int a, b;

    mat(int _a, int _b) {

```

```

    a = _a, b = _b;
    d = new int*[a];
    FOR(i,a) {
        d[i] = new int[b];
        FOR(j,b) d[i][j] = 0;
    }
}

mat (vector<vi> v) : mat(sz(v),sz(v[0])) {
    FOR(i,a) FOR(j,b) d[i][j] = v[i][j];
}

void print() {
    FOR(i,a) {
        FOR(j,b) cout << d[i][j] << " ";
        cout << "\n";
    }
    cout << "-----\n";
}

mat operator+(const mat& m) {
    mat r(a,b);
    FOR(i,a) FOR(j,b) r.d[i][j] =
        (d[i][j]+m.d[i][j]) % MOD;
    return r;
}

mat operator*(const mat& m) {
    mat r(a,m.b);
    FOR(i,a) FOR(j,b) FOR(k,m.b)
        r.d[i][k] =
            (r.d[i][k]+(ll)d[i][j]*m.d[j][k]) % MOD;
    return r;
}

mat operator^(ll p) {
    mat r(a,a), base(*this);
    FOR(i,a) r.d[i][i] = 1;

    while (p) {
        if (p&1) r = r*base;
        base = base*base;
        p /= 2;
    }

    return r;
}
};

```

10.2.2 Matrix Inverse (6)

```

/**
 * Description: Calculates determinant mod a prime via
 *              gaussian elimination
 * Usage: CF Stranger Trees
 */

ll po (ll b, ll p) { return
    !p?1:po(b*b%MOD,p/2)*(p&1?b:1)%MOD; }
ll inv (ll b) { return po(b,MOD-2); }

```

```

int mul(ll a, ll b) { return a*b%MOD; }
int sub(ll a, ll b) { return ((a-b)%MOD+MOD)%MOD; }

void elim(mat& m, int a, int c) { // column, todo row
    ll x = m.d[c][a];
    FOR(i,a,m.b) m.d[c][i] =
        sub(m.d[c][i],x*m.d[a][i]);
}

int det(mat& x, bool b = 0) {
    mat m = x;
    ll prod = 1;
    FOR(i,m.a) {
        bool done = 0;
        FOR(j,i,m.a) if (m.d[j][i] != 0) {
            done = 1; swap(m.d[j],m.d[i]);

            if ((j-i)&1) prod = mul(prod,MOD-1);
            prod = mul(prod,m.d[i][i]);

            ll x = inv(m.d[i][i]);
            FOR(k,i,m.b) m.d[i][k] = mul(m.d[i][k],x);
            FOR(k,m.a) if (k != i) elim(m,i,k);
            break;
        }
        if (!done) return 0;
    }
    if (b) x = m;
    return prod;
}

mat inv(mat m) {
    mat x(m.a,2*m.a);
    FOR(i,m.a) FOR(j,m.a) x.d[i][j] = m.d[i][j];
    FOR(i,m.a) x.d[i][i+m.a] = 1;

    det(x,1);

    mat r(m.a,m.a);
    FOR(i,m.a) FOR(j,m.a) r.d[i][j] = x.d[i][j+m.a];
    return r;
}

```

10.3 Combinatorics (5)

10.3.1 Combo Basic

```

/**
 * Source: Own
 * MOD is a large prime
 */

template<int SZ> struct Combo {
    ll fac[SZ+1], ifac[SZ+1];

    Combo() {
        fac[0] = ifac[0] = 1;
        FOR(i,1,SZ+1) {
            fac[i] = i*fac[i-1] % MOD;

```

```

        ifac[i] = inv(fac[i]);
    }
}

11 po (11 b, 11 p) {
    return !p?1:po(b*b%MOD,p/2)*(p&1?b:1)%MOD;
}

11 inv (11 b) { return po(b,MOD-2); }

11 comb(11 a, 11 b) {
    if (a < b) return 0;
    11 tmp = fac[a]*ifac[b] % MOD;
    tmp = tmp*ifac[a-b] % MOD;
    return tmp;
}
};

```

10.3.2 Combo Plus

```

/**
 * Description: Extends combo to a power of a prime
 * Verification: https://dmoj.ca/problem/tle17c4p5
 */

template<int SZ> struct ComboExtended {
    pl fac[SZ+1], ifac[SZ+1], mod;
    11 MOD = 1;

    void init(pl _mod) { // prime, power
        mod = _mod; FOR(i,mod.s) MOD *= mod.f;

        fac[0] = ifac[0] = {1,0};
        FOR(i,1,SZ+1) {
            fac[i] = fac[i-1];
            int I = i, z = 0;
            while (I % mod.f == 0) I /= mod.f, z++;
            fac[i].f = fac[i].f*I%MOD; fac[i].s += z;
            ifac[i] = {inv(fac[i].f,MOD),fac[i].s};
        }
    }

    11 inv(11 a, 11 b) { // 0 < a < b, gcd(a,b) = 1
        a %= b;
        if (a <= 1) return a;
        11 i = inv(b%a,a);
        11 tmp = -((b/a)*i+((b%a)*i)/a) % b;
        while (tmp < 0) tmp += b;
        return tmp;
    }

    11 comb(11 a, 11 b) {
        if (a < b) return 0;
        11 tmp = (fac[a].f*ifac[b].f%MOD)*ifac[a-b].f
            % MOD;
        11 z = fac[a].s-fac[b].s-fac[a-b].s;
        if (z >= mod.s) return 0;
        FOR(i,z) tmp = tmp*mod.f % MOD;
        return tmp;
    }
}

```

```
};
```

10.4 FFT (6)

10.4.1 NTT

```

/**
 * Description: Use if you are working with
 *               non-negative integers
 * Source: KACTL
 * Verification:
 *               http://codeforces.com/contest/632/submission/33953285
 */

int get(int s) {
    return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
}

namespace NTT {
    const 11 mod = (119 << 23) + 1, root = 3; // =
        998244353
    // For p < 2^30 there is also e.g. (5 << 25, 3),
    // (7 << 26, 3),
    // (479 << 21, 3) and (483 << 21, 5). The last two
    // are > 10^9.

    11 modpow(11 b, 11 p) { return
        !p?1:modpow(b*b%mod,p/2)*(p&1?b:1)%mod; }

    11 inv (11 b) { return modpow(b,mod-2); }

    vl ntt(vl& a) {
        int n = a.size(), x = get(n);
        vl res, RES(n), roots(n);
        roots[0] = 1, roots[1] =
            modpow(root,(mod-1)/n);
        FOR(i,2,n) roots[i] = roots[i-1]*roots[1] %
            mod;

        res = a;
        FOR(i,1,x+1) {
            int inc = n>>i;
            FOR(j,inc) for (int k = 0; k < n; k += inc)
                {
                    int t = 2*k%n+j;
                    RES[k+j] = (res[t]+roots[k]*res[t+inc])
                        % mod;
                }
            swap(res,RES);
        }

        return res;
    }

    vl ntt_rev(vl& a) {
        vl res = ntt(a);
        11 in = inv(a.size());
        FOR(i,sz(res)) res[i] = res[i]*in % mod;
        reverse(res.begin() + 1, res.end());
        return res;
    }
}

```

```

    }

    vl brute(vl& a, vl& b) {
        vl c(sz(a)+sz(b)-1);
        FOR(i,sz(a)) FOR(j,sz(b)) c[i+j] =
            (c[i+j]+a[i]*b[j])%mod;
        return c;
    }

    vl conv(vl a, vl b) {
        int s = sz(a)+sz(b)-1, L = get(s), n = 1<<L;
        if (s <= 0) return {};
        if (s <= 200) return brute(a,b);

        a.resize(n); a = ntt(a);
        b.resize(n); b = ntt(b);

        FOR(i,n) a[i] = a[i]*b[i] % mod;
        a = ntt_rev(a);

        a.resize(s);
        return a;
    }
}

int main() {
    vl X = NTT::conv({1,2,3,4,5,6,7,8},
        {1,2,3,4,5,6,7,8});
    for (auto a: X) cout << a << "\n";
}

```

10.5 Polynomials (6)

10.5.1 And Convolution

```

/**
 * Description: Similar to FWHT
 * Source: CSA - FFT And Variations
 */

typedef vector<double> vd;

int get(int s) {
    return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
}

namespace andConv {
    vd andConv(vd P, bool inv = 0) {
        for (int len = 1; 2 * len <= sz(P); len <= 1)
            for (int i = 0; i < sz(P); i += 2 * len) {
                for (int j = 0; j < len; j++) {
                    double u = P[i + j];
                    double v = P[i + len + j];

                    if (!inv) {
                        P[i + j] = v;
                        P[i + len + j] = u + v;
                    } else {
                        P[i + j] = -u + v;

```

```

                        P[i + len + j] = u;
                    }
                }
            }

        return P;
    }

    vd conv(vd a, vd b) {
        int s = max(sz(a),sz(b)), L = get(s), n = 1<<L;
        if (s <= 0) return {};

        a.resize(n); a = andConv(a);
        b.resize(n); b = andConv(b);

        FOR(i,n) a[i] = a[i]*b[i];
        a = andConv(a,1);
        return a;
    }

    vd orConv(vd a, vd b) {
        int s = max(sz(a),sz(b)), L = get(s), n = 1<<L;
        if (s <= 0) return {};

        a.resize(n); reverse(all(a)); a = andConv(a);
        b.resize(n); reverse(all(b)); b = andConv(b);

        FOR(i,n) a[i] = a[i]*b[i];
        a = andConv(a,1);
        reverse(all(a));

        return a;
    }

    vl orConv(vl a, vl b) {
        vd A; for (ll x: a) A.pb(x);
        vd B; for (ll x: b) B.pb(x);
        vd c = orConv(A,B);
        vl C; for (double x: c) C.pb(round(x));
        return C;
    }

    vl conv(vl a, vl b) {
        vd A; for (ll x: a) A.pb(x);
        vd B; for (ll x: b) B.pb(x);
        vd c = conv(A,B);
        vl C; for (double x: c) C.pb(round(x));
        return C;
    }
}

```

10.5.2 Base Conversion

```

/**
 * Description: NTT Application
 * Usage: 2017 VT HSPC - Alien Codebreaking
 */

// NTT template

```

```

struct Base {
    vl po10[21];
    const int base = 27;

    Base() {
        po10[0] = {10};
        FOR(i,1,21) {
            po10[i] = NTT::conv(po10[i-1], po10[i-1]);
            normalize(po10[i]);
        }
    }

    void normalize(vl& x) {
        FOR(i,sz(x)) if (x[i] >= base) {
            if (i == sz(x)-1) x.pb(0);
            x[i+1] += x[i]/base;
            x[i] %= base;
        }
        while (sz(x) && !x.back()) x.pop_back();
    }

    vl convert(vl in) {
        if (sz(in) == 1) return in;
        vl l =
            convert(vl(in.begin(), in.begin()+sz(in)/2));
        vl r =
            convert(vl(in.begin()+sz(in)/2, in.end()));

        r = NTT::conv(r, po10[get(sz(in))-1]);
        normalize(r);

        int z = max(sz(l), sz(r));
        r.resize(z);
        FOR(i,sz(l)) r[i] += l[i];
        normalize(r);
        return r;
    }
};

Base B;

int main() {
    FOR(i,10) FOR(j,10) FOR(k,10) {
        vl z = {k,j,i};
        vl o = B.transform(z);
        for (ll x: o) cout << x << " ";
        cout << "\n";
    }
}

```

10.5.3 FFT

/**
 * Sources: KACTL, <https://pastebin.com/3Tnj5mRu>
 * Verification: SPOJ polymul, CSA manhattan
 */

```
typedef vector<cd> vcd;
```

```

int get(int s) {
    return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
}

namespace FFT {
    vcd fft(vcd& a) {
        int n = a.size(), x = get(n);
        vcd res, RES(n), roots(n);
        FOR(i,n) roots[i] =
            cd(cos(2*M_PI*i/n), sin(2*M_PI*i/n));

        res = a;
        FOR(i,1,x+1) {
            int inc = n>>i;
            FOR(j,inc) for (int k = 0; k < n; k += inc)
                {
                    int t = 2*k%n+j;
                    RES[k+j] = res[t]+roots[k]*res[t+inc];
                }
            swap(res, RES);
        }

        return res;
    }

    vcd fft_rev(vcd& a) {
        vcd res = fft(a);
        FOR(i,sz(res)) res[i] /= a.size();
        reverse(res.begin() + 1, res.end());
        return res;
    }

    vcd brute(vcd& a, vcd& b) {
        vcd c(sz(a)+sz(b)-1);
        FOR(i,sz(a)) FOR(j,sz(b)) c[i+j] += a[i]*b[j];
        return c;
    }

    vcd conv(vcd a, vcd b) {
        int s = sz(a)+sz(b)-1, L = get(s), n = 1<<L;
        if (s <= 0) return {};
        if (s <= 200) return brute(a,b);

        a.resize(n); a = fft(a);
        b.resize(n); b = fft(b);

        FOR(i,n) a[i] *= b[i];
        a = fft_rev(a);

        a.resize(s);
        return a;
    }

    vl convll(vl a, vl b) {
        vcd A(sz(a)); FOR(i,sz(a)) A[i] = a[i];
        vcd B(sz(b)); FOR(i,sz(b)) B[i] = b[i];
        vcd X = conv(A,B);
        vl x(sz(X)); FOR(i,sz(X)) x[i] =
            round(X[i].real());
        return x;
    }
}

```



```

int main() {
    int T; cin >> T;
    FOR(i,T) {
        int N; cin >> N;
        vl a(N+1), b(N+1);
        FOR(j,N+1) cin >> a[N-j];
        FOR(j,N+1) cin >> b[N-j];
        vl x = FFT::conv11(a,b);
        FORd(j,sz(x)) cout << x[j] << " ";
        cout << "\n";
    }
}

```

10.5.4 Interpolation

```

namespace Poly {
    ll norm(ll x) { return (x%MOD+MOD)%MOD; }

    vl operator+(vl a, vl b) {
        a.resize(max(sz(a),sz(b)));
        FOR(i,sz(a)) a[i] = norm(a[i]+b[i]);
        return a;
    }

    vl operator*(vl a, vl b) {
        vl x(sz(a)+sz(b)-1);
        FOR(i,sz(a)) FOR(j,sz(b)) x[i+j] =
            norm(x[i+j]+a[i]*b[j]);
        return x;
    }

    vl operator*(vl a, ll b) {
        for (ll& i: a) i = norm(i*b);
        return a;
    }

    vl interpolate(vector<pl> v) {
        vl ret;
        FOR(i,sz(v)) {
            vl prod = {1};
            ll todiv = 1;
            FOR(j,sz(v)) if (i != j) {
                todiv = norm(todiv*(v[i].f-v[j].f));
                vl tmp = {norm(-v[j].f),1};
                prod = prod*tmp;
            }
            prod = prod*inv(todiv);
            prod = prod*v[i].s;
            ret = ret+prod;
        }
        return ret;
    }

    void prin(vl x) {
        for (ll i: x) cout << i << " ";
        cout << "\n";
    }
}

```

10.5.5 NTT

```

/**
 * Description: Use if you are working with
 *              non-negative integers
 * Verification:
 *              http://codeforces.com/contest/632/submission/33953285
 */

int get(int s) {
    return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
}

namespace NTT {
    const ll mod = (119 << 23) + 1, root = 3; // =
        998244353
    // For p < 2^30 there is also e.g. (5 << 25, 3),
    // (7 << 26, 3),
    // (479 << 21, 3) and (483 << 21, 5). The last two
    // are > 10^9.

    ll modpow(ll b, ll p) { return
        !p?1:modpow(b*b%mod,p/2)*(p&1?b:1)%mod; }

    ll inv (ll b) { return modpow(b,mod-2); }

    vl ntt(vl& a) {
        int n = a.size(), x = get(n);
        vl res, RES(n), roots(n);
        roots[0] = 1, roots[1] =
            modpow(root,(mod-1)/n);
        FOR(i,2,n) roots[i] = roots[i-1]*roots[1] %
            mod;

        res = a;
        FOR(i,1,x+1) {
            int inc = n>>i;
            FOR(j,inc) for (int k = 0; k < n; k += inc)
                {
                    int t = 2*k%n+j;
                    RES[k+j] = (res[t]+roots[k]*res[t+inc])
                        % mod;
                }
            swap(res,RES);
        }

        return res;
    }

    vl ntt_rev(vl& a) {
        vl res = ntt(a);
        ll in = inv(a.size());
        FOR(i,sz(res)) res[i] = res[i]*in % mod;
        reverse(res.begin() + 1, res.end());
        return res;
    }

    vl brute(vl& a, vl& b) {
        vl c(sz(a)+sz(b)-1);
        FOR(i,sz(a)) FOR(j,sz(b)) c[i+j] =
            (c[i+j]+a[i]*b[j])%mod;
    }
}

```

```

    return c;
}

vl conv(vl a, vl b) {
    int s = sz(a)+sz(b)-1, L = get(s), n = 1<<L;
    if (s <= 0) return {};
    if (s <= 200) return brute(a,b);

    a.resize(n); a = ntt(a);
    b.resize(n); b = ntt(b);

    FOR(i,n) a[i] = a[i]*b[i] % mod;
    a = ntt_rev(a);

    a.resize(s);
    return a;
}

int main() {
    vl X = NTT::conv({1,2,3,4,5,6,7,8},
        {1,2,3,4,5,6,7,8});
    for (auto a: X) cout << a << "\n";
}

```

10.5.6 XOR Convolution

```

/**
 * Description: FWHT, similar to FFT
 * Source: CSA - FFT And Variations
 * Verification: HackerRank XOR Subsequence
 */

typedef vector<double> vd;

int get(int s) {
    return s > 1 ? 32 - __builtin_clz(s - 1) : 0;
}

namespace FWHT {
    vd fwht(vd P) {
        for (int len = 1; 2 * len <= sz(P); len <= 1)
            {
                for (int i = 0; i < sz(P); i += 2 * len) {
                    for (int j = 0; j < len; j++) {
                        double u = P[i + j];
                        double v = P[i + len + j];
                        P[i + j] = u+v;
                        P[i + len + j] = u-v;
                    }
                }
            }
        return P;
    }

    vd fwht_rev(vd& a) {
        vd res = fwht(a);
        FOR(i,sz(res)) res[i] /= a.size();
        return res;
    }
}

```

```

}

vd conv(vd a, vd b) {
    int s = max(sz(a),sz(b)), L = get(s), n = 1<<L;
    if (s <= 0) return {};

    a.resize(n); a = fwht(a);
    b.resize(n); b = fwht(b);

    FOR(i,n) a[i] = a[i]*b[i];
    a = fwht_rev(a);
    return a;
}

vl conv(vl a, vl b) {
    vd A; for (ll x: a) A.pb(x);
    vd B; for (ll x: b) B.pb(x);
    vd c = conv(A,B);
    vl C; for (double x: c) C.pb(round(x));
    return C;
}
}

```

11 Graphs Hard (4)

11.1 Kosaraju

```

/**
 * Source: Wikipedia
 * Description: generates SCC in topological order,
 *              support for 2-SAT
 * Verification: POI 8 peaceful commission
 */

int rev(int x) {
    return x&1?x+1:x-1;
}

template<int SZ> struct scc {
    vi adj[SZ], radj[SZ], todo, allComp;
    int N, comp[SZ];
    bitset<SZ> visit;

    void dfs(int v) {
        visit[v] = 1;
        for (int w: adj[v]) if (!visit[w]) dfs(w);
        todo.pb(v);
    }

    void dfs2(int v, int val) {
        comp[v] = val;
        for (int w: radj[v]) if (!comp[w]) dfs2(w,val);
    }

    void addEdge(int a, int b) {
        adj[a].pb(b), radj[b].pb(a);
    }

    void genSCC() {

```

```

    FOR(i,1,N+1) comp[i] = visit[i] = 0;
    FOR(i,1,N+1) if (!visit[i]) dfs(i);
    reverse(all(todo)); // toposort
    for (int i: todo) if (!comp[i]) {
        dfs2(i,i);
        allComp.pb(i);
    }
}

int tmp[SZ];
bitset<SZ> ans;

bool twosat() {
    for (int i = 1; i <= N; i += 2) if (comp[i] ==
        comp[rev(i)]) return 0;
    reverse(all(allComp));
    for (int i: allComp) if (tmp[i] == 0) {
        tmp[i] = 1;
        tmp[comp[rev(i)]] = -1;
    }
    FOR(i,1,N+1) if (tmp[comp[i]] == 1) ans[i]
        = 1;
    return 1;
}
};

```

11.2 Flows

11.2.1 Edmonds-Karp

```

/**
 * Source: GeeksForGeeks
 */

struct Edge {
    int v;
    ll flow, C;
    int rev;
};

template<int SZ> struct EdmondsKarp {
    pi pre[SZ];
    int SC, SNC;
    ll flow[SZ];
    vector<Edge> adj[SZ];

    void addEdge(int u, int v, int C) {
        Edge a{v, 0, C, sz(adj[v])};
        Edge b{u, 0, 0, sz(adj[u])};
        adj[u].pb(a), adj[v].pb(b);
    }

    bool bfs() {
        memset(flow,0,sizeof flow);
        flow[SC] = INF;

        queue<int> todo; todo.push(SC);
        while (todo.size()) {
            if (flow[SNC]) break;
            int x = todo.front(); todo.pop();

```

```

            for (auto a: adj[x]) if (!flow[a.v] &&
                a.flow < a.C) {
                pre[a.v] = {x,a.rev};
                flow[a.v] = min(flow[x],a.C-a.flow);
                todo.push(a.v);
            }
        }

        return flow[SNC];
    }

    ll maxFlow(int sc, int snc) {
        SC = sc, SNC = snc;

        ll ans = 0;
        while (bfs()) {
            ans += flow[SNC];
            for (int x = SNC; x != SC; x = pre[x].f) {
                adj[x][pre[x].s].flow -= flow[SNC];
                int t = adj[x][pre[x].s].rev;
                adj[pre[x].f][t].flow += flow[SNC];
            }
        }

        return ans;
    }
};

```

11.2.2 Flows Demo

```

/**
 * Link: http://www.spoj.com/problems/FASTFLOW/
 * Use with Dinic, Push-Relabel, Edmonds-Karp
 */

int N,M;
PushRelabel<5001> D;

int main() {
    cin >> N >> M;
    FOR(i,M) {
        int a,b,c; cin >> a >> b >> c;
        D.addEdge(a,b,c);
        D.addEdge(b,a,c);
    }
    cout << D.maxFlow(1,N);
}

```

11.2.3 Dinic (5)

```

/**
 * Source: GeeksForGeeks
 * Verification: Problem Fashion (RMI 2017 Day 1)
 * Code: https://pastebin.com/VJxTvEg1
 */

struct Edge {
    int v;

```

```

    ll flow, C;
    int rev;
};

template<int SZ> struct Dinic {
    int level[SZ], start[SZ];
    vector<Edge> adj[SZ];

    void addEdge(int u, int v, int C) {
        Edge a{v, 0, C, sz(adj[v])};
        Edge b{u, 0, 0, sz(adj[u])};
        adj[u].pb(a), adj[v].pb(b);
    }

    bool bfs(int s, int t) {
        FOR(i,SZ) level[i] = -1;
        level[s] = 0;

        queue<int> q; q.push(s);
        while (!q.empty()) {
            int u = q.front(); q.pop();
            for (auto e: adj[u])
                if (level[e.v] < 0 && e.flow < e.C) {
                    level[e.v] = level[u] + 1;
                    q.push(e.v);
                }
        }

        return level[t] >= 0;
    }

    ll sendFlow(int u, ll flow, int t) {
        if (u == t) return flow;

        for ( ; start[u] < sz(adj[u]); start[u]++) {
            Edge &e = adj[u][start[u]];

            if (level[e.v] == level[u]+1 && e.flow < e.C) {
                ll curr_flow = min(flow, e.C - e.flow);
                ll temp_flow = sendFlow(e.v, curr_flow, t);

                if (temp_flow > 0) {
                    e.flow += temp_flow;
                    adj[e.v][e.rev].flow -= temp_flow;
                    return temp_flow;
                }
            }
        }

        return 0;
    }

    ll maxFlow(int s, int t) {
        if (s == t) return -1;
        ll total = 0;

        while (bfs(s, t)) {
            FOR(i,SZ) start[i] = 0;
            while (ll flow = sendFlow(s, INT_MAX, t))
                total += flow;
        }
    }
};

```

```

    }

    return total;
}
};

```

11.2.4 Push-Relabel (5)

```

/**
 * Source: http://codeforces.com/blog/entry/14378
 * Verification: SPOJ fastflow
 */

struct Edge {
    int v;
    ll flow, C;
    int rev;
};

template <int SZ> struct PushRelabel {
    vector<Edge> adj[SZ];
    ll excess[SZ];
    int dist[SZ], count[SZ+1], b = 0;
    bool active[SZ];
    vi B[SZ];

    void addEdge(int u, int v, int C) {
        Edge a{v, 0, C, sz(adj[v])};
        Edge b{u, 0, 0, sz(adj[u])};
        adj[u].pb(a), adj[v].pb(b);
    }

    void enqueue (int v) {
        if (!active[v] && excess[v] > 0 && dist[v] < SZ) {
            active[v] = 1;
            B[dist[v]].pb(v);
            b = max(b, dist[v]);
        }
    }

    void push (int v, Edge &e) {
        ll amt = min(excess[v], e.C-e.flow);
        if (dist[v] == dist[e.v]+1 && amt > 0) {
            e.flow += amt, adj[e.v][e.rev].flow -= amt;
            excess[e.v] += amt, excess[v] -= amt;
            enqueue(e.v);
        }
    }

    void gap (int k) {
        FOR(v,SZ) if (dist[v] >= k) {
            count[dist[v]]--;
            dist[v] = SZ;
            count[dist[v]]++;
            enqueue(v);
        }
    }

    void relabel (int v) {

```

```

    count[dist[v]]--; dist[v] = SZ;
    for (auto e: adj[v]) if (e.C > e.flow) dist[v]
        = min(dist[v], dist[e.v] + 1);
    count[dist[v]]++;
    enqueue(v);
}

void discharge(int v) {
    for (auto &e: adj[v]) {
        if (excess[v] > 0) push(v,e);
        else break;
    }
    if (excess[v] > 0) {
        if (count[dist[v]] == 1) gap(dist[v]);
        else relabel(v);
    }
}

11 maxFlow (int s, int t) {
    for (auto &e: adj[s]) excess[s] += e.C;

    count[0] = SZ;
    enqueue(s); active[t] = 1;

    while (b >= 0) {
        if (sz(B[b])) {
            int v = B[b].back(); B[b].pop_back();
            active[v] = 0; discharge(v);
        } else b--;
    }
    return excess[t];
}
};

```

11.2.5 MinCostFlow (6)

```

/**
 * Source: GeeksForGeeks
 */

struct Edge {
    int v, flow, C, rev, cost;
};

template<int SZ> struct mcf {
    pi pre[SZ];
    int cost[SZ], num[SZ], SC, SNC;
    ll flo, ans, ccost;
    vector<Edge> adj[SZ];

    void addEdge(int u, int v, int C, int cost) {
        Edge a{v, 0, C, sz(adj[v]), cost};
        Edge b{u, 0, 0, sz(adj[u]), -cost};
        adj[u].pb(a), adj[v].pb(b);
    }

    void reweight() {
        FOR(i,SZ) {
            for (auto& p: adj[i]) p.cost +=
                cost[i]-cost[p.v];
        }
    }
};

```

```

    }
}

bool spfa() {
    FOR(i,SZ) cost[i] = MOD, num[i] = 0;
    cost[SC] = 0, num[SC] = MOD;
    priority_queue<pi, vector<pi>, greater<pi>>
        todo; todo.push({0,SC});

    while (todo.size()) {
        pi x = todo.top(); todo.pop();
        if (x.f > cost[x.s]) continue;
        for (auto a: adj[x.s]) if (x.f+a.cost <
            cost[a.v] && a.flow < a.C) {
            pre[a.v] = {x.s,a.rev};
            cost[a.v] = x.f+a.cost;
            num[a.v] = min(a.C-a.flow,num[x.s]);
            todo.push({cost[a.v],a.v});
        }
    }

    ccost += cost[SNC];
    return num[SNC] > 0;
}

void backtrack() {
    flo += num[SNC], ans += (1ll)num[SNC]*ccost;
    for (int x = SNC; x != SC; x = pre[x].f) {
        adj[x][pre[x].s].flow -= num[SNC];
        int t = adj[x][pre[x].s].rev;
        adj[pre[x].f][t].flow += num[SNC];
    }
}

pi mincostflow(int sc, int snc) {
    SC = sc, SNC = snc;
    flo = ans = ccost = 0;

    spfa();
    while (1) {
        reweight();
        if (!spfa()) return {flo,ans};
        backtrack();
    }
}

mcf<100> m;

int main() {
    m.addEdge(0, 1, 16, 5);
    m.addEdge(1, 2, 13, 7);
    m.addEdge(1, 2, 13, 8);

    pi x = m.mincostflow(0,2);
    cout << x.f << " " << x.s;
}

```

11.3 Tarjan BCC

```

/**
 * Source: GeeksForGeeks (corrected)
 * Verification: USACO December 2017, Push a Box
 * Code: https://pastebin.com/yUWuzTH8
 */

template<int SZ> struct BCC {
    int N, ti = 0;
    vi adj[SZ];
    int disc[SZ], low[SZ], comp[SZ], par[SZ];
    vector<vpi> fin;
    vpi st;

    void addEdge(int u, int v) {
        adj[u].pb(v), adj[v].pb(u);
    }

    void BCCutil(int u) {
        disc[u] = low[u] = ti++;
        int child = 0;

        for (int i: adj[u]) if (i != par[u]) {
            if (disc[i] == -1) {
                child++; par[i] = u;
                st.pb({u,i});
                BCCutil(i);
                low[u] = min(low[u], low[i]);

                if ((disc[u] == 0 && child > 1) ||
                    (disc[u] != 0 && disc[u] <=
                     low[i])) { // articulation point!
                    vector<pi> tmp;
                    while (st.back() != mp(u,i))
                        tmp.pb(st.back()),
                        st.pop_back();
                    tmp.pb(st.back()), st.pop_back();
                    fin.pb(tmp);
                }
            } else if (disc[i] < disc[u]) {
                low[u] = min(low[u], disc[i]);
                st.pb({u,i});
            }
        }

        void bcc() {
            FOR(i,1,N+1) par[i] = disc[i] = low[i] = -1;
            FOR(i,1,N+1) if (disc[i] == -1) {
                BCCutil(i);
                if (sz(st)) fin.pb(st);
                st.clear();
            }
        }
    };
};

```

11.4 Euler Tour (6)

```

/**
 * Description: extra log factor

```

```

* Usage: https://open.kattis.com/problems/eulerianpath
*/

```

```

struct Euler {
    vi circuit;
    multiset<int> adj[MX], ADJ[MX];
    int N,M, out[MX], in[MX];

    void find_circuit(int x) { // directed graph,
        // possible that resulting circuit is not valid
        while (sz(adj[x])) {
            int j = *adj[x].begin();
            adj[x].erase(adj[x].begin());
            find_circuit(j);
        }
        circuit.pb(x);
    }

    int a,b,start;

    vi solve() {
        FOR(i,N) {
            adj[i].clear(), ADJ[i].clear();
            out[i] = in[i] = 0;
        }
        circuit.clear();
        FOR(i,M) {
            cin >> a >> b; // add edges
            adj[a].insert(b), ADJ[a].insert(b);
            out[a]++, in[b]++;
        }
        start = a;
        FOR(i,N) if (out[i]-in[i] == 1) start = i;

        find_circuit(start);
        reverse(all(circuit));

        if (sz(circuit) != M+1) return {};

        FOR(i,M) { // verify that circuit is valid
            if (ADJ[circuit[i]].find(circuit[i+1]) ==
                ADJ[circuit[i]].end()) return {};
            int t = circuit[i];
            ADJ[t].erase(ADJ[t].find(circuit[i+1]));
        }

        return circuit;
    }
};

```

12 Geometry (4)

12.1 Techniques

12.1.1 Pair Operators

```

/**
 * Source: own
 */

```

```

template<class T> pair<T,T> operator+(const pair<T,T>&
    l, const pair<T,T>& r) {
    return {l.f+r.f,l.s+r.s};
}

template<class T> pair<T,T> operator-(const pair<T,T>&
    l, const pair<T,T>& r) {
    return {l.f-r.f,l.s-r.s};
}

template<class T> pair<T,T> operator*(const pair<T,T>&
    l, T r) {
    return {l.f*r,l.s*r};
}

template<class T> pair<T,T> operator/(const pair<T,T>&
    l, T r) {
    return {l.f/r,l.s/r};
}

template<class T> double mag(pair<T,T> p) {
    return sqrt(p.f*p.f+p.s*p.s);
}

template<class T> pair<T,T> operator*(const pair<T,T>&
    l, const pair<T,T>& r) {
    // l.f+l.s*i, r.f+r.s*i
    return {l.f*r.f-l.s*r.s,l.s*r.f+l.f*r.s};
}

template<class T> pair<T,T> operator/(const pair<T,T>&
    l, const pair<T,T>& r) {
    // l.f+l.s*i, r.f+r.s*i
    pair<T,T> z =
        {r.f/(r.f*r.f+r.s*r.s),-r.s/(r.f*r.f+r.s*r.s)};
    return l*z;
}

template<class T> double area(pair<T,T> a, pair<T,T>
    b, pair<T,T> c) {
    b = b-a, c = c-a;
    return (b.f*c.s-b.s*c.f)/2;
}

template<class T> double dist(pair<T,T> l, pair<T,T>
    r) {
    return mag(r-l);
}

template<class T> double dist(pair<T,T> o, pair<T,T>
    x, pair<T,T> d) { // signed distance
    return 2*area(o,x,x+d)/mag(d);
}

```

12.1.2 Polygon Area

```

/**
 * Description: Shoelace Formula
 * Usage: https://open.kattis.com/problems/polygonarea

```

```

*/

double area(vector<pi> v) {
    double x = 0;
    FOR(i,sz(v)) {
        int j = (i+1)%sz(v);
        x += (l1)v[i].f*v[j].s;
        x -= (l1)v[j].f*v[i].s;
    }
    return abs(x)/2;
}

```

12.1.3 Line Segment Intersection (5)

```

/**
 * Verification: Kattis segmentintersection
 * If numbers are small enough, fractions are
 * recommended.
 */

pi A,B,C,D;

pd operator*(int x, pd y) {
    return {x*y.f,x*y.s};
}

pd operator/(pd y, int x) {
    return {y.f/x,y.s/x};
}

pd operator+(pd l, pd r) {
    return {l.f+r.f,l.s+r.s};
}

int sgn(pi a, pi b, pi c) {
    return (b.s-a.s)*(c.f-a.f)-(b.f-a.f)*(c.s-a.s);
}

pd get(pi a, pi b, pi c, pi d) {
    return (abs(sgn(a,b,c))*d+abs(sgn(a,b,d))*c)
        /(abs(sgn(a,b,c))+abs(sgn(a,b,d)));
}

void solve() {
    cin >> A.f >> A.s >> B.f >> B.s >> C.f >> C.s >>
        D.f >> D.s;
    if (A > B) swap(A,B);
    if (C > D) swap(C,D);

    int a1 = sgn(A,B,C), a2 = sgn(A,B,D);
    if (a1 > a2) swap(a1,a2);
    if (!(a1 <= 0 && a2 >= 0)) {
        cout << "none\n";
        return;
    }
    if (a1 == 0 && a2 == 0) {
        if (sgn(A,C,D) != 0) {
            cout << "none\n";
            return;
        }
    }
}

```

```

    pi x1 = max(A,C), x2 = min(B,D);
    if (x1 > x2) cout << "none\n";
    else if (x1 == x2) cout << (double)x1.f << " "
        << (double)x1.s << "\n";
    else cout << (double)x1.f << " " <<
        (double)x1.s << " " << (double)x2.f << " "
        << (double)x2.s << "\n";
    return;
}
pd z = get(A,B,C,D);
if (mp((double)A.f,(double)A.s) <= z && z <=
    mp((double)B.f,(double)B.s)) cout << z.f << "
    " << z.s << "\n";
else cout << "none\n";
}

```

12.1.4 Point in Polygon (5)

```

/**
 * Source: own
 * Usage:
 *   https://open.kattis.com/problems/pointinpolygon
 */

int n,m;
pi p[1000];

int area(pi x, pi y, pi z) {
    return (y.f-x.f)*(z.s-x.s)-(y.s-x.s)*(z.f-x.f);
}

bool on(pi x, pi y, pi z) {
    if (area(x,y,z) != 0) return 0;
    return min(x,y) <= z && z <= max(x,y);
}

double get(pi x, pi y, int z) {
    return double((z-x.s)*y.f+(y.s-z)*x.f)/(y.s-x.s);
}

void test(pi z) {
    int ans = 0;
    FOR(i,n) {
        pi x = p[i], y = p[(i+1)%n];
        if (on(x,y,z)) {
            cout << "on\n";
            return;
        }
        if (x.s > y.s) swap(x,y);
        if (x.s <= z.s && y.s > z.s) {
            double t = get(x,y,z.s);
            if (t > z.f) ans++;
        }
    }
    if (ans % 2 == 1) cout << "in\n";
    else cout << "out\n";
}

void solve() {
    FOR(i,n) cin >> p[i].f >> p[i].s;

```

```

    cin >> m;
    FOR(i,m) {
        pi z; cin >> z.f >> z.s;
        test(z);
    }
}

```

12.1.5 3D Geometry (6)

```

/**
 * Description: Basic 3D Geometry
 * Usage: AMPPZ 2011 Cross Spider
 */

typedef vector<ll> vl;

typedef long double ld;

int n;
vector<vl> cur;

vl operator-(vl a, vl b) {
    vl c(sz(a)); FOR(i,sz(a)) c[i] = a[i]-b[i];
    return c;
}

bool ismult(vl b, vl c) {
    if ((ld)b[0]*c[1] != (ld)b[1]*c[0]) return 0;
    if ((ld)b[0]*c[2] != (ld)b[2]*c[0]) return 0;
    if ((ld)b[2]*c[1] != (ld)b[1]*c[2]) return 0;
    return 1;
}

bool collinear(vl a, vl b, vl c) {
    b = b-a, c = c-a;
    return ismult(b,c);
}

vl cross(vl a, vl b) {
    return {a[1]*b[2]-a[2]*b[1],
            a[2]*b[0]-a[0]*b[2],
            a[0]*b[1]-a[1]*b[0]};
}

bool coplanar(vl a, vl b, vl c, vl d) {
    b = b-a, c = c-a, d = d-a;
    return ismult(cross(b,c),cross(b,d));
}

```

12.1.6 Circles (6)

```

/**
 * Source: Own
 * Usage:
 *   https://codeforces.com/tournaments/s8thqrnQL2YPK7XQt/L
 */

typedef complex<double> cd;

```



```
typedef pair<cd,double> circle;

cd intersect(circle a, circle b, int x = 0) {
    double d = sqrt(norm(a.f-b.f));
    double co = (a.s*a.s+d*d-b.s*b.s)/(2*a.s*d);
    double theta = acos(co);

    cd tmp = (b.f-a.f)/d;
    if (x == 0) return a.f+tmp*a.s*polar(1.0,theta);
    return a.f+tmp*a.s*polar(1.0,-theta);
}

double arc(circle x, cd a, cd b) {
    cd d = (a-x.f)/(b-x.f);
    return x.s*acos(d.real());
}

bool on (circle x, cd y) {
    return norm(y-x.f) == x.s*x.s;
}

int main() {
    cout << intersect({0,2},{1,1}) << "\n";
    cout << arc({0,1},cd(1,0),cd(0,1)) << "\n";
    cout << on({0,1},1) << "\n";
}
```

12.2 Sweep Line

12.2.1 Convex Hull

```
/**
 * Source: Wikibooks
 * Usage: https://open.kattis.com/problems/convexhull
 */

ll cross(pi O, pi A, pi B) {
    return (ll)(A.f-O.f)*(B.s-O.s)
        -(ll)(A.s-O.s)*(B.f-O.f);
}

vector<pi> convex_hull(vector<pi> P) {
    sort(P.begin(),P.end());
    P.erase(unique(P.begin(),P.end()),P.end());
    if (P.size() == 1) return P;

    int n = P.size();

    vector<pi> bot = {P[0]};
    FOR(i,1,n) {
        while (bot.size() > 1 &&
            cross(bot[bot.size()-2], bot.back(), P[i])
            <= 0) bot.pop_back();
        bot.pb(P[i]);
    }
    bot.pop_back();

    vector<pi> up = {P[n-1]};
    FORd(i,n-1) {
```

```
        while (up.size() > 1 && cross(up[up.size()-2],
            up.back(), P[i]) <= 0) up.pop_back();
        up.pb(P[i]);
    }
    up.pop_back();

    bot.insert(bot.end(),all(up));
    return bot;
}

int main() {
    int n;
    while (cin >> n) {
        if (n == 0) break;
        vector<pi> P(n); FOR(i,n) cin >> P[i].f >>
            P[i].s;
        vector<pi> hull = convex_hull(P);

        cout << hull.size() << "\n";
        for (auto a: hull) cout << a.f << " " << a.s
            << "\n";
    }
}
```

12.2.2 Closest Pair (6)

```
/**
 * Source: GeeksForGeeks
 * Description:  $N \log^2 N$ , can be improved
 * Use: https://open.kattis.com/problems/closestpair2
 */

pair<double,pair<pdd,pdd>> MN = {INF,{0,0},{0,0}};

int n;

bool cmp(pdd a, pdd b) {
    return a.s < b.s;
}

double dist(pdd a, pdd b) {
    b.f -= a.f, b.s -= a.s;
    return sqrt(b.f*b.f+b.s*b.s);
}

pair<double,pair<pdd,pdd>> strip(vector<pdd> v, double
    di) {
    pair<double,pair<pdd,pdd>> ans = MN;
    FOR(i,v.size()) FOR(j,i+1,v.size()) {
        if (v[i].s+di <= v[j].s) break;
        ans = min(ans,{dist(v[i],v[j]),{v[i],v[j]}});
    }
    return ans;
}

pair<double,pair<pdd,pdd>> bes (vector<pdd> v) {
    if (v.size() == 1) return MN;
    int M = v.size()/2;
    vector<pdd> v1(v.begin(),v.begin()+M),
        v2(v.begin()+M,v.end());
```

```

auto a = bes(v1), b = bes(v2);
double di = min(a.f,b.f);

vector<pdd> V;
FOR(i,v.size()) if (v[i].f > v[M].f-di && v[i].f <
    v[M].f+di) V.pb(v[i]);
sort(V.begin(),V.end(),cmp);

auto z = strip(V,di);
return min(min(a,b),z);
}

int main() {
    cout << fixed << setprecision(2);
    while (cin >> n) {
        if (n == 0) break;
        vector<pdd> v(n);
        FOR(i,n) cin >> v[i].f >> v[i].s;
        sort(v.begin(),v.end());
        auto a = bes(v);
        cout << a.s.f.f << " " << a.s.f.s << " " <<
            a.s.s.f << " " << a.s.s.s << "\n";
    }
}

```

12.2.3 LineContainer (6)

```

/**
 * Source: KACTL
 * Verification: CSA Squared Ends
 */

bool Q;
struct Line {
    mutable ll k, m, p; // slope, y-intercept,
        last optimal x
    bool operator<(const Line& o) const {
        return Q ? p < o.p : k < o.k;
    }
};

struct LineContainer : multiset<Line> {
    const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        if (b < 0) a *= -1, b *= -1;
        if (a >= 0) return a/b;
        return -((-a+b-1)/b);
    }

    // updates x->p, determines if y is unneeded
    bool isect(iterator x, iterator y) {
        if (y == end()) { x->p = inf; return 0; }
        if (x->k == y->k) x->p = x->m > y->m ?
            inf : -inf;
        else x->p = div(y->m - x->m, x->k -
            y->k);
        return x->p >= y->p;
    }
}

```

```

void add(ll k, ll m) {
    auto z = insert({k, m, 0}), y = z++, x
        = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y))
        isect(x, y = erase(y));
    while ((y = x) != begin() && (--x)->p
        >= y->p) isect(x, erase(y));
}

ll query(ll x) { // gives max value
    assert(!empty());
    Q = 1; auto l = *lb({0,0,x}); Q = 0;
    return l.k * x + l.m;
}
};

```

12.3 Max Collinear

```

/**
 * Source: own
 * Usage: https://open.kattis.com/problems/maxcollinear
 */

int n, mx, ans;
map<pair<pi,int>,int> m;
pi p[1000];

pair<pi,int> getline(pi a, pi b) {
    pi z = {b.f-a.f,b.s-a.s};
    swap(z.f,z.s); z.f *= -1;
    int g = __gcd(z.f,z.s); z.f /= g, z.s /= g;
    if (z.f < 0 || (z.f == 0 && z.s < 0)) z.f *= -1,
        z.s *= -1;
    return {z,z.f*a.f+z.s*a.s};
}

void solve() {
    mx = ans = 0; m.clear();
    FOR(i,n) cin >> p[i].f >> p[i].s;
    FOR(i,n) FOR(j,i+1,n) m[getline(p[i],p[j])] ++;

    for (auto a: m) mx = max(mx,a.s);
    FOR(i,1,n+1) if (i*(i-1)/2 <= mx) ans = i;
    cout << ans << "\n";
}

```

13 Additional (4)

13.1 Mo

```

/**
 * Source: Codeforces
 * Description: Answers queries offline in (N+Q)sqrt(N)
 * Also see Mo's on trees
 */

```

```
int block = 300; // set ~sqrt(N)

bool cmp(vi a, vi b) {
    if (a[0]/block != b[0]/block) return a[0] < b[0];
    return a[1] < b[1];
}
```

13.2 Misc

13.2.1 Discrete Logarithm

```
/**
 * Description: find k such that primitive^k=x
 * meet in the middle, O(sqrt(MOD))
 * Source: Own
 * Verification: PA 2006 - Professor Laugh's Numbers
 */

const int BLOCK = 32000;

int primitive = 5, invy[BLOCK];
unordered_map<int,int> u;

ll po (ll b, ll p) {
    return !p?1:po(b*b%MOD,p/2)*(p&1?b:1)%MOD;
}

ll inv (ll b) { return po(b,MOD-2); }

ll query(int x) {
    FOR(i,BLOCK) if (u.count(x*invy[i]%MOD))
        return i*BLOCK+u[x*invy[i]%MOD];
    return -1;
}

int main() {
    ll cur = 1;
    FOR(i,BLOCK) {
        u[cur] = i;
        cur = primitive*cur%MOD;
    }
    ll t = 1;
    FOR(i,BLOCK) {
        invy[i] = inv(t);
        t = t*cur%MOD;
    }
    ll x; cin >> x;
    cout << query(x) << "\n";
}
```

13.3 Pragma Optimization (6)

```
/**
 * Source: Misc solutions to CF Nagini
 * Description: 1010 operations are ok!
 * Passes the occasional disgusting CF task
 * Also see "Welcome home, Chtholly"
 */
```

```
#pragma GCC optimize ("O3")
#pragma GCC target ("sse4")

int q, mx[100001], mn[100001];

int main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);cout.tie(0);
    cin >> q;
    FOR(i,100001) mx[i] = -MOD, mn[i] = MOD;
    FOR(i,q) {
        int t,l,r,k; cin >> t >> l >> r;
        r -= l;

        auto a = mx+l, b = mn+l;
        if (t == 1) {
            cin >> k;
            if (k > 0) FOR(j,r) b[j] = min(b[j],k);
            else FOR(j,r) a[j] = max(a[j],k);
        } else {
            ll ans = 0;
            FOR(j,r) if (a[j] != -MOD && b[j] != MOD)
                ans += b[j]-a[j];
            cout << ans << "\n";
        }
    }
}
```
