

# 1. OpenMP 程序的编译和运行

## 1.1 执行结果：

```
> ./HelloOMP
Hello World from thread 0
Hello World from thread 1
Hello World from thread 2
Hello World from thread 3
Hello World from thread 4
Hello World from thread 5
Hello World from thread 6
Hello World from thread 7
Hello World from thread 8
Hello World from thread 9
Hello World from thread 10
Hello World from thread 11
Hello World from thread 12
Hello World from thread 13
Hello World from thread 14
Hello World from thread 15
Number of threads is 16
```

## 1.2 相关代码：

```
1 #include <iostream>
2 #include <unistd.h>
3 #include <omp.h>
4
5 int main (int argc, char *argv[])
6 {
7     int nthreads, tid;
8
9     omp_set_num_threads(16);
10
11     #pragma omp parallel private(nthreads, tid)
12     {
13         tid = omp_get_thread_num();
14         sleep(tid);
15         std::cout << "Hello World from thread " << tid << std::endl;
16         if (tid == 0) {
17             nthreads = omp_get_num_threads();
18             sleep(nthreads);
19             std::cout << "Number of threads is " << nthreads << std::endl;
20         }
21     }
22
23     return 0;
24 }
```

# 2. 矩阵乘法的 OpenMP 实现与性能分析

## 2.1 串程序执行结果

```

1 > g++ matrix_multi.cpp -o matrix_multi
2 > ./matrix_multi
3 Initialize Matrix_1 finished
4 Initialize Matrix_2 finished
5 Result:
6 Cost time: 121859 ms

```

## 2.2 并行程序版本执行结果

```

1 #pragma omp parallel for shared(a, b, result) private(j, k)
  schedule(dynamic)
2     // #pragma omp parallel for
3     for (i = 0; i < max; i++) {
4         for (j = 0; j < max; j++) {
5             int temp = 0;
6             for (k = 0; k < max; k++) {
7                 temp += a[i][k] * b[k][j];
8             }
9             result[i][j] = temp;
10        }
11    }

```

```

1 > lvim matrix_multi_parallel_v1.cpp
2 > g++ -fopenmp matrix_multi_parallel_v1.cpp -o parallel_v1
3 > ./parallel_v1
4 Initialize Matrix_1 finished
5 Initialize Matrix_2 finished
6 Result:
7 Cost time: 20700 ms
8 The Max of error is :0
9 Average Error is :0

```

我们经过计算可以得到加速比为5.89。

## 2.3 测试性能

### 2.3.1 线程数量一定，矩阵规模不一定

线程数量一定为8；

矩阵大小	200*200	1500*1500	2000*2000	2500*2500
运行时间 (ms)	36	8219	20698	43692

### 2.3.2 矩阵规模一定，线程数量不一定

矩阵规模一定为2000\*2000；

线程数量	1	2	4	8	16
运行时间 (ms)	100610	50251	25862	20698	21643

## 3. 通过积分计算 $\pi$

求出 $\int_0^1 \frac{4}{1+x^2} \frac{d}{dx}$ 的值。

### 2.1 串程序

```
1  #include <iostream>
2  #include <chrono>
3
4  using namespace std;
5
6  static long num_step = 100000000;
7  double step;
8  int main (int argc, char *argv[])
9  {
10     int i;
11     double x, pi, sum = 0.0;
12
13     step = 1.0/(double) num_step;
14
15
16     chrono::milliseconds start_time =
17     chrono::duration_cast<chrono::milliseconds>
18     (chrono::system_clock::now().time_since_epoch());
19     for (i = 0; i < num_step; ++i) {
20         x = (i + 0.5) * step;
21         // x = (i + 0.4) * step;
22         sum = sum + 4.0/(1.0 + x * x);
23     }
24     chrono::milliseconds end_time =
25     chrono::duration_cast<chrono::milliseconds>
26     (chrono::system_clock::now().time_since_epoch());
27     pi = step * sum;
28
29     std::cout << "The result: " << pi << std::endl;
30     cout << "cost time: " << chrono::milliseconds(end_time).count() -
31     chrono::milliseconds(start_time).count() << "ms" << endl;
32
33     return 0;
34 }
```

运行结果：

```
1  > g++ first.cpp -o first
2  > ./first
3  The result: 3.14159
4  cost time: 215ms
```

### 2.2 并程序

```
1  #include <iostream>
2  #include <chrono>
3  #include <omp.h>
```

```

4  using namespace std;
5
6  static long num_step = 100000000;
7  double step;
8  #define NUM_THREADS 8
9  int main (int argc, char *argv[])
10 {
11
12     double pi = 0.0;
13     step = 1.0/(double) num_step;
14     int number;
15
16
17     chrono::milliseconds start_time =
18     chrono::duration_cast<chrono::milliseconds>
19     (chrono::system_clock::now().time_since_epoch());
20     omp_set_num_threads(NUM_THREADS);
21     #pragma omp parallel
22     {
23         int i, id, nthreads;
24         double x, sum;
25         id = omp_get_thread_num();
26         nthreads = omp_get_num_threads();
27         if (id == 0) {
28             number = nthreads;
29         }
30         #pragma omp for
31         for (i = 0; i < num_step; ++i) {
32             x = (i + 0.5) * step;
33             // x = (i + 0.4) * step;
34             sum = sum + 4.0/(1.0 + x * x);
35         }
36         #pragma omp critical
37         pi = step * sum;
38     }
39     chrono::milliseconds end_time =
40     chrono::duration_cast<chrono::milliseconds>
41     (chrono::system_clock::now().time_since_epoch());
42
43     std::cout << "The result: " << pi << std::endl;
44     cout << "cost time: " << chrono::milliseconds(end_time).count() -
45     chrono::milliseconds(start_time).count() << "ms" << endl;
46
47     return 0;
48 }

```

程序执行结果：

```

1  > ./PI_Parallel_v2
2  The result: 3.14159
3  cost time: 52ms

```

我们经过计算可以得到加速比为4.13.