

AMIDST

Analysis of Masslve Data SStreams

Use Cases in Drilling Domain

Sigve Hovda

Postdoctoral Fellow, Norwegian University of Science and Technology
Principal Research Engineer, Verdande Technology

Greetings from Norway!



① Automatic Formation Detection

② Mechanical Specific Energy

① Automatic Formation Detection

② Mechanical Specific Energy



- Optimization of casing positions



- ▶ Optimization of casing positions
- ▶ Identification top and bottom of reservoir




- ▶ Optimization of casing positions
- ▶ Identification top and bottom of reservoir
- ▶ Optimization of drilling parameters

- ▶ Optimization of casing positions
- ▶ Identification top and bottom of reservoir
- ▶ Optimization of drilling parameters
- ▶ Detection of drilling inefficiencies (with MSE)


- ▶ Optimization of casing positions
- ▶ Identification top and bottom of reservoir
- ▶ Optimization of drilling parameters
- ▶ Detection of drilling inefficiencies (with MSE)
- ▶ Better diagnostics of improper hole cleaning, instability and vibration issues

- ▶ Optimization of casing positions
- ▶ Identification top and bottom of reservoir
- ▶ Optimization of drilling parameters
- ▶ Detection of drilling inefficiencies (with MSE)
- ▶ Better diagnostics of improper hole cleaning, instability and vibration issues
- ▶ Important step on the path to automation

- ▶ Manual inspection of:
 - ▶ Petrophysical measurements from the LWD tool
 - ▶ Drilling parameters at the bit
 - ▶ Cuttings analyses at lag depth
 - ▶ Lithology chart




- ▶ Manual inspection of:
 - ▶ Petrophysical measurements from the LWD tool
 - ▶ Drilling parameters at the bit
 - ▶ Cuttings analyses at lag depth
 - ▶ Lithology chart
- ▶ Drawbacks with manual inspection:



-
- GAMMA RAY**
API units
- NEUTRON / DENSITY**
Equiv. SS % porosity
- Depth (feet)
- neutron
- density
- 3000
- 4000
- 5000
- 6000
- 7000
- 8000
- 9000
- 10000
- 11000
- 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1
- Bulk density gm/cc**
- mafic volcanics
gabbro, diabase
felsic ss & cg
siltstone
pegmatite
ACCESSORY MINERALS
cal (calcite); dol (dolomite); ap (epidote); ft (fracture-filling?) quartz, ...


- ▶ Manual inspection of:
 - ▶ Petrophysical measurements from the LWD tool
 - ▶ Drilling parameters at the bit
 - ▶ Cuttings analyses at lag depth
 - ▶ Lithology chart
- ▶ Drawbacks with manual inspection:
 - ▶ Time consuming
 - ▶ Dependent on analysts time schedule




- [illegible]

- ▶ Automatic formation detection at the LWD tool:


- ▶ Automatic formation detection at the LWD tool:
 - ▶ Use Lithology chart from planning as a prior



- ▶ Automatic formation detection at the LWD tool:
 - ▶ Use Lithology chart from planning as a prior
 - ▶ Detect changes in LWD data




- ▶ Automatic formation detection at the LWD tool:
 - ▶ Use Lithology chart from planning as a prior
 - ▶ Detect changes in LWD data
 - ▶ Detect the most likely lithology chart above the LWD tool




- ▶ Automatic formation detection at the LWD tool:
 - ▶ Use Lithology chart from planning as a prior
 - ▶ Detect changes in LWD data
 - ▶ Detect the most likely lithology chart above the LWD tool
- ▶ Automatic formation detection at the bit:


- ▶ Automatic formation detection at the LWD tool:
 - ▶ Use Lithology chart from planning as a prior
 - ▶ Detect changes in LWD data
 - ▶ Detect the most likely lithology chart above the LWD tool
- ▶ Automatic formation detection at the bit:
 - ▶ Use the updated lithology chart as a prior



- ▶ Automatic formation detection at the LWD tool:
 - ▶ Use Lithology chart from planning as a prior
 - ▶ Detect changes in LWD data
 - ▶ Detect the most likely lithology chart above the LWD tool
- ▶ Automatic formation detection at the bit:
 - ▶ Use the updated lithology chart as a prior
 - ▶ Detect *changes* in drilling parameters



- ▶ Automatic formation detection at the LWD tool:
 - ▶ Use Lithology chart from planning as a prior
 - ▶ Detect changes in LWD data
 - ▶ Detect the most likely lithology chart above the LWD tool
- ▶ Automatic formation detection at the bit:
 - ▶ Use the updated lithology chart as a prior
 - ▶ Detect *changes* in drilling parameters
 - ▶ Decide what is the most likely lithology chart above the bit



How to use Information From Offset Data?



- ▶ Investigate formation changes on offset data:

How to use Information From Offset Data?



- ▶ Investigate formation changes on offset data:
- ▶ How is data from formation A different from data from formation B?



How to use Information From Offset Data?



- ▶ Investigate formation changes on offset data:
- ▶ How is data from formation A different from data from formation B?
- ▶ Some easy wins:



- ▶ Investigate formation changes on offset data:
- ▶ How is data from formation A different from data from formation B?
- ▶ Some easy wins:
 - ▶ Some changes involve a clear step in MSE or a clear drilling break

- ▶ Investigate formation changes on offset data:
- ▶ How is data from formation A different from data from formation B?
- ▶ Some easy wins:
 - ▶ Some changes involve a clear step in MSE or a clear drilling break
 - ▶ Some changes involve a more variable MSE (interbedded formations)

- ▶ Investigate formation changes on offset data:
- ▶ How is data from formation A different from data from formation B?
- ▶ Some easy wins:
 - ▶ Some changes involve a clear step in MSE or a clear drilling break
 - ▶ Some changes involve a more variable MSE (interbedded formations)
 - ▶ Some changes involve ECD increase

- ▶ Investigate formation changes on offset data:
- ▶ How is data from formation A different from data from formation B?
- ▶ Some easy wins:
 - ▶ Some changes involve a clear step in MSE or a clear drilling break
 - ▶ Some changes involve a more variable MSE (interbedded formations)
 - ▶ Some changes involve ECD increase
- ▶ And there are data driven approaches...

Data Driven Approach to Formation Detection



► Classification problem

Offset data
from formation A


Offset data
from formation B

Realtime data
from formation A


Realtime data
from A or B



► Classification problem




► Classification problem




- Classification problem
- Data is time series




- ▶ Classification problem
- ▶ Data is time series
- ▶ Data is control response pairs
 - ▶ Flow \rightarrow pressure
 - ▶ RPM \rightarrow torque
 - ▶ WOB, RPM, flow \rightarrow ROP



- ▶ Classification problem
- ▶ Data is time series
- ▶ Data is control response pairs
 - ▶ Flow -> pressure
 - ▶ RPM -> torque
 - ▶ WOB, RPM, flow -> ROP
- ▶ Solution: Dynamic Bayesian networks (Kalman filters)



- ▶ Classification problem
- ▶ Data is time series
- ▶ Data is control response pairs
 - ▶ Flow -> pressure
 - ▶ RPM -> torque
 - ▶ WOB,RPM,flow -> ROP
- ▶ Solution: Dynamic Bayesian networks (Kalman filters)



① Automatic Formation Detection

② Mechanical Specific Energy

► Definition:

$$MSE(d) = \frac{\sum_{k \in S} W_k d_k + \frac{\pi}{30} \sum_{k \in S} T_k N_k t_k}{\pi r^2 \sum_{k \in S} d_k}$$

S is set of data points that are measured less than a distance $b/2$ from the current depth d . d_k and t_k are depth and time increments. W_k , T_k and N_k are weight, torque and rotation speed at measurement k .

- Definition:

$$MSE(d) = \frac{\sum_{k \in S} W_k d_k + \frac{\pi}{30} \sum_{k \in S} T_k N_k t_k}{\pi r^2 \sum_{k \in S} d_k}$$

S is set of data points that are measured less than a distance $b/2$ from the current depth d . d_k and t_k are depth and time increments. W_k , T_k and N_k are weight, torque and rotation speed at measurement k .

- MSE is a measure of compression strength of the formation, but also how effective the drilling operation is.

- Definition:

$$MSE(d) = \frac{\sum_{k \in S} W_k d_k + \frac{\pi}{30} \sum_{k \in S} T_k N_k t_k}{\pi r^2 \sum_{k \in S} d_k}$$

S is set of data points that are measured less than a distance $b/2$ from the current depth d . d_k and t_k are depth and time increments. W_k , T_k and N_k are weight, torque and rotation speed at measurement k .

- Challenges with this measure:
 - What is downhole torque? Estimate from surface or differential pressure?
 - Drifting of WOB. When is it calibrated?
 - How to set the smoothing parameter b ?

- Definition of normalised RMS-measure:

$$RMS = \frac{\sum_{i=1}^n (S_i - f(MSE_i))^2}{\sum_{i=1}^n (S_i)^2}$$

S_i is sonic measurements (or equivalent) at i and f is some monotone function.

- Definition of normalised RMS-measure:

$$RMS = \frac{\sum_{i=1}^n (S_i - f(MSE_i))^2}{\sum_{i=1}^n (S_i)^2}$$

S_i is sonic measurements (or equivalent) at i and f is some monotone function.

- RMS is a measure of how well the shape of MSE fits the shape of the sonic data.

- ▶ Definition of normalised RMS-measure:

$$RMS = \frac{\sum_{i=1}^n (S_i - f(MSE_i))^2}{\sum_{i=1}^n (S_i)^2}$$

S_i is sonic measurements (or equivalent) at i and f is some monotone function.

- ▶ RMS is a measure of how well the shape of MSE fits the shape of the sonic data.
- ▶ Advantages:
 - ▶ More intuitive interpretation of MSE graphs when compared with downhole data.
 - ▶ Potential input to formation detection at the bit algorithm.

This project has received funding from the European Union's Seventh Framework Program for research, technological development and demonstration under grant agreement no 619209