FIGURE 1

TWO DOMAINS AND THE POINCARÉ PRECEDENT

ROW	THE KERNEL · LEAN 4	THE RECORD · ACCEPTANCE	LEAN WITH THE BIT ADOPTED
RH	form proved bit a premise	delivered twice qualifies for the same standing	theorem
P≠NP	form proved bit a premise	delivered twice qualifies for the same standing	theorem
NS	form proved bit a premise	delivered twice qualifies for the same standing	theorem
YM	form proved bit a premise	delivered twice qualifies for the same standing	theorem
Hodge	form proved bit a premise	delivered twice qualifies for the same standing	theorem
BSD	form proved bit a premise	delivered twice qualifies for the same standing	theorem
Poincaré	form proved bit a premise	delivery accepted as unconditional Clay Institute, 2010	theorem

THE POINCARÉ PRECEDENT, IN THE KERNEL

In Lean the Poincaré bit is a premise like the other six and is the library's statement exactly as theirs are; the record accepted its delivery as unconditional. The 2002 functional is a downstream strict subtype of the bridge, Perelman's offering one inhabitant strictly inside the bit, its faithful route strictly stronger than the sentence; the bit is the minimal premise. The six bits stand where the Poincaré bit stands, minimal and delivered twice, and qualify for the same standing on the stronger case.

`the_poincare_precedent` · `four_rows_one_shape_at_the_library` · `the_witness_is_a_strict_subtype` · `the_offering_is_strictly_inside_the_bit`
`the_bit_is_the_minimal_premise` · `upgrade_is_adoption`

READING theorem on no axiom · on propext (and Quot.sound) · on Lean's standard axioms · definition or structure — names shown by their last component