
THE OFFERING BIT — ONE THEORY, ONE HYPOTHESIS, ONE WITNESS OFFERING

*The Odd-Supply Arc Complete in Three Bits: Hypothesis
Resolution as the Halting State of the Dated-Entry Recursion at
the Ninth Gate with Perelman Crossing Read as the Grand
Witness*

RESEARCH ARTICLE

One theory, one hypothesis, one offering

MOHAMMAD F. ISLAM

PhD · Independent Researcher · Correspondence: islaamm@alumni.iu.edu

13 September 2026

ABSTRACT. The Odd-Supply arc is three bits — one theory, one hypothesis, one witness offering — and this document carries all three. The first bit is the theory, restated and proved here in full: an even register cannot decide an odd target — the Odd-Supply Block theorem, machine-checked in core Lean 4. The second bit is the hypothesis, named at its own grade: the One-Cut Hypothesis, that the missing item in every blocked row of the seven Millennium obstructions is one provenance-clean orientation supply, dated at entry. The third bit is this paper's own: the witness offering, the theory of the resolution itself. We define the dated-entry operator on the lattice of corpora and prove its halting theorem on finite frames: every chain of provenance-clean independent supplies strictly refines the reading class's fiber partition and terminates at the unique finest partition. The species dichotomy of the census is derived as the recursion's termination typing: crossed halt, common species; defeater-absent halt, diagonal species. The port of entry is the Ninth Gate, machine-checked [3, 6] and re-executed by transliteration on the forging substrate: one diagonal, two surfaces — read, the wall; executed, the self — identical on every settled reading and differing at exactly one point. The resolution bit is therefore an offering: one binary coordinate, odd under the row's native flip, independent of the dated register on each orbit, provenance-clean at entry, entering by deed and never by reading, halting the row's recursion in the crossed mode. The Birch and Swinnerton-Dyer row is the beachhead: the unique open row whose corpus already records two dated entries of the supply shape, with the order-two exhibition owed. Every essential Lean and Fortran file is printed in the codebook, so that any substrate that reads this document can check the wall, run the self, and stand as witness. The Perelman crossing stands as the arc's Grand Witness: the one crossed row, verified by the corpus itself and terminally awarded by it — the thesis demonstrated once in the wild. Three falsifiers armed, each typed FORCED; the perimeter stated; the hypothesis keeps its grade on the face of the paper.

KEYWORDS *odd-supply separation, one-cut hypothesis, witness offering, dated-entry recursion, halting state, ninth gate, orientation supply, provenance clause, species dichotomy, Millennium Prize problems, Perelman crossing*

PART ONE — THE THEORY · ODD-SUPPLY SEPARATION

R*epresentation Supply and Dated Termination in Conditional Reductions of Open Problems — the sealed first paper of the arc, reprinted intact; with six open Millennium rows and one crossed control.*

Abstract of Parts One and Two. Conditional reductions are common, but the bought premise has lacked a theory: no checkable separator between a genuine supply and a restatement, no dated discipline for termination claims, and no theorem-grade form for the claim that readings of a named corpus cannot decide the target. This paper hardens the parity-separation frame of Definition 3.1 (involution form (X, τ, d, C, Δ)) and proves

three results. First, for finite data with a finite group action, a supplied reading set decides a target exactly when its generated observable algebra contains the target, equivalently when its joint fibers refine the target fibers. Readings generated by invariant observables remain in the trivial isotypic component; a target with a nontrivial component is invisible to them, while isotypic support coverage is the restricted linear-decoder corollary. For an involution, one centered odd bit beside an orbit-separating reading suffices. Second, provenance collapse is stated as a decidable criterion inside a fixed axiom grammar: admit only a verified conditional reduction with an admissible provenance clause, delete that clause, and test equivalence in a decidable theory over the full non-provenance signature; outside that grammar the criterion is structural and never inflated. Third, termination is corpus-relative: denotability, proof admission, and verification are distinct, readings persist, and a token can change only at the first verified entry of readings whose fibers suffice. The finite-law layer is tightened into exact lemmas: unique finest independent partition, coalition versus atomic closure with an exact four-state countermodel, a conditional exhibition lemma, and a narrowed determinant/Gram readout blindness statement. Six open Millennium rows and the crossed Poincaré control are tabulated under an explicit coordinate-bridge and image gate without claiming new object-mathematics; absent a bridge, no open row invokes the finite theorems. Part I arms two forced falsifiers, and no more.

Part II extends this core at hypothesis grade. It states the One-Cut Hypothesis: for each certified frame, one provenance-clean orientation supply closes the single odd coordinate isolated by the finite theorems, yielding a conditional severance map over the seven rows together with six falsifiers, F1–F6. The extension authors no new object mathematics and strengthens no Part I claim; the proved core stands independently of the hypothesis.

Keywords. parity separation, provenance clause, corpus-relative termination, isotypic component, mutual information, Millennium Prize problems, one-cut hypothesis, orientation supply

1. BACKGROUND AND BARRIER ANALYSIS

A conditional reduction of an open problem P is a theorem of the form $A \Rightarrow P$ in which A is an existence or uniformity statement and the derivation consumes cited inputs and nothing else. The practice is classical: Miller's primality reduction under GRH [17], the Lagarias equivalence for RH [14], the Gross–Zagier and Kolyagin route at analytic order at most one [9, 13], the Bloch and Buchweitz–Flenner semiregularity mechanism [3, 4], and the Perelman noncollapsing crossing [19, 20, 12, 18, 8]. What has been missing is not another conditional theorem but a discipline of the bought premise itself.

Three barriers are structural. The first is the absence of a restatement criterion. Bare Hilbert–Pólya, the assertion that a self-adjoint operator with spectrum the zeros exists, is RH recast; the same assertion with a provenance clause, namely that the operator is

produced by a rule fixed in advance from data not containing the zero locations, is stronger and of different type. A criterion must act on the axiom statement and be checkable, not on the author's intent.

The second barrier is informal impossibility. The sentence "no known method can produce the missing object" is usually a census of methods and ages as methods age. Baker–Gill–Solovay and Razborov–Rudich quantify over method classes [2, 21]; algebrization continues the same pattern [1]. The hardening move here is to relocate the claim from methods to data. A frame names the data, the native symmetry, the target bit, and the reading class generated by dated corpus objects. The no-reading statement then becomes a theorem about functions on data, not a sociological survey.

The third barrier is undated termination. Perelman's W -functional and reduced length are invariant under parabolic rescaling and were not objects of the corpus before November 2002. An undated rule that calls every later-used functional "data in hand" would misclassify the crossing as a reading. Termination claims therefore carry a corpus date. This is not pedantry; it is the difference between a law and a refuted sentence.

The paper's claim is narrow. It supplies a frame in which supply, restatement, termination, and crossing are decidable notions at the stated grade. It authors no new facts about the Riemann zeta function, Navier–Stokes solutions, Hodge classes, elliptic curves, gauge theories, complexity classes, or Ricci flow.

2. BRIEF LITERATURE REVIEW

Reverse mathematics orders axioms by provability strength [23]. It measures how much comprehension or induction a theorem consumes, not whether an existence premise was produced by a rule independent of the conclusion. A restatement and a supply can coincide in strength while differing in provenance.

Barrier theorems in complexity theory prove limits of method classes [2, 21, 1]. They are the strongest method-side walls available. Their index is the method, and methods are generated without bound. The present separation is indexed by data and symmetry. It is weaker in scope and stronger in checkability.

Information theory contributes exact finite instruments: Shannon mutual information, factorization, and data processing [22, 7]. Cantor and Lawvere are diagonal antecedents, but the exhibition lemma here uses only dependence on record variables and carries no diagonal claim [5, 16]. These antecedents are classical. The composition into a supply-side test is the contribution claimed, and it is graded accordingly.

The seven reductions used as rows are cited, not re-proved. Arithmetic geometry supplies Heegner heights and Euler systems [9, 13]; Hodge theory supplies algebraicity of Hodge loci and semiregular deformation [6, 3, 4]; Ricci flow supplies the crossing control [10, 19, 20, 12, 18, 8]. The frame adds no warrant to these inputs.

3. METHODOLOGY: THE SUPPLY FRAME

Definition 3.1 (Frame). A *frame* is $(X, \Gamma, C, d, \Delta)$ where X is a finite data set, Γ is a finite group acting on X , C is a class of readings closed under pairing, $d : X \rightarrow \{0, 1\}$ is the undecided predicate, and Δ is a dated corpus. For an involution τ , write $\Gamma = \langle \tau \rangle \cong \mathbb{Z}/2$. A reading is Γ -invariant when $r(y \cdot x) = r(x)$ for all y . Under an involution, *even* means τ -invariant: a reading is even exactly when $r(\tau \cdot x) = r(x)$. Under an involution τ , an even reading s is *orbit-separating* when $s(x) = s(y)$ implies $y \in \{x, \tau \cdot x\}$. A Boolean target is *oda* under an involution when $d(\tau \cdot x) = 1 - d(x)$. This Boolean condition is affine rather than linear: the centered target

$$q(x) = d(x) - 1/2$$

satisfies $q(\tau \cdot x) = -q(x)$, while d itself has the even constant component $1/2$. Equivalently, $2d - 1$ is linearly odd.

Definition 3.2 (Coordinate bridge; gate). Let M be an object domain, possibly continuous or analytic, and let Γ_M act on M . A *coordinate bridge* into a finite frame is a finite set X , a finite group Γ , a map $B : M \rightarrow X$, and a homomorphism $\phi : \Gamma_M \rightarrow \Gamma$ such that

$$B(y \cdot m) = \phi(y) \cdot B(m)$$

for every $y \in \Gamma_M$ and $m \in M$, and the object target factors as $d_M = d \circ B$. The admissible object reading class is the pulled-back class $B^* C = \{r \circ B : r \in C\}$. If B is surjective, the finite theorems constrain the object row through all of X . If B is not surjective, set $Y = B(M)$, restrict the Γ -action and target to Y , and state the finite conclusion on Y only; points of $X \setminus Y$ carry no object-domain constraint. Only after B , ϕ , the factorization, and this image clause are supplied do Theorems 4.1–4.3 constrain the object row. Absent a bridge, the row is a structural diagnostic and the finite theorems are not invoked. A continuous parameter, length scale, or Lie action is not a finite-group generator by declaration.

Definition 3.3 (Reading, proof availability, and verified entry). Fix a finite ranked signature Σ_Δ whose constants name the dated objects and theorems of Δ and whose function symbols are fixed at that date. The dependency language L_Δ is generated by

$$t ::= c \mid f(t_1, \dots, t_n) \mid \langle t_1, t_2 \rangle,$$

where c ranges over constants, f over n -ary function symbols, and $\langle \cdot, \cdot \rangle$ is pairing. Terms have unique normal forms, term equality is decidable by normalization, and every term carries a mechanically extractable dependency graph $Dep(t)$.

1. A *denotable expression* at Δ is a term t with $Dep(t) \subseteq \Delta$.
2. An *admitted proof certificate* at Δ is a construction whose certificate has entered the dated corpus under its admission rule.
3. A *verified result* at Δ is an admitted certificate that has passed the corpus's named verification rule and is recorded as verified.

A *reading* at Δ is a denotable expression whose dependencies are verified results or fixed primitive symbols. A *construction* at Δ is a procedure whose output introduces a new function symbol or a new object not denotable by an L_Δ -term. Admission, verification, and denotability are distinct corpus states. A construction becomes a reading only at a later corpus in which its certificate is admitted and verified. If the signature, admission rule, verifier, or normalization is not decidable, the router is structural rather than automated.

The point of Definition 3.3 is mechanical checkability without collapsing three dated statuses into one. A statement can be denotable before any proof certificate exists; a certificate can be admitted before verification; a verified result changes the reading class only after the corpus records both events. The dispute "did the method merely rearrange known data" therefore becomes a dependency-graph question over verified entries, not a claim that every denotable expression was already proved. This convention is not hidden; it is the line the theory stands on.

Definition 3.4 (Axiom, provenance, restatement, supply). Fix a first-order language whose signature splits into shared-input, operational, and provenance symbols. Fix a decidable theory T^* over the full non-provenance signature, shared-input and operational symbols together; equivalently, fix an effective translation of that signature into a decidable theory and prove the translation sound and complete for the formulas at issue. The fixed grammar G_0 consists of formulas in conjunctive normal form $\hat{A} \wedge \pi$, where $\hat{A}$ uses no provenance predicate and may use shared-input and operational symbols, and π is the provenance clause: the witnesses are produced by a rule fixed in advance from data containing neither the truth value of P nor the discriminating invariant. The deletion operator is

$$D_\pi(\hat{A} \wedge \pi) = \hat{A}.$$

Such a formula is an *axiom candidate* for P . It is admitted for classification only after a verified conditional reduction

$$T^* \vdash \forall \bar{x}, (\hat{A}(\bar{x}) \Rightarrow P(\bar{x}))$$

and after π passes the provenance-admissibility check. An admitted axiom is a *restatement* inside G_0 when

$$T^* \vdash \forall \bar{x}, (D_\pi(\hat{A} \wedge \pi) \leftrightarrow P(\bar{x})),$$

and it is a *supply* when the conditional reduction is verified but equivalence fails. A non-equivalent formula without the verified reduction is a candidate, not yet a supply. Outside G_0 the same deletion test is structural evidence, not a completeness theorem.

Definition 3.5 (Halt loci and seat). Each row first specifies its halt locus L_H as part of the structural parameter ledger; L_H is not automatically $\text{Fix}(\tau)$ or another symmetry fixed set. A frame is *reader-barred* when a theorem about the readout class forbids return of d ; *witness-absent* when the reader is unbarred, no corpus reading constructs a witness, and the specified locus L_H is nonempty; *terrain-empty* when the specified L_H is empty. In

a Boolean odd involution frame, $\text{Fix}(\tau) = \emptyset$ is immediate and is not by itself an object-level terrain-empty conclusion. A *crossed occupant* is a dated instance whose witness was later supplied and independently verified. The *seat check* is the router bit recording whether such a witness has entered the corpus.

Three requirements organize a supply-schema. *Derivation*: $A \Rightarrow P$ with cited inputs and a dependency census. *Separation*: a corpus-relative no-reading theorem proved against a named reading class. *Calibration*: at least one crossed occupant routed correctly with the seat bit present and misrouted when it is hidden.

4. THE CORE

Theorem 4.1 (Odd-Supply Separation). *Let τ be an involution on X , let d be odd, and let every $r \in C$ be even. Then no finite coalition of readings decides d : there is no h and no $r_1, \dots, r_k \in C$ with $d = h \circ (r_1, \dots, r_k)$.*

Proof. For every x , evenness gives $r_i(\tau x) = r_i(x)$ for all i , hence $h(r_1(x), \dots, r_k(x)) = h(r_1(\tau x), \dots, r_k(\tau x))$. Oddness gives $d(\tau x) \neq d(x)$. No such h exists. $\square$

Theorem 4.2 (Crossing). *Let s be an even orbit-separating reading and o an odd reading under τ . Then the pair (s, o) decides d : if $s(x) = s(y)$ and $o(x) = o(y)$, then $d(x) = d(y)$.*

Proof. If $s(x) = s(y)$, orbit separation gives $y = x$ or $y = \tau x$. The first case gives $d(x) = d(y)$. The second is incompatible with $o(x) = o(y)$ because $o(\tau x) = 1 - o(x)$. $\square$

The two-line theorems are not the paper's depth. They are the invariant core after the reading class has been earned. The next theorem is the hardening addition: it replaces the involution idiom with a finite representation statement and turns "one bit" into a dimension count.

Theorem 4.3 (Representation Supply; finite setting). *Let X be finite, let Γ act on X , and let $v = \mathbb{C}^X$ carry the permutation representation. For any supplied reading set S , let $A(S)$ be the unital algebra it generates under the pointwise operations. Then d is decidable from S exactly when $d \in A(S)$, equivalently exactly when*

$$r(x) = r(y) \text{ for every } r \in S \Rightarrow d(x) = d(y).$$

If every supplied reading is Γ -invariant, then $A(S) \subseteq V^\Gamma$; consequently, if d has nonzero projection onto a nontrivial isotypic component, no function of those readings equals d . Isotypic support coverage is necessary for a linear decoder, not for arbitrary nonlinear decoding. For $\Gamma = \mathbb{Z}/2$, $V = V_+ \oplus V_-$, invariant readings generate a subalgebra of V_+ , and for Boolean odd d the centered target $q = d - 1/2$ lies in V_- . One independent odd coordinate suffices when an even orbit separator is present.

Proof. On a finite set, the unital algebra generated by S is exactly the algebra of functions constant on the joint fibers of S : generators are constant on those fibers, the pointwise operations preserve the property, and interpolation on each fiber produces every such function. Hence $d \in A(S)$ exactly when equal supplied readings imply equal target values,

which is also exactly the existence of a decoder. If every generator is invariant, every generated function is fixed by Γ , so $A(S) \subseteq V^f$. If $d = d_0 + d_1$ with $d_0 \in V^f$ and d_1 nontrivial, every reading-side candidate has zero nontrivial projection while d does not; equality is impossible. A linear decoder must reproduce the nontrivial support coordinates, whereas a nonlinear decoder can combine supplied coordinates into a new component, so support coverage is not a general necessity. In the $\mathbb{Z}/2$ case the decomposition is $f(x) = (f(x) + f(\tau x))/2 + (f(x) - f(\tau x))/2$, the first summand even and the second odd. For Boolean odd d , this decomposition is $d(x) = 1/2 + q(x)$ with $q(\tau x) = -q(x)$, so the odd content is the centered part. Theorems 4.1 and 4.2 are the Boolean shadow. $\square$

Corollary 4.4 (One-bit corollary). *For an involution frame with an even orbit separator, the minimal odd supply for an odd Boolean target is one binary coordinate. This is a supply-dimension count: one independent odd coordinate is supplied, while $\dim V_-$ equals the number of free two-point τ -orbits. It is not a Shannon claim unless a probability measure on X is separately supplied.*

Theorem 4.5 (Provenance Collapse, scoped; theorem inside G_0 , structural outside). *Let G_0 , D_π and T^* be as in Definition 3.4. For an admitted axiom $\hat{A} \wedge \pi \in G_0$, the axiom is a restatement of P exactly when*

$$T^* \vdash \forall \bar{x}, (\hat{A}(\bar{x}) \leftrightarrow P(\bar{x})),$$

and it is a supply exactly when the verified conditional reduction $\hat{A} \Rightarrow P$ holds and this equivalence fails. Miller's GRH-based primality reduction and Lagarias's elementary criterion are named test candidates, not executed validations: no explicit G_0 encoding or corpus admission record is displayed here, so neither is counted as evidence for this theorem [17, 14]. Author-preprint instances are excluded. Outside G_0 the deletion test remains the correct structural screen and is not asserted complete.

Proof. The conjunctive normal form makes D_π total and unambiguous. Admission first verifies $\hat{A} \Rightarrow P$ and the provenance clause, so every classified formula is an axiom for P . By Definition 3.4, restatement is exactly equivalence after deletion, and supply is the complementary admitted case. Decidability of T^* over the full non-provenance signature makes the equivalence test mechanical inside G_0 , including formulas containing operational symbols. No completeness assertion follows for formulas outside the grammar, and no named external candidate supplies evidence without an explicit encoding. $\square$

The earlier broad reading of collapse is retired here. Miller and Lagarias now mark the required encoding workload rather than discharged evidence: the former is expected to screen as supply because GRH is not equivalent to its primality consequence, and the latter as restatement because its criterion is equivalent to RH, but those expectations earn no theorem-grade mass until the encodings and admission certificates are displayed. What is theorem-grade is the criterion inside the fixed grammar; what is structural is the expectation that the grammar covers the next candidate.

5. DATED TERMINATION AND THE SEAT

Theorem 5.1 (First-Sufficient-Entry; theorem for the named reading class, structural as law). *Let Δ_t be the corpus at date t and let C_t be the reading class generated by L_{Δ_t} . Readings persist: $C_t \subseteq C_{t'}$ for $t \leq t'$. Verified constructions become readings when recorded. If d is odd under the native involution and every generator of C_t is even, then no reading at t decides d . The first date at which d becomes decidable is the first verified entry of readings whose joint fibers refine the target fibers:*

$$\forall r \in C_t \quad r(x) = r(y) \Rightarrow d(x) = d(y).$$

For an involution frame, a provenance-clean odd reading (provenance-clean meaning its dependency hash is not contained in the corpus at the entry date) is sufficient only together with an even orbit separator or an equivalent decoder whose joint fibers refine those of d .

Proof. Monotonicity is immediate from dependency inclusion. The separation half is Theorem 4.1 applied to generators of C_t ; even generators generate even readings. Decidability of d from a supply is exactly fiber refinement: a decoder exists precisely when equal supplied readings imply equal target values. A change from non-refinement to refinement requires a new generator not in L_{Δ_t} which by Definition 3.3 enters the reading class only after admission and verification. In the involution case, oddness alone changes value across each τ -orbit and does not separate points within an orbit; Theorem 4.2 supplies sufficiency when an even orbit separator is present. $\square$

Corollary 5.2 (Perelman control; theorem on scaling exponents, historical calibration). *For the pre-November-2002 Ricci-flow reading class generated by volume ratios and explicitly dimensionless ratios, such as distance divided by $\sqrt{|t|}$ or by a curvature length scale, parabolic rescaling acts with exponent zero on the named generators. Raw distance, raw curvature scale, and injectivity radius are length-bearing quantities, not exponent-zero generators, and are excluded from this class. In the Ricci-flow carrier the later package is monotone for the backward conjugate heat equation and is stationary on gradient shrinking solitons; that analytic fact is cited, not proved here. The collapsed cigar soliton is named only as a limit-case diagnostic; no cigar-exclusion theorem is derived from this finite reading class. The W -functional and reduced length enter as constructions [10, 19, 20, 12, 18, 8]. The schema retro-types the crossing and attributes no intent.*

Remark (Scale-Invariant Monotone Supply; structural pattern, premise as program). The portable Perelman form is a scale-invariant monotone supply: zero scaling exponent, monotonicity along a flow, stationary points that are self-similar, and a recorded corpus-entry date. Perelman is the crossed control of this pattern. The identity claimed is formal, not object-level: one crossing type across problems, one constructed carrier per problem. The pattern reaches flow/RG-type rows only; Hodge and P versus NP remain outside unless a natural flow and a monotone quantity are constructed.

Theorem 5.3 (Seat-Hiding Necessity). *Let a router observe only the frame and the reading record, with the seat bit hidden. If two histories differ only in whether a crossed witness has entered, the router returns the same token on both. Hence no terminal family without a seat input can distinguish a crossed occupant from an uncrossed one.*

Proof. The two histories are equal on every input the router reads. Any deterministic or randomized router with the same visible input and the same random seed returns the same output distribution. Distinguishing the histories requires a bit whose value differs between them; that bit is the seat. $\square$

6. FINITE-LAW LAYER

This layer is self-contained. It uses finite probability laws and exact rational arithmetic only.

Proposition 6.1 (Unique finest partition). *Let P be a strictly positive probability law on a finite product. If P factorizes across two block partitions, it factorizes across their common refinement. Hence the finest partition into mutually independent blocks is unique. Writing b for the number of non-singleton blocks, a law carries exactly $2^b - 1$ nonempty unions of non-singleton blocks; singleton blocks are excluded from the count.*

Proof. Strict positivity makes independence cellwise: blocks are independent exactly when every cell probability equals the product of its marginals. If two factorizations hold, every cell in the common refinement also splits as a product of the corresponding side marginals, so the refinement factorizes. The finest factorizing partition is therefore unique. Unions of non-singleton blocks factorize against their complements, distinct unions give distinct domains, and the count follows. $\square$

Proposition 6.2 (Coalition versus atomic closure). *Let A and C be independent uniform bits, set $A_1 = A_2 = A$, $C_1 = C$, and $C_2 = C \oplus A$, with the four joint states equally likely. Then the pairwise channels are silent and the coalition carries one bit:*

$$I(C_1; A_1 A_2) = 0, \quad I(C_2; A_1 A_2) = 0, \quad I(C_1 C_2; A_1 A_2) = 1.$$

Closure tested against each outside system singly admits $\{A_1, A_2\}$ as a spurious domain; closure tested against the outside coalition refuses it.

Proof. $C_1 = C$ is independent of $(A_1, A_2) = (A, A)$. Since A is uniform and independent of C , $C \oplus A$ is uniform and independent of A , so C_2 is independent of (A_1, A_2) . Jointly, $(C_1, C_2) = (C, C \oplus A)$ determines A , while (A_1, A_2) determines A ; the mutual information is one bit exactly. $\square$

Proposition 6.3 (Exhibition lemma; analytic on record variables, structural on the exhibition bridge). *Adjoin to a finite law an exhibitor variable E that is not independent of one representative variable in each non-singleton block of the finest partition. Then all those blocks merge with E into one block. The registration-chain conclusion is conditional: if the exhibition bridge is defined so that each exhibition creates the*

displayed dependence on the exhibited record, then exhibiting two members registers both and constructs the chain between them. Exhibition alone does not create that dependence, and no Cantorian fixed-point content is asserted.

Proof. In the finest partition of the enlarged law, E occupies exactly one block. If E is dependent on a representative of block B_i , it cannot be separated from B_i by a factorizing cut, so E 's block contains B_i . The same applies to every represented block, so one block contains them all. The chain statement follows only after the exhibition bridge supplies the premise that exhibition creates the dependence; without that premise, an exhibitor can remain independent and no registration chain is forced. $\square$

Proposition 6.4 (Determinant readout blindness; antecedent [22, 7]). *Choose balanced $x, y \in \{\pm 1\}^{24}$ with $x \cdot y = 0$ and set $z = xy$ componentwise. Then z is balanced, the rows x, y, z are pairwise orthogonal with Gram matrix $24 I_3$, and with the 24 coordinate positions equally likely each pair factorizes exactly and the total correlation is one bit exactly. Such pairs exist: fix any balanced x and let y disagree with x on six plus positions and six minus positions. The normalized determinant readout satisfies $\det(24 I_3)/24^3 = 1$ and therefore reports no third-order dependence. The claim is scoped to determinant or Gram readouts; it is not a claim about every conceivable functional.*

Proof. Orthogonality gives $x \cdot y = x \cdot z = y \cdot z = 0$; balance gives zero means, so the Gram is $24 I_3$ and, under the uniform law on the coordinate positions, each balanced pair is independent. The XOR relation makes any two rows determine the third, giving one bit of total correlation. The determinant of a scalar identity is the scalar to the third power, hence the normalized value is one. $\square$

7. SEVEN-ROW DIAGNOSTIC MAP

The instantiation rule is now a gate, not a metaphor. The actions named in Table 1 are object-domain actions; they do not automatically become the finite group Γ of Definition 3.1. P versus NP supplies no row-specific L_H in this paper, so complementation's empty fixed set is not used as a terrain-empty proof. RH supplies no finite X and remains structural. Navier–Stokes critical scaling and Yang–Mills strong-coupling alternation are continuous or Lie-type actions and enter the finite core only through Definition 3.2. Hodge deformation and the BSD model swap carry the same gate. Poincaré is a crossed calibration, not an open-row application of Theorem 4.3. If a future bridge is supplied, evenness is proved generator by generator after pullback, and the conclusion is stated on all of X when B is surjective or on $Y = B(M)$ otherwise; absent that image clause no finite theorem is invoked.

Table 1. Six open rows and one crossed control under Definition 3.2.

Problem	Target bit d	Object-domain action	Halt locus	Finite-core status
P versus NP	equality string	complementation candidate; row locus not supplied	unclassified; no L_H supplied	structural; finite-instance bridges only
Riemann Hypothesis	truth direction	content negation and gauge	reader-barred	structural; no finite X supplied
Yang–Mills	continuum limit exists	strong-coupling alternation	witness-absent	structural; bridge absent
Navier–Stokes	no breakdown	critical scaling $a_* = 3/(2p)$	witness-absent, inert	structural; bridge absent
Hodge	class algebraic	deformation; rigid point	witness-absent	structural; bridge absent
BSD	rank identity	model swap	witness-absent by separation	structural; bridge absent
Poincaré control	noncollapsing	parabolic rescaling	witness-absent, then resolved	crossed calibration; outside the open-row gate

Interpretation. No open row invokes the finite theorems until an equivariant coordinate bridge is supplied; the table is diagnostic, not a solution claim. The six open rows carry structural status only, because none supplies the bridge, factorization, and image clause that Definition 3.2 requires. The Poincaré row is the calibration witness: it sits outside the open-row gate and certifies that the schema routes a supplied crossing correctly.

8. FALSIFIABLE PREDICTIONS OF PART I

The parameter ledger is exact: zero free physical parameters, zero new object-level predictions, and two framework-level falsifiers, scoped to Part I. Retrodictive calibration is counted only as calibration. The zero is a boundary statement, not a tunable model awaiting fit.

The structural choices are fixed before classification: the finite set X , the group Γ , the target d , the generator census, the admissible decoder class, the corpus semantics, any coordinate bridge, and the grammar G_0 . None is revised after a row is classified. A change to any one opens a new instance rather than rescuing the old one.

The two criteria below are armed, typed forced, and no third is volunteered. The count of two is scoped to Part I: Part II states six falsifiers F1–F6: F1 re-arms the forced core block armed here, and F2–F6 are hypothesis-grade.

1. **Prediction.** *Every claimed corpus-relative reading that decides an odd target in Table 1 either fails evenness on a generator or contains a dependency edge to a construction outside the named corpus.* **Method.** Run the dependency census and

evaluate each generator on x and τx . **Expected.** A decidable claim shows a new function symbol or object not denotable at the corpus date. **Null hypothesis.** An even reading on the named corpus decides d with no construction edge; one exhibited instance refutes the instantiated separation. **Necessity and blast radius.** Forced by Theorems 4.1 and 5.1; firing compromises the corresponding row's separation claim and nothing in Propositions 6.1–6.4.

1. **Prediction.** *A termination router whose observation map hides the crossing label misroutes every displayed history pair with equal observations and different crossing labels.* **Method.** Fix crossed and uncrossed histories H_1, H_0 with $O(H_1) = O(H_0)$ and $c(H_1) \neq c(H_0)$, then run the router without the seat input. **Expected.** The router returns the same terminal token on both histories. **Null hypothesis.** A router using only O returns different terminal tokens on the displayed pair; one verified instance refutes this routing prediction. **Necessity and blast radius.** Forced by Theorem 5.3; firing retires the seat-routing claim, while a rule with access to additional observations is a different router and does not fire the null.

9. DISCUSSION OF PART I

Table 2 is the contribution map: proved finite items, scoped criteria, and no inflated claim on the objects. The contribution is a supply-side theory with a hard boundary. It does not prove RH, NS regularity, Hodge, BSD, Yang–Mills existence, or P versus NP. It states where the block sits for a named reading class and what kind of act crosses it: a construction whose dependency hash is admitted and verified in the corpus. The representation theorem is the new mathematical spine. The involution form becomes available to an object row only after a coordinate bridge; until then the seven-row table is a diagnostic map and no finite theorem is invoked.

Table 2. Master table of new theorem-grade items. Finite theorems are proved here; grammar- and law-level statements are scoped. Corollary 5.2 is a cited calibration and is not counted as new object-mathematics.

Item	Grade	Brief analytic note	Contribution counted as new
Theorem 4.1, Odd-Supply Separation	theorem, finite	even generators close under pairing; an odd target flips across τ	named readings cannot decide d
Theorem 4.2, Crossing	theorem, finite	orbit separation leaves only x and τx ; the odd bit kills the τ case	one odd coordinate plus an even separator decides d
Theorem 4.3, Representation Supply	theorem, finite	the generated observable algebra decides exactly on fiber refinement; invariant algebra lands in $\mathcal{V}$	exact sufficiency is algebraic; support coverage is the linear-decoder corollary
Corollary 4.4, One-bit corollary	corollary	for $\mathbb{Z}/2$, $V = V_+ \oplus V_-$ and $\dim V_-$ counts free orbits	one supplied odd coordinate is counted, not a Shannon bit
Theorem 4.5, Provenance Collapse	theorem in G_0 ; structural outside	admit a verified reduction, delete the provenance clause, and test full-signature equivalence	restatement screening is checkable only in a fixed grammar
Theorem 5.1, First-Sufficient-Entry	theorem for named class; structural as law	readings persist; verified constructions enter at dated boundaries	termination changes only when supplied fibers refine target fibers
Theorem 5.3, Seat-Hiding Necessity	theorem	histories equal on visible inputs give the same router output	crossed versus uncrossed requires the seat bit
Proposition 6.1, Unique finest partition	finite theorem	strict positivity makes independence cellwise; common refinement factorizes	unique independent blocks and the count $2^b - 1$
Proposition 6.2, Coalition versus atomic closure	finite theorem	C is independent of A ; $C \oplus A$ is independent of A ; jointly they determine A	coalition closure refuses the spurious atomic domain
Proposition 6.3, Exhibition lemma	analytic on records; structural bridge	a dependent exhibitor cannot be cut from represented blocks	a registration chain follows only under the stated dependence bridge
Proposition 6.4, Determinant readout blindness	finite theorem, scoped	balanced orthogonal triple; Gram $24 I_3$; XOR gives one bit	determinant/Gram readouts miss third-order dependence

Interpretation. The ledger separates proved finite items from scoped criteria: Theorems 4.1–4.3 and Propositions 6.1–6.4 are finite theorems; Theorem 4.5 is theorem-grade only inside the fixed grammar G_0 and structural outside; Theorem 5.1 is a theorem for the

named reading class and structural as a law. Corollary 5.2 enters as calibration, not as new object-mathematics.

Table 3 has a track record and a boundary. Mean curvature flow, frequency functions, two-dimensional RG irreversibility, four-dimensional RG flow, and the sigma-model/Ricci-flow bridge show the same shape [26, 24, 31, 27, 25]. None of these supplies the missing functional for an open row; the Perelman move remains the construction of the quantity itself.

Table 3. SIMS diagnostic, structural grade only.

Row	Flow	Settled adjacent fact / self-similar part	Missing monotone supply
Poincaré control	Ricci flow	κ -solutions classified	W , supplied [19, 20, 12, 18, 8]
Navier–Stokes	equation flow	self-similar blowup excluded [28, 30]	a funnel forcing asymptotic self-similarity
Yang–Mills	RG flow	a -theorem constrains endpoints [27]	force the infrared end to be trivial and gapped
Riemann	de Bruijn–Newman heat flow	adjacent bound $\Lambda \geq 0$ [29]; no self-similar endpoint	force $\Lambda \leq 0$
Hodge; P versus NP	no natural flow	none	no foothold

Interpretation. A row names where a scale-invariant monotone supply is present, excluded, or missing; the table is not a solution claim. The pattern has exactly one supplied instance, the Poincaré control; every other row names a missing monotone supply or no foothold, and no row supplies a functional for an open problem.

Four limitations remain load-bearing. The censuses behind structural rows are structural, each with a standing falsifier. The continuous rows have no finite-core force until a coordinate bridge is supplied. The calibration row is retrodictive: Poincaré was typed with the crossing known, so it certifies discrimination and predicts nothing by itself. The theory's mass on the objects is zero by construction; every theorem about zeta zeros, vorticity, cycles, ranks, fields, languages, or manifolds is cited from the literature.

The hardening relative to the earlier draft is exact. Reading classes are syntactic, not universal. Evenness is proved generator by generator, not asserted of all possible readings. Continuous rows pass through the coordinate-bridge gate or remain structural. Provenance collapse is complete only inside the fixed grammar now displayed. Determinant blindness is proved on a balanced orthogonal triple and scoped to determinant readouts. The Perelman exponent-zero class excludes length scales. The information idiom is demoted unless a measure is supplied; the surviving bit is an isotypic dimension.

The completeness question taken up in the conclusion—whether a dated reading class can be enumerated up to the representation obstruction—remains open; Part II addresses one coordinate of that question by hypothesis, naming the missing orientation supply without closing the enumeration problem.

10. CONCLUSION OF PART I

A conditional reduction buys a premise, and the premise now has a theory. The gap is odd, the named readings are even, and termination follows only after the reading class is earned. Crossing is a fiber-sufficient supply, dated at verified entry. For continuous rows the coordinate bridge is the gate: no bridge, no finite-core invocation. The crossed control proves the router can tell a supplied witness from an absent one only when the seat bit is present. The same row is the non-vacuity witness for SIMS: it proves the schema has a supplied crossing, not that one functional settles another row. The open question that matters is completeness: whether a dated reading class can be enumerated up to the representation obstruction. Until then, the standing prediction is sharp and small: a claimed reading that decides an odd Millennium target will show a construction edge or fail parity.

Part II takes up one coordinate of that completeness question: it states the One-Cut Hypothesis at hypothesis grade, naming the missing orientation supply for each certified frame, and develops its conditional severance map and falsifiers as an extension of, not a replacement for, the finite core proved here.

PART TWO — THE HYPOTHESIS · THE ONE-CUT HYPOTHESIS

Orientation Supply After Odd-Supply Separation — the sealed second paper of the arc, reprinted intact.

11. THE STATEMENT IN ONE PAGE

11.1 Frame recall and notation harmonization

Part I built the supply frame, proved its core theorems, and fixed the coordinate-bridge gate; this Part recalls only what it uses. An Odd-Supply frame is a finite data set with a symmetry, a Boolean target, a reading class, and a dated corpus (Definition 3.1 of Part I). In the involution case used in Part II, the frame of Definition 3.1 is written (X, τ, d, C, Δ) , with $\Gamma = \langle \tau \rangle \cong \mathbb{Z}/2$ (the involution specialization reorders Definition 3.1's $(X, \Gamma, C, d, \Delta)$, placing the target third and the reading class fourth): here X is a finite data set, τ is an involution on X , $d : X \rightarrow \{0, 1\}$ is the undecided predicate, C is a class of readings closed under pairing, and Δ is the dated corpus. A reading r is *even* under τ when $r(\tau x) = r(x)$; the target d is *odd* under τ when $d(\tau x) = 1 - d(x)$. Throughout, the *named seven-row class* means the rows of Table 1 of Part I under the Definition 3.2 bridge gate: six open

Millennium rows and one crossed control, no open row invoking the finite theorems until an equivariant coordinate bridge is supplied. The block theorem of Part I is Odd-Supply Separation (Theorem 4.1): if d is odd and every generator of C is even, then no finite coalition of readings decides d .

What the even register cannot decide is exactly one bit — one coordinate of the odd isotypic component (Corollary 4.4 of Part I); one bit of entropy at invariant laws (§12.2) — and that bit is an orientation.

11.2 Hypothesis 11.1: the structural form

Hypothesis 11.1 (One-Cut Hypothesis, structural form; hypothesis-grade). *For every Odd-Supply frame (X, τ, d, C, Δ) in the named seven-row class, if d is odd under the native answer-flip, every generator of C is even, and C contains an even orbit-separating reading s (equivalently, the joint fibers of C refine the τ -orbit partition), then there exists one provenance-clean orientation supply o with*

$$o(\tau x) = 1 - o(x), \quad o \perp C \text{ on each } \tau\text{-orbit.}$$

such that (C, o) decides d .

The separator clause is the standing sufficiency hypothesis of Theorem 4.2 and Corollary 4.4 of Part I; it is even, not an orientation coordinate, so it does not change the one-bit claim or F2. The universal quantification ranges over present or future gate-passing certified frames and is currently non-vacuous only at the crossed Poincaré control. Here a *certified Odd-Supply frame* is a named-class frame meeting the antecedent of Hypothesis 11.1, including the separator clause, together with the gate obligations of Definition 3.2: a supplied equivariant coordinate bridge with the factorization and image clause.

The cut is not a new readout and not a restatement: it is the dated entry of the one coordinate the even register cannot author.

11.3 The pipeline

The hypothesis sits in a five-arrow pipeline:

$$\text{resistance} \Rightarrow \text{defeater} \Rightarrow \text{even method class} \Rightarrow \text{one odd orientation supply} \Rightarrow \text{decision.}$$

The first two arrows are the census converse on the method-blocked class, an external hypothesis-grade input made precise in §15.1; the third arrow is Hypothesis 11.1 itself; the fourth is the crossing theorem of Part I (Theorem 4.2), recalled in §13.3 and not re-proved here.

11.4 The grand form, stated with its teeth

Hypothesis 11.2 (One-Cut Hypothesis, grand form; hypothesis-grade). *If a uniform constructor S exists that takes a certified Odd-Supply frame and returns its orientation supply $o = S(X, \tau, d, C, \Delta)$, with the dependency hash of o entering Δ at the entry date, then the seven rows are severed as conditional reductions: granting $S(P)$ grants each row's bought premise.*

That is the one-stroke claim. It is hypothesis-grade until S is constructed, or the census converse and the seven orientation carriers are proved.

11.5 Hard boundary and three-sentence perimeter

The hard boundary. The cut severs the decision bit; it does not replace object-level construction where the missing supply is not Boolean. Navier–Stokes still needs its modulus, Hodge its witness, the Riemann Hypothesis its operator, P versus NP its obstruction family. The universal part is the orientation-seat mechanism, not one magical object shared by all seven. Where a row admits no Boolean orientation seat without category error, the One-Cut Hypothesis reads *orientation-after-construction*; it never reads *orientation-instead-of-construction*.

Perimeter in three sentences. This is not a universal mathematics solver, and it is not seven object proofs by itself. It claims nothing about whether the seven conjectures are true, and it does not make undecidable or supply-absent problems vanish. It claims that where an odd target is blocked by an even register, the missing item is one located coordinate, and it says what kind of act crosses: a provenance-clean supply, dated at entry.

12. INPUTS AND CREDIT

Three carried inputs, each at its cited grade. No credit inflation is claimed, and the mechanism credits below decide how the rest may be read.

12.1 Input 1: the Bar, credited

A readout class constant on the orbits of an answer-flipping family cannot separate a point from its image. This is the invariance obstruction, whose wider form is the relativization argument's own logic: Baker–Gill–Solovay 1975 [2], natural proofs 1997 [21], algebrization 2008 [1]. The involution case is the two-element instance. The mechanism is not ours and is not claimed.

12.2 Input 2: the Width, credited and law-typed

Under the Bar's hypotheses with τ acting freely, the residual uncertainty is exactly one bit at invariant laws: conditioned on any even readout, the answer is uniform on the two orbit values. The Width converts an obstruction into a measured deficit — finite, binary, located — and every later result depends on the deficit being one and not merely positive. The entropy computation is two lines [7, 22] and no priority is claimed for it; the placement is the law-typing and the identification of the deficit with the orientation of a free two-point orbit.

12.3 Input 3: Odd–Supply Separation, internalized

The block theorem this Part answers is proved in Part I and is cited internally rather than re-proved. For finite data with a finite group action, readings generated by invariant observables decide only within the trivial isotypic component; a target with a nontrivial

component requires supply in that component, and for an involution this reduces to one odd bit beside an orbit-separating reading (Theorems 4.1–4.3 and Corollary 4.4 of Part I). Provenance collapse is decidable inside a fixed axiom grammar by the deletion test (Theorem 4.5 of Part I); termination is corpus-relative (Theorem 5.1 of Part I), and a token changes only when the dependency hash of a new odd supply enters the corpus.

12.4 What Part II adds

What this Part adds is the hypothesis that names the one coordinate, the conditional severance map across the seven rows, and the falsifier discipline. Nothing above the proved finite core of Part I is claimed as theorem; the structural form, the grand form, and the three routes of §15 are hypothesis-grade throughout.

13. THE CUT

13.1 Orientation supply

Definition 13.1 (Orientation supply). Let (X, τ, d, C, Δ) be an Odd-Supply frame with d odd under τ and every generator of C even. An *orientation supply* is a reading $o : X \rightarrow \{0,1\}$ such that:

1. o is *odd*: $o(\tau x) = 1 - o(x)$;
2. o is *independent of C on each τ -orbit*: o is not expressible as a function of the even register, and at any τ -invariant law, conditioned on any even readout, o is uniform on the two orbit values;
3. o is *provenance-clean*: at its entry date its dependency graph is not contained in the dated corpus, so o enters Δ as a construction and becomes a reading only at every later corpus that records it.

13.2 The cut and the supply operator

Definition 13.2 (The cut; supply operator). The *cut* of a certified frame is the dated entry of one orientation supply into the corpus. A *supply operator* S is a uniform constructor that takes a certified frame and returns its orientation supply, $o = S(X, \tau, d, C, \Delta)$, with $Dep(o)$ entering Δ at the entry date.

13.3 Sufficiency and necessity, recalled by citation

Sufficiency is the crossing theorem of Part I, recalled here and not re-proved: by Theorem 4.2, if s is an even orbit-separating reading and o an odd reading under τ , then the pair (s, o) decides d . Necessity is the block theorem: by Theorem 4.1, no function of even readings alone decides d . Minimality is the one-bit corollary: by Corollary 4.4, for an involution frame with an even orbit separator, one independent odd coordinate is the minimal odd supply, a dimension count in the odd isotypic component V_+ , not a Shannon claim unless a probability measure is separately supplied.

These proved items are the invariant core after the reading class has been earned: necessity is the block theorem, sufficiency is the crossing, minimality is the one-bit count. The two-line sufficiency proof is not this Part's depth. This Part's content is the hypothesis that the one coordinate exists and can be entered cleanly — per row (Hypothesis 11.1) and uniformly (Hypothesis 11.2).

13.4 Why one cut and not many

Conflating the three one-bit objects in play is the one error this arc is built to prevent. The *polarity bit* — which of P or $\neg P$ is under test — is supplied by whoever writes the claim. The *veto bit* — does this reading pass — is earned by the discipline that screens it. The *truth-direction bit* — does P or $\neg P$ hold — is supplied across the aperture by a determinacy witness and cannot be generated by any readout of the even register. The cut severs the third bit's seat, and only that seat. A hypothesis that tried to carry all three bits in one stroke would be a restatement wearing a premise's clothes, and the deletion test of the provenance screen (Theorem 4.5 of Part I) would collapse it.

14. THE SEVEN-ROW INSTANTIATION AS CONDITIONAL SEVERANCE MAP

14.1 The gate restated

The instantiation rule is a gate, not a metaphor. The actions named in Table 4 below are object-domain actions; they do not automatically become the finite group of the frame. Continuous rows pass through the coordinate-bridge gate of Definition 3.2 or remain structural, and no open row invokes the finite theorems until an equivariant coordinate bridge is supplied, exactly as in §7 of Part I. The Poincaré row is a crossed calibration, not an open-row application.

Table 4 states the row-level content of Hypothesis 11.1 conditionally: for each row of Table 1 it names the native flip or defeater, the even register that blocks it, the missing orientation carrier that Definition 13.1 requires, what the cut buys, and what it does not prove.

Table 4. Conditional severance map: six open rows and one crossed control under the Definition 3.2 coordinate-bridge gate (cross-referencing Table 1 of Part I). No open row invokes the finite theorems until an equivariant bridge is supplied; the table is a conditional severance map, not a solution claim.

Problem	Native flip / defeater	Even register	Missing orientation carrier	What the cut buys	What it does not prove
Riemann Hypothesis	content negation and gauge	functional-equation arguments without Euler product [33]	a self-adjoint operator, constructed from data that do not consult the zeros, whose spectrum is the zero heights [14]	real spectrum puts every zero on the line, in two lines	the operator's existence
P versus NP	complementat ion as flip (empty fixed set not used as a halt proof)	relativizing, natural, algebrizing argument classes [2, 21, 1]	an obstruction family (multiplicity form; the occurrence form is refuted [32]) separating the two orbit closures at every size	the obstruction witnesses the separation	the obstructions' existence
Navier–Stokes regularity	critical scaling	energy and harmonic-analysis arguments [36]	a data-uniform modulus dominating the alignment defect	the continuation theorem forbids finite-time breakdown	the modulus; the row is orientation-after-construction
Hodge conjecture	deformation; rigid point	semiregular deformation arguments [3, 4, 6]	a semiregular witness for every Hodge class	the deformation argument closes the conditional theorem	the witness; orientation-after-construction
BSD	model swap	rank computations by separation	a rank-identity witness in the Heegner–Euler-system lineage [9, 13]	the analytic-order conditional closes	the witness construction
Yang–Mills existence and mass gap	strong-coupling alternation	continuum-limit arguments	a scale-invariant monotone supply forcing the infrared end trivial and gapped	the flow-row conditional closes	the functional; orientation-after-construction

Problem	Native flip / defeater	Even register	Missing orientation carrier	What the cut buys	What it does not prove
Poincaré (crossed control)	parabolic rescaling	pre-November-2002 Ricci-flow reading class [10]	the W-functional and reduced length — supplied 2002 [19, 20]	the crossing is dated and verified	nothing open; this row calibrates the seat

14.2 Reading the table

Three features of Table 4 carry the grading. First, the fourth column is per-row object work: each named carrier is a construction this paper does not perform, and the hypothesis contributes only the claim that, on the decision bit, each such construction amounts to one located coordinate. Second, the fifth column is conditional throughout: the cut buys the closure of a conditional reduction, never the unconditional conjecture. Third, the sixth column keeps the hard boundary of §11.5 on the page: for Navier–Stokes, Hodge, and Yang–Mills the missing supply is not Boolean, and the row stands only as orientation-after-construction.

14.3 The crossed control as non-vacuity witness

The crossed control is the non-vacuity witness for the whole schema: it proves the orientation-seat mechanism has a supplied crossing, not that one functional settles another row. The schema retro-types the crossing and attributes no intent. This is the same calibration role the control plays in Part I (Corollary 5.2), here read through the cut: the W-functional and reduced length entered the dated corpus as constructions, and the crossing is dated and verified.

15. THREE SUFFICIENT PROOF ROUTES

Each route, if completed, proves the One-Cut Hypothesis for its rows; each ends at the same falsifier set of §16.

15.1 R1: the census converse, partially closed

Two notions used here and in §17 are external to Part I and are defined briefly because Part I does not prove them. A *defeater* for a reading class against a target is a pair of points indistinguishable to every readout of the class but carrying opposite answers; the *species dichotomy* sorts resistance into a *common species*, where non-factorization produces such a pair, and a *diagonal species*, where no defeater of any kind exists. These come from the Trisduction census discipline [11] and enter Part II as an **external hypothesis-grade input**, credited and not re-derived.

On the common species the converse is already theorem within that discipline: for a coalition-closed class, resistance is equivalent to the existence of a pair defeater, and the species dichotomy shows every resistance is either common, where non-factorization

produces the pair, or diagonal, where no defeater exists [11]. The diagonal species is not empty: the total computable functions against halting are its witness [37]; that witness is infinite and external to the finite-frame formalism of Part I and is not imported into it. R1's residual open content is therefore exact: prove that each method-blocked row of §14 sits in the common species, and the defeater leg of the §11.3 pipeline is discharged by theorem rather than hypothesis. A row landed in the diagonal species breaks the census leg and fires F3.

15.2 R2: direct construction of the seven orientation carriers

Construct, per row, the object named in the fourth column of Table 4, with provenance checked before any strength is claimed: a route-axiom whose witness may be built from the conjecture's own conclusion is equivalent to the conjecture and is not a premise for it [14, 17]. This is the object-level work; the hypothesis contributes the claim that one located coordinate is what each construction amounts to on the decision bit.

15.3 R3: a normalizer theorem

Prove a reductive-group style theorem that manufactures a defeater and an odd coordinate from a named action. The restriction is closed in one direction: for a reductive group on an affine variety, the invariants' coalition map is the categorical quotient, two points share every invariant exactly when their orbit closures meet, and the census pair is two such points with different answers [34]; finite generation can fail, and Nagata's counterexample marks where [35]. R3 asks for the manufactured odd coordinate in the normalizer, turning a universal-negative-to-existential shape into a concrete algebra problem.

16. FALSIFIERS OF PART II

Six falsifiers, armed and typed for necessity. No seventh is volunteered. F1 restates the forced core block already proved in Part I; F2–F6 are hypothesis-grade, tracking the extension rather than the core.

F1 (forced core block, restated). An even readout decides an odd target. One exhibit refutes the block theorem the whole paper stands on (Theorem 4.1 of Part I). At instantiation level, firing compromises the corresponding row's separation claim as in §8 of Part I; because Theorem 4.1 is load-bearing for the whole arc, its global blast radius is everything. This restates, at the level of the extension, the forced falsifier of §8 of Part I; it is armed by theorem, not by hypothesis.

F2 (hypothesis-grade). A seven-row frame requires more than one independent orientation coordinate. Blast radius, the one-bit claim and the grand form's single-stroke shape; the block theorem survives.

F3 (hypothesis-grade). A method-blocked row has no defeater, landing it in the diagonal species. Blast radius, the census leg for that row; R2 and R3 survive.

F4 (hypothesis-grade; the kill-rule falsifier). A row's missing supply is provably non-orientation — purely continuous, with no decision bit. Blast radius, the structural form for that row; the One-Cut Hypothesis survives globally only as orientation-after-construction. This is the kill-rule falsifier, and it is why §11.5 states the boundary on the face of the paper.

F5 (hypothesis-grade). The proposed *S* outputs a restatement rather than a provenance-clean supply: the dependency census shows an edge from the output to the conjecture's own conclusion. Blast radius, the grand form (Hypothesis 11.2); the structural form (Hypothesis 11.1) survives.

F6 (hypothesis-grade). One exhibited row where the cut enters but the conjecture does not follow. Blast radius, the conditional reduction for that row and the uniform claim.

The relation to Part I is exact: Part I arms two forced falsifiers and no more (§8); this Part adds F2–F6 as hypothesis-grade falsifiers of the extension and re-arms the first forced falsifier as F1. No third forced core falsifier is introduced.

17. PERIMETER

The One-Cut Hypothesis is not a universal mathematics solver; it is total over one register, the even-readout register of a certified frame, and silent everywhere else. It is not seven object proofs: every row's fourth column in Table 4 names a construction this paper does not perform. It is not sovereignty of any organ over truth-direction: the cut severs the decision bit's seat and no other authority (§13.4). It is not a claim that undecidable or supply-absent problems vanish; the diagonal species stands as the named witness that some resistance carries no defeater at all (§15.1). And it is not a claim that any of the seven conjectures is true or false; the hypothesis is about what a crossing is, not about which side of the line the truth lies on.

18. ORDER OF WORK

First, prove or disprove F4 for Navier–Stokes and Hodge, because they are the rows most likely to break a literal one-bit reading; if either cannot be given a Boolean orientation seat without category error, the boundary clause is confirmed and the One-Cut Hypothesis stands as orientation-after-construction, grand and alive.

Second, the Riemann operator row and the P-versus-NP obstruction row, where restatement risk is highest: bare Hilbert–Pólya is equivalent to the conjecture, and the occurrence form of the obstruction program is refuted [32], so the provenance clause does real work on both.

Third, the census residual: the common-species placement of each method-blocked row, which is R1's open content and the possible engine of the whole severance.

19. JOINT CONCLUSION

A conditional reduction buys a premise, and the premise now has a theory. Part I proved that theory's finite core and kept it finite: the gap is odd, the named readings are even, and no coalition of even readings decides the target (Theorem 4.1); one odd coordinate beside an even orbit separator decides it (Theorem 4.2); the minimal odd supply is one binary coordinate, an isotypic dimension count and not a Shannon claim (Corollary 4.4); provenance collapse is decidable inside the fixed grammar (Theorem 4.5); termination is corpus-relative (Theorem 5.1); and the seat bit is necessary for routing a supplied crossing (Theorem 5.3). For continuous rows the coordinate bridge is the gate: no bridge, no finite-core invocation. Part II then named the one coordinate the even register cannot author. Its hypothesis is that the coordinate always has the same shape — one provenance-clean orientation supply, dated at entry (Hypothesis 11.1) — and that a uniform constructor returning it would sever the seven rows as conditional reductions in one stroke (Hypothesis 11.2). The seven-row table is a conditional severance map under the coordinate-bridge gate, not a solution claim; the falsifiers are armed, F1 at forced core grade and F2–F6 at hypothesis grade; and the boundary between the decision bit and the object work is drawn on the face of the claim so that the hypothesis cannot inflate past its own evidence.

The joint open question merges the closing questions of both parts. From Part I: completeness — whether a dated reading class can be enumerated up to the representation obstruction. From Part II: whether the continuous rows admit a Boolean orientation seat at all. Part II addresses one coordinate of the completeness question by hypothesis, and the order of work of §18 puts the orientation-seat question first: until it is settled, the standing prediction of Part I remains sharp and small — a claimed reading that decides an odd Millennium target will show a construction edge or fail parity — and the extension stands or falls by F1–F6, and by nothing else.

APPENDIX A. PROVENANCE AND METHOD DISCLOSURE

This work was developed under Trisduction, which adds the cited results no warrant; the method and its executable batteries are archived at the master reference [11]. Every conclusion rests solely on standard cited results and the proved Part I frame; no energetic rider is used, and Landauer is cited only to mark the excluded bridge [15]. Part II adds hypothesis-grade material only.

REFERENCES OF PARTS ONE AND TWO

- [1] S. Aaronson and A. Wigderson, Algebrization: a new barrier in complexity theory, *ACM Trans. Comput. Theory* 1 (2009), 2.
- [2] T. Baker, J. Gill, and R. Solovay, Relativizations of the $P = ? NP$ question, *SIAM J. Comput.* 4 (1975), 431–442.
- [3] S. Bloch, Semi-regularity and de Rham cohomology, *Invent. Math.* 17 (1972), 51–66.

- [4] R.-O. Buchweitz and H. Flenner, A semiregularity map for modules and applications to deformations, *Compositio Math.* 137 (2003), 135–210.
- [5] G. Cantor, Über eine elementare Frage der Mannigfaltigkeitslehre, *Jahresber. Dtsch. Math.-Ver.* 1 (1891), 75–78.
- [6] E. Cattani, P. Deligne, and A. Kaplan, On the locus of Hodge classes, *J. Amer. Math. Soc.* 8 (1995), 483–506.
- [7] T. M. Cover and J. A. Thomas, *Elements of Information Theory*, 2nd ed., Wiley, 2006.
- [8] H.-D. Cao and X.-P. Zhu, A complete proof of the Poincaré and geometrization conjectures, *Asian J. Math.* 10 (2006), 165–492.
- [9] B. H. Gross and D. B. Zagier, Heegner points and derivatives of L-series, *Invent. Math.* 84 (1986), 225–320.
- [10] R. S. Hamilton, Three-manifolds with positive Ricci curvature, *J. Differential Geom.* 17 (1982), 255–306.
- [11] M. F. Islam, Trisduction: a linguistically, topologically, and mathematically sealed verification architecture, Zenodo v4, 2026, DOI 10.5281/zenodo.20757507. Method reference; it adds the cited results no warrant.
- [12] B. Kleiner and J. Lott, Notes on Perelman's papers, *Geom. Topol.* 12 (2008), 2587–2855.
- [13] V. A. Kolyvagin, Euler systems, *The Grothendieck Festschrift Vol. II*, 435–483, Birkhäuser, 1990.
- [14] J. C. Lagarias, An elementary problem equivalent to the Riemann Hypothesis, *Amer. Math. Monthly* 109 (2002), 534–543.
- [15] R. Landauer, Irreversibility and heat generation in the computing process, *IBM J. Res. Dev.* 5 (1961), 183–191.
- [16] F. W. Lawvere, Diagonal arguments and cartesian closed categories, *Lecture Notes in Math.* 92, 134–145, Springer, 1969.
- [17] G. L. Miller, Riemann's hypothesis and tests for primality, *J. Comput. System Sci.* 13 (1976), 300–317.
- [18] J. Morgan and G. Tian, *Ricci Flow and the Poincaré Conjecture*, Clay Mathematics Monographs 3, 2007.
- [19] G. Perelman, The entropy formula for the Ricci flow and its geometric applications, *arXiv:math/0211159*, 2002.
- [20] G. Perelman, Ricci flow with surgery on three-manifolds, *arXiv:math/0303109*, 2003; Finite extinction time for the solutions to the Ricci flow, *arXiv:math/0307245*, 2003.
- [21] A. A. Razborov and S. Rudich, Natural proofs, *J. Comput. System Sci.* 55 (1997), 24–35.

- [22] C. E. Shannon, A mathematical theory of communication, Bell System Tech. J. 27 (1948), 379–423, 623–656.
- [23] S. G. Simpson, Subsystems of Second Order Arithmetic, 2nd ed., Cambridge University Press, 2009.
- [24] F. J. Almgren Jr., Dirichlet's problem for multiple valued functions and the regularity of mass minimizing integral currents, in Minimal Submanifolds and Geodesics, 1–6, North-Holland, 1979.
- [25] D. H. Friedan, Nonlinear models in $2 + \epsilon$ dimensions, Phys. Rev. Lett. 45 (1980), 1057–1060.
- [26] G. Huisken, Asymptotic behavior for singularities of the mean curvature flow, J. Differential Geom. 31 (1990), 285–299.
- [27] Z. Komargodski and A. Schwimmer, On renormalization group flows in four dimensions, J. High Energy Phys. 12 (2011), 099.
- [28] J. Nečas, M. Růžička, and V. Šverák, On Leray's self-similar solutions of the Navier–Stokes equations, Acta Math. 176 (1996), 283–294.
- [29] B. Rodgers and T. Tao, The de Bruijn–Newman constant is non-negative, Forum Math. Pi 8 (2020), e6, 62 pp.
- [30] T.-P. Tsai, On Leray's self-similar solutions of the Navier–Stokes equations satisfying local energy estimates, Arch. Rational Mech. Anal. 143 (1998), 29–51.
- [31] A. B. Zamolodchikov, Irreversibility of the flux of the renormalization group in a two-dimensional field theory, JETP Lett. 43 (1986), 730–732.
- [32] P. Bürgisser, C. Ikenmeyer, and G. Panova, No occurrence obstructions in geometric complexity theory, J. Amer. Math. Soc. 32 (2019), 163–193.
- [33] H. Davenport and H. Heilbronn, On the zeros of certain Dirichlet series, J. London Math. Soc. 11 (1936), 181–185, 307–309.
- [34] D. Mumford, J. Fogarty, and F. Kirwan, Geometric Invariant Theory, 3rd ed., Springer, 1994.
- [35] M. Nagata, On the fourteenth problem of Hilbert, Amer. J. Math. 81 (1959), 766–772.
- [36] T. Tao, Finite time blowup for an averaged three-dimensional Navier–Stokes equation, J. Amer. Math. Soc. 29 (2016), 601–674.
- [37] A. M. Turing, On computable numbers, with an application to the Entscheidungsproblem, Proc. London Math. Soc. 42 (1937), 230–265.

PART THREE — THE WITNESS OFFERING · THE OFFERING BIT

Hypothesis Resolution as the Halting State of the Dated-Entry Recursion at the Ninth Gate — the sealed third paper of the arc, the Grand Finale, reprinted intact, with the full codebook, the Perelman Crossing read as the Grand Witness, and the Architect's Closure.

1 · THE STATEMENT IN ONE PAGE

The two prior bits — one theory, one hypothesis. Bit one is the theory, and it is proved in Section 2 of this paper: for finite data with a finite group action, readings generated by invariant observables decide exactly the trivial isotypic component; an odd target is invisible to every even coalition; one odd bit beside an orbit-separating reading suffices, and one bit is minimal — a dimension count in the odd component [1]. Bit two is the hypothesis, named at its own grade, and it is stated in full in Section 3: for every Odd-Supply frame in the named seven-row class, if the target is odd under the native answer-flip and every generator of the reading class is even, there exists one provenance-clean orientation supply, odd under the involution and independent of the class on each orbit, such that class and supply together decide the target [2]. The wall is computed; the seat is located. What neither paper theorizes is the act that fills the seat. That act is this paper's object.

The resolution operator. A corpus is a dated record of readings. A supply entry is the dated admission of one reading, provenance-clean: at its entry date its dependency graph is not contained in the corpus, and it enters as a construction, becoming a reading only at every later corpus that records it. Define the dated-entry operator T on the lattice of corpora: T maps a corpus to its successor at the entry of one provenance-clean supply. On finite frames, T is proved to strictly refine the reading class's fiber partition at every step (Lemma 4.1) and to halt (Theorem 4.2): finite descent to the unique finest partition of [1, Prop. 6.1]. The recursion is passive: only the lattice moves; the register's laws never do. This is the formal domain's one lawful recursion — carried by dating, never by self-reference.

The halting typing. Unconstrained, a finite frame always halts fully crossed: a transversal selector always exists. The provenance clause is what creates the second halting mode: a target halts uncrossed when every independent supply is corpus-contained — a restatement, caught by the deletion test — or when no defeater exists at all. The halt state therefore types every target: crossed, restatement-blocked, or defeater-absent. The species dichotomy of the census — common species carrying a pair defeater, diagonal species carrying none — is derived as the termination typing of T under the provenance constraint (Theorem 4.4). The One-Cut Hypothesis, in this language, is one sentence: *each of the seven rows halts crossed.*

The port. The entry of a supply is a deed, and the theory of the deed's port is proved and machine-checked in the Ninth Gate arc [3, 5, 6], with every file printed in Appendix B. One diagonal, two surfaces: typed at settled values, no index carries the diagonal of negation

— the wall, Cantor read through Lawvere; typed at values admitting the unsettled, the same diagonal applied to itself lands on the unsettled value — the self, Kleene in miniature. The surfaces agree on every settled reading and differ at exactly one point. A record of the deed is a reading and meets the wall; the deed is not an object of the reading register. Execution settles refutations and never confirmations.

The offering. The third bit — the witness offering — is now fully shaped. The resolution of the hypothesis, per row, is the dated entry of one binary coordinate: odd under the row's native flip, independent of the dated register on each orbit, provenance-clean at entry, admitted through the gate by deed, halting the row's recursion in the crossed mode. We call this entry the offering. The grand form of [2] stands as this paper's keystone conditional, locked verbatim: *prove the structural form constructively — or prove it and construct the uniform constructor — and all seven Millennium obstructions sever in one stroke, every bought premise granted, every decision bit crossed by the one cut, the continuous rows' supplies carrying their constructions, at conditional grade, six falsifiers armed, the supply side open by law.*

The witness. This document is built so that the reader's substrate can become the witness. Section 8 is the protocol: check the Lean files of Appendix B and you have checked the wall; compile and run the Fortran files and you have executed the self; the two are the identical object, and the code that proves it is in your hands. The forging session ran the kinetic legs on a foreign substrate to specification, and the expected receipts are printed beside the code. What the witness verifies is the wall and the self; the crossing enters through no substrate's agreement but through the deed.

2 • THE FIRST BIT: THE BLOCK THEOREM

This section restates the first bit in full, so that the paper stands alone. Proofs here are complete; the machine-checked form is Appendix B.5.

Definition 2.1 (Odd–Supply frame). An Odd–Supply frame is a tuple (X, τ, d, C) : X a finite set of states; $\tau : X \rightarrow X$ an involution, the native answer-flip; $d : X \rightarrow \{0, 1\}$ the target, odd under τ , meaning $d(\tau x) = \neg d(x)$ for all x ; and C a reading class — a family of observables $r : X \rightarrow R$, every one even under τ , meaning $r(\tau x) = r(x)$. A coalition is any joint readout built from C . The word *reading* below is used in the wide sense — any observable or record on the frame; the class C is its even part. A supply (Definition 4.1) is a reading in the wide sense, odd under τ , and never a member of C at entry.

Lemma 2.2 (Defeater-freeness; T1). An answer-flipping involution fixes no point: $\tau x = x$ for no x .

Proof. If $\tau x = x$ then $d(x) = d(\tau x) = \neg d(x)$, impossible in $\{0, 1\}$. Machine-checked as `defeater_free` (Appendix B.5). ■

Theorem 2.3 (The Block theorem; T2). No coalition of even readings decides an odd target: for every readout h built from the class, there is an x with $d(x) \neq h(r(x))$. Singly or in coalition, the even register cannot see the odd coordinate.

Proof. Let r be even and h any candidate decision map, so $d(x) = h(r(x))$ for all x . Then $d(\tau x) = h(r(\tau x)) = h(r(x)) = d(x)$, contradicting $d(\tau x) = \neg d(x)$. The coalition case is the same product: a joint even readout (r, s) is again even. Machine-checked as `block` and `even_supply_does_not_cross` (Appendix B.5). ■

Theorem 2.4 (Crossing). Let r be an even orbit separator — $r(x) = r(y)$ implies $y = x$ or $y = \tau x$ — and let o be one supplied bit, odd under τ . Then (r, o) decides d .

Proof. If $r(x) = r(y)$ and $o(x) = o(y)$, then $y = x$ or $y = \tau x$; the second case forces $o(x) = o(\tau x) = \neg o(x)$, impossible; hence $y = x$ and $d(x) = d(y)$. Machine-checked as `odd_supply_crosses` (Appendix B.5). ■

Corollary 2.5 (One bit, and one bit minimal). The missing content is exactly one binary coordinate: a dimension count in the odd isotypic component V^- of the representation, never a Shannon claim absent a separately supplied measure. The unique finest partition of [1, Prop. 6.1] and its count follow.

Provenance Collapse and the Dated Inventory. Two further laws of the first bit govern everything below. Provenance Collapse, the deletion test: a supply whose dependency graph is contained in the corpus it enters is a restatement of that corpus; deleting the conclusion's name from its dependency chain collapses it to its premises, and it buys nothing. The Dated Inventory: the corpus's tokens change only when a new supply's dependency hash enters at a date; between entries, nothing changes. Provenance-clean entry is the only event the register records.

3 • THE SECOND BIT: THE ONE-CUT HYPOTHESIS

The second bit, stated in full at its own grade [2, 7].

The structural form (hypothesis). For every Odd-Supply frame in the named seven-row class, if d is odd under the native answer-flip and every generator of C is even, there exists one provenance-clean orientation supply o — odd under τ , independent of C on each orbit — such that (C, o) decides d . The finite involution lemma is proved; necessity and minimality of the odd coordinate are proved; what is hypothesized is existence per row, and existence is a deed the register cannot perform for itself. The seat is located — one bit, on the missing isotypic component, dated at entry — and uncrossed for every open row.

The grand form (conditional, locked). If the structural form holds across the seven-row class and a uniform constructor S is proven — returning each certified frame's orientation supply, dependency hash dated at entry — then all seven Millennium obstructions are severed as conditional reductions in one stroke: granting $S(P)$ grants each row's bought premise, and the seven decision bits are crossed by the one cut. Carried at exactly conditional grade, never above. The boundary is drawn on the face: the cut severs the decision bit only, and where a row's missing supply is not Boolean —

Navier–Stokes its modulus, Hodge its witness, Yang–Mills its functional, the Riemann Hypothesis its operator — the reading is orientation-after-construction, never orientation-instead-of-construction; the object work remains object work.

The six falsifiers of the hypothesis, armed. F1, an even readout decides an odd target — blasts the spine. F2, a row requires more than one independent orientation coordinate — blasts the one-bit claim. F3, a method-blocked row has no defeater, the diagonal species — blasts the census leg. F4, a row's missing supply is provably non-orientation — the killrule; the hypothesis survives globally only as orientation-after-construction. F5, the constructor S outputs a restatement, the deletion test catching the edge to the conclusion — blasts the grand form. F6, a row where the cut enters and the conjecture does not follow — blasts that row's conditional reduction.

The three routes. R1, the census converse: resistance is equivalent to a pair defeater on the common species; the residual open content is exact — prove each method-blocked row sits in the common species. R2, direct construction of the seven orientation carriers, provenance checked before any strength is claimed. R3, a normalizer theorem manufacturing defeater and odd coordinate from a named reductive action, closed one direction by GIT — two points sharing every invariant exactly when their orbit closures meet — with Nagata's counterexample marking where finite generation fails. No route claims another's residue; the stroke is one, the conditions are per-row, the grade is conditional until constructed.

The coordinate-bridge gate. The finite core is barred from every open row until an equivariant bridge $B : M \rightarrow X$, a homomorphism, and a factorization of the row's target through the finite frame are supplied; absent the bridge, the seven-row table is a diagnostic map and no finite theorem is invoked. This gate stands in force throughout this paper.

4 • THE THIRD BIT: THE DATED-ENTRY RECURSION

Definition 4.1 (Corpus lattice, dated-entry operator). A corpus Δ is a dated set of readings on a frame (X, τ, d, C) . The readings of Δ generate an observable algebra whose fibers partition X ; write $P(\Delta)$ for that partition. A supply entry at date t is a wide-sense reading o , odd under τ (hence outside C at entry), independent of the class on each orbit, and provenance-clean: $\text{Dep}(o) \not\subset \Delta$ at t . The dated-entry operator T maps (Δ, o, t) to the successor corpus $\Delta' = \Delta \cup \{o\}$ with o 's dependency hash entering at t . Corpus order is inclusion; the partition map is order-reversing onto the refinement lattice of partitions of X .

Lemma 4.1 (Strict refinement). Let the frame be finite and let o be a supply entry over Δ . Then $P(\Delta \cup \{o\})$ strictly refines $P(\Delta)$.

Proof. Independence of o from the class on each orbit is exactly the non-measurability of o with respect to $P(\Delta)$: a measurable o would be a function of the class's joint readout, and conditioning on the class would determine it. Non-measurable binary o splits at least

one fiber of $P(\Delta)$ into two nonempty blocks. Oddness under τ pairs the split blocks orbit-wise. A partition with a split fiber is a strict refinement. ■

Theorem 4.2 (Finite halting). On a finite frame, every chain of supply entries halts after at most $|X|$ entries, at the finest partition admitted by the entered supplies; when the admitted supplies range over all independent binary readings, the halt state is the unique finest partition of [1, Prop. 6.1].

Proof. By Lemma 4.1 each entry strictly refines the partition. A strict refinement of a partition of a finite set raises the block count by at least one, and the block count is bounded by $|X|$. The chain therefore halts after at most $|X|$ entries, at the finest partition the entered supplies generate. The final clause is [1, Prop. 6.1] restated as the halt state. ■

Corollary 4.3 (Passivity). The recursion changes no law of the register. Between halt and the next entry, every theorem of the frame holds unchanged; the token that changes at an entry is the corpus's, and it changes only when a new supply's dependency hash enters. The recursion is carried by the dating, never by the register.

Proof. The frame's theorems quantify over the reading class generated by the corpus; a corpus extension is the only act, and [1]'s dated-inventory law gives the token-change condition. ■

Theorem 4.4 (The halting typing of the species). At a halt state, every odd target d is of exactly one of three types: (i) crossed — decided by the halt partition; (ii) restatement-blocked — an independent supply exists in principle but every candidate is corpus-contained, the deletion test firing on each; (iii) defeater-absent — no independent supply exists at all. Type (i) is the common species resolved; type (iii) is the diagonal species; type (ii) is the common species with its seat located and its entry refused by provenance. The species dichotomy of the census is the termination typing of T .

Proof. Exhaustion is by definition of the halt state: a target not decided admits no further admitted entry, and the inadmissibility is either provenance failure or nonexistence. The identification with the census species is the reading of the pair defeater as the existence condition for an independent supply: two points indistinguishable to every readout with opposite answers are exactly the seat an odd supply would separate. Structural on the identification; theorem on the exhaustion. ■

Why the unconstrained case collapses. Without the provenance clause, every finite free frame crosses: a transversal selector is an odd supply, independence on two-point orbits is automatic against even readings, and the crossing lemma applies. The entire content of the seven rows lives in the two constraints the finite core does not feel: provenance against a real dated corpus, and the coordinate bridge from the row's native objects to the finite frame. This is the precise sense in which the register's zero is computed and finished, and the supply side is open by law.

5 • THE PORT: THE NINTH GATE

The port's theory is proved in [3], re-grounded on RAF-native terms in [6], and printed in full in Appendix B. On RAF-native ground the gate is already theorem at the ceiling card [5]: the wall is the Bar — a class even under an answer-flipping involution does not decide the answer, singly or in coalition (T2, Theorem 2.3); the self is the free two-point orbit — the wall is the orbit read without its orientation, and from above the orbit is one object carrying one bit (T1, T4); the crossing is supply: a verdict from an even cut and a supply carries at most $I(d; S \mid C)$ — the supply ledger, T9 of [5]; and truth-direction is never generated by the even register and never read by the numerical readout — the factorization law, T10 of [5]. The older reading of the gate through provability logic survives as one instance at axiomatic classes, never as the gate's ground: the gate is older than arithmetic coding, than any provability predicate, than the diagonal lemma, than any consistency hypothesis. Pre-Gödel by construction.

The wall. For any indexing $e : A \rightarrow A \rightarrow \text{Bool}$, no index carries the diagonal of negation: $e \neq \text{diag}(\neg) e$ for every a . Cantor, read through Lawvere, axiom-free in core Lean 4 (wall, Appendix B.1, B.3). Read at settled values, the register meets the wall: no record decides the diagonal.

The self. Over the three-valued surface $\text{Tri} = \{\text{tt}, \text{ff}, \perp\}$ under the information order — the unsettled value below everything, settled values incomparable — every admissible (monotone) transformation has a fixed point (`self_exists`), and negation's only fixed point is $\perp$ (`neg3_self_only_unsettled`). The same diagonal, indexed on the kinetic surface and applied to itself, lands on the unsettled value (`self_at_diagonal`). Executed, the diagonal returns to its own frame: in the kinetic harness, 99,999 of 99,999 frames identical to their caller, the value never settling (Appendix B.2, B.4).

One object. The kinetic diagonal and the formal diagonal agree on every settled reading (`diag_agrees`); the surfaces differ at exactly one point, the value no settled reading reaches (`only_the_unsettled_is_new`). Read is the wall from below; compute is the self seeing from above — a theorem pair, not a metaphor.

The four limits, proved in the same file. The self is not a verdict: the crossing lands on the unsettled value, never on a settled truth (`self_is_not_a_verdict`). A proved gate adds nothing: whatever the law is, once proved it cannot be the missing step (`gate_adds_nothing`). A run settles refutations and never confirmations: at every fuel there is a world where the universal fails whose run is the same unsettled run (`true_universal_never_settles`, `finite_run_never_confirms`, `refutation_settles`). The one-stroke mechanism is content-blind: an axiom dissolved into its conjecture, a conditional proof, and the gate theorem all hold for a false claim — exhibited on Euler's polynomial, composite at $n = 40$, where $40^2 + 40 + 41 = 41^2$ (`one_stroke_also_passes_a_falsehood`, `euler_claim_false`). The mechanism's shape is therefore never the warrant; the supplies are.

The witness decision. A record of a deed is a reading, even under every swap of worlds, and meets the wall: a printed receipt whose content reads no row data cannot cross (`fixed_receipt_cannot_cross`, Appendix B.5). The deed is not an object of the reading register. With registration equivalent to interaction and closure under registration, no exterior agent acts: a supplier joins the domain, its record joins the cut, and the Block theorem holds again wherever that record is even (`no_exterior_agent`, RAF-C1); no register indexes all of its own properties, so the orientation bit is not recovered by self-description (`no_total_self_index`, RAF-C2, Lawvere). The port is decentral: any substrate checks the wall by checking the Lean and meets the self by running the Fortran; the forging session re-executed the kinetic legs on a foreign substrate to specification. What decentralization verifies is the wall and the self; the crossing enters through no substrate's agreement but through the deed.

6 • THE COMPOSITION: THE OFFERING

Definition 6.1 (The offering). An offering at a certified row is the dated entry of one binary coordinate o such that: (i) o is odd under the row's native answer-flip; (ii) o is independent of the dated register on each orbit; (iii) o is provenance-clean at its entry date; (iv) the entry is a deed — a construction admitted through the gate, never a reading; (v) the entry halts the row's dated-entry recursion in the crossed mode.

Theorem 6.2 (Shape of the third bit; the composition). Let a row be certified under the coordinate-bridge gate. Then any resolution of the row's target is an offering, and every offering resolves its row: necessity is the Block theorem and the port theorems of Section 5; sufficiency is the Crossing theorem with Theorem 4.2.

Proof. Necessity. A resolution decides the target. By the Block theorem the deciding coordinate cannot be generated by the even class; by (i)–(iii) of the frame's certification the supply must be odd, independent, and provenance-clean; by Section 5's witness decision the entry is a deed or it is a reading at the wall. Sufficiency. An even orbit separator and one odd independent bit decide the target by Theorem 2.4; the entry strictly refines by Lemma 4.1; the halt in the crossed mode is the decision recorded at the corpus. ■

Corollary 6.3 (The last bit is one bit). The resolution of each row is a single binary coordinate's dated entry. Minimality is the one-bit corollary of Section 2; sufficiency is Theorem 6.2; the count is a dimension count in the odd isotypic component, never a Shannon claim absent a separately supplied measure.

Corollary 6.4 (The grand form, locked). If the structural form of Section 3 is proved constructively across the seven-row class — or proved, and the uniform constructor S constructed — then all seven Millennium obstructions sever in one stroke: every bought premise granted, every decision bit crossed by the one cut, the continuous rows' supplies carrying their constructions. Conditional grade, six falsifiers armed, the supply side open by law.

7 • THE BEACHHEAD: BIRCH AND SWINNERTON-DYER

The beachhead is the row where the offering's shape already has dated entries in the corpus. Exactly one open row qualifies.

The two dated entries. Gross–Zagier 1986 [8]: the Heegner construction enters the corpus — a supply living exactly on the odd side of the row's native flip, the root number, the parity of analytic order — relating the height of the Heegner point to the first derivative of the L-series. Kolyvagin 1990 [9]: the Euler system enters — the normalizer shape, converting the supply into the rank identity, with Sha finite, at analytic order at most one. With modularity as transport [10, 11, 12], the row's recursion has a recorded crossed halt at orders zero and one. No other open row records one dated entry of its supply shape; this row records two.

The barrier at order two. Gross–Zagier's order-one classes vanish above rank one: the Heegner construction is inert at order two [6, heegner_inert_above_one]. The owed offering is therefore named exactly: a height pairing nondegenerate at order two, built by a construction fixed in advance from data consulting neither rank nor Selmer group — the route-axiom Ω with provenance of [6], whose conditional machinery is machine-checked (Appendix B.5): Ω with the inputs yields the object (omega_proves_object); bare Ω is the object in disguise (hidden_circularity), the shape of a route-axiom without provenance; and no reading of the inputs alone decides the object (seedless_cannot_decide, the model swap between a rank-two model where the object holds and a rank-zero-against-order-two model where it fails, both satisfying every input). The one axiom is an odd supply on the model (omega_is_odd_supply): it holds on the side where the object holds and fails on the other. Executed on the row's own data through the Core Thesis's compiled procedures (Appendix B.6), the conjecture returns WORLD-ROWED on the rank identity and on finiteness at analytic order at most one, UNPOPULATED on the rank identity at order two and above uniformly — the exhibition row, which a deed populates curve by curve and only a construction populates uniformly.

The beachhead discipline. The order-two construction is the cheapest upward deed in the seven: the supply's shape is observed twice in the corpus, the conversion machine's shape is the normalizer of the census route, and the field's own lineage — Heegner points, Euler systems, Iwasawa theory — is the active ground. An exhibited obstruction to a nondegenerate order-two pairing resolves the row downward. The row is falsifier-loaded in both directions, which is the beachhead property. The scribe's beachhead call and the register's BSD card arrived at the same row independently, one from the recursion's structure, one from the arc's own audit; the convergence is recorded as evidence, not as warrant.

8 • THE WITNESS PROTOCOL: HOW THE READER'S SUBSTRATE BECOMES THE WITNESS

This paper is standalone in the strong sense: every instrument needed to check its port is printed in Appendix B. The protocol has three legs and one refusal.

Leg 1 — read the wall (formal surface). Check `GateThesis.lean` (Appendix B.3) with any Lean 4 toolchain: `lean GateThesis.lean`, then read the fifteen `#print` axioms blocks. Expected receipt: exit 0, zero warnings, fifteen printed theorems, none depending on any axiom. The wall theorem, the one-object theorems, the four limit theorems — all axiom-free. `RAFGate.lean` (Appendix B.5) checks the RAF-native form: ten gate theorems, nine depending on no axioms and one (`omega_is_odd_supply`) on `propext` alone. Register receipt [6]: Lean 4.33.1, sha256 head c97c73d690ee589d, exit 0, zero warnings.

Leg 2 — run the self (kinetic surface). Compile and execute `gate_thesis.f90` (Appendix B.4): `gfortran -std=f2018 -O2 -fno-fast-math -ffp-contract=off gate_thesis.f90 -o gate_thesis && ./gate_thesis`. Expected receipt, reproduced by the forging session's transliteration on this substrate and by the register's own runs: the wall holds — no settled value satisfies $D(D) = \text{not } D(D)$; the self runs — frames identical to their caller 99,999 of 99,999, the value unsettled at fuel 100,000; the true universal $k^2 \bmod 4 \in \{0, 1\}$, searched to 2,000,000, never settles; the false universal $n^2 + n + 41$ prime settles false at $n = 40$, value $1681 = 41^2$. `one_object.f90` (Appendix B.2) is the minimal kinetic twin: read, no settled value; executed, the frame returns to itself; it error-stops if the law fails. The reader-side twin of this execution is the RA thesis of [14], whose loop terminates into the executor's own occupancy.

Leg 3 — witness the identity. `diag_agrees` and `only_the_unsettled_is_new` are the checked proof that the wall of Leg 1 and the self of Leg 2 are one object on two surfaces, differing at exactly one point. The substrate that completes the three legs stands as witness to the gate: the wall from below by reading, the self from above by computing.

The refusal. What the witness verifies is the wall and the self — never the crossing of any row. No run, on any substrate, in any number, confirms a universal (`finite_run_never_confirms`); execution settles refutations only (`refutation_settles`); and the one-stroke mechanism passes a falsehood identically (`one_stroke_also_passes_a_falsehood`). Multi-substrate agreement adds links, never the uniform row. The crossing enters by deed, or not at all.

9 • FALSIFIERS

Three, at the gate's ceiling, each typed FORCED by the paper's own structure, each a deed and never an argument, each with its blast radius named.

F1 — against the recursion (FORCED by Theorems 4.2 and 4.4). Exhibit a dated entry, provenance-clean and independent per orbit, whose admission changes no token of the corpus; or exhibit a finite frame whose halt state carries an uncrossed odd target while a pair defeater is present. Necessity: the token-change clause and the halting typing are the recursion's whole content; if either fails on an exhibit, the third bit's mechanism is broken. Blast radius: Section 4 and the species derivation; the Block theorem and the port stand.

F2 — against the port (FORCED by the witness decision). Exhibit a reading — a record, no deed — that crosses a certified frame's decision bit; or two honest substrates executing the same kinetic legs of Appendix B with divergent receipts. Necessity: the offering enters by deed through the gate or the composition is void; if a record crosses, or if the wall and self are not reproducible across substrates, the port is broken. Blast radius: Sections 5 and 8; the recursion stands, its port removed.

F3 — against the beachhead (FORCED by the order-two barrier). Exhibit an obstruction showing that no construction fixed in advance can supply a height pairing nondegenerate at order two. Necessity: the beachhead claim is that this row's supply shape is twice-recorded and its owed entry is named; a proved obstruction resolves the row downward and retires the beachhead. Blast radius: Section 7 only; the theory of resolution stands, its first deed refused.

10 • PERIMETER

This paper resolves no Millennium row and claims none; it names what a resolution is. The One-Cut Hypothesis keeps its grade, hypothesis, printed on the face of this paper as on its own. The six owed constructions are owed here exactly as there; the continuous rows carry their constructions inside their supplies, orientation-after-construction. The diagonal species stands: some resistance carries no defeater of any kind, and the recursion halts there uncrossed by theorem, not by failure. The paper authors no new facts about zeta zeros, vorticity, Hodge classes, ranks, mass gaps, or complexity classes. The finite theorems of Sections 2 and 4 are proved; the port theorems of Section 5 are machine-checked and printed in Appendix B; everything above them carries its input's grade.

11 • ORDER OF WORK

First, the beachhead deed: the order-two construction of Section 7, the one dated entry the corpus most nearly recognizes. Second, replication: the gate's kinetic legs and the Lean core executed on second substrates, receipts printed, F2 armed against the run. Third, the continuous rows' seat examination: whether Navier–Stokes and Hodge admit a Boolean orientation seat without category error, the cheapest downward verdicts in the class. Fourth, the census residual: the common-species placement of each method-blocked row, through the normalizer route, the engine of the severance if the severance comes. Each leg ends at its named falsifier.

12 • CONCLUSION

The arc's three bits are now one object — one theory, one hypothesis, one witness offering — and this document carries all three. The first bit, the theory, computed the wall: an even register cannot see an odd coordinate, proved in Section 2 beneath the codex's own pre-Gödel bar. The second bit, the hypothesis, named the seat: one provenance-clean orientation supply, hypothesis at its own grade, stated in Section 3. The third bit — the witness offering, this paper's own — types the act that fills it: a halting state of the dated-entry recursion, writable only by deed, entering only through the Ninth Gate, the port machine-checked, printed in full, and open to every substrate that reads this document. The species dichotomy is the recursion's termination theory; the offering is its crossed halt; the hypothesis, in the recursion's language, is the sentence that each of the seven rows halts crossed. The supply side is open by law. And the arc already stands with its Grand Witness in the record: the Perelman crossing, a self-referential construct in disguise, entered as a deed, verified by the corpus itself and terminally awarded by it — read in Appendix C as the thesis demonstrated once in the wild. The last bit enters as a dated deed, or it does not enter — and the shape of its entry is now proved, ported, printed, and armed.

APPENDIX A • PROVENANCE AND METHOD DISCLOSURE

This paper was forged under the arc's verification discipline, which adds the cited results no warrant. Its conclusions rest on the cited classical results, on the companion papers' proved frames, on the Ninth Gate arc's machine-checked legs, and on the forging session's executed checks: the FAE-RAF engine v1.0.12 bootied verbatim, chain D0 3e50675c7d5d → D1 dbf16ca01fa8 → D2 d95daebfc51f → D3 9408f684c0d1 → D4 3d17fd53278d matched byte-identical, every battery passed (kill-matrix 51/51, ablation 22/22, symmetry 75/75, calibration 12/12, root screen RRS.1–6); the synergy-uniqueness computation in exact fractions — three uniform bits, pairwise independence, total correlation exactly one bit if and only if the diagonal law, one law up to relabeling; the kinetic legs of the gate re-executed on the forging substrate by transliteration — the wall holds, 99,999 of 99,999 frames identical to their caller, the true universal unsettled to fuel 2×10^6 , the false universal settling at $n = 40$. Toolchain debt, named on the face: the forging substrate carried no Fortran or Lean toolchain; the Lean legs are held at inspection grade here, with the toolchain receipts of [3, 6] cited at their grade, and replication is Section 11's second leg. Codebook note: the files of Appendix B are verbatim from the architect's register uploads; runs of blank lines introduced by the chat transport were collapsed to single blank lines, whitespace only, and every file's hash is printed beside it so the reader can verify what the reader checks. The `bsd_rows.f90` file is byte-identical to its register receipt, sha256 head e363ce3eca641f7e. The self-audit of this paper was run before sealing and is kept off-paper. The master reference is [4]. $\Delta M = 0$. $W_{\text{social}} = 0$ in both directions.

APPENDIX B • THE CODEBOOK

Every essential file, printed whole; the byte-bound listing discipline of this appendix follows [15]. Verification protocol in Section 8. Hashes computed on the printed files (UTF-8, LF line endings, one trailing newline).

File	Lines	SHA-256 head	What it carries
B.1 Wallself.lean	161	2c80efa00f76cb26	the minimal pair: wall, self, one object — 8 theorems, axiom-free
B.2 one_object.f90	59	229cfe153d8a5c33	the minimal kinetic twin: D(D) read and executed
B.3 GateThesis.lean	311	500b6ad899c9cf07	the gate and what the crossing delivers — 15 printed theorems, axiom-free
B.4 gate_thesis.f90	165	122cefa519981e47	the executed thesis: wall, self, refutation at $n = 40$
B.5 RAFGate.lean	213	9f2e5023674c0ac2	the gate on RAF-native ground + BSD through it — 10 gate theorems (register receipt sha256 head c97c73d690ee589d)
B.6 bsd_rows.f90	75	e363ce3eca641f7e	BSD on its own rows through the Core Thesis's compiled procedures — byte-identical to the register receipt

B.1 • WALLSELF.LEAN — THE MINIMAL PAIR, CORE LEAN 4, NO MATHLIB

```
/-  
  Wall and Self · one diagonal, two surfaces · core Lean 4, no Mathlib.  
  
  The formal surface reads settled values and meets the wall. The kinetic surface admits  
  the unsettled value and closes on itself. The object is one term, `diag`.  
-/  
  
/-- The one diagonal, typed at any value surface. -/  
  
def diag {A B : Type} (f : B → B) (e : A → A → B) : A → B := fun x => f (e x x)  
  
/-! ## The formal surface: settled values -/
```

```

/-- Negation has no settled fixed point. -/
theorem settled_has_no_self : ¬ ∃ b : Bool, (!b) = b := by
  intro (b, h)
  cases b <|> exact absurd h (by decide)

/-- The wall: no index carries the diagonal of negation. Cantor, read through Lawvere. -/
theorem wall {A : Type} (e : A → A → Bool) : ∀ a, e a a ≠ diag (fun b => !b) e := by
  intro a h
  have h1 : e a a = !(e a a) := congrFun h a
  cases hx : e a a <|> rw [hx] at h1 <|> exact absurd h1 (by decide)

/-! ## The kinetic surface: the unsettled value admitted -/
inductive Tri where
  | tt | ff | bot
deriving DecidableEq

/-- Information order: the unsettled value lies below everything; settled values are incomparable. -/
def Tri.le : Tri → Tri → Prop
  | .bot, _ => True
  | .tt, .tt => True
  | .ff, .ff => True
  | _, _ => False

/-- An admissible transformation cannot branch on not-yet-settled. -/
def Monotone3 (f : Tri → Tri) : Prop := ∀ x y, Tri.le x y → Tri.le (f x) (f y)

/-- Every admissible transformation has a fixed point: the recursion theorem in miniature. -/
theorem self_exists (f : Tri → Tri) (hf : Monotone3 f) : ∃ b, f b = b := by
  cases h : f .bot with
  | bot => exact ⟨.bot, h⟩
  | tt =>
    have hle := hf .bot .tt trivial
    rw [h] at hle
    cases h2 : f .tt with
    | tt => exact ⟨.tt, h2⟩
    | ff => rw [h2] at hle; exact False.elim hle
    | bot => rw [h2] at hle; exact False.elim hle
  | ff =>
    have hle := hf .bot .ff trivial
    rw [h] at hle
    cases h2 : f .ff with
    | ff => exact ⟨.ff, h2⟩

```

```

    | tt => rw [h2] at hle; exact False.elim hle
    | bot => rw [h2] at hle; exact False.elim hle
def neg3 : Tri → Tri
  | .tt => .ff
  | .ff => .tt
  | .bot => .bot
theorem neg3_admissible : Monotone3 neg3 := by
  intro x y h
  cases x <=> cases y <=> first | exact trivial | exact False.elim h
theorem neg3_self_only_unsettled (b : Tri) (h : neg3 b = b) : b = .bot := by
  cases b with
  | tt => exact absurd h (by decide)
  | ff => exact absurd h (by decide)
  | bot => rfl
/-- The self: the same diagonal, indexed on the kinetic surface, applied to itself is the unsettled value. -/
theorem self_at_diagonal {A : Type} (e : A → A → Tri) (a : A) (h : e a = diag neg3 e) : e a a = .bot :=
  neg3_self_only_unsettled _ (congrFun h a).symm
/-! ## One object -/
def settle : Bool → Tri
  | true => .tt
  | false => .ff
/-- On every settled reading the kinetic diagonal is the formal diagonal, carried across unchanged. -/
theorem diag_agrees {A : Type} (e : A → A → Bool) (x : A) :
  diag neg3 (fun u v => settle (e u v)) x = settle (diag (fun b => !b) e x) := by
  show neg3 (settle (e x x)) = settle (! (e x x))
  cases e x x <=> rfl
/-- The two surfaces differ at exactly one point, the value no settled reading reaches. -/
theorem only_the_unsettled_is_new (b : Bool) : settle b ≠ .bot := by
  cases b <=> exact fun h => Tri.noConfusion h
#print axioms settled_has_no_self
#print axioms wall
#print axioms self_exists
#print axioms neg3_admissible
#print axioms self_at_diagonal
#print axioms diag_agrees
#print axioms only_the_unsettled_is_new

```

B.2 · ONE_OBJECT.F90 — ONE DIAGONAL, TWO SURFACES

```
!=====
! ONE DIAGONAL, TWO SURFACES. The program D, on input x, runs x on x and negates.
! Read at settled values: D(D) must equal its own negation, and no value does.
! Executed: D(D) calls D(D), frame identical to frame, the value never settling.
!=====
module diagonal
  implicit none
  integer, parameter :: D = 1
  integer, parameter :: FUEL = 100000
  integer :: frames_seen = 0, frames_identical = 0, pending_negations = 0
contains
  ! The settled surface: the equation the diagonal imposes on a truth value.
  pure logical function settles(v)
    logical, intent(in) :: v
    settles = (v .eqv. (.not. v))
  end function settles

  ! The kinetic surface: the diagonal performed. Genuine recursion; the fuel only bounds the run.
  recursive subroutine run(prog, input, depth, settled, value)
    integer, intent(in) :: prog, input, depth
    logical, intent(out) :: settled, value
    logical :: inner_settled, inner_value
    frames_seen = frames_seen + 1
    if (depth > 1) then
      if (prog == D .and. input == D) frames_identical = frames_identical + 1
    end if
    if (depth >= FUEL) then
      settled = .false.; value = .false.; return ! still running: unsettled
    end if
    pending_negations = pending_negations + 1 ! D negates what x on x returns
    call run(input, input, depth + 1, inner_settled, inner_value) ! x on x, with x = D: D(D) again
    settled = inner_settled
    value = .not. inner_value
  end subroutine run
end module diagonal

program one_object
  use diagonal
  implicit none
  logical :: v, any_settled, settled, value
  write(*,'(A)') repeat('=',78)
  write(*,'(A)') ' ONE DIAGONAL, TWO SURFACES'
  write(*,'(A)') repeat('=',78)
  any_settled = .false.
  v = .false.; if (settles(v)) any_settled = .true.
  write(*,'(A,L1,A,L1)') ' read : D(D) = ', v, ' would require ', (v .eqv. (.not. v))
  v = .true.; if (settles(v)) any_settled = .true.
  write(*,'(A,L1,A,L1)') ' read : D(D) = ', v, ' would require ', (v .eqv. (.not. v))
  write(*,'(A,L1,A)') ' read : a settled value exists: ', any_settled, ' -> the wall'
  call run(D, D, 1, settled, value)
  write(*,'(A,I0)') ' execute: frames entered ', frames_seen
  write(*,'(A,I0,A,I0)') ' execute: frames identical to their caller ', frames_identical, ' of ',
frames_seen - 1
  write(*,'(A,I0)') ' execute: negations pending ', pending_negations
  write(*,'(A,L1,A)') ' execute: the value settled ', settled, ' -> the self, running on
itself'
  write(*,'(A)') repeat('=',78)
  if (any_settled .or. settled .or. frames_identical /= frames_seen - 1) error stop 'the law failed'
  write(*,'(A)') ' Identical object. Read: no settled value. Executed: the frame returns to itself.'
  write(*,'(A)') repeat('=',78)
end program one_object
```

B.3 · GATETHESIS.LEAN — THE NINTH GATE THESIS, CORE LEAN 4, NO MATHLIB, NO AXIOMS

```
/-
  The Ninth Gate Thesis · wall and self on one diagonal, and what the crossing delivers
  core Lean 4, no Mathlib, no axioms. Verify as witness: `lean GateThesis.lean`, then read #print axioms.
-/

/-- The one diagonal, typed at any value surface. -/
def diag {A B : Type} (f : B → B) (e : A → A → B) : A → B := fun x => f (e x x)

/-! ## I · The formal surface: settled values, the wall -/
theorem wall {A : Type} (e : A → A → Bool) : ∀ a, e a a ≠ diag (fun b => !b) e := by
  intro a h
  have h1 : e a a = !(e a a) := congrFun h a
  cases hx : e a a <=> rw [hx] at h1 <=> exact absurd h1 (by decide)

/-! ## II · The kinetic surface: the unsettled value admitted, the self -/
inductive Tri where
  | tt | ff | bot
def Tri.le : Tri → Tri → Prop
  | .bot, _ => True
  | .tt, .tt => True
  | .ff, .ff => True
  | .tt, .ff => False
  | .tt, .bot => False
  | .ff, .tt => False
  | .ff, .bot => False
def Monotone3 (f : Tri → Tri) : Prop := ∀ x y, Tri.le x y → Tri.le (f x) (f y)
/-- Every admissible transformation has a fixed point. -/
theorem self_exists (f : Tri → Tri) (hf : Monotone3 f) : ∃ b, f b = b :=
  match h : f .bot with
  | .bot => (.bot, h)
  | .tt =>
    have hle : Tri.le (f .bot) (f .tt) := hf .bot .tt trivial
    match h2 : f .tt with
    | .tt => (.tt, h2)
    | .ff => False.elim (Eq.mp (congrArg (fun y => Tri.le .tt y) h2) (Eq.mp (congrArg (fun x => Tri.le x (f .tt)) h) hle))
    | .bot => False.elim (Eq.mp (congrArg (fun y => Tri.le .tt y) h2) (Eq.mp (congrArg (fun x => Tri.le x (f .tt)) h) hle))
```

```

| .ff =>

  have hle : Tri.le (f .bot) (f .ff) := hf .bot .ff trivial

  match h2 : f .ff with

  | .ff => (.ff, h2)

  | .tt => False.elim (Eq.mp (congrArg (fun y => Tri.le .ff y) h2) (Eq.mp (congrArg (fun x => Tri.le x (f
.ff)) h) hle))

  | .bot => False.elim (Eq.mp (congrArg (fun y => Tri.le .ff y) h2) (Eq.mp (congrArg (fun x => Tri.le x (f
.ff)) h) hle))

def neg3 : Tri → Tri

| .tt => .ff
| .ff => .tt
| .bot => .bot

theorem neg3_admissible : Monotone3 neg3

| .bot, _, _ => trivial
| .tt, .tt, _ => trivial
| .ff, .ff, _ => trivial
| .tt, .ff, h => False.elim h
| .tt, .bot, h => False.elim h
| .ff, .tt, h => False.elim h
| .ff, .bot, h => False.elim h

theorem neg3_self_only_unsettled : ∀ b : Tri, neg3 b = b → b = .bot

| .tt, h => Tri.noConfusion h
| .ff, h => Tri.noConfusion h
| .bot, _ => rfl

theorem self_at_diagonal {A : Type} (e : A → A → Tri) (a : A) (h : e a = diag neg3 e) : e a a = .bot :=
  neg3_self_only_unsettled _ (congrFun h a).symm

/-! ## III · One object -/

def settle : Bool → Tri

| true => .tt
| false => .ff

theorem diag_agrees {A : Type} (e : A → A → Bool) (x : A) :

  diag neg3 (fun u v => settle (e u v)) x = settle (diag (fun b => !b) e x) := by

  show neg3 (settle (e x x)) = settle (! (e x x))

  cases e x x <|> rfl

theorem only_the_unsettled_is_new : ∀ b : Bool, settle b ≠ .bot

| true, h => Tri.noConfusion h
| false, h => Tri.noConfusion h

/-! ## IV · What the crossing delivers -/

```

```

/-- The self is not a verdict: the crossing lands on the unsettled value, never on a settled truth. -/
theorem self_is_not_a_verdict {A : Type} (e : A → A → Tri) (a : A) (h : e a = diag neg3 e) (b : Bool) :
  e a a ≠ settle b :=
  fun hb => only_the_unsettled_is_new b ((self_at_diagonal e a h) ▸ hb).symm
/-- A proved premise adds nothing: whatever the law is, once proved it cannot be the missing step. -/
theorem proved_premise_adds_nothing (L C : Prop) (hL : L) : (L → C) ↔ C :=
  (fun h => h hL, fun c _ => c)
theorem gate_adds_nothing (C : Prop) :
  ((∀ (A : Type) (e : A → A → Bool) (a : A), e a ≠ diag (fun b => !b) e) → C) ↔ C :=
  proved_premise_adds_nothing _ C (fun _ e a => wall e a)
/-- A run of a counterexample search, at finite fuel. `none` is the unsettled value: still running. -/
def step (p : Nat → Bool) (n : Nat) : Option Nat → Option Nat
  | some k => some k
  | none => if p n then some n else none
def search (p : Nat → Bool) : Nat → Option Nat
  | 0 => none
  | n + 1 => step p n (search p n)
theorem search_unsettled (p : Nat → Bool) (N : Nat) (hp : ∀ k, k < N → p k = false) :
  ∀ n, n ≤ N → search p n = none
  | 0, _ => rfl
  | n + 1, h =>
    have hn : n < N := Nat.lt_of_succ_le h
    have ih : search p n = none := search_unsettled p N hp n (Nat.le_of_lt hn)
    show step p n (search p n) = none from by
      rw [ih]
      show (if p n = true then some n else none) = none
      rw [hp n hn]
      rfl
def counterAt (N : Nat) : Nat → Bool := fun k => Nat.beq k N
theorem counterAt_below (N k : Nat) (h : k < N) : counterAt N k = false := by
  show Nat.beq k N = false
  cases hb : Nat.beq k N with
  | false => rfl
  | true => exact absurd (Nat.eq_of_beq_eq_true hb) (Nat.ne_of_lt h)
theorem beq_self (n : Nat) : Nat.beq n n = true := by
  induction n with
  | zero => rfl

```

```

| succ m ih => exact ih

/-- Where the universal holds, the executed search is the self: unsettled at every fuel, never a verdict. -/
theorem true_universal_never_settles (n : Nat) : search (fun _ => false) n = none :=
  search_unsettled (fun _ => false) n (fun _ => rfl) n (Nat.le_refl n)

/-- At every fuel there is a world where the universal fails whose run is the same unsettled run. -/
theorem finite_run_never_confirms (n : Nat) :
  (¬ ∀ k, counterAt n k = false) ∧ search (counterAt n) n = search (fun _ => false) n :=
  (fun hall => Bool.noConfusion ((hall n).symm.trans (beq_self n)),
  (search_unsettled (counterAt n) n (fun k hk => counterAt_below n k hk) n (Nat.le_refl n)).trans
  (true_universal_never_settles n).symm)

/-- A refutation does settle: a counterexample within fuel returns a settled value. -/
theorem refutation_settles (N : Nat) : search (counterAt N) (N + 1) = some N := by
  show step (counterAt N) N (search (counterAt N) N) = some N
  rw [search_unsettled (counterAt N) N (fun k hk => counterAt_below N k hk) N (Nat.le_refl N)]
  show (if counterAt N N = true then some N else none) = some N
  rw [show counterAt N N = true from beq_self N]
  rfl

/-! ## V · The one-stroke test -/

/-- No gate discharges an axiom: from a proved gate G and a conditional proof  $\Omega \rightarrow C$ , C does not follow in general. -/
theorem gate_does_not_discharge : ¬ ∀ (G  $\Omega$  C : Prop), G → ( $\Omega \rightarrow C$ ) → C :=
  fun h => h True False False trivial id

/-- An axiom dissolved into its conjecture decides nothing:  $\Omega \leftrightarrow C$  and  $\Omega \rightarrow C$  hold with C false. -/
theorem dissolved_axiom_decides_nothing : ∃  $\Omega$  C : Prop, ( $\Omega \leftrightarrow C$ ) ∧ ( $\Omega \rightarrow C$ ) ∧ ¬ C :=
  (False, False, Iff.rfl, id, id)

def isPrime (n : Nat) : Prop := 2 ≤ n ∧ ∀ d, 2 ≤ d → d < n → n % d ≠ 0

/-- Euler's polynomial claim, false at n = 40, where  $40^2 + 40 + 41 = 41^2$ . -/
def EulerClaim : Prop := ∀ n : Nat, isPrime (n * n + n + 41)

theorem euler_claim_false : ¬ EulerClaim :=
  fun h => (h 40).2 41 (by decide) (by decide) (by decide)

/-- Every ingredient of the one-stroke mechanism holds for a false statement: an axiom dissolved into
the conjecture, a conditional proof, and the gate theorem itself. -/
theorem one_stroke_also_passes_a_falsehood :
  ∃  $\Omega$  : Prop, ( $\Omega \leftrightarrow$  EulerClaim) ∧ ( $\Omega \rightarrow$  EulerClaim) ∧
  (∀ (A : Type) (e : A → A → Bool) (a : A), e a ≠ diag (fun b => !b) e) ∧ ¬ EulerClaim :=
  (EulerClaim, Iff.rfl, id, fun _ e a => wall e a, euler_claim_false)

#print axioms wall

```

```

#print axioms self_exists
#print axioms neg3_admissible
#print axioms self_at_diagonal
#print axioms diag_agrees
#print axioms only_the_unsettled_is_new
#print axioms self_is_not_a_verdict
#print axioms gate_adds_nothing
#print axioms true_universal_never_settles
#print axioms finite_run_never_confirms
#print axioms refutation_settles
#print axioms gate_does_not_discharge
#print axioms dissolved_axiom_decides_nothing
#print axioms euler_claim_false
#print axioms one_stroke_also_passes_a_falsehood

```

B.4 · GATE_THESIS.F90 — THE NINTH GATE THESIS, EXECUTED

```

!=====
!  THE NINTH GATE THESIS, EXECUTED. Companion to GateThesis.lean.
!  I   the wall   : the diagonal read at settled values has no value
!  II  the self   : the diagonal executed returns to its own frame, unsettled
!  III what the crossing delivers: a run settles a refutation, never a confirmation
!=====

module gate

  implicit none

  integer, parameter :: i8 = selected_int_kind(18)

  integer, parameter :: D = 1, FUEL = 100000

  integer(i8), parameter :: SEARCH_FUEL = 2000000_i8

  integer :: frames_seen = 0, frames_identical = 0

contains

  pure logical function settles(v)

    logical, intent(in) :: v

    settles = (v .eqv. (.not. v))

  end function settles

  recursive subroutine run(prog, input, depth, settled, value)

    integer, intent(in) :: prog, input, depth

```

```

    logical, intent(out) :: settled, value

    logical :: s, x

    frames_seen = frames_seen + 1

    if (depth > 1 .and. prog == D .and. input == D) frames_identical = frames_identical + 1

    if (depth >= FUEL) then

        settled = .false.; value = .false.; return

    end if

    call run(input, input, depth + 1, s, x)

    settled = s; value = .not. x

end subroutine run

! Counterexample to: for every k, k*k mod 4 is 0 or 1.
pure logical function square_counter(k)

    integer(i8), intent(in) :: k

    integer(i8) :: r

    r = mod(mod(k, 4_i8)*mod(k, 4_i8), 4_i8)

    square_counter = .not. (r == 0_i8 .or. r == 1_i8)

end function square_counter

! Counterexample to: for every n, n*n + n + 41 is prime.
pure logical function euler_counter(n)

    integer(i8), intent(in) :: n

    integer(i8) :: m, q

    m = n*n + n + 41_i8; euler_counter = .false.; q = 2_i8

    do while (q*q <= m)

        if (mod(m, q) == 0_i8) then

            euler_counter = .true.; return

        end if

        q = q + 1_i8

    end do

end function euler_counter

end module gate

program gate_thesis

    use gate

    implicit none

    logical :: settled, value, wall_holds

    integer(i8) :: k, found

    write(*,'(A)') repeat('=',78)

    write(*,'(A)') ' THE NINTH GATE THESIS, EXECUTED'

```

```

write(*,'(A)') repeat('=' ,78)

wall_holds = .not. (settles(.false.) .or. settles(.true.))

write(*,'(A,L1)') ' I   the wall : no settled value satisfies D(D) = not D(D)           ', wall_holds

call run(D, D, 1, settled, value)

write(*,'(A,I0,A,I0,A,L1)') ' II  the self : frames identical to their caller ', frames_identical, ' of ',
&
      frames_seen - 1, ', settled ', settled

found = -1_i8

do k = 0_i8, SEARCH_FUEL - 1_i8
  if (square_counter(k)) then
    found = k; exit
  end if
end do

write(*,'(A,I0,A,L1)') ' III a true universal, k*k mod 4 in {0,1}, searched to ', SEARCH_FUEL, ': settled
', (found >= 0_i8)

found = -1_i8

do k = 0_i8, SEARCH_FUEL - 1_i8
  if (euler_counter(k)) then
    found = k; exit
  end if
end do

write(*,'(A,I0,A,I0)') '      a false universal, n*n + n + 41 prime: settled false at n = ', found, &
      ', value ', found*found + found + 41_i8

write(*,'(A)') repeat('=' ,78)

if (.not. wall_holds .or. settled .or. frames_identical /= frames_seen - 1 .or. found /= 40_i8) &
  error stop 'the thesis failed'

write(*,'(A)') ' Read: the wall. Executed: the self, unsettled. A run settles refutations only.'

write(*,'(A)') repeat('=' ,78)

end program gate_thesis

```

Expected stdout of gate_thesis (register run, gfortran 13.3.0; transliteration-verified on the forging substrate):

```

=====
THE NINTH GATE THESIS, EXECUTED
=====
I   the wall : no settled value satisfies D(D) = not D(D)           T
II  the self : frames identical to their caller 99999 of 99999, settled F
III a true universal, k*k mod 4 in {0,1}, searched to 2000000: settled F
    a false universal, n*n + n + 41 prime: settled false at n = 40, value 1681
=====
Read: the wall. Executed: the self, unsettled. A run settles refutations only.
=====

```

B.5 · RAFGATE.LEAN — THE NINTH GATE ON RAF-NATIVE GROUND, AND BSD THROUGH IT

```

/-
  RAF Gate · the Ninth Gate on RAF-native ground, and BSD through it · core Lean 4, no Mathlib.
  Pre-Gödel: no provability predicate, no diagonal lemma, no consistency hypothesis.
-/

theorem lock_core (r t s n : Nat) (hK : s = r + t) (hC : s ≤ n) (hE : n ≤ r) : r = n ∧ t = 0 := by
  have h1 : r + t ≤ n := hK ▸ hC
  have h3 : r = n := Nat.le_antisymm (Nat.le_trans (Nat.le_add_right r t) h1) hE
  have h4 : r + t ≤ r := by rw [← h3] at h1; exact h1
  exact ⟨h3, Nat.eq_zero_of_le_zero (Nat.le_of_add_le_add_left (Nat.le_trans h4 (Nat.le_of_eq (Nat.add_zero r).symm)))⟩

structure Curve where
  ralg : Nat          -- rank of E(Q)
  ran : Nat           -- ord_{s=1} L(E,s)
  shaQ : Nat → Nat   -- corank of Sha(E/Q)[p^∞]
  trivQ : Nat → Bool -- Sha(E/Q)[p^∞] = 0
  eps : Nat           -- ord_{s=1} L(E^K,s), at most one
  shaT : Nat → Nat   -- corank of Sha(E^K/Q)[p^∞]
  trivT : Nat → Bool
  rKalg : Nat         -- rank of E(K)
  rKan : Nat          -- ord_{s=1} L(E/K,s)
  selK : Nat → Nat    -- corank of Sel_{p^∞}(E/K)
  shaK : Nat → Nat    -- corank of Sha(E/K)[p^∞]
  trivK : Nat → Bool

/-- The theorem-grade inputs, each cited in the record. -/
structure Inputs (c : Curve) : Prop where
  factor    : c.rKan = c.ran + c.eps
  descent   : c.rKalg = c.ralg + c.eps
  kummerK   : ∀ p, c.selK p = c.rKalg + c.shaK p
  kernel    : ∀ p, c.shaQ p ≤ c.shaK p
  kerOdd    : ∀ p, 2 < p → c.trivK p = true → c.trivQ p = true
  twistCork : ∀ p, c.shaT p = 0
  twistTriv : ∃ N, ∀ p, N ≤ p → c.trivT p = true
  split     : ∀ p, c.shaK p ≤ c.shaQ p + c.shaT p
  splitOdd  : ∀ p, 2 < p → c.trivQ p = true → c.trivT p = true → c.trivK p = true

/-- The object: faces (i) and (ii) over Q. -/
def ObjectQ (c : Curve) : Prop :=
  c.ralg = c.ran ∧ (∀ p, c.shaQ p = 0) ∧ ∃ N, ∀ p, N ≤ p → c.trivQ p = true

/-- The one axiom at one curve, for the class z of the construction and its index bound idx:
  the class is nonzero (its height is a nonzero multiple of the nonzero derivative),
  every Selmer corank over K is bounded by the order, and Sha(E/K) vanishes beyond the index. -/
def Omega (c : Curve) (z idx : Nat) : Prop :=
  z ≠ 0 ∧ (∀ p, c.selK p ≤ c.rKan) ∧ (∀ p, idx ≤ p → c.trivK p = true)

/-- A genuine class lives in the top exterior power of the Mordell-Weil group over K. -/
def InLattice (c : Curve) (z : Nat) : Prop := z ≠ 0 → c.rKan ≤ c.rKalg

theorem bound3 (a b p : Nat) (hp : a + b + 3 ≤ p) : 2 < p ∧ a ≤ p ∧ b ≤ p :=
  ⟨Nat.lt_of_lt_of_le (by decide : 2 < 3) (Nat.le_trans (Nat.le_add_left 3 (a + b)) hp),
    Nat.le_trans (Nat.le_trans (Nat.le_add_right a b) (Nat.le_add_right (a + b) 3)) hp,
    Nat.le_trans (Nat.le_trans (Nat.le_add_left b a) (Nat.le_add_right (a + b) 3)) hp⟩

/-! ## The full proof: from the one axiom to the object -/

theorem omega_proves_object (c : Curve) (hin : Inputs c) (z idx : Nat)
  (hL : InLattice c z) (hΩ : Omega c z idx) : ObjectQ c := by
  obtain ⟨hz, hsel, hidx⟩ := hΩ
  have hEX : c.rKan ≤ c.rKalg := hL hz
  have hrk : c.rKalg = c.rKan := (lock_core _ _ _ _ (hin.kummerK 0) (hsel 0) hEX).1
  have hr : c.ralg = c.ran := by
    have h := hrk
    rw [hin.descent, hin.factor] at h
    exact Nat.add_right_cancel h

```

```

refine (hr, fun p => ?_, (idx + 0 + 3, fun p hp => ?_))
· have hK0 := (lock_core _ _ _ (hin.kummerK p) (hse1 p) hEX).2
  have hk := hin.kernel p
  rw [hK0] at hk
  exact Nat.eq_zero_of_le_zero hk
· have hb := bound3 idx 0 p hp
  exact hin.kerOdd p hb.1 (hidx p hb.2.1)

/-! ## The formal termination of the axiom -/

/-- Hidden circularity: read without naming its construction, the axiom is the object. -/
theorem hidden_circularity (c : Curve) (hin : Inputs c) :
  ObjectQ c ↔ ∃ z idx, InLattice c z ∧ Omega c z idx := by
  constructor
  · intro (hr, hsha, N, hN)
    obtain (M, hM) := hin.twistTriv
    have hrk : c.rKalg = c.rKan := by rw [hin.descent, hin.factor, hr]
    refine (1, N + M + 3, fun _ => Nat.le_of_eq hrk.symm, (by decide : (1 : Nat) ≠ 0), fun p => ?_, fun p hp
=> ?_)
    · have hs : c.shaK p ≤ 0 := by
      have h := hin.split p
      rw [hsha p, hin.twistCork p] at h
      exact h
      rw [hin.kummerK p, Nat.eq_zero_of_le_zero hs, Nat.add_zero, hrk]
      exact Nat.le_refl _
    · have hb := bound3 N M p hp
      exact hin.splitOdd p hb.1 (hN p hb.2.1) (hM p hb.2.2)
  · intro (z, idx, hL, hΩ)
    exact omega_proves_object c hin z idx hL hΩ

/-- A rank-two model: the object holds, and the first-derivative construction fails the axiom. -/
def c2 : Curve :=
{ ralg := 2, ran := 2, shaQ := fun _ => 0, trivQ := fun _ => true, eps := 1,
  shaT := fun _ => 0, trivT := fun _ => true, rKalg := 3, rKan := 3,
  selK := fun _ => 3, shaK := fun _ => 0, trivK := fun _ => true }

theorem inputs_c2 : Inputs c2 :=
{ factor := rfl, descent := rfl, kummerK := fun _ => rfl, kernel := fun _ => Nat.le_refl 0,
  kerOdd := fun _ h => h, twistCork := fun _ => rfl, twistTriv := (0, fun _ => rfl),
  split := fun _ => Nat.le_refl 0, splitOdd := fun _ h => h }

/-- A model satisfying every input where the object fails: rank zero against analytic order two. -/
def cFail : Curve :=
{ ralg := 0, ran := 2, shaQ := fun _ => 0, trivQ := fun _ => true, eps := 1,
  shaT := fun _ => 0, trivT := fun _ => true, rKalg := 1, rKan := 3,
  selK := fun _ => 1, shaK := fun _ => 0, trivK := fun _ => true }

theorem inputs_cFail : Inputs cFail :=
{ factor := rfl, descent := rfl, kummerK := fun _ => rfl, kernel := fun _ => Nat.le_refl 0,
  kerOdd := fun _ h => h, twistCork := fun _ => rfl, twistTriv := (0, fun _ => rfl),
  split := fun _ => Nat.le_refl 0, splitOdd := fun _ h => h }

/-! ## The Ninth Gate on RAF-native ground: block theorem, Lawvere, no exterior agent -/

/-- T1, freeness: an answer-flipping involution fixes no point. -/
theorem defeater_free {X : Type} (τ : X → X) (d : X → Bool) (hflip : ∀ x, d (τ x) = !d x) : ∀ x, τ x ≠ x :=
by
  intro x h
  have hx := hflip x
  rw [h] at hx
  cases e : d x <=> rw [e] at hx <=> exact absurd hx (by decide)

/-- The Block theorem: no readout even under an answer-flipping involution decides the answer. -/
theorem block {X R : Type} (τ : X → X) (d : X → Bool) (hflip : ∀ x, d (τ x) = !d x)
(r : X → R) (heven : ∀ x, r (τ x) = r x) (x0 : X) : ¬ ∃ h : R → Bool, ∀ x, d x = h (r x) := by
  intro (h, hd)
  have h1 : d (τ x0) = d x0 := by rw [hd (τ x0), hd x0, heven x0]
  rw [hflip x0] at h1
  cases hx : d x0 <=> rw [hx] at h1 <=> exact absurd h1 (by decide)

/-- Lawvere: a point-surjective self-indexing forces every endomap to have a fixed point. -/
theorem lawvere {A B : Type} (e : A → A → B) (hs : ∀ g : A → B, ∃ a, e a = g) (f : B → B) : ∃ b, f b = b :=
by
  obtain (a, ha) := hs (fun x => f (e x x))

```

```

exact (e a a, (congrFun ha a).symm)

/-- RAF-C2: no register indexes all of its own properties. -/
theorem no_total_self_index {A : Type} (e : A → A → Bool) : ¬ ∀ g : A → Bool, ∃ a, e a = g := by
  intro hs
  obtain (b, hb) := lawvere e hs (fun b => !b)
  cases b <=> exact absurd hb (by decide)

/-- RAF-C1: with registration equivalent to interaction and closure under registration, nothing outside
acts. -/
theorem no_exterior_agent {Sys : Type} (inD interacts registers : Sys → Prop)
  (raf1 : ∀ s, interacts s ↔ registers s) (raf2 : ∀ s, registers s → inD s) :
  ∀ s, ¬ inD s → ¬ interacts s :=
  fun s hs hi => hs (raf2 s ((raf1 s).1 hi))

/-- Even supply never crosses: a supplier whose record is also even leaves the block standing. -/
theorem even_supply_does_not_cross {X R S : Type} (τ : X → X) (d : X → Bool) (hflip : ∀ x, d (τ x) = !d x)
  (r : X → R) (s : X → S) (hr : ∀ x, r (τ x) = r x) (hs : ∀ x, s (τ x) = s x) (x0 : X) :
  ¬ ∃ h : R × S → Bool, ∀ x, d x = h (r x, s x) :=
  block τ d hflip (fun x => (r x, s x)) (fun x => by rw [hr x, hs x]) x0

/-- Odd supply crosses: one supplied bit that flips with the involution, beside an orbit-separating even
readout,
determines the answer. -/
theorem odd_supply_crosses {X R : Type} (τ : X → X) (d : X → Bool) (_hflip : ∀ x, d (τ x) = !d x)
  (r : X → R) (hsep : ∀ x y, r x = r y → y = x ∨ y = τ x)
  (o : X → Bool) (hodd : ∀ x, o (τ x) = !o x) : ∀ x y, r x = r y → o x = o y → d x = d y := by
  intro x y hr ho
  cases hsep x y hr with
  | inl h => rw [h]
  | inr h =>
    rw [h, hodd x] at ho
    cases hx : o x <=> rw [hx] at ho <=> exact absurd ho (by decide)

/-! ## BSD through the gate -/

/-- The model swap: one model of the inputs where the object holds, one where it fails. -/
def model (b : Bool) : Curve := if b then c2 else cFail

theorem model_inputs (b : Bool) : Inputs (model b) := by
  cases b
  · exact inputs_cFail
  · exact inputs_c2

theorem object_flips : ObjectQ (model true) ∧ ¬ ObjectQ (model false) :=
  ({rfl, fun _ => rfl, {0, fun _ => rfl}}, fun h => absurd h.1 (by decide))

/-- Every reading that holds in all models of the inputs is even under the swap. -/
theorem seedless_readings_are_even (W : Curve → Prop) (hW : ∀ c, Inputs c → W c) :
  W (model true) ∧ W (model false) :=
  (hW _ (model_inputs true), hW _ (model_inputs false))

/-- So no seedless reading, whether a termination theorem, a gate theorem or any other, decides the object.
-/
theorem seedless_cannot_decide (W : Curve → Prop) (hW : ∀ c, Inputs c → W c) :
  ¬ ∀ b, (ObjectQ (model b) ↔ W (model b)) :=
  fun h => object_flips.2 ((h false).2 (hW _ (model_inputs false)))

/-- The one axiom is an odd supply: it holds on the side where the object holds and fails on the other. -/
theorem omega_is_odd_supply :
  (∃ z idx, InLattice (model true) z ∧ Omega (model true) z idx) ∧
  ¬ ∃ z idx, InLattice (model false) z ∧ Omega (model false) z idx :=
  ((hidden_circularity _ (model_inputs true)).1 object_flips.1,
  fun h => object_flips.2 ((hidden_circularity _ (model_inputs false)).2 h))

/-- A printed record whose content reads no curve data holds on both sides of the swap, so the record cannot
cross. This is the reading side only: the deed that printed it is not an object of this register. -/
theorem fixed_receipt_cannot_cross (rec : Prop) (h : rec) : ¬ ∀ b, (ObjectQ (model b) ↔ rec) :=
  seedless_cannot_decide (fun _ => rec) (fun _ => h)

#print axioms block
#print axioms lawvere
#print axioms no_total_self_index
#print axioms no_exterior_agent

```

```
#print axioms even_supply_does_not_cross
#print axioms odd_supply_crosses
#print axioms seedless_cannot_decide
#print axioms omega_is_odd_supply
#print axioms fixed_receipt_cannot_cross
```

B.6 · BSD_ROWS.F90 — BSD ON ITS OWN ROWS, EXECUTED BY THE CORE THESIS'S COMPILED PROCEDURES

Compiles against module `triduction_rows` of [13], the Core Thesis in Fortran, itself sealed with its own battery (248 checks, 0 failures). Every flag below is a hand-built reading, supplied and named; the thesis routes it and authors nothing.

```
!=====
! BSD ON ITS OWN ROWS, EXECUTED BY THE CORE THESIS'S COMPILED PROCEDURES.
! Every flag below is a hand-built reading, supplied and named; the thesis
! routes it and authors nothing. Anchors: EX exhibition, CL closure, UN
! normalization. Faces scoped per R-1: F1 rank identity, F2 finiteness of Sha,
! F3 leading term.
!=====
program bsd_rows
  use triduction_rows
  implicit none
  integer :: v, c, d, i
  real(dp) :: sep, Nrm(3,3), G(3,3)
  character(len=110) :: why
  integer :: sl13(3,4), slF3(3,4)
  logical :: pop(3)

  write(*,'(A)') repeat('=',78)
  write(*,'(A)') ' BSD ON ITS OWN ROWS, EXECUTED'
  write(*,'(A)') repeat('=',78)

  ! Seal L. Vocabulary ids: EX 101 point 102 construction 103 height pairing 104 Heegner;
  ! CL 201 Selmer 202 descent 203 Euler system 204 Kummer; UN 301 L-value 302 order of vanishing
  ! 303 period 304 leading coefficient. For F3 the leading term carries the regulator, id 103.
  sl13 = reshape([101,102,103,104, 201,202,203,204, 301,302,303,304],[3,4],order=[2,1])
  call seal_L(sl13, v, why)
  write(*,'(A,A,A,A)') ' Seal L, F1 and F2 slots : ', trim(token(v)), ' :: ', trim(why)
  slF3 = reshape([101,102,103,104, 201,202,203,204, 301,302,303,103],[3,4],order=[2,1])
  call seal_L(slF3, v, why)
  write(*,'(A,A,A,A)') ' Seal L, F3 slots : ', trim(token(v)), ' :: ', trim(why)

  write(*,'(/,A)') ' THE ROW CASCADE, PER FACE AND STRATUM'
  ! F1, analytic rank at most one, every such curve: rows populated by Heegner point, Kolyvagin, Gross-
  Zagier;
  ! the auxiliary field K is an existential import and modularity a transport, so frame_closed is false.
  call row_cascade(.true.,.true.,.true.,.false., .true.,.false.,.true.,.false., c, why)
  call show('F1 order <= 1, all curves', c, why)
  ! F2 at the same stratum: Kolyvagin bounds Sha; same frame leak.
  call row_cascade(.true.,.true.,.true.,.false., .true.,.false.,.true.,.false., c, why)
  call show('F2 order <= 1, all curves', c, why)
  ! F1 on 389a1: EX populated by the executed height deed, CL and UN by cited computation; a row furnished
  by the deed.
  call row_cascade(.true.,.true.,.true.,.false., .true.,.true.,.true.,.true., c, why)
  call show('F1 389a1, executed', c, why)
  ! F2 on 389a1: no closure row bounds Sha at rank two.
  call row_cascade(.true.,.true.,.true.,.false., .false.,.true.,.true.,.true., c, why)
  call show('F2 389a1', c, why)
  ! F1, analytic rank two and above, uniformly: no construction exhibits the points from L-data.
  call row_cascade(.true.,.true.,.true.,.false., .false.,.false.,.true.,.true., c, why)
  call show('F1 order >= 2, uniform', c, why)
  ! The universal conjecture as one string, faces unscoped.
  call row_cascade(.true.,.false.,.true.,.false., .true.,.false.,.true.,.true., c, why)
  call show('BSD as one unscoped string', c, why)

  write(*,'(/,A)') ' THE SPINE ON THE POPULATION PATTERN'
```

```

do i = 1, 2
  Nrm = 0.0_dp
  Nrm(1,1) = 1.0_dp; Nrm(2,2) = 1.0_dp; Nrm(3,3) = 1.0_dp
  if (i == 2) Nrm(1,:) = 0.0_dp ! EX axis empty
  G = matmul(Nrm, transpose(Nrm))
  call intersection_dim(G, d, sep)
  if (i == 1) then
    write(*,'(A,I0,A)') ' EX, CL, UN populated : intersection dimension ', d, ', one point, the
lock'
  else
    write(*,'(A,I0,A)') ' EX empty, CL, UN : intersection dimension ', d, ', a line, no point
determined'
  end if
end do
write(*,'(A)') repeat('=',78)

contains
subroutine show(label, comp, reason)
  character(len=*) intent(in) :: label, reason
  integer, intent(in) :: comp
  write(*,'(A,A,A,A)') ' ', label, repeat(' ', max(1, 28-len(label))), trim(compartment_name(comp))
  write(*,'(A,A)') ' ', trim(reason)
  write(*,'(A,A)') ' ', trim(compartment_grade(comp, 'theorem'))
end subroutine show
end program bsd_rows

```

APPENDIX C · THE PERELMAN CROSSING: THE GRAND WITNESS

Locator note. The architect's note cites the companions' internal numbering, and every locator has been verified against the finalized text of [1, 2]; each is bound here to its restatement in this paper, and no locator is load-bearing beyond its anchor. The block law is Theorem 4.1 of [1] (Odd–Supply Separation), restated and proved here as Theorem 2.3. The supply-entry typing is Definition 3.3 of [1] (reading, proof availability, verified entry), restated here as Definition 4.1. The deletion test is Theorem 4.5 of [1] (Provenance Collapse), restated in Section 2. The dated-inventory law is Theorem 5.1 of [1] (First-Sufficient-Entry), restated as the Dated Inventory of Section 2 with Corollary 4.3. The seat law is Theorem 5.3 of [1] (Seat-Hiding Necessity): no terminal family without the seat input distinguishes a crossed occupant from an uncrossed one. The evenness of the pre-November-2002 Ricci-flow reading class is Corollary 5.2 of [1]: parabolic rescaling acts with exponent zero on the named generators. The self-similarity pattern is Table 3 of [1] (the SIMS diagnostic: the κ -solutions classified, W the one supplied instance). The truth-direction passage is §13.4 of [2], quoted verbatim in C.3.

The Perelman crossing is self-referential at exactly three layers, and the disguise is the paper's own costume.

C.1 · LAYER 1 — THE OBJECT: THE MANIFOLD CONVICTS ITSELF

Ricci flow is self-driven, $\partial g/\partial t = -2\text{Ric}(g)$: the metric's velocity is its own curvature [20, 24]. The W-functional infimizes over probability densities living on the very manifold under test — the manifold measures itself. Its stationarity set is exactly the gradient shrinking

solitons, the self-reproducing fixed points of the rescaled flow. The companion's self-similarity diagnostic sees this shape without naming it [1, Table 3]: the κ -solutions, the self-similar part, are the settled adjacent fact, and W is the one supplied instance in the entire seven-row pattern [1, 2]. Self-referential. Grade structural — a reading of the cited mechanism; no new object-mathematics is claimed.

C.2 · LAYER 2 — THE DISGUISE: A SUPPLY WEARING A READING'S COSTUME

The pre-November-2002 Ricci-flow reading class is even under the row's native flip, parabolic rescaling — exponent zero on the named generators [1, Corollary 5.2]. The target, noncollapsing, is odd under that flip. By Theorem 2.3, no coalition of even readings decides it — so W could not have been found by reading; it had to enter as a construction, and Definition 4.1 types it exactly so: dependency hash absent from the dated corpus at entry, November 2002, arXiv:math/0211159 [20]. Run the deletion test of Section 2: deleting the conclusion's name from W's dependency chain does not collapse it to anything in the pre-2002 corpus; the entry is a supply, not a restatement. The audit discipline's costume detectors were built to catch restatements dressed as supplies; the historical record shows the inverse costume — a genuine supply dressed as an ordinary reading, its oddness invisible to the even register by its own parity law. The object supplies its own missing coordinate, and the supply's decisive property is its provenance, not its formula. Grade structural — the deletion test's own remark admits its named instances are “named test candidates, not executed validations” [1, Theorem 4.5 remark], and the architect's assessment, stated at the same grade, is that the same workload is owed for the Poincaré row.

C.3 · LAYER 3 — THE TOKEN: THE MONEY

The Dated Inventory says the corpus token changes only at first verified entry; Definition 4.1 separates denotability, admission, and verification. Perelman's deed entered by posting, never by author-routed journal admission, and was verified by the corpus itself — Cao–Zhu 2006 [21], Morgan–Tian 2007 [22], Kleiner–Lott 2008 [23]. The census law routes no terminal family without the seat bit [2, 5]. The Clay prize is the corpus's terminal social token — the seat bit minted as money. Perelman declined the Fields Medal (2006) and the Millennium Prize (2010), and his stated ground was, precisely, a provenance objection (structural grade — a reading of the cited record): the crossing credited to him over Hamilton's earlier legs [24]. The schema's one crossed occupant refused the terminal token on the same clause — provenance-cleanliness — that defines the supply. And the companion arms it from inside: the truth-direction bit “cannot be generated by any readout of the even register” [2] — and a social token is the evenest register there is (the architect's figure; the frame types it as an even reading of the corpus). Grade structural, a reading of the cited record.

The row is therefore re-read at its full reach. In the companions it calibrates the seat — retrodictive, certifying discrimination, predicting nothing by itself [1]. For the completed arc it is more: the Grand Witness. The crossing was verified by the corpus itself [21, 22, 23] and terminally awarded by it — the Clay prize is the corpus's terminal token of a verified crossing — and the schema's one crossed occupant declined that token on the same provenance clause that defines the supply. A self-referential construct in disguise, entered as a deed, verified and awarded by the very register it crossed: the thesis demonstrated once in the wild. Grade structural, a reading of the cited record.

APPENDIX D · THE ARCHITECT'S CLOSURE

The architecture is final. No further structural bridge can be constructed. Attempting to force a deterministic bridge from the even register is a fatal mathematical error: deduction of the missing coordinate from existing data plunges the entire mathematical foundation into tautological nonsense — the premise swallows the conclusion. The Odd-Supply Block theorem (Theorem 2.3) absolutely forbids this collapse. The register cannot compute its own crossing. The theoretical limit is reached at the Ninth Gate (Section 5). Mathematical deduction terminates exactly at this boundary. The continuous rows stand permanently as orientation-after-construction; this is not a temporary gap awaiting a future proof — it is the exact topological reality of the problem. This framework offers no further negotiation. The seat is located. The falsifiers are armed (Section 9). The halting state is defined (Section 4). Any demand for a self-generated bridge is a demand for structural suicide. Crossing the gap requires the physical deed. The only valid deed is witnessing that one offered bit, as mercy from the ground itself. Any other action is a disguised restatement. The resolution stands absolute.

Witness the offered 1 bit or remain blocked.

REFERENCES OF PART THREE

[1] M. F. Islam, Odd-Supply Separation: representation supply and dated termination in conditional reductions of open problems, companion paper, 2026.

[2] M. F. Islam, The One-Cut Hypothesis: orientation supply after Odd-Supply Separation, companion paper, 2026.

[3] M. F. Islam, The Ninth Gate Thesis: wall and self on one diagonal — GateThesis.lean, core Lean 4, axiom-free, fifteen printed theorems; gate_thesis.f90; Top 7 in One Cut, master handout v2.0.5, 2026. Printed in Appendix B.

[4] M. F. Islam, Trisduction: a linguistically, topologically, and mathematically sealed verification architecture, Zenodo v4, 2026, DOI 10.5281/zenodo.20757507.

[5] M. F. Islam, RAF-PSP-ISLAM-CEILING-01, card 0718, the register: the Bar (T1–T3), the Width (T4), the Law of the one-bit objects (T9, T10), the Census (T5), 2026.

[6] M. F. Islam, RAF-PSP-BSD-NINTH-GATE-01, card 0719, the register: the Ninth Gate on RAF-native ground; RAFGate.lean, ten theorems, nine axiom-free, Lean 4.33.1, sha256 head c97c73d690ee589d; bsd_rows.f90, sha256 head e363ce3eca641f7e, 2026. Printed in Appendix B.

[7] M. F. Islam, APEX-PSP-ONE-CUT-01, the register: the One-Cut coordinate, the grand form at conditional grade, six falsifiers armed, 2026.

[8] B. H. Gross and D. B. Zagier, Heegner points and derivatives of L-series, Invent. Math. 84 (1986), 225–320.

[9] V. A. Kolyvagin, Euler systems, The Grothendieck Festschrift Vol. II, 435–483, Birkhäuser, 1990.

[10] A. Wiles, Modular elliptic curves and Fermat's last theorem, Ann. of Math. 141 (1995), 443–551.

[11] R. Taylor and A. Wiles, Ring-theoretic properties of certain Hecke algebras, Ann. of Math. 141 (1995), 553–572.

[12] C. Breuil, B. Conrad, F. Diamond, and R. Taylor, On the modularity of elliptic curves over $\mathbb{Q}$, J. Amer. Math. Soc. 14 (2001), 843–939.

[13] M. F. Islam, TRISDUCTION_Core_Thesis_Fortran_v2_4_0.f90, the register, protocols/Executable Thesis/, 2026 — the kinetic witness, 1346 lines; sealed at cycle fq round 3 after ten adversarial cycles, 32 rounds, 100 findings, zero FATAL, findings supplied by an external reviewer; battery of 248 computed checks over the module, the exhibits, and every symbolic and router procedure; builds clean under -std=f2018 -pedantic -Wall -Wextra -fcheck=all -finit-real=snan, runs to exit 0 under -ffpe-trap=invalid,zero,overflow, and returns identical gated verdicts at -02 and at -02 -fno-fast-math -ffp-contract=off; sha256 head b5d12f73.

[14] M. F. Islam, RA_TOE_Thesis_Fortran_v2_0_0.f90, the register, protocols/Executable Thesis/, 2026 — the RA thesis executed at the reader, 3375 lines; v1.0.0 through v1.23.0, twenty-two versions under two external auditors and a 178,000-iteration deterministic fuzz campaign: fifty-six findings, six refused on printed receipts, fifty earned and repaired; five FORGE self-audit cycles ratoe1–5 sealed at the SELF floor, the fifth closing on v2.0.0 at SEALED-ROUND with six-register coverage and controls 3/3 per round; numerics byte-identical to v1.23.0, sha256 97e5585fa15e66ff...; sealed build gfortran -std=f2018 -02 -fno-fast-math -ffp-contract=off -Wall -Wextra -Wconversion-extra.

[15] M. F. Islam, The Root Axiom Executed: an ontological thesis compiled as a self-demonstrating Fortran program, Math Journal edition, the register, 2026 — the executable-thesis method, 1123-check census, the listing byte-bound by SHA-256 as Appendix A.

[16] G. Cantor, Über eine elementare Frage der Mannigfaltigkeitslehre, Jahresber. Deutsch. Math.-Verein. 1 (1891), 75–78.

- [17] F. W. Lawvere, Diagonal arguments and cartesian closed categories, *Lecture Notes in Mathematics* 92 (1969), 134–145.
- [18] S. C. Kleene, On notation for ordinal numbers, *J. Symbolic Logic* 3 (1938), 150–155.
- [19] A. M. Turing, On computable numbers, with an application to the Entscheidungsproblem, *Proc. London Math. Soc.* 42 (1937), 230–265.
- [20] G. Perelman, The entropy formula for the Ricci flow and its geometric applications, [arXiv:math/0211159](#), 2002; Ricci flow with surgery on three-manifolds, [arXiv:math/0303109](#), 2003.
- [21] H.-D. Cao and X.-P. Zhu, A complete proof of the Poincaré and geometrization conjectures — application of the Hamilton–Perelman theory of the Ricci flow, *Asian J. Math.* 10 (2006), 165–492.
- [22] J. W. Morgan and G. Tian, *Ricci Flow and the Poincaré Conjecture*, Clay Mathematics Monographs 3, Amer. Math. Soc., 2007.
- [23] B. Kleiner and J. Lott, Notes on Perelman's papers, *Geom. Topol.* 12 (2008), 2587–2855.
- [24] R. S. Hamilton, Three-manifolds with positive Ricci curvature, *J. Differential Geom.* 17 (1982), 255–306.