FIGURE 5

THE METHOD IN ONE THEOREM, RUN ON THE ROWS

FOUR INPUTS · WHAT A ROW BUILDS

A ROW OF THE NORMAL FORM
frames, the value, the record of each frame, the record carrying the value with no premise
`NRow · Closure`

A HOST
a frame whose value is exactly the row's sentence

A CALM FRAME
a frame where the value holds

A COUNTER FRAME
a frame where the value fails

ONE THEOREM

`the_method`

nothing before its colon beyond the four inputs

SEVEN CONCLUSIONS · ON NO AXIOM

the sentence is the bit
`sentence_is_the_bit`

the record decides nothing
`record_decides_nothing`

no keyless premise forces the value
`the_wall_on_the_row`

the bit has no uniform answer
`no_uniform_answer`

every route passes the bit
`every_route_passes_the_bit`

either delivery gives the sentence
`delivered_twice`

the upgrade of the bit is adopting the sentence
`upgrade_is_adopting_the_sentence`

RUN ON THE ROWS, AT EVERY HOST

The master builds the four inputs on Navier–Stokes, Yang–Mills, Hodge, BSD and Poincaré at every host, and on Goldbach, and the method returns all seven conclusions on each; where the calm and the counter frame share one record, no predicate of the record decides the value.

`the_method_on_the_rows` · `no_record_predicate_decides_on_four_rows` · `the_closure_on_its_toy_row` · `record_predicate_decides_nothing`

READING theorem on no axiom · on propext (and Quot.sound) · on Lean's standard axioms · definition or structure — names shown by their last component