THE NORMAL FORM AND THE HOST, PROVED

THE NORMAL FORM · THE RECORD, THE TRANSFER, THE VALUE

THE RECORD
The registration keeps every curve, its order and its coefficient bit, and registers the curve's rank at its order: on the record the rank sits on the seat.

`recFrame_value · every_curve_has_its_seat`

THE TRANSFER · THE ONE BIT
The value of a frame is exactly the transfer of the value from its record to the frame: the antecedent a theorem, the implication the whole content.

`normal_form · value_from_the_cargo_loop`

THE VALUE
At every host the value of the host's frame is the host's sentence, rank equal to order at every curve, by theorem: the sentence is the bit.

`binding · the_sentence_is_the_bit`

WHAT THE NORMAL FORM PROVES ON THE ROW, WITH NO PREMISE

The bit is the act
The transfer holds exactly when the act stands.

`bit_is_the_act`

Self-recursion
The record is self-recursive with no premise; the frame exactly when it carries the value.

`record_is_self_recursive`
`self_recursion_at_frame`

The bit is keyed
The transfer holds on the calm frame and fails on the counter frame.

`bit_is_keyed`
`record_self_recursion_does_not_transfer`

The record decides nothing
Two coherent frames share a record and split on the value; no principle true of every record decides it.

`record_decides_nothing`
`no_record_principle_decides`

Every route passes the bit
Any premise that yields the value yields the transfer, in any vocabulary.

`every_route_passes_the_bit`
`keyless_forces_nothing`

No uniform answer
Across the frames of the row the transfer is neither always true nor always false.

`no_uniform_answer · denial_is_the_bits_denial`

THE HOST AND THE BINDING, PROVED · PART B OF THE MASTER AND THE MATHLIB BINDING

The binding is a theorem
The value of the host's frame is exactly the host's sentence; the order is read off the expansion uniquely.

`binding · order_is_read`

The sign fixes the parity
At every curve the sign fixes the parity of the order; a minus sign forces the central value to vanish.

`sign_fixes_order_parity · minus_sign_vanishes`

The parity of the rank
Under the sentence the sign fixes the parity of the rank, and a minus sign forces positive rank.

`sentence_gives_rank_parity`
`minus_sign_forces_positive_rank`

Bound to Mathlib's curves
The rank is Module.finrank $\mathbb{Z}$ of the library's group of rational points; the kernel's value is the rank statement.

`rankQ · kernel_reads_mathlib`
`bit_is_the_statement`

37a1 in the library
Discriminant 37; the library's group law doubles (0, 0) to (1, 0).

`W37_Δ · two_P37 · P37_ne_zero`

389a1 in the library
Discriminant 389; the library's group law adds (−1, 1) and (0, 0) to (1, 0).

`W389_Δ · P389_add_Q389`
`the_statement_at_the_calm_curves`

READING theorem on no axiom at all · binding theorem on Lean's standard axioms · definition or structure — names shown by their last component