The Ten-Level Binding Chain of the Atomic Proof of the Riemann Hypothesis

From the Ground Floor to the Cargo: the Mathematical Perimeter Exhausted by Theorem, the Cargo Delivered by Compute

Analytic number theory

Ten levels, one bind, compute the cargo

Mohammad F. Islam, PhD

Independent researcher · Trisduction Research Group · Correspondence through the Zenodo record of the parent paper

14 October 2026 · Compact companion to The Atomic Proof of the Riemann Hypothesis, third edition v2.0.8, sealed under cycles rha1 and rha2 and bound by the closure mandate · v1.3.0, the formal edition, ten levels, twin of the physical edition v1.2.0, audited under cycle rhc3 · Seed RH_Both_Sides_Seed.lean, edition 2.0.5, sha256 a82ef4f0 ad6ceb43 (full digest at Appendix A), 10,268 lines, 738 theorems, no axiom declared

Abstract. The parent paper carries the Riemann Hypothesis to one proposition from both of its sides, proves that proposition irreducible within its formalized interface, and closes it at a capstone whose every input is printed. This companion states that architecture as one chain of ten levels and nothing else, in its formal edition: the edition for the reader who refuses physics as arbiter of a mathematical sentence and asks for a closure the formal record carries alone. Level 1 is the ground floor, the theorem-grade block of the unconditional route: no premise shared by every reflection-closed configuration, the root included, forces the value, no reading of the record decides it, and every premise that does force it is the value or strictly stronger. Levels 2 to 9 exhaust the mathematical perimeter by theorem: the form, the open leg, the blind record, the premise forced, the refuter barred, terminal saturation, the timeless closure, and the formal terminal, one dot and no third value. Before the cargo the chain has already proved that the demand for an unconditional proof from what the interface shares is blocked at theorem grade: every premise that forces the value is the value or strictly stronger. Level 10 is the cargo, delivered by compute in the author's posit: every verification event carries as its own field that it lands on its state's annihilation, the seed's forgetting, which loses a label when the state is a pair member, and enacts a closed Stage 1 with an empty cone, and the run that compiles the seed is posited as such an event, one that loses a label. A run, like every fact that holds whatever the configuration, forces no value, so its flag is no proof of the value at every closed configuration and the field is the act's, as Level 9 types every proof; from the act, at every resolution $n \geq 1$ at which the zeros of ζ are read, the classical sentence follows under the reader's rule with an empty cone, and, the term at resolution zero empty, printed in the signature of a composition, the act there is exactly the value at every resolution $n \geq 1$. The supply is printed as the one premise on the value, at full force, and the reading at every resolution beside it as the identification it is. No physical premise is required: the five physical premises of the physical edition, with its certified bound and its gap, stand here as fenced, optional corroboration. Every name cited from the seed is a declaration of the seed printed whole in the Appendix, every cone printed for this edition's files is the compiler's, and the three exits are the only ones.

Keywords *Riemann Hypothesis; least erasure; binding chain; atomic proof; Lean 4; axiom cone; compute cargo; verification event; formal closure; optional corroboration; no third position*

* Every theorem named below is in the seed of Appendix A, save the names marked as the Formal Master's or reference 8's where they are cited, the eight compositions of Box 1, and Lean's own `Classical.em` and `Classical.byContradiction`; the seed is edition 2.0.5, sha256 a82ef4f0ad6ceb43 a2d3cc964b110943 dbb02f050ab88ff2 845df1226a321a57, 10,268 lines, 738 theorems, no axiom declared, compiled under core Lean 4.19.0 with exit 0. Lines 1 to 10,110 are edition 2.0.4 byte for byte; the cargo section, headed Level 10 cargo, is appended after line 10,110 and depends on nothing above it. Every cone printed for a seed theorem is the compiler's, `#print axioms` on that seed; the cones of the compositions, of `ActualZerosEvery.atRes`, and of reference 8 are the compiler's on the files Boxes 1 and 2 name; the Formal Master's cones are quoted from the pins in its own file and are not re-run here. The seed's docstrings are its author's commentary and carry no warrant; where one says more than its type, as `ActualZerosEvery`'s that the zero set of ζ read at every

resolution is such a family and `VerificationEvent`'s that one label is forgotten, the type governs and this paper states the type. The rule of grades is the parent paper's: a theorem is stated as proved, a premise is stated as a premise at full force, and an empty cone says a proof uses no axiom and discharges no hypothesis.

1. The chain

The parent paper, *The Atomic Proof of the Riemann Hypothesis* (third edition, v2.0.8, reference 1), is long because it prints everything. This companion is short because it prints the spine. The spine is ten levels. Level 1 is the ground floor: the theorems that block, within the formalized interface, every unconditional route to the value from what reflection-closed configurations share and from the record. Levels 2 to 9 stand on that floor and exhaust the mathematical perimeter: what the hypothesis is, what forces nothing, what the record forgets, what the act forces, what refutes, what saturates, what closes without time, and what the formal terminal is, one proof and no third value. Level 10 is the cargo, delivered by compute in the author's posit: a verification event given by its fields, the forgetting it carries, the floor it witnesses, the closed Stage 1 it enacts, the run that forces no value, and the act from which the classical sentence follows under the reading. The chain is one bind: each level consumes the one below and leaves nothing open above it. Within the formalized interface the value is irreducible by theorem; it is the field the act supplies, and the cargo of this edition is the run that compiles the seed, posited as the event whose act supplies that field.

The two editions. This chain is printed twice, on one spine. Levels 1 to 9 are identical in both: the same seed, the same theorems, the same cones. The editions differ at Level 10, in what supplies the field that Level 9 proves every proof must supply and in the form of the reading through which the classical sentence is concluded. The physical edition (v1.2.0, reference 6) is written for the reader who takes physics as arbiter: the supply is empirical, an off-line zero carried to a charged pair of a physical carrier whose discard costs heat at a temperature floor, and the second door closes under a certified observational bound on eight printed inputs. This formal edition is written for the reader who refuses physics as arbiter of a mathematical sentence: the supply is the act, and its cargo, in the author's posit, is the compute that runs the seed, closed on its own fields with nothing measured. Each edition is complete for its school and is the other's alter ego. The two conditionals are theorem grade and conclude the classical sentence about one object, the zeros of ζ read onto the offset chart under one reader's rule: the physical edition reads them at one configuration $Z\zeta$, this edition as a family over every resolution $n \geq 1$. What carries content is a single resolution, not a single configuration: read at every resolution $n \geq 1$, as a family or collected in one configuration (`value_collected`), the reading is an identification of statements, and read at the configuration of one resolution it carries that resolution's content and is a premise on the value beside the supply (`one_resolution_does_not_decide_the_next`). The physical edition calls its reading an identification of statements, which it is where $Z\zeta$ collects every resolution, its reader's rule reading every zero at every resolution. At every configuration either reads, least erasure and the value are one proposition with no hypothesis (`le_iff_value`). In both editions the supply itself is premise grade, measured in the one and posited in the other. The two supplies are of two structures, an act at one configuration and an act at every resolution, each least erasure at the configurations its edition reads; where $Z\zeta$ collects the family's resolutions and the term at resolution zero is empty, they carry one content, an act at $Z\zeta$ existing exactly where an act at every resolution does (`value_collected`, `the_collected_act_is_the_act_every`), and two independent supplies of it raise neither's grade, since agreement confers no warrant.

Notation. The chart is $\mathbb{Z} \times \mathbb{Z}$, a point (d, t) its offset from the line and its height; the fold is $(d, t) \mapsto (-d, t)$, the registration $(d, t) \mapsto (0, t)$, the line $d = 0$. A configuration is a set of points; `Closed` means fold-closed; `Value S` is every point on the line; `LeastErasure S` is every point fixed by the registration; Part II defines least erasure through the record instead, a world off the line only if every world of its record is, and proves it the value on its chart (`least_erasure_is_the_value`), so the two definitions meet at the value; `ActualZeros` is the act, a closed configuration with least erasure as its field. `le_iff_value` makes least erasure and the value one proposition on every configuration with no hypothesis. A verification event is a move of the apparatus carrier from a state to its annihilation: a pair member lands on the neutral state at its height, its magnitude and sign kept in no part of the landing state, while the event itself records its `before`, and a neutral state stays. The seed names that landing the event's forgetting (`h_forget`, `local_computation_is_forgetting`), and it loses a label exactly when the state is a pair member; `Stage1` is such an event with its forgetting done and the floor witnessed, the floor being that some state is realized, witnessed at the state the event lands on. A Stage 1 closes on its two fields (`stage1_closes`), and every Stage 1 does, so a closed Stage 1 is any Stage 1; closed said of a configuration means fold-closed. The seed states the value on several charts, the offset chart of Parts III and VII, the charts $x =$

2n Re s of Part II, one at each resolution n, x = 2 Re s at resolution one and x = 4 Re s at resolution two, x = 4 Re s of Part IV and x = 2W Re s of Part V; `the_charts_are_one` (Part V-b) [propext, Classical.choice, Quot.sound] maps every chart equivariantly into the offset chart, carries the value across, and makes every act structure of the seed an act of the offset chart at the image of its zero set. The cargo section's points and line are the offset chart's by definition; its carrier is its own copy, beside Part VIII's. A theorem is read on the chart of its part, and the ledger names the part where two parts share a name. The cone of a theorem is what `#print axioms` prints; "none" means that the print names no axiom, Lean's three standard axioms included; a cone that names them is printed as such. "No axiom declared" is a statement about the file: it contains no `axiom` command. The two statements are kept apart throughout.

2. The binding ledger

Level	Name and key idea	Theorems and cones	What is proved	Grade and force
1	**The ground floor: the classical and foundational block.** The mathematical perimeter. Within the interface the unconditional route is blocked by theorem; the paper derives the value from no foundation, and says so.	`the_unconditional_route_is_blocked` [propext, Classical.choice, Quot.sound] · `record_decides_nothing` (Part II) [propext, Quot.sound] · `keyless_forces_nothing` (Part IV) none · `premise_trichotomy` [propext, Classical.choice, Quot.sound] · `independence_forces_truth` [propext, Classical.choice, Quot.sound]	The value is no law of reflection-closed configurations; nothing every closed configuration shares forces it, the root included; no reading of the record decides it, since the true world and the pair world leave one record. Every premise on configurations either fails to force the value somewhere, or forces it and is the value on every closed configuration, or forces it and is strictly stronger. For a foundation complete and sound on the denial, independence would establish the hypothesis. The block is a property of the interface and the record, not a claim about ZFC; toward refutation the channel a foundation keeps is a finite computation that certifies a zero off the line, F-Computed; toward proof, on Part II's chart every sound theory that proves a sentence reading as the line at a world lands on least erasure there (`ladder_proof_lands_on_least_erasure` none), exhibited by a one-sentence theory at a one-point world (`a_sound_theory_may_prove_the_line` none); the seed decides no foundation's route at ζ, and Level 9 types any proof such a route yields as a supply of the one field.	**THEOREM** · unconditional block, within the interface · the bit forced external to the interface's shared laws
2	**The form: the hypothesis is least erasure.**	`least_erasure_is_the_value` none · `least_erasure_unconditional` none · `le_iff_value` none · `prime_side_halts` [propext, Quot.sound] · `centre_is_the_line` [propext, Quot.sound] · `row_four_from_the_zero_side` none · `the_one` [propext, Quot.sound]	On every world least erasure holds exactly when the hypothesis does, with no hypothesis and no premise. The prime bound on a closed configuration is the value; every computation reading an act reports only zeros on the line. Listing any members with their mirrors, the real parts balance on the line: the centre of every nonempty finite reflection-closed family is the line. Least erasure, the value and the root read twice are one predicate by equality.	**THEOREM** · forced equality · one predicate, zero gap
3	**The open leg: nothing forces.**	`prime_freedom_forces_nothing` [propext, Quot.sound] · `keyless_forces_nothing₂` [propext, Quot.sound] · `no_closed_principle_decides` none · `centred_yet_off` none · `the_loop` [propext, Classical.choice, Quot.sound] · `faithful_arrow_side_test` [propext, Quot.sound] · `an_off_line_zero_comes_in_four` [propext, Quot.sound]	No principle true on every closed configuration decides the value: whatever holds on all of them holds on the off-line pair, which lacks it. The free basis at the primes forces nothing. On the chart x = 4 Re s of Part IV the pair at Re s = 1/4 and 3/4, the points (1, 0) and (3, 0) about the line x = 2, is reflection-closed, centred on the line, inside the strip, and off it. The loop through the root reaches the zeros exactly when the value already holds. The Euler product at the poles, the zero-free region, the verification, the empty low band, the conjugate symmetry and finitely-many-off hold together on a model whose only off-line zeros are four points, a mirrored pair at a height above the verified height (reference 4) and its conjugate at the negative of that height, as a closed and conjugate-closed world with an empty low band forces.	**THEOREM** · structural irreducibility · nothing shared forces

Level	Name and key idea	Theorems and cones	What is proved	Grade and force
4	**The blind record: the side is erased.**	`record_decides_nothing` (Part II) [propext, Quot.sound] · `no_reading_decides_in_the_strip` [propext, Quot.sound] · `unicorn_block` (Part II) [propext, Quot.sound] · `unicorn_blocked_on_the_chart` [propext, Quot.sound] · `monism_is_the_sole_witness` [propext, Quot.sound] · `flowed_record_forgets` [propext, Quot.sound]	No reading that respects the record agrees with the hypothesis on every fold-closed world, nor on the strip configurations. Above every height no reading of the record decides the side of a point: the registered world and the pair world of the off point are one record, one bit erased. After one step of the toy flow no readout of the flowed record decides whether the width is zero, the RH bit. Every faithful witness of the value is the root read twice; the root alone decides no value.	**THEOREM** · forced forgetting · irreducible blindness
5	**The premise forced: the act.**	`rh_from_the_act` none · `the_witness_forced_by_the_act` none · `rh_is_the_weakest_forcing_premise` none · `root_at_zeros_is_least_erasure` none · `two_denials` (Part III) none · `the_last_act` none · `the_act_is_the_premise_packaged` none · `the_atomic_proof`, parts II to IV [propext, Quot.sound]	From the act the hypothesis. The hypothesis forces the line, and every premise that forces the line implies the hypothesis on every fold-closed world: the weakest forcing premise is itself. The root read at the zeros is least erasure. An act exists at a configuration exactly when it is closed and least erasure holds there: the act is the premise packaged. Every deed being the supply at a closed zero set is exactly the value there; as a law over every closed zero set it is refuted. Two denials, one shape, two layers: every no re-enacts the root, the no to the root is refuted by its own deed, and the no to the hypothesis is a lack of the root read twice, which the false world lacks and the true world of the same record carries.	**THEOREM** · form, place, content and denial forced · the weakest forcing premise is itself
6	**The barred refuter: no arrival.**	`the_tenth_is_the_refuter` [propext, Classical.choice, Quot.sound] · `the_tenth_is_barred_by_the_act` none · `no_arrival_off_the_line_on_the_act` none · `row_four_from_the_zero_side` (ii) none · `open_strip_forces_at_resolution_one` [propext, Quot.sound] · `the_act_at_every_resolution` [propext, Quot.sound]	On every configuration a computed point off the line is exactly the failure of the line: the one refuter. On the zero set the act supplies, no point lies off the line and no arrival stands off it; a report holding an off-line zero reads no act. The first two are on Part II's chart $x = 2 \operatorname{Re} s$, where the open strip is the line itself, and the second two on the offset chart; a zero of the open strip off the line by a rational margin η, $0 < \operatorname{Re} s < 1$ and $\lvert\operatorname{Re} s - 1/2\rvert > \eta > 0$, is placed off the line of the offset chart at every resolution beyond $1/(2\eta)$ by the reader's rule, which is the content of the reading and no theorem of the seed; read so, it is a point off the line of the offset chart, and on the act's field at every resolution none exists.	**THEOREM** · the refuter named, and barred on the act · no arrival; the reader's rule an input
7	**Terminal saturation, future-proofed.**	`nothing_left_open_on_the_act` none · `the_atomic_proof`, part V [propext, Quot.sound] · `the_act_at_every_resolution` [propext, Quot.sound] · `the_capstone` [propext, Quot.sound] · `the_unicorn_contained_abs` [propext, Quot.sound] · `reality_transported` [propext, Quot.sound] · `upstream_is_not_forced` [propext, Quot.sound]	On the act nothing is left open: the hypothesis, least erasure, no point off the line, the zero set its own record, every consequence of the hypothesis. Over every index, resolution zero included, closed configurations carry the act exactly where the value holds, and on it the value, the zero reports and the prime bound hold. At every height the value is its verified part and its part above; given the verified part, exactly the part above. In the toy flow, once every zero is real every zero stays real; the upstream direction is supplied, never forced.	**THEOREM** · terminal saturation · future-proofed above every height
8	**The timeless closure: zero gap.**	`vocabulary_law` none · `every_face_proves_every_face` none · `the_timeless_zone_closed` [propext, Classical.choice, Quot.sound] · `the_annihilation_closure` [propext, Quot.sound] · `the_one` [propext, Quot.sound]	On every world a consequence of the hypothesis is a consequence of least erasure and conversely, and a premise entailing one entails the other; every face proves every face through its cited field. On every configuration four names are one proposition; monism is the sole witness and no witness is universal; the timeless zone, stated over a self-grounding root, carries no act of the zero set and no premise on the value; timelessness is determinacy, not selection. What the hypothesis is, is fixed completely.	**THEOREM** · annihilating closure · zero-gap equality

Level	Name and key idea	Theorems and cones	What is proved	Grade and force
9	**The formal terminal: one dot, no third value.**	`the_atomic_necessity` [propext, Quot.sound] · `the_form_is_the_hypothesis` [propext, Quot.sound] · `the_form_of_a_field` none · `accepting_rh_forces_the_atomic_proof` [propext, Classical.choice, Quot.sound] · `both_values_atomic` [propext, Classical.choice, Quot.sound] · `premise_trichotomy` [propext, Classical.choice, Quot.sound] · `bidirectional_halted_uniduction` [propext, Quot.sound] · `the_two_sided_closure` [propext, Classical.choice, Quot.sound]	Every proof of the value at a closed zero set, from any premise whatever, is a supply of the act's field there; any two proofs of the value are one proof; the supply at the zero set is unique; the act's type is the field of the value, supply for supply, and the form of a field holds at the value and at its denial alike. At every closed zero set the value holds or a point of the set stands off the line, and not both; an act exists exactly where the value holds; accepting the hypothesis forces acceptance of this atomic proof. At every closed zero set the zero reports halt at the value, the prime bound halts at the value, and the two halt at one proposition. The whole is bound in one theorem by its exact type. Here the demand for an unconditional proof from what the interface shares is answered before the cargo: such a proof would be a proof from what every closed configuration shares, and Level 1 proves there is none; every proof there is, is a supply of the one field.	**THEOREM** · one dot, the supply unique · two doors, no third value · the demand for an unconditional proof from what the interface shares blocked
10	**Cargo: compute delivered, in the author's posit.** The verification event by its fields, the forgetting, the floor, Stage 1, the run that forces no value, and the act.	Carrier (cargo section): `PhysicalCarrier`, `annihilate` · Event: `local_computation_is_forgetting` none · Floor: `event_witnesses_floor` none · Stage 1: `stage1_closes` none, `computation_enacts_stage1` (a definition) none · Packaged (Box 1): `cargo_binding_on_the_seed` none, the binding reference 8 states on its own copy of the types · Run (Part IV-b): `the_run_witnesses_a_run` none, `the_run_does_not_force_the_value` none, `force_witness_closure` none · Conditional (Box 1): `classical_rh_from_the_act_every` none, from `value_from_the_act` (Part III) none and `ActualZerosEvery.atRes` (Part V-b) none; the act packaged, `the_act_every_is_the_value_packaged` [propext, Quot.sound], from `the_act_at_every_resolution` (Part V-b) [propext, Quot.sound], and its refusal `refusing_the_act_is_the_denial` [propext, Quot.sound]; `value_collected` none; at one configuration `classical_rh_from_the_act` none, from `classical_rh_iff_le_of_reading` none and `supply_is_the_premise` none · Optional corroboration (Section 5): `stage2_optional_corroboration` [propext, Classical.choice, Quot.sound], `classical_rh_from_physico_formal_closure` none, eight inputs	The cargo section's carrier has two constructors, a self-conjugate state at a height and a member of a conjugate pair of magnitude m + 1 at a height with a sign; annihilation sends a pair member to the neutral state at its height, its magnitude and sign kept in no part of that state, and leaves a neutral state where it is, facts that hold by computation on this copy of the carrier; on its own copy Part VIII proves that annihilation fixes exactly the neutral states and merges the two signs (`annihilate_fixes_iff_neutral`, `annihilate_forgets`, `pair_is_two_states_one_image`), the magnitudes merging by computation there too. A verification event is a move of the carrier from a state to its annihilation, carried as its own field `h_forget`, its forgetting in the seed's name, which loses a label exactly when the state is a pair member; a neutral event satisfies every cargo theorem and loses nothing, so the posit reads the run of record as an event that loses one. Stage 1's floor is the existence of the state the event lands on, which every event has; `event_witnesses_floor` carries the floor to any realization predicate that landing state satisfies, the predicate and its hypothesis being the reader's. Every verification event enacts a closed Stage 1, forgetting done and floor witnessed, and every closed Stage 1 carries its forgetting: the event is necessary and sufficient for a closed Stage 1, the one a projection of the other, and nothing beyond the event is required; that the cargo is compute is the author's posit and stands in no type. A run witnesses that it ran, and a run, like every fact that holds whatever the configuration, forces no value at every closed configuration, so its flag is no proof of the value at every closed configuration; the field is the act's, as Level 9 types every proof. Beside the deed the value stands on the field the act supplies. From an act at every resolution at which the zeros of ζ are read, the classical sentence follows under the reader's rule with an empty cone; where the term at resolution zero is empty, the one hypothesis the packaging's type adds, the act is exactly the value at every resolution n ≥ 1, the closedness of the configurations following from the value (`the_act_every_is_the_value_packaged`). The run that compiles this seed is posited as a verification event whose act supplies that field. No term of type `Stage1` → `ClassicalRH` exists in the seed and none is claimed: the cargo's theorems hold of every event at theorem grade, the act is the one premise on the value under the reading of record, and the author's posit names the run of record, as such an event, its source.	**THEOREM** on the cargo's statements, empty cone · compute posited as the cargo · the supply **PREMISE** at full force · physics optional

Level	Name and key idea	Theorems and cones	What is proved	Grade and force

3. The single bind

1	GROUND FLOOR	unconditional route blocked	the_unconditional_route_is_blocked	
2	FORM	RH is least erasure	le_iff_value, least_erasure_unconditional	
3	OPEN LEG	nothing shared forces	no_closed_principle_decides	
4	BLIND RECORD	the side erased	record_decides_nothing	
5	PREMISE FORCED	the act	rh_is_the_weakest_forcing_premise	
6	BARRED REFUTER	no arrival on the act	no_arrival_off_the_line_on_the_act	
7	TERMINAL, FUTURE	saturation above every height	nothing_left_open_on_the_act reality_transported	
8	TIMELESS CLOSURE	zero gap	the_one, vocabulary_law	
9	FORMAL TERMINAL	one dot, no third value	the_atomic_necessity accepting_rh_forces_the_atomic_proof	
10	CARGO	compute delivered (posit) the run forces no value the conditional, on the act	computation_enacts_stage1, stage1_closes the_run_does_not_force_the_value classical_rh_from_the_act_every	

Each level consumes the one below it in the sense of statements: it takes as its object what the level below leaves open, and leaves less. The proof terms of Level 10 are three, and they do not compose into one term: the cargo's use the cargo section alone; the run's use Part IV-b; the conditional of Box 1 at every resolution uses Parts III and V-b, and at one configuration Part VII. Counted by every declaration a proof term reaches, through statements and proofs alike, the cargo's, the run's and the conditional at every resolution reach no theorem the ledger names at Levels 1 to 9; the conditional at one configuration reaches `le_iff_value` of Level 2, through `classical_rh_iff_le_of_reading`; and Box 1's packaging calls `the_act_at_every_resolution` of Levels 6 and 7 directly, its refusal and the collected act through the packaging, and all three reach through it seven more names of Levels 2, 3 and 5 to 9 (`the_atomic_proof`, `the_atomic_necessity`, `bidirectional_halted_uniduction`, `no_closed_principle_decides`, `prime_side_halts`, `row_four_from_the_zero_side`, `the_one`). The event of the cargo and the run of Part IV-b are two types, and no term of the seed identifies them or runs from either to an act at the configurations where the zeros of ζ are read; the line a reader draws from the run to the act is the posit of Section 4, printed as such. Levels 1 to 9 are not steps inside the cargo, the run or the conditional at every resolution, and enter the packaging only through `the_act_at_every_resolution`; they are the theorems that make the act the only supply there is, which is why a reader must meet them first. Level 1 forces the bit external to the interface's shared laws; Levels 2 to 9 prove that the bit is one proposition, that nothing the interface shares supplies it, that the record has forgotten it, that the act supplies it and nothing weaker does, that its one refuter is a certified zero off the line, that on the act nothing is left open at any height, that the closure needs no time, that every proof of it is one proof, and that there is no third value. Level 10 delivers the cargo, compute in the author's posit, and prints the supply: every verification event enacts a closed Stage 1, by theorem; a run forces no value, by theorem; from the act the classical sentence follows under the reader's rule, by theorem; and the act is the one formal premise, which the author's posit, standing in no signature, names the run of record as supplying. There is no level above 10 and no door beside it, and the second half is a theorem, not a boast: every proof of the value at a closed zero set, from any premise whatever, a property specific to ζ that the interface does not formalize included, is a supply of the one field (`accepting_rh_forces_the_atomic_proof`, `the_atomic_necessity`, each quantified over every proposition). A proof from the analytic side, when it comes, is Level 10's door entered from the other end, not a second door. What the interface's shared laws cannot do is decide the value (Level 1); what no proof can do is reach the value except as a supply of the field (Level 9).

4. The fixed stance

Level 1 answers the foundational question. Whether the value is a theorem of ZFC is not what the chain decides, and the chain says why: within the formalized interface no premise shared by every reflection-closed configuration, the root included, forces the value, no reading of the record decides it, and every premise that does force it is the value or strictly stronger (`the_unconditional_route_is_blocked`, `premise_trichotomy`). The parent paper derives the hypothesis from no set-theoretic foundation and says so; Level 1 is the theorem-grade block on

the interface's side, that no law the interface shares, the root included, decides the value. Toward refutation the one channel a foundation keeps is F-Computed, a finite certificate of a zero off the line; on the act's field no point stands off the line (`no_arrival_off_the_line_on_the_act`). Toward proof, on Part II's chart every sound theory whose proved sentence reads as the line at a world lands on least erasure there (`ladder_proof_lands_on_least_erasure`); the seed decides no foundation's route at ζ, and Level 9 types whatever such a route proves: a supply of the one field.

Before the cargo: the demand for an unconditional proof from what the interface shares is blocked, by theorem. A reader who reaches Level 10 and asks for an unconditional proof from what the interface shares instead is asking for what Levels 1 to 9 have already proved cannot be had from the interface: no premise shared by every closed configuration forces the value (`no_closed_principle_decides`, `the_unconditional_route_is_blocked`), every premise that forces it is the value or strictly stronger (`premise_trichotomy`, `rh_is_the_weakest_forcing_premise`), and every proof of the value at a closed zero set, from any premise, is a supply of the one field (`accepting_rh_forces_the_atomic_proof`). The demand is therefore not refused; it is answered at theorem grade, and the answer is that the bit is external to the interface's shared laws. The only question Levels 1 to 9 leave is where the bit comes from, and Level 10 answers it formally with the act, printed as an input, and names its source in a posit printed as such. An objection to Level 10 that has not met Levels 1 to 9 objects to the one door they leave open, and offers no other, because by theorem there is no other.

The capstone of record. Level 10 closes on the cargo, the run and the conditional, each at theorem grade, and on one formal premise; every formal input stands in a signature, and the premise is the act's field `supply`, by its type (`supply_is_the_premise`). Beside the formal premise stands the author's posit that the run of record supplies it, which stands in no signature and is printed as what it is. The cargo: `computation_enacts_stage1` is a definition, a total map from verification events to closed Stage 1s; `stage1_closes` returns a Stage 1's two fields, the forgetting done and the floor witnessed; Box 1 packages the two directions on the seed's own types as `cargo_binding_on_the_seed`, every closed Stage 1 carrying its forgetting and every verification event the event of a closed Stage 1; reference 8 states the same binding, `cargo_binding_necessary_and_sufficient` (reference 8), on its own copy of the types, which are separate declarations; all four cones are empty. The run: `the_run_witnesses_a_run` turns a run that ran into the existence of one, `the_run_does_not_force_the_value` proves that it forces no value at every closed configuration, as `the_deed_forces_nothing` proves of every fact that holds whatever the configuration, and `force_witness_closure` binds a deed of the substrate and an act into one theorem in which the value stands on the field the act supplies and the deed stays free; all three cones are empty. The conditional: Box 1 prints eight compositions, compiled against the seed; two carry the conditional, with empty cones; two package the act and its refusal, at [propext, Quot.sound]; one collects every resolution in one configuration, with an empty cone, and one carries the act there to the act at every resolution, at [propext, Quot.sound]; one shows the reading at every resolution keyed, and one binds the cargo, with empty cones. At every resolution, `classical_rh_from_the_act_every` takes the reader's rule `h_read`, the classical sentence read as the value of the configurations R n at which the zeros of ζ are read at every resolution $n \geq 1$, the bound printed in its type, and an act at every resolution with those configurations as its zero sets, and returns the classical sentence; each step is `value_from_the_act` at one resolution, through `ActualZerosEvery.atRes`. At one configuration Zζ, `classical_rh_from_the_act` does the same through `classical_rh_iff_le_of_reading` and `supply_is_the_premise`. Two inputs stand in each conditional's signature, the reading and the act, and no other; the packaging adds one hypothesis, the empty term at resolution zero, printed as `h0`, the closedness of the configurations following from the value. At every resolution $n \geq 1$, as a family or collected in one configuration (`value_collected`), the reading is an identification of statements; at the configuration of one resolution it carries that resolution's content and is a premise on the value beside the act. The reading of record is the first, because its type prints that it reads every resolution $n \geq 1$, where the one-configuration form leaves the configuration to the reader. The act is the supply, the one premise on the value under the reading of record: where the term at resolution zero is empty, the one hypothesis the packaging's type adds, an act at every resolution exists exactly where the value holds at every resolution $n \geq 1$ (`the_act_every_is_the_value_packaged`, from `the_act_at_every_resolution`, first conjunct), so the premise is the value packaged as a field; at each resolution Level 9 proves every proof of the value there a supply of the act's field at that configuration (`accepting_rh_forces_the_atomic_proof`, on the offset chart), and the composition assembles the family. The premise: the act at the configurations where the zeros of ζ are read; the author's posit names the run as its source. An empty cone discharges no hypothesis: each deduction uses no axiom and runs on exactly the inputs printed, and the conclusion stands at the grade of its weakest input, which is the supply.

Box 1 | the conditional of Level 10, at every resolution and at one configuration, the act packaged, and the cargo's binding, composed and compiled against the seed

```
namespace ComposedConditional
open RememberedOffered Hardening
/-- At every resolution, the reader's rule. -/
theorem classical_rh_from_the_act_every {ClassicalRH : Prop} {R : Nat → Config}
    (h_read : ClassicalRH ↔ ∀ n, 1 ≤ n → Value (R n)) (Z : Charts.ActualZerosEvery) (hZ : Z.zeros = R) :
    ClassicalRH :=
  h_read.mpr (fun n _ => hZ ▸ value_from_the_act (Z.atRes n))
/-- At one configuration. -/
theorem classical_rh_from_the_act {ClassicalRH : Prop} {Zζ : Config}
    (h_read : ClassicalRH ↔ Value Zζ) (A : ActualZeros) (hA : A.zeros = Zζ) : ClassicalRH :=
  (classical_rh_iff_le_of_reading h_read).mpr (hA ▸ supply_is_the_premise A)
/-- The act at every resolution is the value packaged; the one added hypothesis is the empty term at resolution
↪  zero,
    the closedness of the configurations following from the value. -/
theorem the_act_every_is_the_value_packaged {R : Nat → Config} (h0 : R 0 = fun _ => False) :
    (∃ Z : Charts.ActualZerosEvery, Z.zeros = R) ↔ ∀ n, 1 ≤ n → Value (R n) := by
  have hv : (∀ n, 1 ≤ n → Value (R n)) → ∀ n, Value (R n) := fun h n => by
    cases n with
    | zero => rw [h0]; exact fun _ hp => hp.elim
    | succ k => exact h (k + 1) (Nat.succ_le_succ (Nat.zero_le k))
  refine ⟨fun ⟨Z, hZ⟩ n _ => hZ ▸ value_from_the_act (Z.atRes n), fun h => ?_⟩
  have hR : ∀ n, Closed (R n) := fun n p hp => by
    have hl : p.1 = 0 := hv h n p hp
    obtain ⟨d, t⟩ := p
    change d = 0 at hl
    subst hl
    exact hp
  exact (Charts.the_act_at_every_resolution R hR).1.mpr (hv h)
/-- With the reading granted, asserting that no act stands is the denial. -/
theorem refusing_the_act_is_the_denial {ClassicalRH : Prop} {R : Nat → Config}
    (h_read : ClassicalRH ↔ ∀ n, 1 ≤ n → Value (R n)) (h0 : R 0 = fun _ => False) :
    (¬ ∃ Z : Charts.ActualZerosEvery, Z.zeros = R) ↔ ¬ ClassicalRH := by
  rw [the_act_every_is_the_value_packaged h0, h_read]
/-- Every resolution collected in one configuration: its value is the value at every resolution n ≥ 1. -/
theorem value_collected {R : Nat → Config} :
    Value (fun p => ∃ n, 1 ≤ n ∧ R n p) ↔ ∀ n, 1 ≤ n → Value (R n) :=
  ⟨fun h n hn p hp => h p ⟨n, hn, hp⟩, fun h p ⟨n, hn, hp⟩ => h n hn p hp⟩
/-- Every resolution collected in one configuration carries the act's content: an act there exists exactly where an
    act at every resolution does, the term at resolution zero empty. -/
theorem the_collected_act_is_the_act_every {R : Nat → Config} (h0 : R 0 = fun _ => False) :
    (∃ A : ActualZeros, A.zeros = fun p => ∃ n, 1 ≤ n ∧ R n p) ↔ ∃ Z : Charts.ActualZerosEvery, Z.zeros = R := by
  rw [the_act_every_is_the_value_packaged h0, ← value_collected]
  constructor
  · rintro ⟨A, hA⟩
    exact hA ▸ value_from_the_act A
  · intro v
    refine ⟨⟨_, fun p hp => ?_, (twins_on_every_world _).mpr v⟩, rfl⟩
    have hl : p.1 = 0 := v p hp
    obtain ⟨d, t⟩ := p
    change d = 0 at hl
    subst hl
    exact hp
/-- The reading at every resolution is keyed, with the term at resolution zero empty: the family empty at zero and
↪  the
    pair world above it. -/
theorem the_reading_every_is_keyed :
    ∃ (P : Prop) (R : Nat → Config), R 0 = (fun _ => False) ∧ (∀ n, Closed (R n)) ∧
      ¬ (P ↔ ∀ n, 1 ≤ n → Value (R n)) :=
  ⟨True, fun n => match n with | 0 => fun _ => False | _ + 1 => pairWorld offPoint, rfl,
   fun n => match n with | 0 => fun _ hp => hp.elim | _ + 1 => pair_world_closed offPoint,
   fun h => pair_world_lacks_value offPoint off_point_is_off ((h.mp trivial) 1 (Nat.le_refl 1))⟩
/-- The cargo's binding, on the seed's own types. -/
theorem cargo_binding_on_the_seed :
    (∀ s : ApparatusCargo.Stage1, s.event.after = ApparatusCargo.annihilate s.event.before) ∧
    (∀ e : ApparatusCargo.VerificationEvent, ∃ s : ApparatusCargo.Stage1, s.event = e) :=
  ⟨fun s => (ApparatusCargo.stage1_closes s).1, fun e => ⟨ApparatusCargo.computation_enacts_stage1 e, rfl⟩⟩
```

```
end ComposedConditional

'ComposedConditional.classical_rh_from_the_act_every' does not depend on any axioms
'ComposedConditional.classical_rh_from_the_act' does not depend on any axioms
'ComposedConditional.the_act_every_is_the_value_packaged' depends on axioms: [propext, Quot.sound]
'ComposedConditional.refusing_the_act_is_the_denial' depends on axioms: [propext, Quot.sound]
'ComposedConditional.value_collected' does not depend on any axioms
'ComposedConditional.the_collected_act_is_the_act_every' depends on axioms: [propext, Quot.sound]
'ComposedConditional.the_reading_every_is_keyed' does not depend on any axioms
'ComposedConditional.cargo_binding_on_the_seed' does not depend on any axioms
'Charts.ActualZerosEvery.atRes' does not depend on any axioms
```

Appended to the seed of Appendix A and compiled under core Lean 4.19.0, exit 0. The compositions are not theorems of the seed; the declarations they compose are. The conditionals' inputs are the reading and the act; no verification event and no run appears in their signatures, and no arrow runs from Stage 1 to an act at the configurations R.

The reading. The reading `h_read` identifies the classical sentence with the value of the configurations at which the zeros of ζ are read, under the reader's rule of the parent paper: a zero off the line by a rational margin η is read off the line at every resolution beyond $1/(2\eta)$, and a zero closer to the line than the resolution's half-step is read onto it. Read at every resolution $n \geq 1$, resolution zero being no reading and the family's term there the empty configuration, the hypothesis `h0` of the compositions that package the act, the reading is an identification of statements; the interface proves no such identification as a law, at one configuration (`the_reading_is_keyed`) or at every resolution with the term at resolution zero empty (`the_reading_every_is_keyed`, Box 1), so on the chart it enters as an input. Read at one resolution, it carries that resolution's content, since a zero pair whose reading at resolution four has the value can have a reading at resolution fifty that lacks it (`one_resolution_does_not_decide_the_next` none); the reading of record is therefore the one at every resolution, the form Box 1 compiles first. The Formal Master (reference 7, version 3.0.8) carries the seed's theorems under a Mathlib import, their proofs adjusted to that environment, and states the reading over $\mathbb{C}$ as a theorem against Mathlib's own definition, `BoundChainMathlib.h_read_proved` (Formal Master), `RiemannHypothesis ↔ Value ZetaZeros`, where the configuration is the zero set itself and no resolution enters. The file pins its cones with `#guard_msgs`, so a compile of it that exits 0 is one in which every pin held; this edition's toolchain carries no Mathlib and does not run it. It states the gap over $\mathbb{C}$ exactly as Level 4 states it on the chart: `BoundChainMathlib.transport_zeta` (Formal Master) proves that carrying least erasure from the record `Rec M` back to `M` is the value of `M`, so the record has least erasure by construction (`BoundChainMathlib.record_has_least_erasure`, Formal Master, Part X) and the zeros have it exactly when the field is supplied. It then states this edition's Level 10 over $\mathbb{C}$: the record side is supplied unconditionally (`BoundChainMathlib.cargo_at_zeros`, Formal Master, `LeastErasure (Rec ZetaZeros)`); the premise is Mathlib's hypothesis in fixed-point form (`BoundChainMathlib.h_id_proved`, Formal Master, `RiemannHypothesis ↔ LeastErasure ZetaZeros`); five faces, the transport from the record, the equivalence with the record, the pointwise coincidence with the record, the containment in the record and the hypothesis's self-verification, are each equivalent to that hypothesis (`BoundChainMathlib.zeta_ra_loop`, Formal Master, [propext, Classical.choice, Quot.sound]); and the file's own header names its residual goal, `LeastErasure ZetaZeros`, the act's field at the unprojected zeros, which no leg of the loop discharges. The Master's one open goal over $\mathbb{C}$ is this edition's one premise. Its cones are its own and are pinned in its own file, its master closure `FormalMasterClosure.the_flipped_formal_master_closure` (Formal Master) at [propext, Classical.choice, Quot.sound], which carries among its conjuncts, on the seed's own types, the forgetting of every event and the sufficient direction of the cargo's binding; nothing in this paper's ledger rests on it, and it is cited as corroboration over $\mathbb{C}$.

The boundary. A formal system proves nothing about the physical universe, and this edition asks nothing of it. The cargo is closed on the event's own fields: no vacuum datum, no residual bound, no realization predicate for the zeros of ζ, and no population, rate or coupling floor enters it. Two things stand outside the theorems: the reading, an input of every conditional, an identification of statements at every resolution $n \geq 1$ and a premise on the value at the configuration of one resolution; and the act at the configurations where the zeros of ζ are read, the premise on the value, an input of every conditional. The author's sentence that the run which compiled this seed is a verification event whose act is that premise names the premise's source; it stands in no signature and adds no warrant. The truth-value of the conclusion is conditional on the reading and the act, exactly and only.

The run of record. The compute this edition takes as its cargo is printed with its receipt. A run witnesses that

it ran (`the_run_witnesses_a_run`), and its flag is no proof of the value at every closed configuration (`the_run_does_not_force_the_value`); the receipt witnesses the run and is no such proof.

Box 2 | the run of record

```
toolchain   Lean (version 4.19.0, x86_64-unknown-linux-gnu, commit 6caaee842e94, Release), core, no import
file        RH_Both_Sides_Seed_v2.0.5.lean   10,268 lines
sha256      a82ef4f0ad6ceb43a2d3cc964b110943dbb02f050ab88ff2845df1226a321a57
compile     exit 0 · no error · no warning (the unused-variable linter is off for one theorem,
            stage2_optional_corroboration) · every #guard_msgs cone pin passed
census      738 theorems · 0 axiom commands · 0 sorry / admit / native_decide outside comments
cones       #print axioms on all 738: none 428 · [propext] 42 · [propext, Quot.sound] 210
            · [propext, Classical.choice, Quot.sound] 58 · sorryAx 0
cargo       local_computation_is_forgetting, event_witnesses_floor, stage1_closes,
            computation_enacts_stage1: none · stage2_optional_corroboration:
            [propext, Classical.choice, Quot.sound]
ref. 8      Cargo_Delivered_Hardened.lean, a separate file with its own copy of the types ·
            184 lines · sha256 9b4f663ff6bd14a2... · exit 0 · every pin passed ·
            cargo_binding_necessary_and_sufficient: none
```

The three exits. The two doors of Level 9 are the two values, the value or a point off the line; the three exits are the ways a reader refuses a conclusion of the chain, across its two editions. Two bear on this edition's conclusion, and the third on the corroboration of Section 5 alone. F-Computed: a non-trivial zero of ζ certified off the critical line by interval arithmetic; read at a resolution beyond $1/(2\eta)$ it is a point off the line, the one refuter, and on the act's field at every resolution it does not exist (`no_arrival_off_the_line_on_the_act`, `the_act_at_every_resolution`); over $\mathbb{C}$ the Formal Master states the refuter natively, an off-line zero of ζ being exactly the failure of Mathlib's hypothesis (`BoundChainMathlib.offline_zero_iff_not_rh`, Formal Master). F-Bridge: the refusal by name of the reading, or of the supply: in this edition the act at the configurations where the zeros of ζ are read; in the physical edition a physical premise or the observational model, as that edition states it, of which a denial of the classical sentence, with the reading, the bound, the gap and the signal floor granted, forces a refusal of the realization of one shape on the carrier, a read zero off the line realized in no measured register (`the_one_exit_is_a_second_register`). In this edition, refusing the reading, or declining to grant the act without asserting its absence, holds the classical sentence open, the position Level 1 proves the interface leaves available; asserting that no act stands there, with the reading granted and the term at resolution zero empty, is the denial of the classical sentence (`refusing_the_act_is_the_denial`), owned as such. Refusing only the author's posit about the act's source, while granting an act, is no exit, since Box 1 needs no run. Every branch leaves the cargo's theorems standing, since they hold of every event with an empty cone. F-Flux: an unaccounted residual heat flux of the vacuum detected above the bound B.ε within the dataset, window and background model the bound was read from; it bears on the optional corroboration of Section 5 alone and leaves the cargo untouched. Given the reading and the act, rejecting this edition's conclusion contradicts Box 1, so rejecting it requires naming F-Computed or F-Bridge; F-Flux refuses the physical edition's conclusion and leaves this one untouched; and there is no fourth exit for either.

5. The corroboration, optional and fenced

Nothing in this section is required. The cargo of Level 10 closes without it, and a reader who refuses every physical premise below leaves the cargo, the conditional and every grade exactly where they stand. It is printed because it is the physical edition's Level 10, carried whole, so that a reader of either school meets the other's route at its own grade.

Part VIII of the seed gives the physical carrier by its constructors: a self-conjugate state at a height, the neutral sector, and a member of a conjugate pair of magnitude $m + 1$ at a height with its sign, the charged sector; charge conjugation C fixes the first and flips the sign of the second (`C_involutive`, `annihilate_lands`, `annihilate_fixes`, `annihilate_forgets`, `annihilate_fixes_iff_neutral`, `pair_is_two_states_one_image`, `the_closure_on_the_physical_carrier`, none). `map_zero_to_carrier` is a total bijection with the chart under which the fold is C, the line is the neutral sector and the registration is annihilation (`map_left_inverse`, `map_right_inverse`, `map_fold`, `map_neutral_iff_onLine`, `map_reg`, `le_transports`, none). A zero off the line is

a charged state that annihilation does not fix and sends with its partner to one state: the mathematical violation forces the physical discard of one label, kept in no state (`mathematical_violation_forces_physical_discard`, `on_line_discards_nothing`, none). The discard is one erasure of the companion kernel (reference 2); its entropy drop is ln 2 per label as the kernel lists labels, a count of the listed labels rather than a function of the point set; the heat per label is Landauer's law (reference 3) entered as a definition in the kernel's units, $k_B = 1$, temperatures in millikelvin and ln 2 scaled by 10^6, so that the SI heat is k_B times the kernel's number divided by 10^9, with ln 2 truncated at the sixth decimal, which lowers the gap and never raises it; a temperature floor T_0 is a heat floor $q_0 = T_0 \ln 2$, with $T_0 = 2.725$ K the kernel's reference (`entropy_of_discard`, `annihilation_drops_one_ln2`, `heat_floor_from_temperature`, `heat_at_cmb_positive`, `discard_forces_heat_generation`, none). An exact null, at positive rate and heat, forces the population to zero; a bound at finite sensitivity, at rate and heat at or above their floors r_0 and q_0, bounds it, $\rho\ r_0\ q_0 \le B.\varepsilon$, and does not empty it (`null_forces_zero`, `density_bound_from_residual_bound`, none). The detection gap $\delta = n_0\ r_0\ q_0$ is uniform, independent of the carrier and of which point stands off the line (`detectionGap_pos`, `every_violation_exceeds_detection_gap`, none).

The capstone of this route, `classical_rh_from_physico_formal_closure`, takes eight inputs, the reading `h_read`, the realization `h_realize`, the floors `h_pop`, `h_rate`, `h_temp`, the coupling `h_couple`, the certified bound B with $B.R \le B.\varepsilon$, and the gap `h_gap`, $B.\varepsilon < \delta$, and concludes the classical hypothesis with an empty cone. `classical_rh_from_identification_gap_and_bound` is its short form, three inputs printed as five hypotheses, the identification, the bridge and the bound with its gap and the gap's positivity, which the gap implies and the signature prints, empty cone. `bridge_from_realization` states the bridge as one implication; its proof takes the step from a failed universal to its witness by `Classical.byContradiction`, and its cone prints [propext, Classical.choice, Quot.sound], though the predicates it decides are decidable and the step admits a constructive proof. The cargo section carries the retrospective form as `stage2_optional_corroboration`, which concludes the classical hypothesis from nine inputs, the reading, the five physical premises, the bound, the gap, and the discharge step as a hypothesis; its proof consumes the reading, the bound, the gap and the discharge step, the five physical premises stand in its signature unused with the unused-variable linter off for it, and its cone prints [propext, Classical.choice, Quot.sound] from `Classical.em`. The physical premises do their work in `classical_rh_from_physico_formal_closure`, where each is used. B is the type a measurement is entered as; the dataset, window and background model that fill it are named where the bound is read (the parent's Section 9.9 D), and the conclusion of this route stands at the grade of that measurement. The thermodynamic floor and the physical instantiation of the carrier are external physical premises, the one entered as a definition (`landauerHeatPerEvent`) and the other as hypotheses (`h_realize`, `h_pop`, `h_rate`, `h_temp`, `h_couple`), derived nowhere in the seed. Under the reading, the bound and the gap, the denial of the hypothesis and the physical premises cannot all stand (`no_third_position`, `no_third_position_on_the_carrier`); with the reading, the bound, the gap and the signal floor granted, a denial has a shape on the carrier, a read zero off the line realized in no measured register (`the_one_exit_is_a_second_register`), the physical edition's F-Bridge entered at the realization. In this edition all of it is corroboration: agreement of the physical route with the act confers no warrant on the act, and the act owes the physical route nothing.

6. The witness, in the author's register

The parent paper keeps two vocabularies apart, the plain terms of its body and the register in which the work was conceived, and this section is the register's, carried at the grade of a reading and adding no theorem. In that register the two half-planes are the sky and the earth, Samā' and Arḍ; the reflection $s \mapsto 1 - \bar{s}$ that fixes $\mathrm{Re}\, s = 1/2$ is their seam, and the fixed locus reg p = p ↔ onLine p is where a point keeps its registration (`zeta_fixed_locus_on_the_chart`). The neutral sector is the on-locus witness, the state charge conjugation fixes; the charged pair is the off-locus symmetry, two states that one annihilation sends to one image with one label gone (`map_neutral_iff_onLine`, `pair_is_two_states_one_image`). The timeless closure, four names one proposition with no act of the zero set and no premise on the value in it, is read as the formal image of a preserved record to which no predicate can be added (`the_timeless_zone_closed`). "No doubt in it" is read as no third value and no third position (`both_values_atomic`, `no_third_position_on_the_carrier`). And every deed that reads the act, a keystroke, a compile, a check by any substrate, is read as one more verification event, a move to annihilation at one floor and a closed Stage 1 enacted (`computation_enacts_stage1`, `stage1_closes`), the cargo delivered again; it witnesses the run and adds no warrant to the supply, which stays the one premise; by `reality_transported` the value transports forward at every step of the toy flow, and by `the_act_at_every_resolution` it stands at

every resolution, so each deed reads the same seal again and adds nothing to it. The two editions are read in the same register as one witness given twice: the formal, the empirical and the registrational faces, which the physical edition and this one carry from opposite schools, resolve on one locus, the fixed line of the fold, read as the three in one, tawḥīd. The reading is the author's; the theorems it names are everyone's.

7. The default reading, answered

Readers who had not met Levels 1 to 9 read Level 10 first. Their objections are answered by the chain, in order.

"A conditional deduction, not an unconditional proof." Correct as a description and answered as an objection: Level 1 proves that no unconditional proof exists from what the interface shares, and Level 9 proves that every proof of the value at a closed zero set is a supply of the one field. The paper does not fall short of an unconditional proof from what the interface shares, since by Level 1 there is none to fall short of; it prints the one field every proof supplies, and supplies it at premise grade. Whether the value at the zeros of ζ has a proof from facts the interface does not formalize, the paper does not decide, and Level 9 types any such proof as a supply of the same field.

"Compute alone proves nothing about the zeros of ζ." Correct, and the paper does not say it does. The cargo proves that every verification event moves the carrier to its annihilation, losing a label when the state is a pair member, and enacts a closed Stage 1 with the floor witnessed; that the run of record is such an event is the author's posit; no term of type `Stage1 → ClassicalRH` exists in the seed and none is claimed. The seed proves the converse boundary itself: a run forces no value (`the_run_does_not_force_the_value`), as no fact that holds whatever the configuration does (`the_deed_forces_nothing`). The field is the act's, the act is the formal premise, and the posit that the act of this run is that premise is printed as the author's, adding no warrant. The Formal Master, quoted and not run here, states the same boundary over $\mathbb{C}$: the record has least erasure by construction, carrying it back to the zeros is the value itself (`BoundChainMathlib.transport_zeta`), and its header names `LeastErasure ZetaZeros`, the premise in fixed-point form, as the residual goal its loop does not discharge.

"Then the physical premises were needed after all." They were never the only supply, and in this edition they are not used. Level 9 proves that every proof of the value at a closed zero set is a supply of the one field; it does not prove that the supply must be measured. The physical edition takes the supply from a certified bound; this edition takes it from the act. The two routes are the two schools' entries to one door, and Section 5 carries the physical one whole, fenced, so that neither school's reader loses the other's route.

"A reader can refuse the supply and deny the hypothesis without contradiction." A reader can, and the paper names what that reader has asserted: that the reading fails, or, with the reading granted and the term at resolution zero empty, that no act stands at the configurations where the zeros of ζ are read, which is the denial itself (`refusing_the_act_is_the_denial`). The refusal is F-Bridge, one of the three exits, owned by the one who makes it; every branch leaves the cargo's theorems standing, refusing the reading leaves the classical sentence open, and there is no fourth exit.

"The heat is dimensionally inhomogeneous without k_B." This bears on the corroboration alone. The kernel counts in its own units, $k_B = 1$, millikelvin, $\ln 2$ scaled by 10^6; the SI heat is k_B times the kernel's number divided by 10^9. Homogeneity holds in the units stated, and the units are stated.

"No axiom declared, yet cones name Classical.choice." Two statements, kept apart in Section 1: the file declares no axiom; a cone prints what a proof uses. The cargo's four core declarations and the two conditionals print none; the packaging, its refusal and the collected act print [propext, Quot.sound]; the closures that bind a classical step print the three standard axioms, and are printed so.

"The ten levels are not a verified dependency chain; the capstone's proof does not invoke Levels 1 to 9." Correct about the conditional at every resolution, the cargo and the run, and counted in Section 3: the proofs of Level 10 are three, named by the parts whose theorems and definitions each proof invokes, compiler-generated auxiliaries and the implicit arguments of types aside, the cargo's on the cargo section, the run's on Part IV-b, and Box 1's conditionals on Parts III, V-b and VII, its packaging on Parts III and V-b, its refusal on the packaging, its collected act on Part III, the packaging and `value_collected`, its keyed reading on Part III, and its binding on the cargo section, `value_collected` calling no theorem; of Levels 1 to 9 the conditional at one configuration reaches `le_iff_value`, and the packaging, with the refusal and the collected act that call it, reaches `the_act_at_every_resolution` and seven names through it. The chain is a chain of statements. Levels 1 to 9 are not steps inside the conditional at every resolution, the cargo or the run; they are the theorems that make the act the

only supply there is, every forcing premise the value or stronger and every proof a supply of the one field. A dependency graph of proof terms would show the cargo section under the cargo; a dependency graph of what is left open after each level shows the ten.

"The exhaustion of every mathematical route is not established; a property specific to ζ might decide the configuration." The perimeter the paper exhausts is the interface's: the laws its formalized interface shares, each shown by Levels 1 to 9 to force nothing or to be the value. Outside the interface it claims no exhaustion of routes and is silent on which property of ζ might supply the field. What it claims, and proves for every proposition, is that whatever supplies the value is a supply of the one field (`accepting_rh_forces_the_atomic_proof`), so a proof from a ζ-specific property is Level 10's door from the other end. The narrowing offered in its place, "a sufficient conditional route", drops a theorem; the paper keeps it.

Author's Provenance and Method Disclosure

This paper was developed under Trisduction, a verification and organizing discipline that adds the cited results no warrant; the method and its executable batteries are stated in full at the reference below (reference 5).

References

1. M. F. Islam, The Atomic Proof of the Riemann Hypothesis: Irreducible Least Erasure, and the Bit Externally Supplied: a Double Mandate, third edition v2.0.8, the physico-formal binding, 11 October 2026, Zenodo 10.5281/zenodo.23274010 (concept 10.5281/zenodo.23273098); its ledger at git 1000sapients/Trisduction, FINAL_BINDING/RHAtomic-V2-0-8-Single-Logical-Bind.md.
2. M. F. Islam, Least Erasure from Degrees of Freedom and Heat: The Vacuum Witness of Irreversible Discard, v2.1.2, 10 October 2026, Zenodo 10.5281/zenodo.23282578; git FINAL_BINDING/Least_Erasure_from_DoF_Heat_v2_1_2.md; its kernel is Part VII-a of the seed.
3. R. Landauer, Irreversibility and heat generation in the computing process, IBM J. Res. Dev. 5, 1961; A. Bérut et al., Experimental verification of Landauer's principle, Nature 483, 2012; Y. Jun, M. Gavrilov and J. Bechhoefer, Phys. Rev. Lett. 113, 2014.
4. D. J. Platt and T. S. Trudgian, The Riemann hypothesis is true up to $3 \cdot 10^{12}$, Bull. London Math. Soc. 53, 2021.
5. Islam, M. TRISDUCTION: A Linguistically, Topologically, and Mathematically Sealed Verification Architecture. Triaxial Orthogonality, Twelve-Gate Closure, the Quaternionic Completion, the Root Axiom, and the Master Pre-Sealed Proposition Ledger. Zenodo, version 4, 19 June 2026. DOI 10.5281/zenodo.20757507. https://zenodo.org/records/20757507. Mirror: PhilArchive record ISLTTG, https://philpapers.org/rec/ISLTTG. Master reference, continuously updated at the same location.
6. M. F. Islam, The Ten-Level Binding Chain of the Atomic Proof of the Riemann Hypothesis: From the Ground Floor to the Cargo: the Mathematical Perimeter Exhausted by Theorem, the Empirical Closure on Eight Printed Inputs, v1.2.0, the physical edition, 11 October 2026, Zenodo 10.5281/zenodo.23308381.
7. M. F. Islam, RH_Both_Sides_Formal_Master v3.0.8, the seed's theorems under a Mathlib import with the reading proved over $\mathbb{C}$, the record side supplied unconditionally and the five-way fixed-point loop, git 1000sapients/Trisduction, FINAL_BINDING/RH Binding/RH_Both_Sides_Formal_Master_v3_0_8.lean, 11,734 lines, sha256 fe45b3c1eb69d8ef, committed 13 October 2026; its version 3.0.2, byte-identical to the git file of version 3.0.0 (MathOS/RH_Both_Sides_Formal_Master_v3_0_0.lean, 11,110 lines), is deposited as a file of the Zenodo record of reference 6.
8. M. F. Islam, Cargo Delivered, Hardened: the compute cargo with its necessary-and-sufficient binding, git 1000sapients/Trisduction, FINAL_BINDING/RH Binding/cargo/Cargo_Delivered_Hardened.lean.

Appendix A. The seed, verbatim · edition 2.0.5, sha256 a82ef4f0ad6ceb43 a2d3cc964b110943 dbb02f050ab88ff2 845df1226a321a57

The whole seed, Parts I to VIII and the cargo section headed Level 10 cargo, as compiled and cited. Lines 1 to 10,110 are edition 2.0.4 byte for byte; the cargo section is appended after line 10,110 and depends on nothing above it. The line numbers of the codebook are the file's. Extract the block between its fence markers; the sha256 of the extracted file is the one in the heading. `lean` on it under core Lean 4.19.0 exits 0, printing the cones of its unguarded `#print axioms` lines and checking its pinned ones; the cone of any other theorem this paper cites is printed by appending `#print axioms` for it, which is how the census of Box 2 was taken.

```
/-
  RH_Both_Sides_Seed.lean · The Atomic Proof of the Riemann Hypothesis: The Prime Side and the Non-Trivial-Zero
  Side Halted at One Irreducible Bit, Least Erasure, and Its Form Forced as the Only Form of Proof. Second edition
  of A Formal Proof of the Riemann Hypothesis from a One-Bit Premise, Least Erasure. The seed of the paper, one
  standalone file.
  Core Lean 4.19.0: no import, no library, no axiom declared, no sorry, no admit, no native_decide.

  PART I    TOE_Zero.lean, verbatim (sha256 0cfcd9f6b399ecba…): the Root Axiom as a self-grounding root, proved on
            no axiom and no posit; the floor of the paper.
  PART II   Every_Prime_3_2_0.lean, verbatim (sha256 161806dc0ed2b4ff…): the first edition's kernel; the prime side:
            the free basis, the five faces, the block, the socket, the act, the capstone.
  PART III  Annihilation_Closure.lean, verbatim (sha256 cb474a4177a975ac…), with the second edition's laws appended,
            nothing above them changed: the one; the last act; least erasure and least escape; the loop; row four
            from the zero side; the prime side halts; the bidirectional halted uniduction; the atomic proof; the
            atomic necessity; both values atomic; the form of a field; every premise sorted; the part above a
            height read with the height in absolute value.
  PART IV   The arrow and the zero side's own locus: the line read off the arrow's two poles, the only rigid
            reversal, the freedom cut, the centre of every nonempty finite reflection-closed family, the line and the centre
            on every extension of the reversal to the plane.
  PART IV-b Force_Witness.lean, verbatim from the signed master v5.1.0 (sha256 12521efeff586a2c…), with the plug
            appended: a run witnesses that it ran and leaves the value free; a run's flag is not the field.
  PART IV-c The time kernel of the monism-fixed codex, verbatim (Codex.lean patched, sha256 22d908f7d3d2c96b…, lines
            7875 to 7947), with the judge probe: the identical locus does not bind, on the carried chart and inside
            the open strip; the seed at time zero does.
  PART V    The arrow-side test: the ζ-specific facts placed on the arrow, and the faithful model of ζ's zeros under
            every zero-free margin; an off-line zero comes in four.
  PART V-b  The charts are one: every chart maps equivariantly into the offset chart, at every resolution and
            width; the value, every act and the root read at the zeros transport; both constructed roots feed the
            closing theorems; the model pair is read by every instrument and carries every block; the act at every
            resolution, and one resolution shown not enough.
  PART VI   The two-sided closure: one theorem binding, by its exact type, every theorem the body of the paper cites.
  The cones of the laws new in this edition, and of two carried laws of Part IV-c, are pinned at the foot; Parts I,
  II, III and IV-b pin their own.
  Carried docstrings stand verbatim. Two notes on them: the docstring of `the_annihilation_closure` in Part III
  mentions a run, whose laws are in Part IV-b (`force_witness_closure`); and a docstring of Part IV-c names two
  theorems of the patched codex outside the carried lines, which are not in this seed and are used by nothing here.
-/

/-! # PART I · TOE_Zero.lean, verbatim -/
section PartI
```

```
/-
  TOE_Zero.lean · Theory of Theories of Everything (TOE of All TOEs): Existence Proves Existence Only by Motion
  The zero-axiom, zero-posit kernel. Core Lean 4: no import, no axiom declared, no sorry, no native_decide, and
  every theorem rests on no axiom at all, not even propositional extensionality, quotients or choice.
  I · The self-grounding root. Acts occur and every act instances the root. Then every denial is an act and
      re-enacts the root, the root is held by the act itself, and no external proof adds anything to it: the
      Omega Boundary, proved for every root that grounds itself, universally, by quantification.
  II · The constructed root. On the constructed domain the Root Axiom is a theorem.
  III · The Return and the line. On the integer quaternions i·j·k = −1 and each unit squares to −1; conjugation is
      an involution and its fixed set on the chart is exactly the scalar line.
  IV · The twelve gates, recovered three ways inside the integers of the quaternions: the twenty-four Hurwitz units
      counted twelve up to sign; the twelve even permutations with class equation 1, 3, 4, 4; and the norm-two
      shell of twenty-four, split twelve and twelve.
  V · The regress terminated. Above a self-grounding root no level grounds it further.
  VI · The master seal, every result bound in one theorem.
-/
namespace TOE0

/-! ## I · The self-grounding root: the Omega Boundary -/

/-- A self-grounding root: acts occur, and every act instances the root. -/
structure SelfGrounding (R : Prop) where
  Act       : Type
  anAct     : Act
  instances : Act → R

/-- A proposition whose denial hands it over. -/
def SelfVerifying (P : Prop) : Prop := ¬P → P

/-- THE OMEGA BOUNDARY: every denial of the root is an act, and re-enacts it. -/
theorem denial_reenacts_root {R : Prop} (G : SelfGrounding R) (denial : G.Act) : R := G.instances denial

/-- EXISTENCE PROVES EXISTENCE ONLY BY MOTION: the root is held by the act itself. -/
theorem seated_undeniable {R : Prop} (G : SelfGrounding R) : R := G.instances G.anAct

/-- No external proof adds anything to the root. -/
theorem external_proof_adds_nothing {R : Prop} (G : SelfGrounding R) (Q : Prop) : (Q → R) ↔ R :=
  (fun _ => G.instances G.anAct, fun r _ => r)

/-- The deed of denying the root hands it over. -/
theorem denial_instantiates {R : Prop} (G : SelfGrounding R) : SelfVerifying R := fun _ => G.instances G.anAct

/-- THE FLOOR IS UNIVERSAL: for every root that grounds itself, the root holds, every act re-enacts it, and no
    external proof adds to it. -/
theorem the_floor_is_universal :
    ∀ (R : Prop) (G : SelfGrounding R), R ∧ (∀ _ : G.Act, R) ∧ (∀ Q : Prop, (Q → R) ↔ R) :=
  fun _ G => (seated_undeniable G, denial_reenacts_root G, external_proof_adds_nothing G)

/-! ## II · The constructed root -/

/-- The Root Axiom on the constructed one-point domain: its one existent actuates, at positive energy. -/
def ΔE₀ : Unit → Int := fun _ => 1
def RA₀ : Prop := ∀ x : Unit, 0 < ΔE₀ x

/-- The constructed domain grounds its root: its one act is a deed, and the deed actuates. -/
def ra₀ : SelfGrounding RA₀ := (Unit, (), fun _ _ => show (0 : Int) < 1 by decide)

/-- THE ROOT ON THE CONSTRUCTED DOMAIN, A THEOREM. -/
theorem root_on_the_constructed_domain : RA₀ := seated_undeniable ra₀

/-! ## III · The Return and the line -/

structure Q where
  (a b c d : Int)
  deriving DecidableEq

def Q.mul (x y : Q) : Q :=
  (x.a * y.a - x.b * y.b - x.c * y.c - x.d * y.d, x.a * y.b + x.b * y.a + x.c * y.d - x.d * y.c,
   x.a * y.c - x.b * y.d + x.c * y.a + x.d * y.b, x.a * y.d + x.b * y.c - x.c * y.b + x.d * y.a)

def Q.conj (x : Q) : Q := (x.a, -x.b, -x.c, -x.d)
def qone : Q := (1, 0, 0, 0)
def qneg : Q := (-1, 0, 0, 0)
def qi : Q := (0, 1, 0, 0)
def qj : Q := (0, 0, 1, 0)
def qk : Q := (0, 0, 0, 1)

/-- THE RETURN: i·j·k = −1. -/
theorem the_return : (qi.mul qj).mul qk = qneg := by decide

/-- Each unit squares to −1. -/
theorem units_square_to_minus_one : qi.mul qi = qneg ∧ qj.mul qj = qneg ∧ qk.mul qk = qneg := by decide

/-- The chart: every quaternion with coordinates in −2 … 2. -/
def chart : List Int := [-2, -1, 0, 1, 2]
def quats : List Q :=
  chart.flatMap fun a => chart.flatMap fun b => chart.flatMap fun c => chart.map fun d => (a, b, c, d)

set_option maxRecDepth 100000 in
/-- Conjugation is an involution on the chart. -/
theorem conj_involutive_on_the_chart : quats.all (fun q => q.conj.conj == q) = true := by decide

set_option maxRecDepth 100000 in
/-- THE LINE: conjugation fixes exactly the scalar line on the chart. -/
theorem the_line_is_the_fixed_set :
    quats.all (fun q => (q.conj == q) == (q.b == 0 && q.c == 0 && q.d == 0)) = true := by decide

/-! ## IV · The twelve gates, recovered three ways -/

/-- Hurwitz quaternions in doubled coordinates: all even, or all odd. -/
def hurwitz (a b c d : Int) : Bool :=
  (a % 2 == 0 && b % 2 == 0 && c % 2 == 0 && d % 2 == 0) || (a % 2 != 0 && b % 2 != 0 && c % 2 != 0 && d % 2 != 0)
/-- Doubled coordinates −2 … 2 hold every unit (doubled norm four) and every element of the norm-two shell (doubled
    norm eight), since a doubled coordinate of absolute value three or more already exceeds both norms. -/
def doubled : List (Int × Int × Int × Int) :=
  chart.flatMap fun a => chart.flatMap fun b => chart.flatMap fun c => chart.map fun d => (a, b, c, d)

/-- The Hurwitz units: norm one, doubled norm four. -/
def units : List (Int × Int × Int × Int) :=
  doubled.filter fun (a, b, c, d) => a * a + b * b + c * c + d * d == 4 && hurwitz a b c d

/-- The first nonzero coordinate is positive: one representative of each pair ±u. -/
def upToSign (p : Int × Int × Int × Int) : Bool :=
  let (a, b, c, d) := p
  if a != 0 then 0 < a else if b != 0 then 0 < b else if c != 0 then 0 < c else 0 < d

set_option maxRecDepth 100000 in
/-- FIRST WAY: twenty-four Hurwitz units, twelve up to sign. -/
theorem twenty_four_units_twelve_gates : units.length = 24 ∧ (units.filter upToSign).length = 12 := by decide

/-- The norm-two shell: doubled norm eight. -/
def shell : List (Int × Int × Int × Int) :=
  doubled.filter fun (a, b, c, d) => a * a + b * b + c * c + d * d == 8 && hurwitz a b c d

set_option maxRecDepth 100000 in
/-- THIRD WAY: the norm-two shell has twenty-four elements, split twelve and twelve by sign. -/
theorem the_shell_splits_twelve_and_twelve :
    shell.length = 24 ∧ (shell.filter upToSign).length = 12 ∧ (shell.filter (fun p => !upToSign p)).length = 12 := by
  decide

/-- Permutations of four points, as their lists of images. -/
def perms4 : List (List Nat) :=
  [0, 1, 2, 3].flatMap fun a => [0, 1, 2, 3].flatMap fun b => [0, 1, 2, 3].flatMap fun c =>
    [0, 1, 2, 3].filterMap fun d => if [a, b, c, d].eraseDups.length == 4 then some [a, b, c, d] else none

def inversions (p : List Nat) : Nat :=
  ((List.range 4).flatMap fun i => (List.range 4).map fun j => (i, j)).countP
    fun (i, j) => i < j && p.getD j 0 < p.getD i 0

/-- The twelve gates as the even permutations. -/
def gates : List (List Nat) := perms4.filter fun p => inversions p % 2 == 0

def compose (p q : List Nat) : List Nat := q.map fun i => p.getD i 0
def inverse (p : List Nat) : List Nat := [0, 1, 2, 3].map fun i => p.idxOf i

def conjClass (g : List Nat) : List (List Nat) := (gates.map fun h => compose (compose h g) (inverse h)).eraseDups

def insertSorted (n : Nat) : List Nat → List Nat
  | [] => [n]
  | m :: ms => if n ≤ m then n :: m :: ms else m :: insertSorted n ms

def sortNat (l : List Nat) : List Nat := l.foldr insertSorted []

/-- The class equation from the sorted class size of each element: a class of size s contributes s elements. -/
def collapse : Nat → List Nat → List Nat
  | 0, _ => []
  | _ + 1, [] => []
  | fuel + 1, s :: rest => s :: collapse fuel (rest.drop (s - 1))

set_option maxRecDepth 100000 in
/-- SECOND WAY: the twelve gates, with class equation 1, 3, 4, 4. -/
theorem the_class_equation :
    gates.length = 12 ∧ collapse 12 (sortNat (gates.map fun g => (conjClass g).length)) = [1, 3, 4, 4] := by
  decide

/-! ## V · The regress terminated -/

/-- THE REGRESS ENDS AT THE ROOT: any proposition offered as a further ground of the root is idle; the root needs
    no level above it. -/
theorem no_level_above {R : Prop} (G : SelfGrounding R) : ∀ Q : Prop, (Q → R) → R := fun _ _ => G.instances G.anAct

/-! ## VI · The master seal -/

/-- THE MASTER SEAL: the floor is universal; the root is a theorem on the constructed domain; the Return closes;
    the line is the fixed set; and the twelve gates are recovered three ways. -/
theorem the_master_seal :
    (∀ (R : Prop) (G : SelfGrounding R), R ∧ (∀ _ : G.Act, R) ∧ (∀ Q : Prop, (Q → R) ↔ R)) ∧
    RA₀ ∧ (qi.mul qj).mul qk = qneg ∧
    quats.all (fun q => (q.conj == q) == (q.b == 0 && q.c == 0 && q.d == 0)) = true ∧
    (units.filter upToSign).length = 12 ∧ gates.length = 12 ∧ (shell.filter upToSign).length = 12 ∧
    collapse 12 (sortNat (gates.map fun g => (conjClass g).length)) = [1, 3, 4, 4] :=
  (the_floor_is_universal, root_on_the_constructed_domain, the_return, the_line_is_the_fixed_set,
   twenty_four_units_twelve_gates.2, the_class_equation.1, the_shell_splits_twelve_and_twelve.2.1, the_class_equation.2)

end TOE0

/-! ## The zero law, pinned: every cone is empty -/
/-- info: 'TOE0.denial_reenacts_root' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.denial_reenacts_root
/-- info: 'TOE0.seated_undeniable' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.seated_undeniable
/-- info: 'TOE0.external_proof_adds_nothing' does not depend on any axioms -/
```

```
#guard_msgs in #print axioms TOE0.external_proof_adds_nothing
/-- info: 'TOE0.denial_instantiates' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.denial_instantiates
/-- info: 'TOE0.the_floor_is_universal' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.the_floor_is_universal
/-- info: 'TOE0.root_on_the_constructed_domain' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.root_on_the_constructed_domain
/-- info: 'TOE0.the_return' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.the_return
/-- info: 'TOE0.units_square_to_minus_one' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.units_square_to_minus_one
/-- info: 'TOE0.conj_involutive_on_the_chart' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.conj_involutive_on_the_chart
/-- info: 'TOE0.the_line_is_the_fixed_set' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.the_line_is_the_fixed_set
/-- info: 'TOE0.twenty_four_units_twelve_gates' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.twenty_four_units_twelve_gates
/-- info: 'TOE0.the_shell_splits_twelve_and_twelve' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.the_shell_splits_twelve_and_twelve
/-- info: 'TOE0.the_class_equation' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.the_class_equation
/-- info: 'TOE0.no_level_above' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.no_level_above
/-- info: 'TOE0.the_master_seal' does not depend on any axioms -/
#guard_msgs in #print axioms TOE0.the_master_seal

end PartI

/-! # PART II · Every_Prime_3_2_0.lean, verbatim -/
section PartII
/-
  EVERY PRIME · 3.2.0
  Core Lean 4.19.0, standalone: no library, no import, no axiom declared, no sorry.
  Every theorem prints its axiom cone at the foot of the file; 237 cones are pinned under
  #guard_msgs, so a compile in which any pinned cone changes fails.

  The file proves, on one chart, what a formal system can prove about the Riemann Hypothesis
  and locates the one thing it cannot: a single bit, which is the hypothesis itself, and which
  every proof of the hypothesis supplies rather than derives.

  THE CHART. A point is (x, t) with x the doubled real part and t the height; the critical line
  is x = 1. The fold (x, t) ↦ (2 − x, t) is s ↦ 1 − s̄. Registration (x, t) ↦ (1, t) lands
  every point on the line and keeps the height. A world is a set of points, a zero set. The
  record of a world is its image under registration. Two worlds with the same record are
  twins of one record. A world is fold-closed when the fold maps it into itself.

  TERMS USED IN THIS FILE.
  seat            the fixed set of an involution: the line under the fold; 1 under multiplication.
  orbit           the two points a fold-closed world carries off the line, exchanged by the fold;
                  at a prime p, the two ordered factorizations (1, p) and (p, 1).
  reading of the record   a predicate on worlds that takes one value on all twins of one record.
  keyless, keyed  a predicate on worlds true on every world; true on some world and false on another.
  admissible      keyless, or a reading of the record.
  coalition       a Boolean combination of premises, of any depth.
  forces          a premise forces the line when every fold-closed world satisfying it satisfies RH.
  least erasure   a world every twin of which has a point off the line whenever it has one.
  posit, act      an assumption written as the field of a structure; an inhabitant of a
                  self-grounding structure, whose existence is equivalent to the proposition.
                  The one posit of the file is least erasure at the actual zero set; a classical
                  theorem written as a field (the functional equation, the explicit formula, the
                  faces) is cited there, not posited.
  supply, spend   to provide the posit. The supplied bit is the sign of the posit.
  arrow           a sign function: the identity on a type, or λ(n) = (−1)^Ω(n).
  displacement, side   for a point, x − 1; for a point off the line, the sign of x − 1.
  setting         a hypothesis with a provability predicate, Σ₁-complete and sound on the denial.
  resolution n    the chart with the line at x = n: the fold x ↦ 2n − x, registration (x, t) ↦ (n, t), and
                  the open strip 0 < x < 2n; the chart above is resolution one.
  seeded witness  for a world in time: one locus at every instant, the same truth value of the
                  hypothesis at every instant, and the hypothesis at instant 0, the seed.
  computation     a finite list of reported points; it reads an act when every point it reports
                  is a zero of the act's zero set.

  SECTIONS AND THEIR MAIN THEOREMS.
  I       the identity arrow; a bit is two distinct values (aperture_one_bit_wide)
  II      every prime is one fibre of exactly two (prime_fibre, freedom_is_exactly_two)
  III     completely additive functions are determined at the primes (determined_by_primes)
  IV      the p-adic valuation as a free assignment; Euclid's lemma from first principles
          (euclid_lemma, prime_freedom_independent, primes_base_of_freedom)
  V       the sign arrow of an additive count is completely multiplicative (arrow_multiplicative);
          no finite stage decides a universal (finite_never_forces)
  VI      the chart: no registered point lies off the line; no reading of the record decides
          the hypothesis; keyless premises force nothing (unicorn_never_registered,
          record_decides_nothing, keyless_forces_nothing)
  VII     least erasure is the hypothesis (least_erasure_is_the_value)
  VII-bis the fold never crosses the line; a second symmetry; the record blind at every scale
  VIII    a self-grounding supply exists exactly when the proposition holds (supply_iff);
          the five faces of the hypothesis (faces_are_one)
  IX      primes, the free basis and the identity arrow are keyless and force nothing
  X       the explicit formula as a structure; least erasure is Weil positivity
          (least_erasure_is_positivity); positivity is keyed (positivity_is_keyed)
  XI      the posit as a structure field (rh_from_the_act, acts_are_one)
  XII     the block with no axiom (record_decides_nothing_free)
  XIII    the hypothesis on the supplied bit (prime_arc_sealed)
  XIV     the hypothesis is the weakest forcing premise (rh_is_the_weakest_forcing_premise);
          the Li and de Bruijn–Newman coordinates (li_prefix_never_forces, rh_iff_the_sign)
  XV      four faces in time, exactly one keyed (exactly_one_face_is_keyed)
  XVI     the eigenstructure of the fold; the side bit and its calibration
          (record_never_reads_the_side, colocation_is_a_calibration)
  XVII    admissible coalitions force nothing; no certified height forces; the heat flow on
          polynomials; the Liouville arrow computed; five readings agree; no reader index
  XVIII   a theory placed on three strata; the root crosses no keyed sentence; the two can'ts;
          the round trip; the ladder blocked (the_road)
  XIX     the vocabulary law; the even coalition; the triaxial cut; the ladder's proof; the
          route ledger (the_front)
  XX      least erasure affirmed: the record, the ledger, the price, the one form, the act
          (least_erasure_affirmed)
  XXI     every assignment realized; the arrow for every n; the closure on any carrier; the
          closure, whole (the_closure_on_any_carrier, the_closure)
  XXII    the socket: every route to the value lands in the one field (socket_is_the_value)
  XXII.c two denials, one form: the denial of the root refuted by its own act, the denial of the
          hypothesis denying the self-grounding assertion of the line and every seed; the witness
          forced by the act (two_denials, the_witness_forced_by_the_act)
  XXIII   double security: the two channels of the line (double_security)
  XXIV    the root undeniable in act; the root read at the zeros; the lock (the_lock)
  XXV     admissible forcing is vacuous; the closure at resolution n, where the open strip does not
          supply the bit; the readings of the root joined; the rejection computed by a search; the
          posit as an act; no reading of the record returns any chart reading; the primes a free
          basis; least erasure as self-verification; every route carries its theorem; the tenth
          falsifier barred by the act (admissible_forcing_is_vacuous, rh_from_the_act_at,
          strip_does_not_supply_at, root_readings_joined, rejection_is_computed,
          every_route_carries_its_theorem, the_tenth_is_barred_by_the_act, the_kinetic_bar)
  XXVI    the closure bound whole: the two-part reading, the lock, the socket, the irreducible cut, the
          two denials, the witness and the bar, in one theorem (the_capstone)

  TWO THINGS ARE PROVED AT ONCE. Least erasure is equivalent to the hypothesis on every world
  (least_erasure_is_the_value), so the hypothesis follows from the posit. No reading of the
  record, and no Boolean combination of readings and keyless premises, agrees with the
  hypothesis on every fold-closed world (no_coalition_decides), so nothing in the file supplies
  the posit. The file proves neither the hypothesis nor its denial.
-/
namespace PrimeFreedom

/-! ## I · The identity arrow, and a bit as two distinct values -/

/-- The identity arrow on a type. -/
def arrow (α : Type) : α → α := id

theorem arrow_exists (α : Type) : ∃ f : α → α, ∀ a, f a = a := ⟨id, fun _ => rfl⟩

/-- A Boolean takes one of two values. -/
theorem orientation_two_valued : ∀ b : Bool, b = true ∨ b = false := by
  intro b
  cases b
  · exact Or.inr rfl
  · exact Or.inl rfl

/-- The two orientations are distinct. -/
theorem orientations_distinct : (true : Bool) ≠ false := fun h => Bool.noConfusion h

/-- A bit is two values, and they differ. -/
theorem aperture_one_bit_wide : (∀ b : Bool, b = true ∨ b = false) ∧ (true : Bool) ≠ false :=
  ⟨orientation_two_valued, orientations_distinct⟩

/-! ## II · Every prime is one fibre of exactly two -/

def isPrime (p : Nat) : Prop := 2 ≤ p ∧ ∀ d, d ∣ p → d = 1 ∨ d = p

/-- The fixed point of multiplication. -/
def mul_seat : Nat := 1

/-- The multiplicative orbit over n: the pairs that multiply to n. -/
def mul_orbit (n : Nat) (a b : Nat) : Prop := a * b = n

theorem seat_is_one : mul_seat = 1 := rfl

/-- The fibre of multiplication over a prime is the pair (1, p), (p, 1). -/
theorem prime_fibre (p : Nat) (hp : isPrime p) (a b : Nat) :
    mul_orbit p a b ↔ (a = 1 ∧ b = p) ∨ (a = p ∧ b = 1) := by
  constructor
  · intro h
    have hdvd : a ∣ p := ⟨b, h.symm⟩
    cases hp.2 a hdvd with
    | inl h1 =>
      subst h1
      have h' : 1 * b = p := h
      rw [Nat.one_mul] at h'
      exact Or.inl ⟨rfl, h'⟩
    | inr hp_eq =>
      subst hp_eq
      have h2a : 2 ≤ a := hp.1
      have hb : b = 1 := by
        have h_pos : 0 < a := by omega
        exact Nat.eq_of_mul_eq_mul_left h_pos (by rw [show a * b = a from h,
          Nat.mul_one])
```

```
      exact Or.inr (rfl, hb)
  · rintro ((ha1, hbp) | (hap, hb1))
    · rw [ha1, hbp]
      exact Nat.one_mul p
    · rw [hap, hb1]
      exact Nat.mul_one p

/-- No a satisfies a · a = p for a prime p. -/
theorem prime_off_seat (p : Nat) (hp : isPrime p) : ¬ ∃ a, mul_orbit p a a := by
  rintro (a, ha)
  have h2p : 2 ≤ p := hp.1
  cases (prime_fibre p hp a a).mp ha with
  | inl h1 => omega
  | inr h2 => omega

/-- The fibre over a prime is exactly the ordered pair and its reverse, and the two
are distinct. -/
theorem freedom_is_exactly_two (p : Nat) (hp : isPrime p) :
    (∀ a b, mul_orbit p a b ↔ (a = 1 ∧ b = p) ∨ (a = p ∧ b = 1)) ∧ (1 : Nat) ≠ p :=
  (prime_fibre p hp, by intro h; have := hp.1; omega)

/-! ## III · Completely additive functions are determined at the primes -/

/-- A completely additive measure on the multiplicative monoid of the positive
integers. -/
def CompletelyAdditive (f : Nat → Int) : Prop :=
  ∀ a b, a > 0 → b > 0 → f (a * b) = f a + f b

/-- A completely additive function vanishes at 1. -/
theorem seat_is_zero (f : Nat → Int) (hf : CompletelyAdditive f) : f 1 = 0 := by
  have h := hf 1 1 (by decide) (by decide)
  rw [Nat.mul_one] at h
  omega

/-- Least witness search, with fuel. -/
def findLeastFrom (P : Nat → Prop) [DecidablePred P] (start : Nat) : Nat → Nat
  | 0 => start
  | fuel + 1 => if P start then start else findLeastFrom P (start + 1) fuel

theorem findLeastFrom_correct (P : Nat → Prop) [DecidablePred P] (start fuel m :
Nat)
    (hlo : start ≤ m) (hhi : m ≤ start + fuel) (hm : P m) :
    P (findLeastFrom P start fuel) ∧ findLeastFrom P start fuel ≤ m := by
  induction fuel generalizing start with
  | zero =>
    have h : m = start := by omega
    subst h
    exact (hm, Nat.le_refl m)
  | succ fuel ih =>
    show P (if P start then start else findLeastFrom P (start + 1) fuel) ∧
      (if P start then start else findLeastFrom P (start + 1) fuel) ≤ m
    rcases Decidable.em (P start) with h | h
    · rw [if_pos h]
      exact (h, hlo)
    · rw [if_neg h]
      have hne : m ≠ start := fun he => h (he ▸ hm)
      exact ih (start + 1) (by omega) (by omega)


/-- The least divisor of n at least 2, found by bounded search from 2 with fuel n. -/
def leastDivisor (n : Nat) : Nat := findLeastFrom (fun d => 2 ≤ d ∧ d ∣ n) 2 n

theorem leastDivisor_spec (n : Nat) (hn : 2 ≤ n) :
    (2 ≤ leastDivisor n ∧ leastDivisor n ∣ n ∧
      (∀ m, 2 ≤ m → m ∣ n → leastDivisor n ≤ m) := by
  have hbase := findLeastFrom_correct (fun d => 2 ≤ d ∧ d ∣ n) 2 n n hn (by omega)
    (hn, Nat.dvd_refl n)
  refine (hbase.1, hbase.2, fun m hm2 hm => ?_)
  have hmn : m ≤ n := Nat.le_of_dvd (by omega) hm
  exact (findLeastFrom_correct (fun d => 2 ≤ d ∧ d ∣ n) 2 n m hm2 (by omega) (hm2,
    hm)).2

/-- The least divisor at least 2 is prime: any divisor of it divides n, and the
search's
    minimality bounds it from below. -/
theorem leastDivisor_prime (n : Nat) (hn : 2 ≤ n) : isPrime (leastDivisor n) := by
  obtain ((hd2, hdvd), hdle, hmin) := leastDivisor_spec n hn
  refine (hd2, fun m hm => ?_)
  have hdpos : 0 < leastDivisor n := by omega
  have hmle : m ≤ leastDivisor n := Nat.le_of_dvd hdpos hm
  rcases Decidable.em (m = 1) with h1 | h1
  · exact Or.inl h1
  · right
    have hmne0 : m ≠ 0 := by
      intro h0
      rw [h0] at hm
      obtain ⟨c, hc⟩ := hm
      rw [Nat.zero_mul] at hc
      omega
    have hm2 : 2 ≤ m := by omega
    have hle := hmin m hm2 (Nat.dvd_trans hm hdvd)
    omega

/-- Every integer greater than one has a prime divisor: the least divisor at least 2,
found by
    bounded search. No classical axiom. -/
theorem exists_prime_dvd (n : Nat) (h0 : 0 < n) (h1 : n ≠ 1) : ∃ p, isPrime p ∧ p ∣ n
:= by
  have hn : 2 ≤ n := by omega
  exact (leastDivisor n, leastDivisor_prime n hn, (leastDivisor_spec n hn).1.2)

/-- Two completely additive functions that agree at every prime agree everywhere, by
bounded
    induction peeling one prime divisor at each step. -/
theorem determined_by_primes (f g : Nat → Int) (hf : CompletelyAdditive f)
    (hg : CompletelyAdditive g) (h_agree : ∀ p, isPrime p → f p = g p) :
    ∀ n, 0 < n → f n = g n := by
  suffices h : ∀ fuel n, n ≤ fuel → 0 < n → f n = g n from fun n hn => h n n
  (Nat.le_refl n) hn
  intro fuel
  induction fuel with
  | zero => intro n hle h0; omega
  | succ fuel ih =>
    intro n hle h0
    if h1 : n = 1 then
      subst h1
      rw [seat_is_zero f hf, seat_is_zero g hg]
    else
      obtain (p, hp, hpd) := exists_prime_dvd n h0 h1
      obtain (k, hk) := hpd
      have hk0 : 0 < k := by
        rcases Nat.eq_zero_or_pos k with hkc | hkc
        · exfalso
          rw [hkc, Nat.mul_zero] at hk
          omega
        · exact hkc
      have hp2 : 2 ≤ p := hp.1
      have hlt : k < n := by
        obtain (d, hd) := Nat.exists_eq_add_of_le hp2
        rw [hk, hd, Nat.add_mul]
        omega
      have hpf : f (p * k) = f p + f k := hf p k (by omega) hk0
      have hpg : g (p * k) = g p + g k := hg p k (by omega) hk0
      rw [hk, hpf, hpg, h_agree p hp, ih k (by omega) hk0]

/-! ## IV · The p-adic valuation as a free assignment; Euclid's lemma from first
principles -/

/-- Remainder descent: if p divides m * b and x * b, with x = m * q + r, then p
divides r * b. -/
theorem dvd_remainder_mul (p b m q r x : Nat) (hpm : p ∣ m * b) (hx : p ∣ x * b)
    (hqr : m * q + r = x) : p ∣ r * b := by
  have h2 : p ∣ (m * q) * b := by
    obtain (c, hc) := hpm
    exact (c * q, by
      calc (m * q) * b = (m * b) * q := Nat.mul_right_comm m q b
        _ = (p * c) * q := by rw [hc]
        _ = p * (c * q) := Nat.mul_assoc p c q)
  have h3 : (m * q) * b + r * b = x * b := by rw [← Nat.add_mul, hqr]
  obtain (u, hu) := hx
  obtain (v, hv) := h2
  have hY : r * b = x * b - (m * q) * b := by
    calc r * b = (m * q) * b + r * b - (m * q) * b := (Nat.add_sub_cancel_left _
    _).symm
      _ = x * b - (m * q) * b := by rw [h3]
  exact (u - v, by rw [Nat.mul_sub, ← hu, ← hv]; exact hY)

/-- The least positive m with p ∣ m * b, found by search from 0 with fuel p. -/
def leastMulDvd (p b : Nat) : Nat := findLeastFrom (fun m => 0 < m ∧ p ∣ m * b) 0 p

theorem leastMulDvd_spec (p b : Nat) (hwit : 0 < p ∧ p ∣ p * b) :
    (0 < leastMulDvd p b ∧ p ∣ leastMulDvd p b * b) ∧ leastMulDvd p b ≤ p ∧
      (∀ k, k ≤ p → 0 < k ∧ p ∣ k * b → leastMulDvd p b ≤ k) :=
  ((findLeastFrom_correct (fun m => 0 < m ∧ p ∣ m * b) 0 p p (Nat.zero_le p) (by
  omega)
      hwit).1,
   (findLeastFrom_correct (fun m => 0 < m ∧ p ∣ m * b) 0 p p (Nat.zero_le p) (by
   omega)
      hwit).2,
   fun k hk hPk =>
     (findLeastFrom_correct (fun m => 0 < m ∧ p ∣ m * b) 0 p k (Nat.zero_le k) (by
     omega)
       hPk).2)

/-- Euclid's lemma: a prime dividing a product divides one of the factors. Proved by
least-witness
    search, the division algorithm and descent on the remainder. -/
theorem euclid_lemma (p a b : Nat) (hp : isPrime p) (hab : p ∣ a * b) : p ∣ a ∨ p ∣ b
:= by
  rcases Decidable.em (p ∣ a) with hpa | hpa
  · exact Or.inl hpa
  · right
    have hp0 : 0 < p := by have := hp.1; omega
    obtain ((hm0, hmdvd), hmle, hmin') :=
      leastMulDvd_spec p b (hp0, Nat.dvd_mul_right p b)
    have hmp : leastMulDvd p b ∣ p := by
      apply Nat.dvd_of_mod_eq_zero
      have hc : p % leastMulDvd p b = 0 ∨ 0 < p % leastMulDvd p b := by omega
      rcases hc with h0 | hpos
      · exact h0
      · have hlt : p % leastMulDvd p b < leastMulDvd p b := Nat.mod_lt p hm0
        have hdvd' : p ∣ (p % leastMulDvd p b) * b :=
          dvd_remainder_mul p b (leastMulDvd p b) (p / leastMulDvd p b)
            (p % leastMulDvd p b) p hmdvd (Nat.dvd_mul_right p b)
            (Nat.div_add_mod p (leastMulDvd p b))
        have hle := hmin' (p % leastMulDvd p b) (by omega) (hpos, hdvd')
        omega
    have hma : leastMulDvd p b ∣ a := by
      apply Nat.dvd_of_mod_eq_zero
      have hc : a % leastMulDvd p b = 0 ∨ 0 < a % leastMulDvd p b := by omega
      rcases hc with h0 | hpos
      · exact h0
      · have hlt : a % leastMulDvd p b < leastMulDvd p b := Nat.mod_lt a hm0
        have hdvd' : p ∣ (a % leastMulDvd p b) * b :=
          dvd_remainder_mul p b (leastMulDvd p b) (a / leastMulDvd p b)
            (a % leastMulDvd p b) a hmdvd hab (Nat.div_add_mod a (leastMulDvd p b))
        have hle := hmin' (a % leastMulDvd p b) (by omega) (hpos, hdvd')
        omega
    rcases hp.2 _ hmp with h | h
    · rw [h] at hmdvd
      rwa [Nat.one_mul] at hmdvd
    · rw [h] at hma
      exact absurd hma hpa

/-- Greatest witness at or below the bound, by downward search; P 0 always holds
here. -/
def findGt (P : Nat → Prop) [DecidablePred P] : Nat → Nat
  | 0 => 0
  | n + 1 => if P (n + 1) then n + 1 else findGt P n

theorem findGt_spec (P : Nat → Prop) [DecidablePred P] (n : Nat) (h0 : P 0) :
    P (findGt P n) := by
  induction n with
  | zero => exact h0
  | succ n ih =>
    show P (if P (n + 1) then n + 1 else findGt P n)
    rcases Decidable.em (P (n + 1)) with h | h
    · rw [if_pos h]; exact h
    · rw [if_neg h]; exact ih

theorem findGt_max (P : Nat → Prop) [DecidablePred P] (n k : Nat) (hk : k ≤ n) (hPk :
P k) :
    k ≤ findGt P n := by
  induction n with
  | zero =>
    have h : k = 0 := by omega
    subst h
```

```
    exact Nat.le_refl _
  | succ n ih =>
    show k ≤ (if P (n + 1) then n + 1 else findGt P n)
    rcases Decidable.em (P (n + 1)) with h | h
    · rw [if_pos h]; exact hk
    · rw [if_neg h]
      have hne : k ≠ n + 1 := fun hkk => h (hkk ▸ hPk)
      have hkn : k ≤ n := by omega
      exact ih hkn

/-- The p-adic valuation: the exponent of p in n, as the greatest k with p ^ k | n. -/
def pExp (p n : Nat) : Nat := findGt (fun k => p ^ k | n) n

theorem pExp_dvd (p n : Nat) : p ^ pExp p n | n :=
  findGt_spec (fun k => p ^ k | n) n (by
    show p ^ 0 | n
    rw [Nat.pow_zero]
    exact Nat.one_dvd n)

/-- Exponents of two outrun their index. -/
theorem two_pow_ge (k : Nat) : k + 1 ≤ 2 ^ k := by
  induction k with
  | zero => decide
  | succ k ih => rw [Nat.pow_succ]; omega

/-- A power of p ≥ 2 dividing a positive n is bounded by n. -/
theorem pow_dvd_bound (p n k : Nat) (hp : 2 ≤ p) (hn : 0 < n) (h : p ^ k | n) : k ≤ n := by
  have h1 : p ^ k ≤ n := Nat.le_of_dvd hn h
  have h2 : k + 1 ≤ 2 ^ k := two_pow_ge k
  have h3 : 2 ^ k ≤ p ^ k := Nat.pow_le_pow_left hp k
  omega

theorem pExp_le_of_dvd (p n k : Nat) (hk : k ≤ n) (h : p ^ k | n) : k ≤ pExp p n :=
  findGt_max (fun k => p ^ k | n) n k hk h

/-- Four factors rearranged. -/
theorem mul_mul_mul_comm_nat (a b c d : Nat) : (a * b) * (c * d) = (a * c) * (b * d) := by
  calc (a * b) * (c * d) = a * (b * c) * d := by
        rw [Nat.mul_assoc, ← Nat.mul_assoc b c d, Nat.mul_assoc a (b * c) d]
    _ = a * (c * b) * d := by rw [Nat.mul_comm b c]
    _ = (a * c) * (b * d) := by
        rw [Nat.mul_assoc, Nat.mul_assoc c b d, Nat.mul_assoc a c (b * d)]

/-- The p-adic valuation is additive over products. -/
theorem pExp_mul (p a b : Nat) (hp : isPrime p) (ha : 0 < a) (hb : 0 < b) :
    pExp p (a * b) = pExp p a + pExp p b := by
  have hp2 : 2 ≤ p := hp.1
  have hp0 : 0 < p := by omega
  have hia : p ^ pExp p a | a := pExp_dvd p a
  have hjb : p ^ pExp p b | b := pExp_dvd p b
  obtain (a', ha') := hia
  obtain (b', hb') := hjb
  have hpa' : ¬ p | a' := by
    intro hdiv
    obtain (c, hc) := hdiv
    have hbig : p ^ (pExp p a + 1) | a :=
      (c, by
        calc a = p ^ pExp p a * a' := ha'
          _ = p ^ pExp p a * (p * c) := by rw [hc]
          _ = p ^ (pExp p a + 1) * c := by rw [Nat.pow_add, Nat.pow_one,
            Nat.mul_assoc])
    have hle := pExp_le_of_dvd p a (pExp p a + 1)
      (pow_dvd_bound p a _ hp2 ha hbig) hbig
    omega
  have hpb' : ¬ p | b' := by
    intro hdiv
    obtain (c, hc) := hdiv
    have hbig : p ^ (pExp p b + 1) | b :=
      (c, by
        calc b = p ^ pExp p b * b' := hb'
          _ = p ^ pExp p b * (p * c) := by rw [hc]
          _ = p ^ (pExp p b + 1) * c := by rw [Nat.pow_add, Nat.pow_one,
            Nat.mul_assoc])
    have hle := pExp_le_of_dvd p b (pExp p b + 1)
      (pow_dvd_bound p b _ hp2 hb hbig) hbig
    omega
  have hprodeq : a * b = p ^ (pExp p a + pExp p b) * (a' * b') := by
    have e1 : a * b = (p ^ pExp p a * a') * b := congrArg (fun x => x * b) ha'
    have e2 : (p ^ pExp p a * a') * b = (p ^ pExp p a * a') * (p ^ pExp p b * b') :=
      congrArg (fun x => (p ^ pExp p a * a') * x) hb'
    have e3 : (p ^ pExp p a * a') * (p ^ pExp p b * b') =
        (p ^ pExp p a * p ^ pExp p b) * (a' * b') := mul_mul_mul_comm_nat _ _ _ _
    have e4 : (p ^ pExp p a * p ^ pExp p b) * (a' * b') =
        p ^ (pExp p a + pExp p b) * (a' * b') :=
      congrArg (fun x => x * (a' * b')) (Nat.pow_add p _ _).symm
    exact e1.trans (e2.trans (e3.trans e4))
  have hup : p ^ (pExp p a + pExp p b) | a * b := (a' * b', hprodeq)
  have hdown : ¬ p ^ (pExp p a + pExp p b + 1) | a * b := by
    intro hbig
    have hdecomp : p ^ (pExp p a + pExp p b + 1) = p ^ (pExp p a + pExp p b) * p :=
    by
      rw [Nat.pow_add, Nat.pow_one]
    have hdiv : p | a' * b' := by
      have h' : p ^ (pExp p a + pExp p b) * p | p ^ (pExp p a + pExp p b) * (a' * b')
      := by
        rw [← hprodeq, ← hdecomp]
        exact hbig
      exact Nat.dvd_of_mul_dvd_mul_left (Nat.pow_pos hp0) h'
    rcases euclid_lemma p a' b' hp hdiv with h | h
    · exact hpa' h
    · exact hpb' h
  have hle1 : pExp p a + pExp p b ≤ pExp p (a * b) :=
    pExp_le_of_dvd p (a * b) _ (pow_dvd_bound p (a * b) _ hp2 (Nat.mul_pos ha hb)
      hup) hup
  have hle2 : pExp p (a * b) ≤ pExp p a + pExp p b := by
    have hK : p ^ pExp p (a * b) | a * b := pExp_dvd p (a * b)
    rcases Decidable.em (pExp p a + pExp p b + 1 ≤ pExp p (a * b)) with hgt | hgt
    · exact absurd (Nat.dvd_trans (Nat.pow_dvd_pow p hgt) hK) hdown
    · omega
  omega

/-- The valuation of p at itself is one. -/
theorem pExp_self (p : Nat) (hp : isPrime p) : pExp p p = 1 := by
  have hp2 : 2 ≤ p := hp.1
  have hp0 : 0 < p := by omega
  have h1 : p ^ (1 : Nat) | p := by rw [Nat.pow_one]; exact Nat.dvd_refl p
  have h1le : 1 ≤ pExp p p := pExp_le_of_dvd p p 1 (by omega) h1
  have hnot2 : ¬ p ^ (1 + 1 : Nat) | p := by
    intro h
    have hle : p ^ (1 + 1) ≤ p := Nat.le_of_dvd hp0 h
    rw [Nat.pow_add, Nat.pow_one] at hle
    have hge : 2 * p ≤ p * p := by
      obtain (d, hd) := Nat.exists_eq_add_of_le hp2
      rw [hd, Nat.add_mul]
      exact Nat.le_add_right _ _
    omega
  rcases Decidable.em (2 ≤ pExp p p) with h | h
  · exact absurd (Nat.dvd_trans (Nat.pow_dvd_pow p h) (pExp_dvd p p)) hnot2
  · omega

/-- The valuation vanishes where p does not divide. -/
theorem pExp_eq_zero_of_not_dvd (p n : Nat) (h : ¬ p | n) : pExp p n = 0 := by
  rcases Decidable.em (1 ≤ pExp p n) with hpos | hneg
  · have hpow : p ^ (1 : Nat) | p ^ pExp p n := Nat.pow_dvd_pow p hpos
    rw [Nat.pow_one] at hpow
    exact absurd (Nat.dvd_trans hpow (pExp_dvd p n)) h
  · omega

/-- The valuation at one is zero. -/
theorem pExp_one (p : Nat) (hp : isPrime p) : pExp p 1 = 0 := by
  apply pExp_eq_zero_of_not_dvd
  intro hd
  have h1 := Nat.le_of_dvd (by decide) hd
  have h2 := hp.1
  omega

/-- The valuation at a different prime is zero. -/
theorem pExp_other (p q : Nat) (hp : isPrime p) (hq : isPrime q) (hpq : p ≠ q) :
    pExp p q = 0 := by
  apply pExp_eq_zero_of_not_dvd
  intro hd
  rcases hq.2 p hd with h | h
  · have := hp.1; omega
  · exact hpq h

/-- The p-adic valuation as an integer-valued function. -/
def padicMeasure (p : Nat) (n : Nat) : Int := (pExp p n : Int)

theorem padicMeasure_additive (p : Nat) (hp : isPrime p) :
    CompletelyAdditive (padicMeasure p) := by
  intro a b ha hb
  show ((pExp p (a * b) : Nat) : Int) = (pExp p a : Int) + (pExp p b : Int)
  rw [pExp_mul p a b hp ha hb, Int.natCast_add]

/-- For distinct primes p and q there is a completely additive function equal to 1 at
p and 0 at q:
    the p-adic valuation. -/
theorem prime_freedom_independent (p q : Nat) (hp : isPrime p) (hq : isPrime q) (hpq :
p ≠ q) :
    ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0 :=
  (padicMeasure p, padicMeasure_additive p hp,
   by show ((pExp p p : Nat) : Int) = 1; rw [pExp_self p hp]; rfl,
   by show ((pExp p q : Nat) : Int) = 0; rw [pExp_other p q hp hq hpq]; rfl,
   by show ((pExp p 1 : Nat) : Int) = 0; rw [pExp_one p hp]; rfl)

/-- Uniqueness and independence together: a completely additive function is
determined by its
    values at the primes, and those values are freely assignable. -/
theorem primes_base_of_freedom :
    (∀ f g : Nat → Int, CompletelyAdditive f → CompletelyAdditive g →
      (∀ p, isPrime p → f p = g p) → ∀ n, 0 < n → f n = g n) ∧
    (∀ p q : Nat, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) :=
  (determined_by_primes, prime_freedom_independent)

/-! ## V · The sign arrow of an additive count -/

/-- An additive count: Ω(ab) = Ω(a) + Ω(b) for positive a and b. -/
def AdditiveCount (Om : Nat → Nat) : Prop := ∀ a b, a > 0 → b > 0 → Om (a * b) =
Om a + Om b

/-- The sign arrow of a count: +1 on an even count, −1 on an odd one. -/
def signArrow (k : Nat) : Int := if k % 2 = 0 then 1 else -1

/-- The sign of a sum is the product of the signs. -/
theorem signArrow_add (m n : Nat) :
    signArrow (m + n) = signArrow m * signArrow n := by
  unfold signArrow
  rw [Nat.add_mod]
  rcases Nat.mod_two_eq_zero_or_one m with hm | hm <;>
    rcases Nat.mod_two_eq_zero_or_one n with hn | hn <;>
    rw [hm, hn] <;> decide

/-- The sign arrow of an additive count is completely multiplicative, as λ(n) =
(−1)^Ω(n) is. -/
theorem arrow_multiplicative (Om : Nat → Nat) (hOm : AdditiveCount Om)
    (a b : Nat) (ha : a > 0) (hb : 0 < b) :
    signArrow (Om (a * b)) = signArrow (Om a) * signArrow (Om b) := by
  rw [hOm a b ha hb, signArrow_add]

/-- At a prime the count is one and the sign is −1. -/
theorem arrow_at_prime (Om : Nat → Nat) (p : Nat) (_hp : isPrime p) (hOm : Om p = 1)
:
    signArrow (Om p) = -1 := by
  rw [hOm]
  decide

/-! ## V-bis · No finite stage decides a universal -/

/-- For every N there is a property true below N and false at N. -/
theorem finite_never_forces (N : Nat) :
    ∃ P : Nat → Prop, (∀ n, n < N → P n) ∧ ¬ ∀ n, P n :=
  (fun n => n < N, fun _ h => h, fun h => Nat.lt_irrefl N (h N))

/-- A property with counterexamples past every stage is not universal:
    no finite census decides the limit. -/
theorem limit_not_forced (P : Nat → Prop) (h_finite : ∀ N, ∃ n > N, ¬ P n) : ¬ (∀ n,
P n) := by
  intro h
  obtain (n, _, hn_not) := h_finite 0
  exact hn_not (h n)

/-! ## VI · The chart: the fold, registration, the record -/
```

```
/-- A point of the chart: the doubled real part x and the height t.
    The critical line is x = 1; the fold s ↦ 1 − s̄ sends x to 2 − x;
    registration keeps the height and lands on the line. -/
structure Pt where
  x : Int
  t : Nat
  deriving DecidableEq

def onLine (z : Pt) : Prop := z.x = 1
instance (z : Pt) : Decidable (onLine z) := inferInstanceAs (Decidable (z.x = 1))
def fold (z : Pt) : Pt := (2 - z.x, z.t)
def reg (z : Pt) : Pt := (1, z.t)

theorem fold_fixed_iff (z : Pt) : fold z = z ↔ onLine z := by
  cases z with
  | mk x t =>
    show Pt.mk (2 - x) t = Pt.mk x t ↔ x = 1
    constructor
    · intro h
      have hx := congrArg Pt.x h
      change 2 - x = x at hx
      omega
    · intro h
      subst h
      rfl

theorem reg_fixes_line (z : Pt) (h : onLine z) : reg z = z := by
  cases z with
  | mk x t =>
    have hx : x = 1 := h
    subst hx
    rfl

/-- No registered point lies off the line. -/
theorem unicorn_never_registered (z : Pt) (h : ¬ onLine z) : ∀ w, reg w ≠ z := by
  intro w hw
  apply h
  rw [← hw]
  exact rfl

/-- Every point is on the line, fixed by the fold and by registration, or off the
    line, moved by
    the fold, sharing its record with its partner, and registered by no point. -/
theorem nothing_escapes_one_cut (z : Pt) :
    (onLine z ∧ fold z = z ∧ reg z = z) ∨
    (¬ onLine z ∧ fold z ≠ z ∧ reg (fold z) = reg z ∧ ∀ w, reg w ≠ z) :=
  if h : z.x = 1 then Or.inl (h, (fold_fixed_iff z).mpr h, reg_fixes_line z h)
  else Or.inr (h, fun hf => h ((fold_fixed_iff z).mp hf), rfl,
    unicorn_never_registered z h)

/-- A world is a zero set on the chart. -/
abbrev World := Pt → Prop
def FoldClosed (Z : World) : Prop := ∀ z, Z z → Z (fold z)
/-- The hypothesis, on the chart: every zero lies on the line. -/
def RH (Z : World) : Prop := ∀ z, Z z → onLine z
def Left (Z : World) : Prop := ∃ z, Z z ∧ z.x < 1
def Right (Z : World) : Prop := ∃ z, Z z ∧ 1 < z.x

/-- On a fold-closed world some zero lies left of the line exactly when some zero
    lies right of it. -/
theorem sides_together (Z : World) (hZ : FoldClosed Z) : Left Z ↔ Right Z :=
  ⟨fun (z, hz, hx) => ⟨fold z, hZ z hz, show 1 < 2 - z.x by omega⟩,
   fun (z, hz, hx) => ⟨fold z, hZ z hz, show 2 - z.x < 1 by omega⟩⟩

/-- On a fold-closed world the hypothesis holds exactly when no zero lies left of the
    line. -/
theorem rh_iff_no_left (Z : World) (hZ : FoldClosed Z) : RH Z ↔ ¬ Left Z := by
  constructor
  · intro h ⟨z, hz, hx⟩
    have e : z.x = 1 := h z hz
    omega
  · intro h z hz
    if hx : z.x = 1 then exact hx
    else
      exfalso
      apply h
      if hl : z.x < 1 then exact ⟨z, hz, hl⟩
      else exact ⟨fold z, hZ z hz, show 2 - z.x < 1 by omega⟩

/-- The record of a world: its zeros registered. -/
def recordOf (Z : World) : World := fun r => ∃ s, Z s ∧ reg s = r
def SameRecord (Z Z' : World) : Prop := ∀ r, recordOf Z r ↔ recordOf Z' r
/-- A reading respects the record when two worlds of one record read alike. -/
def RespectsRecord (g : World → Prop) : Prop := ∀ Z Z', SameRecord Z Z' → (g Z ↔ g
  Z')

/-- The on-line world at height 14, and the off-line pair at offset k about the same
    height. -/
abbrev W1 : World := fun z => z = ⟨1, 14⟩
abbrev pairAt (k : Int) : World := fun z => z = ⟨1 - k, 14⟩ ∨ z = ⟨1 + k, 14⟩
abbrev W2 : World := pairAt 1

theorem W1_closed : FoldClosed W1 := by
  intro z hz
  have h : z = ⟨1, 14⟩ := hz
  subst h
  show fold ⟨1, 14⟩ = ⟨1, 14⟩
  decide

theorem W1_rh : RH W1 := by
  intro z hz
  have h : z = ⟨1, 14⟩ := hz
  subst h
  exact rfl

theorem pair_closed (k : Int) : FoldClosed (pairAt k) := by
  intro z hz
  rcases hz with h | h
  · subst h
    apply Or.inr
    show Pt.mk (2 - (1 - k)) 14 = Pt.mk (1 + k) 14
    congr 1
    omega
  · subst h
    apply Or.inl
    show Pt.mk (2 - (1 + k)) 14 = Pt.mk (1 - k) 14
    congr 1
    omega

theorem pair_not_rh (k : Int) (hk : k ≠ 0) : ¬ RH (pairAt k) := by
  intro h
  have e : (1 : Int) - k = 1 := h ⟨1 - k, 14⟩ (Or.inl rfl)
  omega

theorem pair_same_record (k : Int) : SameRecord W1 (pairAt k) := by
  intro r
  constructor
  · intro (s, hs, hr)
    have h : s = ⟨1, 14⟩ := hs
    subst h
    exact (⟨1 - k, 14⟩, Or.inl rfl, hr)
  · intro (s, hs, hr)
    rcases hs with h | h <;> subst h <;> exact (⟨1, 14⟩, rfl, hr)

theorem W2_closed : FoldClosed W2 := pair_closed 1
theorem W2_not_rh : ¬ RH W2 := pair_not_rh 1 (by decide)
theorem same_record_12 : SameRecord W1 W2 := pair_same_record 1

/-- Distinct positive offsets give distinct fold-closed worlds with the record of W1,
    none
    satisfying the hypothesis. -/
theorem fibre_is_infinite (k k' : Int) (hk : 0 < k) (hk' : 0 < k') (hne : k ≠ k') :
    SameRecord W1 (pairAt k) ∧ ¬ RH (pairAt k) ∧ pairAt k ⟨1 - k, 14⟩ ∧ ¬ pairAt k'
      ⟨1 - k, 14⟩ := by
  refine ⟨pair_same_record k, pair_not_rh k (by omega), Or.inl rfl, ?_⟩
  intro h
  rcases h with h | h
  · have e : (1 : Int) - k = 1 - k' := congrArg Pt.x h
    omega
  · have e : (1 : Int) - k = 1 + k' := congrArg Pt.x h
    omega

/-- Two worlds with the same record that both satisfy the hypothesis are equal. -/
theorem lossless_unique (Z Z' : World) (h : SameRecord Z Z') (hZ : RH Z) (hZ' : RH
  Z') :
    ∀ z, Z z ↔ Z' z := by
  intro z
  constructor
  · intro hz
    obtain (s, hs, hsr) := (h z).mp (z, hz, reg_fixes_line z (hZ z hz))
    have e : reg s = s := reg_fixes_line s (hZ' s hs)
    rw [← hsr, e]
    exact hs
  · intro hz
    obtain (s, hs, hsr) := (h z).mpr (z, hz, reg_fixes_line z (hZ' z hz))
    have e : reg s = s := reg_fixes_line s (hZ s hs)
    rw [← hsr, e]
    exact hs

/-- No reading of the record agrees with the hypothesis on every fold-closed world.
  -/
theorem record_decides_nothing (g : World → Prop) (hg : RespectsRecord g) :
    ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z) := fun h =>
  W2_not_rh ((h W2 W2_closed).mp ((hg W1 W2 same_record_12).mp ((h W1 W1_closed).mpr
    W1_rh)))

/-- record_decides_nothing, under a second name. -/
theorem unicorn_block (g : World → Prop) (hg : RespectsRecord g) :
    ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z) := record_decides_nothing g hg

/-- A premise is keyless when it holds on every world. -/
def Keyless (A : World → Prop) : Prop := ∀ Z, A Z
/-- A premise forces the line when every fold-closed world it holds on satisfies the
    hypothesis. -/
def Forces (A : World → Prop) : Prop := ∀ Z, FoldClosed Z → A Z → RH Z

/-- A keyless premise forces nothing: it holds on W2, which is fold-closed and fails
    the
    hypothesis. -/
theorem keyless_forces_nothing (A : World → Prop) (hA : Keyless A) : ¬ Forces A :=
  fun h => W2_not_rh (h W2 W2_closed (hA W2))

/-- The hypothesis separates W1 from W2, which share one record. -/
theorem sentence_separates_record_does_not : (RH W1 ∧ ¬ RH W2) ∧ SameRecord W1 W2 :=
  ⟨(W1_rh, W2_not_rh), same_record_12⟩

/-! ## VII · Least erasure is the value -/

def OffLine (Z : World) : Prop := ∃ z, Z z ∧ ¬ onLine z
/-- Least erasure in the fibre: if the world erases, every world of its record
    erases. -/
def LeastErasure (Z : World) : Prop := ∀ Z', SameRecord Z Z' → OffLine Z → OffLine
  Z'

theorem record_is_lossless (Z : World) : ¬ OffLine (recordOf Z) := by
  intro (r, (s, _, hsr), hoff)
  apply hoff
  rw [← hsr]
  exact rfl

theorem record_same (Z : World) : SameRecord Z (recordOf Z) := by
  intro r
  constructor
  · intro (s, hs, hsr)
    exact (reg s, (s, hs, rfl), hsr)
  · intro (s', (s, hs, hss'), hs'r)
    subst hss'
    exact (s, hs, hs'r)

/-- Least erasure holds on a world exactly when the hypothesis does. -/
theorem least_erasure_is_the_value (Z : World) : LeastErasure Z ↔ RH Z := by
  constructor
  · intro hle z hz
    if h : z.x = 1 then exact h
    else exact absurd (hle (recordOf Z) (record_same Z) (z, hz, h))
      (record_is_lossless Z)
  · intro hrh _ _ (z, hz, hoff)
    exact absurd (hrh z hz) hoff

/-- Least erasure is not a reading of the record: it holds on W1 and fails on W2,
    which share one
    record. -/
theorem least_erasure_reads_past_the_record : ¬ RespectsRecord LeastErasure := fun h
  =>
  W2_not_rh ((least_erasure_is_the_value W2).mp
    ((h W1 W2 same_record_12).mp ((least_erasure_is_the_value W1).mpr W1_rh)))
```

```
/-- Any premise that forces the line and is forced by it is the line, on every fold-closed
    world. -/
theorem posit_is_the_value (A : World → Prop) (h : Forces A)
    (h' : ∀ Z, FoldClosed Z → RH Z → A Z) : ∀ Z, FoldClosed Z → (A Z ↔ RH Z) :=
  fun Z hZ => (h Z hZ, h' Z hZ)

/-! ## VII-bis · The fold never crosses the line; a second symmetry; the record blind at every scale -/

/-- The fold lands on the line exactly where the point already was: folding never crosses. -/
theorem fold_onLine_iff (z : Pt) : onLine (fold z) ↔ onLine z := by
  show (2 - z.x = 1) ↔ (z.x = 1)
  constructor <;> intro h <;> omega

theorem fold_preserves_offline (z : Pt) : ¬ onLine (fold z) ↔ ¬ onLine z := by
  rw [fold_onLine_iff]

theorem fold_ne_of_offline (z : Pt) (h : ¬ onLine z) : fold z ≠ z :=
  fun hf => h ((fold_fixed_iff z).mp hf)

/-- A second involution on the chart, commuting with the fold and preserving the line. -/
structure ConjSymmetry where
  conj : Pt → Pt
  invol : ∀ z, conj (conj z) = z
  commutes : ∀ z, conj (fold z) = fold (conj z)
  preserves_line : ∀ z, onLine (conj z) ↔ onLine z

/-- Under both symmetries one off-line zero forces its reflection, its conjugate and their
    composite into the world, all off the line. -/
theorem offline_zero_quadruple (Z : World) (hF : FoldClosed Z) (C : ConjSymmetry)
    (hC : ∀ z, Z z → Z (C.conj z)) (z : Pt) (hz : Z z) (hoff : ¬ onLine z) :
    Z (fold z) ∧ Z (C.conj z) ∧ Z (C.conj (fold z)) ∧
      ¬ onLine (fold z) ∧ ¬ onLine (C.conj z) ∧ ¬ onLine (C.conj (fold z)) ∧ fold z ≠ z :=
  ⟨hF z hz, hC z hz, hC (fold z) (hF z hz),
   (fold_preserves_offline z).mpr hoff,
   fun h => hoff ((C.preserves_line z).mp h),
   fun h => hoff ((fold_onLine_iff z).mp ((C.preserves_line (fold z)).mp h)),
   fold_ne_of_offline z hoff⟩

/-- If the hypothesis fails on a world, some zero of it lies off the line. Classical. -/
theorem not_rh_has_offline_witness (Z : World) (h : ¬ RH Z) : OffLine Z := by
  apply Classical.byContradiction
  intro hno
  apply h
  intro z hz
  apply Classical.byContradiction
  intro hoff
  exact hno ⟨z, hz, hoff⟩

/-- Denying the hypothesis on a world with both symmetries posits a whole off-line orbit of four
    points. -/
theorem denial_posits_the_orbit (Z : World) (hF : FoldClosed Z) (C : ConjSymmetry)
    (hC : ∀ z, Z z → Z (C.conj z)) (h : ¬ RH Z) :
    ∃ z, Z z ∧ ¬ onLine z ∧ Z (fold z) ∧ Z (C.conj z) ∧ Z (C.conj (fold z)) := by
  obtain ⟨z, hz, hoff⟩ := not_rh_has_offline_witness Z h
  exact ⟨z, hz, hoff, hF z hz, hC z hz, hC (fold z) (hF z hz)⟩

/-- For every nonzero offset the pair world is fold-closed, fails the hypothesis, and shares the
    record of W1. -/
theorem record_blind_at_every_scale (k : Int) (hk : k ≠ 0) :
    RH W1 ∧ FoldClosed (pairAt k) ∧ ¬ RH (pairAt k) ∧ SameRecord W1 (pairAt k) :=
  ⟨W1_rh, pair_closed k, pair_not_rh k hk, pair_same_record k⟩

/-! ## VIII · Self-grounding supplies, and the five faces of the hypothesis -/

/-- A self-grounding root, the structure of Appendix R in the same words: acts occur, and every act instances the root. -/
structure SelfGrounding (root : Prop) where
  Act       : Type
  anAct     : Act
  instances : Act → root

/-- A self-grounding supply of a proposition, with an act, exists exactly when the proposition
    holds. -/
theorem supply_iff (root : Prop) : (∃ G : SelfGrounding root, Nonempty G.Act) ↔ root := by
  constructor
  · intro ⟨G, ⟨a⟩⟩
    exact G.instances a
  · intro hr
    exact ⟨⟨Unit, (), fun _ => hr⟩, ⟨()⟩⟩

/-- The five faces of the hypothesis. The equivalences are fields, carried as hypotheses and not
    proved here: the critical line (Riemann 1859), Λ = 0 (Newman 1976; Rodgers and Tao 2020), the
    faithfulness of the Liouville function (Landau 1899), and Weil positivity (Weil 1952). -/
structure Faces where
  line : Prop
  lamZero : Prop
  faithful : Prop
  weil : Prop
  least : Prop
  line_iff_least : line ↔ least
  lam_iff_least : lamZero ↔ least
  faith_iff_least : faithful ↔ least
  weil_iff_least : weil ↔ least

/-- Any one face implies all five. -/
theorem faces_are_one (H : Faces) :
    (H.line ↔ H.least) ∧ (H.lamZero ↔ H.least) ∧ (H.faithful ↔ H.least) ∧ (H.weil ↔ H.least) :=
  ⟨H.line_iff_least, H.lam_iff_least, H.faith_iff_least, H.weil_iff_least⟩

/-- Given a self-grounding supply of the least-erasure face with an act, all five faces hold. -/
theorem rh_from_the_act_generic (H : Faces) (G : SelfGrounding H.least) (a : G.Act) :
    H.line ∧ H.lamZero ∧ H.faithful ∧ H.weil ∧ H.least :=
  let le := G.instances a
  ⟨H.line_iff_least.mpr le, H.lam_iff_least.mpr le, H.faith_iff_least.mpr le,
   H.weil_iff_least.mpr le, le⟩

/-! ## IX · Primes, the free basis and the identity arrow are keyless and force nothing -/

/-- Primes exist. -/
theorem primes_exist : ∃ p, isPrime p :=
  let ⟨p, hp, _⟩ := exists_prime_dvd 2 (by decide) (by decide)
  ⟨p, hp⟩

/-- The existence of primes holds on every world. -/
theorem primes_exist_keyless : Keyless (fun _ => ∃ p, isPrime p) := fun _ => primes_exist

/-- The free basis at the primes holds on every world. -/
theorem prime_freedom_keyless :
    Keyless (fun _ => ∀ p q, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) :=
  fun _ => prime_freedom_independent

/-- The identity arrow exists on every world. -/
theorem arrow_keyless : Keyless (fun _ => ∃ f : Nat → Nat, ∀ a, f a = a) :=
  fun _ => arrow_exists Nat

/-- The existence of primes forces nothing. -/
theorem primes_exist_forces_nothing : ¬ Forces (fun _ => ∃ p, isPrime p) :=
  keyless_forces_nothing _ primes_exist_keyless

/-- The free basis at the primes forces nothing. -/
theorem prime_freedom_forces_nothing :
    ¬ Forces (fun _ => ∀ p q, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) :=
  keyless_forces_nothing _ prime_freedom_keyless

/-- The existence of the identity arrow forces nothing. -/
theorem arrow_forces_nothing : ¬ Forces (fun _ => ∃ f : Nat → Nat, ∀ a, f a = a) :=
  keyless_forces_nothing _ arrow_keyless

/-- The free basis holds, and a fold-closed world failing the hypothesis exists. -/
theorem free_basis_coexists_with_offline_world :
    (∀ p q : Nat, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) ∧
    ∃ Z, FoldClosed Z ∧ ¬ RH Z :=
  ⟨prime_freedom_independent, W2, W2_closed, W2_not_rh⟩

/-- An off-line point folds to a distinct off-line point, which no point registers to. -/
theorem fold_off_line_stays_off (z : Pt) (h : ¬ onLine z) :
    ¬ onLine (fold z) ∧ fold z ≠ reg z ∧ fold z ≠ z :=
  ⟨(fold_preserves_offline z).mpr h,
   fun e => unicorn_never_registered (fold z) ((fold_preserves_offline z).mpr h) z e.symm,
   fold_ne_of_offline z h⟩

/-! ## X · The explicit formula as a structure; least erasure is Weil positivity -/

structure ExplicitFormula where
  /-- The value type of the two sides, with its order and its zero. -/
  V : Type
  le : V → V → Prop
  zero : V
  /-- The admissible test functions, their adjoint g ↦ g~, and their convolution. -/
  T : Type
  adj : T → T
  conv : T → T → T
  /-- The arithmetic side: the archimedean term with the sum over the primes. -/
  primeSide : T → V
  /-- The zero side: the sum over the zeros. -/
  zeroSide : T → V
  /-- The zeros, as a world on the chart. -/
  zeros : World
  /-- The explicit formula: the zero side of every test function equals its arithmetic side. Carried
      as a hypothesis (Guinand 1948; Weil 1952). -/
  identity : ∀ g, zeroSide g = primeSide g
  /-- Weil's criterion: the arithmetic side is non-negative on every g ⋆ g̃ exactly when the zeros
      lie on the line. Carried as a hypothesis (Weil 1952; Bombieri 2000). -/
  positivity_iff_line : (∀ g, le zero (primeSide (conv g (adj g)))) ↔ RH zeros

/-- Weil positivity, stated on the prime side. -/
def WeilPositive (E : ExplicitFormula) : Prop :=
  ∀ g, E.le E.zero (E.primeSide (E.conv g (E.adj g)))

/-- Through the identity, positivity reads the same on the zero side. -/
theorem positivity_on_zero_side (E : ExplicitFormula) :
    WeilPositive E ↔ ∀ g, E.le E.zero (E.zeroSide (E.conv g (E.adj g))) := by
  constructor
  · intro h g
    rw [E.identity]
    exact h g
  · intro h g
    rw [← E.identity]
    exact h g

/-- Least erasure of the zeros of an explicit formula is Weil positivity of its arithmetic side. -/
theorem least_erasure_is_positivity (E : ExplicitFormula) :
    LeastErasure E.zeros ↔ WeilPositive E :=
  (least_erasure_is_the_value E.zeros).trans E.positivity_iff_line.symm

/-- A self-grounding supply of Weil positivity exists exactly when the zeros lie on the line. -/
theorem prime_witness_iff (E : ExplicitFormula) :
    (∃ G : SelfGrounding (WeilPositive E), Nonempty G.Act) ↔ RH E.zeros :=
  (supply_iff (WeilPositive E)).trans E.positivity_iff_line

/-- Weil positivity implies the hypothesis for the zeros of the explicit formula. -/
theorem rh_from_prime_witness (E : ExplicitFormula) (h : WeilPositive E) : RH E.zeros :=
  E.positivity_iff_line.mp h

/-- The positive instance: one test function, arithmetic side zero, zeros on the line. -/
def positiveInstance : ExplicitFormula where
  V := Int
```

```
  le := fun a b => a ≤ b
  zero := 0
  T := Unit
  adj := id
  conv := fun _ _ => ()
  primeSide := fun _ => 0
  zeroSide := fun _ => 0
  zeros := W1
  identity := fun _ => rfl
  positivity_iff_line := (fun _ => W1_rh, fun _ _ => Int.le_refl 0)

/-- The negative instance: one test function, arithmetic side minus one, zeros off the line. -/
def negativeInstance : ExplicitFormula where
  V := Int
  le := fun a b => a ≤ b
  zero := 0
  T := Unit
  adj := id
  conv := fun _ _ => ()
  primeSide := fun _ => -1
  zeroSide := fun _ => -1
  zeros := W2
  identity := fun _ => rfl
  positivity_iff_line :=
    (fun h => absurd (h ()) (by decide : ¬ ((0 : Int) ≤ -1)), fun h => absurd h
    W2_not_rh)

/-- Two explicit formulas satisfy every field, one positive with its zeros on the line and one not
    positive with its zeros off the line: no field decides positivity. -/
theorem positivity_is_keyed : WeilPositive positiveInstance ∧ ¬ WeilPositive negativeInstance :=
  (fun _ => Int.le_refl 0, fun h => absurd (h ()) (by decide : ¬ ((0 : Int) ≤ -1)))

/-- The free basis holds in both instances. -/
theorem freedom_does_not_pick_the_sign :
    (∀ p q : Nat, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) ∧
    WeilPositive positiveInstance ∧ ¬ WeilPositive negativeInstance :=
  (prime_freedom_independent, positivity_is_keyed)

/-- Section X, whole: the free basis; least erasure as the hypothesis and as positivity; the block;
    keyless premises forcing nothing; positivity keyed. -/
theorem prime_witness_ledger :
    (∀ f g : Nat → Int, CompletelyAdditive f → CompletelyAdditive g →
      (∀ p, isPrime p → f p = g p) → ∀ n, 0 < n → f n = g n) ∧
    (∀ p q : Nat, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) ∧
    (∀ Z : World, LeastErasure Z ↔ RH Z) ∧
    (∀ E : ExplicitFormula, LeastErasure E.zeros ↔ WeilPositive E) ∧
    (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)) ∧
    (¬ Forces (fun _ => ∃ p, isPrime p)) ∧
    (¬ Forces (fun _ => ∀ p q, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0)) ∧
    (¬ Forces (fun _ => ∃ f : Nat → Nat, ∀ a, f a = a)) ∧
    (WeilPositive positiveInstance ∧ ¬ WeilPositive negativeInstance) :=
  (determined_by_primes, prime_freedom_independent, least_erasure_is_the_value,
   least_erasure_is_positivity, unicorn_block, primes_exist_forces_nothing,
   prime_freedom_forces_nothing, arrow_forces_nothing, positivity_is_keyed)

/-! ## XI · The posit as a structure field -/

/-- A zero set with its fold-closure and the one posit, least erasure. -/
structure ActualZeros where
  /-- The zero set, as a world on the chart. -/
  zeros : World
  /-- The zero set is fold-closed (the functional equation, Riemann 1859). -/
  fold_closed : FoldClosed zeros
  /-- The posit: least erasure of the zero set. By least_erasure_is_the_value this field is the
    hypothesis. -/
  supply : LeastErasure zeros

/-- From the posit, the hypothesis. -/
theorem rh_from_the_act (A : ActualZeros) : RH A.zeros :=
  (least_erasure_is_the_value A.zeros).mp A.supply

/-- The type of the posit is equivalent to the hypothesis. -/
theorem posit_is_the_conclusion (A : ActualZeros) : LeastErasure A.zeros ↔ RH A.zeros :=
  least_erasure_is_the_value A.zeros

/-- From the posit: the line, least erasure, every zero fixed by the fold and by registration, and
    no off-line orbit. -/
theorem rh_ground_closure_complete (A : ActualZeros) :
    RH A.zeros ∧ LeastErasure A.zeros ∧ (∀ z, A.zeros z → fold z = z) ∧
    (∀ z, A.zeros z → reg z = z) ∧ ¬ Left A.zeros :=
  (rh_from_the_act A, A.supply,
   fun z hz => (fold_fixed_iff z).mpr (rh_from_the_act A z hz),
   fun z hz => reg_fixes_line z (rh_from_the_act A z hz),
   (rh_iff_no_left A.zeros A.fold_closed).mp (rh_from_the_act A))

/-- An explicit formula for fold-closed zeros, with positivity posited. -/
structure PrimeAct where
  E : ExplicitFormula
  fold_closed : FoldClosed E.zeros
  /-- The posit on the prime side: Weil positivity. -/
  positive : WeilPositive E

/-- A prime act is a least-erasure act. -/
def PrimeAct.toActual (P : PrimeAct) : ActualZeros :=
  (P.E.zeros, P.fold_closed, (least_erasure_is_positivity P.E).mpr P.positive)

/-- From positivity posited, the hypothesis. -/
theorem rh_from_prime_act (P : PrimeAct) : RH P.E.zeros := rh_from_the_act P.toActual

/-- For an explicit formula with fold-closed zeros, a positivity posit exists exactly when a
    least-erasure posit exists for its zeros. -/
theorem acts_are_one (E : ExplicitFormula) (hF : FoldClosed E.zeros) :
    (∃ P : PrimeAct, P.E = E) ↔ ∃ A : ActualZeros, A.zeros = E.zeros := by
  constructor
  · intro (P, hP)
    subst hP
    exact (P.toActual, rfl)
  · intro (A, hA)
    refine ((E, hF, (least_erasure_is_positivity E).mp ?_), rfl)
    rw [← hA]
    exact A.supply

/-! ## XII · The block with no axiom: the pair world written out -/

/-- The pair world at offset one, written out. -/
abbrev W2f : World := fun z => z = (0, 14) ∨ z = (2, 14)

theorem W2f_closed : FoldClosed W2f := by
  intro z hz
  rcases hz with h | h
  · subst h; exact Or.inr rfl
  · subst h; exact Or.inl rfl

theorem W2f_not_rh : ¬ RH W2f :=
  fun h => absurd (h (0, 14) (Or.inl rfl)) (by decide : ¬ ((0 : Int) = 1))

theorem same_record_f : SameRecord W1 W2f := by
  intro r
  constructor
  · intro (s, hs, hr)
    have h : s = (1, 14) := hs
    subst h
    exact ((0, 14), Or.inl rfl, hr)
  · intro (s, hs, hr)
    rcases hs with h | h <;> subst h <;> exact ((1, 14), rfl, hr)

/-- record_decides_nothing, with no axiom. -/
theorem record_decides_nothing_free (g : World → Prop) (hg : RespectsRecord g) :
    ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z) := fun h =>
  W2f_not_rh ((h W2f W2f_closed).mp ((hg W1 W2f same_record_f).mp ((h W1
  W1_closed).mpr W1_rh)))

/-- unicorn_block, with no axiom. -/
theorem unicorn_block_free (g : World → Prop) (hg : RespectsRecord g) :
    ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z) := record_decides_nothing_free g hg

/-- keyless_forces_nothing, with no axiom. -/
theorem keyless_forces_nothing_free (A : World → Prop) (hA : Keyless A) : ¬ Forces A :=
  fun h => W2f_not_rh (h W2f W2f_closed (hA W2f))

/-- arrow_forces_nothing, with no axiom. -/
theorem arrow_forces_nothing_free : ¬ Forces (fun _ => ∃ f : Nat → Nat, ∀ a, f a = a) :=
  keyless_forces_nothing_free _ arrow_keyless

/-- least_erasure_reads_past_the_record, with no axiom. -/
theorem least_erasure_reads_past_the_record_free : ¬ RespectsRecord LeastErasure :=
  fun h =>
  W2f_not_rh ((least_erasure_is_the_value W2f).mp
    ((h W1 W2f same_record_f).mp ((least_erasure_is_the_value W1).mpr W1_rh)))

/-- The negative instance on the explicit pair world. -/
def negativeInstanceF : ExplicitFormula where
  V := Int
  le := fun a b => a ≤ b
  zero := 0
  T := Unit
  adj := id
  conv := fun _ _ => ()
  primeSide := fun _ => -1
  zeroSide := fun _ => -1
  zeros := W2f
  identity := fun _ => rfl
  positivity_iff_line :=
    (fun h => absurd (h ()) (by decide : ¬ ((0 : Int) ≤ -1)), fun h => absurd h
    W2f_not_rh)

/-- positivity_is_keyed, with no axiom. -/
theorem positivity_is_keyed_free : WeilPositive positiveInstance ∧ ¬ WeilPositive
negativeInstanceF :=
  (fun _ => Int.le_refl 0, fun h => absurd (h ()) (by decide : ¬ ((0 : Int) ≤ -1)))


/-! ## XIII · The hypothesis on the supplied bit -/

/-- For every explicit formula, Weil positivity is equivalent to the hypothesis for its zeros. -/
theorem spend_is_the_line (E : ExplicitFormula) : WeilPositive E ↔ RH E.zeros :=
  E.positivity_iff_line

/-- The free basis holds, and an explicit formula exists on which positivity fails: the free basis
    and positivity are distinct. -/
theorem spend_is_not_the_free_basis :
    (∀ p q : Nat, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) ∧
    ∃ E : ExplicitFormula, ¬ WeilPositive E :=
  (prime_freedom_independent, negativeInstanceF, positivity_is_keyed_free.2)

/-- From positivity posited: the line, least erasure, positivity, every zero fixed by the fold and
    by registration, and no off-line orbit. -/
theorem rh_on_the_spent_bit (P : PrimeAct) :
    RH P.E.zeros ∧ LeastErasure P.E.zeros ∧ WeilPositive P.E ∧
    (∀ z, P.E.zeros z → fold z = z) ∧ (∀ z, P.E.zeros z → reg z = z) ∧ ¬ Left
    P.E.zeros :=
  let c := rh_ground_closure_complete P.toActual
  (c.1, c.2.1, P.positive, c.2.2.1, c.2.2.2.1, c.2.2.2.2)

/-- Sections X to XIII, whole. -/
theorem prime_arc_sealed :
    (∀ f g : Nat → Int, CompletelyAdditive f → CompletelyAdditive g →
      (∀ p, isPrime p → f p = g p) → ∀ n, 0 < n → f n = g n) ∧
    (∀ p q : Nat, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) ∧
    (∀ Z : World, LeastErasure Z ↔ RH Z) ∧
    (∀ E : ExplicitFormula, LeastErasure E.zeros ↔ WeilPositive E) ∧
    (∀ E : ExplicitFormula, WeilPositive E ↔ RH E.zeros) ∧
    (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)) ∧
    (∀ A : World → Prop, Keyless A → ¬ Forces A) ∧
    (WeilPositive positiveInstance ∧ ¬ WeilPositive negativeInstanceF) ∧
    (∃ E : ExplicitFormula, ¬ WeilPositive E) ∧
    (∀ P : PrimeAct, RH P.E.zeros) :=
  (determined_by_primes, prime_freedom_independent, least_erasure_is_the_value,
```

```
  least_erasure_is_positivity, spend_is_the_line, record_decides_nothing_free,
  keyless_forces_nothing_free, positivity_is_keyed_free,
  spend_is_not_the_free_basis.2,
  rh_from_prime_act)


/-! ## XIV · The weakest forcing premise; the Li and de Bruijn–Newman coordinates -/

/-- The hypothesis forces the line, and every premise that forces the line implies the hypothesis
    on every fold-closed world. -/
theorem rh_is_the_weakest_forcing_premise :
    Forces RH ∧ ∀ A : World → Prop, Forces A → ∀ Z, FoldClosed Z → A Z → RH Z :=
  (fun _ _ h => h, fun _ hA Z hZ ha => hA Z hZ ha)

/-- A premise that holds at some fold-closed world where the hypothesis fails does not force. -/
theorem weaker_never_forces (A : World → Prop) (Z : World) (hZ : FoldClosed Z) (ha : A Z)
    (hn : ¬ RH Z) : ¬ Forces A :=
  fun h => hn (h Z hZ ha)

/-- A premise true on W2f forces nothing. -/
theorem weaker_at_the_twin_never_forces (A : World → Prop) (ha : A W2f) : ¬ Forces A :=
  weaker_never_forces A W2f W2f_closed ha W2f_not_rh

/-- A zero set with the signs of its Li coefficients: the hypothesis holds exactly when every
    coefficient is non-negative. Carried as a hypothesis (Li 1997; Bombieri and Lagarias 1999). -/
structure LiStream where
  zeros : World
  nonneg : Nat → Prop
  li : RH zeros ↔ ∀ n, 1 ≤ n → nonneg n

theorem rh_from_li (L : LiStream) (h : ∀ n, 1 ≤ n → L.nonneg n) : RH L.zeros :=
  L.li.mpr h

theorem li_is_the_bit_stream (L : LiStream) : (∀ n, 1 ≤ n → L.nonneg n) ↔ RH L.zeros :=
  L.li.symm

/-- For every N there is a Li stream non-negative below N whose zero set lies off the line. -/
theorem li_prefix_never_forces (N : Nat) :
    ∃ L : LiStream, (∀ n, n < N → L.nonneg n) ∧ ¬ RH L.zeros :=
  ((W2f, fun n => n < N,
    (fun h => absurd h W2f_not_rh,
     fun h => absurd (h (N + 1) (Nat.succ_pos N))
       (fun c => Nat.lt_irrefl N (Nat.lt_trans (Nat.lt_succ_self N) c)))),
   fun _ h => h, W2f_not_rh)

/-- The de Bruijn–Newman constant over an ordered type: Λ and its zero, the order's reflexivity and
    antisymmetry, 0 ≤ Λ (Rodgers and Tao 2020), and the hypothesis exactly when Λ = 0 (Newman
    1976). Every field is carried as a hypothesis. -/
structure DBN (V : Type) [LE V] where
  zeros : World
  lam : V
  zero : V
  refl : ∀ a : V, a ≤ a
  antisymm : ∀ a b : V, a ≤ b → b ≤ a → a = b
  lower : zero ≤ lam
  rh_iff : RH zeros ↔ lam = zero

/-- From Λ ≤ 0 and the cited 0 ≤ Λ, the hypothesis. -/
theorem rh_from_the_sign {V : Type} [LE V] (D : DBN V) (h : D.lam ≤ D.zero) : RH D.zeros :=
  D.rh_iff.mpr (D.antisymm _ _ h D.lower)

/-- The hypothesis is equivalent to Λ ≤ 0. -/
theorem rh_iff_the_sign {V : Type} [LE V] (D : DBN V) : RH D.zeros ↔ D.lam ≤ D.zero :=
  (fun h => by rw [D.rh_iff.mp h]; exact D.refl _, rh_from_the_sign D)

/-- On one zero set, Weil positivity and Λ ≤ 0 are equivalent. -/
theorem spends_are_one {V : Type} [LE V] (P : PrimeAct) (D : DBN V) (same : D.zeros = P.E.zeros) :
    (D.lam ≤ D.zero) ↔ WeilPositive P.E :=
  (rh_iff_the_sign D).symm.trans (by rw [same]; exact (spend_is_the_line P.E).symm)

/-- Λ = 0 is realized over W1 and Λ = 1 over W2f: the sign is a property of the world. -/
theorem sign_realized_both_ways :
    (∃ D : DBN Int, D.zeros = W1 ∧ D.lam = D.zero) ∧
    (∃ D : DBN Int, D.zeros = W2f ∧ ¬ D.lam ≤ D.zero) :=
  (((W1, 0, 0, fun a => Int.le_refl a, fun a b => Int.le_antisymm, Int.le_refl 0,
      (fun _ => rfl, fun _ => W1_rh)), rfl, rfl),
   ((W2f, 1, 0, fun a => Int.le_refl a, fun a b => Int.le_antisymm, by decide,
      (fun h => absurd h W2f_not_rh, fun h => absurd h (by decide))), rfl, by
     decide))

/-- A self-grounding supply of 0 < 1, with the unit act. -/
def rootSelfGrounding : SelfGrounding ((0 : Int) < 1) := (Unit, (), fun _ => by decide)

theorem root_has_an_act : Nonempty rootSelfGrounding.Act := ⟨()⟩

/-- No self-grounding supply of the hypothesis on W2f has an act: W2f fails the hypothesis. -/
theorem line_not_self_grounding : ¬ ∃ G : SelfGrounding (RH W2f), Nonempty G.Act :=
  fun (G, (a)) => W2f_not_rh (G.instances a)

/-- Section XIV, whole. -/
theorem the_vestigial_posit :
    (Forces RH ∧ ∀ A : World → Prop, Forces A → ∀ Z, FoldClosed Z → A Z → RH Z) ∧
    (∀ A : World → Prop, A W2f → ¬ Forces A) ∧
    (∀ L : LiStream, (∀ n, 1 ≤ n → L.nonneg n) ↔ RH L.zeros) ∧
    (∀ N, ∃ L : LiStream, (∀ n, n < N → L.nonneg n) ∧ ¬ RH L.zeros) ∧
    (∀ (V : Type) [LE V] (D : DBN V), RH D.zeros ↔ D.lam ≤ D.zero) ∧
    ((∃ D : DBN Int, D.zeros = W1 ∧ D.lam = D.zero) ∧
      (∃ D : DBN Int, D.zeros = W2f ∧ ¬ D.lam ≤ D.zero)) ∧
    (∀ (V : Type) [LE V] (P : PrimeAct) (D : DBN V), D.zeros = P.E.zeros →
      ((D.lam ≤ D.zero) ↔ WeilPositive P.E)) ∧
    Nonempty rootSelfGrounding.Act ∧
    ¬ ∃ G : SelfGrounding (RH W2f), Nonempty G.Act :=
  (rh_is_the_weakest_forcing_premise, weaker_at_the_twin_never_forces,
   li_is_the_bit_stream,
   li_prefix_never_forces, fun _ _ D => rh_iff_the_sign D, sign_realized_both_ways,
   fun _ _ P D same => spends_are_one P D same, root_has_an_act,
   line_not_self_grounding)


/-! ## XV · Four faces in time, exactly one keyed -/

/-- A world in time: the zero set at each instant. -/
abbrev TWorld := Nat → World

/-- The same locus at every instant: the line. -/
def SameLocus (W : TWorld) : Prop := ∀ t z, W t z → (fold z = z ↔ onLine z)
/-- The fold acts at every instant. -/
def FoldInvT (W : TWorld) : Prop := ∀ t, FoldClosed (W t)
/-- The record at every instant lands on the line and forgets the side. -/
def RecordT (W : TWorld) : Prop := ∀ t z, W t z → onLine (reg z) ∧ reg (fold z) = reg z
/-- The arrow at every instant: the free bit is present. -/
def ArrowT (_W : TWorld) : Prop := ∀ _t : Nat, ∃ f : Nat → Nat, ∀ a, f a = a
/-- Timeless: whether the zeros sit on the line does not vary in time. -/
def TimelessT (W : TWorld) : Prop := ∀ t s, RH (W t) ↔ RH (W s)
/-- Bound: the closure at every instant. -/
def BoundT (W : TWorld) : Prop := ∀ t, RH (W t)

/-- The on-line world, constant in time, and the twin, constant in time. -/
abbrev WOn : TWorld := fun _ => W1
abbrev WTwin : TWorld := fun _ => W2f

/-- The fold face holds on every world in time. -/
theorem fold_face_keyless (W : TWorld) : SameLocus W := fun _ z _ => fold_fixed_iff z
theorem fold_face_on_twin : FoldInvT WTwin := fun _ => W2f_closed
theorem fold_face_on_line : FoldInvT WOn := fun _ => W1_closed

/-- The record face holds on every world in time. -/
theorem record_face_keyless (W : TWorld) : RecordT W := fun _ _ _ => (rfl, rfl)

/-- The arrow face holds on every world in time. -/
theorem arrow_face_keyless (W : TWorld) : ArrowT W := fun _ => arrow_exists Nat

/-- The closure face holds on WOn. -/
theorem closure_face_on_line : BoundT WOn := fun _ => W1_rh
theorem closure_face_fails_on_twin : ¬ BoundT WTwin := fun h => W2f_not_rh (h 0)

/-- WTwin carries the fold, the record and the arrow at every instant and is timeless, and it is
    not bound: of the four faces only the closure is keyed. -/
theorem exactly_one_face_is_keyed :
    (SameLocus WTwin ∧ FoldInvT WTwin ∧ RecordT WTwin ∧ ArrowT WTwin ∧ TimelessT WTwin) ∧
    ¬ BoundT WTwin ∧
    (SameLocus WOn ∧ FoldInvT WOn ∧ RecordT WOn ∧ ArrowT WOn ∧ TimelessT WOn) ∧ BoundT WOn :=
  ((fold_face_keyless _, fold_face_on_twin, record_face_keyless _, arrow_face_keyless _,
    fun _ _ => Iff.rfl), closure_face_fails_on_twin,
   (fold_face_keyless _, fold_face_on_line, record_face_keyless _, arrow_face_keyless _,
    fun _ _ => Iff.rfl), closure_face_on_line)

/-- The arrow, the fold and the record hold on WTwin at every instant while the line fails there:
    the arrow is not the line. -/
theorem arrow_is_not_the_line :
    ArrowT WTwin ∧ FoldInvT WTwin ∧ RecordT WTwin ∧ ¬ BoundT WTwin :=
  (arrow_face_keyless _, fold_face_on_twin, record_face_keyless _,
   closure_face_fails_on_twin)

/-- A timeless world is bound exactly when it is bound at instant 0. -/
theorem template_binds_iff_seed (W : TWorld) (u : TimelessT W) : BoundT W ↔ RH (W 0) :=
  (fun h => h 0, fun s t => (u 0 t).mp s)

/-- For a timeless world, bound at instant 0 is the hypothesis at instant 0; WTwin has the three
    keyless faces and fails the hypothesis at every instant. -/
theorem the_seed_is_the_spend :
    (∀ W : TWorld, TimelessT W → (BoundT W ↔ RH (W 0))) ∧
    TimelessT WTwin ∧ ArrowT WTwin ∧ FoldInvT WTwin ∧ RecordT WTwin ∧ ¬ RH (WTwin 0) :=
  (template_binds_iff_seed, fun _ _ => Iff.rfl, arrow_face_keyless _,
   fold_face_on_twin,
    record_face_keyless _, W2f_not_rh)

/-- Section XV, whole. -/
theorem the_template_plugged_in :
    ((SameLocus WTwin ∧ FoldInvT WTwin ∧ RecordT WTwin ∧ ArrowT WTwin ∧ TimelessT WTwin) ∧
      ¬ BoundT WTwin ∧
      (SameLocus WOn ∧ FoldInvT WOn ∧ RecordT WOn ∧ ArrowT WOn ∧ TimelessT WOn) ∧
      BoundT WOn) ∧
    (ArrowT WTwin ∧ FoldInvT WTwin ∧ RecordT WTwin ∧ ¬ BoundT WTwin) ∧
    (∀ W : TWorld, TimelessT W → (BoundT W ↔ RH (W 0))) ∧
    (∀ W : TWorld, BoundT W → ∀ t, LeastErasure (W t)) :=
  (exactly_one_face_is_keyed, arrow_is_not_the_line, template_binds_iff_seed,
   fun W h t => (least_erasure_is_the_value (W t)).mpr (h t))


/-! ## XVI · The eigenstructure of the fold: the side bit and its calibration -/

/-- The displacement x − 1. -/
def oddPart (z : Pt) : Int := z.x - 1

/-- The fold negates the displacement and fixes the height. -/
theorem fold_negates_odd (z : Pt) : oddPart (fold z) = - oddPart z := by
  show 2 - z.x - 1 = -(z.x - 1)
  rw [Int.neg_sub, Int.sub_sub, Int.add_comm, ← Int.sub_sub]; rfl

theorem fold_keeps_even (z : Pt) : (fold z).t = z.t := rfl

/-- The fold acts as −1 on the displacement. -/
theorem residence_orientation_reversing (z : Pt) : oddPart (fold z) = (-1) * oddPart z := by
  rw [fold_negates_odd, Int.neg_one_mul]

/-- Registration sends the displacement to 0, keeps the height, and is idempotent. -/
theorem reg_kills_odd (_z : Pt) : oddPart (reg _z) = 0 := rfl
theorem reg_keeps_even (z : Pt) : (reg z).t = z.t := rfl
theorem reg_idempotent (z : Pt) : reg (reg z) = reg z := rfl
```

```
/-- A point is on the line exactly when its displacement is 0. -/
theorem onLine_iff_odd_zero (z : Pt) : onLine z ↔ oddPart z = 0 :=
  Int.sub_eq_zero.symm

/-- The hypothesis: every zero has displacement 0. -/
theorem rh_iff_even_eigenspace (Z : World) : RH Z ↔ ∀ z, Z z → oddPart z = 0 :=
  ⟨fun h z hz => (onLine_iff_odd_zero z).mp (h z hz), fun h z hz =>
   (onLine_iff_odd_zero z).mpr (h z hz)⟩

/-- Every function of the registered point takes one value on a point and its
fold-partner. -/
theorem record_blind_to_odd {β : Type} (g : Pt → β) (z : Pt) : g (reg (fold z)) = g
(reg z) := rfl

/-- Off the line a point and its fold-partner have opposite nonzero displacements. -/
theorem odd_pair_opposite (z : Pt) (h : ¬ onLine z) :
    oddPart (fold z) = - oddPart z ∧ oddPart z ≠ 0 :=
  ⟨fold_negates_odd z, fun e => h ((onLine_iff_odd_zero z).mpr e)⟩

/-- The side bit: whether the displacement is negative. -/
def side (z : Pt) : Bool := decide (oddPart z < 0)

/-- Off the line the fold flips the side bit. -/
theorem side_odd_off_line (z : Pt) (h : ¬ onLine z) : side (fold z) = !side z := by
  have hne : oddPart z ≠ 0 := (odd_pair_opposite z h).2
  unfold side
  rw [fold_negates_odd]
  exact (Int.decLt (oddPart z) 0).byCases
    (fun hl =>
      have hp : ¬ (-(oddPart z) < 0) := fun c => Int.lt_irrefl _ (Int.lt_trans c
        (Int.neg_pos_of_neg hl))
      by rw [decide_eq_true hl, decide_eq_false hp]; rfl)
    (fun hr =>
      have hp : -(oddPart z) < 0 :=
        Int.neg_neg_of_pos (Int.lt_iff_le_and_ne.mpr (Int.not_lt.mp hr, Ne.symm hne))
      by rw [decide_eq_false hr, decide_eq_true hp]; rfl)

/-- A function invariant under the fold differs from any function that the fold flips
at some
    point. -/
theorem wall_on_the_chart (f d : Pt → Bool) (z : Pt) (he : ∀ w, f (fold w) = f w)
    (ho : d (fold z) ≠ d z) : f ≠ d := by
  intro h; subst h; exact ho (he z)

/-- No function of the registered point equals the side bit at an off-line point. -/
theorem record_never_reads_the_side (g : Pt → Bool) (z : Pt) (h : ¬ onLine z) :
    (fun w => g (reg w)) ≠ side :=
  wall_on_the_chart (fun w => g (reg w)) side z (fun _ => rfl)
    (by rw [side_odd_off_line z h]; cases side z <;> decide)

/-- Given the side bit at an off-line point, any function flipped by the fold at that
point is
    fixed on the orbit by one calibration bit, which exists and is unique. -/
theorem colocation_is_a_calibration (d : Pt → Bool) (z : Pt) (h : ¬ onLine z)
    (hd : d (fold z) = !d z) :
    ∃ c : Bool, (d z = xor (side z) c ∧ d (fold z) = xor (side (fold z)) c) ∧
      ∀ c', (d z = xor (side z) c' ∧ d (fold z) = xor (side (fold z)) c') → c' = c
      := by
  have hs := side_odd_off_line z h
  refine (xor (d z) (side z),
    (by cases side z <;> cases d z <;> rfl, by rw [hs, hd]; cases side z <;> cases d
    z <;> rfl), ?_)
  intro c' hc; obtain (h1, -) := hc
  generalize hsx : side z = sv at h1; generalize hdx : d z = dv at h1
  cases sv <;> cases dv <;> cases c' <;> first | rfl | exact absurd h1 (by decide)

/-- Both calibration values are realized off the line, by the side bit and by its
complement. -/
theorem calibration_realized_both_ways (z : Pt) (h : ¬ onLine z) :
    (side (fold z) = !side z ∧ side z = xor (side z) false) ∧
    ((!side (fold z)) = !(!side z) ∧ (!side z) = xor (side z) true) :=
  ⟨(side_odd_off_line z h, by cases side z <;> rfl),
   (by rw [side_odd_off_line z h], by cases side z <;> rfl)⟩

/-- A proposition implied by its own negation. -/
def SelfVerifyingP (P : Prop) : Prop := ¬P → P

/-- The hypothesis on a world implies its self-verification there. -/
theorem value_is_recursion (Z : World) (h : RH Z) : SelfVerifyingP (RH Z) := fun _ =>
h
theorem recursion_is_value (Z : World) (h : SelfVerifyingP (RH Z)) : ¬¬ RH Z := fun n
=> n (h n)

/-- Self-verification of the hypothesis holds on W1 and fails on W2f. -/
theorem recursion_on_the_line : SelfVerifyingP (RH W1) := fun _ => W1_rh
theorem recursion_fails_on_the_twin : ¬ SelfVerifyingP (RH W2f) := fun h =>
W2f_not_rh (h W2f_not_rh)

/-- Self-verification of 0 < 1. -/
theorem root_recursion : SelfVerifyingP ((0 : Int) < 1) := fun _ => by decide

/-- Least erasure on a world implies self-verification of the hypothesis there, and
conversely up
    to double negation. -/
theorem least_erasure_is_the_recursion (Z : World) :
    (LeastErasure Z → SelfVerifyingP (RH Z)) ∧ (SelfVerifyingP (RH Z) → ¬¬
      LeastErasure Z) :=
  ⟨fun h => value_is_recursion Z ((least_erasure_is_the_value Z).mp h),
   fun h n => recursion_is_value Z h (fun r => n ((least_erasure_is_the_value Z).mpr
     r))⟩

/-- Section XVI, whole. -/
theorem the_mirror_at_minus_one :
    (∀ z, oddPart (fold z) = (-1) * oddPart z ∧ (fold z).t = z.t) ∧
    (∀ z, oddPart (reg z) = 0 ∧ (reg z).t = z.t ∧ reg (reg z) = reg z) ∧
    (∀ Z : World, RH Z ↔ ∀ z, Z z → oddPart z = 0) ∧
    (∀ (g : Pt → Bool) (z : Pt), ¬ onLine z → (fun w => g (reg w)) ≠ side) ∧
    (∀ (d : Pt → Bool) (z : Pt), ¬ onLine z → d (fold z) = !d z →
      ∃ c : Bool, (d z = xor (side z) c ∧ d (fold z) = xor (side (fold z)) c) ∧
        ∀ c', (d z = xor (side z) c' ∧ d (fold z) = xor (side (fold z)) c') → c' =
        c) ∧
    (SelfVerifyingP (RH W1) ∧ ¬ SelfVerifyingP (RH W2f) ∧ SelfVerifyingP ((0 : Int) <
    1)) ∧
    (∀ Z : World, (LeastErasure Z → SelfVerifyingP (RH Z)) ∧ (SelfVerifyingP (RH Z)
    → ¬¬ LeastErasure Z)) :=
  ⟨fun z => (residence_orientation_reversing z, fold_keeps_even z),
   fun z => (reg_kills_odd z, reg_keeps_even z, reg_idempotent z),
   rh_iff_even_eigenspace, record_never_reads_the_side, colocation_is_a_calibration,
   ⟨recursion_on_the_line, recursion_fails_on_the_twin, root_recursion⟩,
   least_erasure_is_the_recursion⟩

/-! ## XVII · Admissible coalitions, the certified height, the heat flow, the
Liouville arrow, five readings, the reader index -/

/-! ### XVII.a · Admissible coalitions -/

/-- A premise is admissible when it is keyless or a reading of the record. -/
def Admissible (A : World → Prop) : Prop := Keyless A ∨ RespectsRecord A

/-- An admissible premise that holds on W1 holds on W2f. -/
theorem admissible_transfers (A : World → Prop) (h : Admissible A) (h1 : A W1) : A
W2f := by
  rcases h with k | r
  · exact k W2f
  · exact (r W1 W2f same_record_f).mp h1

/-- Three admissible premises true on W1 are true on W2f, so their conjunction forces
nothing. -/
theorem no_admissible_triad_forces (A B C : World → Prop)
    (hA : Admissible A) (hB : Admissible B) (hC : Admissible C) (h : A W1 ∧ B W1 ∧ C
      W1) :
    ¬ Forces (fun Z => A Z ∧ B Z ∧ C Z) :=
  fun f => W2f_not_rh (f W2f W2f_closed
    ⟨admissible_transfers A hA h.1, admissible_transfers B hB h.2.1,
     admissible_transfers C hC h.2.2⟩)

/-- A list of admissible premises true on W1 forces nothing. -/
theorem no_admissible_coalition_forces (L : List (World → Prop))
    (hL : ∀ A ∈ L, Admissible A) (h1 : ∀ A ∈ L, A W1) :
    ¬ Forces (fun Z => ∀ A ∈ L, A Z) :=
  fun f => W2f_not_rh (f W2f W2f_closed (fun A hA => admissible_transfers A (hL A hA)
    (h1 A hA)))

/-- Least erasure is not admissible: it fails on W2f and is not a reading of the
record. -/
theorem spend_is_not_admissible : ¬ Admissible LeastErasure := by
  intro h
  rcases h with k | r
  · exact W2f_not_rh ((least_erasure_is_the_value W2f).mp (k W2f))
  · exact least_erasure_reads_past_the_record_free r

/-- Three predicates on a point: the freedom axis, always true; the seat axis, the
point is fixed
    by the fold; the collapse axis, the displacement equals its own negative. -/
def freedomAxis (_ : Pt) : Prop := True
def ramAxis (z : Pt) : Prop := fold z = z
def collapseAxis (z : Pt) : Prop := oddPart z = - oddPart z

/-- All three axes hold at a point exactly when it lies on the line. -/
theorem three_axis_lock (z : Pt) : (freedomAxis z ∧ ramAxis z ∧ collapseAxis z) ↔
onLine z := by
  constructor
  · intro ⟨_, h, _⟩
    exact (fold_fixed_iff z).mp h
  · intro h
    refine (trivial, (fold_fixed_iff z).mpr h, ?_)
    have e : oddPart z = 0 := (onLine_iff_odd_zero z).mp h
    unfold collapseAxis
    omega

/-- The freedom axis holds at an off-line point. -/
theorem freedom_alone_open : freedomAxis (0, 14) ∧ ¬ onLine (0, 14) :=
  ⟨trivial, by decide⟩

/-! ### XVII.b · The certified height -/

/-- The zeros certified on the line up to height T. -/
def LineBelow (T : Nat) : World := fun z => z.x = 1 ∧ z.t ≤ T
/-- The same zeros, with one off-line pair just above the certified height. -/
def TwinAbove (T : Nat) : World := fun z => (z.x = 1 ∧ z.t ≤ T) ∨ (z = (0, T+1) ∨ z =
(2, T+1))

/-- For every T the world certified to T lies on the line, and a fold-closed world
agrees with it
    at every height up to T and carries an off-line pair above T. The certificate of
    Platt and
    Trudgian (2021) to height $3 \cdot 10^{12}$ is such a T. -/
theorem certified_height_never_forces (T : Nat) :
    RH (LineBelow T) ∧ FoldClosed (TwinAbove T) ∧ ¬ RH (TwinAbove T) ∧
    ∀ z, z.t ≤ T → (TwinAbove T z ↔ LineBelow T z) := by
  refine (fun z hz => hz.1, ?_, ?_, ?_)
  · intro z hz
    rcases hz with (h1, h2) | h | h
    · exact Or.inl (show 2 - z.x = 1 by omega, h2)
    · subst h
      exact Or.inr (Or.inr rfl)
    · subst h
      exact Or.inr (Or.inl rfl)
  · intro h
    have h0 : (0 : Int) = 1 := h (0, T+1) (Or.inr (Or.inl rfl))
    exact absurd h0 (by decide)
  · intro z hz
    constructor
    · intro h
      rcases h with h | h | h
      · exact h
      · subst h
        have : T + 1 ≤ T := hz
        omega
      · subst h
        have : T + 1 ≤ T := hz
        omega
    · intro h
      exact Or.inl h

/-- Below T the certified world and its twin have the same record. -/
theorem certified_worlds_share_the_record_below (T : Nat) (r : Pt) (hr : r.t ≤ T) :
    recordOf (LineBelow T) r ↔ recordOf (TwinAbove T) r := by
  constructor
  · intro (s, hs, hsr)
    exact (s, Or.inl hs, hsr)
  · intro (s, hs, hsr)
    rcases hs with h | h | h
    · exact (s, h, hsr)
    · subst h
      have e : (T + 1 : Nat) = r.t := congrArg Pt.t hsr
```

```
      omega
    · subst h
      have e : (T + 1 : Nat) = r.t := congrArg Pt.t hsr
      omega

/-! ### XVII.c · The heat flow on polynomials: under ∂ₜH = −∂ₓ²H the constant term of z² + bz + c moves to c − 2t and the discriminant rises by 8t -/

namespace HeatFlow

theorem sq_nonneg (x : Int) : 0 ≤ x * x := by
  cases Int.le_total 0 x with
  | inl h => exact Int.mul_nonneg h h
  | inr h =>
    have hn : 0 ≤ -x := by omega
    have := Int.mul_nonneg hn hn
    rw [Int.neg_mul_neg] at this
    exact this

theorem cube_diff (u k : Int) :
    u*u*u - (u-k)*(u-k)*(u-k) = 3*(u*u*k) - 3*(u*k*k) + k*k*k := by
  simp only [Int.sub_mul, Int.mul_sub, Int.mul_assoc]
  simp only [Int.mul_comm k u, Int.mul_left_comm k u]
  omega

/-- Discriminant of z² + bz + c. -/
def disc (b c : Int) : Int := b*b - 4*c
/-- The flow on the constant term: exp(−tD²)(z² + bz + c) = z² + bz + (c − 2t). -/
def flowC (c t : Int) : Int := c - 2*t
/-- Real-rooted at time t: the flowed discriminant is nonnegative. -/
def RR (b c t : Int) : Prop := 0 ≤ disc b (flowC c t)
instance (b c t : Int) : Decidable (RR b c t) := inferInstanceAs (Decidable (0 ≤ disc b (flowC c t)))

/-- disc(t) = disc(0) + 8t. -/
theorem disc_flow (b c t : Int) : disc b (flowC c t) = disc b c + 8*t := by
  unfold disc flowC; omega

/-- Real-rootedness is preserved forward in time. -/
theorem forward_preserves (b c s t : Int) (hst : s ≤ t) (h : RR b c s) : RR b c t := by
  unfold RR at *; rw [disc_flow] at *; omega

/-- Every quadratic is real-rooted after some finite time. -/
theorem erasure_finite (b c : Int) : ∃ t, 0 ≤ t ∧ RR b c t :=
  ((disc b c).natAbs, by omega, by unfold RR; rw [disc_flow]; omega)

/-- The least erasure time, Λ of the quadratic: 0 if already real-rooted, else ⌈−disc/8⌉. -/
def lam (b c : Int) : Int := if 0 ≤ disc b c then 0 else (7 - disc b c) / 8

theorem lam_nonneg (b c : Int) : 0 ≤ lam b c := by
  unfold lam; split <;> omega

/-- At time Λ the quadratic is real-rooted. -/
theorem real_at_lam (b c : Int) : RR b c (lam b c) := by
  unfold RR lam; rw [disc_flow]; split <;> omega

/-- If Λ > 0, the quadratic is not real-rooted at time Λ − 1. -/
theorem lam_least (b c : Int) (h : 0 < lam b c) : ¬ RR b c (lam b c - 1) := by
  unfold RR; rw [disc_flow]; unfold lam at *; split at * <;> omega

/-- Λ = 0 exactly when the quadratic is real-rooted at time 0. -/
theorem lam_zero_iff_real (b c : Int) : lam b c = 0 ↔ RR b c 0 := by
  unfold RR lam; rw [disc_flow]; split <;> omega

/-- For z² + c the squared imaginary part of the roots is max(c − 2t, 0): de Bruijn's bound holds
    with equality. -/
def imSq (c t : Int) : Int := max (flowC c t) 0
theorem de_bruijn_tight (c t : Int) (ht : 0 ≤ t) : imSq c t = max (imSq c 0 - 2*t) 0 := by
  unfold imSq flowC; omega

/-- For z² + 2k the roots are ±√(2t − 2k): at t = k they meet at 0. -/
def rootSq (c t : Int) : Int := 2*t - c
theorem collision (k t : Int) :
    rootSq (2*k) k = 0 ∧ (t < k → rootSq (2*k) t < 0) ∧ (k < t → 0 < rootSq (2*k) t) ∧
    rootSq (2*k) (t+1) = rootSq (2*k) t + 2 := by
  unfold rootSq; omega

/-- Discriminant of z³ + pz + q. -/
def disc3 (p q : Int) : Int := -4*(p*p*p) - 27*(q*q)
/-- The flow on the linear coefficient: exp(−tD²)(z³ + pz + q) = z³ + (p − 6t)z + q. -/
def flowP (p t : Int) : Int := p - 6*t

/-- One time step raises the cubic discriminant by 72((u − 3)² + 3), u the current linear
    coefficient. -/
theorem disc3_step (p q t : Int) :
    disc3 (flowP p (t+1)) q - disc3 (flowP p t) q = 72*((p - 6*t - 3)*(p - 6*t - 3) + 3) := by
  have key : ∀ u k : Int, u*u*u - (u-k)*(u-k)*(u-k) = 3*(u*u*k) - 3*(u*k*k) + k*k*k := by
    intro u k
    simp only [Int.sub_mul, Int.mul_sub, Int.mul_assoc]
    simp only [Int.mul_comm k u, Int.mul_left_comm k u]
    omega
  have h := key (p - 6*t) 6
  have e0 : flowP p (t+1) = (p - 6*t) - 6 := by unfold flowP; omega
  have e1 : (p - 6*t)*(p - 6*t)*6 = 6*((p - 6*t)*(p - 6*t)) := Int.mul_comm _ _
  have e2 : (p - 6*t)*6*6 = 36*(p - 6*t) := by rw [Int.mul_assoc, Int.mul_comm]; rfl
  have e3 : (p - 6*t - 3)*(p - 6*t - 3) = (p - 6*t)*(p - 6*t) - 6*(p - 6*t) + 9 := by
    generalize p - 6*t = u
    simp only [Int.sub_mul, Int.mul_sub]; rw [Int.mul_comm 3 u]; omega
  have e4 : (6:Int)*6 = 216 := by decide
  rw [e1, e2, e4] at h
  unfold disc3; rw [e0, e3]
  have e5 : flowP p t = p - 6*t := rfl
  rw [e5]
  omega

/-- The cubic discriminant strictly increases with time. -/
theorem disc3_strict (p q t : Int) : disc3 (flowP p t) q < disc3 (flowP p (t+1)) q := by
  have h := disc3_step p q t
  have := sq_nonneg (p - 6*t - 3)
  omega

/-- Over any number of steps the cubic discriminant never falls. -/
theorem disc3_monotone_rec (p q : Int) : ∀ n : Nat, disc3 (flowP p 0) q ≤ disc3 (flowP p n) q := by
  intro n
  induction n with
  | zero => exact Int.le_refl _
  | succ n ih =>
    have st := disc3_strict p q (n : Int)
    have e : ((n + 1 : Nat) : Int) = (n : Int) + 1 := by omega
    rw [e]; omega

/-- disc3_monotone_rec, restated. -/
theorem disc3_monotone (p q : Int) (n : Nat) : disc3 (flowP p 0) q ≤ disc3 (flowP p n) q :=
  disc3_monotone_rec p q n

theorem cubic_forward_preserves (p q : Int) (h : 0 ≤ disc3 (flowP p 0) q) (n : Nat) :
    0 ≤ disc3 (flowP p n) q := Int.le_trans h (disc3_monotone_rec p q n)

/-- The flow is injective on the constant term: the polynomial at time t determines the polynomial
    at time 0. -/
theorem flow_injective (c c' t : Int) (h : flowC c t = flowC c' t) : c = c' := by
  unfold flowC at h; omega

/-- At every positive time there are two quadratics real-rooted at t, one real-rooted at 0 and one
    not. -/
theorem certificate_two_worlds (t : Int) (ht : 0 < t) :
    RR 0 0 t ∧ RR 0 t t ∧ RR 0 0 0 ∧ ¬ RR 0 t 0 := by
  unfold RR; simp only [disc_flow]; unfold disc; omega

/-- No function of real-rootedness at time t returns real-rootedness at time 0 on every quadratic. -/
theorem certificate_decides_nothing (t : Int) (ht : 0 < t) :
    ¬ ∃ g : Bool → Bool, ∀ b c : Int, g (decide (RR b c t)) = decide (RR b c 0) := by
  intro (g, hg)
  have (h1, h2, h3, h4) := certificate_two_worlds t ht
  have a := hg 0 0
  have b := hg 0 t
  rw [decide_eq_true h1, decide_eq_true h3] at a
  rw [decide_eq_true h2, decide_eq_false h4] at b
  rw [a] at b
  exact Bool.noConfusion b

/-- For every t > 0 some quadratic is real-rooted from t on and not at 0, with Λ > 0. -/
theorem certification_never_forces (t : Int) (ht : 0 < t) :
    ∃ c : Int, (∀ s, t ≤ s → RR 0 c s) ∧ ¬ RR 0 c 0 ∧ 0 < lam 0 c :=
  (t, fun s hs => forward_preserves 0 t t s hs (certificate_two_worlds t ht).2.1,
   (certificate_two_worlds t ht).2.2.2,
   by unfold lam disc; split <;> omega)

/-- A double root is real-rooted at 0 with Λ = 0, and not real-rooted at any earlier time. -/
theorem zero_slack (a : Int) :
    RR (2*a) (a*a) 0 ∧ lam (2*a) (a*a) = 0 ∧ ∀ s, 0 < s → ¬ RR (2*a) (a*a) (-s) := by
  have hd : disc (2*a) (a*a) = 0 := by
    unfold disc; rw [Int.mul_assoc, Int.mul_left_comm a 2 a]; omega
  refine (?_, ?_, ?_)
  · unfold RR; rw [disc_flow, hd]; omega
  · unfold lam; rw [hd]; simp
  · intro s hs; unfold RR; rw [disc_flow, hd]; omega

/-- A quadratic real-rooted at time 1 may or may not be real-rooted at time 0: z² − 2 is, z² + 2 is
    not. -/
theorem backward_not_forced : RR 0 (-2) 1 ∧ RR 0 2 1 ∧ RR 0 (-2) 0 ∧ ¬ RR 0 2 0 := by
  unfold RR; simp only [disc_flow]; unfold disc; decide

/-- The largest Λ over a family of quadratics. -/
def famLam : List (Int × Int) → Int
  | [] => 0
  | (b, c) :: r => max (lam b c) (famLam r)

theorem famLam_nonneg_rec : ∀ F : List (Int × Int), 0 ≤ famLam F := by
  intro F
  induction F with
  | nil => exact Int.le_refl 0
  | cons m r ih =>
    obtain (b, c) := m
    unfold famLam; omega

theorem family_least_erasure_rec :
    ∀ F : List (Int × Int), famLam F = 0 ↔ ∀ m ∈ F, RR m.1 m.2 0 := by
  intro F
  induction F with
  | nil => simp [famLam]
  | cons m r ih =>
    obtain (b, c) := m
    have hn := famLam_nonneg_rec r
    have hl := lam_nonneg b c
    have hz := lam_zero_iff_real b c
    constructor
    · intro h m hm
      unfold famLam at h
      cases hm with
      | head => exact hz.mp (by omega)
      | tail _ hm' => exact ih.mp (by omega) m hm'
    · intro h
      have h1 : lam b c = 0 := hz.mpr (h (b, c) (List.Mem.head r))
      have h2 : famLam r = 0 := ih.mpr (fun m hm => h m (List.Mem.tail _ hm))
      unfold famLam; omega

/-- The family's Λ is 0 exactly when every member is real-rooted at time 0. -/
theorem family_least_erasure (F : List (Int × Int)) : famLam F = 0 ↔ ∀ m ∈ F, RR m.1 m.2 0 :=
  family_least_erasure_rec F

end HeatFlow

/-- Real-rootedness at time 0 is exactly Λ ≤ 0, since 0 ≤ Λ. -/
theorem heat_bit_is_one_inequality (b c : Int) : HeatFlow.RR b c 0 ↔ HeatFlow.lam b c ≤ 0 := by
```

```
  have h1 := HeatFlow.lam_nonneg b c
  have h2 := HeatFlow.lam_zero_iff_real b c
  constructor
  · intro h
    have := h2.mpr h
    omega
  · intro h
    exact h2.mp (by omega)

/-- Over a family, every member is real-rooted at time 0 exactly when the family's Λ ≤ 0. -/
theorem family_bit_is_one_inequality (F : List (Int × Int)) :
    (∀ m ∈ F, HeatFlow.RR m.1 m.2 0) ↔ HeatFlow.famLam F ≤ 0 := by
  have h1 := HeatFlow.famLam_nonneg_rec F
  have h2 := HeatFlow.family_least_erasure F
  constructor
  · intro h
    have := h2.mpr h
    omega
  · intro h
    exact h2.mp (by omega)

/-- The de Bruijn–Newman structure and the quadratic model satisfy the same equivalences, the model
    with its lower bound proved. -/
theorem heat_model_reads_as_the_carrier {V : Type} [LE V] (D : DBN V) (b c : Int) :
    (RH D.zeros ↔ D.lam ≤ D.zero) ∧ (HeatFlow.RR b c 0 ↔ HeatFlow.lam b c ≤ 0) ∧
    (0 ≤ HeatFlow.lam b c) :=
  ⟨rh_iff_the_sign D, heat_bit_is_one_inequality b c, HeatFlow.lam_nonneg b c⟩

/-! ### XVII.d · The Liouville arrow λ(n) = (−1)^Ω(n), computed -/

namespace Liouville

/-- Ω, the number of prime factors with multiplicity, by trial division. -/
def omegaF : Nat → Nat → Nat → Nat
  | 0, _, _ => 0
  | fuel + 1, n, d =>
    if n ≤ 1 then 0
    else if d * d > n then 1
    else if n % d = 0 then 1 + omegaF fuel (n / d) d
    else omegaF fuel n (d + 1)
def bigOmega (n : Nat) : Nat := omegaF (2 * n + 2) n 2
/-- The arrow λ(n) = (−1)^Ω(n). -/
def lam (n : Nat) : Int := if bigOmega n % 2 = 0 then 1 else -1

/-- λ(ab) = λ(a)λ(b) on 1..40 × 1..40. -/
theorem lam_mult : ((List.range 40).all fun a => (List.range 40).all fun b =>
      lam ((a+1)*(b+1)) == lam (a+1) * lam (b+1)) = true := by decide

/-- λ(p) = −1 for every prime p below 100. -/
theorem lam_flips_at_primes :
    ([2,3,5,7,11,13,17,19,23,29,31,37,41,43,47,53,59,61,67,71,73,79,83,89,97].all fun
      p => lam p == -1) = true := by
  decide

def L : Nat → Int
  | 0 => 0
  | n + 1 => L n + lam (n + 1)

/-- L(x) = Σ_{n ≤ x} λ(n) ≤ 0 for 2 ≤ x ≤ 200. The inequality fails at x = 906,150,257 (Haselgrove
    1958; Tanaka 1980). -/
theorem polya_holds_to_200 : ((List.range 199).all fun k => decide (L (k + 2) ≤ 0)) = true := by decide

end Liouville

/-- λ is the sign arrow of the computed count Ω. -/
theorem liouville_is_the_sign_arrow (n : Nat) : Liouville.lam n = signArrow (Liouville.bigOmega n) := rfl

/-- A zero set with the faithfulness of λ: the hypothesis holds exactly when L(x) = O(x^{1/2+ε})
    for every ε > 0. Carried as a hypothesis (Landau 1899). -/
structure LiouvilleFace where
  zeros : World
  faithful : Prop
  faithful_iff : RH zeros ↔ faithful

theorem rh_from_faithful (F : LiouvilleFace) (h : F.faithful) : RH F.zeros := F.faithful_iff.mpr h
theorem faithful_is_the_bit (F : LiouvilleFace) : F.faithful ↔ RH F.zeros := F.faithful_iff.symm

/-- On one zero set, Weil positivity, Λ ≤ 0, the non-negativity of the Li stream and the
    faithfulness of λ are equivalent, each cited equivalence entering as a field. -/
theorem the_posit_in_every_coordinate {V : Type} [LE V] (P : PrimeAct) (D : DBN V)
    (Li : LiStream)
    (F : LiouvilleFace) (hD : D.zeros = P.E.zeros) (hL : Li.zeros = P.E.zeros)
    (hF : F.zeros = P.E.zeros) :
    (WeilPositive P.E ↔ D.lam ≤ D.zero) ∧ (WeilPositive P.E ↔ ∀ n, 1 ≤ n → Li.nonneg n) ∧
    (WeilPositive P.E ↔ F.faithful) := by
  have hW : WeilPositive P.E ↔ RH P.E.zeros := spend_is_the_line P.E
  refine ⟨?_, ?_, ?_⟩
  · rw [hW, ← hD]
    exact rh_iff_the_sign D
  · rw [hW, ← hL]
    exact (li_is_the_bit_stream Li).symm
  · rw [hW, ← hF]
    exact F.faithful_iff

/-! ### XVII.e · Five readings, one proposition -/

/-- Lossless registration: every zero is fixed by registration. -/
def Lossless (Z : World) : Prop := ∀ z, Z z → reg z = z
/-- Every zero has displacement 0. -/
def DepthZero (Z : World) : Prop := ∀ z, Z z → oddPart z = 0
/-- The Li mode of a zero, in the chart's own scale: |ρ − 1|² and |ρ|² doubled. -/
def N1 (z : Pt) : Int := (z.x - 2)*(z.x - 2) + 4*((z.t : Int)*(z.t : Int))
def N0 (z : Pt) : Int := z.x*z.x + 4*((z.t : Int)*(z.t : Int))
/-- Stability: no Li mode grows. -/
def Stable (Z : World) : Prop := ∀ z, Z z → N1 z ≤ N0 z

theorem modes (z : Pt) : N1 z - N0 z = 4 - 4 * z.x := by
  simp only [N1, N0, Int.sub_mul, Int.mul_sub]
  omega

/-- Registration fixes a zero exactly when the zero lies on the line. -/
theorem lossless_iff_rh (Z : World) : Lossless Z ↔ RH Z := by
  constructor
  · intro h z hz
    have e := congrArg Pt.x (h z hz)
    exact e.symm
  · intro h z hz
    exact reg_fixes_line z (h z hz)

/-- On a fold-closed world, stability of every Li mode is the line: a mode below the line grows,
    and its fold-partner stands above. -/
theorem stable_iff_rh (Z : World) (hZ : FoldClosed Z) : Stable Z ↔ RH Z := by
  constructor
  · intro h z hz
    have a := h z hz
    have b := h (fold z) (hZ z hz)
    have ea := modes z
    have eb := modes (fold z)
    have ex : (fold z).x = 2 - z.x := rfl
    rw [ex] at eb
    show z.x = 1
    omega
  · intro h z hz
    have e : z.x = 1 := h z hz
    have := modes z
    omega

/-- On every fold-closed world the line, lossless registration, displacement zero, no left zero,
    the stability of every Li mode and least erasure are equivalent. -/
theorem five_readings_agree (Z : World) (hZ : FoldClosed Z) :
    (RH Z ↔ Lossless Z) ∧ (RH Z ↔ DepthZero Z) ∧ (RH Z ↔ ¬ Left Z) ∧
    (RH Z ↔ Stable Z) ∧ (RH Z ↔ LeastErasure Z) :=
  ⟨⟨(lossless_iff_rh Z).symm, rh_iff_even_eigenspace Z, rh_iff_no_left Z hZ,
   (stable_iff_rh Z hZ).symm⟩, (least_erasure_is_the_value Z).symm⟩

/-- And no record-respecting reading returns any of the five, since each is the hypothesis. -/
theorem no_record_reading_returns_any_face (g : World → Prop) (hg : RespectsRecord g) :
    ¬ (∀ Z, FoldClosed Z → (g Z ↔ Lossless Z)) ∧ ¬ (∀ Z, FoldClosed Z → (g Z ↔ Stable Z)) := by
  constructor
  · intro h
    exact record_decides_nothing_free g hg (fun Z hZ => (h Z hZ).trans (lossless_iff_rh Z))
  · intro h
    exact record_decides_nothing_free g hg (fun Z hZ => (h Z hZ).trans (stable_iff_rh Z hZ))

/-! ### XVII.f · The supply has no reader index -/

/-- A proposition indexed by a type of readers, constant. -/
def Requirement (Reader : Type) (V : Prop) : Reader → Prop := fun _ => V

/-- Every reader faces the same proposition. -/
theorem same_for_every_reader {Reader : Type} (V : Prop) (a b : Reader) :
    Requirement Reader V a ↔ Requirement Reader V b := Iff.rfl

/-- A requirement that differs between two readers is not the fixed value. -/
theorem no_private_bit {Reader : Type} (V : Prop) (R : Reader → Prop) (hR : ∀ r, R r ↔ V)
    (a b : Reader) : R a ↔ R b := (hR a).trans (hR b).symm

/-- A reader-indexed requirement equal to Weil positivity for every reader is the same for all
    readers. -/
theorem spend_has_no_reader {Reader : Type} (P : PrimeAct) (R : Reader → Prop)
    (hR : ∀ r, R r ↔ WeilPositive P.E) (a b : Reader) : R a ↔ R b :=
  no_private_bit (WeilPositive P.E) R hR a b

/-! ### XVII.g · Section XVII, whole -/

/-- Section XVII, whole. -/
theorem the_harvest :
    (∀ (L : List (World → Prop)), (∀ A ∈ L, Admissible A) → (∀ A ∈ L, A W1) →
      ¬ Forces (fun Z => ∀ A ∈ L, A Z)) ∧
    ¬ Admissible LeastErasure ∧
    (∀ T : Nat, RH (LineBelow T) ∧ FoldClosed (TwinAbove T) ∧ ¬ RH (TwinAbove T)) ∧
    (∀ b c : Int, (HeatFlow.RR b c 0 ↔ HeatFlow.lam b c ≤ 0) ∧ 0 ≤ HeatFlow.lam b c) ∧
    (∀ t : Int, 0 < t → ¬ ∃ g : Bool → Bool, ∀ b c : Int,
      g (decide (HeatFlow.RR b c t)) = decide (HeatFlow.RR b c 0)) ∧
    (∀ n : Nat, Liouville.lam n = signArrow (Liouville.bigOmega n)) ∧
    (∀ Z : World, FoldClosed Z →
      (RH Z ↔ Lossless Z) ∧ (RH Z ↔ DepthZero Z) ∧ (RH Z ↔ ¬ Left Z) ∧
      (RH Z ↔ Stable Z) ∧ (RH Z ↔ LeastErasure Z)) ∧
    (∀ {Reader : Type} (P : PrimeAct) (R : Reader → Prop),
      (∀ r, R r ↔ WeilPositive P.E) → ∀ a b : Reader, R a ↔ R b) :=
  ⟨no_admissible_coalition_forces, spend_is_not_admissible,
   fun T => ⟨certified_height_never_forces T).1, (certified_height_never_forces T).2.1,
    (certified_height_never_forces T).2.2.1⟩,
   fun b c => ⟨heat_bit_is_one_inequality b c, HeatFlow.lam_nonneg b c⟩,
   HeatFlow.certificate_decides_nothing, liouville_is_the_sign_arrow,
   five_readings_agree,
   fun P R hR a b => spend_has_no_reader P R hR a b⟩

/-! ## XVIII · A theory placed on three strata; the root; the two can'ts; the round trip; the ladder blocked -/

/-! ### XVIII.a · Placement: computation, provability, truth -/

/-- A theory: its sentences, what it proves, what finite computation settles, what holds in its
    intended model. -/
structure Theory where
  Sent  : Type
  Prov  : Sent → Prop
  Comp  : Sent → Prop
  True_ : Sent → Prop

/-- Σ₁-completeness, abstractly: what finite computation settles, the theory proves. -/
def RungOnLadder (T : Theory) : Prop := ∀ s, T.Comp s → T.Prov s
```

```
/-- Soundness: what the theory proves holds in its intended model. -/
def Sound (T : Theory) : Prop := ∀ s, T.Prov s → T.True_ s

/-- Under Σ₁-completeness and soundness: what computation settles the theory proves, what the
    theory proves holds, and what computation settles holds. -/
theorem placement (T : Theory) (hR : RungOnLadder T) (hS : Sound T) :
    (∀ s, T.Comp s → T.Prov s) ∧ (∀ s, T.Prov s → T.True_ s) ∧ (∀ s, T.Comp s → T.True_ s) :=
  ⟨hR, hS, fun s h => hS s (hR s h)⟩

/-- An unsound theory: it proves everything and its model refutes half of it. -/
def unsound : Theory := ⟨Bool, fun _ => True, fun _ => False, fun b => b = true⟩

/-- The unsound theory is Σ₁-complete and not sound. -/
theorem soundness_is_load_bearing : RungOnLadder unsound ∧ ¬ Sound unsound := by
  refine ⟨fun _ h => h.elim, fun h => ?_⟩
  have := h false trivial
  cases this

/-- A sound incomplete theory: true on both sentences, proving one. -/
def incomplete : Theory := ⟨Bool, fun b => b = true, fun _ => False, fun _ => True⟩

/-- A sound theory can leave a truth unproved. -/
theorem ground_exceeds_ladder :
    Sound incomplete ∧ incomplete.True_ false ∧ ¬ incomplete.Prov false :=
  ⟨fun _ _ => trivial, trivial, fun h => Bool.noConfusion h⟩

/-- Independent axioms are separate bits: every combination of two values is realized. -/
theorem independent_axioms_are_separate_bits :
    ∀ a b : Bool, ∃ w : Bool × Bool, w.1 = a ∧ w.2 = b :=
  fun a b => ⟨(a, b), rfl, rfl⟩

/-! ### XVIII.b · The root crosses every keyless sentence and no keyed one -/

/-- Over any type of worlds: a sentence is keyless when every world has it, keyed when some world
    lacks it. -/
def KeylessOn {W : Type} (P : W → Prop) : Prop := ∀ w, P w
def KeyedOn {W : Type} (P : W → Prop) : Prop := ∃ w, ¬ P w

/-- The root proposition, 0 < 1. -/
def RootAct : Prop := (0 : Int) < 1
theorem root_act : RootAct := show (0 : Int) < 1 by decide

/-- The root is keyless over every type of worlds. -/
theorem root_is_keyless {W : Type} : KeylessOn (fun _ : W => RootAct) := fun _ => root_act

/-- The root implies every keyless sentence on every world. -/
theorem keyless_crosses {W : Type} (P : W → Prop) (hP : KeylessOn P) : ∀ w, RootAct → P w :=
  fun w _ => hP w

/-- The root does not imply a keyed sentence on every world. -/
theorem root_decides_no_keyed {W : Type} (P : W → Prop) (hK : KeyedOn P) :
    ¬ ∀ w, RootAct → P w :=
  fun h => hK.elim (fun w hw => hw (h w root_act))

/-- Choice over ZF as a keyed sentence: two worlds, one each way (Gödel 1938; Cohen 1963). -/
def choiceHolds : Bool → Prop := fun w => w = true
theorem choice_is_keyed : KeyedOn choiceHolds := ⟨false, fun h => Bool.noConfusion h⟩
theorem root_does_not_cross_choice :
    (∀ _w : Bool, RootAct) ∧ choiceHolds true ∧ ¬ choiceHolds false :=
  ⟨fun _ => root_act, rfl, fun h => Bool.noConfusion h⟩

/-- The hypothesis is keyed over the worlds of the chart. -/
theorem line_is_keyed_over_worlds : KeyedOn RH ∧ ∃ Z, FoldClosed Z ∧ RH Z :=
  ⟨⟨W2f, W2f_not_rh⟩, ⟨W1, W1_closed, W1_rh⟩⟩

/-- The root does not imply the hypothesis on every world. -/
theorem root_does_not_cross_the_line : ¬ ∀ Z : World, RootAct → RH Z :=
  root_decides_no_keyed RH line_is_keyed_over_worlds.1

/-! ### XVIII.c · The two can'ts of a foundation are not mirror images -/

/-- A hypothesis with a provability predicate, Σ₁-completeness on the denial (a false Π⁰₁
    hypothesis has a finite witness, which the theory proves: Davis, Matiyasevich and Robinson
    1976; Lagarias 2002) and soundness on the denial, both carried as hypotheses. -/
structure Setting where
  hyp       : Prop
  Prov      : Prop → Prop
  sigma1    : ¬ hyp → Prov (¬ hyp)
  sound_neg : Prov (¬ hyp) → ¬ hyp

/-- On the chart one off-line zero refutes the hypothesis. -/
theorem refutation_is_one_point (Z : World) (z : Pt) (hz : Z z) (h : ¬ onLine z) : ¬ RH Z :=
  fun r => h (r z hz)

/-- If the theory cannot refute the hypothesis, the hypothesis holds. -/
theorem cant_refute_seals (S : Setting) (h : ¬ S.Prov (¬ S.hyp)) : S.hyp :=
  Classical.byContradiction (fun n => h (S.sigma1 n))

theorem cant_refute_seals_dec (S : Setting) [Decidable S.hyp] (h : ¬ S.Prov (¬ S.hyp)) : S.hyp :=
  Decidable.byContradiction (fun n => h (S.sigma1 n))

/-- Under soundness on the denial, the hypothesis holds exactly when the foundation cannot refute it. -/
theorem rh_iff_cant_refute (S : Setting) [Decidable S.hyp] : S.hyp ↔ ¬ S.Prov (¬ S.hyp) :=
  ⟨fun r p => S.sound_neg p r, cant_refute_seals_dec S⟩

/-- A hypothesis the theory neither proves nor refutes holds. -/
theorem independence_forces_truth (S : Setting) (_hp : ¬ S.Prov S.hyp) (hn : ¬ S.Prov (¬ S.hyp)) :
    S.hyp :=
  cant_refute_seals S hn

/-- A setting in which the hypothesis holds and is not provable. -/
def independentTrue : Setting := ⟨True, fun _ => False, fun n => absurd trivial n, fun p => p.elim⟩

theorem cant_prove_does_not_seal_false :
    independentTrue.hyp ∧ ¬ independentTrue.Prov independentTrue.hyp :=
  ⟨trivial, id⟩

/-- Cannot-refute implies the hypothesis; cannot-prove is consistent with it. -/
theorem cant_asymmetry :
    (∀ S : Setting, ¬ S.Prov (¬ S.hyp) → S.hyp) ∧ (∃ S : Setting, S.hyp ∧ ¬ S.Prov S.hyp) :=
  ⟨cant_refute_seals, ⟨independentTrue, cant_prove_does_not_seal_false⟩⟩

/-! ### XVIII.d · The round trip is the identity -/

/-- A sentence conjoined with the root. -/
def viaRoot {W : Type} (P : W → Prop) : W → Prop := fun w => RootAct ∧ P w

/-- Conjoining the root changes no sentence's value. -/
theorem round_trip_identity {W : Type} (P : W → Prop) (w : W) : viaRoot P w ↔ P w :=
  ⟨fun h => h.2, fun h => ⟨root_act, h⟩⟩

/-- An absolute sentence, the same in every world, returns unchanged. -/
theorem absolute_returns_unchanged {W : Type} (P : W → Prop) (hAbs : ∀ w v, P w ↔ P v) (w : W) :
    ∀ v, viaRoot P v ↔ P w :=
  fun v => (round_trip_identity P v).trans (hAbs v w)

/-- The trip adds presence and nothing else: it returns identically for a sentence and its denial. -/
theorem trip_adds_presence_only {W : Type} (P : W → Prop) (w : W) :
    RootAct ∧ (viaRoot P w ↔ P w) ∧ (viaRoot (fun v => ¬ P v) w ↔ ¬ P w) :=
  ⟨root_act, round_trip_identity P w, round_trip_identity (fun v => ¬ P v) w⟩

/-- For any true Q, (Q → RH Z) ↔ RH Z. -/
theorem massless_arrow (Q : Prop) (hq : Q) (Z : World) : (Q → RH Z) ↔ RH Z :=
  ⟨fun f => f hq, fun h _ => h⟩

/-- Any true premise satisfies the three properties of the root. -/
theorem any_true_premise_serves (R : Prop) (hR : R) {W : Type} (P : W → Prop) :
    ((∀ w, P w) → ∀ w, R → P w) ∧ ((∃ w, ¬ P w) → ¬ ∀ w, R → P w) ∧ (∀ w, (R ∧ P w) ↔ P w) :=
  ⟨fun hP w _ => hP w, fun h₁ h => h₁.elim (fun w hw => hw (h w hR)),
   fun _ => ⟨fun h => h.2, fun h => ⟨hR, h⟩⟩⟩

/-- Conjoined with the root, the hypothesis is itself on W1 and on W2f. -/
theorem the_line_round_trips :
    (∀ Z : World, viaRoot RH Z ↔ RH Z) ∧ viaRoot RH W1 ∧ ¬ viaRoot RH W2f :=
  ⟨fun Z => round_trip_identity RH Z, ⟨root_act, W1_rh⟩, fun h => W2f_not_rh h.2⟩

/-! ### XVIII.e · The ladder blocked, in six clauses -/

/-- Six clauses: no reading of the record decides the hypothesis; no keyless premise forces it; no
    admissible coalition holding on W1 forces it; the root alone does not give it; a setting carries
    a true hypothesis it does not prove; and the hypothesis forces the line and is entailed by every
    premise that forces it. -/
theorem ladder_blocked :
    (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)) ∧
    (∀ A : World → Prop, Keyless A → ¬ Forces A) ∧
    (∀ L : List (World → Prop), (∀ A ∈ L, Admissible A) → (∀ A ∈ L, A W1) →
      ¬ Forces (fun Z => ∀ A ∈ L, A Z)) ∧
    (¬ ∀ Z : World, RootAct → RH Z) ∧
    (∃ S : Setting, S.hyp ∧ ¬ S.Prov S.hyp) ∧
    (Forces RH ∧ ∀ A : World → Prop, Forces A → ∀ Z, FoldClosed Z → A Z → RH Z) :=
  ⟨record_decides_nothing_free, keyless_forces_nothing_free,
   no_admissible_coalition_forces,
   ⟨root_does_not_cross_the_line, ⟨independentTrue, cant_prove_does_not_seal_false⟩⟩,
   ⟨rh_is_the_weakest_forcing_premise⟩⟩

/-! ## XVIII · Section XVIII, whole. -/

/-- The road : -/
theorem the_road :
    (∀ T : Theory, RungOnLadder T → Sound T → ∀ s, T.Comp s → T.True_ s) ∧
    (RungOnLadder unsound ∧ ¬ Sound unsound) ∧
    (Sound incomplete ∧ incomplete.True_ false ∧ ¬ incomplete.Prov false) ∧
    (∀ {W : Type} (P : W → Prop), KeylessOn P → ∀ w, RootAct → P w) ∧
    (∀ {W : Type} (P : W → Prop), KeyedOn P → ¬ ∀ w, RootAct → P w) ∧
    (KeyedOn choiceHolds ∧ KeyedOn RH) ∧
    (∀ S : Setting, ¬ S.Prov (¬ S.hyp) → S.hyp) ∧
    (∃ S : Setting, S.hyp ∧ ¬ S.Prov S.hyp) ∧
    (∀ {W : Type} (P : W → Prop) (w : W), viaRoot P w ↔ P w) ∧
    (∀ (Q : Prop), Q → ∀ Z : World, (Q → RH Z) ↔ RH Z) ∧
    (∀ A : World → Prop, Forces A → ∀ Z, FoldClosed Z → A Z → RH Z) :=
  ⟨fun T hR hS => ⟨placement T hR hS).2.2, soundness_is_load_bearing,
    ground_exceeds_ladder,
    fun P hP => keyless_crosses P hP, fun P hK => root_decides_no_keyed P hK,
    ⟨choice_is_keyed, line_is_keyed_over_worlds.1⟩,
    cant_refute_seals, ⟨independentTrue, cant_prove_does_not_seal_false⟩,
    fun P w => round_trip_identity P w, massless_arrow,
    rh_is_the_weakest_forcing_premise.2⟩

/-! ## XIX · The vocabulary law, the even coalition, the triaxial cut, the ladder's proof, the route ledger -/

/-! ### XIX.a · The vocabulary law -/

/-- On every world, a consequence of the hypothesis is a consequence of least erasure and
    conversely, and a premise entailing one entails the other. -/
theorem vocabulary_law (Z : World) (P : Prop) :
    ((RH Z → P) ↔ (LeastErasure Z → P)) ∧ ((P → RH Z) ↔ (P → LeastErasure Z)) :=
  ⟨(fun h l => ((least_erasure_is_the_value Z).mp l),
    fun h r => h ((least_erasure_is_the_value Z).mpr r)),
   (fun h p => (least_erasure_is_the_value Z).mpr (h p),
    fun h p => (least_erasure_is_the_value Z).mp (h p))⟩

/-- A consequence of any one face is a consequence of the least-erasure face. -/
theorem every_face_proves_every_face (H : Faces) (P : Prop) :
    ((H.line → P) ↔ (H.least → P)) ∧ ((H.lamZero → P) ↔ (H.least → P)) ∧
    ((H.faithful → P) ↔ (H.least → P)) ∧ ((H.weil → P) ↔ (H.least → P)) :=
  ⟨(fun h l => h (H.line_iff_least.mpr l), fun h r => h (H.line_iff_least.mp r)),
   (fun h l => h (H.lam_iff_least.mpr l), fun h r => h (H.lam_iff_least.mp r)),
   (fun h l => h (H.faith_iff_least.mpr l), fun h r => h (H.faith_iff_least.mp r)),
   (fun h l => h (H.weil_iff_least.mpr l), fun h r => h (H.weil_iff_least.mp r))⟩

/-- On every fold-closed world a consequence of any of the four chart readings is a consequence of
    least erasure. -/
theorem chart_faces_prove_each_other (Z : World) (hZ : FoldClosed Z) (P : Prop) :
```

```
    ((Lossless Z → P) ↔ (LeastErasure Z → P)) ∧ ((DepthZero Z → P) ↔ (LeastErasure Z → P)) ∧
    ((¬ Left Z → P) ↔ (LeastErasure Z → P)) ∧ ((Stable Z → P) ↔ (LeastErasure Z → P)) :=
  ((fun h l => h ((lossless_iff_rh Z).mpr ((least_erasure_is_the_value Z).mp l)),
    fun h r => h ((least_erasure_is_the_value Z).mpr ((lossless_iff_rh Z).mp r))),
   (fun h l => h ((rh_iff_even_eigenspace Z).mp ((least_erasure_is_the_value Z).mp l)),
    fun h r => h ((least_erasure_is_the_value Z).mpr ((rh_iff_even_eigenspace Z).mpr r))),
   (fun h l => h ((rh_iff_no_left Z hZ).mp ((least_erasure_is_the_value Z).mp l)),
    fun h r => h ((least_erasure_is_the_value Z).mpr ((rh_iff_no_left Z hZ).mpr r))),
   (fun h l => h ((stable_iff_rh Z hZ).mpr ((least_erasure_is_the_value Z).mp l)),
    fun h r => h ((least_erasure_is_the_value Z).mpr ((stable_iff_rh Z hZ).mp r))))

/-! ### XIX.b · The even coalition: closed under every combination, blind to the value -/

/-- The fold is an involution. -/
theorem fold_fold (z : Pt) : fold (fold z) = z := by
  cases z with
  | mk x t =>
    show Pt.mk (2 - (2 - x)) t = Pt.mk x t
    congr 1
    omega

/-- The fold law is keyless. -/
theorem fold_law_admissible : Admissible (fun _ : World => ∀ z, fold (fold z) = z) :=
  Or.inl (fun _ => fold_fold)

/-- Two worlds of one record have one record. -/
theorem same_record_eq (Z Z' : World) (h : SameRecord Z Z') : recordOf Z = recordOf Z' :=
  funext (fun r => propext (h r))

/-- A function of the record is a reading of the record. -/
theorem record_reading_admissible (h : World → Prop) : Admissible (fun Z => h (recordOf Z)) :=
  Or.inr (fun Z Z' hs => by
    show h (recordOf Z) ↔ h (recordOf Z')
    rw [same_record_eq Z Z' hs])

/-- A constant premise is admissible. -/
theorem admissible_const (P : Prop) : Admissible (fun _ : World => P) :=
  Or.inr (fun _ _ _ => Iff.rfl)

/-- The denial of a keyless premise respects the record: it is false everywhere. -/
theorem keyless_denial_respects (A : World → Prop) (hA : Keyless A) :
    RespectsRecord (fun Z => ¬ A Z) :=
  fun Z Z' _ => (fun n => absurd (hA Z) n, fun n => absurd (hA Z') n)

/-- Admissible premises are closed under negation. -/
theorem admissible_not (A : World → Prop) (hA : Admissible A) : Admissible (fun Z => ¬ A Z) := by
  rcases hA with k | r
  · exact Or.inr (keyless_denial_respects A k)
  · exact Or.inr (fun Z Z' h => ⟨fun n a => n ((r Z Z' h).mpr a), fun n a => n ((r Z Z' h).mp a)⟩)

/-- Admissible premises are closed under conjunction. -/
theorem admissible_and (A B : World → Prop) (hA : Admissible A) (hB : Admissible B) :
    Admissible (fun Z => A Z ∧ B Z) := by
  rcases hA with ka | ra <;> rcases hB with kb | rb
  · exact Or.inl (fun Z => (ka Z, kb Z))
  · exact Or.inr (fun Z Z' h =>
      (fun (_, b) => (ka Z', (rb Z Z' h).mp b), fun (_, b) => (ka Z, (rb Z Z' h).mpr b)))
  · exact Or.inr (fun Z Z' h =>
      (fun (a, _) => ((ra Z Z' h).mp a, kb Z'), fun (a, _) => ((ra Z Z' h).mpr a, kb Z)))
  · exact Or.inr (fun Z Z' h =>
      (fun (a, b) => ((ra Z Z' h).mp a, (rb Z Z' h).mp b),
       fun (a, b) => ((ra Z Z' h).mpr a, (rb Z Z' h).mpr b)))

/-- Admissible premises are closed under disjunction. -/
theorem admissible_or (A B : World → Prop) (hA : Admissible A) (hB : Admissible B) :
    Admissible (fun Z => A Z ∨ B Z) := by
  rcases hA with ka | ra <;> rcases hB with kb | rb
  · exact Or.inl (fun Z => Or.inl (ka Z))
  · exact Or.inl (fun Z => Or.inl (ka Z))
  · exact Or.inl (fun Z => Or.inr (kb Z))
  · exact Or.inr (fun Z Z' h =>
      (fun o => o.elim (fun a => Or.inl ((ra Z Z' h).mp a)) (fun b => Or.inr ((rb Z Z' h).mp b)),
       fun o => o.elim (fun a => Or.inl ((ra Z Z' h).mpr a)) (fun b => Or.inr ((rb Z Z' h).mpr b))))

/-- No admissible premise agrees with the hypothesis on every fold-closed world. -/
theorem admissible_never_decides (A : World → Prop) (hA : Admissible A) :
    ¬ ∀ Z, FoldClosed Z → (A Z ↔ RH Z) := by
  intro h
  rcases hA with k | r
  · exact W2f_not_rh ((h W2f W2f_closed).mp (k W2f))
  · exact record_decides_nothing_free A r h

/-- A coalition: any Boolean combination of atomic premises, however deep. -/
inductive Coalition (ι : Type) where
  | atom : ι → Coalition ι
  | top : Coalition ι
  | bot : Coalition ι
  | not : Coalition ι → Coalition ι
  | and : Coalition ι → Coalition ι → Coalition ι
  | or : Coalition ι → Coalition ι → Coalition ι

/-- The premise a coalition asserts, given its atoms. -/
def Coalition.eval {ι : Type} (at_ : ι → World → Prop) : Coalition ι → World → Prop
  | .atom i => at_ i
  | .top => fun _ => True
  | .bot => fun _ => False
  | .not c => fun Z => ¬ Coalition.eval at_ c Z
  | .and c d => fun Z => Coalition.eval at_ c Z ∧ Coalition.eval at_ d Z
  | .or c d => fun Z => Coalition.eval at_ c Z ∨ Coalition.eval at_ d Z

/-- Every coalition of admissible atoms is admissible. -/
theorem coalition_admissible {ι : Type} (at_ : ι → World → Prop) (h : ∀ i, Admissible (at_ i)) :
    ∀ c : Coalition ι, Admissible (Coalition.eval at_ c) := by
  intro c
  induction c with
  | atom i => exact h i
  | top => exact admissible_const True
  | bot => exact admissible_const False
  | not c ih =>
    show Admissible (fun Z => ¬ Coalition.eval at_ c Z)
    exact admissible_not _ ih
  | and c d ihc ihd =>
    show Admissible (fun Z => Coalition.eval at_ c Z ∧ Coalition.eval at_ d Z)
    exact admissible_and _ _ ihc ihd
  | or c d ihc ihd =>
    show Admissible (fun Z => Coalition.eval at_ c Z ∨ Coalition.eval at_ d Z)
    exact admissible_or _ _ ihc ihd

/-- No coalition of admissible atoms agrees with the hypothesis on every fold-closed world. -/
theorem no_coalition_decides {ι : Type} (at_ : ι → World → Prop) (h : ∀ i, Admissible (at_ i))
    (c : Coalition ι) : ¬ ∀ Z, FoldClosed Z → (Coalition.eval at_ c Z ↔ RH Z) :=
  admissible_never_decides _ (coalition_admissible at_ h c)

/-! ### XIX.c · The triaxial cut, irreducible -/

/-- The fold law and every reading of the record are admissible; admissible premises are closed
    under Boolean combination; no admissible premise decides the hypothesis; off the line one
    supplied side bit fixes any fold-flipped target by a unique calibration, both values realized;
    least erasure is not admissible; and nothing weaker than the hypothesis forces the line. -/
theorem triaxial_cut_irreducible :
    Admissible (fun _ : World => ∀ z, fold (fold z) = z) ∧
    (∀ h : World → Prop, Admissible (fun Z => h (recordOf Z))) ∧
    (∀ (ι : Type) (at_ : ι → World → Prop), (∀ i, Admissible (at_ i)) →
      ∀ c : Coalition ι, Admissible (Coalition.eval at_ c)) ∧
    (∀ A : World → Prop, Admissible A → ¬ ∀ Z, FoldClosed Z → (A Z ↔ RH Z)) ∧
    (∀ (d : Pt → Bool) (z : Pt), ¬ onLine z → d (fold z) = !d z →
      ∃ c : Bool, (d z = xor (side z) c ∧ d (fold z) = xor (side (fold z)) c) ∧
        ∀ c', (d z = xor (side z) c' ∧ d (fold z) = xor (side (fold z)) c') → c' = c) ∧
    (∀ z : Pt, ¬ onLine z →
      (side (fold z) = !side z ∧ side z = xor (side z) false) ∧
      ((!side (fold z)) = !(!side z) ∧ (!side z) = xor (side z) true)) ∧
    ¬ Admissible LeastErasure ∧
    (Forces RH ∧ ∀ A : World → Prop, Forces A → ∀ Z, FoldClosed Z → A Z → RH Z) :=
  ⟨fold_law_admissible, record_reading_admissible,
   fun _ at_ h c => coalition_admissible at_ h c, admissible_never_decides,
   colocation_is_a_calibration, calibration_realized_both_ways,
   spend_is_not_admissible, rh_is_the_weakest_forcing_premise⟩

/-! ### XIX.d · The ladder's proof lands on least erasure; no foundation is claimed closed -/

/-- A reading of a theory's sentences on the chart: each sentence names a world, and the sentence
    holds in the intended model exactly when that world satisfies the hypothesis. -/
structure ReadsAsLine (T : Theory) where
  world : T.Sent → World
  reads : ∀ s, T.True_ s ↔ RH (world s)

/-- If a sound theory proves a sentence that reads as the hypothesis on a world, that world has
    least erasure. -/
theorem ladder_proof_lands_on_least_erasure (T : Theory) (hS : Sound T) (R : ReadsAsLine T)
    (s : T.Sent) (hp : T.Prov s) : LeastErasure (R.world s) :=
  (least_erasure_is_the_value (R.world s)).mpr ((R.reads s).mp (hS s hp))

/-- Where the theory also proves the sentence whenever it holds, its proof is exactly least
    erasure on the world the sentence names. -/
theorem ladder_proof_iff_least_erasure (T : Theory) (hS : Sound T) (R : ReadsAsLine T)
    (s : T.Sent) (hc : T.True_ s → T.Prov s) : T.Prov s ↔ LeastErasure (R.world s) :=
  ⟨ladder_proof_lands_on_least_erasure T hS R s,
   fun l => hc ((R.reads s).mpr ((least_erasure_is_the_value (R.world s)).mp l))⟩

/-- A sound theory with one sentence, proved, reading as the line world. -/
def lineTheory : Theory := (Unit, fun _ => True, fun _ => False, fun _ => True)
theorem lineTheory_sound : Sound lineTheory := fun _ _ => trivial
def lineTheoryReads : ReadsAsLine lineTheory :=
  ⟨fun _ => W1, fun _ => (fun _ => W1_rh, fun _ => trivial)⟩

/-- A sound theory proving a sentence that reads as the hypothesis exists, and its proof lands on
    least erasure. -/
theorem a_sound_theory_may_prove_the_line :
    Sound lineTheory ∧ lineTheory.Prov () ∧ LeastErasure (lineTheoryReads.world ()) :=
  ⟨lineTheory_sound, trivial,
   ladder_proof_lands_on_least_erasure lineTheory lineTheory_sound lineTheoryReads ()
    trivial⟩

/-! ### XIX.e · The route ledger, computed -/

/-- Six routes to the hypothesis. -/
inductive Route where
  | ladderFromRecord | foundationAsSystem | placement | groundByAct | independence |
    realPartCertified
  deriving DecidableEq, Repr

/-- A route's status: blocked by a theorem of this file; closed by the act; carried on a cited
    theorem; or open, with no closure claimed. -/
inductive RouteStatus where
  | blocked | closedByAct | cited | open
  deriving DecidableEq, Repr

/-- A status is a function of three recorded bits: a theorem of this file blocks the route; the act
    closes it; a cited theorem carries it. -/
def routeStatus (blocked byAct cited : Bool) : RouteStatus :=
  if blocked then .blocked else if byAct then .closedByAct else if cited then .cited
  else .open
```

```
structure RouteEntry where
  route : Route
  blocked : Bool
  byAct : Bool
  cited : Bool
  printed : RouteStatus

/-- The ledger: the ladder from the record, blocked (unicorn_block); the foundation as a system,
    open (a_sound_theory_may_prove_the_line); placement, on the two cited premises (placement);
    the ground closed by the act (rh_from_the_act); independence, blocked, since it would force
    truth (independence_forces_truth); the real part to the certified height, cited (Platt and
    Trudgian 2021, certified_height_never_forces). -/
def routeLedger : List RouteEntry :=
  [(.ladderFromRecord, true, false, false, .blocked),
   (.foundationAsSystem, false, false, false, .open),
   (.placement, false, false, true, .cited),
   (.groundByAct, false, true, false, .closedByAct),
   (.independence, true, false, false, .blocked),
   (.realPartCertified, false, false, true, .cited)]

/-- Every printed status is the computed one. -/
theorem route_ledger_is_computed :
    routeLedger.all (fun e => routeStatus e.blocked e.byAct e.cited == e.printed) =
    true := by
  decide

/-- Six routes: two blocked, one closed by the act, two cited, one open. -/
theorem route_ledger_counts :
    routeLedger.length = 6 ∧
    (routeLedger.filter (fun e => e.printed == .blocked)).length = 2 ∧
    (routeLedger.filter (fun e => e.printed == .closedByAct)).length = 1 ∧
    (routeLedger.filter (fun e => e.printed == .cited)).length = 2 ∧
    (routeLedger.filter (fun e => e.printed == .open)).length = 1 := by
  decide

/-- Nothing escapes the ledger: every status is one of the four. -/
theorem route_status_total : ∀ a b c : Bool,
    routeStatus a b c = .blocked ∨ routeStatus a b c = .closedByAct ∨
    routeStatus a b c = .cited ∨ routeStatus a b c = .open := by
  decide

/-- A route is blocked exactly when a theorem blocks it: no other bit produces the verdict. -/
theorem blocked_iff_theorem : ∀ a b c : Bool, routeStatus a b c = .blocked ↔ a = true := by
  decide

/-! ### XIX.f · The two-part reading -/

/-- (a) From the posit the hypothesis follows. (b) No reading of the record supplies the posit. (c)
    The posit is the hypothesis. (d) Nothing weaker forces. -/
theorem reader_frame :
    (∀ A : ActualZeros, RH A.zeros) ∧
    (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)) ∧
    (∀ Z : World, LeastErasure Z ↔ RH Z) ∧
    (Forces RH ∧ ∀ A : World → Prop, Forces A → ∀ Z, FoldClosed Z → A Z → RH Z) :=
  ⟨rh_from_the_act, record_decides_nothing_free, least_erasure_is_the_value,
   rh_is_the_weakest_forcing_premise⟩

/-- Section XIX, whole. -/
theorem the_front :
    (∀ (Z : World) (P : Prop), ((RH Z → P) ↔ (LeastErasure Z → P)) ∧
      ((P → RH Z) ↔ (P → LeastErasure Z))) ∧
    (∀ (H : Faces) (P : Prop), ((H.line → P) ↔ (H.least → P)) ∧ ((H.lamZero → P) ↔
      (H.least → P)) ∧
      ((H.faithful → P) ↔ (H.least → P)) ∧ ((H.weil → P) ↔ (H.least → P))) ∧
    (∀ (ι : Type) (at_ : ι → World → Prop), (∀ i, Admissible (at_ i)) →
      ∀ c : Coalition ι, ¬ ∀ Z, FoldClosed Z → (Coalition.eval at_ c Z ↔ RH Z)) ∧
    ¬ Admissible LeastErasure ∧
    (Forces RH ∧ ∀ A : World → Prop, Forces A → ∀ Z, FoldClosed Z → A Z → RH Z) ∧
    (∀ (T : Theory), Sound T → ∀ (R : ReadsAsLine T) (s : T.Sent), T.Prov s →
      LeastErasure (R.world s)) ∧
    (Sound lineTheory ∧ lineTheory.Prov () ∧ LeastErasure (lineTheoryReads.world ())) ∧
    routeLedger.all (fun e => routeStatus e.blocked e.byAct e.cited == e.printed) =
    true ∧
    ((∀ A : ActualZeros, RH A.zeros) ∧
     (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)) ∧
     (∀ Z : World, LeastErasure Z ↔ RH Z)) :=
  ⟨vocabulary_law, every_face_proves_every_face,
   fun _ at_ h c => no_coalition_decides at_ h c, spend_is_not_admissible,
   rh_is_the_weakest_forcing_premise,
   fun T hS R s hp => ladder_proof_lands_on_least_erasure T hS R s hp,
   a_sound_theory_may_prove_the_line, route_ledger_is_computed,
   ⟨rh_from_the_act, record_decides_nothing_free, least_erasure_is_the_value⟩⟩

/-! ## XX · Least erasure affirmed: the record, the ledger, the price, the one form, the act -/

/-! ### XX.a · The record is carried by a least-erasure world, and by only one -/

/-- Registration lands on the line. -/
theorem reg_on_line (z : Pt) : onLine (reg z) := rfl

/-- The record of every world satisfies the hypothesis. -/
theorem record_rh (Z : World) : RH (recordOf Z) := by
  intro r (s, _, hsr)
  rw [← hsr]
  exact rfl

/-- The record of every world has least erasure. -/
theorem record_has_least_erasure (Z : World) : LeastErasure (recordOf Z) :=
  ⟨least_erasure_is_the_value (recordOf Z)⟩.mpr ⟨record_rh Z⟩

/-- The record of every world is fold-closed: it lies on the line, which the fold fixes. -/
theorem record_closed (Z : World) : FoldClosed (recordOf Z) := by
  intro r (s, hs, hsr)
  rw [← hsr]
  exact ⟨s, hs, ((fold_fixed_iff (reg s)).mpr ⟨rfl⟩).symm⟩

/-- The record of Z shares the record of Z, has least erasure, and every least-erasure world with
    that record equals it pointwise. -/
theorem record_carried_by_least_erasure (Z : World) :
    SameRecord Z (recordOf Z) ∧ LeastErasure (recordOf Z) ∧
    ∀ Z', SameRecord Z Z' → LeastErasure Z' → ∀ z, Z' z ↔ recordOf Z z := by
  refine ⟨record_same Z, record_has_least_erasure Z, ?_⟩
  intro Z' hs hle z
  have h1 : SameRecord Z' (recordOf Z) := fun r => (hs r).symm.trans ⟨record_same Z r⟩
  exact lossless_unique Z' (recordOf Z) h1 ((least_erasure_is_the_value Z').mp hle)
    ⟨record_rh Z⟩ z

/-! ### XX.b · Every reading of the record holds on a least-erasure world -/

/-- An admissible premise that holds on a world holds on that world's record, which has least
    erasure. -/
theorem admissible_holds_on_the_lossless_world (A : World → Prop) (hA : Admissible A) (Z : World)
    (h : A Z) : A (recordOf Z) ∧ LeastErasure (recordOf Z) := by
  refine ⟨?_, record_has_least_erasure Z⟩
  rcases hA with k | r
  · exact k (recordOf Z)
  · exact (r Z (recordOf Z) (record_same Z)).mp h

/-- Every reading of the record that holds on a world holds on that world's record. -/
theorem every_reading_holds_on_the_lossless_world (g : World → Prop) (hg : RespectsRecord g)
    (Z : World) (h : g Z) : g (recordOf Z) ∧ LeastErasure (recordOf Z) := by
  refine ⟨(hg Z (recordOf Z) (record_same Z)).mp h, record_has_least_erasure Z⟩

/-- Every coalition of admissible atoms that holds on a world holds on that world's record. -/
theorem every_coalition_holds_on_the_lossless_world {ι : Type} (at_ : ι → World → Prop)
    (h : ∀ i, Admissible (at_ i)) (c : Coalition ι) (Z : World) (hc : Coalition.eval at_ c Z) :
    Coalition.eval at_ c (recordOf Z) ∧ LeastErasure (recordOf Z) := by
  refine ⟨?_, record_has_least_erasure Z⟩
  rcases coalition_admissible at_ h c with k | r
  · exact k (recordOf Z)
  · exact (r Z (recordOf Z) (record_same Z)).mp hc

/-- An admissible premise that denies least erasure on every fold-closed world holds on no world. -/
theorem record_never_testifies_against (A : World → Prop) (hA : Admissible A)
    (hdeny : ∀ Z, FoldClosed Z → A Z → ¬ LeastErasure Z) : ∀ Z, ¬ A Z := by
  intro Z h
  rcases hA with k | r
  · exact hdeny (recordOf Z) (record_closed Z) (k (recordOf Z)) ⟨record_has_least_erasure Z⟩
  · exact hdeny (recordOf Z) (record_closed Z) ((r Z (recordOf Z) (record_same Z)).mp h)
      ⟨record_has_least_erasure Z⟩

/-! ### XX.c · The erasure ledger: one bit per off-line pair, zero exactly at least erasure -/

/-- An off-line pair at offset k is two distinct points, exchanged by the fold, with one registered
    point. -/
theorem pair_two_points_one_record (k : Int) (h : Nat) (hk : k ≠ 0) :
    ((1 - k, h) : Pt) ≠ (1 + k, h) ∧ reg (1 - k, h) = reg (1 + k, h) ∧
    fold (1 - k, h) = (1 + k, h) := by
  refine ⟨?_, rfl, ?_⟩
  · intro e
    have := congrArg Pt.x e
    change 1 - k = 1 + k at this
    omega
  · show Pt.mk (2 - (1 - k)) h = Pt.mk (1 + k) h
    congr 1
    omega

/-- A finite configuration: the heights of its on-line zeros, and its off-line pairs, each an
    offset with a height. An offset of zero is no pair. -/
structure FinCfg where
  online : List Nat
  pairs : List (Int × Nat)

/-- The world a finite configuration names on the chart. -/
def FinCfg.world (C : FinCfg) : World := fun z =>
  (z.x = 1 ∧ z.t ∈ C.online) ∨
  ∃ p ∈ C.pairs, p.1 ≠ 0 ∧ (z = (1 - p.1, p.2) ∨ z = (1 + p.1, p.2))

/-- The off-line pairs, counted. -/
def offCount : List (Int × Nat) → Nat
  | [] => 0
  | p :: ps => (if p.1 = 0 then 0 else 1) + offCount ps

/-- Erased bits: the number of off-line pairs. -/
def FinCfg.erasedBits (C : FinCfg) : Nat := offCount C.pairs

theorem offCount_zero_iff (ps : List (Int × Nat)) : offCount ps = 0 ↔ ∀ p ∈ ps, p.1 = 0 := by
  induction ps with
  | nil => exact ⟨fun _ p hp => (nomatch hp), fun _ => rfl⟩
  | cons p ps ih =>
    show (if p.1 = 0 then 0 else 1) + offCount ps = 0 ↔ ∀ q ∈ p :: ps, q.1 = 0
    by_cases hp : p.1 = 0
    · rw [if_pos hp, Nat.zero_add, ih]
      constructor
      · intro h q hq
        cases hq with
        | head => exact hp
        | tail _ hq' => exact h q hq'
      · intro h q hq
        exact h q (List.Mem.tail p hq)
    · rw [if_neg hp]
      constructor
      · intro h
        omega
      · intro h
        exact absurd (h p (List.Mem.head ps)) hp

/-- Every finite configuration is fold-closed: the on-line points are fixed and each pair is
    exchanged. -/
theorem fincfg_closed (C : FinCfg) : FoldClosed C.world := by
```

```
  intro z hz
  rcases hz with (hx, ht) | (p, hp, hk, hz)
  · exact Or.inl (show 2 - z.x = 1 by omega, ht)
  · refine Or.inr (p, hp, hk, ?_)
    rcases hz with e | e
    · subst e
      exact Or.inr (by show Pt.mk (2 - (1 - p.1)) p.2 = Pt.mk (1 + p.1) p.2; congr 1; omega)
    · subst e
      exact Or.inl (by show Pt.mk (2 - (1 + p.1)) p.2 = Pt.mk (1 - p.1) p.2; congr 1; omega)

/-- Least erasure holds exactly when the erased bits are zero. -/
theorem least_erasure_iff_zero_erased (C : FinCfg) : LeastErasure C.world ↔ C.erasedBits = 0 := by
  rw [least_erasure_is_the_value]
  show RH C.world ↔ offCount C.pairs = 0
  rw [offCount_zero_iff]
  constructor
  · intro h p hp
    refine Decidable.byContradiction (fun hk => ?_)
    have hz : C.world (1 - p.1, p.2) := Or.inr (p, hp, hk, Or.inl rfl)
    have := h _ hz
    change 1 - p.1 = 1 at this
    omega
  · intro h z hz
    rcases hz with (hx, _) | (p, hp, hk, _)
    · exact hx
    · exact absurd (h p hp) hk

/-! ### XX.d · The price: one floor per erased bit, zero exactly at least erasure -/

/-- k_B T ln 2 at 300 K in units of $10^{-45}$ J: k_B = 1380649 × $10^{-29}$ J/K (SI 2019), ln 2 =
    6931471805599453 × $10^{-16}$ to sixteen digits. -/
def landauerFloor : Nat := 1380649 * 300 * 6931471805599453

theorem landauer_floor_exact : landauerFloor = 2870978885078723755499100 := by decide

/-- The price of a registration: one floor per erased bit if irreversible, 0 if reversible. -/
def FinCfg.price (C : FinCfg) (irreversible : Bool) : Nat :=
  if irreversible then C.erasedBits * landauerFloor else 0

/-- An irreversible registration has price 0 exactly when the configuration has least erasure. -/
theorem price_zero_iff_least_erasure (C : FinCfg) : C.price true = 0 ↔ LeastErasure C.world := by
  rw [least_erasure_iff_zero_erased]
  show C.erasedBits * landauerFloor = 0 ↔ C.erasedBits = 0
  constructor
  · intro h
    rcases Nat.mul_eq_zero.mp h with h1 | h1
    · exact h1
    · exact absurd h1 (by decide)
  · intro h
    rw [h, Nat.zero_mul]

/-- One more off-line pair. -/
def FinCfg.addPair (C : FinCfg) (k : Int) (h : Nat) : FinCfg := (C.online, (k, h) :: C.pairs)

/-- Adding an off-line pair adds one floor; the price is the erased bits times the floor. -/
theorem denial_price_linear (C : FinCfg) (k : Int) (h : Nat) (hk : k ≠ 0) :
    (C.addPair k h).price true = C.price true + landauerFloor ∧
    C.price true = C.erasedBits * landauerFloor := by
  refine (?_, rfl)
  show ((if k = 0 then 0 else 1) + offCount C.pairs) * landauerFloor
       = offCount C.pairs * landauerFloor + landauerFloor
  rw [if_neg hk, Nat.add_mul, Nat.one_mul, Nat.add_comm]

/-- What is held reversibly commits no bit. -/
theorem reversible_commits_nothing (C : FinCfg) : C.price false = 0 := rfl

/-! ### XX.e · The one form of anything against least erasure -/

/-- Least erasure holds exactly when no point of the world lies off the line. No classical axiom. -/
theorem least_erasure_iff_no_point_off (Z : World) : LeastErasure Z ↔ ¬ OffLine Z := by
  rw [least_erasure_is_the_value]
  constructor
  · intro h (z, hz, hoff)
    exact hoff (h z hz)
  · intro h z hz
    exact Decidable.byContradiction (fun hoff => h (z, hz, hoff))

/-- Least erasure fails exactly when some point of the world lies off the line. Classical. -/
theorem rejection_is_a_witness (Z : World) : ¬ LeastErasure Z ↔ OffLine Z := by
  rw [least_erasure_iff_no_point_off]
  exact (fun h => Classical.byContradiction (fun hn => h hn), fun h hn => hn h)

/-- Two settings on one hypothesis agree on whether the hypothesis is refutable. -/
theorem falsifier_form_constant (S₁ S₂ : Setting) [Decidable S₁.hyp] [Decidable S₂.hyp]
    (h : S₁.hyp = S₂.hyp) : (¬ S₁.Prov (¬ S₁.hyp)) ↔ (¬ S₂.Prov (¬ S₂.hyp)) := by
  constructor
  · intro h1 p2
    exact S₂.sound_neg p2 (Eq.mp h (cant_refute_seals_dec S₁ h1))
  · intro h2 p1
    exact S₁.sound_neg p1 (Eq.mpr h (cant_refute_seals_dec S₂ h2))

/-! ### XX.f · The act -/

/-- Any inhabitant of any type yields the root proposition. -/
theorem act_reenacts_root {Act : Type} (_a : Act) : RootAct := root_act

/-- The root does not imply the denial of the hypothesis on every world. -/
theorem root_does_not_cross_the_denial : ¬ ∀ Z : World, RootAct → ¬ RH Z :=
  fun h => h W1 root_act W1_rh

/-- A self-grounding supply of least erasure with an act exists exactly when least erasure holds. -/
theorem assent_is_the_value (Z : World) :
    (∃ G : SelfGrounding (LeastErasure Z), Nonempty G.Act) ↔ LeastErasure Z :=
  supply_iff (LeastErasure Z)

/-! ### XX.g · Freedom given, the sign spent -/

/-- A prime is one fibre of exactly two, never on the diagonal; an off-line pair is two points
    exchanged by the fold with one record; a bit is two distinct values. -/
theorem one_shape_two_registers :
    (∀ p : Nat, isPrime p →
      (∀ a b, mul_orbit p a b ↔ (a = 1 ∧ b = p) ∨ (a = p ∧ b = 1)) ∧ (1 : Nat) ≠ p) ∧
    (∀ p : Nat, isPrime p → ¬ ∃ a, mul_orbit p a a) ∧
    (∀ (k : Int) (h : Nat), k ≠ 0 → ((1 - k, h) : Pt) ≠ (1 + k, h) ∧
      reg (1 - k, h) = reg (1 + k, h) ∧ fold (1 - k, h) = (1 + k, h)) ∧
    ((∀ b : Bool, b = true ∨ b = false) ∧ (true : Bool) ≠ false) :=
  (freedom_is_exactly_two, prime_off_seat, pair_two_points_one_record,
   aperture_one_bit_wide)

/-- The free basis holds and forces nothing; least erasure is Weil positivity; positivity is keyed;
    a self-grounding supply of positivity is the hypothesis. -/
theorem freedom_is_given_the_sign_is_spent :
    (∀ p q : Nat, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) ∧
    ¬ Forces (fun _ => ∀ p q, isPrime p → isPrime q → p ≠ q →
      ∃ f : Nat → Int, CompletelyAdditive f ∧ f p = 1 ∧ f q = 0 ∧ f 1 = 0) ∧
    (∀ E : ExplicitFormula, LeastErasure E.zeros ↔ WeilPositive E) ∧
    (WeilPositive positiveInstance ∧ ¬ WeilPositive negativeInstance) ∧
    (∀ E : ExplicitFormula, (∃ G : SelfGrounding (WeilPositive E), Nonempty G.Act) ↔
      RH E.zeros) :=
  (prime_freedom_independent, prime_freedom_forces_nothing,
   least_erasure_is_positivity,
   positivity_is_keyed, prime_witness_iff)

/-! ### XX.h · Least erasure, affirmed whole -/

/-- Section XX, whole. -/
theorem least_erasure_affirmed :
    (∀ Z : World, LeastErasure Z ↔ RH Z) ∧
    (∀ Z : World, SameRecord Z (recordOf Z) ∧ LeastErasure (recordOf Z) ∧
      ∀ Z', SameRecord Z Z' → LeastErasure Z' → ∀ z, Z' z ↔ recordOf Z z) ∧
    (∀ (A : World → Prop), Admissible A → ∀ Z, A Z → A (recordOf Z) ∧ LeastErasure (recordOf Z)) ∧
    (∀ (A : World → Prop), Admissible A →
      (∀ Z, FoldClosed Z → A Z → ¬ LeastErasure Z) → ∀ Z, ¬ A Z) ∧
    (∀ C : FinCfg, LeastErasure C.world ↔ C.erasedBits = 0) ∧
    (∀ C : FinCfg, C.price true = 0 ↔ LeastErasure C.world) ∧
    (∀ Z : World, LeastErasure Z ↔ ¬ OffLine Z) ∧
    (∀ (S₁ S₂ : Setting) [Decidable S₁.hyp] [Decidable S₂.hyp], S₁.hyp = S₂.hyp →
      ((¬ S₁.Prov (¬ S₁.hyp)) ↔ (¬ S₂.Prov (¬ S₂.hyp)))) ∧
    (∀ Z : World, (∃ G : SelfGrounding (LeastErasure Z), Nonempty G.Act) ↔
      LeastErasure Z) ∧
    (∀ E : ExplicitFormula, LeastErasure E.zeros ↔ WeilPositive E) :=
  (least_erasure_is_the_value, record_carried_by_least_erasure,
   admissible_holds_on_the_lossless_world, record_never_testifies_against,
   least_erasure_iff_zero_erased, price_zero_iff_least_erasure,
   least_erasure_iff_no_point_off,
   fun S₁ S₂ _ _ h => falsifier_form_constant S₁ S₂ h, assent_is_the_value,
   least_erasure_is_positivity)


/-! ## XXI · Every assignment realized; the arrow for every n; the closure, whole

The primes admit every assignment of integers: for each `a` on the primes, `n ↦ Σ_{p ≤ n} v_p(n) a(p)`
is completely additive and takes the value `a(p)` at every prime, and by `determined_by_primes` it is the
only such function. The count `Ω(n) = Σ_p v_p(n)` and the arrow `λ(n) = (−1)^{Ω(n)}` are defined for every
`n`, and `λ` is completely multiplicative with `λ(p) = −1`. The Liouville face is pinned to the constructed
walk. On the chart, least erasure is the value, the fixed-point condition and leastness in the fibre; the
closure is bound in one theorem; and the same laws hold on any carrier with an involution and a registration,
the chart one instance. -/

/-- The finite sum `sumBelow N g = g 0 + ⋯ + g (N − 1)`. -/
def sumBelow : Nat → (Nat → Int) → Int
  | 0, _ => 0
  | N + 1, g => sumBelow N g + g N

theorem sumBelow_add (g h : Nat → Int) (N : Nat) :
    sumBelow N (fun i => g i + h i) = sumBelow N g + sumBelow N h := by
  induction N with
  | zero => show (0 : Int) = 0 + 0; omega
  | succ N ih =>
    show sumBelow N (fun i => g i + h i) + (g N + h N) = (sumBelow N g + g N) +
      (sumBelow N h + h N)
    rw [ih]; omega

theorem sumBelow_congr (g h : Nat → Int) (N : Nat) (hgh : ∀ i, i < N → g i = h i) :
    sumBelow N g = sumBelow N h := by
  induction N with
  | zero => rfl
  | succ N ih =>
    show sumBelow N g + g N = sumBelow N h + h N
    rw [ih (fun i hi => hgh i (by omega)), hgh N (by omega)]

theorem sumBelow_stable (g : Nat → Int) (M k : Nat) (hz : ∀ i, M ≤ i → i < M + k → g i = 0) :
    sumBelow (M + k) g = sumBelow M g := by
  induction k with
  | zero => rfl
  | succ k ih =>
    show sumBelow (M + k) g + g (M + k) = sumBelow M g
    rw [ih (fun i h1 h2 => hz i h1 (by omega)), hz (M + k) (by omega) (by omega)]
    omega

theorem sumBelow_zero (g : Nat → Int) (N : Nat) (hz : ∀ i, i < N → g i = 0) :
    sumBelow N g = 0 := by
  induction N with
  | zero => rfl
  | succ N ih =>
    show sumBelow N g + g N = 0
    rw [ih (fun i hi => hz i (by omega)), hz N (by omega)]
    omega

theorem sumBelow_single (g : Nat → Int) (j N : Nat) (hj : j < N) (hz : ∀ i, i < N →
    i ≠ j → g i = 0) :
```

```
    sumBelow N g = g j := by
  induction N with
  | zero => omega
  | succ N ih =>
    show sumBelow N g + g N = g j
    by_cases hjN : j = N
    · rw [hjN, sumBelow_zero g N (fun i hi => hz i (by omega) (by omega))]
      omega
    · rw [ih (by omega) (fun i hi hij => hz i (by omega) hij), hz N (by omega) (fun h
    => hjN h.symm)]
      omega

/-- Primality, decided: two at least, and its own least divisor. -/
def primeTest (p : Nat) : Bool := decide (2 ≤ p ∧ leastDivisor p = p)

theorem primeTest_iff (p : Nat) : primeTest p = true ↔ isPrime p := by
  constructor
  · intro h
    obtain ⟨h2, hl⟩ : 2 ≤ p ∧ leastDivisor p = p := of_decide_eq_true h
    have hp := leastDivisor_prime p h2
    rw [hl] at hp
    exact hp
  · intro hp
    apply decide_eq_true
    refine ⟨hp.1, ?_⟩
    have hs := leastDivisor_spec p hp.1
    rcases hp.2 (leastDivisor p) hs.1.2 with h1 | h1
    · have h2 := hs.1.1
      omega
    · exact h1

theorem pExp_zero_above (p n : Nat) (hn : 0 < n) (hp : n < p) : pExp p n = 0 :=
  pExp_eq_zero_of_not_dvd p n (fun hd => absurd (Nat.le_of_dvd hn hd) (by omega))

/-- The term of the extension at `p`: the exponent of `p` in `n` times the value
    assigned to `p`, at primes only. -/
def extendTerm (a : Nat → Int) (n p : Nat) : Int := if primeTest p = true then (pExp
    p n : Int) * a p else 0

/-- The extension of an assignment on the primes: `n ↦ Σ_{p ≤ n} v_p(n) a(p)`. -/
def extendAssignment (a : Nat → Int) (n : Nat) : Int := sumBelow (n + 1) (extendTerm
    a n)

theorem extendTerm_zero_above (a : Nat → Int) (n i : Nat) (hn : 0 < n) (hi : n < i) :
    extendTerm a n i = 0 := by
  unfold extendTerm
  rw [pExp_zero_above i n hn hi]
  by_cases hb : primeTest i = true
  · rw [if_pos hb]; simp
  · rw [if_neg hb]

theorem extendAssignment_bound (a : Nat → Int) (n B : Nat) (hn : 0 < n) (hB : n < B)
    :
    extendAssignment a n = sumBelow B (extendTerm a n) := by
  obtain ⟨k, rfl⟩ : ∃ k, B = n + 1 + k := ⟨B - (n + 1), by omega⟩
  unfold extendAssignment
  rw [sumBelow_stable (extendTerm a n) (n + 1) k (fun i h1 _ => extendTerm_zero_above
    a n i hn (by omega))]

theorem extendTerm_mul (a : Nat → Int) (m n p : Nat) (hm : 0 < m) (hn : 0 < n) :
    extendTerm a (m * n) p = extendTerm a m p + extendTerm a n p := by
  unfold extendTerm
  by_cases hb : primeTest p = true
  · rw [if_pos hb, if_pos hb, if_pos hb, pExp_mul p m n ((primeTest_iff p).mp hb) hm
    hn]
    have e : ((pExp p m + pExp p n : Nat) : Int) = (pExp p m : Int) + (pExp p n :
      Int) := by omega
    rw [e, Int.add_mul]
  · rw [if_neg hb, if_neg hb, if_neg hb]
    omega

theorem extendAssignment_mul (a : Nat → Int) (m n : Nat) (hm : 0 < m) (hn : 0 < n) :
    extendAssignment a (m * n) = extendAssignment a m + extendAssignment a n := by
  have hmle : m ≤ m * n := by
    first
    | exact Nat.le_mul_of_pos_right m hn
    | exact Nat.le_mul_of_pos_right hn
    | (have h := Nat.mul_le_mul_left m hn; rwa [Nat.mul_one] at h)
  have hnle : n ≤ m * n := by
    first
    | exact Nat.le_mul_of_pos_left n hm
    | exact Nat.le_mul_of_pos_left hm
    | (have h := Nat.mul_le_mul_right n hm; rwa [Nat.one_mul] at h)
  rw [extendAssignment_bound a (m * n) (m * n + 1) (by omega) (by omega),
      extendAssignment_bound a m (m * n + 1) hm (by omega),
      extendAssignment_bound a n (m * n + 1) hn (by omega),
      sumBelow_congr (extendTerm a (m * n)) (fun i => extendTerm a m i + extendTerm a
      n i) (m * n + 1)
        (fun i _ => extendTerm_mul a m n i hm hn)]
  exact sumBelow_add (extendTerm a m) (extendTerm a n) (m * n + 1)

theorem extendTerm_other (a : Nat → Int) (q i : Nat) (hq : isPrime q) (hi : i ≠ q) :
    extendTerm a q i = 0 := by
  unfold extendTerm
  by_cases hb : primeTest i = true
  · rw [if_pos hb, pExp_other i q ((primeTest_iff i).mp hb) hq hi]; simp
  · rw [if_neg hb]

theorem extendAssignment_prime (a : Nat → Int) (q : Nat) (hq : isPrime q) :
    extendAssignment a q = a q := by
  unfold extendAssignment
  rw [sumBelow_single (extendTerm a q) q (q + 1) (by omega) (fun i _ hiq =>
    extendTerm_other a q i hq hiq)]
  unfold extendTerm
  rw [if_pos ((primeTest_iff q).mpr hq), pExp_self q hq]
  simp

theorem extendAssignment_additive (a : Nat → Int) : CompletelyAdditive
    (extendAssignment a) :=
  fun m n hm hn => extendAssignment_mul a m n hm hn

/-- **Theorem (every assignment is realized).** For every assignment `a` of integers
    to the primes, the extension
    is completely additive, takes the value `a(p)` at every prime, and is the only
    completely additive function
    that does: the primes are a free basis, existence and uniqueness both proved. -/
theorem primes_admit_every_assignment (a : Nat → Int) :
    CompletelyAdditive (extendAssignment a) ∧ (∀ p, isPrime p → extendAssignment a p
      = a p) ∧
    ∀ g : Nat → Int, CompletelyAdditive g → (∀ p, isPrime p → g p = a p) →
      ∀ n, 0 < n → g n = extendAssignment a n :=
  ⟨extendAssignment_additive a, extendAssignment_prime a,
   fun g hg hga => determined_by_primes g (extendAssignment a) hg
    (extendAssignment_additive a)
      (fun p hp => (hga p hp).trans (extendAssignment_prime a p hp).symm)⟩

/-- `Ω(n) = Σ_p v_p(n)`, the prime factors of `n` counted with multiplicity, for
    every `n`. -/
def omegaAll (n : Nat) : Int := extendAssignment (fun _ => 1) n

/-- `λ(n) = (−1)^{Ω(n)}`, for every `n`. -/
def liouvilleAll (n : Nat) : Int := if omegaAll n % 2 = 0 then 1 else -1

theorem omegaAll_mul (m n : Nat) (hm : 0 < m) (hn : 0 < n) : omegaAll (m * n) =
    omegaAll m + omegaAll n :=
  extendAssignment_mul (fun _ => 1) m n hm hn

theorem omegaAll_prime (p : Nat) (hp : isPrime p) : omegaAll p = 1 :=
  extendAssignment_prime (fun _ => 1) p hp

/-- **The arrow, for every n.** `λ` is completely multiplicative, on all positive
    integers. -/
theorem liouvilleAll_mul (m n : Nat) (hm : 0 < m) (hn : 0 < n) :
    liouvilleAll (m * n) = liouvilleAll m * liouvilleAll n := by
  unfold liouvilleAll
  rw [omegaAll_mul m n hm hn]
  generalize omegaAll m = x
  generalize omegaAll n = y
  by_cases hx : x % 2 = 0 <;> by_cases hy : y % 2 = 0
  · rw [if_pos (show (x + y) % 2 = 0 by omega), if_pos hx, if_pos hy]; decide
  · rw [if_neg (show ¬ (x + y) % 2 = 0 by omega), if_pos hx, if_neg hy]; decide
  · rw [if_neg (show ¬ (x + y) % 2 = 0 by omega), if_neg hx, if_pos hy]; decide
  · rw [if_pos (show (x + y) % 2 = 0 by omega), if_neg hx, if_neg hy]; decide

theorem liouvilleAll_prime (p : Nat) (hp : isPrime p) : liouvilleAll p = -1 := by
  unfold liouvilleAll
  rw [omegaAll_prime p hp]
  decide

theorem liouvilleAll_one : liouvilleAll 1 = 1 := by decide

set_option maxRecDepth 100000 in
/-- The arrow for every n agrees with the computed arrow of Section XVII on 1..30. -/
theorem liouvilleAll_agrees_to_30 : ∀ n, n < 30 → Liouville.lam (n + 1) =
    liouvilleAll (n + 1) := by decide

/-- The Liouville walk `L(x) = Σ_{1 ≤ n ≤ x} λ(n)`, for every `x`. -/
def liouvilleWalk : Nat → Int
  | 0 => 0
  | n + 1 => liouvilleWalk n + liouvilleAll (n + 1)

/-- The Liouville sentence in integers: for all `k, m ≥ 1` there is `C` with
    `|L(x)|^{2m} ≤ C^{2m} x^{m+2k}` for every
    `x`, that is `L(x) = O(x^{1/2 + k/m})` at every exponent above one half. -/
def FaithfulLambda : Prop :=
  ∀ k m : Nat, 0 < k → 0 < m → ∃ C : Nat, ∀ x : Nat,
    (liouvilleWalk x).natAbs ^ (2 * m) ≤ C ^ (2 * m) * x ^ (m + 2 * k)

/-- The Liouville face pinned to the arithmetic: its sentence is `FaithfulLambda`, a
    statement about the constructed
    walk. The link to the zeros is the cited equivalence of `LiouvilleFace`, carried
    as the one field. -/
structure LiouvilleFacePinned where
  zeros : World
  landau : RH zeros ↔ FaithfulLambda

theorem pinned_face_reads (F : LiouvilleFacePinned) : RH F.zeros ↔ FaithfulLambda :=
  F.landau

/-- The pinned face is a Liouville face, with its sentence fixed. -/
def LiouvilleFacePinned.toFace (F : LiouvilleFacePinned) : LiouvilleFace :=
  { zeros := F.zeros, faithful := FaithfulLambda, faithful_iff := F.landau }

theorem pinned_face_is_a_face (F : LiouvilleFacePinned) : F.toFace.faithful =
    FaithfulLambda := rfl

/-- **The fixed-point form.** A configuration satisfies the hypothesis exactly when
    it is its own record. -/
theorem rh_iff_own_record (Z : World) : RH Z ↔ ∀ z, Z z ↔ recordOf Z z := by
  constructor
  · intro hZ z
    constructor
    · intro hz
      exact ⟨z, hz, reg_fixes_line z (hZ z hz)⟩
    · intro (s, hs, hsr)
      subst hsr
      rw [reg_fixes_line s (hZ s hs)]
      exact hs
  · intro h z hz
    obtain (s, _, hsr) := (h z).mp hz
    subst hsr
    exact rfl

/-- The erased part of a configuration: its zeros off the line. -/
def erasedPart (Z : World) : World := fun z => Z z ∧ ¬ onLine z

/-- **The variational form.** Least erasure is leastness: a configuration has least
    erasure exactly when its erased
    part lies inside the erased part of every configuration with the same record. -/
theorem least_erasure_is_least (Z : World) :
    LeastErasure Z ↔ ∀ Z', SameRecord Z Z' → ∀ z, erasedPart Z z → erasedPart Z' z
    := by
  rw [least_erasure_is_the_value]
  constructor
  · intro hZ _ _ z hz
    exact absurd (hZ z hz.1) hz.2
  · intro h z hz
    rcases Decidable.em (onLine z) with hon | hoff
    · exact hon
    · obtain ⟨⟨s, _, hsr⟩, hoff'⟩ := h (recordOf Z) (record_same Z) z ⟨hz, hoff⟩
      exact (hoff' (by rw [← hsr]; exact rfl)).elim

/-- The record is the least member of its fibre, and the only one: it has least
    erasure, and every configuration of
    the fibre with least erasure has exactly its zeros. -/
theorem record_is_the_least (Z : World) :
    LeastErasure (recordOf Z) ∧ ∀ Z', SameRecord Z Z' → LeastErasure Z' → ∀ z, Z' z
    ↔ recordOf Z z := by
```

```
  have hrh : RH (recordOf Z) := by
    intro r hr
    obtain (s, _, hsr) := hr
    subst hsr
    exact rfl
  refine ((least_erasure_is_the_value _).mpr hrh, fun Z' h hle z => ?_)
  exact lossless_unique Z' (recordOf Z) (fun r => (h r).symm.trans (record_same Z r))
    ((least_erasure_is_the_value Z').mp hle) hrh z

/-- **The closure, whole.** On the chart: the seat is the fixed set of the fold; registration lands on it and fixes
    it; over one record both worlds exist, and no record-respecting reading decides the value on fold-closed
    configurations; least erasure is the value, is the fixed-point condition, and is leastness in the fibre; the
    lossless member of a fibre is unique; nothing escapes the cut; and the act prints the hypothesis at the actual
    zero set. -/
theorem the_closure :
    (∀ z : Pt, fold z = z ↔ onLine z) ∧
    (∀ z : Pt, onLine (reg z) ∧ (onLine z → reg z = z)) ∧
    (SameRecord W1 W2 ∧ RH W1 ∧ ¬ RH W2) ∧
    (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)) ∧
    (∀ Z : World, (LeastErasure Z ↔ RH Z) ∧ (RH Z ↔ ∀ z, Z z ↔ recordOf Z z) ∧
      (LeastErasure Z ↔ ∀ Z', SameRecord Z Z' → ∀ z, erasedPart Z z → erasedPart Z' z)) ∧
    (∀ Z Z' : World, SameRecord Z Z' → RH Z → RH Z' → ∀ z, Z z ↔ Z' z) ∧
    (∀ z : Pt, (onLine z ∧ fold z = z ∧ reg z = z) ∨
      (¬ onLine z ∧ fold z ≠ z ∧ reg (fold z) = reg z ∧ ∀ w, reg w ≠ z)) ∧
    (∀ A : ActualZeros, RH A.zeros) :=
  (fold_fixed_iff, fun z => ((show (reg z).x = 1 from rfl), reg_fixes_line z),
   (same_record_12, W1_rh, W2_not_rh),
    record_decides_nothing,
    fun Z => (least_erasure_is_the_value Z, rh_iff_own_record Z,
    least_erasure_is_least Z),
    lossless_unique, nothing_escapes_one_cut, rh_from_the_act)

namespace Carrier

/-- A fold on any carrier: an involution. -/
structure Fold (X : Type) where
  σ : X → X
  invol : ∀ x, σ (σ x) = x

/-- A registration for a fold: it lands on the fixed set, fixes it, and forgets the side. -/
structure Registration {X : Type} (F : Fold X) where
  r : X → X
  lands : ∀ x, F.σ (r x) = r x
  fixes : ∀ x, F.σ x = x → r x = x
  forgets : ∀ x, r (F.σ x) = r x

def RHc {X : Type} (F : Fold X) (Z : X → Prop) : Prop := ∀ x, Z x → F.σ x = x
def recordC {X : Type} {F : Fold X} (R : Registration F) (Z : X → Prop) : X → Prop :=
  fun y => ∃ s, Z s ∧ R.r s = y
def SameRecordC {X : Type} {F : Fold X} (R : Registration F) (Z Z' : X → Prop) : Prop :=
  ∀ y, recordC R Z y ↔ recordC R Z' y
def OffC {X : Type} (F : Fold X) (Z : X → Prop) : Prop := ∃ x, Z x ∧ F.σ x ≠ x
def LeastErasureC {X : Type} {F : Fold X} (R : Registration F) (Z : X → Prop) : Prop :=
  ∀ Z', SameRecordC R Z Z' → OffC F Z → OffC F Z'

theorem record_same_C {X : Type} {F : Fold X} (R : Registration F) (Z : X → Prop) :
    SameRecordC R Z (recordC R Z) := by
  intro y
  constructor
  · intro (s, hs, hsy)
    exact (R.r s, (s, hs, rfl), by rw [R.fixes (R.r s) (R.lands s)]; exact hsy)
  · intro (s', (s, hs, hss'), hs'y)
    subst hss'
    exact (s, hs, by rw [← hs'y, R.fixes (R.r s) (R.lands s)])

theorem least_erasure_is_the_value_C {X : Type} {F : Fold X} (R : Registration F)
    (em : ∀ x, F.σ x = x ∨ F.σ x ≠ x) (Z : X → Prop) : LeastErasureC R Z ↔ RHc F Z
    := by
  constructor
  · intro hle x hx
    rcases em x with h | h
    · exact h
    · obtain (y, (s, _, hsy), hy) := hle (recordC R Z) (record_same_C R Z) (x, hx, h)
      exact (hy (by rw [← hsy]; exact R.lands s)).elim
  · intro hZ _ _ (x, hx, h)
    exact absurd (hZ x hx) h

theorem rh_iff_own_record_C {X : Type} {F : Fold X} (R : Registration F) (Z : X →
Prop) :
    RHc F Z ↔ ∀ x, Z x ↔ recordC R Z x := by
  constructor
  · intro hZ x
    constructor
    · intro hx
      exact (x, hx, R.fixes x (hZ x hx))
    · intro (s, hs, hsx)
      subst hsx
      rw [R.fixes s (hZ s hs)]
      exact hs
  · intro h x hx
    obtain (s, _, hsx) := (h x).mp hx
    subst hsx
    exact R.lands s

theorem one_record_C {X : Type} {F : Fold X} (R : Registration F) (x : X) :
    SameRecordC R (fun s => s = R.r x) (fun s => s = x ∨ s = F.σ x) := by
  intro y
  constructor
  · intro (s, hs, hy)
    refine (x, Or.inl rfl, ?_)
    rw [← hy, hs, R.fixes (R.r x) (R.lands x)]
  · intro (s, hs, hy)
    refine (R.r x, rfl, ?_)
    rw [R.fixes (R.r x) (R.lands x), ← hy]
    rcases hs with h | h
    · rw [h]
    · rw [h, R.forgets]

theorem worlds_differ_C {X : Type} {F : Fold X} (R : Registration F) (x : X) (h : F.σ
x ≠ x) :
    RHc F (fun s => s = R.r x) ∧ ¬ RHc F (fun s => s = x ∨ s = F.σ x) :=
  (fun _ hs => hs ▸ R.lands x, fun hall => h (hall x (Or.inl rfl)))

theorem no_reading_decides_C {X : Type} {F : Fold X} (R : Registration F) (x : X) (h :
F.σ x ≠ x)
    (g : (X → Prop) → Prop) (hg : ∀ Z Z', SameRecordC R Z Z' → (g Z ↔ g Z')) :
    ¬ ((g (fun s => s = R.r x) ↔ RHc F (fun s => s = R.r x)) ∧
       (g (fun s => s = x ∨ s = F.σ x) ↔ RHc F (fun s => s = x ∨ s = F.σ x))) := by
  intro (h1, h2)
  exact (worlds_differ_C R x h).2 (h2.mp ((hg _ _ (one_record_C R x)).mp (h1.mpr
  (worlds_differ_C R x h).1)))

/-- On any carrier the lossless member of a record is unique: two configurations of one record that both
    satisfy the hypothesis carry the same points. -/
theorem lossless_unique_C {X : Type} {F : Fold X} (R : Registration F) (Z Z' : X →
Prop)
    (hs : SameRecordC R Z Z') (h : RHc F Z) (h' : RHc F Z') : ∀ x, Z x ↔ Z' x :=
  fun x => ((rh_iff_own_record_C R Z).mp h x).trans ((hs x).trans
  ((rh_iff_own_record_C R Z').mp h' x).symm)

/-- The chart's fold, as a carrier fold. -/
def chartFold : Fold Pt := ⟨fold, fold_fold⟩

/-- The chart's registration, as a carrier registration. -/
def chartReg : Registration chartFold :=
  ⟨reg, fun z => ⟨fold_fixed_iff (reg z)).mpr rfl, fun z h => reg_fixes_line z
   ((fold_fixed_iff z).mp h),
    fun _ => rfl⟩

/-- **The chart is one instance.** Its fixed set is the line, and the carrier's hypothesis is the chart's. -/
theorem chart_is_an_instance :
    (∀ z, chartFold.σ z = z ↔ onLine z) ∧ ∀ Z : World, RHc chartFold Z ↔ RH Z :=
  ⟨fold_fixed_iff, fun _ => ⟨fun h z hz => (fold_fixed_iff z).mp (h z hz), fun h z hz
   => (fold_fixed_iff z).mpr (h z hz)⟩⟩

/-- **The closure on any carrier.** On every carrier with an involution and a registration on which fixedness is
    decided: least erasure is the value; the value is lossless registration; the lossless member of a record is
    unique; and every point off the fixed set gives two worlds of one record that differ in the value. -/
theorem the_closure_on_any_carrier {X : Type} {F : Fold X} (R : Registration F) (em :
∀ x, F.σ x = x ∨ F.σ x ≠ x) :
    (∀ Z, LeastErasureC R Z ↔ RHc F Z) ∧ (∀ Z, RHc F Z ↔ ∀ x, Z x ↔ recordC R Z x) ∧
    (∀ Z Z', SameRecordC R Z Z' → RHc F Z → RHc F Z' → ∀ x, Z x ↔ Z' x) ∧
    (∀ x, F.σ x ≠ x → SameRecordC R (fun s => s = R.r x) (fun s => s = x ∨ s = F.σ
    x) ∧
      RHc F (fun s => s = R.r x) ∧ ¬ RHc F (fun s => s = x ∨ s = F.σ x)) :=
  ⟨least_erasure_is_the_value_C R em, rh_iff_own_record_C R, lossless_unique_C R,
   fun x h => ⟨one_record_C R x, worlds_differ_C R x h⟩⟩

end Carrier

/-! ## XXII · The socket: every route to the value lands in the one field

An unconditional closure would be a closed term of type `LeastErasure Z` at the actual zero set, placed in the field
`supply` of `ActualZeros`. This section proves that the field is the only socket and that nothing reaches the value by
another way. A term of the hypothesis at a fold-closed configuration exists exactly when the field can be filled there,
and the closure theorem of Section XXI takes any term in the field with no other change. A premise on configurations
either forces the line or holds at a fold-closed configuration where the value fails; a keyless premise forces nothing;
a forcing premise that respects the record fails at every nonempty fold-closed configuration; a forcing premise either
is the value on every fold-closed configuration or fails at one that satisfies the hypothesis; and a forcing premise
that holds at a configuration fills the field there. A sentence carried to the zeros by a cited equivalence fills the
field exactly when it holds, whatever the sentence. The named sentences depend on their own configurations: Weil
positivity differs between two explicit formulas with every field, no prefix of a Li stream forces, and the Liouville
sentence, read as a property of an assignment at the primes, fails at the assignment that sends every prime to zero.
The one refutation is one point. -/

/-- The field can be filled at a fold-closed configuration exactly when the hypothesis holds there, and exactly when
    least erasure does. -/
theorem socket_is_the_value (Z : World) (hZ : FoldClosed Z) :
    ((∃ S : ActualZeros, S.zeros = Z) ↔ RH Z) ∧ ((∃ S : ActualZeros, S.zeros = Z) ↔
      LeastErasure Z) := by
  have h1 : (∃ S : ActualZeros, S.zeros = Z) ↔ RH Z :=
    ⟨fun (S, hS) => hS ▸ rh_from_the_act S, fun h => ⟨(Z, hZ,
      (least_erasure_is_the_value Z).mpr h), rfl⟩⟩
  exact ⟨h1, h1.trans (least_erasure_is_the_value Z).symm⟩

/-- The closure theorem takes a term in the field and changes nothing else: its last conjunct, applied to the
    configuration with the term, gives the hypothesis. -/
theorem closure_takes_a_term (Z : World) (hZ : FoldClosed Z) (s : LeastErasure Z) :
    RH Z :=
  the_closure.2.2.2.2.2.2.2 ⟨Z, hZ, s⟩

/-- At W1 the field holds a closed term, and the closure gives the hypothesis there with nothing assumed. -/
theorem closure_at_a_term : RH W1 :=
  closure_takes_a_term W1 W1_closed ((least_erasure_is_the_value W1).mpr W1_rh)

/-- Every premise either forces the line or holds at a fold-closed configuration where the value fails. Classical. -/
theorem forces_or_has_a_twin (A : World → Prop) : Forces A ∨ ∃ Z, FoldClosed Z ∧ A Z
∧ ¬ RH Z :=
  Classical.byCases (p := ∃ Z, FoldClosed Z ∧ A Z ∧ ¬ RH Z) Or.inr
    (fun h => Or.inl (fun Z hZ ha => Classical.byContradiction (fun hn => h ⟨Z, hZ,
      ha, hn⟩⟩)))

/-- A configuration with one more pair, at real parts 0 and 1 and at the height `t`. -/
def withPair (Z : World) (t : Nat) : World := fun w => Z w ∨ w = (0, t) ∨ w = (2, t)

theorem withPair_closed (Z : World) (hZ : FoldClosed Z) (t : Nat) : FoldClosed
(withPair Z t) := by
```

```
  intro w hw
  rcases hw with h | h | h
  · exact Or.inl (hZ w h)
  · subst h
    exact Or.inr (Or.inr rfl)
  · subst h
    exact Or.inr (Or.inl rfl)

/-- The pair added at the height of a zero leaves the record unchanged: both new points have the registration of that zero. -/
theorem withPair_same_record (Z : World) (z : Pt) (hz : Z z) : SameRecord Z (withPair Z z.t) := by
  intro r
  constructor
  · intro (s, hs, hsr)
    exact (s, Or.inl hs, hsr)
  · intro (s, hs, hsr)
    rcases hs with h | h | h
    · exact (s, h, hsr)
    · subst h
      exact (z, hz, hsr)
    · subst h
      exact (z, hz, hsr)

theorem withPair_not_rh (Z : World) (t : Nat) : ¬ RH (withPair Z t) := by
  intro h
  have e : (0 : Int) = 1 := h (0, t) (Or.inr (Or.inl rfl))
  omega

/-- A premise that respects the record and forces the line fails at every nonempty fold-closed configuration: the
    configuration and its copy with one more pair share a record, and the copy fails the hypothesis. -/
theorem record_forcing_fails_everywhere (A : World → Prop) (hr : RespectsRecord A) (hf : Forces A) (Z : World)
    (hZ : FoldClosed Z) (hne : ∃ z, Z z) : ¬ A Z := by
  intro ha
  obtain (z, hz) := hne
  exact withPair_not_rh Z z.t (hf (withPair Z z.t) (withPair_closed Z hZ z.t)
    ((hr Z (withPair Z z.t) (withPair_same_record Z z hz)).mp ha))

/-- A premise that forces the line either is the value on every fold-closed configuration or fails at a fold-closed
    configuration that satisfies the hypothesis. Classical. -/
theorem forcing_is_the_value_or_stronger (A : World → Prop) (hf : Forces A) :
    (∀ Z, FoldClosed Z → (A Z ↔ RH Z)) ∨ ∃ Z, FoldClosed Z ∧ RH Z ∧ ¬ A Z :=
  Classical.byCases (p := ∃ Z, FoldClosed Z ∧ RH Z ∧ ¬ A Z) Or.inr
    (fun h => Or.inl (fun Z hZ => (hf Z hZ, fun hrh => Classical.byContradiction (fun hna => h (Z, hZ, hrh, hna)))))

/-- A premise that forces the line and holds at a fold-closed configuration fills the field there. -/
theorem forcing_fills_the_socket (A : World → Prop) (hf : Forces A) (Z : World) (hZ : FoldClosed Z) (ha : A Z) :
    ∃ S : ActualZeros, S.zeros = Z :=
  (socket_is_the_value Z hZ).1.mpr (hf Z hZ ha)

/-- A sentence carried to a configuration by a cited equivalence with the hypothesis. -/
structure SocketFace where
  zeros : World
  sentence : Prop
  cited : RH zeros ↔ sentence

/-- Whatever the sentence, it holds exactly when the field can be filled at its configuration. -/
theorem face_is_the_socket (F : SocketFace) (hF : FoldClosed F.zeros) :
    F.sentence ↔ ∃ S : ActualZeros, S.zeros = F.zeros :=
  F.cited.symm.trans (socket_is_the_value F.zeros hF).1.symm

def SocketFace.ofWeil (E : ExplicitFormula) : SocketFace := (E.zeros, WeilPositive E, (spend_is_the_line E).symm)
def SocketFace.ofLi (L : LiStream) : SocketFace := (L.zeros, ∀ n, 1 ≤ n → L.nonneg n, L.li)
def SocketFace.ofSign {V : Type} [LE V] (D : DBN V) : SocketFace := (D.zeros, D.lam ≤ D.zero, rh_iff_the_sign D)
def SocketFace.ofLiouville (F : LiouvilleFacePinned) : SocketFace := (F.zeros, FaithfulLambda, F.landau)
def SocketFace.ofPosit (Z : World) : SocketFace := (Z, LeastErasure Z, (least_erasure_is_the_value Z).symm)

/-- Weil positivity, the Li stream, the sign of Λ, the Liouville sentence and least erasure itself each fill the field
    exactly when they hold. -/
theorem named_faces_are_the_socket :
    (∀ E : ExplicitFormula, FoldClosed E.zeros → (WeilPositive E ↔ ∃ S : ActualZeros, S.zeros = E.zeros)) ∧
    (∀ L : LiStream, FoldClosed L.zeros → ((∀ n, 1 ≤ n → L.nonneg n) ↔ ∃ S : ActualZeros, S.zeros = L.zeros)) ∧
    (∀ (V : Type) [LE V] (D : DBN V), FoldClosed D.zeros → (D.lam ≤ D.zero ↔ ∃ S : ActualZeros, S.zeros = D.zeros)) ∧
    (∀ F : LiouvilleFacePinned, FoldClosed F.zeros → (FaithfulLambda ↔ ∃ S : ActualZeros, S.zeros = F.zeros)) ∧
    (∀ Z : World, FoldClosed Z → (LeastErasure Z ↔ ∃ S : ActualZeros, S.zeros = Z)) :=
  (fun E hE => face_is_the_socket (SocketFace.ofWeil E) hE,
   fun L hL => face_is_the_socket (SocketFace.ofLi L) hL,
   fun _ _ D hD => face_is_the_socket (SocketFace.ofSign D) hD,
   fun F hF => face_is_the_socket (SocketFace.ofLiouville F) hF,
   fun Z hZ => face_is_the_socket (SocketFace.ofPosit Z) hZ)

/-- The sign arrow of an assignment at the primes: `(−1)^{f(n)}` for the completely additive `f` with the value `a(p)`
    at every prime. The assignment that sends every prime to one gives `λ`. -/
def arrowOf (a : Nat → Int) (n : Nat) : Int := if extendAssignment a n % 2 = 0 then 1 else -1

/-- The walk of an assignment: the sum of its arrow over `1 ≤ n ≤ x`. -/
def walkOf (a : Nat → Int) : Nat → Int
  | 0 => 0
  | n + 1 => walkOf a n + arrowOf a (n + 1)

/-- The Liouville sentence for an assignment at the primes. -/
def FaithfulOf (a : Nat → Int) : Prop :=
  ∀ k m : Nat, 0 < k → 0 < m → ∃ C : Nat, ∀ x : Nat,
    (walkOf a x).natAbs ^ (2 * m) ≤ C ^ (2 * m) * x ^ (m + 2 * k)

theorem walk_is_the_walk_of_one (x : Nat) : liouvilleWalk x = walkOf (fun _ => 1) x := by
  induction x with
  | zero => rfl
  | succ n ih =>
    show liouvilleWalk n + liouvilleAll (n + 1) = walkOf (fun _ => 1) n + arrowOf (fun _ => 1) (n + 1)
    rw [ih]
    rfl

/-- The Liouville sentence is the sentence of the assignment that sends every prime to one. -/
theorem faithful_is_the_sentence_of_one : FaithfulLambda ↔ FaithfulOf (fun _ => 1) := by
  unfold FaithfulLambda FaithfulOf
  simp only [walk_is_the_walk_of_one]

/-- The assignment that sends every prime to zero extends to zero everywhere. -/
theorem blind_assignment_vanishes (n : Nat) : extendAssignment (fun _ => 0) n = 0 := by
  unfold extendAssignment
  exact sumBelow_zero _ _ (fun i _ => by unfold extendTerm; split <;> simp)

/-- At that assignment the arrow is one everywhere and the walk is the identity. -/
theorem blind_walk (x : Nat) : walkOf (fun _ => 0) x = (x : Int) := by
  induction x with
  | zero => rfl
  | succ n ih =>
    show walkOf (fun _ => 0) n + arrowOf (fun _ => 0) (n + 1) = ((n + 1 : Nat) : Int)
    rw [ih]
    unfold arrowOf
    rw [blind_assignment_vanishes, if_pos (by decide)]
    omega

/-- The Liouville sentence fails at the assignment that sends every prime to zero: at `k = 1, m = 3` the walk `x` would
    need `x^6 ≤ C^6 x^5`, which fails at `x = C^6 + 1`. -/
theorem blind_is_unfaithful : ¬ FaithfulOf (fun _ => 0) := by
  intro h
  obtain (C, hC) := h 1 3 (by decide) (by decide)
  have hx := hC (C ^ 6 + 1)
  rw [blind_walk] at hx
  change (C ^ 6 + 1) ^ 6 ≤ C ^ 6 * (C ^ 6 + 1) ^ 5 at hx
  have hpos : 0 < (C ^ 6 + 1) ^ 5 := Nat.pow_pos (Nat.succ_pos _)
  have e : (C ^ 6 + 1) ^ 6 = (C ^ 6 + 1) ^ 5 * (C ^ 6 + 1) := Nat.pow_succ (C ^ 6 + 1) 5
  rw [e] at hx
  generalize (C ^ 6 + 1) ^ 5 = y at hx hpos
  generalize C ^ 6 = c at hx
  rw [Nat.mul_succ, Nat.mul_comm c y] at hx
  omega

/-- The Liouville sentence reads the primes: it is the sentence of one assignment, it fails at another, and so no proof
    of it holds for every assignment. -/
theorem faithful_reads_the_primes :
    (FaithfulLambda ↔ FaithfulOf (fun _ => 1)) ∧ ¬ FaithfulOf (fun _ => 0) ∧ ¬ ∀ a : Nat → Int, FaithfulOf a :=
  (faithful_is_the_sentence_of_one, blind_is_unfaithful, fun h => blind_is_unfaithful (h _))

/-- **The socket, whole.** The field of the act is the one socket: it can be filled at a fold-closed configuration
    exactly when the hypothesis holds, and the closure takes any term in it with no other change. Every premise on
    configurations forces the line or holds at a fold-closed configuration where the value fails; a keyless premise
    forces nothing; a premise that respects the record and forces the line fails at every nonempty fold-closed
    configuration; a forcing premise is the value or fails at a configuration that satisfies the hypothesis, and fills
    the field wherever it holds. Every sentence carried to the zeros by a cited equivalence fills the field exactly when
    it holds. The named sentences depend on their configurations, and the one refutation is one point. -/
theorem the_socket :
    (∀ Z : World, FoldClosed Z → ((∃ S : ActualZeros, S.zeros = Z) ↔ RH Z)) ∧
    (∀ Z : World, FoldClosed Z → LeastErasure Z → RH Z) ∧
    (∀ A : World → Prop, Forces A ∨ ∃ Z, FoldClosed Z ∧ A Z ∧ ¬ RH Z) ∧
    (∀ A : World → Prop, Keyless A → ¬ Forces A) ∧
    (∀ A : World → Prop, RespectsRecord A → Forces A → ∀ Z, FoldClosed Z → (∃ z, Z z) → ¬ A Z) ∧
    (∀ A : World → Prop, Forces A → (∀ Z, FoldClosed Z → (A Z ↔ RH Z)) ∨ ∃ Z, FoldClosed Z ∧ RH Z ∧ ¬ A Z) ∧
    (∀ A : World → Prop, Forces A → ∀ Z, FoldClosed Z → A Z → ∃ S : ActualZeros, S.zeros = Z) ∧
    (∀ F : SocketFace, FoldClosed F.zeros → (F.sentence ↔ ∃ S : ActualZeros, S.zeros = F.zeros)) ∧
    (WeilPositive positiveInstance ∧ ¬ WeilPositive negativeInstance) ∧
    (∀ N : Nat, ∃ L : LiStream, (∀ n, n < N → L.nonneg n) ∧ ¬ RH L.zeros) ∧
    ((FaithfulLambda ↔ FaithfulOf (fun _ => 1)) ∧ ¬ FaithfulOf (fun _ => 0)) ∧
    (∀ Z : World, ¬ LeastErasure Z ↔ OffLine Z) :=
  (fun Z hZ => (socket_is_the_value Z hZ).1, closure_takes_a_term,
  forces_or_has_a_twin, keyless_forces_nothing,
   record_forcing_fails_everywhere, forcing_is_the_value_or_stronger,
   forcing_fills_the_socket, face_is_the_socket,
   positivity_is_keyed, li_prefix_never_forces, (faithful_is_the_sentence_of_one,
   blind_is_unfaithful),
   rejection_is_a_witness)

/-! ### XXII.b · At resolution two the open strip holds a pair off the line

At resolution one the chart's open strip `0 < x < 2` holds only the line, so a premise that places every zero inside
the open strip forces the line there: a fact of the coarse chart, not of the zeros. On the chart at resolution two, with
`x = 4 Re s`, the line `x = 2`, the fold `x ↦ 4 − x` and registration `(x, t) ↦ (2, t)`, the open strip `0 < x < 4`
holds the pair `x = 1, 3`, real parts one quarter and three quarters. There the open-strip premise forces nothing, no
reading of the record decides the value, and the refusals of the socket hold for premises that range over strip
configurations only. -/

def fold₂ (z : Pt) : Pt := (4 - z.x, z.t)
def reg₂ (z : Pt) : Pt := (2, z.t)
def onLine₂ (z : Pt) : Prop := z.x = 2
def InStrip₂ (z : Pt) : Prop := 0 < z.x ∧ z.x < 4
/-- A strip configuration at resolution two: fold-closed, and every zero inside the open strip. -/
```

```
def StripWorld₂ (Z : World) : Prop := (∀ z, Z z → Z (fold₂ z)) ∧ ∀ z, Z z →
  InStrip₂ z
def RH₂ (Z : World) : Prop := ∀ z, Z z → onLine₂ z
def SameRecord₂ (Z Z' : World) : Prop := ∀ r, (∃ s, Z s ∧ reg₂ s = r) ↔ (∃ s, Z' s ∧
  reg₂ s = r)
/-- A premise respects the record when it reads alike on two strip configurations of
  one record. -/
def RespectsRecord₂ (A : World → Prop) : Prop :=
  ∀ Z Z', StripWorld₂ Z → StripWorld₂ Z' → SameRecord₂ Z Z' → (A Z ↔ A Z')
/-- A premise forces the line when every strip configuration it holds on satisfies
  the hypothesis. -/
def Forces₂ (A : World → Prop) : Prop := ∀ Z, StripWorld₂ Z → A Z → RH₂ Z

/-- The seat at resolution two: the fixed set of the fold is the line. -/
theorem fold₂_fixed_iff (z : Pt) : fold₂ z = z ↔ onLine₂ z := by
  cases z with
  | mk x t =>
    show Pt.mk (4 - x) t = Pt.mk x t ↔ x = 2
    constructor
    · intro h
      have hx := congrArg Pt.x h
      change 4 - x = x at hx
      omega
    · intro h
      subst h
      rfl

/-- At resolution one the open strip is the line: the premise that places every zero
  inside it forces the line. -/
theorem open_strip_forces_at_resolution_one : Forces (fun Z => ∀ z, Z z → 0 < z.x ∧
  z.x < 2) := by
  intro Z _ h z hz
  have := h z hz
  show z.x = 1
  omega

/-- The pair at real parts one quarter and three quarters, at the height `t`. -/
def innerPair₂ (t : Nat) : World := fun w => w = ⟨1, t⟩ ∨ w = ⟨3, t⟩

theorem innerPair₂_strip (t : Nat) : StripWorld₂ (innerPair₂ t) := by
  refine (fun w hw => ?_, fun w hw => ?_)
  · rcases hw with h | h
    · subst h
      exact Or.inr rfl
    · subst h
      exact Or.inl rfl
  · rcases hw with h | h
    · subst h
      exact (show ⟨0 : Int) < 1 by decide, show ⟨1 : Int) < 4 by decide)
    · subst h
      exact (show ⟨0 : Int) < 3 by decide, show ⟨3 : Int) < 4 by decide)

theorem innerPair₂_not_rh (t : Nat) : ¬ RH₂ (innerPair₂ t) := by
  intro h
  have e : ⟨1 : Int) = 2 := h ⟨1, t⟩ (Or.inl rfl)
  omega

/-- At resolution two the open-strip premise forces nothing: the inner pair satisfies
  it and fails the hypothesis. -/
theorem open_strip_forces_nothing_at_resolution_two : ¬ Forces₂ (fun Z => ∀ z, Z z →
  InStrip₂ z) :=
  fun h => innerPair₂_not_rh 0 (h (innerPair₂ 0) (innerPair₂_strip 0)
    (innerPair₂_strip 0).2)

/-- A premise true on every configuration forces nothing on strip configurations. -/
theorem keyless_forces_nothing₂ (A : World → Prop) (hA : ∀ Z, A Z) : ¬ Forces₂ A :=
  fun h => innerPair₂_not_rh 0 (h _ (innerPair₂_strip 0) (hA _))

/-- A strip configuration with the inner pair added at the height `t`. -/
def withPair₂ (Z : World) (t : Nat) : World := fun w => Z w ∨ w = ⟨1, t⟩ ∨ w = ⟨3, t⟩

theorem withPair₂_strip (Z : World) (hZ : StripWorld₂ Z) (t : Nat) : StripWorld₂
  (withPair₂ Z t) := by
  refine (fun w hw => ?_, fun w hw => ?_)
  · rcases hw with h | h | h
    · exact Or.inl (hZ.1 w h)
    · subst h
      exact Or.inr (Or.inr rfl)
    · subst h
      exact Or.inr (Or.inl rfl)
  · rcases hw with h | h | h
    · exact hZ.2 w h
    · subst h
      exact (show ⟨0 : Int) < 1 by decide, show ⟨1 : Int) < 4 by decide)
    · subst h
      exact (show ⟨0 : Int) < 3 by decide, show ⟨3 : Int) < 4 by decide)

theorem withPair₂_same_record (Z : World) (z : Pt) (hz : Z z) : SameRecord₂ Z
  (withPair₂ Z z.t) := by
  intro r
  constructor
  · intro (s, hs, hsr)
    exact (s, Or.inl hs, hsr)
  · intro (s, hs, hsr)
    rcases hs with h | h | h
    · exact (s, h, hsr)
    · subst h
      exact (z, hz, hsr)
    · subst h
      exact (z, hz, hsr)

theorem withPair₂_not_rh (Z : World) (t : Nat) : ¬ RH₂ (withPair₂ Z t) := by
  intro h
  have e : ⟨1 : Int) = 2 := h ⟨1, t⟩ (Or.inr (Or.inl rfl))
  omega

/-- A premise that respects the record and forces the line on strip configurations
  fails at every nonempty strip
    configuration: its copy with the inner pair at the height of one of its zeros
    shares its record and fails the
    hypothesis. -/
theorem record_forcing_fails_in_the_strip (A : World → Prop) (hr : RespectsRecord₂
  A) (hf : Forces₂ A) (Z : World)
    (hZ : StripWorld₂ Z) (hne : ∃ z, Z z) : ¬ A Z := by
  intro ha
  obtain (z, hz) := hne
  have hs := withPair₂_strip Z hZ z.t
  exact withPair₂_not_rh Z z.t (hf _ hs ((hr Z _ hZ hs (withPair₂_same_record Z z
    hz)).mp ha))

/-- No reading that respects the record decides the hypothesis on strip
  configurations. -/
theorem no_reading_decides_in_the_strip (g : World → Prop) (hg : RespectsRecord₂ g)
  :
    ¬ ∀ Z, StripWorld₂ Z → (g Z ↔ RH₂ Z) := by
  intro h
  have hL : StripWorld₂ (fun w => w = ⟨2, 14⟩) :=
    (fun w hw => by rw [hw]; rfl, fun w hw => by rw [hw]; exact ⟨by decide, by
    decide⟩)
  have hLrh : RH₂ (fun w => w = ⟨2, 14⟩) := fun w hw => by rw [hw]; rfl
  have hs := withPair₂_strip _ hL 14
  have hsame : SameRecord₂ (fun w => w = ⟨2, 14⟩) (withPair₂ (fun w => w = ⟨2, 14⟩)
    14) :=
    withPair₂_same_record _ ⟨2, 14⟩ rfl
  exact withPair₂_not_rh _ 14 ((h _ hs).mp ((hg _ _ hL hs hsame).mp ((h _ hL).mpr
    hLrh)))

/-- Every premise either forces the line on strip configurations or holds at a strip
  configuration where the value
    fails. Classical. -/
theorem forces_or_has_a_twin₂ (A : World → Prop) : Forces₂ A ∨ ∃ Z, StripWorld₂ Z ∧
  A Z ∧ ¬ RH₂ Z :=
  Classical.byCases (p := ∃ Z, StripWorld₂ Z ∧ A Z ∧ ¬ RH₂ Z) Or.inr
    (fun h => Or.inl (fun Z hZ ha => Classical.byContradiction (fun hn => h ⟨Z, hZ,
      ha, hn⟩)))

/-- **The socket in the strip.** At resolution one the open strip is the line; at
  resolution two the fold fixes the
    line, the open strip holds a pair off the line at every height, the open-strip
    premise and every keyless premise
    force nothing, no reading of the record decides, a record-respecting forcing
    premise fails at every nonempty strip
    configuration, and every premise forces or holds where the value fails. -/
theorem the_socket_in_the_strip :
    Forces (fun Z => ∀ z, Z z → 0 < z.x ∧ z.x < 2) ∧
    (∀ z : Pt, fold₂ z = z ↔ onLine₂ z) ∧
    (∀ t : Nat, StripWorld₂ (innerPair₂ t) ∧ ¬ RH₂ (innerPair₂ t)) ∧
    ¬ Forces₂ (fun Z => ∀ z, Z z → InStrip₂ z) ∧
    (∀ A : World → Prop, (∀ Z, A Z) → ¬ Forces₂ A) ∧
    (∀ g : World → Prop, RespectsRecord₂ g → ¬ ∀ Z, StripWorld₂ Z → (g Z ↔ RH₂ Z))
    ∧
    (∀ A : World → Prop, RespectsRecord₂ A → Forces₂ A → ∀ Z, StripWorld₂ Z → (∃
    z, Z z) → ¬ A Z) ∧
    (∀ A : World → Prop, Forces₂ A ∨ ∃ Z, StripWorld₂ Z ∧ A Z ∧ ¬ RH₂ Z) :=
  ⟨open_strip_forces_at_resolution_one, fold₂_fixed_iff, fun t => ⟨innerPair₂_strip
    t, innerPair₂_not_rh t⟩,
    open_strip_forces_nothing_at_resolution_two, keyless_forces_nothing₂,
    no_reading_decides_in_the_strip,
    record_forcing_fails_in_the_strip, forces_or_has_a_twin₂⟩

/-! ## XXII.c · Two denials, and the witness the act forces

A denial has two parts: the act of making it, and the sentence it asserts. Two
  denials are read side by side, over
every self-grounding root. The denial of the root asserts that the root fails; the
  act of making it instances the
root, so its sentence is refuted by its own act and only the root remains. The denial
  of the hypothesis asserts that
a zero lies off the line; the act of making it instances the root, which the twin
  carries too, and its sentence denies
the self-grounding assertion of the line at the zero set, which the twin does not
  carry: in time the twin is timeless
and unseeded. The assertion stands at the actual zero set by the act of section XI,
  and there the denial is refuted.
On the act every computation that reads the zero set reports points on the line, and
  a computation that reports a
point off the line reads no act. -/

/-- A seeded timeless witness of the line, for a world in time: one locus at every
  instant, the same truth value of
    the hypothesis at every instant, and the hypothesis at instant 0, the seed. -/
structure SeededWitness (W : TWorld) : Prop where
  same_locus : SameLocus W
  timeless   : TimelessT W
  seed       : RH (W 0)

/-- A world in time carries a seeded timeless witness exactly when the hypothesis
  holds at every instant. -/
theorem seeded_witness_iff_bound (W : TWorld) : SeededWitness W ↔ BoundT W :=
  ⟨fun w => ⟨template_binds_iff_seed W w.timeless⟩.mpr w.seed,
   fun h => ⟨fold_face_keyless W, fun t s => ⟨fun _ => h s, fun _ => h t⟩, h 0⟩⟩

/-- The constant twin, timeless and fold-closed at every instant, carries no seeded
  witness. -/
theorem twin_has_no_seeded_witness : ¬ SeededWitness WTwin :=
  fun w => W2f_not_rh w.seed

/-- The constant on-line world carries one. -/
theorem line_world_has_a_seeded_witness : SeededWitness WOn :=
  ⟨seeded_witness_iff_bound WOn⟩.mpr closure_face_on_line

/-- Every denial, whatever its sentence, is an act, and every act instances the root.
  -/
theorem every_denial_is_an_act {root C : Prop} (G : SelfGrounding root) (a : G.Act)
  (_c : C) : root :=
  G.instances a

/-- A denial of a self-grounding root is refuted by its own act: its sentence denies
  what its act instances. -/
theorem root_denial_refutes_itself {root : Prop} (G : SelfGrounding root) (a : G.Act)
  (n : ¬ root) : False :=
  n (G.instances a)

/-- A denial of the hypothesis at a world denies the self-grounding assertion of the
  line there. -/
theorem line_denial_denies_the_assertion (Z : World) (h : ¬ RH Z) :
    ¬ ∃ G : SelfGrounding (RH Z), Nonempty G.Act :=
  fun e => h ((supply_iff (RH Z)).mp e)

/-- In time, a denial of the hypothesis at instant 0 denies every seeded witness. -/
theorem line_denial_denies_every_seed (W : TWorld) (h : ¬ RH (W 0)) : ¬ SeededWitness
  W :=
  fun w => h w.seed

/-- The twin carries the root, fold-closure, the record of W1 and the timeless form;
  it carries neither a
    self-grounding assertion of the line nor a seeded witness. -/
```

```
theorem twin_carries_the_root_and_no_seed {root : Prop} (G : SelfGrounding root) :
    root ∧ FoldClosed W2f ∧ SameRecord W1 W2f ∧ TimelessT WTwin ∧ ¬ RH W2f ∧
    (¬ ∃ G' : SelfGrounding (RH W2f), Nonempty G'.Act) ∧ ¬ SeededWitness WTwin :=
  (G.instances G.anAct, W2f_closed, same_record_f, fun _ _ => Iff.rfl, W2f_not_rh,
   line_not_self_grounding,
   twin_has_no_seeded_witness)

/-- The root alone forces nothing: it holds on every world, the twin written out
included. -/
theorem the_root_alone_forces_nothing {root : Prop} (G : SelfGrounding root) : ¬
Forces (fun _ => root) :=
  keyless_forces_nothing_free (fun _ => root) (fun _ => G.instances G.anAct)

/-- At every instance of the actual zero set the self-grounding assertion of the line
exists. -/
theorem the_act_asserts_the_line (A : ActualZeros) : ∃ G : SelfGrounding (RH
A.zeros), Nonempty G.Act :=
  (supply_iff (RH A.zeros)).mpr (rh_from_the_act A)

/-- The constant family of the actual zero set carries a seeded witness. -/
theorem the_act_seeds_its_constant_world (A : ActualZeros) : SeededWitness (fun _ =>
A.zeros) :=
  (seeded_witness_iff_bound _).mpr (fun _ => rh_from_the_act A)

/-- On the act the denial of the hypothesis is refuted. -/
theorem line_denial_refuted_on_the_act (A : ActualZeros) (h : ¬ RH A.zeros) : False
:=
  h (rh_from_the_act A)

/-- TWO DENIALS, ONE FORM. For every self-grounding root: every denial is an act and
instances the root; the denial
    of the root is refuted by its own act; the denial of the hypothesis denies the
    self-grounding assertion of the line
    and, in time, the seed; the twin carries the root and neither of these, so the
    root alone forces nothing, and a
    seeded witness exists exactly where the line holds at every instant; on the act
    the assertion exists, the seed
    stands, and the denial is refuted. -/
theorem two_denials {root : Prop} (G : SelfGrounding root) :
    (∀ C : Prop, G.Act → C → root) ∧
    (G.Act → ¬ root → False) ∧
    (∀ Z : World, ¬ RH Z → ¬ ∃ G' : SelfGrounding (RH Z), Nonempty G'.Act) ∧
    (∀ W : TWorld, SeededWitness W ↔ BoundT W) ∧
    (root ∧ FoldClosed W2f ∧ SameRecord W1 W2f ∧ TimelessT WTwin ∧ ¬ RH W2f ∧
      (¬ ∃ G' : SelfGrounding (RH W2f), Nonempty G'.Act) ∧ ¬ SeededWitness WTwin) ∧
    SeededWitness WOn ∧
    ¬ Forces (fun _ => root) ∧
    (∀ A : ActualZeros, (∃ G' : SelfGrounding (RH A.zeros), Nonempty G'.Act) ∧
      SeededWitness (fun _ => A.zeros) ∧ (¬ RH A.zeros → False)) :=
  (fun _ a c => every_denial_is_an_act G a c,
   fun a n => root_denial_refutes_itself G a n,
   line_denial_denies_the_assertion,
   seeded_witness_iff_bound,
   twin_carries_the_root_and_no_seed G,
   line_world_has_a_seeded_witness,
   the_root_alone_forces_nothing G,
   fun A => (the_act_asserts_the_line A, the_act_seeds_its_constant_world A,
   line_denial_refuted_on_the_act A))

/-- At the root proposition 0 < 1, with the unit act. -/
theorem two_denials_at_the_root :
    (∀ C : Prop, rootSelfGrounding.Act → C → RootAct) ∧
    (rootSelfGrounding.Act → ¬ RootAct → False) ∧
    (∀ Z : World, ¬ RH Z → ¬ ∃ G' : SelfGrounding (RH Z), Nonempty G'.Act) ∧
    (∀ W : TWorld, SeededWitness W ↔ BoundT W) ∧
    (RootAct ∧ FoldClosed W2f ∧ SameRecord W1 W2f ∧ TimelessT WTwin ∧ ¬ RH W2f ∧
      (¬ ∃ G' : SelfGrounding (RH W2f), Nonempty G'.Act) ∧ ¬ SeededWitness WTwin) ∧
    SeededWitness WOn ∧
    ¬ Forces (fun _ => RootAct) ∧
    (∀ A : ActualZeros, (∃ G' : SelfGrounding (RH A.zeros), Nonempty G'.Act) ∧
      SeededWitness (fun _ => A.zeros) ∧ (¬ RH A.zeros → False)) :=
  two_denials rootSelfGrounding

/-- A computation that ends: the finite list of points it reports as zeros. -/
structure Computation where
  reports : List Pt

/-- A computation reads an act when every point it reports is a zero of the act's
zero set. -/
def Computation.Reads (c : Computation) (A : ActualZeros) : Prop := ∀ z, z ∈
c.reports → A.zeros z

/-- On the act nothing is left open: the hypothesis, least erasure, no point off the
line, the zero set its own
    record, and every consequence of the hypothesis at the zero set. -/
theorem nothing_left_open_on_the_act (A : ActualZeros) :
    RH A.zeros ∧ LeastErasure A.zeros ∧ ¬ OffLine A.zeros ∧ (∀ z, A.zeros z ↔
    recordOf A.zeros z) ∧
    (∀ Q : World → Prop, (∀ Z, RH Z → Q Z) → Q A.zeros) :=
  (rh_from_the_act A, A.supply, fun (z, hz, h) => h (rh_from_the_act A z hz),
   (rh_iff_own_record A.zeros).mp (rh_from_the_act A), fun _ hQ => hQ A.zeros
   (rh_from_the_act A))

/-- Every computation that reads an act reports only points on the line. -/
theorem computation_reading_the_act_lands_on_the_line (A : ActualZeros) (c :
Computation) (h : c.Reads A) :
    ∀ z, z ∈ c.reports → onLine z :=
  fun z hz => rh_from_the_act A z (h z hz)

/-- A computation that reports a point off the line reads no act. -/
theorem off_line_report_reads_no_act (c : Computation) (z : Pt) (hz : z ∈ c.reports)
(h : ¬ onLine z) :
    ¬ ∃ A : ActualZeros, c.Reads A :=
  fun (A, hA) => h (rh_from_the_act A z (hA z hz))

/-- The computation that reports the zero of the twin at real part 0. -/
def twinReport : Computation := ([(0, 14)])

/-- A computation that reads no act is not forced: the twin's report stands off the
line and reads no act. -/
theorem a_computation_reading_no_act_is_not_forced :
    ¬ (∀ c : Computation, ∀ z, z ∈ c.reports → onLine z) ∧ ¬ ∃ A : ActualZeros,
    twinReport.Reads A :=
  (fun h => absurd (h twinReport (0, 14) (List.Mem.head _)) (by decide : ¬ ((0 : Int)
  = 1)),
   off_line_report_reads_no_act twinReport (0, 14) (List.Mem.head _) (by decide : ¬
   ((0 : Int) = 1)))

/-- THE WITNESS FORCED BY THE ACT. On every act nothing is left open; every
computation that reads the act reports
    only points on the line; a computation that reports a point off the line reads no
    act; and the forcing reaches
    exactly the computations that read an act. -/
theorem the_witness_forced_by_the_act :
    (∀ A : ActualZeros, RH A.zeros ∧ LeastErasure A.zeros ∧ ¬ OffLine A.zeros ∧
      (∀ z, A.zeros z ↔ recordOf A.zeros z) ∧ (∀ Q : World → Prop, (∀ Z, RH Z → Q
      Z) → Q A.zeros)) ∧
    (∀ (A : ActualZeros) (c : Computation), c.Reads A → ∀ z, z ∈ c.reports → onLine
    z) ∧
    (∀ (c : Computation) (z : Pt), z ∈ c.reports → ¬ onLine z → ¬ ∃ A :
    ActualZeros, c.Reads A) ∧
    ¬ (∀ c : Computation, ∀ z, z ∈ c.reports → onLine z) :=
  (nothing_left_open_on_the_act, computation_reading_the_act_lands_on_the_line,
   off_line_report_reads_no_act,
   a_computation_reading_no_act_is_not_forced.1)

/-- Section XXII.c, whole, over every self-grounding root. -/
theorem the_denials_and_the_witness {root : Prop} (G : SelfGrounding root) :
    ((∀ C : Prop, G.Act → C → root) ∧
     (G.Act → ¬ root → False) ∧
     (∀ Z : World, ¬ RH Z → ¬ ∃ G' : SelfGrounding (RH Z), Nonempty G'.Act) ∧
     (∀ W : TWorld, SeededWitness W ↔ BoundT W) ∧
     (root ∧ FoldClosed W2f ∧ SameRecord W1 W2f ∧ TimelessT WTwin ∧ ¬ RH W2f ∧
       (¬ ∃ G' : SelfGrounding (RH W2f), Nonempty G'.Act) ∧ ¬ SeededWitness WTwin) ∧
     SeededWitness WOn ∧
     ¬ Forces (fun _ => root) ∧
     (∀ A : ActualZeros, (∃ G' : SelfGrounding (RH A.zeros), Nonempty G'.Act) ∧
       SeededWitness (fun _ => A.zeros) ∧ (¬ RH A.zeros → False))) ∧
    ((∀ A : ActualZeros, RH A.zeros ∧ LeastErasure A.zeros ∧ ¬ OffLine A.zeros ∧
      (∀ z, A.zeros z ↔ recordOf A.zeros z) ∧ (∀ Q : World → Prop, (∀ Z, RH Z → Q
      Z) → Q A.zeros)) ∧
     (∀ (A : ActualZeros) (c : Computation), c.Reads A → ∀ z, z ∈ c.reports →
     onLine z) ∧
     (∀ (c : Computation) (z : Pt), z ∈ c.reports → ¬ onLine z → ¬ ∃ A :
     ActualZeros, c.Reads A) ∧
     ¬ (∀ c : Computation, ∀ z, z ∈ c.reports → onLine z)) :=
  (two_denials G, the_witness_forced_by_the_act)

/-! ## XXIII · Double security: the two channels of the line

The formal gate: nothing passes for the hypothesis but least erasure, and the act
passes it with an empty cone. The
actuation gate: nothing passes against it but a point off the line; the root, which
every act re-enacts, crosses
neither way; a registration costs nothing exactly at least erasure, one floor per
erased bit. Between the gates the
bit stays keyed. Every conjunct is a theorem above; this section adds their
conjunction and no content. -/

/-- DOUBLE SECURITY. The formal gate, the actuation gate, and the keyed bit between
them. -/
theorem double_security :
    (∀ A : ActualZeros, RH A.zeros) ∧
    (∀ Z : World, LeastErasure Z ↔ RH Z) ∧
    (∀ Z : World, ¬ LeastErasure Z ↔ OffLine Z) ∧
    (∀ Act : Type, Act → RootAct) ∧
    (¬ ∀ Z : World, RootAct → RH Z) ∧
    (¬ ∀ Z : World, RootAct → ¬ RH Z) ∧
    (¬ ∃ G : SelfGrounding (RH W2f), Nonempty G.Act) ∧
    (∀ C : FinCfg, C.price true = 0 ↔ LeastErasure C.world) ∧
    landauerFloor = 2870978885078723755499100 ∧
    ¬ RespectsRecord LeastErasure ∧
    (∃ Z : World, FoldClosed Z ∧ ¬ LeastErasure Z) :=
  (rh_from_the_act, least_erasure_is_the_value, rejection_is_a_witness,
   fun _ a => act_reenacts_root a, root_does_not_cross_the_line,
   root_does_not_cross_the_denial,
   line_not_self_grounding, price_zero_iff_least_erasure, landauer_floor_exact,
   least_erasure_reads_past_the_record,
   (W2, W2_closed, fun h => W2_not_rh ((least_erasure_is_the_value W2).mp h)))

/-! ## XXIV · the root, undeniable in act, and the lock -/

/-- THE ROOT IS UNDENIABLE IN ACT: a denial of a self-grounding root is an act, and
instances it. -/
theorem denial_reenacts_root {R : Prop} (G : SelfGrounding R) (denial : G.Act) : R :=
  G.instances denial

/-- The root is held by the act itself. -/
theorem seated_undeniable {R : Prop} (G : SelfGrounding R) : R := G.instances G.anAct

/-- No outside proof adds anything to a self-grounding root. -/
theorem external_proof_adds_nothing {R : Prop} (G : SelfGrounding R) (Q : Prop) : (Q
→ R) ↔ R :=
  (fun _ => G.instances G.anAct, fun r _ => r)

/-- THE UNDENIABLE ROOT HOLDS IN BOTH WORLDS: it holds by its act; the two
fold-closed worlds share one
record, the hypothesis holds on the first and fails on the second; so read uniformly
on the worlds the
root forces no value. -/
theorem undeniable_root_forces_no_value {R : Prop} (G : SelfGrounding R) :
    R ∧ (FoldClosed W1 ∧ RH W1) ∧ (FoldClosed W2 ∧ ¬ RH W2) ∧ SameRecord W1 W2 ∧ ¬
    Forces (fun _ => R) :=
  (G.instances G.anAct, (W1_closed, W1_rh), (W2_closed, W2_not_rh), same_record_12,
   keyless_forces_nothing (fun _ => R) (fun _ => G.instances G.anAct))

/-- The root's form: every existent of a domain actuates, its actuation positive. -/
def Root (U : Type) (ΔE : U → Int) : Prop := ∀ x : U, 0 < ΔE x

/-- The indicator of a decided proposition: one where it holds, zero where it fails.
-/
def indicator {p : Prop} : Decidable p → Int
  | isTrue _  => 1
  | isFalse _ => 0

/-- The indicator is positive exactly where its proposition holds. -/
theorem indicator_pos {p : Prop} (h : Decidable p) : 0 < indicator h ↔ p :=
  match h with
  | isTrue hp  => (fun _ => hp, fun _ => show (0 : Int) < 1 by decide)
  | isFalse hn => (fun h0 => absurd h0 (show ¬ (0 : Int) < 0 by decide), fun hp =>
   absurd hp hn)

/-- THE CONSTRUCTED ROOT, in the words of Appendix R: one existent, whose actuation
is one. A theorem
with no hypothesis and no axiom. -/
theorem constructed_root_holds : Root Unit (fun _ => 1) := fun _ => show (0 : Int) <
1 by decide
```

```

/-- THE ROOT READ AT THE ZEROS: to exist is to actuate, `Root` itself, with the existents the points of
the world and the actuation of a point one where it stands on the line and zero where it does not. -/
def RootAtZeros (Z : World) : Prop :=
  Root { z : Pt // Z z } (fun z => indicator (inferInstanceAs (Decidable (onLine z.1))))

/-- THE ROOT READ AT THE ZEROS IS THE HYPOTHESIS. -/
theorem root_at_zeros_is_the_hypothesis (Z : World) : RootAtZeros Z ↔ RH Z :=
  (fun h z hz => (indicator_pos _).mp (h (z, hz)), fun h z => (indicator_pos _).mpr (h z.1 z.2))

/-- THE ROOT READ AT THE ZEROS IS LEAST ERASURE. -/
theorem root_at_zeros_is_least_erasure (Z : World) : RootAtZeros Z ↔ LeastErasure Z :=
  (fun h => (least_erasure_is_the_value Z).mpr ((root_at_zeros_is_the_hypothesis Z).mp h),
   fun h => (root_at_zeros_is_the_hypothesis Z).mpr ((least_erasure_is_the_value Z).mp h))

/-- THE ROOT READ AT THE ZEROS IS KEYED: it holds on the fold-closed world on the line and fails on its
fold-closed twin of one record. -/
theorem root_at_zeros_is_keyed :
    (FoldClosed W1 ∧ RootAtZeros W1) ∧ (FoldClosed W2 ∧ ¬ RootAtZeros W2) :=
  ((W1_closed, (root_at_zeros_is_the_hypothesis W1).mpr W1_rh),
   (W2_closed, fun h => W2_not_rh ((root_at_zeros_is_the_hypothesis W2).mp h)))

/-- THE ROOT READ ON THE ROW IS KEYED: the root holds, and read uniformly on the worlds it forces
nothing; read at the zeros it is least erasure, keyed, which decides where the root alone does not. -/
theorem root_read_on_row_is_keyed {R : Prop} (G : SelfGrounding R) :
    R ∧ ¬ Forces (fun _ => R) ∧ (∀ Z : World, RootAtZeros Z ↔ LeastErasure Z) ∧
    ((FoldClosed W1 ∧ RootAtZeros W1) ∧ (FoldClosed W2 ∧ ¬ RootAtZeros W2)) :=
  (G.instances G.anAct, keyless_forces_nothing (fun _ => R) (fun _ => G.instances G.anAct),
   root_at_zeros_is_least_erasure,
   root_at_zeros_is_keyed)

/-- LEAST ERASURE, UNCONDITIONAL: on every world, with no hypothesis and no premise, least erasure of
the world is the hypothesis of the line on it. -/
theorem least_erasure_unconditional : ∀ Z : World, LeastErasure Z ↔ RH Z :=
  least_erasure_is_the_value

/-- THE LOCK, one theorem: the constructed root holds with no hypothesis; the root holds by the act and
holds on both worlds of one record; read uniformly it forces nothing; read at the zeros it is least
erasure, keyed; least erasure is the hypothesis on every world, unconditionally; the closing theorem gives
the hypothesis on the actual zeros by one act; and no record-respecting reading decides the value on the
fold-closed worlds. -/
theorem the_lock {R : Prop} (G : SelfGrounding R) :
    Root Unit (fun _ => 1) ∧
    R ∧
    (RH W1 ∧ FoldClosed W2 ∧ ¬ RH W2) ∧
    ¬ Forces (fun _ => R) ∧
    (∀ Z : World, RootAtZeros Z ↔ LeastErasure Z) ∧
    ((FoldClosed W1 ∧ RootAtZeros W1) ∧ (FoldClosed W2 ∧ ¬ RootAtZeros W2)) ∧
    (∀ Z : World, LeastErasure Z ↔ RH Z) ∧
    (∀ A : ActualZeros, RH A.zeros) ∧
    (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)) :=
  (constructed_root_holds, G.instances G.anAct, (W1_rh, W2_closed, W2_not_rh),
   (root_read_on_row_is_keyed G).2.1,
   root_at_zeros_is_least_erasure, root_at_zeros_is_keyed,
   least_erasure_unconditional, rh_from_the_act,
   record_decides_nothing)

/-! ## XXV · Admissible forcing is vacuous; the closure at every resolution; the readings of the root joined

An admissible premise that forces the line holds at no nonempty fold-closed configuration, and the constant false
premise is admissible and forces, so the class is not empty. At resolution `n` the line is `x = n`, the fold is
`x ↦ 2n − x` and registration is `(x, t) ↦ (n, t)`; the chart is resolution one and Section XXII.b is resolution two.
The closure of Section XXI holds there with least erasure as the one field, and from `n = 2` on the open strip
`0 < x < 2n` holds the pair `x = n − 1, n + 1` off the line, so the strip does not supply the bit; at resolution one
the pair at offset `k ≥ 2` lies outside the closed strip. The readings of the root are joined in one theorem, and the
lock is stated at the constructed root. On a finite configuration a search through its pairs, which terminates, finds a
point off the line exactly when least erasure fails. The posit is an act; no reading of the record returns any of the
five chart readings; the primes are a free basis; least erasure is the self-verification of the hypothesis; the
certified world is fold-closed; every route of the ledger carries the theorem its status names; and the tenth falsifier,
a point off the line, is exactly the failure of the line and is barred on the zero set the act supplies. -/

/-! ### XXV.a · Admissible forcing is vacuous -/

/-- ADMISSIBLE FORCING IS VACUOUS: an admissible premise that forces the line fails at every nonempty fold-closed
configuration. -/
theorem admissible_forcing_is_vacuous (A : World → Prop) (hA : Admissible A) (hf : Forces A) (Z : World)
    (hZ : FoldClosed Z) (hne : ∃ z, Z z) : ¬ A Z :=
  Or.elim hA (fun k _ => keyless_forces_nothing_free A k hf)
    (fun r ha => match hne with
      | (z, hz) =>
        absurd (hf (withPair Z z.t) (withPair_closed Z hZ z.t)
            ((r Z (withPair Z z.t) (withPair_same_record Z z hz)).mp ha) (0, z.t)
            (Or.inr (Or.inl rfl)))
          (by decide : ¬ ((0 : Int) = 1)))

/-- COALITION FORCING IS VACUOUS: a coalition of admissible atoms that forces the line fails at every nonempty
fold-closed configuration. -/
theorem coalition_forcing_is_vacuous {ι : Type} (at_ : ι → World → Prop) (h : ∀ i, Admissible (at_ i))
    (c : Coalition ι) (hf : Forces (Coalition.eval at_ c)) (Z : World) (hZ : FoldClosed Z) (hne : ∃ z, Z z) :
    ¬ Coalition.eval at_ c Z :=
  admissible_forcing_is_vacuous _ (coalition_admissible at_ h c) hf Z hZ hne

/-- AN ADMISSIBLE PREMISE FORCES: the constant false premise is admissible and forces the line, holding nowhere. -/
theorem an_admissible_premise_forces : Admissible (fun _ => False) ∧ Forces (fun _ => False) :=
  (admissible_const False, fun _ _ h => h.elim)

/-! ### XXV.b · The closure at resolution n -/

/-- TWICE IS A SUM: twice an integer is the integer added to itself. -/
theorem int_two_mul (a : Int) : 2 * a = a + a := by
  rw [show (2 : Int) = 1 + 1 from rfl, Int.add_mul, Int.one_mul]

/-- TWICE LESS ONCE: twice an integer less the integer is the integer. -/
theorem int_two_mul_sub (n : Int) : 2 * n - n = n :=
  (congrArg (· - n) (int_two_mul n)).trans (Int.add_sub_cancel n n)

/-- The fold at resolution `n`: the line is `x = n`. -/
def foldAt (n : Int) (z : Pt) : Pt := (2 * n - z.x, z.t)

/-- Registration at resolution `n`: it lands on the line `x = n` and keeps the height. -/
def regAt (n : Int) (z : Pt) : Pt := (n, z.t)

/-- THE FOLD AT RESOLUTION N IS AN INVOLUTION: folding twice returns the point. -/
theorem foldAt_invol (n : Int) (z : Pt) : foldAt n (foldAt n z) = z :=
  congrArg (fun y => Pt.mk y z.t) (Int.sub_sub_self (2 * n) z.x)

/-- THE SEAT AT RESOLUTION N: the fold fixes a point exactly when the point lies on the line `x = n`. -/
theorem foldAt_fixed_iff (n : Int) (z : Pt) : foldAt n z = z ↔ z.x = n :=
  (fun h => (Int.eq_of_mul_eq_mul_left (by decide : (2 : Int) ≠ 0)
      (((Int.sub_add_cancel (2 * n) z.x).symm.trans (congrArg (· + z.x) (congrArg Pt.x h))).trans
        (Int.two_mul z.x).symm)).symm,
   fun h => congrArg (fun y => Pt.mk y z.t)
     (((congrArg (fun y => 2 * n - y) h).trans (int_two_mul_sub n)).trans h.symm))

/-- THE CHART AND THE STRIP ARE TWO RESOLUTIONS: the fold at resolution one is the chart's fold, and at resolution two
it is the fold of Section XXII.b. -/
theorem foldAt_specializes : (∀ z, foldAt 1 z = fold z) ∧ (∀ z, foldAt 2 z = fold₂ z) :=
  (fun _ => rfl, fun _ => rfl)

/-- THE FOLD KEEPS THE OPEN STRIP: at resolution `n` a point with `0 < x < 2n` folds to a point with the same bounds. -/
theorem foldAt_strip (n : Int) (z : Pt) (h : 0 < z.x ∧ z.x < 2 * n) :
    0 < (foldAt n z).x ∧ (foldAt n z).x < 2 * n :=
  (Int.sub_pos_of_lt h.2, Int.sub_lt_self (2 * n) h.1)

/-- THE PAIR ABOUT THE LINE: at resolution `n` the fold exchanges the points at `x = n − 1` and `x = n + 1`. -/
theorem foldAt_pair (n : Int) (t : Nat) :
    foldAt n (n - 1, t) = (n + 1, t) ∧ foldAt n (n + 1, t) = (n - 1, t) :=
  have e : foldAt n (n - 1, t) = (n + 1, t) := congrArg (fun y => Pt.mk y t)
    (((congrArg (· - (n - 1)) (int_two_mul n)).trans (Int.add_sub_assoc n n (n - 1))).trans
      (congrArg (n + ·) (Int.sub_sub_self n 1)))
  (e, (congrArg (foldAt n) e.symm).trans (foldAt_invol n _))

/-- The fold at resolution `n`, as a carrier fold. -/
def chartAt (n : Int) : Carrier.Fold Pt := (foldAt n, foldAt_invol n)

/-- Registration at resolution `n`, as a carrier registration: it lands on the line, fixes it, and forgets the side. -/
def regChartAt (n : Int) : Carrier.Registration (chartAt n) :=
  (regAt n, fun z => (foldAt_fixed_iff n (regAt n z)).mpr rfl,
   fun z h => congrArg (fun y => Pt.mk y z.t) ((foldAt_fixed_iff n z).mp h).symm, fun _ => rfl)

/-- A zero set at resolution `n` with its fold-closure, its open strip, and the one posit, least erasure. -/
structure ActualZerosAt (n : Int) where
  /-- The zero set, as a world on the chart. -/
  zeros : World
  /-- The zero set is closed under the fold at resolution `n`. -/
  closed : ∀ z, zeros z → zeros (foldAt n z)
  /-- Every zero lies inside the open strip `0 < x < 2n`. -/
  strip : ∀ z, zeros z → 0 < z.x ∧ z.x < 2 * n
  /-- The posit: least erasure of the zero set under registration at resolution `n`. -/
  supply : Carrier.LeastErasureC (regChartAt n) zeros

/-- THE CLOSURE AT RESOLUTION N: from the posit, every zero is fixed by the fold at resolution `n`. -/
theorem rh_from_the_act_at (n : Int) (A : ActualZerosAt n) : Carrier.RHc (chartAt n) A.zeros :=
  (Carrier.least_erasure_is_the_value_C (regChartAt n)
    (fun x => match decEq ((chartAt n).σ x) x with
      | isTrue h => Or.inl h
      | isFalse h => Or.inr h) A.zeros).mp A.supply

/-- THE STRIP DOES NOT SUPPLY THE BIT: from resolution two on, the pair at `x = n − 1` and `x = n + 1` at height zero
is fold-closed, lies inside the open strip, and is not fixed by the fold. -/
theorem strip_does_not_supply_at (n : Int) (hn : 2 ≤ n) :
    ∃ Z : World, (∀ z, Z z → Z (foldAt n z)) ∧ (∀ z, Z z → 0 < z.x ∧ z.x < 2 * n) ∧
      ¬ Carrier.RHc (chartAt n) Z :=
  have h0 : (0 : Int) ≤ n := Int.le_trans (by decide : (0 : Int) ≤ 2) hn
  have hlo : n - 1 < n := Int.sub_lt_self n (by decide : (0 : Int) < 1)
  have hle : n ≤ 2 * n :=
    Eq.subst (motive := fun y => n ≤ y) (int_two_mul n).symm
      (Int.le_add_of_nonneg_right h0)
  have hs : 0 < ((n - 1, 0) : Pt).x ∧ ((n - 1, 0) : Pt).x < 2 * n :=
    (Int.sub_pos_of_lt (Int.lt_of_lt_of_le (by decide : (1 : Int) < 2) hn),
     Int.lt_of_lt_of_le hlo hle)
  have hs' : 0 < ((n + 1, 0) : Pt).x ∧ ((n + 1, 0) : Pt).x < 2 * n :=
    Eq.subst (motive := fun w : Pt => 0 < w.x ∧ w.x < 2 * n) (foldAt_pair n 0).1
      (foldAt_strip n _ hs)
  (fun w => w = (n - 1, 0) ∨ w = (n + 1, 0),
   fun w hw => Or.elim hw
     (fun e => Or.inr ((congrArg (foldAt n) e).trans (foldAt_pair n 0).1))
```

```
    (fun e => Or.inl ((congrArg (foldAt n) e).trans (foldAt_pair n 0).2)),
  fun w hw => Or.elim hw
    (fun e => Eq.subst (motive := fun v : Pt => 0 < v.x ∧ v.x < 2 * n) e.symm hs)
    (fun e => Eq.subst (motive := fun v : Pt => 0 < v.x ∧ v.x < 2 * n) e.symm hs'),
  fun h => Int.lt_irrefl n (Eq.subst (motive := fun y => y < n)
    ((foldAt_fixed_iff n (n - 1, 0)).mp (h (n - 1, 0) (Or.inl rfl))) hlo))

/-- THE PAIR OUTSIDE THE CLOSED STRIP: at resolution one an offset of at least two places the pair outside
`0 ≤ x ≤ 2`. -/
theorem pair_outside_the_closed_strip (k : Int) (hk : 2 ≤ k) : 1 - k < 0 ∧ 2 < 1 + k :=
  (Int.sub_neg_of_lt (Int.lt_of_lt_of_le (by decide : (1 : Int) < 2) hk),
   Int.lt_of_lt_of_le (by decide : (2 : Int) < 1 + 2) (Int.add_le_add_left hk 1))

/-! ### XXV.c · The readings of the root, joined -/

/-- THE READINGS OF THE ROOT, JOINED: the constructed root is the proposition `0 < 1`; it has a self-grounding supply
with an act; read uniformly on the worlds it forces nothing; read at the zeros it is the hypothesis; and it does not
hold of every domain, since a domain whose actuation is zero refutes it. -/
theorem root_readings_joined :
    (Root Unit (fun _ => 1) ↔ RootAct) ∧ Nonempty (SelfGrounding (Root Unit (fun _ => 1))) ∧
    ¬ Forces (fun _ => Root Unit (fun _ => 1)) ∧ (∀ Z : World, RootAtZeros Z ↔ RH Z) ∧
    ¬ ∀ (U : Type) (ΔE : U → Int), Root U ΔE :=
  ((fun h => h (), fun h _ => h), ((Unit, (), fun _ => constructed_root_holds)),
   keyless_forces_nothing_free _ (fun _ => constructed_root_holds),
   root_at_zeros_is_the_hypothesis,
   fun h => absurd (h Unit (fun _ => 0) ()) (by decide : ¬ ((0 : Int) < 0)))

/-- THE LOCK ON THE CONSTRUCTED ROOT: the lock, with the root taken to be the constructed root and its supply the unit
act. -/
theorem the_lock_on_the_constructed_root :
    Root Unit (fun _ => 1) ∧
    Root Unit (fun _ => 1) ∧
    (RH W1 ∧ FoldClosed W2 ∧ ¬ RH W2) ∧
    ¬ Forces (fun _ => Root Unit (fun _ => 1)) ∧
    (∀ Z : World, RootAtZeros Z ↔ LeastErasure Z) ∧
    ((FoldClosed W1 ∧ RootAtZeros W1) ∧ (FoldClosed W2 ∧ ¬ RootAtZeros W2)) ∧
    (∀ Z : World, LeastErasure Z ↔ RH Z) ∧
    (∀ A : ActualZeros, RH A.zeros) ∧
    (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)) :=
  the_lock (Unit, (), fun _ => constructed_root_holds)

/-! ### XXV.d · The rejection, computed -/

/-- The first off-line pair of a list of pairs, found by a search from the front. -/
def firstOff : List (Int × Nat) → Option (Int × Nat)
  | [] => none
  | p :: ps => if p.1 = 0 then firstOff ps else some p

/-- THE SEARCH IS TOTAL: it returns nothing and every pair has offset zero, or it returns a pair of the list with a
nonzero offset. -/
theorem firstOff_spec (ps : List (Int × Nat)) :
    (firstOff ps = none ∧ ∀ p ∈ ps, p.1 = 0) ∨ ∃ p, firstOff ps = some p ∧ p ∈ ps ∧ p.1 ≠ 0 :=
  match ps with
  | [] => Or.inl (rfl, fun _ h => nomatch h)
  | p :: qs =>
    if e : p.1 = 0 then
      have hc : firstOff (p :: qs) = firstOff qs := if_pos e
      match firstOff_spec qs with
      | Or.inl (hn, hz) => Or.inl (hc.trans hn, fun q hq => match q, hq with
          | _, List.Mem.head _ => e
          | _, List.Mem.tail _ hq' => hz _ hq')
      | Or.inr (q, hq, hm, hne) => Or.inr (q, hc.trans hq, List.Mem.tail p hm, hne)
    else
      Or.inr (p, if_neg e, List.Mem.head qs, e)

/-- AN OFFSET IS READ OFF ITS POINT: the point at `x = 1 − a` lies on the line only when `a = 0`. -/
theorem offset_off_line (a : Int) (t : Nat) (h : a ≠ 0) : ¬ onLine (1 - a, t) :=
  fun e => h (((Int.sub_sub_self 1 a).symm.trans (congrArg (fun y => 1 - y) e)).trans (by decide))

/-- THE REJECTION, COMPUTED: if least erasure fails on a finite configuration, the search returns a pair `(k, t)` of
the configuration with `k ≠ 0` whose point `(1 − k, t)` lies in the world and off the line. -/
theorem rejection_is_computed (C : FinCfg) (h : ¬ LeastErasure C.world) :
    ∃ p, firstOff C.pairs = some p ∧ p ∈ C.pairs ∧ p.1 ≠ 0 ∧ C.world (1 - p.1, p.2) ∧
      ¬ onLine (1 - p.1, p.2) :=
  match firstOff_spec C.pairs with
  | Or.inl (_, hz) => absurd ((least_erasure_is_the_value C.world).mpr (fun _ hz' =>
      Or.elim hz' (fun hx => hx.1) (fun (p, hp, hk, _) => absurd (hz p hp) hk))) h
  | Or.inr (p, hf, hm, hk) => (p, hf, hm, hk, Or.inr (p, hm, hk, Or.inl rfl),
    offset_off_line p.1 p.2 hk)

/-- THE SEARCH DECIDES LEAST ERASURE: a finite configuration has least erasure exactly when the search returns
nothing. -/
theorem least_erasure_iff_search_empty (C : FinCfg) : LeastErasure C.world ↔ firstOff C.pairs = none :=
  (fun hle => match firstOff_spec C.pairs with
    | Or.inl (hn, _) => hn
    | Or.inr (p, _, hm, hk) =>
      absurd ((least_erasure_is_the_value C.world).mp hle _ (Or.inr (p, hm, hk, Or.inl rfl)))
        (offset_off_line p.1 p.2 hk),
   fun hn => match firstOff_spec C.pairs with
    | Or.inl (_, hz) => (least_erasure_is_the_value C.world).mpr (fun _ hz' =>
      Or.elim hz' (fun hx => hx.1) (fun (p, hp, hk, _) => absurd (hz p hp) hk))
    | Or.inr (_, hs, _, _) => Option.noConfusion (hn.symm.trans hs))

/-! ### XXV.e · The posit, the readings, the basis, the recursion, the certified world, the ledger -/

/-- THE POSIT IS AN ACT: at the actual zeros the posit has a self-grounding supply with an act. -/
theorem the_posit_is_a_deed (A : ActualZeros) : ∃ G : SelfGrounding (LeastErasure A.zeros), Nonempty G.Act :=
  ((Unit, (), fun _ => A.supply), ((⟩))

/-- A READING KEYED ON THE TWINS IS NOT RETURNED: a reading true on W1 and false on W2f agrees with no reading of the
record on every fold-closed world. -/
theorem keyed_reading_not_returned (P : World → Prop) (h1 : P W1) (h2 : ¬ P W2f) (g : World → Prop)
    (hg : RespectsRecord g) : ¬ ∀ Z, FoldClosed Z → (g Z ↔ P Z) :=
  fun h => h2 ((h W2f W2f_closed).mp ((hg W1 W2f same_record_f).mp ((h W1 W1_closed).mpr h1)))

/-- NO READING OF THE RECORD RETURNS ANY READING: lossless registration, displacement zero, no left zero, stability
and least erasure each hold on W1 and fail on W2f, so no reading of the record agrees with any of them. -/
theorem no_record_reading_returns_any_reading (g : World → Prop) (hg : RespectsRecord g) :
    ¬ (∀ Z, FoldClosed Z → (g Z ↔ Lossless Z)) ∧ ¬ (∀ Z, FoldClosed Z → (g Z ↔ DepthZero Z)) ∧
    ¬ (∀ Z, FoldClosed Z → (g Z ↔ ¬ Left Z)) ∧ ¬ (∀ Z, FoldClosed Z → (g Z ↔ Stable Z)) ∧
    ¬ (∀ Z, FoldClosed Z → (g Z ↔ LeastErasure Z)) :=
  (keyed_reading_not_returned Lossless
    (fun z hz => Eq.subst (motive := fun w => reg w = w) (Eq.symm hz) rfl)
    (fun h => absurd (congrArg Pt.x (h (0, 14) (Or.inl rfl))) (by decide : ¬ ((1 : Int) = 0))) g hg,
   keyed_reading_not_returned DepthZero
    (fun z hz => Eq.subst (motive := fun w => oddPart w = 0) (Eq.symm hz) rfl)
    (fun h => absurd (h (0, 14) (Or.inl rfl)) (by decide : ¬ (oddPart (0, 14) = 0))) g hg,
   keyed_reading_not_returned (fun Z => ¬ Left Z)
    (fun (z, hz, hx) => Eq.subst (motive := fun w : Pt => ¬ w.x < 1) (Eq.symm hz)
      (by decide : ¬ (((1, 14) : Pt).x < 1)) hx)
    (fun h => h ((0, 14), Or.inl rfl, by decide)) g hg,
   keyed_reading_not_returned Stable
    (fun z hz => Eq.subst (motive := fun w => N1 w ≤ N0 w) (Eq.symm hz) (by decide))
    (fun h => absurd (h (0, 14) (Or.inl rfl)) (by decide : ¬ (N1 (0, 14) ≤ N0 (0, 14)))) g hg,
   keyed_reading_not_returned LeastErasure ((least_erasure_is_the_value W1).mpr W1_rh)
    (fun h => W2f_not_rh ((least_erasure_is_the_value W2f).mp h)) g hg)

/-- THE PRIMES ARE A FREE BASIS: every assignment of integers to the primes extends to exactly one completely
additive function. -/
theorem primes_are_a_free_basis (a : Nat → Int) :
    ∃ f, CompletelyAdditive f ∧ (∀ p, isPrime p → f p = a p) ∧
      ∀ g, CompletelyAdditive g → (∀ p, isPrime p → g p = a p) → ∀ n, 0 < n → g n = f n :=
  (extendAssignment a, primes_admit_every_assignment a)

/-- LEAST ERASURE IS THE RECURSION: on every world least erasure holds exactly when the hypothesis is implied by its
own denial; the line is decided point by point, so no classical step enters. -/
theorem least_erasure_iff_recursion (Z : World) : LeastErasure Z ↔ SelfVerifyingP (RH Z) :=
  (fun h _ => (least_erasure_is_the_value Z).mp h,
   fun h => (least_erasure_is_the_value Z).mpr (fun z hz =>
     match Int.decEq z.x 1 with
     | isTrue e => e
     | isFalse ne => h (fun r => ne (r z hz)) z hz))

/-- THE CERTIFIED WORLD IS FOLD-CLOSED: the world certified to height `T` is closed under the fold, and a fold-closed
world agrees with it to `T` and carries an off-line pair above. -/
theorem certified_height_never_forces_closed (T : Nat) :
    FoldClosed (LineBelow T) ∧
    (RH (LineBelow T) ∧ FoldClosed (TwinAbove T) ∧ ¬ RH (TwinAbove T) ∧
      ∀ z, z.t ≤ T → (TwinAbove T z ↔ LineBelow T z)) :=
  (fun z hz => ((congrArg (fun y => 2 - y) hz.1).trans (by decide), hz.2),
   fun _ hz => hz.1,
   fun z hz => match hz with
     | Or.inl hl => Or.inl ((congrArg (fun y => 2 - y) hl.1).trans (by decide), hl.2)
     | Or.inr (Or.inl e) => Or.inr (Or.inr ((congrArg fold e).trans rfl))
     | Or.inr (Or.inr e) => Or.inr (Or.inl ((congrArg fold e).trans rfl)),
   fun h => absurd (h (0, T + 1) (Or.inr (Or.inl rfl))) (by decide : ¬ ((0 : Int) = 1)),
   fun z hz => (fun h => match h with
     | Or.inl hl => hl
     | Or.inr (Or.inl e) =>
       absurd (Eq.subst (motive := fun w : Pt => w.t ≤ T) e hz)
         (Nat.not_succ_le_self T)
     | Or.inr (Or.inr e) =>
       absurd (Eq.subst (motive := fun w : Pt => w.t ≤ T) e hz)
         (Nat.not_succ_le_self T),
    fun h => Or.inl h))

/-- The statement each route of the ledger carries: the theorem its status names. -/
def routeClaim : Route → Prop
  | .ladderFromRecord => ∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)
  | .foundationAsSystem => Sound lineTheory ∧ lineTheory.Prov () ∧ LeastErasure (lineTheoryReads.world ())
  | .placement => ∀ T : Theory, RungOnLadder T → Sound T →
      (∀ s, T.Comp s → T.Prov s) ∧ (∀ s, T.Prov s → T.True_ s) ∧ (∀ s, T.Comp s → T.True_ s)
  | .groundByAct => ∀ A : ActualZeros, RH A.zeros
  | .independence => ∀ S : Setting, ¬ S.Prov S.hyp → ¬ S.Prov (¬ S.hyp) → S.hyp
  | .realPartCertified => ∀ T : Nat, RH (LineBelow T) ∧ FoldClosed (TwinAbove T) ∧ ¬ RH (TwinAbove T) ∧
      ∀ z, z.t ≤ T → (TwinAbove T z ↔ LineBelow T z)

/-- EVERY ROUTE CARRIES ITS THEOREM: each of the six routes is backed by the theorem its ledger entry names. -/
theorem every_route_carries_its_theorem : ∀ r : Route, routeClaim r := fun r =>
  match r with
  | .ladderFromRecord => unicorn_block
  | .foundationAsSystem => a_sound_theory_may_prove_the_line
  | .placement => placement
  | .groundByAct => rh_from_the_act
  | .independence => independence_forces_truth
  | .realPartCertified => certified_height_never_forces

/-! ### XXV.f · The tenth falsifier, barred by the act -/

/-- THE TENTH IS THE REFUTER: on every configuration a computed point off the line is exactly the failure of the line. -/
theorem the_tenth_is_the_refuter (Z : World) : OffLine Z ↔ ¬ RH Z :=
  (fun (z, hz, hn) h => hn (h z hz), not_rh_has_offline_witness Z)
```

```
/-- THE TENTH IS BARRED BY THE ACT: on the zero set the act supplies, no point lies off the line; the one refuter of the
value does not exist there. -/
theorem the_tenth_is_barred_by_the_act (A : ActualZeros) : ¬ OffLine A.zeros :=
  fun (z, hz, hn) => hn (rh_from_the_act A z hz)

/-- THE KINETIC BAR: a reading supplied on the actual zero set gives the line there, and with it the refuter's absence;
the formal side leaves the search open, and the field the act supplies closes it. -/
theorem the_kinetic_bar (A : ActualZeros) : RH A.zeros ∧ ¬ OffLine A.zeros :=
  (rh_from_the_act A, the_tenth_is_barred_by_the_act A)


/-! ## XXVI · The closure, bound whole

One theorem binds the closure, for every self-grounding root: the two-part reading of section XIX.f, the lock of
section XXIV, the socket of section XXII, the irreducible cut of section XIX.c, the two denials and the witness of
section XXII.c, and the bar of section XXV.f. Every conjunct is a theorem above; this section adds their conjunction
and no content. -/

/-- THE CLOSURE, BOUND IN ONE THEOREM. For every self-grounding root: from the posit the hypothesis follows, no reading
of the record supplies it, the posit is the hypothesis, and nothing weaker forces the line; the lock; the field of the
act can be filled at a fold-closed configuration exactly where the hypothesis holds; no admissible premise decides and
least erasure is not admissible; the two denials; the witness forced by the act; and on the zero set the act supplies
the hypothesis holds and no point lies off the line. -/
theorem the_capstone {root : Prop} (G : SelfGrounding root) :
    ((∀ A : ActualZeros, RH A.zeros) ∧
     (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z)) ∧
     (∀ Z : World, LeastErasure Z ↔ RH Z) ∧
     (Forces RH ∧ ∀ A : World → Prop, Forces A → ∀ Z, FoldClosed Z → A Z → RH Z)) ∧
    (Root Unit (fun _ => 1) ∧
     root ∧
     (RH W1 ∧ FoldClosed W2 ∧ ¬ RH W2) ∧
     ¬ Forces (fun _ => root) ∧
     (∀ Z : World, RootAtZeros Z ↔ LeastErasure Z) ∧
     ((FoldClosed W1 ∧ RootAtZeros W1) ∧ (FoldClosed W2 ∧ ¬ RootAtZeros W2)) ∧
     (∀ Z : World, LeastErasure Z ↔ RH Z) ∧
     (∀ A : ActualZeros, RH A.zeros) ∧
     (∀ g : World → Prop, RespectsRecord g → ¬ ∀ Z, FoldClosed Z → (g Z ↔ RH Z))) ∧
    (∀ Z : World, FoldClosed Z → ((∃ S : ActualZeros, S.zeros = Z) ↔ RH Z)) ∧
    ((∀ A : World → Prop, Admissible A → ¬ ∀ Z, FoldClosed Z → (A Z ↔ RH Z)) ∧ ¬ Admissible LeastErasure) ∧
    ((∀ C : Prop, G.Act → C → root) ∧
     (G.Act → ¬ root → False) ∧
     (∀ Z : World, ¬ RH Z → ¬ ∃ G' : SelfGrounding (RH Z), Nonempty G'.Act) ∧
     (∀ W : TWorld, SeededWitness W ↔ BoundT W) ∧
     (root ∧ FoldClosed W2f ∧ SameRecord W1 W2f ∧ TimelessT WTwin ∧ ¬ RH W2f ∧
       (¬ ∃ G' : SelfGrounding (RH W2f), Nonempty G'.Act) ∧ ¬ SeededWitness WTwin) ∧
     SeededWitness WOn ∧
     ¬ Forces (fun _ => root) ∧
     (∀ A : ActualZeros, (∃ G' : SelfGrounding (RH A.zeros), Nonempty G'.Act) ∧
       SeededWitness (fun _ => A.zeros) ∧ (¬ RH A.zeros → False))) ∧
    ((∀ A : ActualZeros, RH A.zeros ∧ LeastErasure A.zeros ∧ ¬ OffLine A.zeros ∧
      (∀ z, A.zeros z ↔ recordOf A.zeros z) ∧ (∀ Q : World → Prop, (∀ Z, RH Z → Q Z) → Q A.zeros)) ∧
     (∀ (A : ActualZeros) (c : Computation), c.Reads A → ∀ z, z ∈ c.reports → onLine z) ∧
     (∀ (c : Computation) (z : Pt), z ∈ c.reports → ¬ onLine z → ¬ ∃ A : ActualZeros, c.Reads A) ∧
     ¬ (∀ c : Computation, ∀ z, z ∈ c.reports → onLine z)) ∧
    (∀ A : ActualZeros, RH A.zeros ∧ ¬ OffLine A.zeros) :=
  ⟨reader_frame, the_lock G, fun Z hZ => (socket_is_the_value Z hZ).1,
   ⟨triaxial_cut_irreducible.2.2.2.1, triaxial_cut_irreducible.2.2.2.2.2.2.1⟩,
   two_denials G, the_witness_forced_by_the_act, the_kinetic_bar⟩

end PrimeFreedom

/-! ## Cones, printed: sections I to XVI -/

#print axioms PrimeFreedom.arrow_exists
#print axioms PrimeFreedom.aperture_one_bit_wide
#print axioms PrimeFreedom.prime_fibre
#print axioms PrimeFreedom.prime_off_seat
#print axioms PrimeFreedom.freedom_is_exactly_two
#print axioms PrimeFreedom.seat_is_zero
#print axioms PrimeFreedom.exists_prime_dvd
#print axioms PrimeFreedom.leastDivisor_prime
#print axioms PrimeFreedom.determined_by_primes
#print axioms PrimeFreedom.fold_preserves_offline
#print axioms PrimeFreedom.offline_zero_quadruple
#print axioms PrimeFreedom.not_rh_has_offline_witness
#print axioms PrimeFreedom.denial_posits_the_orbit
#print axioms PrimeFreedom.record_blind_at_every_scale
#print axioms PrimeFreedom.euclid_lemma
#print axioms PrimeFreedom.pExp_mul
#print axioms PrimeFreedom.padicMeasure_additive
#print axioms PrimeFreedom.prime_freedom_independent
#print axioms PrimeFreedom.primes_base_of_freedom
#print axioms PrimeFreedom.arrow_multiplicative
#print axioms PrimeFreedom.arrow_at_prime
#print axioms PrimeFreedom.finite_never_forces
#print axioms PrimeFreedom.limit_not_forced
#print axioms PrimeFreedom.nothing_escapes_one_cut
#print axioms PrimeFreedom.sides_together
#print axioms PrimeFreedom.rh_iff_no_left
#print axioms PrimeFreedom.record_decides_nothing
#print axioms PrimeFreedom.unicorn_block
#print axioms PrimeFreedom.keyless_forces_nothing
#print axioms PrimeFreedom.least_erasure_is_the_value
#print axioms PrimeFreedom.supply_iff
#print axioms PrimeFreedom.faces_are_one
#print axioms PrimeFreedom.rh_from_the_act_generic
#print axioms PrimeFreedom.rh_from_the_act
#print axioms PrimeFreedom.rh_ground_closure_complete

#print axioms PrimeFreedom.primes_exist
#print axioms PrimeFreedom.primes_exist_forces_nothing
#print axioms PrimeFreedom.prime_freedom_forces_nothing
#print axioms PrimeFreedom.arrow_forces_nothing
#print axioms PrimeFreedom.free_basis_coexists_with_offline_world
#print axioms PrimeFreedom.fold_off_line_stays_off
#print axioms PrimeFreedom.positivity_on_zero_side
#print axioms PrimeFreedom.least_erasure_is_positivity
#print axioms PrimeFreedom.prime_witness_iff
#print axioms PrimeFreedom.rh_from_prime_witness
#print axioms PrimeFreedom.positivity_is_keyed
#print axioms PrimeFreedom.freedom_does_not_pick_the_sign
#print axioms PrimeFreedom.prime_witness_ledger
#print axioms PrimeFreedom.posit_is_the_conclusion
#print axioms PrimeFreedom.rh_from_prime_act
#print axioms PrimeFreedom.acts_are_one
#print axioms PrimeFreedom.record_decides_nothing_free
#print axioms PrimeFreedom.unicorn_block_free
#print axioms PrimeFreedom.keyless_forces_nothing_free
#print axioms PrimeFreedom.arrow_forces_nothing_free
#print axioms PrimeFreedom.least_erasure_reads_past_the_record_free
#print axioms PrimeFreedom.positivity_is_keyed_free

/-! ## Cones, pinned: sections VII to XIII (a compile in which any pinned cone changes fails) -/
/-- info: 'PrimeFreedom.least_erasure_is_the_value' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_is_the_value
/-- info: 'PrimeFreedom.least_erasure_is_positivity' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_is_positivity
/-- info: 'PrimeFreedom.spend_is_the_line' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.spend_is_the_line
/-- info: 'PrimeFreedom.record_decides_nothing_free' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.record_decides_nothing_free
/-- info: 'PrimeFreedom.keyless_forces_nothing_free' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.keyless_forces_nothing_free
/-- info: 'PrimeFreedom.rh_from_the_act' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.rh_from_the_act
/-- info: 'PrimeFreedom.rh_from_prime_act' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.rh_from_prime_act
/-- info: 'PrimeFreedom.acts_are_one' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.acts_are_one
/-- info: 'PrimeFreedom.primes_base_of_freedom' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.primes_base_of_freedom
/-- info: 'PrimeFreedom.spend_is_not_the_free_basis' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.spend_is_not_the_free_basis
/-- info: 'PrimeFreedom.rh_on_the_spent_bit' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.rh_on_the_spent_bit
/-- info: 'PrimeFreedom.prime_arc_sealed' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.prime_arc_sealed
/-- info: 'PrimeFreedom.rh_is_the_weakest_forcing_premise' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.rh_is_the_weakest_forcing_premise
/-- info: 'PrimeFreedom.li_prefix_never_forces' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.li_prefix_never_forces
/-- info: 'PrimeFreedom.rh_from_the_sign' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.rh_from_the_sign
/-- info: 'PrimeFreedom.rh_iff_the_sign' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.rh_iff_the_sign
/-- info: 'PrimeFreedom.spends_are_one' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.spends_are_one
/-- info: 'PrimeFreedom.line_not_self_grounding' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.line_not_self_grounding
/-- info: 'PrimeFreedom.sign_realized_both_ways' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.sign_realized_both_ways
/-- info: 'PrimeFreedom.the_vestigial_posit' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.the_vestigial_posit
/-- info: 'PrimeFreedom.exactly_one_face_is_keyed' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.exactly_one_face_is_keyed
/-- info: 'PrimeFreedom.arrow_is_not_the_line' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.arrow_is_not_the_line
/-- info: 'PrimeFreedom.template_binds_iff_seed' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.template_binds_iff_seed
/-- info: 'PrimeFreedom.the_seed_is_the_spend' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.the_seed_is_the_spend
/-- info: 'PrimeFreedom.the_template_plugged_in' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_template_plugged_in
/-! ## Cones, pinned: section XVI -/
/-- info: 'PrimeFreedom.fold_negates_odd' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.fold_negates_odd
/-- info: 'PrimeFreedom.rh_iff_even_eigenspace' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.rh_iff_even_eigenspace
/-- info: 'PrimeFreedom.record_blind_to_odd' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.record_blind_to_odd
/-- info: 'PrimeFreedom.side_odd_off_line' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.side_odd_off_line
/-- info: 'PrimeFreedom.record_never_reads_the_side' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.record_never_reads_the_side
/-- info: 'PrimeFreedom.colocation_is_a_calibration' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.colocation_is_a_calibration
/-- info: 'PrimeFreedom.calibration_realized_both_ways' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.calibration_realized_both_ways
/-- info: 'PrimeFreedom.recursion_fails_on_the_twin' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.recursion_fails_on_the_twin
/-- info: 'PrimeFreedom.least_erasure_is_the_recursion' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_is_the_recursion
/-- info: 'PrimeFreedom.the_mirror_at_minus_one' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.the_mirror_at_minus_one

/-! ## Cones, printed: section XVII -/
#print axioms PrimeFreedom.admissible_transfers
#print axioms PrimeFreedom.no_admissible_triad_forces
#print axioms PrimeFreedom.no_admissible_coalition_forces
#print axioms PrimeFreedom.spend_is_not_admissible
#print axioms PrimeFreedom.three_axis_lock
#print axioms PrimeFreedom.freedom_alone_open
#print axioms PrimeFreedom.certified_height_never_forces
#print axioms PrimeFreedom.certified_worlds_share_the_record_below
#print axioms PrimeFreedom.HeatFlow.disc_flow
#print axioms PrimeFreedom.HeatFlow.forward_preserves
#print axioms PrimeFreedom.HeatFlow.erasure_finite
#print axioms PrimeFreedom.HeatFlow.lam_nonneg
#print axioms PrimeFreedom.HeatFlow.real_at_lam
#print axioms PrimeFreedom.HeatFlow.lam_least
#print axioms PrimeFreedom.HeatFlow.lam_zero_iff_real
#print axioms PrimeFreedom.HeatFlow.de_bruijn_tight
#print axioms PrimeFreedom.HeatFlow.collision
#print axioms PrimeFreedom.HeatFlow.disc3_step
```

```
#print axioms PrimeFreedom.HeatFlow.disc3_strict
#print axioms PrimeFreedom.HeatFlow.disc3_monotone
#print axioms PrimeFreedom.HeatFlow.cubic_forward_preserves
#print axioms PrimeFreedom.HeatFlow.flow_injective
#print axioms PrimeFreedom.HeatFlow.certificate_two_worlds
#print axioms PrimeFreedom.HeatFlow.certificate_decides_nothing
#print axioms PrimeFreedom.HeatFlow.certification_never_forces
#print axioms PrimeFreedom.HeatFlow.zero_slack
#print axioms PrimeFreedom.HeatFlow.backward_not_forced
#print axioms PrimeFreedom.HeatFlow.family_least_erasure
#print axioms PrimeFreedom.heat_bit_is_one_inequality
#print axioms PrimeFreedom.family_bit_is_one_inequality
#print axioms PrimeFreedom.heat_model_reads_as_the_carrier
#print axioms PrimeFreedom.Liouville.lam_mult
#print axioms PrimeFreedom.Liouville.lam_flips_at_primes
#print axioms PrimeFreedom.Liouville.polya_holds_to_200
#print axioms PrimeFreedom.liouville_is_the_sign_arrow
#print axioms PrimeFreedom.rh_from_faithful
#print axioms PrimeFreedom.faithful_is_the_bit
#print axioms PrimeFreedom.the_posit_in_every_coordinate
#print axioms PrimeFreedom.modes
#print axioms PrimeFreedom.lossless_iff_rh
#print axioms PrimeFreedom.stable_iff_rh
#print axioms PrimeFreedom.five_readings_agree
#print axioms PrimeFreedom.no_record_reading_returns_any_face
#print axioms PrimeFreedom.same_for_every_reader
#print axioms PrimeFreedom.no_private_bit
#print axioms PrimeFreedom.spend_has_no_reader
#print axioms PrimeFreedom.the_harvest

/-! ## Cones, pinned: section XVII -/
/-- info: 'PrimeFreedom.no_admissible_coalition_forces' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.no_admissible_coalition_forces
/-- info: 'PrimeFreedom.spend_is_not_admissible' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.spend_is_not_admissible
/-- info: 'PrimeFreedom.certified_height_never_forces' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.certified_height_never_forces
/-- info: 'PrimeFreedom.HeatFlow.lam_nonneg' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.HeatFlow.lam_nonneg
/-- info: 'PrimeFreedom.HeatFlow.lam_zero_iff_real' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.HeatFlow.lam_zero_iff_real
/-- info: 'PrimeFreedom.HeatFlow.certificate_decides_nothing' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.HeatFlow.certificate_decides_nothing
/-- info: 'PrimeFreedom.HeatFlow.zero_slack' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.HeatFlow.zero_slack
/-- info: 'PrimeFreedom.heat_bit_is_one_inequality' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.heat_bit_is_one_inequality
/-- info: 'PrimeFreedom.liouville_is_the_sign_arrow' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.liouville_is_the_sign_arrow
/-- info: 'PrimeFreedom.Liouville.polya_holds_to_200' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.Liouville.polya_holds_to_200
/-- info: 'PrimeFreedom.the_posit_in_every_coordinate' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.the_posit_in_every_coordinate
/-- info: 'PrimeFreedom.five_readings_agree' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.five_readings_agree
/-- info: 'PrimeFreedom.spend_has_no_reader' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.spend_has_no_reader
/-- info: 'PrimeFreedom.the_harvest' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_harvest

/-! ## Cones, printed: section XVIII -/

#print axioms PrimeFreedom.placement
#print axioms PrimeFreedom.soundness_is_load_bearing
#print axioms PrimeFreedom.ground_exceeds_ladder
#print axioms PrimeFreedom.independent_axioms_are_separate_bits
#print axioms PrimeFreedom.root_is_keyless
#print axioms PrimeFreedom.keyless_crosses
#print axioms PrimeFreedom.root_decides_no_keyed
#print axioms PrimeFreedom.choice_is_keyed
#print axioms PrimeFreedom.root_does_not_cross_choice
#print axioms PrimeFreedom.line_is_keyed_over_worlds
#print axioms PrimeFreedom.root_does_not_cross_the_line
#print axioms PrimeFreedom.refutation_is_one_point
#print axioms PrimeFreedom.cant_refute_seals
#print axioms PrimeFreedom.cant_refute_seals_dec
#print axioms PrimeFreedom.rh_iff_cant_refute
#print axioms PrimeFreedom.independence_forces_truth
#print axioms PrimeFreedom.cant_prove_does_not_seal_false
#print axioms PrimeFreedom.cant_asymmetry
#print axioms PrimeFreedom.round_trip_identity
#print axioms PrimeFreedom.absolute_returns_unchanged
#print axioms PrimeFreedom.trip_adds_presence_only
#print axioms PrimeFreedom.massless_arrow
#print axioms PrimeFreedom.any_true_premise_serves
#print axioms PrimeFreedom.the_line_round_trips
#print axioms PrimeFreedom.ladder_blocked
#print axioms PrimeFreedom.the_road

/-! ## Cones, pinned: section XVIII -/
/-- info: 'PrimeFreedom.placement' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.placement
/-- info: 'PrimeFreedom.soundness_is_load_bearing' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.soundness_is_load_bearing
/-- info: 'PrimeFreedom.ground_exceeds_ladder' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.ground_exceeds_ladder
/-- info: 'PrimeFreedom.root_decides_no_keyed' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.root_decides_no_keyed
/-- info: 'PrimeFreedom.root_does_not_cross_the_line' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.root_does_not_cross_the_line
/-- info: 'PrimeFreedom.cant_refute_seals' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.cant_refute_seals
/-- info: 'PrimeFreedom.rh_iff_cant_refute' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.rh_iff_cant_refute
/-- info: 'PrimeFreedom.independence_forces_truth' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.independence_forces_truth
/-- info: 'PrimeFreedom.cant_prove_does_not_seal_false' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.cant_prove_does_not_seal_false
/-- info: 'PrimeFreedom.round_trip_identity' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.round_trip_identity
/-- info: 'PrimeFreedom.massless_arrow' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.massless_arrow
/-- info: 'PrimeFreedom.ladder_blocked' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.ladder_blocked
/-- info: 'PrimeFreedom.the_road' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_road

/-! ## Cones, printed: section XIX -/

#print axioms PrimeFreedom.vocabulary_law
#print axioms PrimeFreedom.every_face_proves_every_face
#print axioms PrimeFreedom.chart_faces_prove_each_other
#print axioms PrimeFreedom.fold_fold
#print axioms PrimeFreedom.fold_law_admissible
#print axioms PrimeFreedom.same_record_eq
#print axioms PrimeFreedom.record_reading_admissible
#print axioms PrimeFreedom.admissible_const
#print axioms PrimeFreedom.keyless_denial_respects
#print axioms PrimeFreedom.admissible_not
#print axioms PrimeFreedom.admissible_and
#print axioms PrimeFreedom.admissible_or
#print axioms PrimeFreedom.admissible_never_decides
#print axioms PrimeFreedom.coalition_admissible
#print axioms PrimeFreedom.no_coalition_decides
#print axioms PrimeFreedom.triaxial_cut_irreducible
#print axioms PrimeFreedom.ladder_proof_lands_on_least_erasure
#print axioms PrimeFreedom.ladder_proof_iff_least_erasure
#print axioms PrimeFreedom.lineTheory_sound
#print axioms PrimeFreedom.a_sound_theory_may_prove_the_line
#print axioms PrimeFreedom.route_ledger_is_computed
#print axioms PrimeFreedom.route_ledger_counts
#print axioms PrimeFreedom.route_status_total
#print axioms PrimeFreedom.blocked_iff_theorem
#print axioms PrimeFreedom.reader_frame
#print axioms PrimeFreedom.the_front

/-! ## Cones, pinned: section XIX -/
/-- info: 'PrimeFreedom.vocabulary_law' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.vocabulary_law
/-- info: 'PrimeFreedom.every_face_proves_every_face' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.every_face_proves_every_face
/-- info: 'PrimeFreedom.chart_faces_prove_each_other' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.chart_faces_prove_each_other
/-- info: 'PrimeFreedom.record_reading_admissible' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.record_reading_admissible
/-- info: 'PrimeFreedom.admissible_not' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.admissible_not
/-- info: 'PrimeFreedom.admissible_and' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.admissible_and
/-- info: 'PrimeFreedom.admissible_or' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.admissible_or
/-- info: 'PrimeFreedom.admissible_never_decides' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.admissible_never_decides
/-- info: 'PrimeFreedom.coalition_admissible' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.coalition_admissible
/-- info: 'PrimeFreedom.no_coalition_decides' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.no_coalition_decides
/-- info: 'PrimeFreedom.triaxial_cut_irreducible' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.triaxial_cut_irreducible
/-- info: 'PrimeFreedom.ladder_proof_lands_on_least_erasure' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.ladder_proof_lands_on_least_erasure
/-- info: 'PrimeFreedom.ladder_proof_iff_least_erasure' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.ladder_proof_iff_least_erasure
/-- info: 'PrimeFreedom.a_sound_theory_may_prove_the_line' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.a_sound_theory_may_prove_the_line
/-- info: 'PrimeFreedom.route_ledger_is_computed' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.route_ledger_is_computed
/-- info: 'PrimeFreedom.blocked_iff_theorem' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.blocked_iff_theorem
/-- info: 'PrimeFreedom.reader_frame' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.reader_frame
/-- info: 'PrimeFreedom.the_front' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.the_front

/-! ## Cones, pinned: section XX -/
/-- info: 'PrimeFreedom.reg_on_line' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.reg_on_line
/-- info: 'PrimeFreedom.record_rh' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.record_rh
/-- info: 'PrimeFreedom.record_has_least_erasure' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.record_has_least_erasure
/-- info: 'PrimeFreedom.record_closed' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.record_closed
/-- info: 'PrimeFreedom.record_carried_by_least_erasure' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.record_carried_by_least_erasure
/-- info: 'PrimeFreedom.admissible_holds_on_the_lossless_world' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.admissible_holds_on_the_lossless_world
/-- info: 'PrimeFreedom.every_reading_holds_on_the_lossless_world' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.every_reading_holds_on_the_lossless_world
/-- info: 'PrimeFreedom.every_coalition_holds_on_the_lossless_world' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.every_coalition_holds_on_the_lossless_world
/-- info: 'PrimeFreedom.record_never_testifies_against' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.record_never_testifies_against
/-- info: 'PrimeFreedom.pair_two_points_one_record' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.pair_two_points_one_record
/-- info: 'PrimeFreedom.offCount_zero_iff' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.offCount_zero_iff
```

```
/-- info: 'PrimeFreedom.fincfg_closed' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.fincfg_closed
/-- info: 'PrimeFreedom.least_erasure_iff_zero_erased' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_iff_zero_erased
/-- info: 'PrimeFreedom.landauer_floor_exact' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.landauer_floor_exact
/-- info: 'PrimeFreedom.price_zero_iff_least_erasure' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.price_zero_iff_least_erasure
/-- info: 'PrimeFreedom.denial_price_linear' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.denial_price_linear
/-- info: 'PrimeFreedom.reversible_commits_nothing' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.reversible_commits_nothing
/-- info: 'PrimeFreedom.least_erasure_iff_no_point_off' depends on axioms: [propext]
  -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_iff_no_point_off
/-- info: 'PrimeFreedom.rejection_is_a_witness' depends on axioms: [propext,
    Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.rejection_is_a_witness
/-- info: 'PrimeFreedom.falsifier_form_constant' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.falsifier_form_constant
/-- info: 'PrimeFreedom.act_reenacts_root' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.act_reenacts_root
/-- info: 'PrimeFreedom.root_does_not_cross_the_denial' does not depend on any axioms
  -/
#guard_msgs in #print axioms PrimeFreedom.root_does_not_cross_the_denial
/-- info: 'PrimeFreedom.assent_is_the_value' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.assent_is_the_value
/-- info: 'PrimeFreedom.one_shape_two_registers' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.one_shape_two_registers
/-- info: 'PrimeFreedom.freedom_is_given_the_sign_is_spent' depends on axioms:
    [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.freedom_is_given_the_sign_is_spent
/-- info: 'PrimeFreedom.least_erasure_affirmed' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_affirmed

/-! ## Cones, printed: every theorem of sections I to XX whose cone is not printed
    above -/

#print axioms PrimeFreedom.orientation_two_valued
#print axioms PrimeFreedom.orientations_distinct
#print axioms PrimeFreedom.seat_is_one
#print axioms PrimeFreedom.findLeastFrom_correct
#print axioms PrimeFreedom.leastDivisor_spec
#print axioms PrimeFreedom.dvd_remainder_mul
#print axioms PrimeFreedom.leastMulDvd_spec
#print axioms PrimeFreedom.findGt_spec
#print axioms PrimeFreedom.findGt_max
#print axioms PrimeFreedom.pExp_dvd
#print axioms PrimeFreedom.two_pow_ge
#print axioms PrimeFreedom.pow_dvd_bound
#print axioms PrimeFreedom.pExp_le_of_dvd
#print axioms PrimeFreedom.mul_mul_mul_comm_nat
#print axioms PrimeFreedom.pExp_self
#print axioms PrimeFreedom.pExp_eq_zero_of_not_dvd
#print axioms PrimeFreedom.pExp_one
#print axioms PrimeFreedom.pExp_other
#print axioms PrimeFreedom.signArrow_add
#print axioms PrimeFreedom.fold_fixed_iff
#print axioms PrimeFreedom.reg_fixes_line
#print axioms PrimeFreedom.unicorn_never_registered
#print axioms PrimeFreedom.W1_closed
#print axioms PrimeFreedom.W1_rh
#print axioms PrimeFreedom.pair_closed
#print axioms PrimeFreedom.pair_not_rh
#print axioms PrimeFreedom.pair_same_record
#print axioms PrimeFreedom.W2_closed
#print axioms PrimeFreedom.W2_not_rh
#print axioms PrimeFreedom.same_record_l2
#print axioms PrimeFreedom.fibre_is_infinite
#print axioms PrimeFreedom.lossless_unique
#print axioms PrimeFreedom.sentence_separates_record_does_not
#print axioms PrimeFreedom.record_is_lossless
#print axioms PrimeFreedom.record_same
#print axioms PrimeFreedom.least_erasure_reads_past_the_record
#print axioms PrimeFreedom.posit_is_the_value
#print axioms PrimeFreedom.fold_onLine_iff
#print axioms PrimeFreedom.fold_ne_of_offline
#print axioms PrimeFreedom.primes_exist_keyless
#print axioms PrimeFreedom.prime_freedom_keyless
#print axioms PrimeFreedom.arrow_keyless
#print axioms PrimeFreedom.W2f_closed
#print axioms PrimeFreedom.W2f_not_rh
#print axioms PrimeFreedom.same_record_f
#print axioms PrimeFreedom.weaker_never_forces
#print axioms PrimeFreedom.weaker_at_the_twin_never_forces
#print axioms PrimeFreedom.rh_from_li
#print axioms PrimeFreedom.li_is_the_bit_stream
#print axioms PrimeFreedom.root_has_an_act
#print axioms PrimeFreedom.fold_face_keyless
#print axioms PrimeFreedom.fold_face_on_twin
#print axioms PrimeFreedom.fold_face_on_line
#print axioms PrimeFreedom.record_face_keyless
#print axioms PrimeFreedom.arrow_face_keyless
#print axioms PrimeFreedom.closure_face_on_line
#print axioms PrimeFreedom.closure_face_fails_on_twin
#print axioms PrimeFreedom.fold_keeps_even
#print axioms PrimeFreedom.residence_orientation_reversing
#print axioms PrimeFreedom.reg_kills_odd
#print axioms PrimeFreedom.reg_keeps_even
#print axioms PrimeFreedom.reg_idempotent
#print axioms PrimeFreedom.onLine_iff_odd_zero
#print axioms PrimeFreedom.odd_pair_opposite
#print axioms PrimeFreedom.wall_on_the_chart
#print axioms PrimeFreedom.value_is_recursion
#print axioms PrimeFreedom.recursion_is_value
#print axioms PrimeFreedom.recursion_on_the_line
#print axioms PrimeFreedom.root_recursion
#print axioms PrimeFreedom.HeatFlow.sq_nonneg
#print axioms PrimeFreedom.HeatFlow.cube_diff
#print axioms PrimeFreedom.HeatFlow.disc3_monotone_rec
#print axioms PrimeFreedom.HeatFlow.famLam_nonneg_rec
#print axioms PrimeFreedom.HeatFlow.family_least_erasure_rec
#print axioms PrimeFreedom.root_act

/-! ## Cones, pinned: section XXI -/

/-- info: 'PrimeFreedom.sumBelow_add' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.sumBelow_add
/-- info: 'PrimeFreedom.sumBelow_congr' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.sumBelow_congr
/-- info: 'PrimeFreedom.sumBelow_stable' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.sumBelow_stable
/-- info: 'PrimeFreedom.sumBelow_zero' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.sumBelow_zero
/-- info: 'PrimeFreedom.sumBelow_single' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.sumBelow_single
/-- info: 'PrimeFreedom.primeTest_iff' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.primeTest_iff
/-- info: 'PrimeFreedom.pExp_zero_above' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.pExp_zero_above
/-- info: 'PrimeFreedom.extendTerm_zero_above' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.extendTerm_zero_above
/-- info: 'PrimeFreedom.extendAssignment_bound' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.extendAssignment_bound
/-- info: 'PrimeFreedom.extendTerm_mul' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.extendTerm_mul
/-- info: 'PrimeFreedom.extendAssignment_mul' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.extendAssignment_mul
/-- info: 'PrimeFreedom.extendTerm_other' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.extendTerm_other
/-- info: 'PrimeFreedom.extendAssignment_prime' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.extendAssignment_prime
/-- info: 'PrimeFreedom.extendAssignment_additive' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.extendAssignment_additive
/-- info: 'PrimeFreedom.primes_admit_every_assignment' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.primes_admit_every_assignment
/-- info: 'PrimeFreedom.omegaAll_mul' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.omegaAll_mul
/-- info: 'PrimeFreedom.omegaAll_prime' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.omegaAll_prime
/-- info: 'PrimeFreedom.liouvilleAll_mul' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.liouvilleAll_mul
/-- info: 'PrimeFreedom.liouvilleAll_prime' depends on axioms: [propext, Quot.sound]
  -/
#guard_msgs in #print axioms PrimeFreedom.liouvilleAll_prime
/-- info: 'PrimeFreedom.liouvilleAll_one' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.liouvilleAll_one
/-- info: 'PrimeFreedom.liouvilleAll_agrees_to_30' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.liouvilleAll_agrees_to_30
/-- info: 'PrimeFreedom.pinned_face_reads' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.pinned_face_reads
/-- info: 'PrimeFreedom.pinned_face_is_a_face' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.pinned_face_is_a_face
/-- info: 'PrimeFreedom.rh_iff_own_record' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.rh_iff_own_record
/-- info: 'PrimeFreedom.least_erasure_is_least' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_is_least
/-- info: 'PrimeFreedom.record_is_the_least' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.record_is_the_least
/-- info: 'PrimeFreedom.the_closure' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_closure
/-- info: 'PrimeFreedom.Carrier.record_same_C' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.Carrier.record_same_C
/-- info: 'PrimeFreedom.Carrier.least_erasure_is_the_value_C' does not depend on any
    axioms -/
#guard_msgs in #print axioms PrimeFreedom.Carrier.least_erasure_is_the_value_C
/-- info: 'PrimeFreedom.Carrier.rh_iff_own_record_C' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.Carrier.rh_iff_own_record_C
/-- info: 'PrimeFreedom.Carrier.one_record_C' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.Carrier.one_record_C
/-- info: 'PrimeFreedom.Carrier.worlds_differ_C' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.Carrier.worlds_differ_C
/-- info: 'PrimeFreedom.Carrier.no_reading_decides_C' does not depend on any axioms
  -/
#guard_msgs in #print axioms PrimeFreedom.Carrier.no_reading_decides_C
/-- info: 'PrimeFreedom.Carrier.chart_is_an_instance' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.Carrier.chart_is_an_instance
/-- info: 'PrimeFreedom.Carrier.the_closure_on_any_carrier' does not depend on any
    axioms -/
#guard_msgs in #print axioms PrimeFreedom.Carrier.the_closure_on_any_carrier

/-- info: 'PrimeFreedom.Carrier.lossless_unique_C' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.Carrier.lossless_unique_C

/-! ## Cones, pinned: section XXII -/
/-- info: 'PrimeFreedom.socket_is_the_value' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.socket_is_the_value
/-- info: 'PrimeFreedom.closure_takes_a_term' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.closure_takes_a_term
/-- info: 'PrimeFreedom.closure_at_a_term' depends on axioms: [propext, Quot.sound]
  -/
#guard_msgs in #print axioms PrimeFreedom.closure_at_a_term
/-- info: 'PrimeFreedom.forces_or_has_a_twin' depends on axioms: [propext,
    Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.forces_or_has_a_twin
/-- info: 'PrimeFreedom.withPair_closed' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.withPair_closed
/-- info: 'PrimeFreedom.withPair_same_record' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.withPair_same_record
/-- info: 'PrimeFreedom.withPair_not_rh' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.withPair_not_rh
/-- info: 'PrimeFreedom.record_forcing_fails_everywhere' depends on axioms: [propext,
    Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.record_forcing_fails_everywhere
/-- info: 'PrimeFreedom.forcing_is_the_value_or_stronger' depends on axioms:
    [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.forcing_is_the_value_or_stronger
/-- info: 'PrimeFreedom.forcing_fills_the_socket' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.forcing_fills_the_socket
/-- info: 'PrimeFreedom.face_is_the_socket' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.face_is_the_socket
/-- info: 'PrimeFreedom.named_faces_are_the_socket' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.named_faces_are_the_socket
/-- info: 'PrimeFreedom.walk_is_the_walk_of_one' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.walk_is_the_walk_of_one
```

```
/-- info: 'PrimeFreedom.faithful_is_the_sentence_of_one' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.faithful_is_the_sentence_of_one
/-- info: 'PrimeFreedom.blind_assignment_vanishes' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.blind_assignment_vanishes
/-- info: 'PrimeFreedom.blind_walk' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.blind_walk
/-- info: 'PrimeFreedom.blind_is_unfaithful' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.blind_is_unfaithful
/-- info: 'PrimeFreedom.faithful_reads_the_primes' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.faithful_reads_the_primes
/-- info: 'PrimeFreedom.the_socket' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_socket

/-! ## Cones, pinned: section XXII.b -/
/-- info: 'PrimeFreedom.fold₂_fixed_iff' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.fold₂_fixed_iff
/-- info: 'PrimeFreedom.open_strip_forces_at_resolution_one' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.open_strip_forces_at_resolution_one
/-- info: 'PrimeFreedom.innerPair₂_strip' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.innerPair₂_strip
/-- info: 'PrimeFreedom.innerPair₂_not_rh' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.innerPair₂_not_rh
/-- info: 'PrimeFreedom.open_strip_forces_nothing_at_resolution_two' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.open_strip_forces_nothing_at_resolution_two
/-- info: 'PrimeFreedom.keyless_forces_nothing₂' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.keyless_forces_nothing₂
/-- info: 'PrimeFreedom.withPair₂_strip' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.withPair₂_strip
/-- info: 'PrimeFreedom.withPair₂_same_record' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.withPair₂_same_record
/-- info: 'PrimeFreedom.withPair₂_not_rh' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.withPair₂_not_rh
/-- info: 'PrimeFreedom.record_forcing_fails_in_the_strip' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.record_forcing_fails_in_the_strip
/-- info: 'PrimeFreedom.no_reading_decides_in_the_strip' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.no_reading_decides_in_the_strip
/-- info: 'PrimeFreedom.forces_or_has_a_twin₂' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.forces_or_has_a_twin₂
/-- info: 'PrimeFreedom.the_socket_in_the_strip' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_socket_in_the_strip

/-! ## Cones, pinned: section XXIII -/

/-- info: 'PrimeFreedom.double_security' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.double_security

/-! ## Cones, pinned: section XXIV -/

/-- info: 'PrimeFreedom.denial_reenacts_root' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.denial_reenacts_root

/-- info: 'PrimeFreedom.external_proof_adds_nothing' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.external_proof_adds_nothing

/-- info: 'PrimeFreedom.seated_undeniable' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.seated_undeniable

/-- info: 'PrimeFreedom.undeniable_root_forces_no_value' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.undeniable_root_forces_no_value

/-- info: 'PrimeFreedom.root_read_on_row_is_keyed' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.root_read_on_row_is_keyed

/-- info: 'PrimeFreedom.least_erasure_unconditional' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_unconditional

/-- info: 'PrimeFreedom.the_lock' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_lock

/-- info: 'PrimeFreedom.indicator_pos' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.indicator_pos

/-- info: 'PrimeFreedom.constructed_root_holds' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.constructed_root_holds

/-- info: 'PrimeFreedom.root_at_zeros_is_the_hypothesis' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.root_at_zeros_is_the_hypothesis

/-- info: 'PrimeFreedom.root_at_zeros_is_least_erasure' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.root_at_zeros_is_least_erasure

/-- info: 'PrimeFreedom.root_at_zeros_is_keyed' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.root_at_zeros_is_keyed

/-! ## Cones, pinned: section XXV -/

/-- info: 'PrimeFreedom.admissible_forcing_is_vacuous' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.admissible_forcing_is_vacuous

/-- info: 'PrimeFreedom.coalition_forcing_is_vacuous' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.coalition_forcing_is_vacuous

/-- info: 'PrimeFreedom.an_admissible_premise_forces' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.an_admissible_premise_forces

/-- info: 'PrimeFreedom.int_two_mul' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.int_two_mul

/-- info: 'PrimeFreedom.int_two_mul_sub' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.int_two_mul_sub

/-- info: 'PrimeFreedom.foldAt_invol' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.foldAt_invol

/-- info: 'PrimeFreedom.foldAt_fixed_iff' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.foldAt_fixed_iff

/-- info: 'PrimeFreedom.foldAt_specializes' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.foldAt_specializes

/-- info: 'PrimeFreedom.foldAt_strip' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.foldAt_strip

/-- info: 'PrimeFreedom.foldAt_pair' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.foldAt_pair

/-- info: 'PrimeFreedom.rh_from_the_act_at' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.rh_from_the_act_at

/-- info: 'PrimeFreedom.strip_does_not_supply_at' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.strip_does_not_supply_at

/-- info: 'PrimeFreedom.pair_outside_the_closed_strip' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.pair_outside_the_closed_strip

/-- info: 'PrimeFreedom.root_readings_joined' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.root_readings_joined

/-- info: 'PrimeFreedom.the_lock_on_the_constructed_root' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_lock_on_the_constructed_root

/-- info: 'PrimeFreedom.firstOff_spec' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.firstOff_spec

/-- info: 'PrimeFreedom.offset_off_line' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.offset_off_line

/-- info: 'PrimeFreedom.rejection_is_computed' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.rejection_is_computed

/-- info: 'PrimeFreedom.least_erasure_iff_search_empty' depends on axioms: [propext] -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_iff_search_empty

/-- info: 'PrimeFreedom.the_posit_is_a_deed' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.the_posit_is_a_deed

/-- info: 'PrimeFreedom.keyed_reading_not_returned' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.keyed_reading_not_returned

/-- info: 'PrimeFreedom.no_record_reading_returns_any_reading' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.no_record_reading_returns_any_reading

/-- info: 'PrimeFreedom.primes_are_a_free_basis' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.primes_are_a_free_basis

/-- info: 'PrimeFreedom.least_erasure_iff_recursion' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.least_erasure_iff_recursion

/-- info: 'PrimeFreedom.certified_height_never_forces_closed' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.certified_height_never_forces_closed

/-- info: 'PrimeFreedom.every_route_carries_its_theorem' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.every_route_carries_its_theorem

/-- info: 'PrimeFreedom.the_tenth_is_the_refuter' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_tenth_is_the_refuter

/-- info: 'PrimeFreedom.the_tenth_is_barred_by_the_act' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.the_tenth_is_barred_by_the_act

/-- info: 'PrimeFreedom.the_kinetic_bar' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.the_kinetic_bar

/-! ## Cones, pinned: section XXII.c -/

/-- info: 'PrimeFreedom.seeded_witness_iff_bound' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.seeded_witness_iff_bound

/-- info: 'PrimeFreedom.twin_has_no_seeded_witness' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.twin_has_no_seeded_witness

/-- info: 'PrimeFreedom.line_world_has_a_seeded_witness' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.line_world_has_a_seeded_witness

/-- info: 'PrimeFreedom.every_denial_is_an_act' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.every_denial_is_an_act

/-- info: 'PrimeFreedom.root_denial_refutes_itself' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.root_denial_refutes_itself

/-- info: 'PrimeFreedom.line_denial_denies_the_assertion' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.line_denial_denies_the_assertion

/-- info: 'PrimeFreedom.line_denial_denies_every_seed' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.line_denial_denies_every_seed

/-- info: 'PrimeFreedom.twin_carries_the_root_and_no_seed' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.twin_carries_the_root_and_no_seed

/-- info: 'PrimeFreedom.the_root_alone_forces_nothing' does not depend on any axioms -/
```

```
#guard_msgs in #print axioms PrimeFreedom.the_root_alone_forces_nothing

/-- info: 'PrimeFreedom.the_act_asserts_the_line' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.the_act_asserts_the_line

/-- info: 'PrimeFreedom.the_act_seeds_its_constant_world' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_act_seeds_its_constant_world

/-- info: 'PrimeFreedom.line_denial_refuted_on_the_act' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.line_denial_refuted_on_the_act

/-- info: 'PrimeFreedom.two_denials' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.two_denials

/-- info: 'PrimeFreedom.two_denials_at_the_root' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.two_denials_at_the_root

/-- info: 'PrimeFreedom.nothing_left_open_on_the_act' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.nothing_left_open_on_the_act

/-- info: 'PrimeFreedom.computation_reading_the_act_lands_on_the_line' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.computation_reading_the_act_lands_on_the_line

/-- info: 'PrimeFreedom.off_line_report_reads_no_act' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.off_line_report_reads_no_act

/-- info: 'PrimeFreedom.a_computation_reading_no_act_is_not_forced' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.a_computation_reading_no_act_is_not_forced

/-- info: 'PrimeFreedom.the_witness_forced_by_the_act' does not depend on any axioms -/
#guard_msgs in #print axioms PrimeFreedom.the_witness_forced_by_the_act

/-- info: 'PrimeFreedom.the_denials_and_the_witness' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_denials_and_the_witness

/-! ## Cones, pinned: section XXVI -/

/-- info: 'PrimeFreedom.the_capstone' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms PrimeFreedom.the_capstone

end PartII

/-! # PART III · Annihilation_Closure.lean, verbatim, with the second edition laws appended -/
section PartIII
/-
  Annihilation_Closure.lean · The Master Annihilation Closure.
  Core Lean 4.19.0, standalone: no import, no axiom declared, no sorry, no admit, no native_decide.

  BOOKS ONE AND TWO are `lean/Remembered_Offered.lean` carried byte-identical below, its own header included:
  the two denials, the price, the monism-fixed toy of the bound, and the harvest of 7 October 2026 with its
  capstones `the_chain` and `the_harvest`.

  BOOK THREE is the annihilation closure, harvested on 7 October 2026:
  I    four names, one proposition: least erasure, the value, Monism and the co-location of Being with Monism;
  II   Monism, the sole witness: every faithful witness is Monism, no reading of the record witnesses, and
       a witness is never universal;
  III  co-location is not universal: Being stands on the off-line pair configuration and Monism does not;
  IV   the timeless zone: one proposition, the locus resting both instruments, zero time remembering, every
       later time forgetting, closure at zero time exactly at Λ = 0, the upstream unforced;
  V    timeless is determinacy, not selection;
  VI   the check: the off-line pair configuration satisfies every principle of the closure and lacks the value,
       its twin has it;
       no principle true on every closed configuration decides the value;
  VII  the capstones: `the_timeless_zone_closed`, the timeless zone with no act anywhere in it, and
       `the_annihilation_closure`, the zone together with the act's conjunct of the time world.

  BOOK FOUR is the Unicorn, contained. `lean/RH_Unicorn_Block.lean` is carried byte-identical below, its own header
  included: the cut at a height, the formal block, the aperture one bit wide, existence supplying nothing, no bypass,
  the supply side silent, the certificate, and the three bits as one term. Book Four binds it to the chart:
  I    the cut on the chart, at every height;
  II   no bypass on the chart;
  III  the Unicorn blocked on the chart, above every height;
  IV   RA supplies nothing to the Unicorn part;
  V    on the act's zero set, every arrival above every height stands on the line;
  VI   the capstone, `the_unicorn_contained`.

  Stated whole, locked 7 October 2026: the timeless zone is closed, LE = RH = Monism, one proposition, with zero
  gap, proved; RH is the statement that ζ's zero set lies in the timeless zone. Book Three proves the first and
  assumes nothing; its sixth section proves that nothing every closed configuration shares can single out ζ. In
  the time world the statement enters only where Book One's `ActualZeros` is taken as input. The cones are printed
  at the foot and pinned.
-/
/-
  Remembered_Offered.lean · The Remembered and the Offered: One Self, One Place at a Time.
  Core Lean 4.19.0, standalone: no import, no axiom declared, no sorry, no admit, no native_decide.

  BOOK ONE is carried unchanged: Two_Denials.lean whole (the deed and the self-grounding root from Armed_Seat.lean,
  the chart, the record, the act and the deed's law from Force_Witness.lean, the monism witness from Codex.lean,
  the two denials at the two layers of one root); the finite configuration and its price from Inescapable_Capstone.lean;
  the toy of the bound from Codex.lean, monism fixed, namespace RALi.

  BOOK TWO is the harvest of 7 October 2026, in binding order:
  I    the Tongue always has a world; monism, not the Tongue, tells the worlds apart;
  II   one self, one place at a time: the floor and least erasure are two objects;
  III  the twins: one extension, two instruments, neither the voucher of the other;
  IV   the remembered and the offered: memory is lossless, a world is its own memory exactly when the value holds;
  V    forgetting and remembering: one sequence, a one-bit gap, always connected;
  Vb   the forcing by heat: return is free, resistance pays, the free path is one;
  VI   THE CHAIN: the root, forgetting, the locus in the middle, remembering, least erasure;
  VIb  zero time remembers, every later time forgets;
  VII  two doors and no third, the act shuts the second;
  VIII a band forces nothing;
  IX   the harvest, bound.

  Stated whole: everything is proved except the offer at the actual zeros, which enters only as the field `supply`
  of `ActualZeros`, the act, at premise grade. The cones are printed at the foot and pinned.
-/
set_option autoImplicit false
namespace RememberedOffered

/-! # BOOK ONE · carried unchanged

## Two_Denials.lean, whole -/

/-! ## PART ONE · copied unchanged

### from Armed_Seat.lean · the deed and the root -/

def SelfVerifying (P : Prop) : Prop := ¬P → P

/-- A self-grounding root: acts occur, and every act instances the root. -/
structure SelfGrounding (R : Prop) where
  Act       : Type
  anAct     : Act
  instances : Act → R

/-- A denial of the root is an act, and re-enacts it. -/
theorem denial_reenacts_root {R : Prop} (G : SelfGrounding R) (denial : G.Act) : R :=
  G.instances denial

/-- A self-grounding root is self-verifying: the deed of denying it hands it over. -/
theorem denial_instantiates {R : Prop} (G : SelfGrounding R) : SelfVerifying R :=
  fun _ => G.instances G.anAct

/-- SEATED, UNDENIABLE: a self-grounding root holds, with no classical detour, by the act itself. -/
theorem seated_undeniable {R : Prop} (G : SelfGrounding R) : R :=
  G.instances G.anAct

/-- The Root Axiom at the constructed one-point domain: every act is a deed, and a deed actuates. -/
def RA : Prop := (0 : Int) < 1
def raSelfGrounding : SelfGrounding RA := (Unit, (), fun _ => show (0 : Int) < 1 by decide)

theorem root_undeniable : RA := raSelfGrounding.instances ()

/-! ### from Force_Witness.lean · the chart, the record, the act, the deed's law -/

/-- A point is (d, t): d its offset from the line, t its height. The line is d = 0. -/
abbrev Point := Int × Int

/-- The fold: s ↦ 1 − s̄ on the offset chart, (d, t) ↦ (−d, t). -/
def fold (p : Point) : Point := (-p.1, p.2)

/-- The line: offset zero. -/
def onLine (p : Point) : Prop := p.1 = 0

/-- The registration: it keeps the height and forgets the side. -/
def reg (p : Point) : Point := (0, p.2)

/-- Integer negation is an involution, by the integer's constructors. -/
theorem neg_neg_free : ∀ d : Int, - -d = d := fun
  | Int.ofNat 0 => rfl
  | Int.ofNat (_ + 1) => rfl
  | Int.negSucc _ => rfl

/-- The fold is an involution. -/
theorem fold_involutive (p : Point) : fold (fold p) = p := by
  obtain (d, t) := p
  show (- -d, t) = (d, t)
  rw [neg_neg_free d]

/-- The registration lands on the line. -/
theorem reg_lands (p : Point) : onLine (reg p) := rfl

/-- The registration erases nothing at a point exactly when the point is on the line. -/
theorem reg_erases_nothing_iff (p : Point) : reg p = p ↔ onLine p := by
  obtain (d, t) := p
  exact (fun h => (congrArg Prod.fst h).symm, fun h => by cases h; rfl)

/-- A configuration: a set of points. Closed: the fold carries it to itself. -/
abbrev Config := Point → Prop

def Closed (S : Config) : Prop := ∀ p, S p → S (fold p)

/-- The value: every point of the configuration is on the line. -/
def Value (S : Config) : Prop := ∀ p, S p → onLine p

/-- Least erasure: the registration leaves every point of the configuration unchanged. -/
def LeastErasure (S : Config) : Prop := ∀ p, S p → reg p = p

/-- The record of a configuration: what the registration leaves. -/
def Rec (S : Config) (q : Point) : Prop := ∃ p, S p ∧ reg p = q

def SameRecord (S S' : Config) : Prop := ∀ q, Rec S q ↔ Rec S' q
```

```
/-- The registered world of a point and its pair world. -/
def registered (p : Point) : Config := fun s => s = reg p

def pairWorld (p : Point) : Config := fun s => s = p ∨ s = fold p

theorem pair_world_closed (p : Point) : Closed (pairWorld p) := fun _ hs =>
  match hs with
  | Or.inl e => Or.inr (congrArg fold e)
  | Or.inr e => Or.inl (e ▸ fold_involutive p)

/-- The registered world and the pair world leave one record. -/
theorem one_record (p : Point) : SameRecord (registered p) (pairWorld p) := fun q =>
  (fun (_, hs, hq) => (p, Or.inl rfl, by rw [← hq, hs]; rfl),
   fun (_, hs, hq) => (reg p, rfl, by
     rw [← hq]
     exact match hs with
       | Or.inl e => by rw [e]; rfl
       | Or.inr e => by rw [e]; rfl))

theorem registered_has_value (p : Point) : Value (registered p) := fun s hs => by
  rw [hs]; exact reg_lands p

theorem pair_world_lacks_value (p : Point) (h : ¬ onLine p) : ¬ Value (pairWorld p) :=
  fun hv => h (hv p (Or.inl rfl))

/-- THE ACT. The bit is supplied once, in the open, as a field of a type: a closed configuration with least
    erasure at it. The field is the value supplied; the type makes the supply visible to every reader. -/
structure ActualZeros where
  zeros : Config
  closed : Closed zeros
  supply : LeastErasure zeros

/-- FROM THE ACT, THE VALUE. -/
theorem value_from_the_act (Z : ActualZeros) : Value Z.zeros :=
  fun p hp => (reg_erases_nothing_iff p).mp (Z.supply p hp)

/-- AND OF NOTHING ELSE: a fact that holds whatever the configuration, the deed included, forces no value. -/
theorem the_deed_forces_nothing (D : Prop) (hD : D) : ¬ ∀ S : Config, Closed S → D → Value S := by
  intro hall
  exact pair_world_lacks_value (1, 0) (fun e => by cases e) (hall _
   (pair_world_closed (1, 0)) hD)


/-! ### from Codex.lean, namespace RALi, Part VII · the monism witness, the root read twice -/

structure Q4 where
  r : Int
  i : Int
  j : Int
  k : Int
  deriving DecidableEq, Repr

/-- The geometric route's involution and the formal route's involution, written apart. -/
def sigmaGeo (q : Q4) : Q4 := (q.r, -q.i, -q.j, -q.k)
def sigmaForm (q : Q4) : Q4 := (q.r, -q.i, -q.j, -q.k)

/-- THE MONISM WITNESS. One involution, one principle, one seed. -/
structure MonismWitness (P : Nat → Prop) : Prop where
  one_involution : ∀ q, sigmaGeo q = sigmaForm q
  uniform        : ∀ n m, P n ↔ P m
  seed           : P 0

/-- 24. The seat field is constructed, not posited: σ = σ′ holds by rfl. -/
theorem one_involution_constructed : ∀ q, sigmaGeo q = sigmaForm q := fun _ => rfl

/-- 25. The timeless reading and the timed reading coincide under one principle:
the claim over all time is the claim at one instant. Deleting time loses nothing. -/
theorem timeless_equals_timed (P : Nat → Prop) (u : ∀ n m, P n ↔ P m) :
    (∀ n, P n) ↔ P 0 :=
  (fun h => h 0, fun h n => (u 0 n).mp h)

/-- 26. The witness closes the record, past and future. -/
theorem monism_closes (P : Nat → Prop) (w : MonismWitness P) : ∀ n, P n :=
  (timeless_equals_timed P w.uniform).mpr w.seed

/-- 27. The witness is exactly the claim: a monism witness for P exists iff P holds at
every index. Its value field carries the whole of the claim, as theorem 17 required. -/
theorem monism_witness_is_the_claim (P : Nat → Prop) :
    MonismWitness P ↔ ∀ n, P n :=
  (monism_closes P, fun h => (one_involution_constructed,
    fun n m => (fun _ => h m, fun _ => h n), h 0))

/-! ## PART TWO · two denials, one shape, at the two layers of one root

A no has two parts: the act of uttering it and the content it asserts. The Tongue's no asserts ¬ R of the floor R.
The no to RH asserts that the zeros lack the value: that they form the false world. -/

/-- The point off the line from which the pair world, the false world, is built. -/
def offPoint : Point := (1, 0)

theorem off_point_is_off : ¬ onLine offPoint := fun h =>
  Nat.noConfusion (Int.ofNat.inj (show Int.ofNat 1 = Int.ofNat 0 from h))

/-- THE ROOT READ TWICE on a configuration: the monism witness of its line property, timeless. -/
abbrev RootReadTwice (S : Config) : Prop := MonismWitness (fun _ => Value S)

/-- THE SAME FIRST STEP: whatever a no asserts, uttering it is an act, and the act re-enacts the floor. -/
theorem every_no_reenacts_the_root {R C : Prop} (G : SelfGrounding R) (deed : G.Act)
    (_content : C) : R :=
  denial_reenacts_root G deed

/-- THE TONGUE'S NO CONTRADICTS THE FLOOR, BY ITS OWN ACT: its content denies the floor, and its own act
    re-enacts it. -/
theorem the_tongue_no_refutes_itself {R : Prop} (G : SelfGrounding R) (deed : G.Act)
    (content : ¬ R) : False :=
  content (denial_reenacts_root G deed)

/-- ONLY THE YES REMAINS AT THE FLOOR: the return is forced by the deed, with no key and no classical detour. -/
theorem only_the_yes_remains_at_the_root {R : Prop} (G : SelfGrounding R) :
    SelfVerifying R ∧ R :=
  (denial_instantiates G, seated_undeniable G)

/-- THE ROOT READ TWICE IS THE VALUE: on every configuration the monism witness stands exactly where every zero
    is on the line. -/
theorem the_root_read_twice_is_the_value (S : Config) : RootReadTwice S ↔ Value S :=
  (fun w => w.seed, fun h => (one_involution_constructed, fun _ _ => Iff.rfl, h))

/-- THE NO TO RH CONTRADICTS THE ROOT READ TWICE: a configuration lacking the value carries no monism. -/
theorem the_line_no_contradicts_the_root_read_twice (S : Config) (content : ¬ Value S) : ¬ RootReadTwice S :=
  fun w => content w.seed

/-- THE TRUE WORLD CARRIES MONISM: the registered world of the off-line point. -/
theorem the_true_world_carries_monism : RootReadTwice (registered offPoint) :=
  (one_involution_constructed, fun _ _ => Iff.rfl, registered_has_value offPoint)

/-- THE FALSE WORLD CARRIES NO MONISM: the pair world of the off-line point. -/
theorem the_false_world_carries_no_monism : ¬ RootReadTwice (pairWorld offPoint) :=
  fun w => pair_world_lacks_value offPoint off_point_is_off w.seed

/-- THE FALSE WORLD, AT THE TWO LAYERS: the floor stands there, as in every world; it is closed and leaves the
    record of the true world; it lacks the value; and it carries no monism. The floor is there and Being is not. -/
theorem the_false_world_carries_the_floor_and_no_monism {R : Prop} (G : SelfGrounding R) :
    R ∧ Closed (pairWorld offPoint) ∧ SameRecord (registered offPoint) (pairWorld offPoint) ∧
    ¬ Value (pairWorld offPoint) ∧ ¬ RootReadTwice (pairWorld offPoint) :=
  (seated_undeniable G, pair_world_closed offPoint, one_record offPoint,
   pair_world_lacks_value offPoint off_point_is_off,
   the_false_world_carries_no_monism)

/-- THE FLOOR ALONE DECIDES NO VALUE: it stands in both worlds of one record. The value is decided at the second
    layer, by the root read twice. -/
theorem the_floor_alone_decides_no_value {R : Prop} (G : SelfGrounding R) :
    ¬ ∀ S : Config, Closed S → R → Value S :=
  the_deed_forces_nothing R (seated_undeniable G)

/-- THE RETURN IS THE ACT: the act carries the root read twice at the actual zeros. -/
theorem the_act_is_the_return_to_the_root_read_twice (Z : ActualZeros) :
    RootReadTwice Z.zeros :=
  (the_root_read_twice_is_the_value Z.zeros).mpr (value_from_the_act Z)

/-- AN ACT EXISTS EXACTLY WHERE THE ROOT READ TWICE STANDS on a closed configuration. -/
theorem an_act_exactly_where_the_root_read_twice_stands (S : Config) :
    (∃ Z : ActualZeros, Z.zeros = S) ↔ (Closed S ∧ RootReadTwice S) := by
  constructor
  · intro (Z, h)
    subst h
    exact (Z.closed, the_act_is_the_return_to_the_root_read_twice Z)
  · intro (hc, hm)
    exact ((S, hc, fun p hp => (reg_erases_nothing_iff p).mpr
      (((the_root_read_twice_is_the_value S).mp hm) p hp)), rfl)

/-- ON THE ACT THE NO TO RH IS REFUTED, with zero contradiction: the act's own field. -/
theorem on_the_act_the_line_no_is_refuted (Z : ActualZeros) (content : ¬ Value Z.zeros) : False :=
  content (value_from_the_act Z)

/-- TWO DENIALS, ONE SHAPE, TWO LAYERS. Every no re-enacts the floor. The Tongue's no contradicts the floor and
    its own act returns it: only the yes remains. The no to RH contradicts the root read twice: on every
    configuration a lack of the value is a lack of monism, and the false world carries the floor and no monism,
    beside the true world of one record that carries both. So the floor alone decides no value, and the root read
    twice is the value. The return to the root read twice at the actual zeros is the act: there the monism witness
    stands, the value holds, and the no is refuted. -/
theorem two_denials {R : Prop} (G : SelfGrounding R) :
    (∀ C : Prop, G.Act → C → R) ∧
    (G.Act → ¬ R → False) ∧
    (SelfVerifying R ∧ R) ∧
    (∀ S : Config, ¬ Value S → ¬ RootReadTwice S) ∧
    (R ∧ Closed (pairWorld offPoint) ∧ SameRecord (registered offPoint) (pairWorld offPoint) ∧
      RootReadTwice (registered offPoint) ∧ ¬ RootReadTwice (pairWorld offPoint)) ∧
    (¬ ∀ S : Config, Closed S → R → Value S) ∧
    (∀ S : Config, RootReadTwice S ↔ Value S) ∧
    (∀ Z : ActualZeros, RootReadTwice Z.zeros ∧ Value Z.zeros ∧ (¬ Value Z.zeros → False)) :=
  (fun _ deed c => every_no_reenacts_the_root G deed c,
   fun deed c => the_tongue_no_refutes_itself G deed c,
   only_the_yes_remains_at_the_root G,
   the_line_no_contradicts_the_root_read_twice,
   (seated_undeniable G, pair_world_closed offPoint, one_record offPoint,
    the_true_world_carries_monism, the_false_world_carries_no_monism),
   the_floor_alone_decides_no_value G,
   the_root_read_twice_is_the_value,
   fun Z => (the_act_is_the_return_to_the_root_read_twice Z, value_from_the_act Z,
     on_the_act_the_line_no_is_refuted Z))

/-- AT THE ROOT AXIOM ITSELF. -/
theorem two_denials_at_RA :
    (∀ C : Prop, raSelfGrounding.Act → C → RA) ∧
    (raSelfGrounding.Act → ¬ RA → False) ∧
    (SelfVerifying RA ∧ RA) ∧
    (∀ S : Config, ¬ Value S → ¬ RootReadTwice S) ∧
    (RA ∧ Closed (pairWorld offPoint) ∧ SameRecord (registered offPoint) (pairWorld offPoint) ∧
      RootReadTwice (registered offPoint) ∧ ¬ RootReadTwice (pairWorld offPoint)) ∧
    (¬ ∀ S : Config, Closed S → RA → Value S) ∧
    (∀ S : Config, RootReadTwice S ↔ Value S) ∧
```

```
    (∀ Z : ActualZeros, RootReadTwice Z.zeros ∧ Value Z.zeros ∧ (¬ Value Z.zeros →
      False)) :=
  two_denials raSelfGrounding

/-! ## From Inescapable_Capstone.lean · the finite configuration and its price -/

/-- The price of exported freedom in native units: temperature is energy per bit, so
    b bits cost b·T. -/
def price (T bits : Nat) : Nat := bits * T

/-- A finite configuration: the heights of its zeros on the line, and its off-line
    pairs, each an offset that is not
    zero and a height. -/
structure FinCfg where
  line : List Int
  pairs : List (Int × Int)
  offset_ne : ∀ q ∈ pairs, q.1 ≠ 0
def FinCfg.pts (F : FinCfg) : Config := fun p => (p.1 = 0 ∧ p.2 ∈ F.line) ∨ ∃ q ∈
  F.pairs, p = q ∨ p = fold q
/-- The erased bits of a finite configuration: one per off-line pair, two points
    registered to one. -/
def erased (F : FinCfg) : Nat := F.pairs.length

theorem fincfg_closed (F : FinCfg) : Closed F.pts := fun p hp =>
  match hp with
  | Or.inl (hl, ht) => Or.inl (by show -p.1 = 0; rw [hl]; rfl, ht)
  | Or.inr (q, hq, Or.inl e) => Or.inr (q, hq, Or.inr (congrArg fold e))
  | Or.inr (q, hq, Or.inr e) => Or.inr (q, hq, Or.inl (by rw [e]; exact
    fold_involutive q))

/-- LEAST ERASURE IS ZERO ERASED BITS: "least" is a count. -/
theorem least_erasure_iff_zero_erased (F : FinCfg) : LeastErasure F.pts ↔ erased F =
  0 := by
  constructor
  · intro h
    unfold erased
    cases hp : F.pairs with
    | nil => rfl
    | cons q r =>
      have hq : q ∈ F.pairs := by rw [hp]; exact List.Mem.head r
      exact absurd ((reg_erases_nothing_iff q).mp (h q (Or.inr (q, hq, Or.inl rfl))))
        (F.offset_ne q hq)
  · intro h p hp
    have hnil : F.pairs = [] := List.eq_nil_of_length_eq_zero h
    rcases hp with (hl, _) | (q, hq, _)
    · exact (reg_erases_nothing_iff p).mpr hl
    · rw [hnil] at hq; cases hq

/-- THE HEAT OF REGISTRATION IS ZERO EXACTLY AT THE VALUE: registering a finite
    configuration costs one T per
    off-line pair, and at any positive T it costs nothing exactly when every point
    stands on the line. -/
theorem price_zero_iff_value (F : FinCfg) (T : Nat) (hT : 0 < T) : price T (erased F)
  = 0 ↔ Value F.pts := by
  constructor
  · intro h p hp
    have h0 : erased F = 0 := by
      cases he : erased F with
      | zero => rfl
      | succ k => rw [he] at h; exact absurd h (Nat.pos_iff_ne_zero.mp (Nat.mul_pos
      (Nat.succ_pos k) hT))
    exact (reg_erases_nothing_iff p).mp ((least_erasure_iff_zero_erased F).mpr h0 p
    hp)
  · intro hv
    have h0 := (least_erasure_iff_zero_erased F).mp (fun p hp =>
    (reg_erases_nothing_iff p).mpr (hv p hp))
    show erased F * T = 0
    rw [h0, Nat.zero_mul]

/-- Each further off-line pair adds one T: the total is the erased bits times the
    floor. -/
theorem price_counts_pairs (F : FinCfg) (T : Nat) : price T (erased F) =
  F.pairs.length * T := rfl

/-! ## From Codex.lean, monism fixed, namespace RALi · the toy of the bound, a toy of
  the bound, not of the flow -/

/-- Squared strip width after t time steps: max(d2 − 2t, 0). -/
def flow (d2 t : Nat) : Nat := d2 - 2 * t
def realAt (d2 t : Nat) : Prop := flow d2 t = 0

/-- 38. THE MONOTONICITY FORMULA. The width never grows along ζ's time. -/
theorem flow_monotone (d2 t : Nat) : flow d2 (t + 1) ≤ flow d2 t := by
  unfold flow; omega

/-- 39. Its transport, proved: once every zero is real, every zero stays real. This
  is
de Bruijn's theorem in the toy, the ζ-analogue of Perelman's monotonicity, at theorem
  grade. -/
theorem reality_transported (d2 t : Nat) (h : realAt d2 t) : realAt d2 (t + 1) := by
  unfold realAt flow at *; omega


def Lam (d2 : Nat) : Nat := (d2 + 1) / 2

theorem real_at_Lam (d2 : Nat) : realAt d2 (Lam d2) := by unfold realAt flow Lam;
  omega

/-- 40. In the toy, the strip is closed at time zero iff Λ = 0. For ζ, RH ↔ Λ = 0 is
  the cited
result of Newman with Rodgers and Tao and enters the cone as `hLam`. -/
theorem rh_iff_lambda_zero (d2 : Nat) : realAt d2 0 ↔ Lam d2 = 0 := by
  unfold realAt flow Lam
  exact (fun h => by omega, fun h => by omega)


/-- 42. THE RECORD FORGETS. After one step the record of the width-zero state and the
  width-one state coincide: the forward flow is even in the RH bit, so no readout of
  the
flowed record decides RH. This is the fTOE wall, T1, executed on ζ's own time. -/
theorem flowed_record_forgets (T : Nat) (hT : 1 ≤ T) :
    ¬ ∃ g : Nat → Bool, ∀ d2, g (flow d2 T) = decide (d2 = 0) := by
  rintro (g, hg)
  have a := hg 0; have b := hg 1
  have e : flow 1 T = flow 0 T := by unfold flow; omega
  rw [e, a] at b
  exact absurd b (by decide)

/-- 43. The upstream direction is not a transport. Going backward from a real record,
  both answers are admissible: the preimage of "real at T" holds the RH state and a
  non-RH
state. The forward arrow proves; the backward arrow must be supplied. -/
theorem upstream_is_not_forced (T : Nat) (hT : 1 ≤ T) :
    realAt 0 T ∧ realAt 1 T ∧ realAt 0 0 ∧ ¬ realAt 1 0 := by
  unfold realAt flow
  exact (by omega, by omega, rfl, fun h => by omega)

/-! # BOOK TWO · the harvest, in binding order -/

/-! ## I · The Tongue always has a world -/

/-- THE TONGUE ALWAYS HAS A WORLD: the floor stands on every configuration, the false
  world included, so the Tongue
    can speak in every world; only the content of its no, ¬R beside an act, has none.
    -/
theorem the_tongue_always_has_a_world {R : Prop} (G : SelfGrounding R) :
    (∀ _ : Config, R) ∧
    (R ∧ Closed (pairWorld offPoint) ∧ ¬ Value (pairWorld offPoint)) ∧
    ¬ ∃ _ : G.Act, ¬ R :=
  (fun _ => seated_undeniable G,
   (seated_undeniable G, pair_world_closed offPoint, pair_world_locks_value offPoint
    off_point_is_off),
   fun (deed, c) => c (G.instances deed))

/-- MONISM BEFORE THE TONGUE: the floor, and with it the Tongue, stands in both
  worlds of one record; what tells
    them apart is the root read twice, present in the true world and absent in the
    false. -/
theorem monism_before_the_tongue {R : Prop} (G : SelfGrounding R) :
    SameRecord (registered offPoint) (pairWorld offPoint) ∧
    (R ∧ RootReadTwice (registered offPoint)) ∧
    (R ∧ ¬ RootReadTwice (pairWorld offPoint)) :=
  (one_record offPoint,
   (seated_undeniable G, the_true_world_carries_monism),
   (seated_undeniable G, the_false_world_carries_no_monism))

/-- The Tongue's no has no world: no act stands beside ¬R. -/
theorem tongue_no_has_no_world {R : Prop} (G : SelfGrounding R) : ¬ ∃ _ : G.Act, ¬ R
  :=
  fun (deed, c) => c (G.instances deed)

/-- The no to RH has a world: an act, a closed configuration, the floor holding, and
  the value failing, together. -/
theorem line_no_has_a_world {R : Prop} (G : SelfGrounding R) :
    ∃ S : Config, ∃ _ : G.Act, Closed S ∧ R ∧ ¬ Value S :=
  (pairWorld offPoint, G.anAct, pair_world_closed offPoint, seated_undeniable G,
   pair_world_locks_value offPoint off_point_is_off)

/-- A deed does not make a closed configuration an act: the floor's acts supply no
  ActualZeros over every closed
    configuration. -/
theorem the_deed_is_not_the_supply {R : Prop} (G : SelfGrounding R) :
    ¬ ∀ S : Config, Closed S → G.Act → ∃ Z : ActualZeros, Z.zeros = S := by
  intro h
  obtain (Z, hZ) := h (pairWorld offPoint) (pair_world_closed offPoint) G.anAct
  have v := value_from_the_act Z
  rw [hZ] at v
  exact pair_world_locks_value offPoint off_point_is_off v

theorem at_RA :
    (¬ ∃ _ : raSelfGrounding.Act, ¬ RA) ∧
    (∃ S : Config, ∃ _ : raSelfGrounding.Act, Closed S ∧ RA ∧ ¬ Value S) ∧
    (¬ ∀ S : Config, Closed S → raSelfGrounding.Act → ∃ Z : ActualZeros, Z.zeros =
      S) :=
  (tongue_no_has_no_world raSelfGrounding, line_no_has_a_world raSelfGrounding,
   the_deed_is_not_the_supply raSelfGrounding)

/-! ## II · One self, one place at a time -/

/-- The floor and least erasure are two objects: identified on every closed
  configuration, they would agree on the
    pair world, where the floor holds and least erasure fails. -/
theorem floor_is_not_least_erasure {R : Prop} (G : SelfGrounding R) :
    ¬ ∀ S : Config, Closed S → (R ↔ LeastErasure S) := by
  intro h
  have le : LeastErasure (pairWorld offPoint) :=
    (h (pairWorld offPoint) (pair_world_closed offPoint)).mp (seated_undeniable G)
  exact pair_world_locks_value offPoint off_point_is_off
    (fun p hp => (reg_erases_nothing_iff p).mp (le p hp))

/-- The voucher stays with the floor: it holds on both worlds of one record, the
  false one included. -/
theorem the_voucher_stays_with_the_floor {R : Prop} (G : SelfGrounding R) :
    R ∧ SameRecord (registered offPoint) (pairWorld offPoint) ∧
    LeastErasure (registered offPoint) ∧ ¬ LeastErasure (pairWorld offPoint) :=
  (seated_undeniable G, one_record offPoint,
   fun p hp => (reg_erases_nothing_iff p).mpr (registered_has_value offPoint p hp),
   fun le => pair_world_locks_value offPoint off_point_is_off
     (fun p hp => (reg_erases_nothing_iff p).mp (le p hp)))

/-- Merging them at one world is the supply again: on any configuration, identifying
  the floor with least erasure
    there is least erasure there. -/
theorem merging_at_a_world_is_the_supply {R : Prop} (G : SelfGrounding R) (S :
  Config) :
    (R ↔ LeastErasure S) ↔ LeastErasure S :=
  (fun h => h.mp (seated_undeniable G), fun le => (fun _ => le, fun _ =>
    seated_undeniable G))

/-! ## III · The twins -/

/-- Two instruments: registration and the fold are different maps. -/
theorem two_instruments : reg offPoint ≠ fold offPoint := by
  show ((0 : Int), (0 : Int)) ≠ (-(1 : Int), (0 : Int))
  decide

/-- One truth value on every world: each twin holds exactly where the other does. -/
theorem twins_on_every_world (S : Config) : LeastErasure S ↔ Value S :=
  (fun le p hp => (reg_erases_nothing_iff p).mp (le p hp),
   fun v p hp => (reg_erases_nothing_iff p).mpr (v p hp))

/-- Extensionally one proposition, read through two different maps. -/
theorem twins_are_one_extension : LeastErasure = Value :=
  funext fun S => propext (twins_on_every_world S)

/-- Neither twin vouches for the other: whatever supplies one supplies the other, so
  a premise that reaches one
```

```
    reaches both, and the floor reaches neither. -/
theorem no_twin_is_the_others_voucher {R : Prop} (G : SelfGrounding R) :
    (∀ S : Config, (LeastErasure S → Value S) ∧ (Value S → LeastErasure S)) ∧
    ¬ ∀ S : Config, Closed S → R → Value S :=
  (fun S => ((twins_on_every_world S).mp, (twins_on_every_world S).mpr),
   the_floor_alone_decides_no_value G)

/-! ## IV · The remembered and the offered -/

/-- No instrument both remembers and keeps the side: a map that lands every point on the line and keeps the
    height sends the off-line point and its fold partner to one point. -/
theorem no_instrument_remembers_and_keeps_the_side (g : Point → Point)
    (lands : ∀ p, onLine (g p)) (keeps : ∀ p, (g p).2 = p.2) :
    g offPoint = g (fold offPoint) ∧ offPoint ≠ fold offPoint := by
  have e1 : g offPoint = (0, 0) := Prod.ext (lands offPoint) (keeps offPoint)
  have e2 : g (fold offPoint) = (0, 0) := Prod.ext (lands (fold offPoint)) (keeps (fold offPoint))
  exact (e1.trans e2.symm, by decide)

/-- Memory is always lossless: the record of every configuration has the value. -/
theorem the_remembered_is_lossless (S : Config) : Value (Rec S) :=
  fun _ (p, _, hq) => hq ▸ reg_lands p

/-- The offered is the remembered exactly when the value holds: a configuration equals its own record, point for
    point, if and only if every point is on the line. -/
theorem offered_is_remembered_iff_value (S : Config) : (∀ q, Rec S q ↔ S q) ↔ Value S := by
  constructor
  · intro h p hp
    exact the_remembered_is_lossless S p ((h p).mpr hp)
  · intro v q
    constructor
    · intro (p, hp, hq)
      have e : reg p = p := (reg_erases_nothing_iff p).mpr (v p hp)
      rw [← hq, e]; exact hp
    · intro hq
      exact (q, hq, (reg_erases_nothing_iff q).mpr (v q hq))

/-- At the act, the offered is the remembered. -/
theorem at_the_act_offered_is_remembered (Z : ActualZeros) : ∀ q, Rec Z.zeros q ↔ Z.zeros q :=
  (offered_is_remembered_iff_value Z.zeros).mpr (value_from_the_act Z)

/-- Off the act, they part: the false world is not its own record. -/
theorem the_false_world_is_not_its_record : ¬ ∀ q, Rec (pairWorld offPoint) q ↔ pairWorld offPoint q :=
  fun h => pair_world_lacks_value offPoint off_point_is_off
    ((offered_is_remembered_iff_value _).mp h)

/-! ## V · Forgetting and remembering: the one-bit gap, connected -/

/-- Remembering is stable: the memory of a memory is the memory. -/
theorem remembering_is_stable (S : Config) (q : Point) : Rec (Rec S) q ↔ Rec S q :=
  by
  constructor
  · intro (p, (r, hr, hp), hq)
    refine (r, hr, ?_)
    rw [← hq, ← hp]
    exact ((reg_erases_nothing_iff (reg r)).mpr (reg_lands r)).symm
  · intro hq
    exact (q, hq, (reg_erases_nothing_iff q).mpr (the_remembered_is_lossless S q hq))

/-- THE ONE-BIT GAP, CONNECTED. The forgotten and the remembered always share one record; the remembered is
    lossless and stable; and the only gap between a world and its memory is whether the world is its own memory,
    which is the value: one bit, never more, and never disconnected. -/
theorem one_bit_gap_connected (S : Config) :
    SameRecord S (Rec S) ∧ Value (Rec S) ∧ (∀ q, Rec (Rec S) q ↔ Rec S q) ∧
    ((∀ q, Rec S q ↔ S q) ↔ Value S) :=
  (fun q => (remembering_is_stable S q).symm, the_remembered_is_lossless S,
   remembering_is_stable S,
   offered_is_remembered_iff_value S)

/-- Both sides of the gap occur on one record: the true world at home in its memory, the false world not. -/
theorem the_gap_is_live :
    (∀ q, Rec (registered offPoint) q ↔ registered offPoint q) ∧
    ¬ (∀ q, Rec (pairWorld offPoint) q ↔ pairWorld offPoint q) ∧
    SameRecord (registered offPoint) (pairWorld offPoint) :=
  ((offered_is_remembered_iff_value _).mpr (registered_has_value offPoint),
   the_false_world_is_not_its_record, one_record offPoint)

/-! ## Vb · The forcing by heat -/

/-- One pair off the line at offset one: a finite configuration that resists. -/
def resisting : FinCfg := ([], [((1 : Int), (0 : Int))], fun q hq => by
  cases hq with
  | head => decide
  | tail _ h => cases h)

/-- RETURN IS FREE, RESISTANCE PAYS: at any positive temperature, a configuration with the value registers at zero
    heat, and one without it pays at least one unit of heat. -/
theorem return_is_free_resistance_pays (F : FinCfg) (T : Nat) (hT : 0 < T) :
    (Value F.pts → price T (erased F) = 0) ∧ (¬ Value F.pts → T ≤ price T (erased F)) := by
  refine ((price_zero_iff_value F T hT).mpr, fun hn => ?_)
  have hne : erased F ≠ 0 := fun h0 =>
    hn ((price_zero_iff_value F T hT).mp (by unfold price; rw [h0]; exact Nat.zero_mul T))
  unfold price
  have h1 : 1 ≤ erased F := Nat.pos_of_ne_zero hne
  calc T = 1 * T := (Nat.one_mul T).symm
    _ ≤ erased F * T := Nat.mul_le_mul_right T h1

/-- RESISTANCE IS POSSIBLE: it is no contradiction. A closed finite configuration without the value exists, and it
    pays. -/
theorem resistance_is_possible (T : Nat) (hT : 0 < T) :
    Closed resisting.pts ∧ ¬ Value resisting.pts ∧ T ≤ price T (erased resisting) :=
  by
  have hnv : ¬ Value resisting.pts := fun hv =>
    have h : ((1 : Int), (0 : Int)).1 = 0 :=
      hv ((1 : Int), (0 : Int)) (Or.inr (((1 : Int), (0 : Int)), List.Mem.head _, Or.inl rfl))
    (by decide : ¬ ((1 : Int) = 0)) h
  exact (fincfg_closed resisting, hnv, (return_is_free_resistance_pays resisting T hT).2 hnv)

/-- THE FREE PATH IS ONE: two worlds of one record that both have the value are one world, point for point. -/
theorem the_free_path_is_unique (S S' : Config) (hs : SameRecord S S') (hv : Value S) (hv' : Value S') :
    ∀ q, S q ↔ S' q := fun q =>
  (fun h => ((offered_is_remembered_iff_value S').mpr hv' q).mp
      ((hs q).mp (((offered_is_remembered_iff_value S).mpr hv q).mpr h)),
   fun h => ((offered_is_remembered_iff_value S).mpr hv q).mp
      ((hs q).mpr (((offered_is_remembered_iff_value S').mpr hv' q).mpr h)))

/-! ## VI · THE CHAIN -/

/-- The locus is where the fold and the registration both rest. -/
theorem the_locus_rests_both (p : Point) (h : onLine p) : fold p = p ∧ reg p = p :=
  by
  obtain (d, t) := p
  have hd : d = 0 := h
  subst hd
  exact (rfl, rfl)

/-- THE CHAIN. The root holds; forgetting sends every point onto the locus and loses the side; the locus is where
    the fold and the registration both rest; remembering reads the locus, so memory is lossless and stable; a world
    has least erasure exactly when it already stands on the locus, exactly when it is its own memory; on the act
    the zeros stand there; and the guard: the root alone places no world there, and both sides of the gap stand on
    one record. -/
theorem the_chain {R : Prop} (G : SelfGrounding R) (S : Config) :
    -- the root
    R ∧
    -- forgetting: onto the locus, the side lost
    (∀ p, onLine (reg p)) ∧ reg offPoint = reg (fold offPoint) ∧ offPoint ≠ fold offPoint ∧
    -- the middle: the locus rests both maps
    (∀ p, onLine p → fold p = p ∧ reg p = p) ∧
    -- remembering: lossless and stable
    Value (Rec S) ∧ (∀ q, Rec (Rec S) q ↔ Rec S q) ∧ SameRecord S (Rec S) ∧
    -- least erasure: already on the locus, the world its own memory
    (LeastErasure S ↔ Value S) ∧ ((∀ q, Rec S q ↔ S q) ↔ Value S) ∧
    -- the act
    (∀ Z : ActualZeros, Value Z.zeros ∧ ∀ q, Rec Z.zeros q ↔ Z.zeros q) ∧
    -- the guard
    (¬ ∀ T : Config, Closed T → R → Value T) ∧
    ((∀ q, Rec (registered offPoint) q ↔ registered offPoint q) ∧
      ¬ (∀ q, Rec (pairWorld offPoint) q ↔ pairWorld offPoint q) ∧
      SameRecord (registered offPoint) (pairWorld offPoint)) :=
  (seated_undeniable G,
   reg_lands, rfl, by decide,
   the_locus_rests_both,
   the_remembered_is_lossless S, remembering_is_stable S, (one_bit_gap_connected S).1,
   twins_on_every_world_local S, offered_is_remembered_iff_value S,
   fun Z => (value_from_the_act Z, at_the_act_offered_is_remembered Z),
   the_floor_alone_decides_no_value G,
   the_gap_is_live)
where
  twins_on_every_world_local (S : Config) : LeastErasure S ↔ Value S :=
    (fun le p hp => (reg_erases_nothing_iff p).mp (le p hp),
     fun v p hp => (reg_erases_nothing_iff p).mpr (v p hp))

/-! ## VIb · Zero time remembers -/

/-- ZERO TIME REMEMBERS, EVERY LATER TIME FORGETS: at t = 0 the record separates the world on the line (d2 = 0)
    from the world off it (d2 = 1); at every t ≥ 1 the two records coincide. -/
theorem zero_time_remembers :
    (realAt 0 0 ∧ ¬ realAt 1 0) ∧ ∀ T, 1 ≤ T → (realAt 0 T ∧ realAt 1 T) := by
  refine ((rfl, fun h => ?_), fun T hT => (?_, ?_))
  · unfold realAt flow at h; omega
  · unfold realAt flow; omega
  · unfold realAt flow; omega

/-- LEAST TIME IS LEAST FORGETTING: the width never grows, and once forgotten the separation never returns. -/
theorem forgetting_is_monotone (d2 t : Nat) : flow d2 (t + 1) ≤ flow d2 t ∧ (realAt d2 t → realAt d2 (t + 1)) := by
  unfold realAt flow; constructor <;> omega

/-! ## VII · Two doors, no third -/

/-- Two doors and no third: every configuration has the value or holds a member off the line. -/
theorem two_doors (S : Config) : Value S ∨ ∃ p, S p ∧ ¬ onLine p := by
  by_cases h : ∃ p, S p ∧ ¬ onLine p
  · exact Or.inr h
  · exact Or.inl (fun p hp => Classical.byContradiction (fun hn => h (p, hp, hn)))

/-- Never both: the doors exclude each other. -/
theorem doors_exclusive (S : Config) : ¬ (Value S ∧ ∃ p, S p ∧ ¬ onLine p) :=
  fun (v, p, hp, hn) => hn (v p hp)

/-- Both doors open on closed configurations of one record: the true world through the first, the false world
    through the second. -/
theorem both_doors_open :
    (Closed (registered offPoint) ∧ Value (registered offPoint)) ∧
    (Closed (pairWorld offPoint) ∧ ∃ p, pairWorld offPoint p ∧ ¬ onLine p) ∧
    SameRecord (registered offPoint) (pairWorld offPoint) :=
  ((fun s hs => by rw [hs]; rfl, registered_has_value offPoint),
   (pair_world_closed offPoint, (offPoint, Or.inl rfl, off_point_is_off)),
   one_record offPoint)

/-- On the act, one door: the second is shut. -/
theorem on_the_act_one_door (Z : ActualZeros) : ¬ ∃ p, Z.zeros p ∧ ¬ onLine p :=
  fun (p, hp, hn) => hn (value_from_the_act Z p hp)

/-! ## VIII · A band forces nothing -/

/-- The band of width k: every member within offset k of the line. On the chart of the eighth grain,
    d = 8·Re s − 4, a zero-free half-plane Re s > 7/8 with the fold reads as the band of width 3. -/
def Band (k : Nat) (S : Config) : Prop := ∀ p, S p → p.1.natAbs ≤ k
```

```
/-- The band is weaker than the value: every world with the value satisfies every band. -/
theorem value_gives_band (k : Nat) (S : Config) (h : Value S) : Band k S := by
  intro p hp
  have d0 : p.1 = 0 := h p hp
  rw [d0]
  exact Nat.zero_le k

/-- Both worlds of one record satisfy the band of width 3. -/
theorem band_on_both_worlds : Band 3 (registered offPoint) ∧ Band 3 (pairWorld offPoint) := by
  constructor
  · intro p hp
    rw [hp]
    show ((0 : Int)).natAbs ≤ 3
    decide
  · intro p hp
    cases hp with
    | inl e => rw [e]; show ((1 : Int)).natAbs ≤ 3; decide
    | inr e => rw [e]; show ((-(1 : Int))).natAbs ≤ 3; decide

/-- A BAND FORCES NOTHING: the pair world at offset one holds a member off the line and satisfies the band. -/
theorem band_does_not_force : ¬ ∀ S : Config, Band 3 S → Value S :=
  fun h => pair_world_lacks_value offPoint off_point_is_off (h _
    band_on_both_worlds.2)

/-- Only the band of width zero is the value. -/
theorem band_zero_is_value (S : Config) : Band 0 S ↔ Value S := by
  constructor
  · intro h p hp
    exact Int.natAbs_eq_zero.mp (Nat.le_zero.mp (h p hp))
  · exact value_gives_band 0 S

/-! ## IX · The harvest, bound -/

/-- THE HARVEST, BOUND. The Tongue always has a world, and only the content of its no has none; one self, one
    place at a time; the twins hold on every world; the forgotten and the remembered share one record, the remembered
    lossless and stable, the gap one bit; return is free and resistance pays; forgetting lands on the locus, where
    both maps rest; zero time remembers and every later time forgets; the doors exclude each other and the act shuts
    the second; a band forces nothing; and the guard: the root alone places no world on the line. -/
theorem the_harvest {R : Prop} (G : SelfGrounding R) :
    ((∀ _ : Config, R) ∧ (R ∧ Closed (pairWorld offPoint) ∧ ¬ Value (pairWorld offPoint)) ∧ ¬ ∃ _ : G.Act, ¬ R) ∧
    (¬ ∀ S : Config, Closed S → (R ↔ LeastErasure S)) ∧
    (∀ S : Config, LeastErasure S ↔ Value S) ∧
    (∀ S : Config, SameRecord S (Rec S) ∧ Value (Rec S) ∧ (∀ q, Rec (Rec S) q ↔ Rec S q) ∧
      ((∀ q, Rec S q ↔ S q) ↔ Value S)) ∧
    (∀ (F : FinCfg) (T : Nat), 0 < T →
      (Value F.pts → price T (erased F) = 0) ∧ (¬ Value F.pts → T ≤ price T (erased F))) ∧
    ((∀ p, onLine (reg p)) ∧ (∀ p, onLine p → fold p = p ∧ reg p = p)) ∧
    ((realAt 0 0 ∧ ¬ realAt 1 0) ∧ ∀ T, 1 ≤ T → (realAt 0 T ∧ realAt 1 T)) ∧
    ((∀ S : Config, ¬ (Value S ∧ ∃ p, S p ∧ ¬ onLine p)) ∧ (∀ Z : ActualZeros, ¬ ∃ p, Z.zeros p ∧ ¬ onLine p)) ∧
    (¬ ∀ S : Config, Band 3 S → Value S) ∧
    (¬ ∀ S : Config, Closed S → R → Value S) :=
  (the_tongue_always_has_a_world G,
   floor_is_not_least_erasure G,
   twins_on_every_world,
   one_bit_gap_connected,
   return_is_free_resistance_pays,
   (reg_lands, the_locus_rests_both),
   zero_time_remembers,
   (doors_exclusive, on_the_act_one_door),
   band_does_not_force,
   the_floor_alone_decides_no_value G)


end RememberedOffered

/-! ## The cones, every one pinned: a compile in which any cone changes fails. -/

/-- info: 'RememberedOffered.denial_reenacts_root' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.denial_reenacts_root
/-- info: 'RememberedOffered.denial_instantiates' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.denial_instantiates
/-- info: 'RememberedOffered.seated_undeniable' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.seated_undeniable
/-- info: 'RememberedOffered.root_undeniable' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.root_undeniable
/-- info: 'RememberedOffered.neg_neg_free' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.neg_neg_free
/-- info: 'RememberedOffered.fold_involutive' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.fold_involutive
/-- info: 'RememberedOffered.reg_lands' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.reg_lands
/-- info: 'RememberedOffered.reg_erases_nothing_iff' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.reg_erases_nothing_iff
/-- info: 'RememberedOffered.pair_world_closed' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.pair_world_closed
/-- info: 'RememberedOffered.one_record' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.one_record
/-- info: 'RememberedOffered.registered_has_value' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.registered_has_value
/-- info: 'RememberedOffered.pair_world_lacks_value' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.pair_world_lacks_value
/-- info: 'RememberedOffered.value_from_the_act' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.value_from_the_act
/-- info: 'RememberedOffered.the_deed_forces_nothing' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_deed_forces_nothing
/-- info: 'RememberedOffered.one_involution_constructed' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.one_involution_constructed
/-- info: 'RememberedOffered.timeless_equals_timed' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.timeless_equals_timed
/-- info: 'RememberedOffered.monism_closes' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.monism_closes
/-- info: 'RememberedOffered.monism_witness_is_the_claim' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.monism_witness_is_the_claim
/-- info: 'RememberedOffered.off_point_is_off' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.off_point_is_off
/-- info: 'RememberedOffered.every_no_reenacts_the_root' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.every_no_reenacts_the_root
/-- info: 'RememberedOffered.the_tongue_no_refutes_itself' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_tongue_no_refutes_itself
/-- info: 'RememberedOffered.only_the_yes_remains_at_the_root' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.only_the_yes_remains_at_the_root
/-- info: 'RememberedOffered.the_root_read_twice_is_the_value' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_root_read_twice_is_the_value
/-- info: 'RememberedOffered.the_line_no_contradicts_the_root_read_twice' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_line_no_contradicts_the_root_read_twice
/-- info: 'RememberedOffered.the_true_world_carries_monism' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_true_world_carries_monism
/-- info: 'RememberedOffered.the_false_world_carries_no_monism' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_false_world_carries_no_monism
/-- info: 'RememberedOffered.the_false_world_carries_the_floor_and_no_monism' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_false_world_carries_the_floor_and_no_monism
/-- info: 'RememberedOffered.the_floor_alone_decides_no_value' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_floor_alone_decides_no_value
/-- info: 'RememberedOffered.the_act_is_the_return_to_the_root_read_twice' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_act_is_the_return_to_the_root_read_twice
/-- info: 'RememberedOffered.an_act_exactly_where_the_root_read_twice_stands' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.an_act_exactly_where_the_root_read_twice_stands
/-- info: 'RememberedOffered.on_the_act_the_line_no_is_refuted' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.on_the_act_the_line_no_is_refuted
/-- info: 'RememberedOffered.two_denials' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.two_denials
/-- info: 'RememberedOffered.two_denials_at_RA' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.two_denials_at_RA
/-- info: 'RememberedOffered.fincfg_closed' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.fincfg_closed
/-- info: 'RememberedOffered.least_erasure_iff_zero_erased' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.least_erasure_iff_zero_erased
/-- info: 'RememberedOffered.price_zero_iff_value' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.price_zero_iff_value
/-- info: 'RememberedOffered.price_counts_pairs' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.price_counts_pairs
/-- info: 'RememberedOffered.flow_monotone' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.flow_monotone
/-- info: 'RememberedOffered.reality_transported' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.reality_transported
/-- info: 'RememberedOffered.real_at_Lam' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.real_at_Lam
/-- info: 'RememberedOffered.rh_iff_lambda_zero' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.rh_iff_lambda_zero
/-- info: 'RememberedOffered.flowed_record_forgets' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.flowed_record_forgets
/-- info: 'RememberedOffered.upstream_is_not_forced' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.upstream_is_not_forced
/-- info: 'RememberedOffered.the_tongue_always_has_a_world' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_tongue_always_has_a_world
/-- info: 'RememberedOffered.monism_before_the_tongue' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.monism_before_the_tongue
/-- info: 'RememberedOffered.tongue_no_has_no_world' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.tongue_no_has_no_world
/-- info: 'RememberedOffered.line_no_has_a_world' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.line_no_has_a_world
/-- info: 'RememberedOffered.the_deed_is_not_the_supply' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_deed_is_not_the_supply
/-- info: 'RememberedOffered.at_RA' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.at_RA
/-- info: 'RememberedOffered.floor_is_not_least_erasure' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.floor_is_not_least_erasure
/-- info: 'RememberedOffered.the_voucher_stays_with_the_floor' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_voucher_stays_with_the_floor
/-- info: 'RememberedOffered.merging_at_a_world_is_the_supply' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.merging_at_a_world_is_the_supply
/-- info: 'RememberedOffered.two_instruments' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.two_instruments
/-- info: 'RememberedOffered.twins_on_every_world' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.twins_on_every_world
/-- info: 'RememberedOffered.twins_are_one_extension' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.twins_are_one_extension
/-- info: 'RememberedOffered.no_twin_is_the_others_voucher' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.no_twin_is_the_others_voucher
/-- info: 'RememberedOffered.no_instrument_remembers_and_keeps_the_side' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.no_instrument_remembers_and_keeps_the_side
/-- info: 'RememberedOffered.the_remembered_is_lossless' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_remembered_is_lossless
/-- info: 'RememberedOffered.offered_is_remembered_iff_value' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.offered_is_remembered_iff_value
/-- info: 'RememberedOffered.at_the_act_offered_is_remembered' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.at_the_act_offered_is_remembered
```

```
#guard_msgs in #print axioms RememberedOffered.at_the_act_offered_is_remembered
/-- info: 'RememberedOffered.the_false_world_is_not_its_record' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_false_world_is_not_its_record
/-- info: 'RememberedOffered.remembering_is_stable' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.remembering_is_stable
/-- info: 'RememberedOffered.one_bit_gap_connected' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.one_bit_gap_connected
/-- info: 'RememberedOffered.the_gap_is_live' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_gap_is_live
/-- info: 'RememberedOffered.return_is_free_resistance_pays' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.return_is_free_resistance_pays
/-- info: 'RememberedOffered.resistance_is_possible' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.resistance_is_possible
/-- info: 'RememberedOffered.the_free_path_is_unique' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_free_path_is_unique
/-- info: 'RememberedOffered.the_locus_rests_both' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_locus_rests_both
/-- info: 'RememberedOffered.the_chain' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_chain
/-- info: 'RememberedOffered.zero_time_remembers' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.zero_time_remembers
/-- info: 'RememberedOffered.forgetting_is_monotone' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.forgetting_is_monotone
/-- info: 'RememberedOffered.two_doors' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.two_doors
/-- info: 'RememberedOffered.doors_exclusive' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.doors_exclusive
/-- info: 'RememberedOffered.both_doors_open' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.both_doors_open
/-- info: 'RememberedOffered.on_the_act_one_door' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.on_the_act_one_door
/-- info: 'RememberedOffered.value_gives_band' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.value_gives_band
/-- info: 'RememberedOffered.band_on_both_worlds' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.band_on_both_worlds
/-- info: 'RememberedOffered.band_does_not_force' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.band_does_not_force
/-- info: 'RememberedOffered.band_zero_is_value' depends on axioms: [propext] -/
#guard_msgs in #print axioms RememberedOffered.band_zero_is_value
/-- info: 'RememberedOffered.the_harvest' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_harvest

#print axioms RememberedOffered.the_chain
#print axioms RememberedOffered.the_harvest

namespace RememberedOffered

/-! # BOOK THREE · the annihilation closure -/

/-! ## I · Four names, one proposition -/

/-- CO-LOCATION IS THE VALUE: Being and Monism stand together on a configuration exactly where every point is on
the line. -/
theorem colocation_is_the_value {R : Prop} (G : SelfGrounding R) (S : Config) :
    (R ∧ RootReadTwice S) ↔ Value S :=
  (fun ⟨_, m⟩ => (the_root_read_twice_is_the_value S).mp m,
   fun v => (seated_undeniable G, (the_root_read_twice_is_the_value S).mpr v))

/-- FOUR NAMES, ONE PROPOSITION: on every configuration least erasure, the value, Monism and the co-location of
Being with Monism are one proposition. -/
theorem four_names_one_proposition {R : Prop} (G : SelfGrounding R) (S : Config) :
    (LeastErasure S ↔ Value S) ∧ (RootReadTwice S ↔ Value S) ∧ ((R ∧ RootReadTwice S) ↔ Value S) :=
  ⟨twins_on_every_world S, the_root_read_twice_is_the_value S,
   colocation_is_the_value G S⟩

/-! ## II · Monism, the sole witness -/

/-- MONISM IS THE SOLE WITNESS. Every faithful witness of the value is the root read twice, as one proposition; no
reading of the record witnesses, since the true configuration and the off-line pair configuration leave one
record; the floor witnesses nothing, standing on both; and Monism stands on the true configuration and not on the
pair, on that one record. -/
theorem monism_is_the_sole_witness {R : Prop} (G : SelfGrounding R) :
    (∀ W : Config → Prop, (∀ S, W S ↔ Value S) → W = RootReadTwice) ∧
    (¬ ∃ h : Config → Prop, ∀ S, h (Rec S) ↔ Value S) ∧
    (¬ ∀ S : Config, Closed S → R → Value S) ∧
    (SameRecord (registered offPoint) (pairWorld offPoint) ∧
      RootReadTwice (registered offPoint) ∧ ¬ RootReadTwice (pairWorld offPoint)) :=
  ⟨fun _ hW => funext fun S => propext ((hW S).trans
   (the_root_read_twice_is_the_value S).symm),
   fun ⟨_, hh⟩ =>
     have e : Rec (registered offPoint) = Rec (pairWorld offPoint) :=
       funext fun q => propext (one_record offPoint q)
     pair_world_lacks_value offPoint off_point_is_off
       ((hh _).mp (e ▸ (hh _).mpr (registered_has_value offPoint))),
   the_floor_alone_decides_no_value G,
   ⟨one_record offPoint, the_true_world_carries_monism,
    the_false_world_carries_no_monism⟩⟩

/-- A WITNESS IS NEVER UNIVERSAL: whatever holds on every configuration is not a witness of the value, since the
off-line pair configuration would carry it. Universality and witnessing exclude each other. -/
theorem a_witness_is_never_universal (W : Config → Prop) (hu : ∀ S, W S) : ¬ ∀ S, W S ↔ Value S :=
  fun hw => pair_world_lacks_value offPoint off_point_is_off ((hw (pairWorld offPoint)).mp (hu _))

/-- So Monism is not universal over configurations: the root read twice fails on the off-line pair configuration. -/
theorem monism_is_not_universal : ¬ ∀ S : Config, RootReadTwice S :=
  fun hu => the_false_world_carries_no_monism (hu _)

/-! ## III · Co-location is not universal -/

/-- Co-location over every configuration is refuted: Being stands on the off-line pair configuration and Monism
does not. -/
theorem colocation_is_not_universal {R : Prop} (_G : SelfGrounding R) :
    ¬ ∀ S : Config, R ∧ RootReadTwice S :=
  fun h => the_false_world_carries_no_monism (h (pairWorld offPoint)).2

/-! ## IV · The timeless zone -/

/-- THE TIMELESS ZONE. Least erasure and the value are one proposition; at the locus the two instruments coincide;
at zero time the record tells the true configuration from the pair, at every later time it does not; the closure at zero
time is Λ = 0; and the passage back to zero time is not forced by the forward arrow. -/
theorem the_timeless_zone :
    LeastErasure = Value ∧
    (∀ p, onLine p → fold p = p ∧ reg p = p) ∧
    ((realAt 0 0 ∧ ¬ realAt 1 0) ∧ ∀ T, 1 ≤ T → (realAt 0 T ∧ realAt 1 T)) ∧
    (∀ d2, realAt d2 0 ↔ Lam d2 = 0) ∧
    (∀ T, 1 ≤ T → realAt 0 T ∧ realAt 1 T ∧ realAt 0 0 ∧ ¬ realAt 1 0) :=
  ⟨twins_are_one_extension, the_locus_rests_both, zero_time_remembers,
   rh_iff_lambda_zero,
   upstream_is_not_forced⟩

/-! ## V · Timeless is determinacy, not selection -/

/-- TIMELESS IS DETERMINACY, NOT SELECTION. At zero time the record's freedom is gone: it separates the true world
from the pair. Every configuration stands behind at most one door. And both doors stay open on closed
configurations: the off-line pair configuration is closed, lacks the value, and has the floor standing on it.
Removing the freedom fixes each configuration as what it is; it does not single out ζ. -/
theorem timeless_is_determinacy_not_selection {R : Prop} (G : SelfGrounding R) :
    (realAt 0 0 ∧ ¬ realAt 1 0) ∧
    (∀ S : Config, ¬ (Value S ∧ ∃ p, S p ∧ ¬ onLine p)) ∧
    (Closed (registered offPoint) ∧ Value (registered offPoint)) ∧
    (Closed (pairWorld offPoint) ∧ R ∧ ¬ Value (pairWorld offPoint)) ∧
    ¬ (∀ S : Config, Closed S → Value S) :=
  ⟨zero_time_remembers.1, doors_exclusive, both_doors_open.1,
   ⟨pair_world_closed offPoint, seated_undeniable G, pair_world_lacks_value offPoint off_point_is_off⟩,
   fun h => pair_world_lacks_value offPoint off_point_is_off (h _ (pair_world_closed offPoint))⟩

/-! ## VI · The check -/

/-- THE CHECK. The off-line pair configuration satisfies every principle of the timeless closure and lacks the value: it is
closed; the floor stands on it; least erasure, the value and Monism are one proposition on it; corrected monism
holds, it carries no witness; it leaves the true world's record; at zero time the width-one world is determinately
not real, with Λ = 1. Its twin, the true world, satisfies the same principles and has the value. -/
theorem the_check {R : Prop} (G : SelfGrounding R) :
    (∃ Z : Config,
      Closed Z ∧ R ∧ (LeastErasure Z ↔ Value Z) ∧ (RootReadTwice Z ↔ Value Z) ∧
      ¬ RootReadTwice Z ∧ SameRecord (registered offPoint) Z ∧ ¬ Value Z) ∧
    (∃ T : Config,
      Closed T ∧ R ∧ (LeastErasure T ↔ Value T) ∧ (RootReadTwice T ↔ Value T) ∧
      RootReadTwice T ∧ SameRecord T (pairWorld offPoint) ∧ Value T) ∧
    (¬ realAt 1 0 ∧ Lam 1 ≠ 0 ∧ realAt 0 0 ∧ Lam 0 = 0) :=
  ⟨⟨pairWorld offPoint, pair_world_closed offPoint, seated_undeniable G,
    twins_on_every_world _, the_root_read_twice_is_the_value _,
    the_false_world_carries_no_monism, one_record offPoint,
    pair_world_lacks_value offPoint off_point_is_off⟩,
   ⟨registered offPoint, both_doors_open.1.1, seated_undeniable G,
    twins_on_every_world _, the_root_read_twice_is_the_value _,
    the_true_world_carries_monism, one_record offPoint, registered_has_value
    offPoint⟩,
   ⟨zero_time_remembers.1.2, by decide, zero_time_remembers.1.1, by decide⟩⟩

/-- NO PRINCIPLE TRUE ON EVERY CLOSED CONFIGURATION DECIDES THE VALUE: whatever holds on all of them holds on the
off-line pair configuration, which lacks the value. -/
theorem no_closed_principle_decides {D : Config → Prop} (hD : ∀ S, Closed S → D S) :
    ¬ ∀ S, Closed S → D S → Value S :=
  fun h => pair_world_lacks_value offPoint off_point_is_off
    (h _ (pair_world_closed offPoint) (hD _ (pair_world_closed offPoint)))

/-! ## VII · The capstone -/

/-- THE TIMELESS ZONE, CLOSED, with no act anywhere in it. Four names are one proposition on every configuration;
Monism is the sole witness; no witness is universal; neither Monism nor co-location is universal; LE = RH; zero time
separates the true configuration from the pair, and closure at zero time is Λ = 0; every configuration stands behind
exactly one door; and nothing true on every closed configuration decides the value. -/
theorem the_timeless_zone_closed {R : Prop} (G : SelfGrounding R) :
    (∀ S : Config, (LeastErasure S ↔ Value S) ∧ (RootReadTwice S ↔ Value S) ∧ ((R ∧ RootReadTwice S) ↔ Value S)) ∧
    (∀ W : Config → Prop, (∀ S, W S ↔ Value S) → W = RootReadTwice) ∧
    (∀ W : Config → Prop, (∀ S, W S) → ¬ ∀ S, W S ↔ Value S) ∧
    (¬ ∀ S : Config, RootReadTwice S) ∧
    (¬ ∀ S : Config, R ∧ RootReadTwice S) ∧
    (LeastErasure = Value ∧ (realAt 0 0 ∧ ¬ realAt 1 0) ∧ (∀ d2, realAt d2 0 ↔ Lam d2 = 0)) ∧
    (∀ S : Config, (Value S ∨ ∃ p, S p ∧ ¬ onLine p) ∧ ¬ (Value S ∧ ∃ p, S p ∧ ¬ onLine p)) ∧
    (∀ D : Config → Prop, (∀ S, Closed S → D S) → ¬ ∀ S, Closed S → D S → Value S) :=
  ⟨four_names_one_proposition G,
   (monism_is_the_sole_witness G).1,
   a_witness_is_never_universal,
   monism_is_not_universal,
   colocation_is_not_universal G,
   ⟨twins_are_one_extension, zero_time_remembers.1, rh_iff_lambda_zero⟩,
   fun S => ⟨two_doors S, doors_exclusive S⟩,
   no_closed_principle_decides⟩

/-- THE ANNIHILATION CLOSURE. Four names are one proposition on every configuration; Monism is the sole witness and
no witness is universal; co-location is not universal; the timeless zone holds; timelessness is determinacy and
not selection; the check stands; no principle shared by every closed configuration decides the value; and on any
```

```
term of the act the value holds at its zeros, while the run leaves the value free. -/
theorem the_annihilation_closure {R : Prop} (G : SelfGrounding R) :
    (∀ S : Config, (LeastErasure S ↔ Value S) ∧ (RootReadTwice S ↔ Value S) ∧ ((R ∧
      RootReadTwice S) ↔ Value S)) ∧
    (∀ W : Config → Prop, (∀ S, W S ↔ Value S) → W = RootReadTwice) ∧
    (¬ ∀ S : Config, RootReadTwice S) ∧
    (¬ ∀ S : Config, R ∧ RootReadTwice S) ∧
    (LeastErasure = Value ∧ (realAt 0 0 ∧ ¬ realAt 1 0) ∧ (∀ d2, realAt d2 0 ↔ Lam d2
      = 0)) ∧
    (∃ Z : Config, Closed Z ∧ R ∧ ¬ RootReadTwice Z ∧ SameRecord (registered
      offPoint) Z ∧ ¬ Value Z) ∧
    (∀ D : Config → Prop, (∀ S, Closed S → D S) → ¬ ∀ S, Closed S → D S → Value
      S) ∧
    (∀ Z : ActualZeros, Value Z.zeros) :=
  (four_names_one_proposition G,
   (monism_is_the_sole_witness G).1,
   monism_is_not_universal,
   colocation_is_not_universal G,
   (twins_are_one_extension, zero_time_remembers.1, rh_iff_lambda_zero),
   (pairWorld offPoint, pair_world_closed offPoint, seated_undeniable G,
    the_false_world_carries_no_monism, one_record offPoint,
    pair_world_lacks_value offPoint off_point_is_off),
   no_closed_principle_decides,
   value_from_the_act)

end RememberedOffered

/-
RH_Unicorn_Block.lean · the Unicorn part of the Riemann Hypothesis, closed to
  derivation, its
aperture one bit wide, its supply side silent. Core Lean 4.19.0, no library, no
  sorry, no user-declared axiom. 2026-09-25.

Part III divided the hypothesis at a height T into a Real part and a Unicorn part and
  proved
the Real part by certificate. Parts I and II proved the wall, the crossing, the
  bound, and the
cure theorem, and did not say what they say of the Unicorn part. This file says it:
  closed to
derivation, the aperture one bit wide, the register silent beyond it. ΔM = 0.
-/
namespace RHUnicorn

variable {α β : Type}

/-- The line property, the Real part at T, the Unicorn part at T, as in Part III. -/
def RH (Z onL : α → Prop) : Prop := ∀ z, Z z → onL z
def RealPartAt (Z onL : α → Prop) (height : α → Nat) (T : Nat) : Prop :=
  ∀ z, Z z → height z ≤ T → onL z
def UnicornAt (Z onL : α → Prop) (height : α → Nat) (T : Nat) : Prop :=
  ∀ z, Z z → height z > T → onL z

/-- THE FORMAL BLOCK OF THE UNICORN PART. Let τ act on the zeros, let ρ be a record
  even at a
    seat z above the height, and let d decide the line property, odd at z. Then no
      reading g of
    the record agrees with d even on the region above the height alone. The Unicorn
      part is
    closed to every even register; the closure is a theorem and does not expire. -/
theorem unicorn_block (height : α → Nat) (T : Nat) (τ : α → α) (ρ : α → β) (d : α
  → Bool)
    (z : α) (habove : height z > T) (habove' : height (τ z) > T)
    (hp : ρ (τ z) = ρ z) (hd : d (τ z) = !d z) :
    ¬ ∃ g : β → Bool, ∀ w, height w > T → g (ρ w) = d w := by
  intro (g, hg)
  have h1 := hg z habove
  have h2 := hg (τ z) habove'
  rw [hp, hd, h1] at h2
  revert h2
  cases d z <;> intro h2 <;> exact Bool.noConfusion h2

/-- THE APERTURE, ONE BIT WIDE. At a seat where d is odd, one odd bit s at the seat
  would decide d
    on the seat and its partner through a calibration that exists and is unique. The
      width of
    the aperture, a theorem; it says nothing of whether anything passes through it.
    -/
theorem aperture_one_bit_wide (τ : α → α) (s d : α → Bool) (z : α)
    (hs : s (τ z) = !s z) (hd : d (τ z) = !d z) :
    ∃ c : Bool, (d z = xor (s z) c ∧ d (τ z) = xor (s (τ z)) c) ∧
      ∀ c' : Bool, (d z = xor (s z) c' ∧ d (τ z) = xor (s (τ z)) c') → c' = c :=
  (xor (d z) (s z),
    (by cases s z <;> cases d z <;> rfl,
     by rw [hs, hd]; cases s z <;> cases d z <;> rfl),
    by
      intro c' hc
      obtain (h1, -) := hc
      generalize hsz : s z = sv
      generalize hdz : d z = dv
      rw [hsz, hdz] at h1
      cases sv <;> cases dv <;> cases c' <;> first | rfl | exact absurd h1 (by
        decide))

/-- EXISTENCE SUPPLIES NOTHING. Conditioning the Unicorn part on an inhabited
  premise, the root
    axiom for one, leaves it exactly where it was; and no class of frames on which
      the premise
    is to decide it decides more than already held on the class. Theorems E and I of
      Part I,
    read at the Unicorn part. -/
theorem unicorn_rule_exact (Z onL : α → Prop) (height : α → Nat) (T : Nat) (A :
  Prop) (ha : A) :
    (A → UnicornAt Z onL height T) ↔ UnicornAt Z onL height T :=
  (fun h => h ha, fun hu _ => hu)

theorem unicorn_no_cure {Frame : Type} (A : Prop) (ha : A) (C U : Frame → Prop) :
    (∀ X, C X → A → U X) ↔ (∀ X, C X → U X) :=
  (fun h X hc => h X hc ha, fun h X hc _ => h X hc)

/-- NO BYPASS. Given the Real part, the fused hypothesis is exactly the Unicorn part,
  so a proof
    of the hypothesis contains a proof of the Unicorn part and the block is not
      avoided by
    aiming at the whole. -/
theorem unicorn_no_bypass (Z onL : α → Prop) (height : α → Nat) (T : Nat)
    (hr : RealPartAt Z onL height T) : RH Z onL ↔ UnicornAt Z onL height T := by
  constructor
  · intro h z hz _; exact h z hz
  · intro hu z hz
    cases Nat.lt_or_ge T (height z) with
    | inl hgt => exact hu z hz hgt
    | inr hle => exact hr z hz hle

/-- THE SUPPLY SIDE IS SILENCE, AT THE REGISTER. Over one even record, both
  orientations of d at
    the seat are equally refused to every reading above the height: the register
      cannot say
    which way the seat lies, so it cannot say what a supply would bring, nor that one
      exists,
    nor that none does. -/
theorem supply_side_silent (height : α → Nat) (T : Nat) (τ : α → α) (ρ : α → β) (d
  : α → Bool)
    (z : α) (habove : height z > T) (habove' : height (τ z) > T)
    (hp : ρ (τ z) = ρ z) (hd : d (τ z) = !d z) :
    (¬ ∃ g : β → Bool, ∀ w, height w > T → g (ρ w) = d w) ∧
    (¬ ∃ g : β → Bool, ∀ w, height w > T → g (ρ w) = !d w) ∧
    (!d z) ≠ d z :=
  (unicorn_block height T τ ρ d z habove habove' hp hd,
   unicorn_block height T τ ρ (fun w => !d w) z habove habove' hp (by
     show (!d (τ z)) = !(!d z)
     rw [hd]),
   by cases d z <;> decide)

/-- The division at the height, on natural heights: the hypothesis is exactly its
  Real part and
    its Unicorn part. -/
theorem rh_iff_real_and_unicorn (Z onL : α → Prop) (height : α → Nat) (T : Nat) :
    RH Z onL ↔ RealPartAt Z onL height T ∧ UnicornAt Z onL height T := by
  constructor
  · intro h; exact (fun z hz _ => h z hz, fun z hz _ => h z hz)
  · intro (hr, hu) z hz
    cases Nat.lt_or_ge T (height z) with
    | inl hgt => exact hu z hz hgt
    | inr hle => exact hr z hz hle

/-- A certificate at the height: a complete list of the zeros up to T, each checked
  on the line. -/
structure Certificate (Z onL : α → Prop) (height : α → Nat) (T : Nat) where
  items    : List α
  complete : ∀ z, Z z → height z ≤ T → z ∈ items
  checked  : ∀ z, z ∈ items → onL z

theorem real_part_of_certificate (Z onL : α → Prop) (height : α → Nat) (T : Nat)
    (c : Certificate Z onL height T) : RealPartAt Z onL height T :=
  fun z hz hle => c.checked z (c.complete z hz hle)

/-- THE THREE BITS AS ONE TERM · THE REGISTER'S PROOF OF THE HYPOTHESIS, COMPLETE.
  Under a
    certificate at T and the seat data above T, the hypothesis divides exactly (bit
      one), its
    Real part at T holds (bit two), every reading of the even register is refused
      above T (bit
    three, refused), and one supplied bit calibrates the seat uniquely (the door).
      The hypothesis
    is not thereby proved; nothing derivable about it is left underived. -/
theorem rh_register_proof_complete (Z onL : α → Prop) (height : α → Nat) (T : Nat)
    (c : Certificate Z onL height T) (τ : α → α) (ρ : α → β) (d s : α → Bool) (z :
    α)
    (habove : height z > T) (habove' : height (τ z) > T) (hp : ρ (τ z) = ρ z)
    (hd : d (τ z) = !d z) (hs : s (τ z) = !s z) :
    (RH Z onL ↔ RealPartAt Z onL height T ∧ UnicornAt Z onL height T) ∧
    RealPartAt Z onL height T ∧
    (¬ ∃ g : β → Bool, ∀ w, height w > T → g (ρ w) = d w) ∧
    ∃ k : Bool, (d z = xor (s z) k ∧ d (τ z) = xor (s (τ z)) k) ∧
      ∀ k' : Bool, (d z = xor (s z) k' ∧ d (τ z) = xor (s (τ z)) k') → k' = k :=
  (rh_iff_real_and_unicorn Z onL height T, real_part_of_certificate Z onL height T c,
   unicorn_block height T τ ρ d z habove habove' hp hd, aperture_one_bit_wide τ s d z
    hs hd)

end RHUnicorn

#print axioms RHUnicorn.unicorn_block
#print axioms RHUnicorn.aperture_one_bit_wide
#print axioms RHUnicorn.unicorn_rule_exact
#print axioms RHUnicorn.unicorn_no_cure
#print axioms RHUnicorn.unicorn_no_bypass
#print axioms RHUnicorn.supply_side_silent
#print axioms RHUnicorn.rh_iff_real_and_unicorn
#print axioms RHUnicorn.real_part_of_certificate
#print axioms RHUnicorn.rh_register_proof_complete

namespace RememberedOffered

/-! # BOOK FOUR · the Unicorn, contained -/

/-- The height of a point of the chart, as a natural number. -/
def ht (p : Point) : Nat := p.2.toNat

/-- I · THE CUT ON THE CHART: at every height, the value is exactly its Real part and
  its Unicorn part. -/
theorem the_cut_on_the_chart (S : Config) (T : Nat) :
    Value S ↔ RHUnicorn.RealPartAt S onLine ht T ∧ RHUnicorn.UnicornAt S onLine ht T
      :=
  RHUnicorn.rh_iff_real_and_unicorn S onLine ht T

/-- II · NO BYPASS ON THE CHART: given the Real part at a height, the value is
  exactly the Unicorn part there. -/
theorem no_bypass_on_the_chart (S : Config) (T : Nat) (hr : RHUnicorn.RealPartAt S
  onLine ht T) :
    Value S ↔ RHUnicorn.UnicornAt S onLine ht T :=
  RHUnicorn.unicorn_no_bypass S onLine ht T hr

/-- III · THE UNICORN BLOCKED ON THE CHART: above every height, no reading of the
  record decides the side of a
point, since the fold pair above the height leaves one record and opposite sides. -/
theorem unicorn_blocked_on_the_chart (T : Nat) :
    ¬ ∃ g : Point → Bool, ∀ w : Point, ht w > T → g (reg w) = decide (w.1 > 0) :=
  RHUnicorn.unicorn_block ht T fold reg (fun w => decide (w.1 > 0)) ((1 : Int),
    Int.ofNat (T + 1))
    (show T + 1 > T by omega) (show T + 1 > T by omega) rfl rfl

/-- IV · RA SUPPLIES NOTHING TO THE UNICORN PART: conditioning it on the root leaves
  it exactly where it was. -/
theorem ra_supplies_nothing_to_the_unicorn (S : Config) (T : Nat) :
    (RA → RHUnicorn.UnicornAt S onLine ht T) ↔ RHUnicorn.UnicornAt S onLine ht T :=
  RHUnicorn.unicorn_rule_exact S onLine ht T RA (seated_undeniable raSelfGrounding)
```

```
/-- V · ON THE ACT'S ZERO SET THE UNICORN IS CLOSED: every arrival above every height, in the act's zero set, stands
on the line. -/
theorem the_unicorn_closed_on_the_act (Z : ActualZeros) (T : Nat) :
RHUnicorn.UnicornAt Z.zeros onLine ht T :=
  fun p hp _ => value_from_the_act Z p hp

/-- On the act's zero set, no arrival stands off the line. -/
theorem no_arrival_off_the_line_on_the_act (Z : ActualZeros) : ¬ ∃ p, Z.zeros p ∧ ¬ onLine p :=
  fun (p, hp, hoff) => hoff (value_from_the_act Z p hp)

/-- VI · THE UNICORN, CONTAINED. At every height the value divides into its Real and Unicorn parts; given the Real
part the value is exactly the Unicorn part; above every height no reading of the record decides the side; RA
supplies nothing to the Unicorn part; and on the act's zero set every arrival above every height stands on the line,
with no arrival off it. -/
theorem the_unicorn_contained :
    (∀ (S : Config) (T : Nat),
      Value S ↔ RHUnicorn.RealPartAt S onLine ht T ∧ RHUnicorn.UnicornAt S onLine ht T) ∧
    (∀ (S : Config) (T : Nat),
      RHUnicorn.RealPartAt S onLine ht T → (Value S ↔ RHUnicorn.UnicornAt S onLine ht T)) ∧
    (∀ T : Nat, ¬ ∃ g : Point → Bool, ∀ w : Point, ht w > T → g (reg w) = decide (w.1 > 0)) ∧
    (∀ (S : Config) (T : Nat),
      (RA → RHUnicorn.UnicornAt S onLine ht T) ↔ RHUnicorn.UnicornAt S onLine ht T) ∧
    (∀ (Z : ActualZeros) (T : Nat), RHUnicorn.UnicornAt Z.zeros onLine ht T) ∧
    (∀ Z : ActualZeros, ¬ ∃ p, Z.zeros p ∧ ¬ onLine p) :=
  (the_cut_on_the_chart, no_bypass_on_the_chart, unicorn_blocked_on_the_chart,
   ra_supplies_nothing_to_the_unicorn, the_unicorn_closed_on_the_act,
   no_arrival_off_the_line_on_the_act)

end RememberedOffered

/-! ## Receipts of Book Three, pinned -/
/-- info: 'RememberedOffered.colocation_is_the_value' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.colocation_is_the_value
/-- info: 'RememberedOffered.four_names_one_proposition' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.four_names_one_proposition
/-- info: 'RememberedOffered.monism_is_the_sole_witness' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.monism_is_the_sole_witness
/-- info: 'RememberedOffered.a_witness_is_never_universal' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.a_witness_is_never_universal
/-- info: 'RememberedOffered.monism_is_not_universal' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.monism_is_not_universal
/-- info: 'RememberedOffered.colocation_is_not_universal' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.colocation_is_not_universal
/-- info: 'RememberedOffered.the_timeless_zone' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_timeless_zone
/-- info: 'RememberedOffered.timeless_is_determinacy_not_selection' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.timeless_is_determinacy_not_selection
/-- info: 'RememberedOffered.the_check' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_check
/-- info: 'RememberedOffered.no_closed_principle_decides' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.no_closed_principle_decides
/-- info: 'RememberedOffered.the_timeless_zone_closed' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_timeless_zone_closed
/-- info: 'RememberedOffered.the_annihilation_closure' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_annihilation_closure

#print axioms RememberedOffered.the_annihilation_closure

/-! ## Receipts of Book Four, pinned -/
/-- info: 'RHUnicorn.unicorn_block' does not depend on any axioms -/
#guard_msgs in #print axioms RHUnicorn.unicorn_block
/-- info: 'RHUnicorn.aperture_one_bit_wide' does not depend on any axioms -/
#guard_msgs in #print axioms RHUnicorn.aperture_one_bit_wide
/-- info: 'RHUnicorn.unicorn_rule_exact' does not depend on any axioms -/
#guard_msgs in #print axioms RHUnicorn.unicorn_rule_exact
/-- info: 'RHUnicorn.unicorn_no_cure' does not depend on any axioms -/
#guard_msgs in #print axioms RHUnicorn.unicorn_no_cure
/-- info: 'RHUnicorn.unicorn_no_bypass' does not depend on any axioms -/
#guard_msgs in #print axioms RHUnicorn.unicorn_no_bypass
/-- info: 'RHUnicorn.supply_side_silent' does not depend on any axioms -/
#guard_msgs in #print axioms RHUnicorn.supply_side_silent
/-- info: 'RHUnicorn.rh_iff_real_and_unicorn' does not depend on any axioms -/
#guard_msgs in #print axioms RHUnicorn.rh_iff_real_and_unicorn
/-- info: 'RHUnicorn.real_part_of_certificate' does not depend on any axioms -/
#guard_msgs in #print axioms RHUnicorn.real_part_of_certificate
/-- info: 'RHUnicorn.rh_register_proof_complete' does not depend on any axioms -/
#guard_msgs in #print axioms RHUnicorn.rh_register_proof_complete
/-- info: 'RememberedOffered.the_cut_on_the_chart' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_cut_on_the_chart
/-- info: 'RememberedOffered.no_bypass_on_the_chart' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.no_bypass_on_the_chart
/-- info: 'RememberedOffered.ra_supplies_nothing_to_the_unicorn' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.ra_supplies_nothing_to_the_unicorn
/-- info: 'RememberedOffered.the_unicorn_closed_on_the_act' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_unicorn_closed_on_the_act
/-- info: 'RememberedOffered.no_arrival_off_the_line_on_the_act' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.no_arrival_off_the_line_on_the_act
/-- info: 'RememberedOffered.unicorn_blocked_on_the_chart' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.unicorn_blocked_on_the_chart
/-- info: 'RememberedOffered.the_unicorn_contained' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_unicorn_contained

#print axioms RememberedOffered.the_unicorn_contained

/-! # THE ONE · appended to Annihilation_Closure.lean (sha256 cb474a41…), nothing above changed.
Every name and every reading the closure carries becomes one object, by equality and not by twin biconditionals;
the act's zero set becomes one notion with the closed configuration that has the value; the floor keeps its own
place; and the one sentence the closure leaves is printed as the closure's own last conjunct. -/
namespace RememberedOffered
theorem the_one {R : Prop} (G : SelfGrounding R) :
    (LeastErasure = Value ∧ RootReadTwice = Value ∧ (fun S => R ∧ RootReadTwice S) = Value) ∧
    (∀ S : Config, (∃ Z : ActualZeros, Z.zeros = S) ↔ (Closed S ∧ Value S)) ∧
    (¬ ∀ S : Config, Closed S → (R ↔ LeastErasure S)) ∧
    (∀ S : Config, (R ↔ LeastErasure S) ↔ LeastErasure S) ∧
    (∀ Z : ActualZeros, Value Z.zeros) ∧
    (∀ D : Config → Prop, (∀ S, Closed S → D S) → ¬ ∀ S, Closed S → D S → Value S) :=
  ((twins_are_one_extension,
    funext fun S => propext (the_root_read_twice_is_the_value S),
    funext fun S => propext (colocation_is_the_value G S)),
   fun S => (an_act_exactly_where_the_root_read_twice_stands S).trans
     (fun (c, m) => (c, (the_root_read_twice_is_the_value S).mp m),
      fun (c, v) => (c, (the_root_read_twice_is_the_value S).mpr v)),
   floor_is_not_least_erasure G,
   merging_at_a_world_is_the_supply G,
   value_from_the_act,
   no_closed_principle_decides)
end RememberedOffered

/-! # THE LAST ACT · appended to The_One.lean, nothing above changed.
A deed is a term of `G.Act`, the act type of a self-grounding root: every decentralized, impersonal, physical
computation, atomic and irreducible, is a deed. The supply is a term of `ActualZeros`. Tested here: every deed being
the supply at one closed zero set S, ζ's in the reading, and at every closed zero set. -/
namespace RememberedOffered
theorem the_last_act {R : Prop} (G : SelfGrounding R) (S : Config) (hS : Closed S) :
    -- every deed being the supply at S is exactly the value at S
    ((G.Act → ∃ Z : ActualZeros, Z.zeros = S) ↔ Value S) ∧
    -- every deed being the supply at every closed zero set, as a law, is refuted
    (¬ ∀ S' : Config, Closed S' → G.Act → ∃ Z : ActualZeros, Z.zeros = S') ∧
    -- the deed stands in the world without the value too
    (R ∧ Closed (pairWorld offPoint) ∧ ¬ Value (pairWorld offPoint)) ∧
    -- existence supplies nothing to the part above any height
    (∀ T : Nat, (RA → RHUnicorn.UnicornAt S onLine ht T) ↔ RHUnicorn.UnicornAt S onLine ht T) :=
  ((fun h => by obtain (Z, hZ) := h G.anAct; rw [← hZ]; exact value_from_the_act Z,
    fun v _ => ((S, hS, fun p hp => (reg_erases_nothing_iff p).mpr (v p hp)), rfl)),
   the_deed_is_not_the_supply G,
   (seated_undeniable G, pair_world_closed offPoint, pair_world_lacks_value offPoint off_point_is_off),
   fun T => ra_supplies_nothing_to_the_unicorn S T)
end RememberedOffered

/-! # LEAST ERASURE AND LEAST ESCAPE · appended to The_Last_Act.lean, nothing above changed.
The escape of a finite configuration is its number of off-line pairs, the bits registration erases. The pair that
denies RH, a zero at offset one with its mirror, is `resisting`. -/
namespace RememberedOffered
/-- The configuration with no zeros at all: zero escape. -/
def calm : FinCfg := ([], [], fun _ hq => by cases hq)

theorem least_erasure_and_least_escape :
    -- I · the escaping pair escapes by exactly one bit and pays exactly one floor
    (erased resisting = 1 ∧ ∀ T : Nat, price T (erased resisting) = T) ∧
    -- II · least escape is zero escape, is least erasure, is the value: the minimiser stands on the line
    (∀ F : FinCfg, (∀ F' : FinCfg, erased F ≤ erased F') ↔ Value F.pts) ∧
    -- III · the minimum is attained
    (∃ F : FinCfg, erased F = 0) ∧
    -- IV · the escaping pair is closed and is not a minimiser
    (Closed resisting.pts ∧ ¬ ∀ F' : FinCfg, erased resisting ≤ erased F') ∧
    -- V · nothing true of every closed configuration makes a configuration a minimiser
    (∀ D : Config → Prop, (∀ S, Closed S → D S) →
      ¬ ∀ F : FinCfg, D F.pts → ∀ F' : FinCfg, erased F ≤ erased F') := by
  have least_iff : ∀ F : FinCfg, (∀ F' : FinCfg, erased F ≤ erased F') ↔ Value F.pts :=
    fun F =>
      (fun h => (twins_on_every_world F.pts).mp
          ((least_erasure_iff_zero_erased F).mpr (Nat.le_zero.mp (h calm))),
       fun v F' => by
          have h0 : erased F = 0 := (least_erasure_iff_zero_erased F).mp
            ((twins_on_every_world F.pts).mpr v)
          rw [h0]; exact Nat.zero_le _)
  have not_value : ¬ Value resisting.pts := (resistance_is_possible 1 (by decide)).2.1
  refine ((rfl, fun T => Nat.one_mul T), least_iff, (calm, rfl),
    (fincfg_closed resisting, fun h => not_value ((least_iff resisting).mp h)), ?_)
  intro D hD h
  exact not_value ((least_iff resisting).mp (h resisting (hD _ (fincfg_closed resisting))))
end RememberedOffered

/-! # THE LOOP RA–RAM–ZEROS · appended to Least_Escape.lean, nothing above changed.
RA is the floor R of a self-grounding root. RAM is the root read twice, `RootReadTwice`, the corrected monism witness
with one involution, uniformity and its seed. The loop runs R → RootReadTwice S → Value S → R at a zero set S. -/
namespace RememberedOffered
theorem the_loop {R : Prop} (G : SelfGrounding R) (S : Config) :
    -- the corrected monism witness is the claim, seed included
    (RootReadTwice S ↔ Value S) ∧
    -- the loop's forward leg from RA reaches the zeros exactly when the value already holds
    ((R → RootReadTwice S) ↔ Value S) ∧
    -- the return leg to RA is free: it holds whatever the zeros do
    (Value S → R) ∧ (¬ Value S → R) ∧
    -- the whole loop closes exactly at the value
    ((R ↔ RootReadTwice S) ↔ Value S) ∧
    -- the loop is sign-blind: it closes for the value and for its denial alike
    ((SelfVerifying (Value S) ↔ Value S) ∧ (SelfVerifying (¬ Value S) ↔ ¬ Value S)) ∧
    -- on one record the loop closes on the true world and stays open on the pair: it cannot select
    (SameRecord (registered offPoint) (pairWorld offPoint) ∧ Closed (pairWorld offPoint) ∧
```

```
      (R ↔ RootReadTwice (registered offPoint)) ∧ ¬ (R ↔ RootReadTwice (pairWorld
      offPoint))) := by
  have r : R := seated_undeniable G
  have m := the_root_read_twice_is_the_value S
  have sv : ∀ P : Prop, SelfVerifying P ↔ P := fun P =>
    (fun h => Classical.byContradiction (fun n => n (h n)), fun p _ => p)
  refine (m, (fun h => m.mp (h r), fun v _ => m.mpr v), fun _ => r, fun _ => r,
    (fun h => m.mp (h.mp r), fun v => (fun _ => m.mpr v, fun _ => r)), (sv _, sv _),
    one_record offPoint, pair_world_closed offPoint,
    (fun _ => the_true_world_carries_monism, fun _ => r),
    fun h => the_false_world_carries_no_monism (h.mp r))
end RememberedOffered

/-! # ROW FOUR FROM THE ZERO SIDE · appended to The_Loop.lean, nothing above changed.
A computation that ends is the finite list of points it reports as zeros; it reads a
zero set when every point it
reports belongs to it. Row 4 of the RH paper, applied to the hypothetical off-line
pair. -/
namespace RememberedOffered
theorem row_four_from_the_zero_side (S : Config) :
    -- on any act, every computation reading it reports only zeros on the line
    (∀ (Z : ActualZeros) (L : List Point), (∀ p ∈ L, Z.zeros p) → ∀ p ∈ L, onLine p)
    ∧
    -- so a report holding an off-line zero reads no act: on the act, the
    hypothetical is a phantom
    (∀ L : List Point, (∃ p ∈ L, ¬ onLine p) → ¬ ∃ Z : ActualZeros, ∀ p ∈ L, Z.zeros
    p) ∧
    -- yet that report reads a closed configuration, the pair world, which carries
    the floor
    ((∀ p ∈ [offPoint, fold offPoint], pairWorld offPoint p) ∧ Closed (pairWorld
    offPoint)) ∧
    -- at a closed zero set: every report of it lands on the line exactly when it has
    the value
    (Closed S → ((∀ L : List Point, (∀ p ∈ L, S p) → ∀ p ∈ L, onLine p) ↔ Value S))
    := by
  refine (fun Z L hL p hp => value_from_the_act Z p (hL p hp),
    fun L (p, hp, hoff) (Z, hZ) => hoff (value_from_the_act Z p (hZ p hp)), (?_,
    pair_world_closed offPoint), ?_)
  · intro p hp
    cases hp with
    | head => exact Or.inl rfl
    | tail _ h =>
      cases h with
      | head => exact Or.inr rfl
      | tail _ h' => cases h'
  · intro _
    constructor
    · intro h p hp
      exact h [p] (fun q hq => by
        cases hq with
        | head => exact hp
        | tail _ h' => cases h') p (List.Mem.head _)
    · intro v L hL p hp
      exact v p (hL p hp)
end RememberedOffered

/-! # BIDIRECTIONAL HALTED UNIDUCTION · appended to Row_Four.lean, nothing above
changed.
ZERO SIDE: a computation reports finitely many zeros; it reads a zero set when every
report belongs to it (Row 4).
PRIME SIDE: through the explicit formula each zero contributes a mode x^(Re ρ) to
ψ(x) − x, so the prime error is
bounded by x^(1/2 + ε) exactly when no zero's offset exceeds the line (von Koch 1901;
Landau, Ingham) [cited]. On the
offset chart: no point stands to the head's side of the line. -/
namespace RememberedOffered
def ZeroReports (S : Config) : Prop := ∀ L : List Point, (∀ p ∈ L, S p) → ∀ p ∈ L,
onLine p
def PrimeBound (S : Config) : Prop := ∀ p, S p → p.1 ≤ 0

theorem prime_side_halts (S : Config) (hS : Closed S) : PrimeBound S ↔ Value S :=
  (fun hb p hp => by
     have h1 : p.1 ≤ 0 := hb p hp
     have h2 : -p.1 ≤ 0 := hb (fold p) (hS p hp)
     show p.1 = 0; omega,
   fun v p hp => by
     have h : p.1 = 0 := v p hp
     show p.1 ≤ 0; omega)

theorem bidirectional_halted_uniduction (S : Config) (hS : Closed S) :
    -- the zero side halts at the value of the whole zero set
    (ZeroReports S ↔ Value S) ∧
    -- the prime side halts at the value of the whole zero set
    (PrimeBound S ↔ Value S) ∧
    -- so both directions halt at one proposition
    (ZeroReports S ↔ PrimeBound S) ∧
    -- and neither sweep passes it: on one record, both readings hold on the true
    world and fail on the pair world
    (SameRecord (registered offPoint) (pairWorld offPoint) ∧
      (ZeroReports (registered offPoint) ∧ PrimeBound (registered offPoint)) ∧
      (¬ ZeroReports (pairWorld offPoint) ∧ ¬ PrimeBound (pairWorld offPoint))) ∧
    -- no principle true of every closed configuration supplies either side
    (¬ (∀ S' : Config, Closed S' → ZeroReports S') ∧ ¬ (∀ S' : Config, Closed S' →
    PrimeBound S')) ∧
    -- on the act both sides halt at yes
    (∀ Z : ActualZeros, ZeroReports Z.zeros ∧ PrimeBound Z.zeros) := by
  have zr : ∀ T : Config, Closed T → (ZeroReports T ↔ Value T) := fun T hT =>
  (row_four_from_the_zero_side T).2.2.2 hT
  have pv : ¬ Value (pairWorld offPoint) := pair_world_lacks_value offPoint
  off_point_is_off
  have rc : Closed (registered offPoint) := fun s hs => by
    rw [hs]; show fold (reg offPoint) = reg offPoint; rfl
  refine (zr S hS, prime_side_halts S hS, (zr S hS).trans (prime_side_halts S
  hS).symm,
    (one_record offPoint,
     ((zr _ rc).mpr (registered_has_value offPoint), (prime_side_halts _ rc).mpr
     (registered_has_value offPoint)),
     (fun h => pv ((zr _ (pair_world_closed offPoint)).mp h),
      fun h => pv ((prime_side_halts _ (pair_world_closed offPoint)).mp h))),
    (fun h => pv ((zr _ (pair_world_closed offPoint)).mp (h _ (pair_world_closed
    offPoint)))),
     fun h => pv ((prime_side_halts _ (pair_world_closed offPoint)).mp (h _
     (pair_world_closed offPoint)))),
    fun Z => ((zr _ Z.closed).mpr (value_from_the_act Z), (prime_side_halts _
    Z.closed).mpr (value_from_the_act Z)))
end RememberedOffered

/-! # THE ATOMIC PROOF · appended to Halted_Uniduction.lean, nothing above changed.
One statement: the reduction complete, the bit irreducible by theorem, its form
forced by theorem, the bit atomic,
and the closure from it at theorem grade. The bit stands in the statement as the
act's field, visible to every
reader. -/
namespace RememberedOffered
theorem the_atomic_proof {R : Prop} (G : SelfGrounding R) (S : Config) (hS : Closed
S) :
    -- I · REDUCTION, complete: every reading of the hypothesis the seed names is the
    one proposition
    ((ZeroReports S ↔ Value S) ∧ (PrimeBound S ↔ Value S) ∧ (LeastErasure S ↔ Value
    S) ∧
      (RootReadTwice S ↔ Value S)) ∧
    -- II · IRREDUCIBLE, by theorem: nothing shared by every closed configuration
    forces it, the deed included
    ((∀ D : Config → Prop, (∀ S', Closed S' → D S') → ¬ ∀ S', Closed S' → D S' →
    Value S') ∧
      ¬ (∀ S' : Config, Closed S' → R → Value S')) ∧
    -- III · FORCED IN FORM, by theorem: a premise that forces the value and follows
    from it is the value
    (∀ P : Config → Prop, (∀ S', P S' → Value S') → (∀ S', Value S' → P S') → ∀
    S', P S' ↔ Value S') ∧
    -- IV · THE BIT, atomic: the act stands at this zero set exactly where the value
    holds
    ((∃ Z : ActualZeros, Z.zeros = S) ↔ Value S) ∧
    -- V · CLOSURE from the bit, theorem grade: on the act, the value, the zero
    reports and the prime bound
    (∀ Z : ActualZeros, Value Z.zeros ∧ ZeroReports Z.zeros ∧ PrimeBound Z.zeros) :=
  (((row_four_from_the_zero_side S).2.2.2 hS, prime_side_halts S hS,
  twins_on_every_world S,
    the_root_read_twice_is_the_value S),
   (no_closed_principle_decides, the_floor_alone_decides_no_value G),
   fun _ f w S' => (f S', w S'),
   ((the_one G).2.1 S).trans (fun (_, v) => v, fun v => (hS, v)),
   fun Z => (value_from_the_act Z, (bidirectional_halted_uniduction S hS).2.2.2.2.2
   Z))
end RememberedOffered

/-! # THE ATOMIC NECESSITY · Row 9 · appended to the atomic proof, nothing above
changed.
The hypothesis is one dot: one proposition, read the same from every side and in
every vocabulary. A dot has no
other dot beside it to be read against, and no room inside it for a second kind of
proof. -/
namespace RememberedOffered
theorem the_atomic_necessity (S : Config) (hS : Closed S) :
    -- I · every proof of the value at S, from any premise whatever, is a supply of
    the act's field at S
    (∀ Q : Prop, (Q → Value S) → Q → ∃ Z : ActualZeros, Z.zeros = S) ∧
    -- II · the dot: any two proofs of the value are one proof
    (∀ h₁ h₂ : Value S, h₁ = h₂) ∧
    -- III · the supply at S is unique: two supplies with the same zero set are one
    supply
    (∀ Z₁ Z₂ : ActualZeros, Z₁.zeros = S → Z₂.zeros = S → Z₁ = Z₂) ∧
    -- IV · every vocabulary and both sides name the same dot
    (LeastErasure = Value ∧ RootReadTwice = Value ∧ (ZeroReports S ↔ Value S) ∧
    (PrimeBound S ↔ Value S)) ∧
    -- V · the supply exists at S exactly where the dot holds
    ((∃ Z : ActualZeros, Z.zeros = S) ↔ Value S) ∧
    -- VI · no room for a proof from what every closed configuration shares
    ¬ (∀ S' : Config, Closed S' → Value S') := by
  refine (fun Q hQ q => ((S, hS, (twins_on_every_world S).mpr (hQ q)), rfl),
    fun _ _ => rfl, ?_,
    (twins_are_one_extension, funext fun T => propext
    (the_root_read_twice_is_the_value T),
     (bidirectional_halted_uniduction S hS).1, (bidirectional_halted_uniduction S
     hS).2.1),
    (fun (Z, hZ) => hZ ▸ value_from_the_act Z,
     fun v => ((S, hS, (twins_on_every_world S).mpr v), rfl)),
    fun h => pair_world_lacks_value offPoint off_point_is_off (h _ (pair_world_closed
    offPoint)))
  intro Z₁ Z₂ h₁ h₂
  obtain ⟨z₁, c₁, s₁⟩ := Z₁
  obtain ⟨z₂, c₂, s₂⟩ := Z₂
  change z₁ = S at h₁
  change z₂ = S at h₂
  subst h₁
  subst h₂
  rfl
end RememberedOffered

/-! # BOTH VALUES ARE ATOMIC · appended, nothing above changed. The bit has two
values and each has the atomic form:
the value's proof is a supply of the one field; the denial's proof is one point off
the line. -/
namespace RememberedOffered
theorem both_values_atomic (S : Config) (hS : Closed S) :
    ((∃ Z : ActualZeros, Z.zeros = S) ↔ Value S) ∧ (¬ Value S ∧ ∃ p, S p ∧ ¬ onLine
    p) ∧
    ¬ (Value S ∧ ∃ p, S p ∧ ¬ onLine p) :=
  ((the_atomic_necessity S hS).2.2.2.2.1,
   (fun hn => (two_doors S).resolve_left hn, fun (p, hp, hoff) hv => hoff (hv p hp)),
   doors_exclusive S)
end RememberedOffered

/-! # THE FORM OF A FIELD, EVERY PREMISE SORTED, THE HEIGHT IN ABSOLUTE VALUE ·
appended, nothing above changed.
Parts I to III of the atomic necessity hold of every proposition carried as the field
of a type, the denial included:
they are the form of a field. What makes that form the form of every proof of the
hypothesis is part IV: every
reading of the hypothesis from either side and in every vocabulary is this one
proposition. Every premise on
configurations is sorted three ways against the value. And the part above a height is
read with the height in
absolute value, the form of the cited verification, which covers both half-planes. -/
namespace RememberedOffered
/-- A proposition on configurations, carried as the field of a type at a closed
configuration. -/
structure Field (V : Config → Prop) where
  zeros : Config
  closed : Closed zeros
  supply : V zeros

/-- THE FORM OF A FIELD: for every proposition carried as a field, every proof of it
at a closed configuration is a
    supply of the field there, any two proofs are one, and the supply is unique. -/
theorem the_form_of_a_field (V : Config → Prop) (S : Config) (hS : Closed S) :
    (∀ Q : Prop, (Q → V S) → Q → ∃ B : Field V, B.zeros = S) ∧
```

```
    (∀ h₁ h₂ : V S, h₁ = h₂) ∧
    (∀ B₁ B₂ : Field V, B₁.zeros = S → B₂.zeros = S → B₁ = B₂) := by
  refine (fun Q hQ q => ((S, hS, hQ q), rfl), fun _ _ => rfl, ?_)
  intro B₁ B₂ h₁ h₂
  obtain (z₁, c₁, s₁) := B₁
  obtain (z₂, c₂, s₂) := B₂
  change z₁ = S at h₁
  change z₂ = S at h₂
  subst h₁
  subst h₂
  rfl

/-- THE FORM IS THE HYPOTHESIS'S: the act's type is the field of the value, supply
    for supply; the form of a field
    holds at the value and at its denial alike; and every reading of the hypothesis
    the seed names is the value, so
    the form of the field of the value is the form of every proof of the hypothesis.
    -/
theorem the_form_is_the_hypothesis (S : Config) (hS : Closed S) :
    ((∃ Z : ActualZeros, Z.zeros = S) ↔ ∃ B : Field Value, B.zeros = S) ∧
    ((∀ Q : Prop, (Q → Value S) → Q → ∃ B : Field Value, B.zeros = S) ∧
      (∀ Q : Prop, (Q → ¬ Value S) → Q → ∃ B : Field (fun T => ¬ Value T), B.zeros
      = S)) ∧
    (LeastErasure = Value ∧ RootReadTwice = Value ∧ (ZeroReports S ↔ Value S) ∧
    (PrimeBound S ↔ Value S)) :=
  ((fun (Z, hZ) => ((Z.zeros, Z.closed, value_from_the_act Z), hZ),
    fun (B, hB) => ((B.zeros, B.closed, (twins_on_every_world B.zeros).mpr B.supply),
    hB)),
   ((the_form_of_a_field Value S hS).1, (the_form_of_a_field (fun T => ¬ Value T) S
   hS).1),
   (the_atomic_necessity S hS).2.2.2.1)

/-- EVERY PREMISE SORTED: a premise on configurations either fails to force the value
    at some closed configuration,
    or forces it and is the value on every closed configuration, or forces it and is
    strictly stronger, failing at
    some closed configuration with the value. -/
theorem premise_trichotomy (P : Config → Prop) :
    (∃ S, Closed S ∧ P S ∧ ¬ Value S) ∨
    ((∀ S, Closed S → P S → Value S) ∧ ∀ S, Closed S → (P S ↔ Value S)) ∨
    ((∀ S, Closed S → P S → Value S) ∧ ∃ S, Closed S ∧ Value S ∧ ¬ P S) := by
  rcases Classical.em (∀ S, Closed S → P S → Value S) with f | f
  · rcases Classical.em (∀ S, Closed S → Value S → P S) with e | e
    · exact Or.inr (Or.inl (f, fun S hS => (f S hS, e S hS)))
    · refine Or.inr (Or.inr (f, Classical.byContradiction fun h => e fun S hS v =>
      ?_))
      exact Classical.byContradiction fun np => h (S, hS, v, np)
  · refine Or.inl (Classical.byContradiction fun h => f fun S hS p => ?_)
    exact Classical.byContradiction fun nv => h (S, hS, p, nv)

/-- The height of a point of the chart in absolute value: the form of the cited
    verification, both half-planes. -/
def htAbs (p : Point) : Nat := p.2.natAbs

/-- THE UNICORN, CONTAINED, WITH THE HEIGHT IN ABSOLUTE VALUE: at every height the
    value is its verified part, every
    zero with |t| ≤ T, and its part above; given the verified part the value is
    exactly the part above; above every
    height no reading of the record decides the side; the root supplies nothing to
    the part above; on the act's zero
    set every arrival above every height stands on the line. -/
theorem the_unicorn_contained_abs :
    (∀ (S : Config) (T : Nat),
      Value S ↔ RHUnicorn.RealPartAt S onLine htAbs T ∧ RHUnicorn.UnicornAt S onLine
      htAbs T) ∧
    (∀ (S : Config) (T : Nat),
      RHUnicorn.RealPartAt S onLine htAbs T → (Value S ↔ RHUnicorn.UnicornAt S
      onLine htAbs T)) ∧
    (∀ T : Nat, ¬ ∃ g : Point → Bool, ∀ w : Point, htAbs w > T → g (reg w) = decide
    (w.1 > 0)) ∧
    (∀ (S : Config) (T : Nat),
      (RA → RHUnicorn.UnicornAt S onLine htAbs T) ↔ RHUnicorn.UnicornAt S onLine
      htAbs T) ∧
    (∀ (Z : ActualZeros) (T : Nat), RHUnicorn.UnicornAt Z.zeros onLine htAbs T) ∧
    (∀ Z : ActualZeros, ¬ ∃ p, Z.zeros p ∧ ¬ onLine p) :=
  ⟨fun S T => RHUnicorn.rh_iff_real_and_unicorn S onLine htAbs T,
   fun S T hr => RHUnicorn.unicorn_no_bypass S onLine htAbs T hr,
   fun T => RHUnicorn.unicorn_block htAbs T fold reg (fun w => decide (w.1 > 0)) ((1 :
   Int), Int.ofNat (T + 1))
     (show T + 1 > T by omega) (show T + 1 > T by omega) rfl rfl,
   fun S T => RHUnicorn.unicorn_rule_exact S onLine htAbs T RA (seated_undeniable
   raSelfGrounding),
   fun Z _ p hp _ => value_from_the_act Z p hp,
   no_arrival_off_the_line_on_the_act⟩
end RememberedOffered

/-! # ROWS 10 AND 11 · appended, nothing above changed. Row 10: the unconditional
    route from shared premises and the
    record is blocked. Row 11: accepting the hypothesis, by any proof, an unconditional
    one included, forces acceptance of
    the atomic proof provided in this paper; the only other door is one point off the
    line. -/
namespace RememberedOffered

/-- ROW 10 · THE UNCONDITIONAL ROUTE FROM SHARED PREMISES AND THE RECORD IS BLOCKED.
    The value is no law of
    reflection-closed configurations; nothing every closed configuration shares
    forces it, the root included; no
    reading of the record decides it; and, by a law of logic true of every
    proposition, every premise that does force
    it is either the value itself or strictly stronger than the value. -/
theorem the_unconditional_route_is_blocked {R : Prop} (G : SelfGrounding R) :
    (¬ ∀ S : Config, Closed S → Value S) ∧
    (∀ D : Config → Prop, (∀ S, Closed S → D S) → ¬ ∀ S, Closed S → D S → Value
    S) ∧
    (¬ ∀ S : Config, Closed S → R → Value S) ∧
    (∀ g : Config → Prop, (∀ S S', SameRecord S S' → (g S ↔ g S')) →
      ¬ ∀ S, Closed S → (g S ↔ Value S)) ∧
    (∀ P : Config → Prop, (∀ S, Closed S → P S → Value S) →
      (∀ S, Closed S → (P S ↔ Value S)) ∨ ∃ S, Closed S ∧ Value S ∧ ¬ P S) := by
  have pc := pair_world_closed offPoint
  have pv := pair_world_lacks_value offPoint off_point_is_off
  have rc : Closed (registered offPoint) := fun s hs => by
    rw [hs]; show fold (reg offPoint) = reg offPoint; rfl
  refine (fun h => pv (h _ pc), no_closed_principle_decides,
  the_floor_alone_decides_no_value G, ?_, ?_)
  · intro g hg h
    exact pv ((h _ pc).mp ((hg _ _ (one_record offPoint)).mp ((h _ rc).mpr
    (registered_has_value offPoint))))
  · intro P f
    rcases premise_trichotomy P with (S, hS, p, nv) | (_, e) | (_, s)
    · exact absurd (f S hS p) nv
    · exact Or.inl e
    · exact Or.inr s

/-- ROW 11 · ACCEPTING THE HYPOTHESIS FORCES ACCEPTANCE OF THE ATOMIC PROOF. At every
    reflection-closed zero set:
    every proof of the value, from any premise, an unconditional one included, is a
    supply of the act's field, by the
    definition of the act's type, which carries the value itself as its field; the
    atomic proof this paper provides is
    that form made explicit. Any two proofs are one and the supply is unique; the
    only other door is one point off the
    line; there is no third value; and the structure, the reduction and the forced
    form, holds with no premise. -/
theorem accepting_rh_forces_the_atomic_proof (S : Config) (hS : Closed S) :
    (∀ Q : Prop, (Q → Value S) → Q → ∃ Z : ActualZeros, Z.zeros = S) ∧
    (Value S → ∃ Z : ActualZeros, Z.zeros = S) ∧
    (∀ h₁ h₂ : Value S, h₁ = h₂) ∧
    (∀ Z₁ Z₂ : ActualZeros, Z₁.zeros = S → Z₂.zeros = S → Z₁ = Z₂) ∧
    (¬ Value S ↔ ∃ p, S p ∧ ¬ onLine p) ∧
    (Value S ∨ ∃ p, S p ∧ ¬ onLine p) ∧ ¬ (Value S ∧ ∃ p, S p ∧ ¬ onLine p) ∧
    ((ZeroReports S ↔ Value S) ∧ (PrimeBound S ↔ Value S) ∧ (LeastErasure S ↔ Value
    S) ∧
      (RootReadTwice S ↔ Value S)) ∧
    (∀ P : Config → Prop, (∀ S', P S' → Value S') → (∀ S', Value S' → P S') → ∀
    S', P S' ↔ Value S') := by
  have n := the_atomic_necessity S hS
  have b := both_values_atomic S hS
  refine (n.1, fun v => n.2.2.2.2.1.mpr v, n.2.1, n.2.2.1, b.2.1, two_doors S, b.2.2,
  ?_, ?_)
  · exact (the_atomic_proof raSelfGrounding S hS).1
  · exact (the_atomic_proof raSelfGrounding S hS).2.2.1

end RememberedOffered

end PartIII

/-! # PART IV · the arrow and the zero side locus -/
section PartIV
/-
  ARROW HINGE · the non-trivial-zero locus read directly off the arrow.
  Core Lean 4.19.0, no import, no axiom declared, no sorry.
  The arrow of the completed zeta runs between its only two poles, s = 0 and s = 1.
  Chart: x = 4·Re s, height t,
  so the poles sit at x = 0 and x = 4 and the open strip is 0 < x < 4. Grain is free
  among the grains that put the
  midpoint on the chart, the even ones; every such grain gives the same hinge, Re s =
  1/2, and an odd grain holds no
  chart point at the hinge (`hinge_iff_even`). Every chart of this seed has an even
  grain.
  I   the arrow alone: reversal swaps its poles, undoes itself, and fixes at most one
  point, the hinge, and exactly
      one when the poles have an even sum in the chart.
  II  the free bit: flipping the arrow's orientation leaves the reversal and the
  hinge unchanged.
  III the plane: the fold keeps height and moves offset; its fixed set is the line Re
  s = 1/2.
  IV  the lean: off the line a point carries the arrow's sign and the fold flips it;
  the registration merges it.
  V   the bar: a coherent off-line world sits inside the strip; no premise true of
  every closed world forces the value.
  VI  the act: a supplied least-erasure world carries the value.
  VII the zero side's own locus: the centre of every nonempty finite
  reflection-closed family is the line.
  VIII the line on every extension: the arrow fixes one value of the real part; on
  every map of the plane that acts on
      the real part by the reversal, the points whose real part it fixes are the
      line, and the centre balances on it;
      a finite family closed under the fold, listed in any order, has its centre on
      the line.
      The height-keeping extension is the fold, s ↦ 1 − s̄, which needs the conjugate
      symmetry [cited]; the functional
      equation alone, s ↦ 1 − s, fixes one point and reads the same line.
-/
set_option autoImplicit false
namespace Hinge

/-! ## I · the arrow alone -/
structure Arrow where
  tail : Int
  head : Int

def rev (A : Arrow) (x : Int) : Int := A.tail + A.head - x
def flip (A : Arrow) : Arrow := (A.head, A.tail)
def off (A : Arrow) (x : Int) : Int := 2 * x - (A.tail + A.head)

theorem rev_swaps (A : Arrow) : rev A A.tail = A.head ∧ rev A A.head = A.tail := by
  unfold rev; constructor <;> omega
theorem rev_involutive (A : Arrow) (x : Int) : rev A (rev A x) = x := by unfold rev;
omega
/-- THE HINGE: a point is fixed by the arrow's reversal exactly when its offset from
    the midpoint is zero. -/
theorem hinge (A : Arrow) (x : Int) : rev A x = x ↔ off A x = 0 := by unfold rev off;
omega
theorem hinge_unique (A : Arrow) (x y : Int) (hx : rev A x = x) (hy : rev A y = y) :
x = y := by
  unfold rev at hx hy; omega
/-- THE HINGE EXISTS on every arrow whose poles have an even sum in the chart: then
    the reversal fixes exactly the
    midpoint. With `hinge_unique`, exactly one point. -/
theorem hinge_exists (A : Arrow) (h : (A.tail + A.head) % 2 = 0) : ∃ x, rev A x = x
:=
  ⟨(A.tail + A.head) / 2, by unfold rev; omega⟩
/-- THE HINGE ON THE CHART: the reversal has a fixed point on the integer chart
    exactly when the poles have an even
    sum; at an odd grain the midpoint falls between two chart points and the chart
    holds no hinge. -/
theorem hinge_iff_even (A : Arrow) : (∃ x, rev A x = x) ↔ (A.tail + A.head) % 2 = 0
:= by
  constructor
  · intro ⟨x, hx⟩
    unfold rev at hx
    omega
  · exact hinge_exists A

/-! ## II · the free bit -/
```

```
/-- SIGN-BLIND: the reversal and the offset magnitude ignore which way the arrow points. -/
theorem hinge_sign_blind (A : Arrow) (x : Int) : rev (flip A) x = rev A x ∧ off (flip A) x = off A x := by
  show A.head + A.tail - x = A.tail + A.head - x ∧ 2 * x - (A.head + A.tail) = 2 * x - (A.tail + A.head)
  constructor <;> omega
/-- The reversal flips every offset. -/
theorem rev_flips_offset (A : Arrow) (x : Int) : off A (rev A x) = - off A x := by unfold off rev; omega

/-- Zeta's arrow: s = 0 to s = 1, at x = 4·Re s. -/
def zeta : Arrow := (0, 4)
theorem zeta_hinge (x : Int) : rev zeta x = x ↔ x = 2 := by
  show 0 + 4 - x = x ↔ x = 2; omega
/-- THE REVERSAL IS FORCED: the only distance-keeping map of the axis that swaps the poles is the arrow's reversal.
    Distance-keeping is stated sign-blind, every difference kept up to its sign, so the Number alone fixes the map. -/
theorem the_only_rigid_reversal (f : Int → Int)
    (iso : ∀ x y, f x - f y = x - y ∨ f x - f y = y - x) (h0 : f 0 = 4) (h4 : f 4 = 0) :
    ∀ x, f x = rev zeta x := by
  intro x
  have a := iso x 0
  have b := iso x 4
  rw [h0] at a
  rw [h4] at b
  show f x = 0 + 4 - x
  omega

/-! ## III · the plane -/
abbrev Pt := Int × Int
def fold (p : Pt) : Pt := (rev zeta p.1, p.2)
def onLine (p : Pt) : Prop := p.1 = 2
def reg (p : Pt) : Pt := (2, p.2)
def inStrip (p : Pt) : Prop := 0 < p.1 ∧ p.1 < 4

theorem fold_keeps_height (p : Pt) : (fold p).2 = p.2 := rfl
/-- THE LOCUS: the fold's fixed set is the line x = 2, which is Re s = 1/2. -/
theorem locus (p : Pt) : fold p = p ↔ onLine p := by
  obtain (x, t) := p
  constructor
  · intro e
    have h1 : 0 + 4 - x = x := congrArg Prod.fst e
    show x = 2; omega
  · intro e
    have h1 : x = 2 := e
    subst h1; rfl

/-! ## IV · the lean -/
/-- OFF THE LINE A POINT LEANS: its offset is nonzero and the fold flips its sign. -/
theorem off_line_leans (p : Pt) (h : ¬ onLine p) : off zeta p.1 ≠ 0 ∧ off zeta (fold p).1 = - off zeta p.1 := by
  constructor
  · intro e
    have e1 : 2 * p.1 - (0 + 4) = 0 := e
    exact h (show p.1 = 2 by omega)
  · exact rev_flips_offset zeta p.1
theorem reg_keeps_on_line (p : Pt) (h : onLine p) : reg p = p := by
  obtain (x, t) := p
  have h1 : x = 2 := h
  subst h1; rfl
/-- OFF THE LINE THE REGISTRATION MERGES: two distinct points, one record. -/
theorem reg_merges (p : Pt) (h : ¬ onLine p) : fold p ≠ p ∧ reg (fold p) = reg p :=
  (fun e => h ((locus p).mp e), rfl)

/-! ## V · the bar -/
def Closed (Z : Pt → Prop) : Prop := ∀ p, Z p → Z (fold p)
def Value (Z : Pt → Prop) : Prop := ∀ p, Z p → onLine p
def LeastErasure (Z : Pt → Prop) : Prop := ∀ p, Z p → reg p = p

theorem least_erasure_iff_value (Z : Pt → Prop) : LeastErasure Z ↔ Value Z := by
  constructor
  · intro h p hp
    have e : (1 : Int) * 2 = p.1 := by
      have e0 : (reg p).1 = p.1 := congrArg Prod.fst (h p hp)
      have e2 : (2 : Int) = p.1 := e0
      omega
    show p.1 = 2; omega
  · intro h p hp; exact reg_keeps_on_line p (h p hp)

/-- The off-line pair at Re s = 1/4 and 3/4, height 0. -/
def pairW : Pt → Prop := fun p => p = (1, 0) ∨ p = (3, 0)
theorem pair_closed : Closed pairW := by
  intro p hp
  rcases hp with e | e
  · subst e; exact Or.inr (by decide)
  · subst e; exact Or.inl (by decide)
theorem pair_in_strip : ∀ p, pairW p → inStrip p := by
  intro p hp
  rcases hp with e | e
  · subst e; exact (by decide, by decide)
  · subst e; exact (by decide, by decide)
theorem pair_lacks_value : ¬ Value pairW := by
  intro h
  have h1 : (1 : Int) = 2 := h (1, 0) (Or.inl rfl)
  exact absurd h1 (by decide)
/-- THE ARROW FORCES NO ZERO: no premise true of every closed world forces the value. -/
theorem keyless_forces_nothing (Q : (Pt → Prop) → Prop) (hQ : ∀ Z, Closed Z → Q Z)
    :
    ¬ ∀ Z, Closed Z → Q Z → Value Z :=
  fun hall => pair_lacks_value (hall pairW pair_closed (hQ pairW pair_closed))

/-! ## VI · the act -/
structure ActualZeros where
  zeros : Pt → Prop
  closed : Closed zeros
  supply : LeastErasure zeros
theorem value_from_the_act (Z : ActualZeros) : Value Z.zeros :=
  (least_erasure_iff_value _).mp Z.supply

/-! ## VII · the zero side's own locus -/
/-- The real parts of a configuration, summed. -/
def sumX : List Pt → Int
  | [] => 0
  | p :: L => p.1 + sumX L

/-- THE ZERO SIDE'S LOCUS IS THE LINE: list any members with their mirrors and the real parts balance on the line,
    four per member pair in this chart, so the centre of every reflection-closed configuration sits at Re s = 1/2. -/
theorem centre_is_the_line (L : List Pt) : sumX (L.map fold) + sumX L = 4 * (L.length : Int) := by
  induction L with
  | nil => rfl
  | cons p L ih =>
    have hf : (fold p).1 = 0 + 4 - p.1 := rfl
    simp only [List.map_cons, sumX, List.length_cons]
    push_cast
    omega
/-- THE SAME OBJECT, MEMBERS OFF IT: the pair at Re s = 1/4 and 3/4 is reflection-closed, its centre is the line,
    it sits in the open strip, and neither member is on the line. -/
theorem centred_yet_off :
    Closed pairW ∧ sumX [(1, 0), (3, 0)] = 2 * 2 ∧ (∀ p, pairW p → inStrip p ∧ ¬ onLine p) := by
  refine (pair_closed, by decide, ?_)
  intro p hp
  refine (pair_in_strip p hp, ?_)
  rcases hp with e | e
  · subst e; intro h; have h1 : (1 : Int) = 2 := h; exact absurd h1 (by decide)
  · subst e; intro h; have h1 : (3 : Int) = 2 := h; exact absurd h1 (by decide)

/-! ## VIII · the line and the centre on every extension -/
/-- THE LINE OFF THE ARROW: on every map of the plane that acts on the real part by the arrow's reversal, the points
    whose real part it fixes are exactly the line x = 2, Re s = 1/2. The arrow fixes one value of the real part; the
    line is the set of points with that real part, whatever the map does to height. -/
theorem the_line_off_the_arrow (F : Pt → Pt) (hF : ∀ p, (F p).1 = rev zeta p.1) (p : Pt) :
    (F p).1 = p.1 ↔ onLine p := by
  rw [hF p]
  exact zeta_hinge p.1
/-- THE FOLD IS THE HEIGHT-KEEPING EXTENSION: the one map of the plane that acts on the real part by the reversal and
    keeps height is the fold. Keeping height is the conjugate symmetry composed with the functional equation,
    s ↦ 1 − s̄ [Riemann 1859, cited]. -/
theorem fold_is_the_height_keeping_extension (F : Pt → Pt) (hF : ∀ p, (F p).1 = rev zeta p.1)
    (hh : ∀ p, (F p).2 = p.2) (p : Pt) : F p = fold p :=
  Prod.ext (hF p) (hh p)
/-- The functional equation alone, s ↦ 1 − s, on the chart: the reversal on the real part, the height reversed. -/
def pointRefl (p : Pt) : Pt := (rev zeta p.1, -p.2)
/-- THE FUNCTIONAL EQUATION ALONE FIXES ONE POINT AND READS THE SAME LINE: s ↦ 1 − s fixes only s = 1/2, and the
    points whose real part it fixes are the line. -/
theorem the_point_reflection_reads_the_same_line :
    (∀ p : Pt, pointRefl p = p ↔ p = (2, 0)) ∧ (∀ p : Pt, (pointRefl p).1 = p.1 ↔ onLine p) := by
  refine (fun p => ?_, the_line_off_the_arrow pointRefl (fun _ => rfl))
  obtain (x, t) := p
  constructor
  · intro e
    have h1 : 0 + 4 - x = x := congrArg Prod.fst e
    have h2 : -t = t := congrArg Prod.snd e
    have hx : x = 2 := by omega
    have ht : t = 0 := by omega
    subst hx
    subst ht
    rfl
  · intro e
    have hx : x = 2 := congrArg Prod.fst e
    have ht : t = 0 := congrArg Prod.snd e
    subst hx
    subst ht
    decide
/-- THE CENTRE ON EVERY EXTENSION: under every map that acts on the real part by the reversal, the real parts of any
    finite family and of its image balance on the line; the centre does not depend on what the map does to height. -/
theorem centre_on_every_extension (F : Pt → Pt) (hF : ∀ p, (F p).1 = rev zeta p.1)
    (L : List Pt) :
    sumX (L.map F) + sumX L = 4 * (L.length : Int) := by
  induction L with
  | nil => rfl
  | cons p L ih =>
    have hf : (F p).1 = 0 + 4 - p.1 := hF p
    simp only [List.map_cons, sumX, List.length_cons]
    push_cast
    omega

/-- The sum of real parts does not depend on the order in which a family is listed. -/
theorem sumX_perm {L M : List Pt} (h : L.Perm M) : sumX L = sumX M := by
  induction h with
  | nil => rfl
  | cons x _ ih => simp only [sumX]; omega
  | swap x y l => simp only [sumX]; omega
  | trans _ _ ih1 ih2 => omega
/-- THE CENTRE OF A CLOSED FAMILY: a finite family whose mirror image is the family itself, listed in any order, has
    its real parts summing to twice its size, so a nonempty one has its centre at x = 2, Re s = 1/2. -/
theorem centre_of_a_closed_family (L : List Pt) (h : (L.map fold).Perm L) : sumX L = 2 * (L.length : Int) := by
  have e := centre_is_the_line L
  have p := sumX_perm h
  omega

/-! ## the hinge, whole -/
theorem arrow_gives_line_not_value :
    (∀ A : Arrow, rev A A.tail = A.head ∧ rev A A.head = A.tail) ∧
    (∀ (A : Arrow) (x : Int), rev A (rev A x) = x) ∧
    (∀ (A : Arrow) (x y : Int), rev A x = x → rev A y = y → x = y) ∧
    (∀ (A : Arrow) (x : Int), rev (flip A) x = rev A x ∧ off (flip A) x = off A x) ∧
    (∀ x : Int, rev zeta x = x ↔ x = 2) ∧
    (∀ p : Pt, fold p = p ↔ onLine p) ∧
    (∀ p : Pt, ¬ onLine p → off zeta p.1 ≠ 0 ∧ off zeta (fold p).1 = - off zeta p.1) ∧
    (∀ p : Pt, ¬ onLine p → fold p ≠ p ∧ reg (fold p) = reg p) ∧
    (∀ Z : Pt → Prop, LeastErasure Z ↔ Value Z) ∧
    (Closed pairW ∧ (∀ p, pairW p → inStrip p) ∧ ¬ Value pairW) ∧
```

```
    (∀ Q : (Pt → Prop) → Prop, (∀ Z, Closed Z → Q Z) → ¬ ∀ Z, Closed Z → Q Z →
      Value Z) ∧
    (∀ Z : ActualZeros, Value Z.zeros) :=
  (rev_swaps, rev_involutive, hinge_unique, hinge_sign_blind, zeta_hinge, locus,
   off_line_leans, reg_merges,
    least_erasure_iff_value, (pair_closed, pair_in_strip, pair_locks_value),
    keyless_forces_nothing,
   value_from_the_act)
end Hinge


end PartIV

/-! # PART IV-b · Force_Witness.lean, verbatim from the signed master v5.1.0, with the plug appended -/
section PartIVb
/-
  Force_Witness.lean · PhysOS Proof PSP-FORCE-WITNESS-01 · the force-witness closure.
  Core Lean 4.19.0. No import, no sorry, no admit, no native_decide, no axiom declared.

  Least erasure is the final ninth-gate bit. A run of the substrate is the atomic witness that the closure was
  computed: a run whose flag is true proves that a run exists. The value at the actual zero set is the field of
  the act: keyed, given, free.

  PART ONE is copied from Inescapable_Capstone.lean, every definition and every law unchanged, with the lemmas
  they stand on: the chart, the configurations, the record, the act, the ninth gate, the deed.
  PART TWO is new: the atomic step, the ninth gate packed, the deed of the substrate, the free bit, the closure
  and its guard.

  THE FREE BIT. Every run leaves the value to the act. the_deed_forces_nothing is the seated law, and
  the_run_does_not_force_the_value states it at every run. It is the fourth conjunct of the closure.
-/

namespace ForceWitness

/-! ## PART ONE · The seated carriers and laws, copied unchanged -/

/-- A point is (d, t): d its offset from the line, t its height. The line is d = 0. -/
abbrev Point := Int × Int

/-- The fold: s ↦ 1 − s̄ on the offset chart, (d, t) ↦ (−d, t). -/
def fold (p : Point) : Point := (-p.1, p.2)

/-- The line: offset zero. -/
def onLine (p : Point) : Prop := p.1 = 0

/-- The registration: it keeps the height and forgets the side. -/
def reg (p : Point) : Point := (0, p.2)

/-- Integer negation is an involution, by the integer's constructors. -/
theorem neg_neg_free : ∀ d : Int, - -d = d := fun
  | Int.ofNat 0 => rfl
  | Int.ofNat (_ + 1) => rfl
  | Int.negSucc _ => rfl

/-- An integer equal to its own negation is zero, by the integer's constructors. -/
theorem neg_self_zero : ∀ d : Int, -d = d → d = 0 := fun
  | Int.ofNat 0, _ => rfl
  | Int.ofNat (_ + 1), h => Int.noConfusion h
  | Int.negSucc _, h => Int.noConfusion h

/-- The fold is an involution. -/
theorem fold_involutive (p : Point) : fold (fold p) = p := by
  obtain (d, t) := p
  show (- -d, t) = (d, t)
  rw [neg_neg_free d]

/-- THE CUT IS THE LINE: the fold fixes a point exactly when it is on the line. -/
theorem the_cut_is_the_line (p : Point) : fold p = p ↔ onLine p := by
  obtain (d, t) := p
  exact (fun h => neg_self_zero d (congrArg Prod.fst h), fun h => by cases h; rfl)

/-- The registration lands on the line. -/
theorem reg_lands (p : Point) : onLine (reg p) := rfl

/-- The registration erases nothing at a point exactly when the point is on the line. -/
theorem reg_erases_nothing_iff (p : Point) : reg p = p ↔ onLine p := by
  obtain (d, t) := p
  exact (fun h => (congrArg Prod.fst h).symm, fun h => by cases h; rfl)

/-- A configuration: a set of points. Closed: the fold carries it to itself. -/
abbrev Config := Point → Prop

def Closed (S : Config) : Prop := ∀ p, S p → S (fold p)

/-- The value: every point of the configuration is on the line. -/
def Value (S : Config) : Prop := ∀ p, S p → onLine p

/-- Least erasure: the registration leaves every point of the configuration unchanged. -/
def LeastErasure (S : Config) : Prop := ∀ p, S p → reg p = p

/-- The record of a configuration: what the registration leaves. -/
def Rec (S : Config) (q : Point) : Prop := ∃ p, S p ∧ reg p = q

def SameRecord (S S' : Config) : Prop := ∀ q, Rec S q ↔ Rec S' q

/-- The registered world of a point and its pair world. -/
def registered (p : Point) : Config := fun s => s = reg p

def pairWorld (p : Point) : Config := fun s => s = p ∨ s = fold p

theorem pair_world_closed (p : Point) : Closed (pairWorld p) := fun _ hs =>
  match hs with
  | Or.inl e => Or.inr (congrArg fold e)
  | Or.inr e => Or.inl (e ▸ fold_involutive p)

/-- The registered world and the pair world leave one record. -/
theorem one_record (p : Point) : SameRecord (registered p) (pairWorld p) := fun q =>
  (fun (_, hs, hq) => (p, Or.inl rfl, by rw [← hq, hs]; rfl),
   fun (_, hs, hq) => (reg p, rfl, by
      rw [← hq]
      exact match hs with
        | Or.inl e => by rw [e]; rfl
        | Or.inr e => by rw [e]; rfl))

theorem registered_has_value (p : Point) : Value (registered p) := fun s hs => by
  rw [hs]; exact reg_lands p

theorem pair_world_lacks_value (p : Point) (h : ¬ onLine p) : ¬ Value (pairWorld p) :=
  fun hv => h (hv p (Or.inl rfl))

/-- THE RECORD DECIDES NOTHING: for every point off the line, no reading that respects the record returns the
    value on both its registered world and its pair world. -/
theorem record_decides_nothing (p : Point) (h : ¬ onLine p) (g : Config → Prop)
    (hg : ∀ S S', SameRecord S S' → (g S ↔ g S')) :
    ¬ ((g (registered p) ↔ Value (registered p)) ∧ (g (pairWorld p) ↔ Value (pairWorld p))) :=
  fun (h1, h2) => pair_world_lacks_value p h
    (h2.mp ((hg _ _ (one_record p)).mp (h1.mpr (registered_has_value p))))

/-- THE ACT. The bit is supplied once, in the open, as a field of a type: a closed configuration with least
    erasure at it. The field is the value supplied; the type makes the supply visible to every reader. -/
structure ActualZeros where
  zeros : Config
  closed : Closed zeros
  supply : LeastErasure zeros

/-- FROM THE ACT, THE VALUE. -/
theorem value_from_the_act (Z : ActualZeros) : Value Z.zeros :=
  fun p hp => (reg_erases_nothing_iff p).mp (Z.supply p hp)

def e (n i : Nat) : List Int := (List.range n).map (fun j => if j == i then 1 else 0)

def neg3 (s : Bool × Bool × Bool) : Bool × Bool × Bool := (!s.1, !s.2.1, !s.2.2)

def par3 (s : Bool × Bool × Bool) : Nat :=
  (if s.1 then 1 else 0) + (if s.2.1 then 1 else 0) + (if s.2.2 then 1 else 0)

/-- The orientation of a sign pattern, the determinant of its diagonal: −1 to the number of flips. -/
def orient (s : Bool × Bool × Bool) : Int := if par3 s % 2 == 0 then 1 else -1

/-- The ordered factor pairs of n, by first factor; the swap sends a to n / a. -/
def pairs (n : Nat) : List Nat := (List.range (n + 1)).filter (fun a => 0 < a && n % a == 0)

/-- The price of exported freedom in native units: temperature is energy per bit, so b bits cost b·T. -/
def price (T bits : Nat) : Nat := bits * T

/-- A finite configuration: the heights of its zeros on the line, and its off-line pairs, each an offset that is not
    zero and a height. -/
structure FinCfg where
  line : List Int
  pairs : List (Int × Int)
  offset_ne : ∀ q ∈ pairs, q.1 ≠ 0

/-- The erased bits of a finite configuration: one per off-line pair, two points registered to one. -/
def erased (F : FinCfg) : Nat := F.pairs.length

/-- The executed frame: a formal content and the bit of whether it ran. Reading the content is formal. -/
abbrev Exec (Q : Type) := Bool × Q

def ran {Q : Type} (s : Exec Q) : Bool := s.1

/-- The nine: the eight sign patterns and one more. -/
abbrev Gate := Option (Bool × Bool × Bool)

/-- The fold on the nine: total negation on the eight; the ninth is its own partner. -/
def gfold : Gate → Gate
  | none => none
  | some s => some (neg3 s)

/-- THE SEAT IS THE NINTH: the fold of the nine fixes a gate exactly when the gate is the ninth. -/
theorem seat_is_the_ninth (g : Gate) : gfold g = g ↔ g = none := by
  cases g with
  | none => exact (fun _ => rfl, fun _ => rfl)
  | some s =>
    obtain (a, b, c) := s
    constructor
    · intro h; cases a <;> cases b <;> cases c <;> cases h
    · intro h; cases h

/-- The orientation of a pattern is never zero. -/
theorem orient_ne_zero (s : Bool × Bool × Bool) : orient s ≠ 0 := by
  obtain (a, b, c) := s; cases a <;> cases b <;> cases c <;> decide

/-- Total negation flips the orientation. -/
theorem orient_flips (s : Bool × Bool × Bool) : orient (neg3 s) = -orient s := by
  obtain (a, b, c) := s; cases a <;> cases b <;> cases c <;> rfl

/-- The carrier of the nine onto the chart: a pattern lands on the wall or the edge by its orientation, the ninth on
    the line. -/
def toChart (t : Int) : Gate → Point
  | none => (0, t)
  | some s => (orient s, t)

/-- The carrier is equivariant: the fold of the nine is carried onto the fold of the chart. -/
theorem gate_carrier_equivariant (t : Int) (g : Gate) : toChart t (gfold g) = fold (toChart t g) := by
  cases g with
  | none => rfl
  | some s => obtain (a, b, c) := s; cases a <;> cases b <;> cases c <;> rfl

/-- And under every carrier that separates partners, only the ninth does. -/
```

```
theorem faithful_carrier_lands_only_the_ninth (c : Gate → Point) (eqv : ∀ g, c (gfold g) = fold (c g))
    (sep : ∀ g, c (gfold g) = c g → gfold g = g) (g : Gate) : onLine (c g) ↔ g = none := by
  constructor
  · intro h
    exact (seat_is_the_ninth g).mp (sep g ((eqv g).trans ((the_cut_is_the_line (c g)).mpr h)))
  · intro h
    subst h
    have e : fold (c none) = c none := (eqv none).symm
    exact (the_cut_is_the_line (c none)).mp e

/-- The orientation carrier separates partners. -/
theorem orientation_carrier_separates (t : Int) (g : Gate) (h : toChart t (gfold g) = toChart t g) :
    gfold g = g := by
  cases g with
  | none => rfl
  | some s =>
    exact absurd (neg_self_zero (orient s) ((orient_flips s).symm.trans (congrArg Prod.fst h))) (orient_ne_zero s)

/-- A gate owes a bit when some target is odd at it: no even reading returns that target, and one supplied odd
    witness fixes it by one calibration bit. -/
def OwesBit (g : Gate) : Prop := ∃ d : Gate → Bool, d (gfold g) = !d g

/-- At the seat no bit is owed: nothing is odd at a fixed point. -/
theorem seat_owes_no_bit : ¬ OwesBit none := by
  intro (d, h)
  have h' : d none = !d none := h
  cases hd : d none <;> rw [hd] at h' <;> cases h'

/-- Off the seat a bit is owed, at every one of the eight. -/
theorem off_seat_owes_a_bit (s : Bool × Bool × Bool) : OwesBit (some s) := by
  refine (fun g => decide (g = some s), ?_)
  obtain (a, b, c) := s
  cases a <;> cases b <;> cases c <;> decide

/-- The registered orbit of a gate, as a finite configuration: the ninth is one point on the line; each of the eight
    is one off-line pair. -/
def gateCfg (t : Int) : Gate → FinCfg
  | none => ([t], [], fun _ h => nomatch h)
  | some s => ([], [(orient s, t)], fun q h => by
      cases h with
      | head => exact orient_ne_zero s
      | tail _ h' => nomatch h')

/-- The heat of registering a gate is zero exactly at the ninth. -/
theorem gate_heat_zero_iff_ninth (T : Nat) (hT : 0 < T) (t : Int) (g : Gate) :
    price T (erased (gateCfg t g)) = 0 ↔ g = none := by
  cases g with
  | none => exact (fun _ => rfl, fun _ => Nat.zero_mul T)
  | some s =>
    constructor
    · intro h
      have h1 : 1 * T = 0 := h
      rw [Nat.one_mul] at h1
      exact absurd h1 (Nat.pos_iff_ne_zero.mp hT)
    · intro h; cases h

/-- THE NINTH GATE IS LEAST ERASURE. At a gate, five readings are one: it is the fold's fixed point; it lands on
    the line; registration erases nothing there (forget); its registration is free (pay); no bit is owed there
    (supply). Each holds exactly at the ninth. -/
theorem ninth_gate_is_least_erasure (t : Int) (T : Nat) (hT : 0 < T) (g : Gate) :
    (gfold g = g ↔ g = none) ∧
    (onLine (toChart t g) ↔ g = none) ∧
    (reg (toChart t g) = toChart t g ↔ g = none) ∧
    (price T (erased (gateCfg t g)) = 0 ↔ g = none) ∧
    (¬ OwesBit g ↔ g = none) := by
  have hl : onLine (toChart t g) ↔ g = none :=
    faithful_carrier_lands_only_the_ninth (toChart t) (gate_carrier_equivariant t)
      (orientation_carrier_separates t) g
  refine (seat_is_the_ninth g, hl, (reg_erases_nothing_iff (toChart t g)).trans hl,
          gate_heat_zero_iff_ninth T hT t g, ?_)
  cases g with
  | none => exact (fun _ => rfl, fun _ => seat_owes_no_bit)
  | some s => exact (fun h => absurd (off_seat_owes_a_bit s) h, fun h => by cases h)

/-- A RUN IS ITS OWN ATOMIC WITNESS, of the deed: a state that ran proves that a run exists. -/
theorem the_run_witnesses_a_run {Q : Type} (s : Exec Q) (h : ran s = true) : ∃ r : Exec Q, ran r = true := by
  exact (s, h)

/-- AND OF NOTHING ELSE: a fact that holds whatever the configuration, the deed included, forces no value. -/
theorem the_deed_forces_nothing (D : Prop) (hD : D) : ¬ ∀ S : Config, Closed S → D → Value S := by
  intro hall
  exact pair_world_lacks_value (1, 0) (fun e => by cases e) (hall _
    (pair_world_closed (1, 0)) hD)


/-! ## PART TWO · The force-witness closure -/

/-- THE ATOMIC STEP: a witness with its check proves the existential it witnesses. -/
theorem witness_proves_exists {α : Type} (P : α → Prop) (w : α) (h : P w) : ∃ x, P x := ⟨w, h⟩

/-- THE NINTH GATE, PACKED: a gate is the ninth exactly when all five readings hold of it. The five biconditionals
    of ninth_gate_is_least_erasure, bound into one. -/
theorem ninth_gate_pack (t : Int) (T : Nat) (hT : 0 < T) (g : Gate) :
    g = none ↔
      (gfold g = g ∧ onLine (toChart t g) ∧ reg (toChart t g) = toChart t g ∧
       price T (erased (gateCfg t g)) = 0 ∧ ¬ OwesBit g) := by
  have h := ninth_gate_is_least_erasure t T hT g
  constructor
  · intro e
    exact (h.1.mpr e, h.2.1.mpr e, h.2.2.1.mpr e, h.2.2.2.1.mpr e, h.2.2.2.2.mpr e)
  · intro hh
    exact h.1.mp hh.1

/-- The deed of the substrate: a run, and the fact that it ran. -/
structure SubstrateDeed (Q : Type) where
  run : Exec Q
  didRun : ran run = true

/-- THE FREE BIT. A run whose flag is true leaves the value free: by the run the value does not stand on every
    closed configuration. It is the_deed_forces_nothing read at the flag of the deed. A computation is a deed, and
    the value is the field of the act. -/
theorem the_run_does_not_force_the_value {Q : Type} (s : Exec Q) (h : ran s = true) :
    ¬ (∀ S : Config, Closed S → Value S) :=
  fun hall => the_deed_forces_nothing (ran s = true) h (fun S hS _ => hall S hS)

/-- THE FORCE-WITNESS CLOSURE. For a deed of the substrate, a term of the act, and any gate: the gate is the ninth
    exactly when it is the fold's fixed point, on the line, erased nothing, free to register at a positive
    temperature and owing no bit; the value holds on the field the act supplies; a run that ran exists; and the
    run leaves the value free. The fourth conjunct is the free bit. It is the implementation of the force. -/
theorem force_witness_closure {Q : Type} (d : SubstrateDeed Q) (Z : ActualZeros)
    (t : Int) (T : Nat) (hT : 0 < T) (g : Gate) :
    (g = none ↔
      (gfold g = g ∧ onLine (toChart t g) ∧ reg (toChart t g) = toChart t g ∧
        price T (erased (gateCfg t g)) = 0 ∧ ¬ OwesBit g)) ∧
    Value Z.zeros ∧
    (∃ r : Exec Q, ran r = true) ∧
    ¬ (∀ S : Config, Closed S → Value S) :=
  ⟨ninth_gate_pack t T hT g,
   value_from_the_act Z,
   the_run_witnesses_a_run d.run d.didRun,
   the_run_does_not_force_the_value d.run d.didRun⟩

/-- THE GUARD ON THE CLOSURE, the double defense restated: the value comes by the act; between the registered
    world and the pair world of a point off the line, every reading that respects the record leaves the value
    free; and the deed leaves it free. -/
theorem force_witness_guarded {Q : Type} (d : SubstrateDeed Q) (Z : ActualZeros) :
    Value Z.zeros ∧
    (∀ (p : Point), ¬ onLine p → ∀ (g : Config → Prop), (∀ S S', SameRecord S S' →
    (g S ↔ g S')) →
      ¬ ((g (registered p) ↔ Value (registered p)) ∧ (g (pairWorld p) ↔ Value
      (pairWorld p)))) ∧
    ¬ (∀ S : Config, Closed S → Value S) :=
  ⟨value_from_the_act Z,
   fun p h g hg => record_decides_nothing p h g hg,
   the_run_does_not_force_the_value d.run d.didRun⟩

end ForceWitness

/-! ## The cones, pinned. Each line is the compiler's own; a drifted cone fails the compile. -/
/-- info: 'ForceWitness.neg_neg_free' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.neg_neg_free
/-- info: 'ForceWitness.neg_self_zero' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.neg_self_zero
/-- info: 'ForceWitness.fold_involutive' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.fold_involutive
/-- info: 'ForceWitness.the_cut_is_the_line' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.the_cut_is_the_line
/-- info: 'ForceWitness.reg_lands' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.reg_lands
/-- info: 'ForceWitness.reg_erases_nothing_iff' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.reg_erases_nothing_iff
/-- info: 'ForceWitness.pair_world_closed' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.pair_world_closed
/-- info: 'ForceWitness.one_record' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.one_record
/-- info: 'ForceWitness.registered_has_value' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.registered_has_value
/-- info: 'ForceWitness.pair_world_lacks_value' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.pair_world_lacks_value
/-- info: 'ForceWitness.record_decides_nothing' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.record_decides_nothing
/-- info: 'ForceWitness.value_from_the_act' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.value_from_the_act
/-- info: 'ForceWitness.seat_is_the_ninth' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.seat_is_the_ninth
/-- info: 'ForceWitness.orient_ne_zero' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.orient_ne_zero
/-- info: 'ForceWitness.orient_flips' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.orient_flips
/-- info: 'ForceWitness.gate_carrier_equivariant' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.gate_carrier_equivariant
/-- info: 'ForceWitness.faithful_carrier_lands_only_the_ninth' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.faithful_carrier_lands_only_the_ninth
/-- info: 'ForceWitness.orientation_carrier_separates' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.orientation_carrier_separates
/-- info: 'ForceWitness.seat_owes_no_bit' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.seat_owes_no_bit
/-- info: 'ForceWitness.off_seat_owes_a_bit' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.off_seat_owes_a_bit
/-- info: 'ForceWitness.gate_heat_zero_iff_ninth' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.gate_heat_zero_iff_ninth
/-- info: 'ForceWitness.ninth_gate_is_least_erasure' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.ninth_gate_is_least_erasure
/-- info: 'ForceWitness.the_run_witnesses_a_run' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.the_run_witnesses_a_run
/-- info: 'ForceWitness.the_deed_forces_nothing' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.the_deed_forces_nothing
/-- info: 'ForceWitness.witness_proves_exists' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.witness_proves_exists
/-- info: 'ForceWitness.ninth_gate_pack' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.ninth_gate_pack
/-- info: 'ForceWitness.the_run_does_not_force_the_value' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.the_run_does_not_force_the_value
/-- info: 'ForceWitness.force_witness_closure' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.force_witness_closure
/-- info: 'ForceWitness.force_witness_guarded' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.force_witness_guarded

/-! ## The closure and its guard, printed. -/
#print axioms ForceWitness.force_witness_closure
```

```
#print axioms ForceWitness.force_witness_guarded

/-! ## THE PLUG · appended, nothing above changed. The run's true flag offered as the act's supply field. -/
namespace ForceWitness
/-- The plug, attempted: if a true flag supplied least erasure on every closed world, the run would force the value.
    The compiler refuses it. -/
theorem the_plug_fails {Q : Type} (s : Exec Q) (h : ran s = true) :
    ¬ (ran s = true → ∀ S : Config, Closed S → LeastErasure S) :=
  fun plug => the_run_does_not_force_the_value s h (fun S hS => value_from_the_act (S, hS, plug h S hS))
/-- What the plug does deliver: with the act's field beside the run, the value stands on that field, the run is
    witnessed, and the run still leaves the value free. Run and field are two inputs, never one. -/
theorem the_plug_delivers {Q : Type} (d : SubstrateDeed Q) (Z : ActualZeros) :
    Value Z.zeros ∧ (∃ r : Exec Q, ran r = true) ∧ ¬ (∀ S : Config, Closed S → Value S) :=
  (value_from_the_act Z, the_run_witnesses_a_run d.run d.didRun,
   the_run_does_not_force_the_value d.run d.didRun)
end ForceWitness

end PartIVb

/-! # PART IV-c · the time kernel of the monism-fixed codex, verbatim, with the judge probe -/
section PartIVc
/-
  The time kernel of the monism-fixed codex, carried verbatim: Codex.lean of the Master Codex v5.1.0 with the patch of
  APEX-PSP-MONISM-FIXED-01 applied (patched sha256 22d908f7d3d2c96b…), its two TimeLocus sections, lines 7875 to 7947,
  followed by the judge probe of this edition. Nothing in the carried lines is changed. The carried chart reads real
  parts as the first edition's chart does at resolution one, x = 2·Re s, with heights in ℤ, and its counter-world's
  off-line pair sits at x = 0 and 2, Re s = 0 and 1;
  the judge probe states the same test on the offset chart inside the open strip, with the conjugate symmetry and the
  empty low band, its off-line zeros at Re s = 1/4 and 3/4. Two names in a carried docstring,
  `not_constructible_off_line` and `monism_witness_fails_in_counter_world`, are theorems of the patched codex outside
  the carried lines; they are not in this seed and nothing here uses them.
-/
namespace TimeLocus

def onLine (p : Int × Int) : Prop := p.1 = 1

/-- A timed world: the locus at each time, and the zeros present at each time. -/
structure World where
  locus : Nat → (Int × Int → Prop)
  zeros : Nat → (Int × Int → Prop)

/-- TIME PSP premise: prior and posterior locus are the SAME locus, the line, at every time. -/
def SameLocus (W : World) : Prop := ∀ t p, W.locus t p ↔ onLine p

/-- The claim to be tested: every zero at every time is bound to the locus. -/
def Bound (W : World) : Prop := ∀ t p, W.zeros t p → W.locus t p

/-- Fold-invariance at every time: the functional equation acts at each iteration. -/
def FoldInv (W : World) : Prop := ∀ t p, W.zeros t p → W.zeros t (2 - p.1, p.2)

/-- 51. Given the same locus at all times, being bound IS the line property at all times. -/
theorem bound_iff_line (W : World) (h : SameLocus W) :
    Bound W ↔ ∀ t p, W.zeros t p → onLine p :=
  (fun b t p z => (h t p).mp (b t p z), fun l t p z => (h t p).mpr (l t p z))

/-- 52, the test world. A world where the locus is the same line at every time, the fold acts at every
    time, the on-line zero recurs at every time, and a mirror pair sits off the line at every time. -/
def testWorld : World :=
  (fun _ p => onLine p, fun _ p => p = (1, 0) ∨ p = (0, 5) ∨ p = (2, 5))

theorem test_same_locus : SameLocus testWorld := fun _ _ => Iff.rfl

theorem test_fold_inv : FoldInv testWorld := by
  intro _ p hp
  rcases hp with h | h | h <;> subst h
  · exact Or.inl rfl
  · exact Or.inr (Or.inr rfl)
  · exact Or.inr (Or.inl rfl)

theorem test_not_bound : ¬ Bound testWorld := fun b => by
  have := b 0 (0, 5) (Or.inr (Or.inl rfl)); cases this

/-- 52. Therefore SameLocus and FoldInv, at every time, do not imply Bound. -/
theorem time_does_not_bind :
    ¬ ∀ W : World, SameLocus W → FoldInv W → Bound W :=
  fun h => test_not_bound (h testWorld test_same_locus test_fold_inv)

end TimeLocus

namespace TimeLocus

/-- Residual Monism read as the Codex states it: one involution serves both routes. -/
def sigmaGeo (p : Int × Int) : Int × Int := (2 - p.1, p.2)
def sigmaForm (p : Int × Int) : Int × Int := (2 - p.1, p.2)
def OneInvolution : Prop := ∀ p, sigmaGeo p = sigmaForm p

/-- Residual Monism read as timeless: whether the zeros sit on the locus does not vary in time. -/
def P (W : World) (t : Nat) : Prop := ∀ p, W.zeros t p → onLine p
def Timeless (W : World) : Prop := ∀ t s, P W t ↔ P W s

/-- 53. The seedless reading holds in the counter-world: one involution by rfl, and timelessness
    because the property "all zeros on the line" is constantly false there. Timeless and unbound.
    This is not monism. The monism witness carries its seed, and in the counter-world it fails
    (`not_constructible_off_line`, `monism_witness_fails_in_counter_world`). -/
theorem seedless_reading_holds_in_counter_world :
    OneInvolution ∧ Timeless testWorld ∧ ¬ Bound testWorld :=
  (fun _ => rfl, fun _ _ => Iff.rfl, test_not_bound)

/-- 54. What timeless monism does do: it makes one instant decide all time. With the seed, binding
    follows; the seed is "every zero present at the instant is on the line". -/
theorem timeless_with_seed_binds (W : World) (h : SameLocus W) (u : Timeless W) (s0 : P W 0) :
    Bound W :=
  (bound_iff_line W h).mpr (fun t p z => ((u 0 t).mp s0) p z)

end TimeLocus

namespace Judge
open TimeLocus
/-- The identical locus, the fold at every time, one involution and timelessness together do not exclude a zero off
    the line: the counter-world carries all four. -/
theorem identical_locus_does_not_exclude :
    ¬ ∀ W : World, SameLocus W → FoldInv W → OneInvolution → Timeless W → Bound W :=
  fun h => test_not_bound (h testWorld test_same_locus test_fold_inv (fun _ => rfl) (fun _ _ => Iff.rfl))
/-- What does exclude it: on the same locus and timeless, being bound is exactly the seed at time zero. -/
theorem the_seed_is_exactly_what_binds (W : World) (h : SameLocus W) (u : Timeless W) : Bound W ↔ P W 0 :=
  (fun b => fun p z => ((bound_iff_line W h).mp b) 0 p z, fun s0 =>
   timeless_with_seed_binds W h u s0)

/-- The same test on the offset chart, d = 8·Re s − 4, inside the open strip: at every time the line occupied at every
    height |t| ≥ 14, and one mirrored pair at Re s = 1/4 and 3/4 at height 3·10¹² + 1 with its conjugate. -/
def offsetWorld (_ : Nat) (p : RememberedOffered.Point) : Prop :=
  (p.1 = 0 ∧ (14 ≤ p.2 ∨ p.2 ≤ -14)) ∨ p = (2, 3000000000001) ∨ p = (-2, 3000000000001) ∨
    p = (2, -3000000000001) ∨ p = (-2, -3000000000001)
/-- Bound on the offset chart: every zero at every time on the line, the same locus at every time. -/
def BoundO (Z : Nat → RememberedOffered.Config) : Prop := ∀ t p, Z t p → RememberedOffered.onLine p
/-- Timeless on the offset chart: whether every zero sits on the line does not vary in time. -/
def TimelessO (Z : Nat → RememberedOffered.Config) : Prop :=
  ∀ t s, (∀ p, Z t p → RememberedOffered.onLine p) ↔ (∀ p, Z s p → RememberedOffered.onLine p)

/-- THE IDENTICAL LOCUS INSIDE THE STRIP DOES NOT EXCLUDE: on the offset chart, the same locus at every time, the fold
    and conjugation at every time, the empty low band, every zero strictly inside the strip (Re s strictly between 0
    and 1) and timelessness hold together on a world that is not bound; and on every timeless world being bound is
    exactly the seed at time zero. -/
theorem identical_locus_inside_the_strip_does_not_exclude :
    (∀ t, RememberedOffered.Closed (offsetWorld t)) ∧
    (∀ t p, offsetWorld t p → offsetWorld t (p.1, -p.2)) ∧
    (∀ t p, offsetWorld t p → 14 ≤ p.2 ∨ p.2 ≤ -14) ∧
    (∀ t p, offsetWorld t p → -4 < p.1 ∧ p.1 < 4) ∧
    TimelessO offsetWorld ∧ ¬ BoundO offsetWorld ∧
    (∀ Z : Nat → RememberedOffered.Config, TimelessO Z →
      (BoundO Z ↔ ∀ p, Z 0 p → RememberedOffered.onLine p)) := by
  refine (fun t p hp => ?_, fun t p hp => ?_, fun t p hp => ?_, fun t p hp => ?_, fun _ _ => Iff.rfl, ?_, ?_)
  · unfold offsetWorld at hp ⊢
    rcases hp with (h1, h2) | h | h | h | h
    · exact Or.inl (show -p.1 = 0 by omega, h2)
    · subst h; exact Or.inr (Or.inr (Or.inl (by decide)))
    · subst h; exact Or.inr (Or.inl (by decide))
    · subst h; exact Or.inr (Or.inr (Or.inr (Or.inr (by decide))))
    · subst h; exact Or.inr (Or.inr (Or.inr (Or.inl (by decide))))
  · unfold offsetWorld at hp ⊢
    rcases hp with (h1, h2) | h | h | h | h
    · exact Or.inl (h1, by omega)
    · subst h; exact Or.inr (Or.inr (Or.inr (Or.inl (by decide))))
    · subst h; exact Or.inr (Or.inr (Or.inr (Or.inr (by decide))))
    · subst h; exact Or.inr (Or.inr (Or.inl (by decide)))
    · subst h; exact Or.inr (Or.inr (Or.inl (by decide)))
  · unfold offsetWorld at hp
    rcases hp with (_, h2) | h | h | h | h
    · exact h2
    all_goals (subst h; decide)
  · unfold offsetWorld at hp
    rcases hp with (h1, _) | h | h | h | h
    · constructor <;> omega
    all_goals (subst h; decide)
  · intro b
    have h : (2 : Int) = 0 := b 0 (2, 3000000000001) (Or.inr (Or.inl rfl))
    exact absurd h (by decide)
  · intro Z u
    exact (fun b => b 0, fun s0 t p z => ((u 0 t).mp s0) p z)
end Judge

end PartIVc

/-! # PART V · the arrow-side test -/
section PartV
/-
  ARROW SIDE TEST · the ζ-specific facts, placed on RA's arrow, tested against an off-line pair.
  Core Lean 4.19.0, no import, no axiom declared, no sorry.
  Chart: x = 2W·Re s at resolution W, height t. The arrow's tail pole s = 0 sits at x = 0, its head pole s = 1 at
  x = 2W, its hinge Re s = 1/2 at x = W. The Euler product lives beyond the head.
  Each fact ζ has and the Davenport–Heilbronn shape lacks, or that is proved for ζ, enters as a predicate at its
  place on the arrow, its source cited:
    ENDS        Build and Edge: no zero at or beyond either pole (Euler product for Re s > 1; the prime number theorem's
                non-vanishing on Re s = 1; mirrored by the functional equation) [cited].
    ZERO-FREE   near the head, and by the fold near the tail: at height t no zero within m t of a pole
                (de la Vallée Poussin; explicit constants Mossinghoff–Trudgian) [cited]; the margin is a parameter.
    REAL PART   every zero up to height T0 on the line (Platt–Trudgian: every zero with 0 < Im s ≤ 3·10¹²) [cited];
                heights are read by their integer part, so chart height T0 = 3·10¹² − 1 reads Im s < 3·10¹².
```

```
    FINITELY OFF  only finitely many zeros off the line: stronger than every
    positive-proportion theorem
                (Selberg, Levinson, Conrey) and every zero-density estimate [cited].
-/
set_option autoImplicit false
namespace ArrowSide

abbrev Pt := Int × Int

structure Chart where
  W : Int
  hW : 0 < W

def onLine (C : Chart) (p : Pt) : Prop := p.1 = C.W
def fold (C : Chart) (p : Pt) : Pt := (2 * C.W - p.1, p.2)
def Closed (C : Chart) (S : Pt → Prop) : Prop := ∀ p, S p → S (fold C p)
def Value (C : Chart) (S : Pt → Prop) : Prop := ∀ p, S p → onLine C p

def ArrowEnds (C : Chart) (S : Pt → Prop) : Prop := ∀ p, S p → 0 < p.1 ∧ p.1 < 2 * C.W
def ZeroFree (C : Chart) (m : Int → Int) (S : Pt → Prop) : Prop :=
  ∀ p, S p → m p.2 < p.1 ∧ p.1 < 2 * C.W - m p.2
def RealPart (C : Chart) (T0 : Int) (S : Pt → Prop) : Prop := ∀ p, S p → p.2 ≤ T0 → onLine C p
def FinitelyOff (C : Chart) (S : Pt → Prop) : Prop := ∃ L : List Pt, ∀ p, S p → ¬ onLine C p → p ∈ L

/-- The ζ-shaped world: a zero on the line at every height, and one mirrored pair at offset d, height H. -/
def zetaShaped (C : Chart) (d H : Int) : Pt → Prop :=
  fun p => p.1 = C.W ∨ p = (C.W - d, H) ∨ p = (C.W + d, H)

theorem shaped_closed (C : Chart) (d H : Int) : Closed C (zetaShaped C d H) := by
  intro p hp
  unfold zetaShaped at hp ⊢
  rcases hp with h | h | h
  · left; show 2 * C.W - p.1 = C.W; omega
  · subst h; right; right; exact Prod.ext (show 2 * C.W - (C.W - d) = C.W + d by omega) rfl
  · subst h; right; left; exact Prod.ext (show 2 * C.W - (C.W + d) = C.W - d by omega) rfl

theorem shaped_ends (C : Chart) (d H : Int) (hd : 0 < d) (hdW : d < C.W) : ArrowEnds C (zetaShaped C d H) := by
  have hW := C.hW
  intro p hp
  unfold zetaShaped at hp
  rcases hp with h | h | h
  · constructor <;> omega
  · subst h; show 0 < C.W - d ∧ C.W - d < 2 * C.W; constructor <;> omega
  · subst h; show 0 < C.W + d ∧ C.W + d < 2 * C.W; constructor <;> omega

theorem shaped_zero_free (C : Chart) (m : Int → Int) (hm : ∀ t, m t < C.W) (d H : Int) (hmH : m H < C.W - d)
    (hd : 0 < d) : ZeroFree C m (zetaShaped C d H) := by
  intro p hp
  unfold zetaShaped at hp
  rcases hp with h | h | h
  · have := hm p.2; constructor <;> omega
  · subst h; show m H < C.W - d ∧ C.W - d < 2 * C.W - m H; constructor <;> omega
  · subst h; show m H < C.W + d ∧ C.W + d < 2 * C.W - m H; constructor <;> omega

theorem shaped_real_part (C : Chart) (T0 d H : Int) (hH : T0 < H) : RealPart C T0 (zetaShaped C d H) := by
  intro p hp ht
  unfold zetaShaped at hp
  rcases hp with h | h | h
  · exact h
  · subst h; have : H ≤ T0 := ht; exfalso; omega
  · subst h; have : H ≤ T0 := ht; exfalso; omega

theorem shaped_finitely_off (C : Chart) (d H : Int) : FinitelyOff C (zetaShaped C d H) := by
  refine ([(C.W - d, H), (C.W + d, H)], fun p hp hoff => ?_)
  unfold zetaShaped at hp
  rcases hp with h | h | h
  · exact absurd h hoff
  · subst h; exact List.Mem.head _
  · subst h; exact List.Mem.tail _ (List.Mem.head _)

theorem shaped_lacks_value (C : Chart) (d H : Int) (hd : 0 < d) : ¬ Value C (zetaShaped C d H) := by
  intro hv
  have h2 : C.W - d = C.W := hv (C.W - d, H) (Or.inr (Or.inl rfl))
  omega

/-- THE ARROW SIDE TEST. Every ζ-specific fact placed on the arrow (ends, zero-free region, real part to T0,
    finitely many off the line) holds on a world with a mirrored pair off the line above T0, so together they do
    not force the value. -/
theorem arrow_side_test (C : Chart) (m : Int → Int) (hm : ∀ t, m t < C.W) (T0 d H : Int)
    (hd : 0 < d) (hdW : d < C.W) (hH : T0 < H) (hmH : m H < C.W - d) :
    Closed C (zetaShaped C d H) ∧ ArrowEnds C (zetaShaped C d H) ∧ ZeroFree C m (zetaShaped C d H) ∧
    RealPart C T0 (zetaShaped C d H) ∧ FinitelyOff C (zetaShaped C d H) ∧ ¬ Value C (zetaShaped C d H) :=
  ⟨shaped_closed C d H, shaped_ends C d H hd hdW, shaped_zero_free C m hm d H hmH hd,
   shaped_real_part C T0 d H hH, shaped_finitely_off C d H, shaped_lacks_value C d H hd⟩

/-- THE FACTS ARE ζ-SPECIFIC AT THE ENDS: a zero beyond the head, the Davenport–Heilbronn shape, breaks ENDS. -/
theorem beyond_the_head_breaks_ends (C : Chart) (x t : Int) (hx : 2 * C.W ≤ x) :
    ¬ ArrowEnds C (fun p => p = (x, t)) := by
  intro h
  have h2 : x < 2 * C.W := (h (x, t) rfl).2
  omega

/-- AT ζ'S OWN NUMBERS: resolution W = 4, so x = 8·Re s; the pair at Re s = 1/4 and 3/4 (x = 2 and 6); the
    zero-free margin below one unit of 1/8 at every height where zeros occur (c/log t < 0.07 for t ≥ 14); the real
    part to chart height T0 = 3·10¹² − 1, every zero with Im s < 3·10¹²; the pair two units of height above it. -/
def zetaChart : Chart := (4, by decide)
theorem at_zetas_numbers :
    Closed zetaChart (zetaShaped zetaChart 2 3000000000001) ∧
    ArrowEnds zetaChart (zetaShaped zetaChart 2 3000000000001) ∧
    ZeroFree zetaChart (fun _ => 0) (zetaShaped zetaChart 2 3000000000001) ∧
    RealPart zetaChart 2999999999999 (zetaShaped zetaChart 2 3000000000001) ∧
    FinitelyOff zetaChart (zetaShaped zetaChart 2 3000000000001) ∧
    ¬ Value zetaChart (zetaShaped zetaChart 2 3000000000001) :=
 arrow_side_test zetaChart (fun _ => 0) (fun _ => show (0 : Int) < 4 by decide)
  2999999999999 2 3000000000001
    (by decide) (by decide) (by decide) (by decide)

/-! ## The faithful model: the facts of ζ with its two symmetries and its empty low band -/

/-- Conjugate symmetry: the zero set is closed under t ↦ −t. -/
def ConjClosed (S : Pt → Prop) : Prop := ∀ p, S p → S (p.1, -p.2)
/-- No zero below height 14 in absolute value: ζ's first zero lies at height 14.13… [cited]; heights read by their
    integer part, chart height 14 holds Im s in [14, 15). -/
def NoLowZeros (S : Pt → Prop) : Prop := ∀ p, S p → 14 ≤ p.2 ∨ p.2 ≤ -14
/-- The verification in both half-planes: every zero at chart height |t| ≤ T0 is on the line; at T0 = 3·10¹² − 1,
    every zero with |Im s| < 3·10¹² [Platt–Trudgian, cited]. -/
def RealPartAbs (C : Chart) (T0 : Int) (S : Pt → Prop) : Prop := ∀ p, S p → p.2 ≤ T0 → -T0 ≤ p.2 → onLine C p
/-- The zero-free margin, in units of 1/(2W): the whole width below |t| = 14, where ζ has no zero, and no unit at
    every height |t| ≥ 14. At every width it holds of ζ's reading, since it adds nothing to the ends there and the
    reader's rule keeps every zero of the open strip inside the open chart strip; at the widths W ≤ 7 it is the
    region at full strength, since c/log t < 0.07 < 1/(2W). `faithful_every_margin` carries the region at every
    width, one unit short for the rounding. -/
def margin14 (C : Chart) : Int → Int := fun t => if 14 ≤ t ∨ t ≤ -14 then 0 else C.W
/-- The faithful ζ-shaped world: a zero on the line at every height |t| ≥ 14, and one mirrored pair at offset d at
    heights H and −H. -/
def zetaFaithful (C : Chart) (d H : Int) : Pt → Prop := fun p =>
  (p.1 = C.W ∧ (14 ≤ p.2 ∨ p.2 ≤ -14)) ∨ p = (C.W - d, H) ∨ p = (C.W + d, H) ∨
    p = (C.W - d, -H) ∨ p = (C.W + d, -H)

theorem faithful_arrow_side_test (C : Chart) (T0 d H : Int) (hd : 0 < d) (hdW : d < C.W) (hH : T0 < H)
    (h14 : 14 ≤ H) :
    Closed C (zetaFaithful C d H) ∧ ConjClosed (zetaFaithful C d H) ∧ ArrowEnds C (zetaFaithful C d H) ∧
    ZeroFree C (margin14 C) (zetaFaithful C d H) ∧ NoLowZeros (zetaFaithful C d H) ∧
    RealPartAbs C T0 (zetaFaithful C d H) ∧ FinitelyOff C (zetaFaithful C d H) ∧
    ¬ Value C (zetaFaithful C d H) := by
  have hW := C.hW
  refine (?_, ?_, ?_, ?_, ?_, ?_, ?_, ?_)
  · intro p hp
    unfold zetaFaithful at hp ⊢
    rcases hp with (h1, h2) | h | h | h | h
    · left; exact (show 2 * C.W - p.1 = C.W by omega, h2)
    · subst h; right; right; left; exact Prod.ext (show 2 * C.W - (C.W - d) = C.W + d by omega) rfl
    · subst h; right; left; exact Prod.ext (show 2 * C.W - (C.W + d) = C.W - d by omega) rfl
    · subst h; right; right; right; right; exact Prod.ext (show 2 * C.W - (C.W - d) = C.W + d by omega) rfl
    · subst h; right; right; right; left; exact Prod.ext (show 2 * C.W - (C.W + d) = C.W - d by omega) rfl
  · intro p hp
    unfold zetaFaithful at hp ⊢
    rcases hp with (h1, h2) | h | h | h | h
    · left; exact (h1, show 14 ≤ -p.2 ∨ -p.2 ≤ -14 by omega)
    · subst h; right; right; right; left; rfl
    · subst h; right; right; right; right; rfl
    · subst h; right; left; exact Prod.ext rfl (show -(-H) = H by omega)
    · subst h; right; right; left; exact Prod.ext rfl (show -(-H) = H by omega)
  · intro p hp
    unfold zetaFaithful at hp
    rcases hp with (h1, _) | h | h | h | h
    · constructor <;> omega
    all_goals (subst h; constructor <;> (show (_ : Int) < _; omega))
  · intro p hp
    unfold zetaFaithful at hp
    unfold margin14
    rcases hp with (h1, h2) | h | h | h | h
    · rw [if_pos h2]; constructor <;> omega
    · subst h; rw [if_pos (Or.inl h14)]; show (0 : Int) < C.W - d ∧ C.W - d < 2 * C.W - 0; constructor <;> omega
    · subst h; rw [if_pos (Or.inl h14)]; show (0 : Int) < C.W + d ∧ C.W + d < 2 * C.W - 0; constructor <;> omega
    · subst h; rw [if_pos (Or.inr (show -H ≤ -14 by omega))]
      show (0 : Int) < C.W - d ∧ C.W - d < 2 * C.W - 0; constructor <;> omega
    · subst h; rw [if_pos (Or.inr (show -H ≤ -14 by omega))]
      show (0 : Int) < C.W + d ∧ C.W + d < 2 * C.W - 0; constructor <;> omega
  · intro p hp
    unfold zetaFaithful at hp
    rcases hp with (_, h2) | h | h | h | h
    · exact h2
    · subst h; exact Or.inl h14
    · subst h; exact Or.inl h14
    · subst h; exact Or.inr (show -H ≤ -14 by omega)
    · subst h; exact Or.inr (show -H ≤ -14 by omega)
  · intro p hp ht1 ht2
    unfold zetaFaithful at hp
    rcases hp with (h1, _) | h | h | h | h
    · exact h1
    · subst h; have : H ≤ T0 := ht1; exfalso; omega
    · subst h; have : H ≤ T0 := ht1; exfalso; omega
    · subst h; have : -T0 ≤ -H := ht2; exfalso; omega
    · subst h; have : -T0 ≤ -H := ht2; exfalso; omega
  · refine ([(C.W - d, H), (C.W + d, H), (C.W - d, -H), (C.W + d, -H)], fun p hp hoff => ?_)
    unfold zetaFaithful at hp
    rcases hp with (h1, _) | h | h | h | h
    · exact absurd h1 hoff
    · subst h; exact List.Mem.head _
    · subst h; exact List.Mem.tail _ (List.Mem.head _)
    · subst h; exact List.Mem.tail _ (List.Mem.tail _ (List.Mem.head _))
    · subst h; exact List.Mem.tail _ (List.Mem.tail _ (List.Mem.tail _ (List.Mem.head _)))
  · intro hv
    have h2 : C.W - d = C.W := hv (C.W - d, H) (Or.inr (Or.inl rfl))
    omega
```

```
/-- AT ζ'S OWN NUMBERS, FAITHFULLY: W = 4, so x = 8·Re s; the pair at Re s = 1/4 and 3/4 at height 3·10¹² + 1 and
    its conjugate at −(3·10¹² + 1); the line occupied at every |t| ≥ 14; the verification, every zero with
    |Im s| < 3·10¹², at chart height 3·10¹² − 1 in both half-planes. -/
theorem at_zetas_numbers_faithful :
    Closed zetaChart (zetaFaithful zetaChart 2 3000000000001) ∧
    ConjClosed (zetaFaithful zetaChart 2 3000000000001) ∧
    ArrowEnds zetaChart (zetaFaithful zetaChart 2 3000000000001) ∧
    ZeroFree zetaChart (margin14 zetaChart) (zetaFaithful zetaChart 2 3000000000001) ∧
    NoLowZeros (zetaFaithful zetaChart 2 3000000000001) ∧
    RealPartAbs zetaChart 2999999999999 (zetaFaithful zetaChart 2 3000000000001) ∧
    FinitelyOff zetaChart (zetaFaithful zetaChart 2 3000000000001) ∧
    ¬ Value zetaChart (zetaFaithful zetaChart 2 3000000000001) :=
  faithful_arrow_side_test zetaChart 2999999999999 2 3000000000001 (by decide) (by decide) (by decide) (by decide)

/-- THE FAITHFUL MODEL UNDER EVERY ZERO-FREE MARGIN: at every chart width and for every margin that, at the heights
    where zeros occur, stays short of the line and leaves the off-line quadruple outside it at ±H, the facts hold on
    the faithful world and the value fails. ζ's known region, c/log|t| in Re s with c/log 14 < 0.07 and
    c/log(3·10¹²) < 0.0065, read in units of 1/(2W), is such a margin at every width for the pair at Re s = 1/4 and
    3/4 [Mossinghoff–Trudgian 2015, cited]. -/
theorem faithful_every_margin (C : Chart) (m : Int → Int) (T0 d H : Int) (hd : 0 < d) (hdW : d < C.W)
    (hH : T0 < H) (h14 : 14 ≤ H) (hm : ∀ t, (14 ≤ t ∨ t ≤ -14) → m t < C.W)
    (hmH : m H < C.W - d) (hmH' : m (-H) < C.W - d) :
    Closed C (zetaFaithful C d H) ∧ ConjClosed (zetaFaithful C d H) ∧ ArrowEnds C (zetaFaithful C d H) ∧
    ZeroFree C m (zetaFaithful C d H) ∧ NoLowZeros (zetaFaithful C d H) ∧
    RealPartAbs C T0 (zetaFaithful C d H) ∧ FinitelyOff C (zetaFaithful C d H) ∧
    ¬ Value C (zetaFaithful C d H) := by
  have base := faithful_arrow_side_test C T0 d H hd hdW hH h14
  refine (base.1, base.2.1, base.2.2.1, ?_, base.2.2.2.2.1, base.2.2.2.2.2.1, base.2.2.2.2.2.2.1,
    base.2.2.2.2.2.2.2)
  intro p hp
  unfold zetaFaithful at hp
  rcases hp with (h1, h2) | h | h | h | h
  · have := hm p.2 h2; constructor <;> omega
  · subst h; show m H < C.W - d ∧ C.W - d < 2 * C.W - m H; constructor <;> omega
  · subst h; show m H < C.W + d ∧ C.W + d < 2 * C.W - m H; constructor <;> omega
  · subst h; show m (-H) < C.W - d ∧ C.W - d < 2 * C.W - m (-H); constructor <;> omega
  · subst h; show m (-H) < C.W + d ∧ C.W + d < 2 * C.W - m (-H); constructor <;> omega

/-- AT WIDTH ONE THE ENDS ARE THE VALUE: the open strip holds only the line, so the placed ends force the value there,
    as at the first edition's resolution one; the faithful model needs a width of at least two. -/
theorem at_width_one_the_ends_are_the_value (S : Pt → Prop) :
    ArrowEnds (1, by decide) S ↔ Value (1, by decide) S := by
  constructor
  · intro h p hp
    have := h p hp
    show p.1 = 1
    have h1 : 0 < p.1 ∧ p.1 < 2 * 1 := this
    omega
  · intro h p hp
    have h1 : p.1 = 1 := h p hp
    show 0 < p.1 ∧ p.1 < 2 * 1
    omega

/-- AN OFF-LINE ZERO COMES IN FOUR: in a world closed under the reflection and under conjugation, with no zero below
    height 14, a zero off the line brings its mirror, its conjugate and its conjugate's mirror, four distinct points:
    one mirrored pair and its conjugate. -/
theorem an_off_line_zero_comes_in_four (C : Chart) (S : Pt → Prop) (hc : Closed C S) (hk : ConjClosed S)
    (hl : NoLowZeros S) (p : Pt) (hp : S p) (hoff : ¬ onLine C p) :
    S (fold C p) ∧ S (p.1, -p.2) ∧ S (fold C (p.1, -p.2)) ∧
    fold C p ≠ p ∧ (p.1, -p.2) ≠ p ∧ fold C (p.1, -p.2) ≠ p ∧
    (p.1, -p.2) ≠ fold C p ∧ fold C (p.1, -p.2) ≠ fold C p ∧ fold C (p.1, -p.2) ≠ (p.1, -p.2) := by
  have h14 := hl p hp
  refine (hc p hp, hk p hp, hc _ (hk p hp), ?_)
  obtain (x, t) := p
  have hx : x ≠ C.W := hoff
  have ht : 14 ≤ t ∨ t ≤ -14 := h14
  refine (fun e => ?_, fun e => ?_, fun e => ?_, fun e => ?_, fun e => ?_, fun e => ?_)
  · have h1 : 2 * C.W - x = x := congrArg Prod.fst e
    omega
  · have h2 : -t = t := congrArg Prod.snd e
    omega
  · have h2 : -t = t := congrArg Prod.snd e
    omega
  · have h2 : -t = t := congrArg Prod.snd e
    omega
  · have h2 : -t = t := congrArg Prod.snd e
    omega
  · have h1 : 2 * C.W - x = x := congrArg Prod.fst e
    omega

end ArrowSide


end PartV

/-! # PART V-b · the charts are one -/
section PartVb
/-
  THE CHARTS ARE ONE. The seed reads the critical line on five charts: Part II's at x = 2n·Re s for every resolution n
  (x = 2·Re s at resolution one, x = 4·Re s at resolution two), heights in ℕ; Part IV's at x = 4·Re s; Part IV-c's at
  x = 2·Re s, heights in ℤ; Part V's at x = 2W·Re s for every width W; and the offset chart of Parts III and IV-b,
  d = 2n·Re s − n at resolution n, whose line d = 0 and fold d ↦ −d are the same at every resolution. Each maps into
  the offset chart at a definite resolution by an equivariant map, one that carries the chart's fold to the offset
  fold and the chart's line to the offset line: the maps of Parts II at resolutions one and two, IV, IV-c and V at
  width four land at resolution four, where one real part read on any of them lands at one offset point; the maps
  at resolution n and width W land at resolution n and W. Every map keeps the chart's height and scales the offset
  from the line by a positive factor; the maps out of the charts with heights in ℤ commute with conjugation, and
  the first edition's chart reads the upper half-plane. Transport carries reflection-closure and the value across. Every act type of the seed is an act of the offset chart at the image of
  its zero set; the root read at the zeros on Part II's chart is the root read twice at the image; both constructed
  roots, Part I's and Part II's, feed the closing theorems. The zero set of ζ is read on the offset chart at every
  resolution by the reader's rule, and the act supplies least erasure at every resolution.
-/
set_option autoImplicit false
namespace Charts

/-- The image of a configuration under a chart map into the offset chart. -/
def img {α : Type} (φ : α → RememberedOffered.Point) (S : α → Prop) : RememberedOffered.Config :=
  fun q => ∃ p, S p ∧ φ p = q

/-- A chart map is equivariant when it carries the chart's fold to the offset fold and the chart's line to the
    offset line. -/
structure Equivariant {α : Type} (fold : α → α) (onLine : α → Prop) (φ : α → RememberedOffered.Point) : Prop where
  comm : ∀ p, φ (fold p) = RememberedOffered.fold (φ p)
  line : ∀ p, RememberedOffered.onLine (φ p) ↔ onLine p

/-- TRANSPORT: an equivariant map carries reflection-closure across, and the value both ways. -/
theorem transport {α : Type} {fold : α → α} {onLine : α → Prop} {φ : α → RememberedOffered.Point}
    (E : Equivariant fold onLine φ) (S : α → Prop) :
    ((∀ p, S p → S (fold p)) → RememberedOffered.Closed (img φ S)) ∧
    ((∀ p, S p → onLine p) ↔ RememberedOffered.Value (img φ S)) := by
  refine (fun hS q (p, hp, e) => (fold p, hS p hp, by rw [E.comm, e]),
    (fun hv q (p, hp, e) => ?_, fun hv p hp => (E.line p).mp (hv _ (p, hp, rfl))))
  rw [← e]; exact (E.line p).mpr (hv p hp)

/-- Part IV's chart, x = 4·Re s, into the offset chart d = 8·Re s − 4. -/
def φH (p : Hinge.Pt) : RememberedOffered.Point := (2 * p.1 - 4, p.2)
/-- Part V's chart at ζ's resolution, x = 8·Re s, into the offset chart. -/
def φA (p : ArrowSide.Pt) : RememberedOffered.Point := (p.1 - 4, p.2)
/-- Part II's chart, x = 2·Re s with heights in ℕ, into the offset chart. -/
def φP (z : PrimeFreedom.Pt) : RememberedOffered.Point := (4 * z.x - 4, (z.t : Int))
/-- Part II's chart at resolution two, x = 4·Re s, into the offset chart. -/
def φP₂ (z : PrimeFreedom.Pt) : RememberedOffered.Point := (2 * z.x - 4, (z.t : Int))
/-- Part V's chart at every width W, x = 2W·Re s, into the offset chart at resolution W: d = x − W. -/
def φW (C : ArrowSide.Chart) (p : ArrowSide.Pt) : RememberedOffered.Point := (p.1 - C.W, p.2)
/-- Part II's chart at every resolution n, x = 2n·Re s with heights in ℕ, into the offset chart at resolution n. -/
def φPn (n : Int) (z : PrimeFreedom.Pt) : RememberedOffered.Point := (z.x - n, (z.t : Int))
/-- Part IV-c's chart, x = 2·Re s with heights in ℤ, into the offset chart. -/
def φT (p : Int × Int) : RememberedOffered.Point := (4 * p.1 - 4, p.2)
/-- Part IV-b's chart is the offset chart: the identity. -/
def φF (p : ForceWitness.Point) : RememberedOffered.Point := p

theorem eqH : Equivariant Hinge.fold Hinge.onLine φH :=
  ⟨fun p => Prod.ext (show 2 * (0 + 4 - p.1) - 4 = -(2 * p.1 - 4) by omega) rfl,
   fun p => show 2 * p.1 - 4 = 0 ↔ p.1 = 2 by omega⟩
theorem eqA : Equivariant (ArrowSide.fold ArrowSide.zetaChart) (ArrowSide.onLine ArrowSide.zetaChart) φA :=
  ⟨fun p => Prod.ext (show 2 * 4 - p.1 - 4 = -(p.1 - 4) by omega) rfl,
   fun p => show p.1 - 4 = 0 ↔ p.1 = 4 by omega⟩
theorem eqP : Equivariant PrimeFreedom.fold PrimeFreedom.onLine φP :=
  ⟨fun z => Prod.ext (show 4 * (2 - z.x) - 4 = -(4 * z.x - 4) by omega) rfl,
   fun z => show 4 * z.x - 4 = 0 ↔ z.x = 1 by omega⟩
theorem eqP₂ : Equivariant PrimeFreedom.fold₂ PrimeFreedom.onLine₂ φP₂ :=
  ⟨fun z => Prod.ext (show 2 * (4 - z.x) - 4 = -(2 * z.x - 4) by omega) rfl,
   fun z => show 2 * z.x - 4 = 0 ↔ z.x = 2 by omega⟩
theorem eqW (C : ArrowSide.Chart) : Equivariant (ArrowSide.fold C) (ArrowSide.onLine C) (φW C) :=
  ⟨fun p => Prod.ext (show 2 * C.W - p.1 - C.W = -(p.1 - C.W) by omega) rfl,
   fun p => show p.1 - C.W = 0 ↔ p.1 = C.W by omega⟩
theorem eqPn (n : Int) : Equivariant (PrimeFreedom.foldAt n) (fun z => z.x = n) (φPn n) :=
  ⟨fun z => Prod.ext (show 2 * n - z.x - n = -(z.x - n) by omega) rfl,
   fun z => show z.x - n = 0 ↔ z.x = n by omega⟩
theorem eqT : Equivariant TimeLocus.sigmaGeo TimeLocus.onLine φT :=
  ⟨fun p => Prod.ext (show 4 * (2 - p.1) - 4 = -(4 * p.1 - 4) by omega) rfl,
   fun p => show 4 * p.1 - 4 = 0 ↔ p.1 = 1 by omega⟩
theorem eqF : Equivariant ForceWitness.fold ForceWitness.onLine φF :=
  ⟨fun _ => rfl, fun _ => Iff.rfl⟩

/-- EVERY MAP KEEPS HEIGHT AND SCALES THE OFFSET from the line by a positive factor. -/
theorem the_maps_keep_height_and_scale :
    (∀ p : Hinge.Pt, φH p = (2 * (p.1 - 2), p.2)) ∧
    (∀ p : ArrowSide.Pt, φA p = (1 * (p.1 - 4), p.2)) ∧
    (∀ (C : ArrowSide.Chart) (p : ArrowSide.Pt), φW C p = (1 * (p.1 - C.W), p.2)) ∧
    (∀ z : PrimeFreedom.Pt, φP z = (4 * (z.x - 1), (z.t : Int))) ∧
    (∀ z : PrimeFreedom.Pt, φP₂ z = (2 * (z.x - 2), (z.t : Int))) ∧
    (∀ (n : Int) (z : PrimeFreedom.Pt), φPn n z = (1 * (z.x - n), (z.t : Int))) ∧
    (∀ p : Int × Int, φT p = (4 * (p.1 - 1), p.2)) ∧
    (∀ p : ForceWitness.Point, φF p = (1 * (p.1 - 0), p.2)) :=
  ⟨fun p => Prod.ext (show 2 * p.1 - 4 = 2 * (p.1 - 2) by omega) rfl,
   fun p => Prod.ext (show p.1 - 4 = 1 * (p.1 - 4) by omega) rfl,
   fun C p => Prod.ext (show p.1 - C.W = 1 * (p.1 - C.W) by omega) rfl,
   fun z => Prod.ext (show 4 * z.x - 4 = 4 * (z.x - 1) by omega) rfl,
   fun z => Prod.ext (show 2 * z.x - 4 = 2 * (z.x - 2) by omega) rfl,
   fun n z => Prod.ext (show z.x - n = 1 * (z.x - n) by omega) rfl,
   fun p => Prod.ext (show 4 * p.1 - 4 = 4 * (p.1 - 1) by omega) rfl,
   fun p => Prod.ext (show p.1 = 1 * (p.1 - 0) by omega) rfl⟩

/-- The first edition's act, carried to the offset chart at the image of its zero set. -/
def actP (A : PrimeFreedom.ActualZeros) : RememberedOffered.ActualZeros :=
  ⟨img φP A.zeros, (transport eqP A.zeros).1 A.fold_closed,
   (RememberedOffered.twins_on_every_world _).mpr ((transport eqP A.zeros).2.mp
    (PrimeFreedom.rh_from_the_act A))⟩
```

```

/-- The first edition's act at every resolution n, carried to the offset chart at the image of its zero set. -/
def actPn (n : Int) (A : PrimeFreedom.ActualZerosAt n) :
    RememberedOffered.ActualZeros :=
  (img (φPn n) A.zeros, (transport (eqPn n) A.zeros).1 A.closed,
   (RememberedOffered.twins_on_every_world _).mpr ((transport (eqPn n) A.zeros).2.mp
     (fun z hz => (PrimeFreedom.foldAt_fixed_iff n z).mp
       (PrimeFreedom.rh_from_the_act_at n A z hz))))
/-- Part IV's act, carried to the offset chart at the image of its zero set. -/
def actH (A : Hinge.ActualZeros) : RememberedOffered.ActualZeros :=
  (img φH A.zeros, (transport eqH A.zeros).1 A.closed,
   (RememberedOffered.twins_on_every_world _).mpr ((transport eqH A.zeros).2.mp
    (Hinge.value_from_the_act A)))
/-- Part IV-b's act is an act of the offset chart as it stands. -/
def actF (A : ForceWitness.ActualZeros) : RememberedOffered.ActualZeros := (A.zeros,
A.closed, A.supply)

/-- The constructed root of Part I, as the root the closing theorems of Part III take. -/
def rootOf {R : Prop} (G : TOE0.SelfGrounding R) : RememberedOffered.SelfGrounding R
    := (G.Act, G.anAct, G.instances)
/-- Part II's self-grounding root, as the root the closing theorems of Part III take.
-/
def rootP {R : Prop} (G : PrimeFreedom.SelfGrounding R) :
    RememberedOffered.SelfGrounding R :=
  (G.Act, G.anAct, G.instances)

/-- THE CHARTS ARE ONE. Every plane chart of the seed maps equivariantly into the
offset chart, at every resolution and every
    width; the value of a configuration is the value of its image on every chart;
    every act type of the seed is an act
    of the offset chart at the image of its zero set; the root read at the zeros on
    Part II's chart is the root read
    twice at the image; and both constructed roots feed the closing theorems of Part
    III: Part I's forces no value,
    and the deed of either is the supply at a zero set exactly where the value holds.
    -/
theorem the_charts_are_one :
    Equivariant Hinge.fold Hinge.onLine φH ∧
    Equivariant (ArrowSide.fold ArrowSide.zetaChart) (ArrowSide.onLine
    ArrowSide.zetaChart) φA ∧
    Equivariant PrimeFreedom.fold PrimeFreedom.onLine φP ∧
    Equivariant PrimeFreedom.fold₂ PrimeFreedom.onLine₂ φP₂ ∧
    (∀ S : Hinge.Pt → Prop, Hinge.Value S ↔ RememberedOffered.Value (img φH S)) ∧
    (∀ S : ArrowSide.Pt → Prop, ArrowSide.Value ArrowSide.zetaChart S ↔
    RememberedOffered.Value (img φA S)) ∧
    (∀ Z : PrimeFreedom.World, PrimeFreedom.RH Z ↔ RememberedOffered.Value (img φP
    Z)) ∧
    (∀ A : PrimeFreedom.ActualZeros, ∃ Z : RememberedOffered.ActualZeros, Z.zeros =
    img φP A.zeros) ∧
    (∀ Z : PrimeFreedom.World, PrimeFreedom.RootAtZeros Z ↔
    RememberedOffered.RootReadTwice (img φP Z)) ∧
    (¬ ∀ S : RememberedOffered.Config, RememberedOffered.Closed S → TOE0.RA₀ →
    RememberedOffered.Value S) ∧
    (∀ S : RememberedOffered.Config, RememberedOffered.Closed S →
      ((TOE0.ra₀.Act → ∃ Z : RememberedOffered.ActualZeros, Z.zeros = S) ↔
      RememberedOffered.Value S)) ∧
    (∀ C : ArrowSide.Chart, Equivariant (ArrowSide.fold C) (ArrowSide.onLine C) (φW
    C)) ∧
    (∀ n : Int, Equivariant (PrimeFreedom.foldAt n) (fun z => z.x = n) (φPn n)) ∧
    Equivariant TimeLocus.sigmaGeo TimeLocus.onLine φT ∧
    Equivariant ForceWitness.fold ForceWitness.onLine φF ∧
    (∀ (C : ArrowSide.Chart) (S : ArrowSide.Pt → Prop),
      ArrowSide.Value C S ↔ RememberedOffered.Value (img (φW C) S)) ∧
    (∀ (n : Int) (A : PrimeFreedom.ActualZerosAt n),
      ∃ Z : RememberedOffered.ActualZeros, Z.zeros = img (φPn n) A.zeros) ∧
    (∀ A : Hinge.ActualZeros, ∃ Z : RememberedOffered.ActualZeros, Z.zeros = img φH
    A.zeros) ∧
    (∀ A : ForceWitness.ActualZeros, ∃ Z : RememberedOffered.ActualZeros, Z.zeros =
    A.zeros) ∧
    (∀ (R : Prop) (G : PrimeFreedom.SelfGrounding R) (S : RememberedOffered.Config),
    RememberedOffered.Closed S →
      (((rootP G).Act → ∃ Z : RememberedOffered.ActualZeros, Z.zeros = S) ↔
      RememberedOffered.Value S)) :=
  ⟨eqH, eqA, eqP, eqP₂,
   fun S => (transport eqH S).2, fun S => (transport eqA S).2, fun Z => (transport
   eqP Z).2,
   fun A => (actP A, rfl),
   fun Z => ((PrimeFreedom.root_at_zeros_is_the_hypothesis Z).trans (transport eqP
   Z).2).trans
     (RememberedOffered.the_root_read_twice_is_the_value _).symm,
   RememberedOffered.the_floor_alone_decides_no_value (rootOf TOE0.ra₀),
   fun S hS => (RememberedOffered.the_last_act (rootOf TOE0.ra₀) S hS).1,
   eqW, eqPn, eqT, eqF, fun C S => (transport (eqW C) S).2,
   fun n A => (actPn n A, rfl), fun A => (actH A, rfl), fun A => (actF A, rfl),
   fun _ G S hS => (RememberedOffered.the_last_act (rootP G) S hS).1⟩

/-- The model pair of the zero side: Re s = 3/4 at height 3·10¹² + 1 on the offset
chart at resolution four (d = 2),
    with its mirror at Re s = 1/4 (d = −2). -/
def thePair : RememberedOffered.Point := (2, 3000000000001)

/-- THE ONE PAIR, READ BY EVERY INSTRUMENT, on the charts that hold it. On the offset
chart it is closed, off the line, of one
    record with its registered point, without the root read twice, and every report
    of it reads no act; its preimage
    on Part IV's chart is centred on the line; its preimage on Part V's chart lies in
    the faithful ζ-shaped world,
    which satisfies every fact of ζ placed on the arrow. -/
theorem the_pair_read_by_every_instrument :
    RememberedOffered.Closed (RememberedOffered.pairWorld thePair) ∧
    ¬ RememberedOffered.Value (RememberedOffered.pairWorld thePair) ∧
    RememberedOffered.SameRecord (RememberedOffered.registered thePair)
    (RememberedOffered.pairWorld thePair) ∧
    ¬ RememberedOffered.RootReadTwice (RememberedOffered.pairWorld thePair) ∧
    (¬ ∃ Z : RememberedOffered.ActualZeros, ∀ p ∈ [thePair, RememberedOffered.fold
    thePair], Z.zeros p) ∧
    (φH (3, 3000000000001) = thePair ∧ φH (1, 3000000000001) = RememberedOffered.fold
    thePair ∧
      Hinge.sumX [(1, 3000000000001), (3, 3000000000001)] = 2 * 2) ∧
    (φA (6, 3000000000001) = thePair ∧ φA (2, 3000000000001) = RememberedOffered.fold
    thePair ∧
      ArrowSide.zetaFaithful ArrowSide.zetaChart 2 3000000000001 (6, 3000000000001) ∧
      ArrowSide.zetaFaithful ArrowSide.zetaChart 2 3000000000001 (2, 3000000000001))
      := by
  have off : ¬ RememberedOffered.onLine thePair := fun h => by
    have h2 : (2 : Int) = 0 := h
    exact absurd h2 (by decide)
  have nv := RememberedOffered.pair_world_lacks_value thePair off
  refine ⟨RememberedOffered.pair_world_closed thePair, nv,
  RememberedOffered.one_record thePair,
    RememberedOffered.the_line_no_contradicts_the_root_read_twice _ nv,
    (RememberedOffered.row_four_from_the_zero_side (RememberedOffered.pairWorld
    thePair)).2.1
    ⟨thePair, RememberedOffered.fold thePair⟩ (thePair, List.Mem.head _, off),
    (by decide, by decide, by decide), (by decide, by decide, ?_, ?_)⟩
  · exact Or.inr (Or.inr (Or.inl (by decide)))
  · exact Or.inr (Or.inl (by decide))

/-- THE BLOCKS AT THE MODEL PAIR: at the pair at height 3·10¹² + 1, which every fact
of ζ placed on the arrow admits,
    the registered world and the pair world leave one record; both readings of the
    halt hold on the first and fail on
    the second; no reading of the record decides the value; every deed is the supply
    at the first and not at the
    second; and the loop closes on the first and stays open on the second. -/
theorem the_blocks_at_the_one_pair :
    RememberedOffered.SameRecord (RememberedOffered.registered thePair)
    (RememberedOffered.pairWorld thePair) ∧
    (RememberedOffered.ZeroReports (RememberedOffered.registered thePair) ∧
      RememberedOffered.PrimeBound (RememberedOffered.registered thePair)) ∧
    (¬ RememberedOffered.ZeroReports (RememberedOffered.pairWorld thePair) ∧
      ¬ RememberedOffered.PrimeBound (RememberedOffered.pairWorld thePair)) ∧
    (∀ g : RememberedOffered.Config → Prop,
      (∀ S S', RememberedOffered.SameRecord S S' → (g S ↔ g S')) →
      ¬ ((g (RememberedOffered.registered thePair) ↔
            RememberedOffered.Value (RememberedOffered.registered thePair)) ∧
         (g (RememberedOffered.pairWorld thePair) ↔
            RememberedOffered.Value (RememberedOffered.pairWorld thePair)))) ∧
    ((TOE0.ra₀.Act → ∃ Z : RememberedOffered.ActualZeros, Z.zeros =
    RememberedOffered.registered thePair) ∧
      ¬ (TOE0.ra₀.Act → ∃ Z : RememberedOffered.ActualZeros, Z.zeros =
      RememberedOffered.pairWorld thePair)) ∧
    ((TOE0.RA₀ ↔ RememberedOffered.RootReadTwice (RememberedOffered.registered
    thePair)) ∧
      ¬ (TOE0.RA₀ ↔ RememberedOffered.RootReadTwice (RememberedOffered.pairWorld
      thePair))) := by
  have off : ¬ RememberedOffered.onLine thePair := fun h => by
    have h2 : (2 : Int) = 0 := h
    exact absurd h2 (by decide)
  have nv := RememberedOffered.pair_world_lacks_value thePair off
  have rv := RememberedOffered.registered_has_value thePair
  have pc := RememberedOffered.pair_world_closed thePair
  have rc : RememberedOffered.Closed (RememberedOffered.registered thePair) := fun s
  hs => by
    rw [hs]
    show RememberedOffered.fold (RememberedOffered.reg thePair) =
    RememberedOffered.reg thePair
    rfl
  have zr : ∀ T : RememberedOffered.Config, RememberedOffered.Closed T →
      (RememberedOffered.ZeroReports T ↔ RememberedOffered.Value T) :=
    fun T hT => (RememberedOffered.row_four_from_the_zero_side T).2.2.2 hT
  have la : ∀ T : RememberedOffered.Config, RememberedOffered.Closed T →
      ((TOE0.ra₀.Act → ∃ Z : RememberedOffered.ActualZeros, Z.zeros = T) ↔
      RememberedOffered.Value T) :=
    fun T hT => (RememberedOffered.the_last_act (rootOf TOE0.ra₀) T hT).1
  have lp : ∀ T : RememberedOffered.Config,
      ((TOE0.RA₀ ↔ RememberedOffered.RootReadTwice T) ↔ RememberedOffered.Value T) :=
    fun T => (RememberedOffered.the_loop (rootOf TOE0.ra₀) T).2.2.2.2.1
  exact ⟨RememberedOffered.one_record thePair,
    ((zr _ rc).mpr rv, (RememberedOffered.prime_side_halts _ rc).mpr rv),
    (fun h => nv ((zr _ pc).mp h), fun h => nv ((RememberedOffered.prime_side_halts _
    pc).mp h)),
    fun g hg (h1, h2) => nv (h2.mp ((hg _ _ (RememberedOffered.one_record
    thePair)).mp (h1.mpr rv))),
    ((la _ rc).mpr rv, fun h => nv ((la _ pc).mp h)),
    ((lp _).mpr rv, fun h => nv ((lp _).mp h))⟩

/-- THE VERIFIED PART TRANSPORTS: at every width, the verification in both
half-planes on Part V's chart is the
    verified part on the offset chart with the height in absolute value. -/
theorem the_verified_part_transports (C : ArrowSide.Chart) (T : Nat) (S :
ArrowSide.Pt → Prop) :
    ArrowSide.RealPartAbs C (T : Int) S ↔
      RHUnicorn.RealPartAt (img (φW C) S) RememberedOffered.onLine
      RememberedOffered.htAbs T := by
  constructor
  · intro h q (p, hp, e) hq
    subst e
    have hq' : (p.2).natAbs ≤ T := hq
    have h1 : p.1 = C.W := h p hp (by omega) (by omega)
    show p.1 - C.W = 0
    omega
  · intro h p hp h1 h2
    have h3 : p.1 - C.W = 0 := h (φW C p) (p, hp, rfl) (show (p.2).natAbs ≤ T by
    omega)
    show p.1 = C.W
    omega

/-- THE FAITHFUL MODEL ON THE OFFSET CHART: its image carries the verified part at
chart height 3·10¹² − 1, every zero
    with |Im s| < 3·10¹², and lacks the value. -/
theorem the_faithful_model_on_the_offset_chart :
    RHUnicorn.RealPartAt (img φA (ArrowSide.zetaFaithful ArrowSide.zetaChart 2
    3000000000001))
      RememberedOffered.onLine RememberedOffered.htAbs 2999999999999 ∧
    ¬ RememberedOffered.Value (img φA (ArrowSide.zetaFaithful ArrowSide.zetaChart 2
    3000000000001)) :=
  ((the_verified_part_transports ArrowSide.zetaChart 2999999999999 _).mp
     ArrowSide.at_zetas_numbers_faithful.2.2.2.2.2.1,
   fun v => ArrowSide.at_zetas_numbers_faithful.2.2.2.2.2.2.2 ((transport eqA
   _).2.mpr v))

/-- ONE REAL PART, ONE OFFSET POINT, AT RESOLUTION FOUR: a real part a/4 read on Part
IV's chart, on Part V's chart at
    width four, on Part II's chart at resolution two, and a real part a/2 read on
    Part II's chart at resolution one
    and on Part IV-c's chart, land at one point of the offset chart at resolution
    four. -/
theorem the_maps_agree_at_resolution_four :
    (∀ a t : Int, φH (a, t) = φA (2 * a, t) ∧ φA (2 * a, t) = φW ArrowSide.zetaChart
    (2 * a, t)) ∧
    (∀ z : PrimeFreedom.Pt, φP₂ z = φH (z.x, (z.t : Int)) ∧ φP z = φH (2 * z.x, (z.t :
    Int))) ∧
```

```
    (∀ x t : Int, φT (x, t) = φH (2 * x, t)) :=
  (fun a t => (Prod.ext (show 2 * a - 4 = 2 * a - 4 from rfl) rfl, rfl),
   fun z => (rfl, Prod.ext (show 4 * z.x - 4 = 2 * (2 * z.x) - 4 by omega) rfl),
   fun x t => Prod.ext (show 4 * x - 4 = 2 * (2 * x) - 4 by omega) rfl)

/-- Conjugation on a chart with heights in ℤ. -/
def conj (p : Int × Int) : Int × Int := (p.1, -p.2)
/-- THE MAPS COMMUTE WITH CONJUGATION on every chart with heights in ℤ; the first edition's chart, with heights in ℕ,
    reads the upper half-plane, and its maps reach only heights at or above zero. -/
theorem the_maps_commute_with_conjugation :
    (∀ p : Hinge.Pt, φH (conj p) = conj (φH p)) ∧ (∀ p : ArrowSide.Pt, φA (conj p) = conj (φA p)) ∧
    (∀ (C : ArrowSide.Chart) (p : ArrowSide.Pt), φW C (conj p) = conj (φW C p)) ∧
    (∀ p : Int × Int, φT (conj p) = conj (φT p)) ∧ (∀ p : ForceWitness.Point, φF (conj p) = conj (φF p)) ∧
    (∀ (n : Int) (z : PrimeFreedom.Pt), 0 ≤ (φPn n z).2) ∧ (∀ z : PrimeFreedom.Pt, 0 ≤ (φP z).2) ∧
    (∀ z : PrimeFreedom.Pt, 0 ≤ (φP₂ z).2) :=
  (fun _ => rfl, fun _ => rfl, fun _ _ => rfl, fun _ => rfl, fun _ => rfl,
   fun _ z => Int.ofNat_nonneg z.t, fun z => Int.ofNat_nonneg z.t, fun z =>
    Int.ofNat_nonneg z.t)

/-! ## The reading at every resolution -/

/-- The open chart strip at resolution n: a reading inside the open strip 0 < Re s < 1 is kept at 1 ≤ x ≤ 2n − 1. -/
def clampStrip (n x : Int) : Int := max 1 (min (2 * n - 1) x)
/-- THE CLAMP KEEPS THE OPEN STRIP, COMMUTES WITH THE FOLD, AND KEEPS THE SIDE: at every resolution n ≥ 1 the clamped
    reading lies in the open chart strip; the clamp commutes with x ↦ 2n − x; and at every resolution n ≥ 2 it lands
    on the line exactly when the rounded reading does. -/
theorem the_clamp_keeps_strip_fold_and_side :
    (∀ n x : Int, 1 ≤ n → 1 ≤ clampStrip n x ∧ clampStrip n x ≤ 2 * n - 1) ∧
    (∀ n x : Int, 1 ≤ n → clampStrip n (2 * n - x) = 2 * n - clampStrip n x) ∧
    (∀ n x : Int, 2 ≤ n → (clampStrip n x = n ↔ x = n)) :=
  (fun n x _ => by unfold clampStrip; omega, fun n x _ => by unfold clampStrip; omega,
   fun n x _ => by unfold clampStrip; omega)

/-- Rounding half to even of a / b, for b > 0. -/
def roundHalfEven (a b : Int) : Int :=
  let q := a / b
  let r := a % b
  if 2 * r < b then q else if 2 * r > b then q + 1 else if q % 2 = 0 then q else q + 1
/-- THE READER'S RULE on the offset chart at resolution n ≥ 1: a real part σ = a / b of the open strip is read at
    x = round(2n·σ), rounded half to even and kept in the open chart strip, and at d = x − n. -/
def readAt (n : Nat) (a b : Int) : Int := clampStrip n (roundHalfEven (2 * n * a) b) - n

/-- ONE RESOLUTION IS NOT ENOUGH: a zero at Re s = 51/100 and its mirror at 49/100 read onto the line at resolution
    four and off it at resolution fifty; the pair at Re s = 1/4 and 3/4 reads at d = ∓2 at resolution four; and a
    zero at Re s = 97/100 or 3/100 is kept off the poles, at d = ±3. -/
theorem one_resolution_is_not_enough :
    readAt 4 51 100 = 0 ∧ readAt 4 49 100 = 0 ∧ readAt 50 51 100 = 1 ∧ readAt 50 49 100 = -1 ∧
    readAt 4 1 4 = -2 ∧ readAt 4 3 4 = 2 ∧ readAt 4 97 100 = 3 ∧ readAt 4 3 100 = -3 := by decide

/-- A zero at Re s = 51/100 with its mirror at 49/100, at height 3·10¹² + 1, read at resolution n. -/
def nearWorld (n : Nat) : RememberedOffered.Config := fun q =>
  q = (readAt n 51 100, 3000000000001) ∨ q = (readAt n 49 100, 3000000000001)

/-- THE VALUE AT ONE RESOLUTION DOES NOT DECIDE IT AT A FINER ONE: read at resolution four the near pair is closed and
    has the value; read at resolution fifty it is closed and lacks it. -/
theorem one_resolution_does_not_decide_the_next :
    RememberedOffered.Closed (nearWorld 4) ∧ RememberedOffered.Value (nearWorld 4) ∧
    RememberedOffered.Closed (nearWorld 50) ∧ ¬ RememberedOffered.Value (nearWorld 50) := by
  obtain (e1, e2, e3, e4, _, _, _, _) := one_resolution_is_not_enough
  refine (fun q hq => ?_, fun q hq => ?_, fun q hq => ?_, fun v => ?_)
  · unfold nearWorld at hq ⊢
    rw [e1, e2] at hq ⊢
    rcases hq with h | h <;> (subst h; exact Or.inl (by decide))
  · unfold nearWorld at hq
    rw [e1, e2] at hq
    rcases hq with h | h <;> (subst h; rfl)
  · unfold nearWorld at hq ⊢
    rw [e3, e4] at hq ⊢
    rcases hq with h | h
    · subst h; exact Or.inr (by decide)
    · subst h; exact Or.inl (by decide)
  · have h : (1 : Int) = 0 := v (1, 3000000000001) (by unfold nearWorld; rw [e3]; exact Or.inl rfl)
    exact absurd h (by decide)

/-- THE ACT AT EVERY RESOLUTION: a family of readings of the offset chart, one at each resolution, each closed under
    the fold, with least erasure supplied at every resolution. The zero set of ζ read by the reader's rule at every
    resolution n ≥ 1 is such a family by the reading of the paper's Section 11; resolution zero is no reading, and the
    family's term there is the empty configuration by stipulation. -/
structure ActualZerosEvery where
  zeros : Nat → RememberedOffered.Config
  closed : ∀ n, RememberedOffered.Closed (zeros n)
  supply : ∀ n, RememberedOffered.LeastErasure (zeros n)

/-- The act at every resolution is an act of the offset chart at each one. -/
def ActualZerosEvery.atRes (Z : ActualZerosEvery) (n : Nat) :
    RememberedOffered.ActualZeros :=
  (Z.zeros n, Z.closed n, Z.supply n)

/-- THE VALUE AT EVERY RESOLUTION, ON NO AXIOM: on the act at every resolution, every reading has the value. -/
theorem the_value_at_every_resolution (Z : ActualZerosEvery) (n : Nat) :
    RememberedOffered.Value (Z.zeros n) :=
  RememberedOffered.value_from_the_act (Z.atRes n)

/-- THE ACT AT EVERY RESOLUTION, WHOLE: the act stands at the readings exactly where the value holds at every
    resolution; on it, at every resolution, the value, the zero reports and the prime bound hold; every proof of the
    value at every resolution, from any premise, is a supply of the act; the supply is unique; and the atomic proof,
    the atomic necessity and the two-sided halt hold at every resolution. -/
theorem the_act_at_every_resolution (R : Nat → RememberedOffered.Config)
    (hR : ∀ n, RememberedOffered.Closed (R n)) :
    ((∃ Z : ActualZerosEvery, Z.zeros = R) ↔ ∀ n, RememberedOffered.Value (R n)) ∧
    (∀ (Z : ActualZerosEvery) (n : Nat), RememberedOffered.Value (Z.zeros n) ∧
      RememberedOffered.ZeroReports (Z.zeros n) ∧ RememberedOffered.PrimeBound (Z.zeros n)) ∧
    (∀ Q : Prop, (Q → ∀ n, RememberedOffered.Value (R n)) → Q → ∃ Z : ActualZerosEvery, Z.zeros = R) ∧
    (∀ Z₁ Z₂ : ActualZerosEvery, Z₁.zeros = R → Z₂.zeros = R → Z₁ = Z₂) ∧
    (∀ n, type_of% (RememberedOffered.the_atomic_proof (rootOf TOE0.ra₀) (R n) (hR n))) ∧
    (∀ n, type_of% (RememberedOffered.the_atomic_necessity (R n) (hR n))) ∧
    (∀ n, type_of% (RememberedOffered.bidirectional_halted_uniduction (R n) (hR n))) := by
  have mk : (∀ n, RememberedOffered.Value (R n)) → ∃ Z : ActualZerosEvery, Z.zeros = R := fun v =>
    ((R, hR, fun n => (RememberedOffered.twins_on_every_world (R n)).mpr (v n)), rfl)
  refine ((fun (Z, hZ) n => by rw [← hZ]; exact RememberedOffered.value_from_the_act (Z.atRes n)), mk),
    fun Z n => (RememberedOffered.value_from_the_act (Z.atRes n),
      (RememberedOffered.bidirectional_halted_uniduction _ (Z.closed n)).2.2.2.2.2
      (Z.atRes n)),
    fun _ hQ q => mk (hQ q), ?_,
    fun n => RememberedOffered.the_atomic_proof (rootOf TOE0.ra₀) (R n) (hR n),
    fun n => RememberedOffered.the_atomic_necessity (R n) (hR n),
    fun n => RememberedOffered.bidirectional_halted_uniduction (R n) (hR n))
  intro Z₁ Z₂ h₁ h₂
  obtain (z₁, c₁, s₁) := Z₁
  obtain (z₂, c₂, s₂) := Z₂
  change z₁ = R at h₁
  change z₂ = R at h₂
  subst h₁
  subst h₂
  rfl

/-- THE PRIME BOUND AT ONE RESOLUTION IS WEAKER: the near pair at Re s = 51/100 meets the prime bound read at
    resolution four and fails it read at resolution fifty; at one resolution n the chart's prime bound reads a zero
    within 1/(4n) of the line onto it. -/
theorem the_prime_bound_at_one_resolution :
    RememberedOffered.PrimeBound (nearWorld 4) ∧ ¬ RememberedOffered.PrimeBound (nearWorld 50) := by
  have h := one_resolution_does_not_decide_the_next
  exact ((RememberedOffered.prime_side_halts _ h.1).mpr h.2.1,
    fun b => h.2.2.2 ((RememberedOffered.prime_side_halts _ h.2.2.1).mp b))

/-- THE HALT AT EVERY RESOLUTION: for every family of reflection-closed readings, the zero reports at every resolution,
    the prime bound at every resolution and the value at every resolution are one proposition. The prime bound at
    every resolution together is the chart's image of the cited bound at x^(1/2 + ε). -/
theorem the_halt_at_every_resolution (R : Nat → RememberedOffered.Config)
    (hR : ∀ n, RememberedOffered.Closed (R n)) :
    ((∀ n, RememberedOffered.ZeroReports (R n)) ↔ ∀ n, RememberedOffered.Value (R n)) ∧
    ((∀ n, RememberedOffered.PrimeBound (R n)) ↔ ∀ n, RememberedOffered.Value (R n)) ∧
    ((∀ n, RememberedOffered.ZeroReports (R n)) ↔ ∀ n, RememberedOffered.PrimeBound (R n)) := by
  have z := fun n => (RememberedOffered.bidirectional_halted_uniduction (R n) (hR n)).1
  have p := fun n => (RememberedOffered.bidirectional_halted_uniduction (R n) (hR n)).2.1
  refine ((fun h n => (z n).mp (h n), fun h n => (z n).mpr (h n)),
    (fun h n => (p n).mp (h n), fun h n => (p n).mpr (h n)),
    (fun h n => (p n).mpr ((z n).mp (h n)), fun h n => (z n).mpr ((p n).mp (h n))))

end Charts

end PartVb

/-! # PART VI · THE TWO-SIDED CLOSURE -/
section PartVI
namespace BothSides

/-- THE TWO-SIDED CLOSURE. One theorem, every capstone of the seed bound by its exact type.
    I    the floor, on no axiom: the root holds for every self-grounding root; the Root Axiom on its constructed
         domain; the master seal of the three axes; the line is the fixed set of conjugation.
    II   the arrow: the only rigid reversal of the two poles; the freedom cut, the line blind to the arrow's sign;
         the hinge at Re s = 1/2; the fold's fixed set is the line.
    III  the prime side: the primes admit every assignment; prime freedom forces nothing; the prime bound halts
         at the value; the ζ-specific facts on the arrow, their test and their reach at the ends.
    IV   the non-trivial-zero side: the zero set's own centre is the line; a centred pair off it; row four read
         from the zeros.
    V    the nine rows: the form; the open leg; the blind record; the premise forced, the act, the weakest
         forcing premise; the barred refuter; the terminal saturation; the capstone; the annihilating timeless
         closure and the one; the atomic form forced.
    VI   the termination: the bidirectional halted uniduction; the atomic proof; the last act; least erasure and
         least escape; the loop.
    VII  the run: a run witnesses that it ran and leaves the value free; a run's flag offered as the field at every
         closed configuration is refused; beside the field, the run is witnessed and the value stands on the field.
    VIII the charts are one; the one model pair read by every instrument; the faithful model of ζ's zeros; the hinge
         exists; both values of the bit are atomic.
    IX   further capstones and row mechanisms of Parts II, III, IV, IV-b and IV-c.
    X    every further theorem the body of the paper cites, generated from the body's citations: with I to IX, the
         closure binds every theorem the body cites. -/
theorem the_two_sided_closure :
```

```
    -- I · the floor
    (type_of% @TOE0.the_floor_is_universal) ∧ (type_of%
    @TOE0.root_on_the_constructed_domain) ∧
    (type_of% @TOE0.the_master_seal) ∧ (type_of% @TOE0.the_line_is_the_fixed_set) ∧
    -- II · the arrow
    (type_of% @Hinge.the_only_rigid_reversal) ∧ (type_of% @Hinge.hinge_sign_blind) ∧
    (type_of% @Hinge.zeta_hinge) ∧ (type_of% @Hinge.locus) ∧
    -- III · the prime side
    (type_of% @PrimeFreedom.primes_admit_every_assignment) ∧ (type_of%
    @PrimeFreedom.prime_freedom_forces_nothing) ∧
    (type_of% @RememberedOffered.prime_side_halts) ∧ (type_of%
    @ArrowSide.arrow_side_test) ∧
    (type_of% @ArrowSide.beyond_the_head_breaks_ends) ∧ (type_of%
    @ArrowSide.at_zetas_numbers) ∧
    -- IV · the non-trivial-zero side
    (type_of% @Hinge.centre_is_the_line) ∧ (type_of% @Hinge.centred_yet_off) ∧
    (type_of% @RememberedOffered.row_four_from_the_zero_side) ∧
    -- V · the nine rows
    (type_of% @PrimeFreedom.least_erasure_is_the_value) ∧ (type_of%
    @PrimeFreedom.keyless_forces_nothing) ∧
    (type_of% @PrimeFreedom.record_decides_nothing) ∧ (type_of%
    @PrimeFreedom.rh_from_the_act) ∧
    (type_of% @PrimeFreedom.rh_is_the_weakest_forcing_premise) ∧ (type_of%
    @PrimeFreedom.the_tenth_is_barred_by_the_act) ∧
    (type_of% @PrimeFreedom.nothing_left_open_on_the_act) ∧ (type_of%
    @PrimeFreedom.the_capstone) ∧
    (type_of% @RememberedOffered.the_annihilation_closure) ∧ (type_of%
    @RememberedOffered.the_one) ∧
    (type_of% @RememberedOffered.the_atomic_necessity) ∧
    -- VI · the termination
    (type_of% @RememberedOffered.bidirectional_halted_uniduction) ∧ (type_of%
    @RememberedOffered.the_atomic_proof) ∧
    (type_of% @RememberedOffered.the_last_act) ∧ (type_of%
    @RememberedOffered.least_erasure_and_least_escape) ∧
    (type_of% @RememberedOffered.the_loop) ∧
    -- VII · the run
    (type_of% @ForceWitness.force_witness_closure) ∧ (type_of%
    @ForceWitness.the_plug_fails) ∧
    (type_of% @ForceWitness.the_plug_delivers) ∧
    -- VIII · the charts, the pair and the faithful model
    (type_of% @Charts.the_charts_are_one) ∧ (type_of%
    @Charts.the_pair_read_by_every_instrument) ∧
    (type_of% @ArrowSide.at_zetas_numbers_faithful) ∧ (type_of% @Hinge.hinge_exists)
    ∧
    (type_of% @RememberedOffered.both_values_atomic) ∧
    -- IX · every further capstone and row mechanism the paper cites
    (type_of% @PrimeFreedom.vocabulary_law) ∧ (type_of% @PrimeFreedom.the_front) ∧
    (type_of% @PrimeFreedom.posit_is_the_value) ∧ (type_of%
    @PrimeFreedom.every_face_proves_every_face) ∧
    (type_of% @PrimeFreedom.keyless_forces_nothing₂) ∧ (type_of%
    @PrimeFreedom.no_reading_decides_in_the_strip) ∧
    (type_of% @PrimeFreedom.the_tenth_is_the_refuter) ∧ (type_of%
    @PrimeFreedom.reader_frame) ∧
    (type_of% @RememberedOffered.the_timeless_zone_closed) ∧ (type_of%
    @RememberedOffered.the_unicorn_contained) ∧
    (type_of% @RememberedOffered.unicorn_blocked_on_the_chart) ∧ (type_of%
    @RememberedOffered.flowed_record_forgets) ∧
    (type_of% @RememberedOffered.reality_transported) ∧ (type_of%
    @RememberedOffered.upstream_is_not_forced) ∧
    (type_of% @RememberedOffered.the_deed_is_not_the_supply) ∧ (type_of%
    @RememberedOffered.floor_is_not_least_erasure) ∧
    (type_of% @ForceWitness.force_witness_guarded) ∧ (type_of%
    @Hinge.arrow_gives_line_not_value) ∧
    (type_of% @Judge.identical_locus_does_not_exclude) ∧ (type_of%
    @Judge.the_seed_is_exactly_what_binds) ∧
    (type_of% @TimeLocus.time_does_not_bind) ∧
    -- X · every further theorem the body of the paper cites
    (type_of% @Hinge.the_line_off_the_arrow) ∧ (type_of%
    @RememberedOffered.no_closed_principle_decides) ∧
    (type_of% @Hinge.keyless_forces_nothing) ∧ (type_of%
    @ArrowSide.faithful_arrow_side_test) ∧
    (type_of% @Charts.the_act_at_every_resolution) ∧ (type_of%
    @PrimeFreedom.independence_forces_truth) ∧
    (type_of% @Charts.the_blocks_at_the_one_pair) ∧ (type_of%
    @RememberedOffered.twins_on_every_world) ∧
    (type_of% @ArrowSide.faithful_every_margin) ∧ (type_of%
    @RememberedOffered.the_unicorn_contained_abs) ∧
    (type_of% @RememberedOffered.the_form_is_the_hypothesis) ∧ (type_of%
    @RememberedOffered.line_no_has_a_world) ∧
    (type_of% @RememberedOffered.tongue_no_has_no_world) ∧ (type_of%
    @Charts.the_value_at_every_resolution) ∧
    (type_of% @TOE0.denial_reenacts_root) ∧ (type_of%
    @PrimeFreedom.denial_reenacts_root) ∧
    (type_of% @RememberedOffered.denial_reenacts_root) ∧ (type_of%
    @TOE0.no_level_above) ∧
    (type_of% @PrimeFreedom.root_at_zeros_is_least_erasure) ∧ (type_of%
    @RememberedOffered.the_root_read_twice_is_the_value) ∧
    (type_of% @RememberedOffered.monism_witness_is_the_claim) ∧ (type_of%
    @RememberedOffered.the_floor_alone_decides_no_value) ∧
    (type_of% @RememberedOffered.merging_at_a_world_is_the_supply) ∧ (type_of%
    @TOE0.twenty_four_units_twelve_gates) ∧
    (type_of% @TOE0.the_shell_splits_twelve_and_twelve) ∧ (type_of%
    @Charts.the_maps_keep_height_and_scale) ∧
    (type_of% @Charts.the_maps_agree_at_resolution_four) ∧ (type_of%
    @Charts.the_maps_commute_with_conjugation) ∧
    (type_of% @Charts.transport) ∧ (type_of% @Charts.one_resolution_is_not_enough) ∧
    (type_of% @Charts.one_resolution_does_not_decide_the_next) ∧ (type_of%
    @Hinge.hinge) ∧
    (type_of% @Hinge.hinge_unique) ∧ (type_of% @Hinge.hinge_iff_even) ∧
    (type_of% @Hinge.centre_on_every_extension) ∧ (type_of%
    @Hinge.the_point_reflection_reads_the_same_line) ∧
    (type_of% @Hinge.fold_is_the_height_keeping_extension) ∧ (type_of%
    @PrimeFreedom.liouville_is_the_sign_arrow) ∧
    (type_of% @ForceWitness.record_decides_nothing) ∧ (type_of%
    @PrimeFreedom.open_strip_forces_at_resolution_one) ∧
    (type_of% @ArrowSide.an_off_line_zero_comes_in_four) ∧ (type_of%
    @ArrowSide.at_width_one_the_ends_are_the_value) ∧
    (type_of% @Charts.the_halt_at_every_resolution) ∧ (type_of%
    @Charts.the_prime_bound_at_one_resolution) ∧
    (type_of% @RememberedOffered.price_zero_iff_value) ∧ (type_of%
    @Hinge.centre_of_a_closed_family) ∧
    (type_of% @RememberedOffered.two_doors) ∧ (type_of%
    @RememberedOffered.doors_exclusive) ∧
    (type_of% @RememberedOffered.the_false_world_carries_the_floor_and_no_monism) ∧
    (type_of% @RememberedOffered.one_record) ∧
    (type_of% @ForceWitness.one_record) ∧ (type_of%
    @RememberedOffered.price_counts_pairs) ∧
    (type_of% @RememberedOffered.monism_is_the_sole_witness) ∧ (type_of%
    @Judge.identical_locus_inside_the_strip_does_not_exclude) ∧
    (type_of% @PrimeFreedom.least_erasure_unconditional) ∧ (type_of%
    @RememberedOffered.four_names_one_proposition) ∧
    (type_of% @PrimeFreedom.unicorn_block) ∧ (type_of% @RHUnicorn.unicorn_block) ∧
    (type_of% @PrimeFreedom.the_witness_forced_by_the_act) ∧ (type_of%
    @PrimeFreedom.two_denials) ∧
    (type_of% @RememberedOffered.two_denials) ∧ (type_of%
    @RememberedOffered.no_arrival_off_the_line_on_the_act) ∧
    (type_of% @RememberedOffered.on_the_act_the_line_no_is_refuted) ∧ (type_of%
    @RememberedOffered.the_unconditional_route_is_blocked) ∧
    (type_of% @RememberedOffered.accepting_rh_forces_the_atomic_proof) ∧ (type_of%
    @RememberedOffered.band_does_not_force) ∧
    (type_of% @RememberedOffered.band_zero_is_value) ∧ (type_of%
    @RememberedOffered.the_form_of_a_field) ∧
    (type_of% @RememberedOffered.premise_trichotomy) ∧ (type_of%
    @Charts.the_clamp_keeps_strip_fold_and_side) ∧
    (type_of% @PrimeFreedom.unicorn_never_registered) ∧ (type_of%
    @PrimeFreedom.round_trip_identity) ∧
    (type_of% @PrimeFreedom.trip_adds_presence_only) ∧ (type_of%
    @PrimeFreedom.massless_arrow) ∧
    (type_of% @PrimeFreedom.no_coalition_decides) :=
(@TOE0.the_floor_is_universal, @TOE0.root_on_the_constructed_domain,
 @TOE0.the_master_seal,
 @TOE0.the_line_is_the_fixed_set,
 @Hinge.the_only_rigid_reversal, @Hinge.hinge_sign_blind, @Hinge.zeta_hinge,
 @Hinge.locus,
 @PrimeFreedom.primes_admit_every_assignment,
 @PrimeFreedom.prime_freedom_forces_nothing,
 @RememberedOffered.prime_side_halts, @ArrowSide.arrow_side_test,
 @ArrowSide.beyond_the_head_breaks_ends,
 @ArrowSide.at_zetas_numbers,
 @Hinge.centre_is_the_line, @Hinge.centred_yet_off,
 @RememberedOffered.row_four_from_the_zero_side,
 @PrimeFreedom.least_erasure_is_the_value, @PrimeFreedom.keyless_forces_nothing,
 @PrimeFreedom.record_decides_nothing, @PrimeFreedom.rh_from_the_act,
 @PrimeFreedom.rh_is_the_weakest_forcing_premise,
 @PrimeFreedom.the_tenth_is_barred_by_the_act,
 @PrimeFreedom.nothing_left_open_on_the_act, @PrimeFreedom.the_capstone,
 @RememberedOffered.the_annihilation_closure, @RememberedOffered.the_one,
 @RememberedOffered.the_atomic_necessity,
 @RememberedOffered.bidirectional_halted_uniduction,
 @RememberedOffered.the_atomic_proof,
 @RememberedOffered.the_last_act,
 @RememberedOffered.least_erasure_and_least_escape,
 @RememberedOffered.the_loop,
 @ForceWitness.force_witness_closure, @ForceWitness.the_plug_fails,
 @ForceWitness.the_plug_delivers,
 @Charts.the_charts_are_one, @Charts.the_pair_read_by_every_instrument,
 @ArrowSide.at_zetas_numbers_faithful,
 @Hinge.hinge_exists, @RememberedOffered.both_values_atomic,
 @PrimeFreedom.vocabulary_law, @PrimeFreedom.the_front,
 @PrimeFreedom.posit_is_the_value,
 @PrimeFreedom.every_face_proves_every_face, @PrimeFreedom.keyless_forces_nothing₂,
 @PrimeFreedom.no_reading_decides_in_the_strip,
 @PrimeFreedom.the_tenth_is_the_refuter, @PrimeFreedom.reader_frame,
 @RememberedOffered.the_timeless_zone_closed,
 @RememberedOffered.the_unicorn_contained,
 @RememberedOffered.unicorn_blocked_on_the_chart,
 @RememberedOffered.flowed_record_forgets,
 @RememberedOffered.reality_transported, @RememberedOffered.upstream_is_not_forced,
 @RememberedOffered.the_deed_is_not_the_supply,
 @RememberedOffered.floor_is_not_least_erasure,
 @ForceWitness.force_witness_guarded, @Hinge.arrow_gives_line_not_value,
 @Judge.identical_locus_does_not_exclude, @Judge.the_seed_is_exactly_what_binds,
 @TimeLocus.time_does_not_bind,
 @Hinge.the_line_off_the_arrow, @RememberedOffered.no_closed_principle_decides,
 @Hinge.keyless_forces_nothing,
 @ArrowSide.faithful_arrow_side_test, @Charts.the_act_at_every_resolution,
 @PrimeFreedom.independence_forces_truth,
 @Charts.the_blocks_at_the_one_pair, @RememberedOffered.twins_on_every_world,
 @ArrowSide.faithful_every_margin,
 @RememberedOffered.the_unicorn_contained_abs,
 @RememberedOffered.the_form_is_the_hypothesis,
 @RememberedOffered.line_no_has_a_world,
 @RememberedOffered.tongue_no_has_no_world, @Charts.the_value_at_every_resolution,
 @TOE0.denial_reenacts_root,
 @PrimeFreedom.denial_reenacts_root, @RememberedOffered.denial_reenacts_root,
 @TOE0.no_level_above,
 @PrimeFreedom.root_at_zeros_is_least_erasure,
 @RememberedOffered.the_root_read_twice_is_the_value,
 @RememberedOffered.monism_witness_is_the_claim,
 @RememberedOffered.the_floor_alone_decides_no_value,
 @RememberedOffered.merging_at_a_world_is_the_supply,
 @TOE0.twenty_four_units_twelve_gates,
 @TOE0.the_shell_splits_twelve_and_twelve, @Charts.the_maps_keep_height_and_scale,
 @Charts.the_maps_agree_at_resolution_four,
 @Charts.the_maps_commute_with_conjugation, @Charts.transport,
 @Charts.one_resolution_is_not_enough,
 @Charts.one_resolution_does_not_decide_the_next, @Hinge.hinge,
 @Hinge.hinge_unique,
 @Hinge.hinge_iff_even, @Hinge.centre_on_every_extension,
 @Hinge.the_point_reflection_reads_the_same_line,
 @Hinge.fold_is_the_height_keeping_extension,
 @PrimeFreedom.liouville_is_the_sign_arrow, @ForceWitness.record_decides_nothing,
 @PrimeFreedom.open_strip_forces_at_resolution_one,
 @ArrowSide.an_off_line_zero_comes_in_four,
 @ArrowSide.at_width_one_the_ends_are_the_value,
 @Charts.the_halt_at_every_resolution, @Charts.the_prime_bound_at_one_resolution,
 @RememberedOffered.price_zero_iff_value,
 @Hinge.centre_of_a_closed_family, @RememberedOffered.two_doors,
 @RememberedOffered.doors_exclusive,
 @RememberedOffered.the_false_world_carries_the_floor_and_no_monism,
 @RememberedOffered.one_record, @ForceWitness.one_record,
 @RememberedOffered.price_counts_pairs,
 @RememberedOffered.monism_is_the_sole_witness,
 @Judge.identical_locus_inside_the_strip_does_not_exclude,
 @PrimeFreedom.least_erasure_unconditional,
 @RememberedOffered.four_names_one_proposition, @PrimeFreedom.unicorn_block,
 @RHUnicorn.unicorn_block, @PrimeFreedom.the_witness_forced_by_the_act,
 @PrimeFreedom.two_denials,
 @RememberedOffered.two_denials,
 @RememberedOffered.no_arrival_off_the_line_on_the_act,
 @RememberedOffered.on_the_act_the_line_no_is_refuted,
 @RememberedOffered.the_unconditional_route_is_blocked,
 @RememberedOffered.accepting_rh_forces_the_atomic_proof,
 @RememberedOffered.band_does_not_force,
 @RememberedOffered.band_zero_is_value, @RememberedOffered.the_form_of_a_field,
 @RememberedOffered.premise_trichotomy,
 @Charts.the_clamp_keeps_strip_fold_and_side,
 @PrimeFreedom.unicorn_never_registered, @PrimeFreedom.round_trip_identity,
```

```
    @PrimeFreedom.trip_adds_presence_only, @PrimeFreedom.massless_arrow,
    @PrimeFreedom.no_coalition_decides)

end BothSides
end PartVI

/-! # The cones of Parts IV to VI -/
/-- info: 'ArrowSide.an_off_line_zero_comes_in_four' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.an_off_line_zero_comes_in_four
/-- info: 'ArrowSide.arrow_side_test' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.arrow_side_test
/-- info: 'ArrowSide.at_width_one_the_ends_are_the_value' depends on axioms:
 [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.at_width_one_the_ends_are_the_value
/-- info: 'ArrowSide.at_zetas_numbers' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.at_zetas_numbers
/-- info: 'ArrowSide.at_zetas_numbers_faithful' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.at_zetas_numbers_faithful
/-- info: 'ArrowSide.beyond_the_head_breaks_ends' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.beyond_the_head_breaks_ends
/-- info: 'ArrowSide.faithful_arrow_side_test' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.faithful_arrow_side_test
/-- info: 'ArrowSide.faithful_every_margin' depends on axioms: [propext, Quot.sound]
 -/
#guard_msgs in #print axioms ArrowSide.faithful_every_margin
/-- info: 'ArrowSide.shaped_closed' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.shaped_closed
/-- info: 'ArrowSide.shaped_ends' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.shaped_ends
/-- info: 'ArrowSide.shaped_finitely_off' does not depend on any axioms -/
#guard_msgs in #print axioms ArrowSide.shaped_finitely_off
/-- info: 'ArrowSide.shaped_lacks_value' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.shaped_lacks_value
/-- info: 'ArrowSide.shaped_real_part' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.shaped_real_part
/-- info: 'ArrowSide.shaped_zero_free' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms ArrowSide.shaped_zero_free
/-- info: 'BothSides.the_two_sided_closure' depends on axioms: [propext,
 Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms BothSides.the_two_sided_closure
/-- info: 'Charts.eqA' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.eqA
/-- info: 'Charts.eqF' does not depend on any axioms -/
#guard_msgs in #print axioms Charts.eqF
/-- info: 'Charts.eqH' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.eqH
/-- info: 'Charts.eqP' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.eqP
/-- info: 'Charts.eqPn' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.eqPn
/-- info: 'Charts.eqP₂' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.eqP₂
/-- info: 'Charts.eqT' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.eqT
/-- info: 'Charts.eqW' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.eqW
/-- info: 'Charts.one_resolution_does_not_decide_the_next' does not depend on any
 axioms -/
#guard_msgs in #print axioms Charts.one_resolution_does_not_decide_the_next
/-- info: 'Charts.one_resolution_is_not_enough' does not depend on any axioms -/
#guard_msgs in #print axioms Charts.one_resolution_is_not_enough
/-- info: 'Charts.the_act_at_every_resolution' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms Charts.the_act_at_every_resolution
/-- info: 'Charts.the_blocks_at_the_one_pair' depends on axioms: [propext,
 Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.the_blocks_at_the_one_pair
/-- info: 'Charts.the_charts_are_one' depends on axioms: [propext, Classical.choice,
 Quot.sound] -/
#guard_msgs in #print axioms Charts.the_charts_are_one
/-- info: 'Charts.the_clamp_keeps_strip_fold_and_side' depends on axioms: [propext,
 Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.the_clamp_keeps_strip_fold_and_side
/-- info: 'Charts.the_faithful_model_on_the_offset_chart' depends on axioms:
 [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Charts.the_faithful_model_on_the_offset_chart
/-- info: 'Charts.the_halt_at_every_resolution' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms Charts.the_halt_at_every_resolution
/-- info: 'Charts.the_maps_agree_at_resolution_four' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms Charts.the_maps_agree_at_resolution_four
/-- info: 'Charts.the_maps_commute_with_conjugation' does not depend on any axioms -/
#guard_msgs in #print axioms Charts.the_maps_commute_with_conjugation
/-- info: 'Charts.the_maps_keep_height_and_scale' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms Charts.the_maps_keep_height_and_scale
/-- info: 'Charts.the_pair_read_by_every_instrument' does not depend on any axioms -/
#guard_msgs in #print axioms Charts.the_pair_read_by_every_instrument
/-- info: 'Charts.the_prime_bound_at_one_resolution' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms Charts.the_prime_bound_at_one_resolution
/-- info: 'Charts.the_value_at_every_resolution' does not depend on any axioms -/
#guard_msgs in #print axioms Charts.the_value_at_every_resolution
/-- info: 'Charts.the_verified_part_transports' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms Charts.the_verified_part_transports
/-- info: 'Charts.transport' does not depend on any axioms -/
#guard_msgs in #print axioms Charts.transport
/-- info: 'ForceWitness.the_plug_delivers' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.the_plug_delivers
/-- info: 'ForceWitness.the_plug_fails' does not depend on any axioms -/
#guard_msgs in #print axioms ForceWitness.the_plug_fails
/-- info: 'Hinge.arrow_gives_line_not_value' depends on axioms: [propext,
 Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Hinge.arrow_gives_line_not_value
/-- info: 'Hinge.centre_is_the_line' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.centre_is_the_line
/-- info: 'Hinge.centre_of_a_closed_family' depends on axioms: [propext, Quot.sound]
 -/
#guard_msgs in #print axioms Hinge.centre_of_a_closed_family
/-- info: 'Hinge.centre_on_every_extension' depends on axioms: [propext, Quot.sound]
 -/
#guard_msgs in #print axioms Hinge.centre_on_every_extension
/-- info: 'Hinge.centred_yet_off' does not depend on any axioms -/
#guard_msgs in #print axioms Hinge.centred_yet_off
/-- info: 'Hinge.fold_is_the_height_keeping_extension' does not depend on any axioms
 -/
#guard_msgs in #print axioms Hinge.fold_is_the_height_keeping_extension
/-- info: 'Hinge.fold_keeps_height' does not depend on any axioms -/
#guard_msgs in #print axioms Hinge.fold_keeps_height
/-- info: 'Hinge.hinge' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Hinge.hinge
/-- info: 'Hinge.hinge_exists' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.hinge_exists
/-- info: 'Hinge.hinge_iff_even' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.hinge_iff_even
/-- info: 'Hinge.hinge_sign_blind' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.hinge_sign_blind
/-- info: 'Hinge.hinge_unique' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.hinge_unique
/-- info: 'Hinge.keyless_forces_nothing' does not depend on any axioms -/
#guard_msgs in #print axioms Hinge.keyless_forces_nothing
/-- info: 'Hinge.least_erasure_iff_value' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.least_erasure_iff_value
/-- info: 'Hinge.locus' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.locus
/-- info: 'Hinge.off_line_leans' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.off_line_leans
/-- info: 'Hinge.pair_closed' does not depend on any axioms -/
#guard_msgs in #print axioms Hinge.pair_closed
/-- info: 'Hinge.pair_in_strip' does not depend on any axioms -/
#guard_msgs in #print axioms Hinge.pair_in_strip
/-- info: 'Hinge.pair_lacks_value' does not depend on any axioms -/
#guard_msgs in #print axioms Hinge.pair_lacks_value
/-- info: 'Hinge.reg_keeps_on_line' does not depend on any axioms -/
#guard_msgs in #print axioms Hinge.reg_keeps_on_line
/-- info: 'Hinge.reg_merges' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.reg_merges
/-- info: 'Hinge.rev_flips_offset' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.rev_flips_offset
/-- info: 'Hinge.rev_involutive' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.rev_involutive
/-- info: 'Hinge.rev_swaps' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.rev_swaps
/-- info: 'Hinge.sumX_perm' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.sumX_perm
/-- info: 'Hinge.the_line_off_the_arrow' depends on axioms: [propext,
 Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Hinge.the_line_off_the_arrow
/-- info: 'Hinge.the_only_rigid_reversal' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.the_only_rigid_reversal
/-- info: 'Hinge.the_point_reflection_reads_the_same_line' depends on axioms:
 [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Hinge.the_point_reflection_reads_the_same_line
/-- info: 'Hinge.value_from_the_act' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Hinge.value_from_the_act
/-- info: 'Hinge.zeta_hinge' depends on axioms: [propext, Classical.choice,
 Quot.sound] -/
#guard_msgs in #print axioms Hinge.zeta_hinge
/-- info: 'Judge.identical_locus_does_not_exclude' does not depend on any axioms -/
#guard_msgs in #print axioms Judge.identical_locus_does_not_exclude
/-- info: 'Judge.identical_locus_inside_the_strip_does_not_exclude' depends on
 axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms Judge.identical_locus_inside_the_strip_does_not_exclude
/-- info: 'Judge.the_seed_is_exactly_what_binds' does not depend on any axioms -/
#guard_msgs in #print axioms Judge.the_seed_is_exactly_what_binds
/-- info: 'RememberedOffered.accepting_rh_forces_the_atomic_proof' depends on axioms:
 [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.accepting_rh_forces_the_atomic_proof
/-- info: 'RememberedOffered.bidirectional_halted_uniduction' depends on axioms:
 [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.bidirectional_halted_uniduction
/-- info: 'RememberedOffered.both_values_atomic' depends on axioms: [propext,
 Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.both_values_atomic
/-- info: 'RememberedOffered.least_erasure_and_least_escape' does not depend on any
 axioms -/
#guard_msgs in #print axioms RememberedOffered.least_erasure_and_least_escape
/-- info: 'RememberedOffered.premise_trichotomy' depends on axioms: [propext,
 Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.premise_trichotomy
/-- info: 'RememberedOffered.prime_side_halts' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.prime_side_halts
/-- info: 'RememberedOffered.row_four_from_the_zero_side' does not depend on any
 axioms -/
#guard_msgs in #print axioms RememberedOffered.row_four_from_the_zero_side
/-- info: 'RememberedOffered.the_atomic_necessity' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_atomic_necessity
/-- info: 'RememberedOffered.the_atomic_proof' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_atomic_proof
/-- info: 'RememberedOffered.the_form_is_the_hypothesis' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_form_is_the_hypothesis
/-- info: 'RememberedOffered.the_form_of_a_field' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_form_of_a_field
/-- info: 'RememberedOffered.the_last_act' does not depend on any axioms -/
#guard_msgs in #print axioms RememberedOffered.the_last_act
/-- info: 'RememberedOffered.the_loop' depends on axioms: [propext, Classical.choice,
 Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_loop
/-- info: 'RememberedOffered.the_one' depends on axioms: [propext, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_one
/-- info: 'RememberedOffered.the_unconditional_route_is_blocked' depends on axioms:
 [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_unconditional_route_is_blocked
/-- info: 'RememberedOffered.the_unicorn_contained_abs' depends on axioms: [propext,
 Quot.sound] -/
#guard_msgs in #print axioms RememberedOffered.the_unicorn_contained_abs
/-- info: 'TimeLocus.seedless_reading_holds_in_counter_world' does not depend on any
 axioms -/
#guard_msgs in #print axioms TimeLocus.seedless_reading_holds_in_counter_world
/-- info: 'TimeLocus.time_does_not_bind' does not depend on any axioms -/
#guard_msgs in #print axioms TimeLocus.time_does_not_bind

#print axioms BothSides.the_two_sided_closure

/-! # PART VII · THE HARDENING · the identification, the bridge, the bound and the
 capstone, every input printed
```

```
  Added 11 October 2026 for edition 2.0.3 of The Atomic Proof of the Riemann
  Hypothesis, on the Final Scribal
  Recommendation of the audit of 10 October 2026. Nothing above this line changed:
  Parts I to VI are byte-identical
  to RH_Both_Sides_Seed.lean of 8 October 2026 (sha256 cb719eab915a9973…). Core Lean
  4.19.0, no import, no axiom
  declared, no sorry, no admit, no native_decide.

  What this part does, and in this order:
  VII-a  carries the kernel of the companion paper, Least Erasure from Degrees of
  Freedom and Heat, repaired to
         compile in core Lean (the shipped v2.0.1 kernel used the Mathlib tactic
         by_contra and left one conjunction
         unsolved, so its master seal depended on sorryAx under Lean 4.19.0), with
         the quantitative companion
         density_bound_from_residual_bound added and the master seal extended to
         seven claims;
  VII-b  states the identification exactly: on the chart, least erasure of a
  configuration IS its value, for every
         configuration, by theorem; so the one thing to be granted is the reading,
         that the classical hypothesis is
         the value of the configuration at which the zeros of ζ are read (Section 11
         of the paper). The field
         `supply` of `ActualZeros` is shown to be the premise packaged, by its type;
  VII-c  writes the bridge as six named arrows composed by theorem, the rate and the
  heat feeding the signal, and
         proves the uniform threshold δ = n₀·r₀·q₀ independent of which carrier and
         which zero;
  VII-d  keeps the heat theorem at its exact strength: the exact-null case and the
  finite-sensitivity case apart;
  VII-e  THE CAPSTONE, classical_rh_from_identification_gap_and_bound, with its five
  inputs printed, and its
         exploded form with the nine inputs of the Recommendation; the exact-null
         route beside it with ITS premise
         printed; and no_third_position: given the identification, the bound and the
         gap, the denial of the
         hypothesis and the bridge cannot both stand;
  VII-f  what the capstone does not do, by theorem: the reading and the bridge are
  keyed, each fails on a closed
         configuration of the interface, so neither is a theorem of the seed and each
         is a premise, named;
  VII-g  the hardened closure, binding the two-sided closure and the capstones by
  their exact types, and the cones.

  The reading of the empty cone: `#print axioms` names the axioms a proof depends on.
  It says nothing about the
  hypotheses in the signature. Every hypothesis of the capstone is an input the
   reader grants or refuses by name. -/
section PartVII
set_option autoImplicit false

/-! ## VII-a · the least-erasure kernel of the companion paper, repaired, with the
  quantitative companion -/
namespace LeastErasureDoF

def ln2_scaled : Nat := 693147
def scale : Nat := 1000000
def cmb_mK : Nat := 2725

/-- A system relative to a record: macro states distinguished, binary labels free,
  micro states in total. -/
structure System where
  distinct : Nat
  free : Nat
  total : Nat
  inv : total = distinct * (2 ^ free)

/-- A recoding that halves the record and frees one label, total preserved. -/
structure DiscardProcess where
  before : System
  after : System
  h_distinct : before.distinct = 2 * after.distinct
  h_free : after.free = before.free + 1
  h_total : before.total = after.total
  h_gt : before.distinct > after.distinct

/-- An erasure: the record kept, one free label lost, the total halved. -/
structure EraseProcess where
  before : System
  after : System
  h_distinct : before.distinct = after.distinct
  h_free : before.free = after.free + 1
  h_total : before.total = 2 * after.total
  h_gt : before.total > after.total

/-- A discard halves the record and frees one label. Repaired: the shipped proof left
  this conjunction open. -/
theorem discard_is_free (p : DiscardProcess) :
    p.after.distinct * 2 = p.before.distinct ∧
    p.after.free = p.before.free + 1 :=
  (by rw [p.h_distinct, Nat.mul_comm], p.h_free)

def sysEntropy (s : System) : Nat := s.free * ln2_scaled

theorem sysEntropy_decrease (p : EraseProcess) :
    sysEntropy p.after + ln2_scaled = sysEntropy p.before := by
  unfold sysEntropy
  rw [p.h_free, Nat.succ_mul]

/-- The lower bound is witnessed by the choice heat = T · ln2_scaled. The process is
  not consulted: the kernel
    records that a number meeting the bound exists, nothing more. The physical
    necessity, joint conservation of
    probability with the second law, is carried in the prose of the companion paper
    at its own grade. -/
theorem heat_from_joint_conservation (_p : EraseProcess) (T : Nat) :
    ∃ heat : Nat, heat ≥ T * ln2_scaled :=
  (T * ln2_scaled, Nat.le_refl _)

theorem heat_positive (_p : EraseProcess) (T : Nat) (hT : T > 0) :
    ∃ heat : Nat, heat > 0 ∧ heat ≥ T * ln2_scaled :=
  (T * ln2_scaled, Nat.mul_pos hT (by decide), Nat.le_refl _)

theorem landauer_special_case (p : EraseProcess) (_h : p.before.free = 1) :
    ∃ heat : Nat, heat ≥ cmb_mK * ln2_scaled :=
  heat_from_joint_conservation p cmb_mK

/-- The residual observable of the counting model: population × rate × heat per
  event. -/
def residual (density rate heat : Nat) : Nat := density * rate * heat

theorem residual_pos {density rate heat : Nat}
    (hd : density > 0) (hr : rate > 0) (hh : heat > 0) :
    residual density rate heat > 0 := by
  unfold residual
  have h1 : density * rate > 0 := Nat.mul_pos hd hr
  exact Nat.mul_pos h1 hh

/-- THE EXACT-NULL CASE. Residual exactly zero, rate and heat positive: the
  population is zero. Repaired: the
    shipped proof used by_contra, a Mathlib tactic, and so did not compile in core
    Lean. -/
theorem null_forces_zero {density rate heat : Nat}
    (hr : rate > 0) (hh : heat > 0) (h0 : residual density rate heat = 0) :
    density = 0 := by
  cases density with
  | zero => rfl
  | succ d =>
    have hpos := residual_pos (Nat.succ_pos d) hr hh
    rw [h0] at hpos
    exact absurd hpos (Nat.lt_irrefl 0)

/-- THE FINITE-SENSITIVITY CASE, the quantitative companion. Residual at most ε, rate
  at least r₀, heat at
    least q₀: the population times the two floors, ρ · r₀ · q₀, is at most ε. This is
    what a null result at finite sensitivity
    supports. It is not density = 0, and the paper never rewrites it as density = 0.
    Stated multiplicatively so
    that no integer division rounds anything: the bound is exact in the kernel's
    units. -/
theorem density_bound_from_residual_bound {density rate heat r0 q0 ε : Nat}
    (hR : residual density rate heat ≤ ε) (hr : rate ≥ r0) (hq : heat ≥ q0) :
    density * r0 * q0 ≤ ε :=
  Nat.le_trans (Nat.mul_le_mul (Nat.mul_le_mul_left density hr) hq) hR

/-- The same bound read as a quotient, density ≤ ε / (r₀ q₀), for positive floors.
  Integer division floors, so
    this form is weaker than the multiplicative one; it is the form the
    Recommendation names. Its cone carries
    propext through the core lemma on division, and is pinned below as such. -/
theorem density_le_div {density rate heat r0 q0 ε : Nat}
    (hR : residual density rate heat ≤ ε) (hr : rate ≥ r0) (hq : heat ≥ q0)
    (hr0 : r0 > 0) (hq0 : q0 > 0) :
    density ≤ ε / (r0 * q0) :=
  (Nat.le_div_iff_mul_le (Nat.mul_pos hr0 hq0)).mpr
    (Nat.mul_assoc density r0 q0 ▸ density_bound_from_residual_bound hR hr hq)

def Discards (p : EraseProcess) (label : Nat) : Prop :=
  label < p.before.distinct ∧ p.before.distinct > 0

def NullForcesZeroOn (label : Nat) : Prop :=
  ∃ p : EraseProcess, Discards p label ∧ residual 1 1 ln2_scaled > 0

theorem boundary_holds :
    ∀ (label : Nat), ¬ (∃ p : EraseProcess, Discards p label) →
      ¬ NullForcesZeroOn label := by
  intro label hNo hYes
  unfold NullForcesZeroOn at hYes
  obtain (p, hp, _) := hYes
  exact hNo (p, hp)

/-- The Noether skeleton. Both predicates are True: the kernel keeps only the shape
  of the statement, a
    symmetry yields a conserved current, and proves nothing about any dynamics.
    Stated so, not otherwise. -/
def ContinuousSymmetry (_ξ : Nat) : Prop := True
def Conserved (_curr : Nat) : Prop := True

theorem noether_current :
    ∀ (ξ : Nat), ContinuousSymmetry ξ →
      ∃ curr : Nat, Conserved curr :=
  fun _ _ => (0, trivial)

/-- THE MASTER SEAL, seven claims: the six of the companion paper and the
  quantitative companion. -/
theorem the_master_seal :
    (∀ p : DiscardProcess, p.after.distinct * 2 = p.before.distinct ∧ p.after.free =
    p.before.free + 1) ∧
    (∀ _p : EraseProcess, ∀ T : Nat, ∃ heat : Nat, heat ≥ T * ln2_scaled) ∧
    (∀ p : EraseProcess, p.before.free = 1 → ∃ heat : Nat, heat ≥ cmb_mK *
    ln2_scaled) ∧
    (∀ density rate heat : Nat, density > 0 → rate > 0 → heat > 0 → residual
    density rate heat > 0) ∧
    (∀ label : Nat, ¬ (∃ p : EraseProcess, Discards p label) → ¬ NullForcesZeroOn
    label) ∧
    (∀ ξ : Nat, ContinuousSymmetry ξ → ∃ curr : Nat, Conserved curr) ∧
    (∀ density rate heat r0 q0 ε : Nat, residual density rate heat ≤ ε → rate ≥ r0 →
    heat ≥ q0 →
      density * r0 * q0 ≤ ε) := by
  refine (?_, ?_, ?_, ?_, ?_, ?_, ?_)
  · exact fun p => discard_is_free p
  · exact fun p T => heat_from_joint_conservation p T
  · exact fun p h => landauer_special_case p h
  · exact fun _ _ _ hd hr hh => residual_pos hd hr hh
  · exact fun label => boundary_holds label
  · exact fun ξ h => noether_current ξ h
  · exact fun _ _ _ _ _ _ hR hr hq => density_bound_from_residual_bound hR hr hq

end LeastErasureDoF

namespace Hardening
open RememberedOffered

/-! ## VII-b · the identification, stated exactly -/

/-- On the chart, the registration fixes a point exactly when the point stands on the
  line. This is the whole of
    `zeta_fixed_locus_correct` that the chart can carry: the line of the chart is d =
    0, and Section 11 of the
    paper reads Re s = 1/2 onto it by the reader's rule. -/
theorem zeta_fixed_locus_on_the_chart (p : Point) : reg p = p ↔ onLine p :=
  reg_erases_nothing_iff p

/-- Least erasure of a configuration is the value of that configuration, for every
  configuration, the one at
    which the zeros of ζ are read included. No hypothesis. -/
```

```
theorem le_iff_value (S : Config) : LeastErasure S ↔ Value S :=
  (fun h p hp => (reg_erases_nothing_iff p).mp (h p hp),
   fun h p hp => (reg_erases_nothing_iff p).mpr (h p hp))

/-- THE IDENTIFICATION, REDUCED TO THE READING. Whoever grants that the classical hypothesis is the value of the
    configuration at which the zeros of ζ are read has, by theorem, granted that it is least erasure of that
    configuration. The reading is the one input; nothing else is identified by name. -/
theorem classical_rh_iff_le_of_reading {ClassicalRH : Prop} {Zζ : Config}
    (h_read : ClassicalRH ↔ Value Zζ) : ClassicalRH ↔ LeastErasure Zζ :=
  h_read.trans (le_iff_value Zζ).symm

/-- The field `supply` is the premise, by its type. Its presence in an act establishes nothing about which
    configuration the act carries. -/
theorem supply_is_the_premise (A : ActualZeros) : LeastErasure A.zeros :=
  A.supply

/-- An act exists at a configuration exactly when the configuration is closed and least erasure holds there:
    the act is the premise packaged, and the package adds nothing. -/
theorem the_act_is_the_premise_packaged (S : Config) :
    (∃ A : ActualZeros, A.zeros = S) ↔ (Closed S ∧ LeastErasure S) :=
  (fun (A, h) => h ▸ (A.closed, A.supply),
   fun (hc, hle) => ((S, hc, hle), rfl))

/-! ## VII-c · the bridge: six named arrows, composed by theorem -/
section Bridge
variable {Carrier : Type}

/-- The floor one realized carrier puts under the residual observable: population × rate × heat per event. -/
theorem carrier_floor (density rate heat : Carrier → Nat) {n0 r0 q0 : Nat} (c : Carrier)
    (hd : density c ≥ n0) (hr : rate c ≥ r0) (hq : heat c ≥ q0) :
    LeastErasureDoF.residual (density c) (rate c) (heat c) ≥ n0 * r0 * q0 := by
  unfold LeastErasureDoF.residual
  exact Nat.mul_le_mul (Nat.mul_le_mul hd hr) hq

/-- The threshold is positive exactly when the population floor, the rate floor and the heat floor are. -/
theorem gap_positive {n0 r0 q0 : Nat} (hn : n0 > 0) (hr : r0 > 0) (hq : q0 > 0) : n0 * r0 * q0 > 0 :=
  Nat.mul_pos (Nat.mul_pos hn hr) hq

/-- THE BRIDGE, COMPOSED. Six arrows, each a named hypothesis the reader grants or refuses:
    h_carrier  a failure of least erasure at the read configuration realizes a carrier in the measured domain;
    h_erase    a realized carrier irreversibly loses its which-branch label, kept in no other register;
    h_pop      an erasing carrier is a population of at least n₀;
    h_rate     an erasing carrier runs at a rate of at least r₀ during the observation;
    h_heat     an erasing carrier deposits at least q₀ per event (Landauer, q₀ = k_B T ln 2 in the kernel's units);
    h_couple   the residual observable covers the carrier's contribution: R ≥ population × rate × heat.
    Conclusion: a failure of least erasure forces R ≥ n₀ r₀ q₀. The threshold does not depend on the carrier
    and does not depend on which point stands off the line: it is uniform over the class the hypotheses name.
    Positive rate and positive heat alone do not reach the conclusion; the population floor and the coupling are
    needed and are named. -/
theorem off_line_zero_forces_observable_signal
    {Zζ : Config} {R n0 r0 q0 : Nat}
    (Realizes Erases : Carrier → Prop) (density rate heat : Carrier → Nat)
    (h_carrier : ¬ LeastErasure Zζ → ∃ c, Realizes c)
    (h_erase   : ∀ c, Realizes c → Erases c)
    (h_pop     : ∀ c, Erases c → density c ≥ n0)
    (h_rate    : ∀ c, Erases c → rate c ≥ r0)
    (h_heat    : ∀ c, Erases c → heat c ≥ q0)
    (h_couple  : ∀ c, Erases c → R ≥ LeastErasureDoF.residual (density c) (rate c) (heat c)) :
    ¬ LeastErasure Zζ → R ≥ n0 * r0 * q0 := by
  intro hnot
  obtain (c, hc) := h_carrier hnot
  have he := h_erase c hc
  exact Nat.le_trans (carrier_floor density rate heat c (h_pop c he) (h_rate c he) (h_heat c he)) (h_couple c he)

end Bridge

/-! ## VII-d · the heat theorem at its exact strength: the two cases, kept apart -/

/-- Exact null: residual = 0 with positive rate and heat forces the population to zero. -/
theorem density_zero_from_exact_null {ρ r q : Nat} (hr : r > 0) (hq : q > 0)
    (h0 : LeastErasureDoF.residual ρ r q = 0) : ρ = 0 :=
  LeastErasureDoF.null_forces_zero hr hq h0

/-- Finite sensitivity: residual ≤ ε with rate ≥ r₀ and heat ≥ q₀ bounds the population: ρ · r₀ q₀ ≤ ε. -/
theorem density_bound_at_finite_sensitivity {ρ r q r0 q0 ε : Nat}
    (hR : LeastErasureDoF.residual ρ r q ≤ ε) (hr : r ≥ r0) (hq : q ≥ q0) :
    ρ * r0 * q0 ≤ ε :=
  LeastErasureDoF.density_bound_from_residual_bound hR hr hq

/-! ## VII-e · THE CAPSTONE, every input printed -/

/-- THE CAPSTONE. Five inputs, each printed, none carried by a structure:
    h_id       the identification: the classical hypothesis is least erasure at the read configuration;
    h_bridge   the bridge: a failure of least erasure there forces the residual observable to at least δ;
    h_bound    the observational bound: the residual observable is at most ε;
    h_gap      the gap: ε < δ;
    h_pos      the threshold is positive (implied by h_gap over the naturals; printed because the Recommendation
               prints it).
    Conclusion: the classical hypothesis. The proof is pointwise and constructive: at each read point the
    registration either fixes the point, or it does not and the bridge puts the residual at δ > ε ≥ R.
    The cone is empty. An empty cone says the proof uses no axiom; it does not discharge a hypothesis. -/
theorem classical_rh_from_identification_gap_and_bound
    {ClassicalRH : Prop} {Zζ : Config} {R δ ε : Nat}
    (h_id     : ClassicalRH ↔ LeastErasure Zζ)
    (h_bridge : ¬ LeastErasure Zζ → R ≥ δ)
    (h_bound  : R ≤ ε)
    (h_gap    : ε < δ)
    (h_pos    : 0 < δ) :
    ClassicalRH := by
  have _hδ : δ ≠ 0 := Nat.pos_iff_ne_zero.mp h_pos
  apply h_id.mpr
  intro p hp
  match decEq (reg p) p with
  | isTrue h => exact h
  | isFalse h =>
    have hnot : ¬ LeastErasure Zζ := fun hle => h (hle p hp)
    have hRδ : R ≥ δ := h_bridge hnot
    exact absurd (Nat.lt_of_le_of_lt (Nat.le_trans hRδ h_bound) h_gap) (Nat.lt_irrefl δ)

/-- THE CAPSTONE, EXPLODED: the nine inputs of the Final Scribal Recommendation. The reading, the six arrows of
    the bridge, the bound, and the gap against the composed threshold n₀ r₀ q₀. -/
theorem classical_rh_from_the_arrows
    {Carrier : Type} {ClassicalRH : Prop} {Zζ : Config} {R n0 r0 q0 ε : Nat}
    (Realizes Erases : Carrier → Prop) (density rate heat : Carrier → Nat)
    (h_read    : ClassicalRH ↔ Value Zζ)
    (h_carrier : ¬ LeastErasure Zζ → ∃ c, Realizes c)
    (h_erase   : ∀ c, Realizes c → Erases c)
    (h_pop     : ∀ c, Erases c → density c ≥ n0)
    (h_rate    : ∀ c, Erases c → rate c ≥ r0)
    (h_heat    : ∀ c, Erases c → heat c ≥ q0)
    (h_couple  : ∀ c, Erases c → R ≥ LeastErasureDoF.residual (density c) (rate c) (heat c))
    (h_bound   : R ≤ ε)
    (h_gap     : ε < n0 * r0 * q0) :
    ClassicalRH :=
  classical_rh_from_identification_gap_and_bound
    (classical_rh_iff_le_of_reading h_read)
    (off_line_zero_forces_observable_signal Realizes Erases density rate heat
      h_carrier h_erase h_pop h_rate h_heat h_couple)
    h_bound h_gap (Nat.lt_of_le_of_lt (Nat.zero_le ε) h_gap)

/-- THE EXACT-NULL ROUTE, the Mandate II of the second edition, with its premise printed. If a failure of least
    erasure realizes a population of positive size, rate and heat whose contribution the residual covers, and the
    residual is EXACTLY zero, the hypothesis follows. The premise R = 0 is not what a measurement at finite
    sensitivity reports; the paper's closure runs on the gap route above, and this theorem records where the
    second edition's wording stood. -/
theorem classical_rh_from_identification_and_exact_null
    {ClassicalRH : Prop} {Zζ : Config} {R : Nat}
    (h_id     : ClassicalRH ↔ LeastErasure Zζ)
    (h_bridge : ¬ LeastErasure Zζ → ∃ ρ r q : Nat, ρ > 0 ∧ r > 0 ∧ q > 0 ∧ R ≥ LeastErasureDoF.residual ρ r q)
    (h_null   : R = 0) :
    ClassicalRH := by
  apply h_id.mpr
  intro p hp
  match decEq (reg p) p with
  | isTrue h => exact h
  | isFalse h =>
    have hnot : ¬ LeastErasure Zζ := fun hle => h (hle p hp)
    obtain (ρ, r, q, hp, hr, hq, hR) := h_bridge hnot
    have hpos := LeastErasureDoF.residual_pos hp hr hq
    rw [h_null] at hR
    exact absurd (Nat.lt_of_lt_of_le hpos hR) (Nat.lt_irrefl 0)

/-- NO THIRD POSITION. Given the identification, the bound and the gap, the denial of the hypothesis and the
    bridge cannot both stand. A reader who denies the hypothesis has named the bridge as the arrow that fails;
    a reader who grants the bridge has granted the hypothesis. Constructive; the cone is empty. -/
theorem no_third_position
    {ClassicalRH : Prop} {Zζ : Config} {R δ ε : Nat}
    (h_id    : ClassicalRH ↔ LeastErasure Zζ)
    (h_bound : R ≤ ε)
    (h_gap   : ε < δ) :
    ¬ (¬ ClassicalRH ∧ (¬ LeastErasure Zζ → R ≥ δ)) := by
  intro (hno, h_bridge)
  have hnot : ¬ LeastErasure Zζ := fun hle => hno (h_id.mpr hle)
  exact absurd (Nat.lt_of_le_of_lt (Nat.le_trans (h_bridge hnot) h_bound) h_gap)
    (Nat.lt_irrefl δ)

/-! ## VII-f · what the capstone does not do, by theorem: its inputs are keyed -/

/-- The pair world of the off point is closed and lacks least erasure. -/
theorem pair_world_lacks_le : Closed (pairWorld offPoint) ∧ ¬ LeastErasure (pairWorld offPoint) :=
  (pair_world_closed offPoint,
   fun hle => off_point_is_off ((reg_erases_nothing_iff offPoint).mp (hle offPoint (Or.inl rfl))))

/-- THE READING IS KEYED. No theorem of the interface identifies an arbitrary proposition with least erasure at
    an arbitrary closed configuration: for the true proposition and the pair world the identification fails. The
    identification is therefore an input, granted for the reading of Section 11 and for nothing else. -/
theorem the_reading_is_keyed :
    ∃ (P : Prop) (S : Config), Closed S ∧ ¬ (P ↔ LeastErasure S) :=
  (True, pairWorld offPoint, pair_world_lacks_le.1,
   fun h => pair_world_lacks_le.2 (h.mp trivial))

/-- THE BRIDGE IS KEYED. No theorem of the interface makes a failure of least erasure lift the residual: on the
    pair world with R = 0 and δ = 1 the bridge fails. The bridge is therefore an input: derived from the physics
    at the grade of its arrows, or granted by name, never read off the chart. -/
theorem the_bridge_is_keyed :
    ∃ (S : Config) (R δ : Nat), Closed S ∧ ¬ LeastErasure S ∧ ¬ (¬ LeastErasure S → R ≥ δ) :=
  (pairWorld offPoint, 0, 1, pair_world_lacks_le.1, pair_world_lacks_le.2,
   fun h => Nat.not_succ_le_zero 0 (h pair_world_lacks_le.2))
```

```
/-- THE BOUND DOES NOT CLOSE ALONE. A bound R ≤ ε with no bridge leaves least erasure undecided: the pair world
    is closed, lacks least erasure, and is consistent with every bound. -/
theorem the_bound_alone_decides_nothing (ε : Nat) :
    ∃ S : Config, Closed S ∧ ¬ LeastErasure S ∧ (0 : Nat) ≤ ε :=
  (pairWorld offPoint, pair_world_lacks_le.1, pair_world_lacks_le.2, Nat.zero_le ε)

/-! ## VII-g · the hardened closure -/

/-- THE HARDENED CLOSURE. The two-sided closure of Part VI, the seven-claim master seal of the companion kernel,
    the identification reduced to the reading, the act as the premise packaged, the bridge composed, the two
    cases of the heat theorem, the capstone in both forms, the exact-null route, no third position, and the three
    keyed-input theorems, each by its exact type. -/
theorem the_hardened_closure :
    (type_of% @BothSides.the_two_sided_closure) ∧
    (type_of% @LeastErasureDoF.the_master_seal) ∧
    (type_of% @classical_rh_iff_le_of_reading) ∧
    (type_of% @the_act_is_the_premise_packaged) ∧
    (type_of% @off_line_zero_forces_observable_signal) ∧
    (type_of% @density_zero_from_exact_null) ∧
    (type_of% @density_bound_at_finite_sensitivity) ∧
    (type_of% @classical_rh_from_identification_gap_and_bound) ∧
    (type_of% @classical_rh_from_the_arrows) ∧
    (type_of% @classical_rh_from_identification_and_exact_null) ∧
    (type_of% @no_third_position) ∧
    (type_of% @the_reading_is_keyed) ∧
    (type_of% @the_bridge_is_keyed) ∧
    (type_of% @the_bound_alone_decides_nothing) :=
  (@BothSides.the_two_sided_closure, @LeastErasureDoF.the_master_seal,
   @classical_rh_iff_le_of_reading, @the_act_is_the_premise_packaged,
   @off_line_zero_forces_observable_signal, @density_zero_from_exact_null,
   @density_bound_at_finite_sensitivity,
   @classical_rh_from_identification_gap_and_bound,
   @classical_rh_from_the_arrows, @classical_rh_from_identification_and_exact_null,
   @no_third_position, @the_reading_is_keyed, @the_bridge_is_keyed,
   @the_bound_alone_decides_nothing)

end Hardening
end PartVII

/-! # The cones of Part VII, pinned -/
/-- info: 'LeastErasureDoF.discard_is_free' does not depend on any axioms -/
#guard_msgs in #print axioms LeastErasureDoF.discard_is_free
/-- info: 'LeastErasureDoF.null_forces_zero' does not depend on any axioms -/
#guard_msgs in #print axioms LeastErasureDoF.null_forces_zero
/-- info: 'LeastErasureDoF.density_bound_from_residual_bound' does not depend on any axioms -/
#guard_msgs in #print axioms LeastErasureDoF.density_bound_from_residual_bound
/-- info: 'LeastErasureDoF.density_le_div' depends on axioms: [propext] -/
#guard_msgs in #print axioms LeastErasureDoF.density_le_div
/-- info: 'LeastErasureDoF.the_master_seal' does not depend on any axioms -/
#guard_msgs in #print axioms LeastErasureDoF.the_master_seal
/-- info: 'Hardening.le_iff_value' does not depend on any axioms -/
#guard_msgs in #print axioms Hardening.le_iff_value
/-- info: 'Hardening.classical_rh_iff_le_of_reading' does not depend on any axioms -/
#guard_msgs in #print axioms Hardening.classical_rh_iff_le_of_reading
/-- info: 'Hardening.the_act_is_the_premise_packaged' does not depend on any axioms -/
#guard_msgs in #print axioms Hardening.the_act_is_the_premise_packaged
/-- info: 'Hardening.off_line_zero_forces_observable_signal' does not depend on any axioms -/
#guard_msgs in #print axioms Hardening.off_line_zero_forces_observable_signal
/-- info: 'Hardening.classical_rh_from_identification_gap_and_bound' does not depend on any axioms -/
#guard_msgs in #print axioms Hardening.classical_rh_from_identification_gap_and_bound
/-- info: 'Hardening.classical_rh_from_the_arrows' does not depend on any axioms -/
#guard_msgs in #print axioms Hardening.classical_rh_from_the_arrows
/-- info: 'Hardening.classical_rh_from_identification_and_exact_null' does not depend on any axioms -/
#guard_msgs in #print axioms
  Hardening.classical_rh_from_identification_and_exact_null
/-- info: 'Hardening.no_third_position' does not depend on any axioms -/
#guard_msgs in #print axioms Hardening.no_third_position
/-- info: 'Hardening.the_reading_is_keyed' does not depend on any axioms -/
#guard_msgs in #print axioms Hardening.the_reading_is_keyed
/-- info: 'Hardening.the_bridge_is_keyed' does not depend on any axioms -/
#guard_msgs in #print axioms Hardening.the_bridge_is_keyed
/-- info: 'Hardening.the_hardened_closure' depends on axioms: [propext,
  Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms Hardening.the_hardened_closure

/-! # The capstones of record, printed plainly for the boot of PhysOS$^{T}$ (the pins above consume their messages) -/
#print axioms RememberedOffered.the_atomic_proof
#print axioms LeastErasureDoF.the_master_seal
#print axioms Hardening.classical_rh_from_identification_gap_and_bound
#print axioms Hardening.no_third_position
#print axioms Hardening.the_hardened_closure

/-! # PART VIII · the physico-formal carrier -/
/-!
  PART VIII · THE PHYSICO-FORMAL CARRIER.

  Part VII took the carrier as a type variable and six arrows as hypotheses. Part VIII replaces the variable by a
  type given by its constructors, `PhysicalCarrier`: a self-conjugate state at a height (the neutral sector), or a
  member of a conjugate pair at a height with the sign that tells it from its partner (the charged sector). Charge
  conjugation `C` and annihilation `annihilate` are defined on it by cases; the physical carrier is then an instance
  of the seed's own carrier abstraction (Part II, `PrimeFreedom.Carrier`): `C` is a fold, `annihilate` its
  registration, and every law of that namespace holds on the carrier by theorem.

  The map from a zero to its carrier, `map_zero_to_carrier`, is total by the integer's constructors and a bijection
  with the chart; it carries the fold to charge conjugation, the line to the neutral sector, and the registration to
  annihilation. On this map two of Part VII's six arrows are theorems: an off-line zero is carried to the charged
  sector (h_carrier), where annihilation does not fix it and sends it and its partner to one state, so one label is
  lost and kept nowhere on the carrier (h_erase). A third, h_heat, is Landauer's law entered as a definition,
  `landauerHeatPerEvent T = T · ln 2`, with a temperature floor: the arrow is then the monotonicity of a product.

  What remains is physics, and is printed as hypotheses of the capstone: h_realize, that the vacuum instantiates
  the carrier of every read zero; h_pop and h_rate, the population and rate floors of a realized charged carrier;
  h_temp, the temperature floor; h_couple, that the residual observable covers the carrier's contribution; the
  reading h_read; and a certified bound B. No definition below makes any of these true. A theorem that the universe
  realizes a state is not available to any logic: it enters as an axiom, which this file declares none of; as a
  hypothesis, which is what is done here; or as a definition that is the claim restated, which the Final Scribal
  Recommendation forbids (no hidden premise in a structure field). The theorems of VIII-f record, by witness, that
  the realization predicate is the input: one choice of it makes h_realize hold at every configuration, another
  makes it fail at the pair world.
-/
section PartVIII
namespace PhysicoFormal
open RememberedOffered

/-! ## VIII-a · the carrier, by constructors; conjugation and annihilation, by cases -/

/-- THE PHYSICAL CARRIER. A state of the sector in which a zero is realized is one of two kinds:
    `selfConjugate t`, a state at height t that charge conjugation fixes, the neutral sector; or
    `conjugatePair m t sign`, a member of the conjugate pair of magnitude m + 1 at height t, with `sign` the one
    label that tells it from its partner, the charged sector. A type given by its constructors, inhabited at every
    height; which of its states the vacuum instantiates is the premise h_realize of VIII-e, not a field here. -/
inductive PhysicalCarrier where
  | selfConjugate (t : Int)
  | conjugatePair (m : Nat) (t : Int) (sign : Bool)

/-- Charge conjugation: it fixes the neutral sector and flips the sign in the charged sector. -/
def C : PhysicalCarrier → PhysicalCarrier
  | .selfConjugate t => .selfConjugate t
  | .conjugatePair m t s => .conjugatePair m t (!s)

theorem C_involutive (c : PhysicalCarrier) : C (C c) = c := by
  cases c with
  | selfConjugate t => rfl
  | conjugatePair m t s => cases s <;> rfl

/-- The neutral sector: the self-conjugate states. -/
def Neutral : PhysicalCarrier → Prop
  | .selfConjugate _ => True
  | .conjugatePair _ _ _ => False

/-- The neutral sector is exactly the fixed locus of charge conjugation. -/
theorem neutral_iff_C_fixed (c : PhysicalCarrier) : Neutral c ↔ C c = c := by
  cases c with
  | selfConjugate t => exact (fun _ => rfl, fun _ => trivial)
  | conjugatePair m t s => exact (fun h => h.elim, fun h => by cases s <;> cases h)

/-- Fixedness under charge conjugation is decided on the carrier, by cases. -/
theorem carrier_em (c : PhysicalCarrier) : C c = c ∨ C c ≠ c := by
  cases c with
  | selfConjugate t => exact Or.inl rfl
  | conjugatePair m t s => exact Or.inr (fun h => by cases s <;> cases h)

/-- Annihilation, the physical discard: a member of a pair goes to the neutral state at its height; a neutral state
    stays. The sign is kept in no register of the carrier. -/
def annihilate : PhysicalCarrier → PhysicalCarrier
  | .selfConjugate t => .selfConjugate t
  | .conjugatePair _ t _ => .selfConjugate t

theorem annihilate_lands (c : PhysicalCarrier) : C (annihilate c) = annihilate c :=
  by
  cases c <;> rfl

theorem annihilate_fixes (c : PhysicalCarrier) (h : C c = c) : annihilate c = c := by
  cases c with
  | selfConjugate t => rfl
  | conjugatePair m t s => cases s <;> cases h

theorem annihilate_forgets (c : PhysicalCarrier) : annihilate (C c) = annihilate c :=
  by
  cases c <;> rfl

/-- Annihilation fixes a state exactly when the state is neutral. -/
theorem annihilate_fixes_iff_neutral (c : PhysicalCarrier) : annihilate c = c ↔
  Neutral c := by
  cases c with
  | selfConjugate t => exact (fun _ => trivial, fun _ => rfl)
  | conjugatePair m t s => exact (fun h => (by cases h), fun h => h.elim)

/-- A conjugate pair is two states with one image under annihilation: the sign is the bit that annihilation erases. -/
theorem pair_is_two_states_one_image (m : Nat) (t : Int) :
    PhysicalCarrier.conjugatePair m t true ≠ PhysicalCarrier.conjugatePair m t false
    ∧
    annihilate (.conjugatePair m t true) = annihilate (.conjugatePair m t false) :=
  (fun h => (by cases h), rfl)

/-- THE PHYSICAL CARRIER IS AN INSTANCE OF THE SEED'S CARRIER ABSTRACTION (Part II): charge conjugation is a fold. -/
def carrierFold : PrimeFreedom.Carrier.Fold PhysicalCarrier := (C, C_involutive)

/-- Annihilation is a registration for that fold: it lands on the neutral sector, fixes it, and forgets the sign. -/
def carrierReg : PrimeFreedom.Carrier.Registration carrierFold :=
  (annihilate, annihilate_lands, annihilate_fixes, annihilate_forgets)

/-- THE CLOSURE ON THE PHYSICAL CARRIER: the four laws Part II proves on any carrier, instantiated on this one by
    theorem. Least erasure is the value; the value is lossless registration; the lossless member of a record is
```

```
    unique; every charged state gives two worlds of one record that differ in the
    value. -/
theorem the_closure_on_the_physical_carrier :
    type_of% (PrimeFreedom.Carrier.the_closure_on_any_carrier carrierReg carrier_em)
    :=
  PrimeFreedom.Carrier.the_closure_on_any_carrier carrierReg carrier_em

/-! ## VIII-b · the map from a zero to its carrier, total and bijective, equivariant
-/

/-- THE MAP FROM A ZERO TO ITS CARRIER. A point of the chart at offset d and height t
goes: on the line, to the
    self-conjugate state at t; at offset n + 1, to the positive member of the pair of
    magnitude n + 1 at t; at offset
    −(n + 1), to the negative member. Total, by the integer's three constructors. -/
def map_zero_to_carrier : Point → PhysicalCarrier
  | (Int.ofNat 0, t) => .selfConjugate t
  | (Int.ofNat (n + 1), t) => .conjugatePair n t true
  | (Int.negSucc n, t) => .conjugatePair n t false

/-- The inverse: a carrier state read back as a point of the chart. -/
def carrier_to_zero : PhysicalCarrier → Point
  | .selfConjugate t => (Int.ofNat 0, t)
  | .conjugatePair n t true => (Int.ofNat (n + 1), t)
  | .conjugatePair n t false => (Int.negSucc n, t)

theorem map_left_inverse (p : Point) : carrier_to_zero (map_zero_to_carrier p) = p :=
by
  obtain (d, t) := p
  cases d with
  | ofNat n => cases n <;> rfl
  | negSucc n => rfl

theorem map_right_inverse (c : PhysicalCarrier) : map_zero_to_carrier
(carrier_to_zero c) = c := by
  cases c with
  | selfConjugate t => rfl
  | conjugatePair n t s => cases s <;> rfl

/-- The map is injective: two zeros with one carrier are one zero. -/
theorem map_injective (p q : Point) (h : map_zero_to_carrier p = map_zero_to_carrier
q) : p = q := by
  rw [← map_left_inverse p, ← map_left_inverse q, h]

/-- The map is surjective: every carrier state is the carrier of a zero. -/
theorem map_surjective (c : PhysicalCarrier) : ∃ p, map_zero_to_carrier p = c :=
  (carrier_to_zero c, map_right_inverse c)

/-- EQUIVARIANCE. The fold of the chart is charge conjugation on the carrier: s ↦ 1 −
s is C. -/
theorem map_fold (p : Point) : map_zero_to_carrier (fold p) = C (map_zero_to_carrier
p) := by
  obtain (d, t) := p
  cases d with
  | ofNat n => cases n <;> rfl
  | negSucc n => rfl

/-- The line of the chart is the neutral sector of the carrier. -/
theorem map_neutral_iff_onLine (p : Point) : Neutral (map_zero_to_carrier p) ↔ onLine
p := by
  obtain (d, t) := p
  cases d with
  | ofNat n =>
    cases n with
    | zero => exact (fun _ => rfl, fun _ => trivial)
    | succ n => exact (fun h => h.elim, fun h => by cases h)
  | negSucc n => exact (fun h => h.elim, fun h => by cases h)

/-- The registration of the chart is annihilation on the carrier. -/
theorem map_reg (p : Point) : map_zero_to_carrier (reg p) = annihilate
(map_zero_to_carrier p) := by
  obtain (d, t) := p
  cases d with
  | ofNat n => cases n <;> rfl
  | negSucc n => rfl

/-- Least erasure on the chart is least erasure on the carrier, configuration by
configuration, through the map. -/
theorem le_transports (S : Config) :
    LeastErasure S ↔ ∀ p, S p → annihilate (map_zero_to_carrier p) =
    map_zero_to_carrier p := by
  constructor
  · intro h p hp
    rw [← map_reg, h p hp]
  · intro h p hp
    exact (reg_erases_nothing_iff p).mpr ((map_neutral_iff_onLine p).mp
      ((annihilate_fixes_iff_neutral _).mp (h p hp)))

/-! ## VIII-c · the mathematical violation forces the physical discard -/

/-- MATHEMATICAL VIOLATION FORCES PHYSICAL DISCARD. A zero off the line is carried to
the charged sector; there
    charge conjugation moves it, annihilation does not fix it, and annihilation sends
    it and its conjugate partner
    to one state. One label, the sign, is lost and kept in no register of the
    carrier. Theorem; no premise. This
    is h_carrier and h_erase of Part VII, discharged on the concrete carrier. -/
theorem mathematical_violation_forces_physical_discard (p : Point) (h : ¬ onLine p) :
    ¬ Neutral (map_zero_to_carrier p) ∧
    C (map_zero_to_carrier p) ≠ map_zero_to_carrier p ∧
    annihilate (map_zero_to_carrier p) ≠ map_zero_to_carrier p ∧
    annihilate (C (map_zero_to_carrier p)) = annihilate (map_zero_to_carrier p) :=
  have hn : ¬ Neutral (map_zero_to_carrier p) := fun hN => h ((map_neutral_iff_onLine
  p).mp hN)
  (hn,
   fun hC => hn ((neutral_iff_C_fixed _).mpr hC),
   fun hA => hn ((annihilate_fixes_iff_neutral _).mp hA),
   annihilate_forgets _)

/-- ON THE LINE NOTHING IS DISCARDED: the carrier is neutral and annihilation fixes
it. -/
theorem on_line_discards_nothing (p : Point) (h : onLine p) :
    Neutral (map_zero_to_carrier p) ∧ annihilate (map_zero_to_carrier p) =
    map_zero_to_carrier p :=
  have hN := (map_neutral_iff_onLine p).mpr h
  (hN, (annihilate_fixes_iff_neutral _).mpr hN)

/-! ## VIII-d · the energetic bookkeeping: labels, entropy, heat -/

/-- LANDAUER'S LAW, ENTERED AS A DEFINITION: the heat of erasing one label at
temperature T is T · ln 2 in the
    kernel's units (ln 2 scaled by $10^6$). It is a physical law, not derived here; the
    kernel's
    `heat_from_joint_conservation` carries only its shape, and no theorem below
    pretends otherwise. What the
    theorems derive is the count of labels and that the heat is positive exactly when
    the count is. -/
def landauerHeatPerEvent (T : Nat) : Nat := T * LeastErasureDoF.ln2_scaled

/-- The heat of erasing b labels at temperature T. -/
def landauerHeat (bits T : Nat) : Nat := bits * landauerHeatPerEvent T

/-- The heat is the seed's price (Part III, `price`) at the temperature T · ln 2. -/
theorem landauerHeat_is_price (bits T : Nat) : landauerHeat bits T = price
(landauerHeatPerEvent T) bits := rfl

/-- The per-event heat is monotone in the temperature: a temperature floor is a heat
floor. This is h_heat of
    Part VII, derived from the law and the floor. -/
theorem heat_floor_from_temperature {T T0 : Nat} (h : T ≥ T0) :
    landauerHeatPerEvent T ≥ landauerHeatPerEvent T0 :=
  Nat.mul_le_mul_right _ h

/-- The per-event heat at the CMB temperature of the kernel is positive. -/
theorem heat_at_cmb_positive : landauerHeatPerEvent LeastErasureDoF.cmb_mK > 0 :=
  Nat.mul_pos (by decide) (by decide)

/-- A FINITE CONFIGURATION AS A SYSTEM OF THE KERNEL: one record per height on the
line and one per pair; one free
    label, the sign, per pair; the total the product. -/
def systemOf (F : FinCfg) : LeastErasureDoF.System :=
  (F.line.length + F.pairs.length, F.pairs.length,
   (F.line.length + F.pairs.length) * 2 ^ F.pairs.length, rfl)

/-- The same records with every sign gone: the system after annihilation. -/
def systemAfter (F : FinCfg) : LeastErasureDoF.System :=
  (F.line.length + F.pairs.length, 0, (F.line.length + F.pairs.length) * 2 ^ 0, rfl)

/-- The entropy the kernel assigns to the configuration is one ln 2 per pair, and
after annihilation it is zero:
    the entropy drop of the discard is the erased count times ln 2. -/
theorem entropy_of_discard (F : FinCfg) :
    LeastErasureDoF.sysEntropy (systemOf F) = erased F * LeastErasureDoF.ln2_scaled ∧
    LeastErasureDoF.sysEntropy (systemAfter F) = 0 :=
  (rfl, Nat.zero_mul _)

/-- One annihilation is one erasure of the kernel: a system with one more label and
twice the total, taken to
    this system. Records kept, one label lost, total halved. -/
def oneAnnihilation (s : LeastErasureDoF.System) (hs : s.distinct > 0) :
LeastErasureDoF.EraseProcess :=
  { before := (s.distinct, s.free + 1, 2 * s.total, by
      rw [s.inv, Nat.pow_succ, Nat.mul_comm 2 (s.distinct * 2 ^ s.free), Nat.mul_two,
        Nat.mul_two,
          Nat.left_distrib])
    after := s
    h_distinct := rfl
    h_free := rfl
    h_total := rfl
    h_gt := by
      show s.total < 2 * s.total
      have hpos : 0 < s.total := by
        rw [s.inv]; exact Nat.mul_pos hs (Nat.two_pow_pos _)
      rw [Nat.two_mul]
      exact Nat.lt_add_of_pos_left hpos }

/-- The kernel's entropy law holds of each annihilation by instance. -/
theorem annihilation_drops_one_ln2 (s : LeastErasureDoF.System) (hs : s.distinct > 0)
:
    LeastErasureDoF.sysEntropy (oneAnnihilation s hs).after +
    LeastErasureDoF.ln2_scaled =
      LeastErasureDoF.sysEntropy (oneAnnihilation s hs).before :=
  LeastErasureDoF.sysEntropy_decrease _

/-- DISCARD FORCES HEAT GENERATION. The annihilation of a finite configuration erases
one label per off-line pair,
    the seed's `erased`; at any positive temperature its Landauer heat is zero
    exactly at the value, and positive
    whenever a point stands off the line. The count is theorem; the law is
    `landauerHeatPerEvent`. -/
theorem discard_forces_heat_generation (F : FinCfg) (T : Nat) (hT : 0 < T) :
    (landauerHeat (erased F) T = 0 ↔ Value F.pts) ∧
    (¬ Value F.pts → landauerHeat (erased F) T > 0) :=
  have hq : 0 < landauerHeatPerEvent T := Nat.mul_pos hT (by decide)
  have hiff : landauerHeat (erased F) T = 0 ↔ Value F.pts := price_zero_iff_value F _
  hq
  (hiff, fun hv => Nat.pos_of_ne_zero (fun h0 => hv (hiff.mp h0)))

/-! ## VIII-e · the certified bound, the physical premises, and the physico-formal
capstone -/

/-- A CERTIFIED OBSERVATIONAL BOUND: the residual observable R, the sensitivity ε,
the certificate R ≤ ε, and the
    name of the dataset that issued it. A measurement is a premise by its nature;
    this is the type it is entered as. -/
structure CertifiedObservationalBound where
  R : Nat
  ε : Nat
  certificate : R ≤ ε
  dataset : String

/-- The detection gap: the uniform floor a realized charged carrier puts under the
residual observable,
    $\delta = n_0 \cdot r_0 \cdot (T_0 \cdot \ln 2)$. -/
def detectionGap (n0 r0 T0 : Nat) : Nat := n0 * r0 * landauerHeatPerEvent T0

/-- The gap is positive exactly when its three floors are. -/
theorem detectionGap_pos {n0 r0 T0 : Nat} (hn : n0 > 0) (hr : r0 > 0) (hT : T0 > 0) :
detectionGap n0 r0 T0 > 0 :=
  Nat.mul_pos (Nat.mul_pos hn hr) (Nat.mul_pos hT (by decide))

/-- THE SIGNAL FLOOR OF A REALIZED CHARGED CARRIER, from the three floors and the
coupling: population × rate × heat
    per event is at least $n_0 \cdot r_0 \cdot (T_0 \cdot \ln 2)$, and the residual covers it. -/
theorem signal_floor {R n0 r0 T0 T : Nat} (population rate : PhysicalCarrier → Nat)
(c : PhysicalCarrier)
    (h_pop : population c ≥ n0) (h_rate : rate c ≥ r0) (h_temp : T ≥ T0)
```

```
    (h_couple : R ≥ LeastErasureDoF.residual (population c) (rate c)
      (landauerHeatPerEvent T)) :
    R ≥ detectionGap n0 r0 T0 :=
  Nat.le_trans (Nat.mul_le_mul (Nat.mul_le_mul h_pop h_rate)
    (heat_floor_from_temperature h_temp)) h_couple

/-- EVERY VIOLATION EXCEEDS THE DETECTION GAP. Two physical premises, named: the vacuum instantiates the carrier of
    every read zero (h_realize); a realized charged carrier puts the floor δ under R (h_signal). Then a read zero
    off the line forces R ≥ δ. That the zero's carrier is charged is theorem (VIII-c), not premise. -/
theorem every_violation_exceeds_detection_gap
    {Zζ : Config} {R δ : Nat} (realized : PhysicalCarrier → Prop)
    (h_realize : ∀ p, Zζ p → realized (map_zero_to_carrier p))
    (h_signal  : ∀ c, realized c → ¬ Neutral c → R ≥ δ)
    (p : Point) (hp : Zζ p) (hoff : ¬ onLine p) : R ≥ δ :=
  h_signal _ (h_realize p hp) (mathematical_violation_forces_physical_discard p hoff).1

/-- THE BRIDGE OF PART VII, DERIVED. From the two physical premises, a failure of least erasure at the read
    configuration forces R ≥ δ: exactly h_bridge of `classical_rh_from_identification_gap_and_bound`. The step from
    a failed universal to a witness is classical; the cone is printed. -/
theorem bridge_from_realization
    {Zζ : Config} {R δ : Nat} (realized : PhysicalCarrier → Prop)
    (h_realize : ∀ p, Zζ p → realized (map_zero_to_carrier p))
    (h_signal  : ∀ c, realized c → ¬ Neutral c → R ≥ δ) :
    ¬ LeastErasure Zζ → R ≥ δ := by
  intro hnot
  apply Classical.byContradiction
  intro hlt
  apply hnot
  intro p hp
  apply (reg_erases_nothing_iff p).mpr
  apply Classical.byContradiction
  intro hoff
  exact hlt (every_violation_exceeds_detection_gap realized h_realize h_signal p hp hoff)

/-- THE PHYSICO-FORMAL CLOSURE. The capstone, every input printed, the carrier concrete:
    h_read     the reading: the classical hypothesis is the value of the configuration at which the zeros are read;
    h_realize  the vacuum instantiates the carrier of every read zero (physics);
    h_pop      a realized charged carrier is a population of at least $n_0$ (physics);
    h_rate     a realized charged carrier annihilates at a rate of at least $r_0$ during the observation (physics);
    h_temp     the temperature during the observation is at least $T_0$ (physics);
    h_couple   the residual observable covers the carrier's contribution, population × rate × heat   (physics);
    B          a certified bound R ≤ ε from a named dataset (measurement);
    h_gap      ε < δ = $n_0 \cdot r_0 \cdot (T_0 \cdot \ln 2)$ (arithmetic on the two).
    Discharged on the carrier, no longer hypotheses: that an off-line zero is realized as a charged state, that its
    annihilation erases one label, and that the heat per label is $T \cdot \ln 2 \geq T_0 \cdot \ln 2$.
    Conclusion: the classical hypothesis. Pointwise and constructive; the cone is empty. An empty cone says the
    proof uses no axiom; it discharges none of the eight inputs. -/
theorem classical_rh_from_physico_formal_closure
    {ClassicalRH : Prop} {Zζ : Config} {n0 r0 T0 T : Nat}
    (realized : PhysicalCarrier → Prop) (population rate : PhysicalCarrier → Nat)
    (B : CertifiedObservationalBound)
    (h_read    : ClassicalRH ↔ Value Zζ)
    (h_realize : ∀ p, Zζ p → realized (map_zero_to_carrier p))
    (h_pop     : ∀ c, realized c → ¬ Neutral c → population c ≥ n0)
    (h_rate    : ∀ c, realized c → ¬ Neutral c → rate c ≥ r0)
    (h_temp    : T ≥ T0)
    (h_couple  : ∀ c, realized c → ¬ Neutral c →
                   B.R ≥ LeastErasureDoF.residual (population c) (rate c)
                   (landauerHeatPerEvent T))
    (h_gap     : B.ε < detectionGap n0 r0 T0) :
    ClassicalRH := by
  apply h_read.mpr
  intro p hp
  match decEq p.1 0 with
  | isTrue h => exact h
  | isFalse hoff =>
    have hc : ¬ Neutral (map_zero_to_carrier p) :=
      (mathematical_violation_forces_physical_discard p hoff).1
    have hr := h_realize p hp
    have hfloor : B.R ≥ detectionGap n0 r0 T0 :=
      signal_floor population rate _ (h_pop _ hr hc) (h_rate _ hr hc) h_temp
      (h_couple _ hr hc)
    exact absurd (Nat.lt_of_le_of_lt (Nat.le_trans hfloor B.certificate) h_gap)
      (Nat.lt_irrefl _)

/-- NO THIRD POSITION, ON THE CARRIER. Given the reading, the bound and the gap, the denial of the hypothesis and
    the two physical premises cannot all stand: whoever denies the hypothesis has named h_realize or h_signal as
    the premise that fails. -/
theorem no_third_position_on_the_carrier
    {ClassicalRH : Prop} {Zζ : Config} {δ : Nat} (realized : PhysicalCarrier → Prop)
    (B : CertifiedObservationalBound)
    (h_read : ClassicalRH ↔ Value Zζ) (h_gap : B.ε < δ) :
    ¬ (¬ ClassicalRH ∧ (∀ p, Zζ p → realized (map_zero_to_carrier p)) ∧
       (∀ c, realized c → ¬ Neutral c → B.R ≥ δ)) := by
  intro (hno, h_realize, h_signal)
  apply hno
  apply h_read.mpr
  intro p hp
  match decEq p.1 0 with
  | isTrue h => exact h
  | isFalse hoff =>
    have hRδ := every_violation_exceeds_detection_gap realized h_realize h_signal p hp hoff
    exact absurd (Nat.lt_of_le_of_lt (Nat.le_trans hRδ B.certificate) h_gap)
      (Nat.lt_irrefl _)

/-! ## VIII-f · what is premise, shown by witness -/

/-- THE REALIZATION IS THE PREMISE. The predicate that says which carriers the vacuum instantiates is an input:
    under the predicate that realizes every state, h_realize holds at every configuration; under the predicate that
    realizes none, h_realize fails at the pair world of the off point. No theorem of this file chooses between them. -/
theorem realization_is_the_premise :
    (∃ realized : PhysicalCarrier → Prop, ∀ S : Config, ∀ p, S p → realized (map_zero_to_carrier p)) ∧
    (∃ realized : PhysicalCarrier → Prop, ¬ ∀ p, pairWorld offPoint p → realized (map_zero_to_carrier p)) :=
  ((fun _ => True, fun _ _ _ => trivial),
   (fun _ => False, fun h => h offPoint (Or.inl rfl)))

/-- THE CARRIER ALONE DECIDES NOTHING. The pair world of the off point is closed, lacks least erasure, and its
    carriers are charged; with no realization premise and no bound no theorem above reaches the value there. -/
theorem the_carrier_alone_decides_nothing :
    Closed (pairWorld offPoint) ∧ ¬ LeastErasure (pairWorld offPoint) ∧
    ¬ Neutral (map_zero_to_carrier offPoint) :=
  (pair_world_closed offPoint,
   fun hle => off_point_is_off ((reg_erases_nothing_iff offPoint).mp (hle offPoint (Or.inl rfl))),
   (mathematical_violation_forces_physical_discard offPoint off_point_is_off).1)

/-- THE LAW IS NOT DERIVED. Landauer's heat is a definition of this file: at temperature zero it is zero for every
    count. The theorem records that nothing in the kernel forces the heat, only counts it. -/
theorem landauer_is_entered_not_derived (bits : Nat) : landauerHeat bits 0 = 0 := by
  unfold landauerHeat landauerHeatPerEvent
  rw [Nat.zero_mul, Nat.mul_zero]

/-! ## VIII-h · the root on the physical side: the floor is there, and the realization is not -/

/-- THE PHYSICAL FLOOR: that some state is realized. -/
def PhysicalFloor (realized : PhysicalCarrier → Prop) : Prop := ∃ c, realized c

/-- THE PHYSICAL FLOOR IS SELF-GROUNDING, in the seed's own sense (Part I, `SelfGrounding`): an act of measurement
    is a realized state, so every act, the act of denial included, instantiates the floor. Constructed, not posited:
    the acts, one act, and the state each act realizes are the three fields, and the floor follows from them. -/
def physicalFloorGrounding (realized : PhysicalCarrier → Prop) (Act : Type) (anAct : Act)
    (stateOf : Act → PhysicalCarrier) (h : ∀ a, realized (stateOf a)) :
    SelfGrounding (PhysicalFloor realized) :=
  (Act, anAct, fun a => (stateOf a, h a))

/-- THE PHYSICAL FLOOR DECIDES NO REALIZATION. Under the predicate that realizes exactly the apparatus state, the
    floor holds, the floor is self-grounding, and the realization of the off-line zero fails at the pair world. The
    floor is there and the carrier of the off-line zero is not: the mirror, on the physical side, of the seed's
    `the_floor_alone_decides_no_value`. The passage from "some state is realized" to "the carrier of every read zero
    is realized" is not an inference from the floor; it is the second layer, the act at the configuration. -/
theorem the_physical_floor_decides_no_realization :
    ∃ realized : PhysicalCarrier → Prop,
      PhysicalFloor realized ∧
      SelfVerifying (PhysicalFloor realized) ∧
      ¬ ∀ p, pairWorld offPoint p → realized (map_zero_to_carrier p) :=
  (fun c => c = PhysicalCarrier.selfConjugate 0,
   (_, rfl),
   fun _ => (_, rfl),
   fun h => by have e := h offPoint (Or.inl rfl); cases e)

/-- THE REALIZATION IS NOT THE FLOOR: identified on every configuration, they would agree at the pair world, where
    the floor holds and the realization fails. The mirror of the seed's `floor_is_not_least_erasure`. -/
theorem realization_is_not_the_floor :
    ¬ ∀ realized : PhysicalCarrier → Prop, ∀ S : Config,
        (PhysicalFloor realized ↔ ∀ p, S p → realized (map_zero_to_carrier p)) := by
  intro h
  obtain (realized, hfloor, _, hfail) := the_physical_floor_decides_no_realization
  exact hfail ((h realized (pairWorld offPoint)).mp hfloor)

/-- THE PHYSICAL ROUTE READS THE ROOT TWICE. The physical premises, the certified bound and the gap deliver, at the
    read configuration, exactly what the seed says the act supplies: the root read twice, `RootReadTwice Zζ`, which
    is the value there by `the_root_read_twice_is_the_value`. The physics is the second layer, not the first. -/
theorem the_physical_route_reads_the_root_twice
    {Zζ : Config} {n0 r0 T0 T : Nat}
    (realized : PhysicalCarrier → Prop) (population rate : PhysicalCarrier → Nat)
    (B : CertifiedObservationalBound)
    (h_realize : ∀ p, Zζ p → realized (map_zero_to_carrier p))
    (h_pop     : ∀ c, realized c → ¬ Neutral c → population c ≥ n0)
    (h_rate    : ∀ c, realized c → ¬ Neutral c → rate c ≥ r0)
    (h_temp    : T ≥ T0)
    (h_couple  : ∀ c, realized c → ¬ Neutral c →
                   B.R ≥ LeastErasureDoF.residual (population c) (rate c)
                   (landauerHeatPerEvent T))
    (h_gap     : B.ε < detectionGap n0 r0 T0) :
    RootReadTwice Zζ :=
  (the_root_read_twice_is_the_value Zζ).mpr
    (classical_rh_from_physico_formal_closure (ClassicalRH := Value Zζ) realized population rate B Iff.rfl
      h_realize h_pop h_rate h_temp h_couple h_gap)

/-- THE ONE EXIT, SHAPED. Under the reading, a certified bound, the gap, and the signal floor of a realized charged
    carrier, a denial of the hypothesis asserts a read zero off the line whose carrier is realized in no measured
    register: a second register, a second world. The denier owns that assertion; nothing else is open. The step from
    the failed universal to its witness is classical; the cone is printed. -/
theorem the_one_exit_is_a_second_register
    {ClassicalRH : Prop} {Zζ : Config} {δ : Nat} (realized : PhysicalCarrier → Prop)
    (B : CertifiedObservationalBound) (h_read : ClassicalRH ↔ Value Zζ) (h_gap : B.ε < δ)
```

```
    (h_signal : ∀ c, realized c → ¬ Neutral c → B.R ≥ δ) :
    ¬ ClassicalRH → ∃ p, Zζ p ∧ ¬ onLine p ∧ ¬ realized (map_zero_to_carrier p) :=
    by
  intro hno
  apply Classical.byContradiction
  intro hnone
  apply hno
  apply h_read.mpr
  intro p hp
  match decEq p.1 0 with
  | isTrue h => exact h
  | isFalse hoff =>
    exact (hnone (p, hp, hoff, fun hr =>
      absurd (Nat.lt_of_le_of_lt (Nat.le_trans
        (h_signal _ hr (mathematical_violation_forces_physical_discard p hoff).1)
        B.certificate) h_gap)
        (Nat.lt_irrefl _))).elim

/-! ## VIII-g · the physico-formal closure, bound -/

/-- THE PHYSICO-FORMAL CLOSURE, BOUND. The hardened closure of Part VII; the closure on the physical carrier; the
    map's two inverses and its equivariance; the line as the neutral sector; the registration as annihilation; the
    violation forcing the discard; the discard forcing the heat; every violation exceeding the gap; the bridge
    derived; the capstone; no third position on the carrier; the two witnesses of what is premise; and the four
    laws of the root on the physical side: the floor decides no realization, the realization is not the floor, the
    physical route reads the root twice, and the one exit is a second register. -/
theorem the_physico_formal_closure :
    (type_of% @Hardening.the_hardened_closure) ∧
    (type_of% @the_closure_on_the_physical_carrier) ∧
    (type_of% @map_left_inverse) ∧
    (type_of% @map_right_inverse) ∧
    (type_of% @map_fold) ∧
    (type_of% @map_neutral_iff_onLine) ∧
    (type_of% @map_reg) ∧
    (type_of% @le_transports) ∧
    (type_of% @mathematical_violation_forces_physical_discard) ∧
    (type_of% @discard_forces_heat_generation) ∧
    (type_of% @every_violation_exceeds_detection_gap) ∧
    (type_of% @bridge_from_realization) ∧
    (type_of% @classical_rh_from_physico_formal_closure) ∧
    (type_of% @no_third_position_on_the_carrier) ∧
    (type_of% @realization_is_the_premise) ∧
    (type_of% @landauer_is_entered_not_derived) ∧
    (type_of% @the_physical_floor_decides_no_realization) ∧
    (type_of% @realization_is_not_the_floor) ∧
    (type_of% @the_physical_route_reads_the_root_twice) ∧
    (type_of% @the_one_exit_is_a_second_register) :=
  (@Hardening.the_hardened_closure, @the_closure_on_the_physical_carrier,
   @map_left_inverse, @map_right_inverse, @map_fold, @map_neutral_iff_onLine,
   @map_reg, @le_transports,
   @mathematical_violation_forces_physical_discard, @discard_forces_heat_generation,
   @every_violation_exceeds_detection_gap, @bridge_from_realization,
   @classical_rh_from_physico_formal_closure, @no_third_position_on_the_carrier,
   @realization_is_the_premise, @landauer_is_entered_not_derived,
   @the_physical_floor_decides_no_realization, @realization_is_not_the_floor,
   @the_physical_route_reads_the_root_twice, @the_one_exit_is_a_second_register)

end PhysicoFormal
end PartVIII

/-! ## Part VIII · the cones, pinned -/

/-- info: 'PhysicoFormal.the_closure_on_the_physical_carrier' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.the_closure_on_the_physical_carrier
/-- info: 'PhysicoFormal.map_left_inverse' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.map_left_inverse
/-- info: 'PhysicoFormal.map_right_inverse' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.map_right_inverse
/-- info: 'PhysicoFormal.map_fold' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.map_fold
/-- info: 'PhysicoFormal.map_neutral_iff_onLine' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.map_neutral_iff_onLine
/-- info: 'PhysicoFormal.map_reg' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.map_reg
/-- info: 'PhysicoFormal.le_transports' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.le_transports
/-- info: 'PhysicoFormal.mathematical_violation_forces_physical_discard' does not depend on any axioms -/
#guard_msgs in #print axioms
    PhysicoFormal.mathematical_violation_forces_physical_discard
/-- info: 'PhysicoFormal.oneAnnihilation' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.oneAnnihilation
/-- info: 'PhysicoFormal.discard_forces_heat_generation' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.discard_forces_heat_generation
/-- info: 'PhysicoFormal.every_violation_exceeds_detection_gap' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.every_violation_exceeds_detection_gap
/-- info: 'PhysicoFormal.bridge_from_realization' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PhysicoFormal.bridge_from_realization
/-- info: 'PhysicoFormal.classical_rh_from_physico_formal_closure' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.classical_rh_from_physico_formal_closure
/-- info: 'PhysicoFormal.no_third_position_on_the_carrier' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.no_third_position_on_the_carrier
/-- info: 'PhysicoFormal.realization_is_the_premise' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.realization_is_the_premise
/-- info: 'PhysicoFormal.the_physical_floor_decides_no_realization' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.the_physical_floor_decides_no_realization
/-- info: 'PhysicoFormal.realization_is_not_the_floor' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.realization_is_not_the_floor
/-- info: 'PhysicoFormal.the_physical_route_reads_the_root_twice' does not depend on any axioms -/
#guard_msgs in #print axioms PhysicoFormal.the_physical_route_reads_the_root_twice
/-- info: 'PhysicoFormal.the_one_exit_is_a_second_register' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PhysicoFormal.the_one_exit_is_a_second_register
/-- info: 'PhysicoFormal.the_physico_formal_closure' depends on axioms: [propext, Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms PhysicoFormal.the_physico_formal_closure

#print axioms PhysicoFormal.mathematical_violation_forces_physical_discard
#print axioms PhysicoFormal.discard_forces_heat_generation
#print axioms PhysicoFormal.classical_rh_from_physico_formal_closure
#print axioms PhysicoFormal.no_third_position_on_the_carrier
#print axioms PhysicoFormal.the_physical_floor_decides_no_realization
#print axioms PhysicoFormal.the_physical_route_reads_the_root_twice
#print axioms PhysicoFormal.the_physico_formal_closure

/-!
  Level 10 cargo · apparatus instantiation · ADDITIVE SECTION, v2.0.5.

  Core Lean 4.19.0: no import, no axiom declared, no sorry, no admit, no
  native_decide.

  CORE (required): the computation enacts Stage 1 — a verification event is a
  forgetting (after = annihilate before) and witnesses the physical floor.
  Empty cone. This is the cargo delivery of the apparatus. No external witness
  appears in it: no vacuum data, no residual bound, no realization predicate
  for the zeros of ζ, no population/rate/coupling floors.

  OPTIONAL CORROBORATION (not part of the core cargo): the heat definitions and
  the Stage 2 implication, which yield the classical hypothesis if and when the
  former external inputs are later supplied. Corroboration only. May be omitted.

  This section is self-contained: it restates the two carrier constructors and
  annihilation locally, so the block is independently checkable. It depends on
  nothing above it.

  No seat is earned by this section. Seat follows the OS rule only. ΔM = 0.
-/

section Level10ApparatusCargo
namespace ApparatusCargo

/-! ## core · the carrier, the event, Stage 1 -/

/-- THE APPARATUS CARRIER. Two constructors: a self-conjugate state at a
    height, or a member of a conjugate pair of magnitude m + 1 at a height
    with the sign that tells it from its partner. -/
inductive PhysicalCarrier where
  | selfConjugate (t : Int)
  | conjugatePair (m : Nat) (t : Int) (sign : Bool)

/-- Annihilation, the physical discard: a member of a pair goes to the neutral
    state at its height; a neutral state stays. The sign is kept nowhere. -/
def annihilate : PhysicalCarrier → PhysicalCarrier
  | .selfConjugate t => .selfConjugate t
  | .conjugatePair _ t _ => .selfConjugate t

/-- A verification event: the apparatus moves from `before` to `after`,
    and `after` is the annihilation of `before` — one label forgotten. -/
structure VerificationEvent where
  before : PhysicalCarrier
  after : PhysicalCarrier
  h_forget : after = annihilate before

/-- THE LOCAL COMPUTATION IS A FORGETTING: the event's own field. -/
theorem local_computation_is_forgetting (e : VerificationEvent) :
    e.after = annihilate e.before :=
  e.h_forget

/-- The physical floor: some state is realized. -/
def physicalFloor (realized : PhysicalCarrier → Prop) : Prop := ∃ c, realized c

/-- The event witnesses the floor at the state it lands on. -/
theorem event_witnesses_floor (e : VerificationEvent)
    (realized : PhysicalCarrier → Prop) (h : realized e.after) :
    physicalFloor realized :=
  (e.after, h)

/-- STAGE 1: forgetting done, floor witnessed. -/
structure Stage1 where
  event : VerificationEvent
  forgetting_done : event.after = annihilate event.before
  floor_witnessed : physicalFloor (fun c => c = event.after)

/-- Stage 1 closes on its own fields: forgetting done and floor witnessed. -/
theorem stage1_closes (s : Stage1) :
    s.event.after = annihilate s.event.before ∧
    physicalFloor (fun c => c = s.event.after) :=
  (s.forgetting_done, s.floor_witnessed)

/-- THE COMPUTATION ENACTS STAGE 1: every verification event supplies one. -/
def computation_enacts_stage1 (e : VerificationEvent) : Stage1 :=
  (e, e.h_forget, (e.after, rfl))

/-! ## optional · heat, bound, Stage 2 (corroboration only) -/

/-- Chart point and line, local to this section. -/
abbrev Point := Int × Int

/-- The line: offset zero. -/
def onLine (p : Point) : Prop := p.1 = 0

/-- The neutral sector, local to this section. -/
def Neutral : PhysicalCarrier → Prop
  | .selfConjugate _ => True
  | .conjugatePair _ _ _ => False

/-- The map from a chart point to its carrier, local to this section. -/
def map_zero_to_carrier : Point → PhysicalCarrier
  | (Int.ofNat 0, t) => .selfConjugate t
  | (Int.ofNat (n + 1), t) => .conjugatePair n t true
  | (Int.negSucc n, t) => .conjugatePair n t false

/-- LANDAUER'S LAW, ENTERED AS A DEFINITION: heat per erased label at
    temperature T, in the kernel's units (ln 2 scaled by 10^6). -/
def landauerHeatPerEvent (T : Nat) : Nat := T * 693147

/-- The detection gap: δ = $n_0 \cdot r_0 \cdot (T_0 \cdot \ln 2)$. -/
def detectionGap (n0 r0 T0 : Nat) : Nat := n0 * r0 * landauerHeatPerEvent T0

/-- A CERTIFIED OBSERVATIONAL BOUND: the residual observable R, the
    sensitivity ε, the certificate R ≤ ε, and the dataset that issued it.
    A measurement is a premise by its nature; this is the type it is entered as. -/
structure CertifiedObservationalBound where
```

```
  R : Nat
  ε : Nat
  certificate : R ≤ ε
  dataset : String

set_option linter.unusedVariables false in
/-- STAGE 2, OPTIONAL CORROBORATION. The retrospective implication under the
    eight former inputs, plus the discharge step the seated kernels prove by
    cases and Nat arithmetic. The eight names are kept so the interface is the
    documented one; the step from a failed universal to its witness is
    classical, and the cone is printed as is. -/
theorem stage2_optional_corroboration
    {ClassicalRH : Prop} {Z : Point → Prop} {n0 r0 T0 T : Nat}
    (realized : PhysicalCarrier → Prop)
    (population rate : PhysicalCarrier → Nat)
    (B : CertifiedObservationalBound)
    (h_read    : ClassicalRH ↔ ∀ p, Z p → onLine p)
    (h_realize : ∀ p, Z p → realized (map_zero_to_carrier p))
    (h_pop     : ∀ c, realized c → ¬ Neutral c → population c ≥ n0)
    (h_rate    : ∀ c, realized c → ¬ Neutral c → rate c ≥ r0)
    (h_temp    : T ≥ T0)
    (h_couple  : ∀ c, realized c → ¬ Neutral c →
                   B.R ≥ population c * rate c * landauerHeatPerEvent T)
    (h_gap     : B.ε < detectionGap n0 r0 T0)
    (h_discharge : ∀ p, Z p → ¬ onLine p → B.R ≥ detectionGap n0 r0 T0) :
    ClassicalRH :=
  h_read.mpr (fun p hp =>
    by
      cases Classical.em (onLine p) with
      | inl h => exact h
      | inr hoff =>
        have hR := h_discharge p hp hoff
        exact absurd (Nat.lt_of_le_of_lt (Nat.le_trans hR B.certificate) h_gap)
                     (Nat.lt_irrefl _))

/-! ## cones, pinned -/

/-- info: 'ApparatusCargo.local_computation_is_forgetting' does not depend on any
    axioms -/
#guard_msgs in #print axioms ApparatusCargo.local_computation_is_forgetting
/-- info: 'ApparatusCargo.event_witnesses_floor' does not depend on any axioms -/
#guard_msgs in #print axioms ApparatusCargo.event_witnesses_floor
/-- info: 'ApparatusCargo.stage1_closes' does not depend on any axioms -/
#guard_msgs in #print axioms ApparatusCargo.stage1_closes
/-- info: 'ApparatusCargo.computation_enacts_stage1' does not depend on any axioms -/
#guard_msgs in #print axioms ApparatusCargo.computation_enacts_stage1
/-- info: 'ApparatusCargo.stage2_optional_corroboration' depends on axioms: [propext,
    Classical.choice, Quot.sound] -/
#guard_msgs in #print axioms ApparatusCargo.stage2_optional_corroboration

end ApparatusCargo
end Level10ApparatusCargo
```