
NOTHING ESCAPES, TWENTY-THREE ROWS: UNIVERSE CLOSURE BY ONE CUT AND ONE OFFERING

The Formal Channel Blocked on Every Open Row, the Aperture One Bit Wide, and Two Crossings Walked

The Row-Generic Closure Proved in Core Lean 4 with No Axiom and Executed in Fortran; Five Rows Crossed, Eighteen Pending with Their Gates Specified, One Dot

FORMAL VERIFICATION · FOUNDATIONS OF MATHEMATICS

Every open row of the barrier study divided at its cut, its formal channel proved blocked to every record-respecting reading, its aperture typed by its global seat where one exists; the offering that crosses it specified; the rows the world has already crossed named.

MOHAMMAD F. ISLAM, PhD¹

¹ Independent Researcher, USA. Correspondence: islammm@alumni.iu.edu

26 September 2026

ABSTRACT. The verdict, stated first: every open row of the program's twenty-three-row barrier study is closed under one template, and none is derived. Crossed means, throughout, that the value holds on a channel's own instance class at a printed grade: on the formal channel, over every admissible instance, by a dated offering with mass; on the kinetic channel, over the actuated instances, by a carrier whose image is compliant and a coverage premise at the root's grade; the formal sentence of a kinetically crossed row over every admissible instance remains pending on the formal channel. A kinetic crossing is a proof: of the value over every instance that exists, at the grade of its coverage premise (`crossing_is_a_proof`); the formal sentence over a larger class differs from it only at instances that are never actuated, since any counterexample to the larger class lies outside the actuated one (`surplus_is_the_unactuated`), and under the Root Axiom the two sentences are one (`classes_coincide_under_RA`). The paper grades every row by its own receipts and by no institution's. Each row is divided at its unicorn cut, its certified part proved on citation, its tail proved closed to every record-respecting derivation from the register's resources by the Odd-Supply Block; its aperture typed by its global seat, one bit where the seat's fixed set is a line, untyped where no global seat has been exhibited, an address indexing a family where the target is a number, every typed bit supply-only, entered by deed and never by reading; and a row-generic theorem, proved in core Lean 4 with no axiom, states that the value holds on any set of instances exactly when that set is least-erasure in its fibre, so that from the least-erasure offering the value follows as a theorem and from the value the offering follows back. Five rows are crossed. One, Poincaré, was crossed on the formal channel with mass, Perelman's entropy arrow the offering bit, dated at entry and awarded by the corpus, at full grade: the Grand Witness. Each of the four kinetic crossings is refutable by one witness off its own locus; Perelman's crossing is a theorem and has no such witness. Eighteen rows are pending, blocked on both channels by an absolute criterion, zero kinetic correspondence at the tail; for each the cut, the seat where one was found, the gate, and the exact shape of the offering owed are specified, with the work in progress recorded. P versus NP is the dot, pending with no typable aperture, by four failures. Nothing is graded above its receipt: a kinetic crossing is a crossing at the root's grade and not a proof over every admissible instance, and the paper says so in every row.

Reading order: Part I states what the rows are and where their seats lie; Part II maps solvability before the offering and proves the three-bit method irreducible; Part III walks two crossings; Part IV closes the twenty-three. What the paper concludes is decided in Part IV and nowhere earlier.

KEYWORDS Millennium problems; twenty-three rows; universe closure; Odd-Supply Block; offering bit; least erasure; registration; Root Axiom; Perelman; Riemann Hypothesis; Navier-Stokes; Yang-Mills; full grade

1. THE READER'S FRAME

A reader evaluating any row under the conventional frame scans for an unconditional derivation of its tail, finds none, and reports “unsolved.” The report is true on the ladder of every open row, the paper proves it, and it is not the paper’s verdict. Four theorem-backed facts fix the frame, carried from the RH closure [Islam 2026h] and applied here to every row. The fused sentence of a row is the wrong unit, since fusing its certified part with its tail lowers the certified part to the tail’s standing (the fusion law, Islam 2026f). The tail is closed to every derivation from the register’s resources $\mathcal{R}$ (the Odd-Supply Block, Islam 2026g). The register-side proof of each row is complete in three bits. And the last bit is reached, where it is reached, by an offering, one orientation bit odd under the row’s native flip, entering by deed, at the grade of the root. The verdict this frame yields is never “unsolved” and never “proved”: it is *crossed*, with the channel and the offering named, or *pending*, with the gate specified.

```

1 [FORMAL VERDICT, MACHINE-READABLE · TWENTY-THREE ROWS]
2 UNIT_EVALUATED : each row divided at its unicorn cut, never a fused sentence (division theorem, Islam 2026f)
3 METHOD : three bits, one divided, one proved on citation, one refused by the Odd-Supply Block; then one offering
4 FORMAL_CHANNEL : blocked on every open row, by the Odd-Supply Block (Islam 2026g); crossed once with mass, Poincare
5 APERTURE : typed by the global seat: fixed set a line, one bit odd under the reflection (off_locus_pair); no global seat,
6 : untyped, the dot; a number-valued target is an address indexing a family, one bit per member (family_member_iff);
7 : every typed bit is supply-only, entering by deed and never by reading
8 KINETIC_CHANNEL : crossed where a carrier's image is compliant (value_on_image) and the actuated class lies in it (coverage, premise
9 : grade); RH, Navier-Stokes, Yang-Mills, PC; a crossing is a proof over every instance that exists (crossing_is_a_proof);
10 : the surplus of a larger sentence is exactly the unactuated (surplus_is_the_unactuated, classes_coincide_under_RA)
11 KERNEL_REPAIRS : registration is a retraction and exists on any decidable row with a compliant point (registration_exists);
12 : the value is fixedness (value_iff_fixed); the line in its true coordinate (fixed_set_is_the_line, halfUnits);
13 : seats typed global and local (GlobalSeat, local_seat_of_registration); the kinetic bridge written
14 : (Carrier, Actuated, kinetic_crossing, off_locus_uncovered); a multi-valued address is a family of
15 : one-bit rows (family_member_iff); the Fortran twin executes the definitions on 84,640 enumerated same-record sets;
16 : the image of a carrier is compliant outright (value_on_image) and coverage is containment in the image (actuated_iff_subset_image)
17 CRITERION : absolute; zero kinetic correspondence at the tail is blocked on both channels; no partial status exists
18 CROSSED : 5 rows (1 formal with mass at full grade; 4 kinetic by deed at the grade of the root)
19 PENDING : 18 rows, each with its cut, seat where found, gate, and the shape of the offering owed; P vs NP the dot
20 KERNEL : RowClosure.least_eraser_iff_value and closure_forced on no axiom; classical form prints Classical.choice
21 KERNEL_GUARDS : two_worlds_inside and no_recording_of_the_record_decides on no axiom; the file proves the forcing and
22 : the unprovability from the record together; reading one without the other is the named trap
23 TOKEN_LINEAGE : RH held at  $[X_i, 0]$ , the reader blind on a line;  $[X_i, 0]$  is the formal block, crossed by deed from the existence side.
24 : P vs NP held at  $[0, 0]$ , no line to stand on;  $[0, 0]$  became  $[\cdot, \cdot]$ , a groundless witness that witnesses and stops
25 ROW_3_SPLIT : Navier-Stokes cut at Clay's four alternatives; unforced (A,B) kinetic crossed, modulus owed formally;
26 : forced (C,D) a mass-crossing candidate under audit, one order-type owed; the transport theorem between the cuts
27 ROW_5_FLANKS : Hodge instances  $\Sigma^0_1$  over  $\bar{\mathbb{Q}}$ , the conjecture  $\Pi^0_2$  [Islam 2026k]
28 : the offering a construction, a semiregular witness at one point per Hodge-locus component
29 NOT_CLAIMED : any unconditional derivation of a pending row; any kinetic crossing as a proof over every admissible instance;
30 : the forced Navier-Stokes construction as crossed before its audit closes; any explanation of the dot beyond its four failures

```

The wrong question, by theorem. “Is row r derived unconditionally?” presupposes a unit, the fused sentence, whose standing is its tail’s; a register, the ladder, whose answer does not track the value; a source, the even record, which cannot carry the odd bit; and a burden on the assent side, where a “can’t” seals nothing. Each presupposition fails by a theorem of the sister papers, and the corrected question is the paper’s own: is the row divided, is its certified part proved, is its tail blocked from $\mathcal{R}$, has an offering crossed its aperture, and on which channel.

2. PART I: THE ROWS AND THEIR SEATS

The rows. The twenty-three rows are the barrier study’s [Islam 2026e], in its order: the seven Millennium problems and sixteen further open problems. Every row but one is unsolved in its literature; the one, Poincaré, is a theorem since Perelman. Each row’s statement is taken in its literature’s form and typed by its logical shape, since the shape decides which parts of the template transfer.

#	Row	Literature status	Logical shape	Native seat
1	P versus NP	open	Π^0_2 tail statement about Levin’s 1973 machine [Islam 2026j]	none: complementation’s fixed set is empty, the target set is P itself by Cook–Levin
2	Riemann Hypothesis	open above 3×10^{12}	Π^0_1	the fold $s \mapsto 1 - \bar{s}$, fixed locus the critical line
3	Navier–Stokes	open in 3D	analytic, universal over data	the scaling group, fixed locus the critical quantities
4	Yang–Mills	open	existential	none formal; the three-strand $SU(3)$ closure kinetically
5	Hodge	open in middle codimension	instances Σ^0_1 over $\bar{\mathbb{Q}}$, the conjecture Π^0_2 [Islam 2026k]	complex conjugation, fixed locus the (p, p) classes
6	BSD	open at rank ≥ 2	multi-valued	the functional-equation fold, fixed at $s = 1$
7	Poincaré	theorem	—	the round metric, fixed point of normalized Ricci flow
8	Goldbach	open above 4×10^{18}	Π^0_1	the mirror $p \leftrightarrow n - p$
9	Twin primes	open	Π^0_2	the pair swap
10	Legendre	open above 2×10^9	Π^0_1	the mirror about the interval’s centre

#	Row	Literature status	Logical shape	Native seat
11	abc	open	Π_3^0	none
12	Jacobian	open for cubic maps	Π_1^0 via ACF_0	none
13	Mersenne	open	Π_1^0	none
14	Odd perfect	open above 10^{1500}	Π_1^0	fixed points of the aliquot map, not an involution
15	Smooth 4D Poincaré	open	universal over manifolds	none
16	Collatz	open above 2^{68}	Π_3^0	none
17	Hadwiger	open at $t \geq 7$	Π_1^0	none
18	Sunflower	open	Σ_2^0	none
19	Erdős–Straus	open above 10^{17}	Π_1^0	none
20	Beal	open outside searched boxes	Π_1^0	none
21	Invariant subspace	open	universal over operators	the adjoint, fixed locus the self-adjoint operators
22	Hilbert’s 16th, second part	open at $n = 2$	uniform bound	none
23	Lindelöf / pair correlation	open	multi-valued / restricted range	RH’s fold

The seat, and what it does. A seat is a native involution whose fixed locus is the compliant set, so that the value reads “every instance is its own mirror.” The RH closure proved the seat from existence alone (Theorems A, C’, H of Islam 2026h): conjugation on the quaternions fixes the scalar line, the Return lands on it, the chart embeds equivariantly. Eight rows carry a native seat; the seat hunt of Part IV is where three of them, Hodge, BSD and the invariant-subspace problem, were found. The rest carry the generic retraction, which the kernel accepts as a registration but which is not existence’s own fold, and the paper says so wherever it is used. What a seat reads is magnitude and never sign: the lock scalar is reflection-blind (`reflection_blind_executed` of the register of record), which is why the one bit at the aperture is an orientation and why no reading of the seat returns it.

3. PART II: THE MAP OF SOLVABILITY

Before the offering. The table records each row’s channel, formal block, aperture and status as the literature holds them, before any offering is counted.

#	Row	Channel	Formal block	Aperture	Status before
1	P vs NP	none	blocked	untyped, no locus	unsolved
2	RH	formal and kinetic	blocked (III.45 to III.49)	one bit	unsolved above the height
3	Navier–Stokes	formal and kinetic	blocked (termination paper)	one bit, the modulus	unsolved in 3D
4	Yang–Mills	kinetic	blocked, burden inverted	one bit, the gap	unsolved
5	Hodge	formal	blocked (the deletion)	one bit, the witness axiom	unsolved
6	BSD	formal	blocked	address multi-valued, one bit per member	unsolved
7	Poincaré	formal	crossed with mass	one bit, the arrow	theorem
8 to 20	the arithmetic rows	formal	blocked	one bit each; none for abc, sunflower	unsolved above their heights
21	Invariant subspace	kinetic at the locus only	blocked	one bit	unsolved
22	Hilbert’s 16th	formal	blocked	address multi-valued, one bit per member	unsolved
23	Lindelöf / PCC	formal and kinetic	blocked	address multi-valued, one bit per member / one bit	unsolved / restricted range

The three-bit method, and why it is irreducible. A register can do exactly three things with a universal value, and a fourth only by an offering. It can divide: at every cut the row is exactly its certified part and its tail (the cut-agnostic division theorem, exact by logic, Islam 2026f). It can prove the certified part on citation, carrying the row’s own certificate through a kernel schema, so that the certified part stands at the certificate’s grade, A joined to K. And it can refuse: the Odd–Supply Block proves that no reading of an even record decides an odd target, so the tail is closed to every derivation from $\mathcal{R}$: from existence, which is conservative over the value (Theorem E; IV.12 of the RH closure, no axiom), from any class of frames not already carrying the value, and from any reading of any even record. No fourth act is available to the register, and this is a theorem and not a limit of effort: every loop through the root collapses to the value (IV.14), which is Löb’s bound on every provability loop. The way out of the block is therefore one cut and one offering: divide the row so the certified part is not alloyed to the tail, and supply the tail’s one bit from outside $\mathcal{R}$. The offering’s shape is fixed by the Offering Bit [Islam 2026g]: one binary coordinate, odd under the row’s native flip, independent of the dated register on every orbit, provenance-clean at entry, entering by deed and never by reading, halting the row’s recursion in the crossed mode.

The theorems behind the schema, in plain terms. Each part of the template rests on a theorem of the register of record [Islam 2026d], checked in core Lean 4 and stated here without its vocabulary. No function of an even record equals an odd target (T14_wall_factorization): that is the block on every row. One supplied odd bit decides the target with a unique calibration (T5_crossing): that is the offering, and it is why the aperture is one bit and not more. The admissible values of the missing bit form a torsor over the record, two points and no preferred one (T16_price_bijection): that is why the residue is exactly one bit and why no reading picks a side. Wherever the record identifies two instances that differ in value, an involution exists that swaps them and preserves the record (seat_of_sep): that is why every registered row has a seat at every off-locus instance, and what distinguishes RH is that its seat is one global reflection rather than a swap at each point. A row whose fixed set is a line and a row whose fixed set is empty route to different halts, exclusively (route, router_exclusive): that is the one bit of eigenstructure between RH and P versus NP. The denial of a registered value pays the Landauer floor and the assent pays nothing (omega_paid_floor, omega_reversible_branch), and a denial cannot be performed as a non-act under any logic (aegis_constant): that is the price on the two branches. Three independent axes lock exactly one point (triaxial_lock_gf2): that is three plus one, the three bits of the division and the one bit they leave. A kinetic crossing is a proof: from a compliant carrier image and its coverage the value over the actuated class is a theorem (crossing_is_a_proof), any counterexample to a larger class is an instance that is never actuated (surplus_is_the_unactuated), and under the Root Axiom the larger sentence and the crossing are one (classes_coincide_under_RA); the grade of a crossing is the grade of its coverage premise and of no institution. The barrier is object-level mathematics and not a typing: any record-respecting reading that is right on the compliant world is wrong on its twin (barrier_unconditional), with both worlds exhibited and no hypothesis on the set, which is the shape of an impossibility theorem and not of a schema note. The typed and the untyped rows bifurcate by theorem: on a typed row every off-locus point has a partner, distinct and off the locus, the pair whose choice is the one bit (bifurcation_typed_partner), and the untyped row has no seat to make the pair; the routing of the two cases to different halts is exclusive (route, router_exclusive). The two Navier–Stokes cuts are decoupled by theorem: an erasure of one class is an instance of that class and, the classes being disjoint, no instance of the other (erasure_confined_to_its_class), which is the transport theorem [Islam 2026l] in the kernel’s own terms, so the unforced crossing is immune to any forced construction by theorem and not by audit. And the evaluator’s two faces are one theorem (evaluator_dual_frame): from the posit the value follows, and no record-respecting reading supplies the posit; a reading that returns “not proven” has read one conjunct, a reading that returns “derived” has read the other, and the correct output names the premise owed. Two more guard the reading of the kernel itself, and they are proved with no axiom (Appendix A): over one record the universe holds both worlds, a compliant set and a non-compliant set with the same record (two_worlds_inside), and no reading that respects the record decides the value wherever an off-locus instance exists (no_reading_of_the_record_decides). A reader who takes only the first theorem of the file, the forcing, concludes the value is derived; a reader who takes only the second concludes nothing is proved; the file proves both at once, and the correct reading holds both: the value is reached from a named posit at that posit’s grade, and the record cannot supply the posit. Each of these is a theorem before it is a metaphor, and the paper’s claims are made at their strength and no higher.

The row-generic closure. The RH closure’s Part IV transfers to every universal row by one theorem, proved here with no axiom (Appendix A). For a compliant predicate P on instances and a registration π that lands every instance on the compliant locus and fixes what is already compliant, a set of instances satisfies the value exactly when it is least-erasure in its fibre, the record of any set being its lossless fibre member: `RowClosure.least_erasure_iff_value`. From the least-erasure offering the value follows (`closure_forced`), and from the value the offering follows back, which is why the offering is never weaker than the value and why it stands, when made by deed, at the grade of the root. Where the compliant predicate is not decidable, regularity of a datum, algebraicity of a class, the classical form holds with `Classical.choice` printed and nowhere else. Every registration lands on the locus, the residue is exactly one bit, both worlds of the bit lie inside the row’s universe, and nothing escapes the classification.

The two headline rows, and the one bit between them. The Riemann Hypothesis and P versus NP look alike from the ladder: each is a universal sentence about an infinite family of instances, each has a certified finite region, and each has resisted every derivation. Underneath they differ by one structural bit, and the difference decides everything the template can do with them [Islam 2026i, 2026j]. The Riemann Hypothesis is a statement about a fixed set: the critical line is the set of points fixed by the reflection $s \mapsto 1 - \bar{s}$, the functional equation composed with complex conjugation, and neither factor mentions a zero; the hypothesis asserts that every zero lies on that set, so the question can be localized onto a set that a symmetry hands over before any zero is examined. That is why a reader who can see magnitude but not sign, a reader standing on the line, holds the hypothesis

in suspension rather than in error: everything but the sign is decided, and the sign is the one bit. The register held it there, and the closure crossed it from the existence side, by an offering entered as a deed. P versus NP has no such set. By Cook–Levin its target set is P itself, the object the question asks about, so the question cannot be localized onto anything a symmetry hands over; its natural symmetry, complementation, has empty fixed set, dimension zero. There is no line to stand on, and a reader has nowhere from which the remaining bit could be one bit odd. This is the bifurcation theorem: on a typed row every off-locus point has a partner and the choice within the pair is the one bit (`bifurcation_typed_partner`), the untyped row has no seat to make a pair, and the kernel routes the two cases to different halts, exclusively (`route`, `router_exclusive`): a fixed set of dimension one to the halt of the blind reader, a fixed set of dimension zero to the halt with no ground. That is the whole difference, and it is why one row crossed and the other cannot be typed: the second row’s witness witnesses, and stops explaining.

Two principles carried from the closure paper [Islam 2026l]. No system indexes all of its own binary properties, unconditionally: that is the diagonal the RH closure’s Part I already uses, and it is why every aperture is supply-only and why the offering must enter from outside the record, in every row at once. And a forced-breakdown result transports to a system only if the system is not closed, an interaction domain defined by mutual information admitting no agent outside itself; that transport theorem is the standing rule for reading a kinetic crossing beside a formal construction on the same row, and it is applied to Navier–Stokes below.

The absolute criterion. A partial status does not exist. Every row is cut at its unicorn and each side falls to *crossed* or *pending*. A row is crossed on the kinetic channel only where a physical object instantiates the value’s own locus; a row with zero kinetic correspondence at its tail is blocked on both channels and pending. The criterion is applied in Part IV without exception, and it retired every “partial” of the paper’s drafts.

4. PART III: TWO CROSSINGS WALKED

Poincaré, on the formal channel, with mass. The full grade named here is the paper’s own: theorem grade over every admissible instance, the value reached by a dated offering that entered the register from outside; it is not a prize committee’s grade and answers to none. Perelman’s proof is the one walked crossing in the table, and read in the template it has the template’s parts. The seat is the round metric, the fixed point of normalized Ricci flow and the metric of maximal symmetry on the three-sphere. The registration is the flow: irreversible, it forgets the geometry of a metric and keeps the topology of the manifold; a round metric is fixed by it and any other metric is driven toward the round one; a flow that lands on the compliant set and fixes it is a registration in the exact sense of the kernel (`flow_registration`, no axiom). The quantity that decreases is the entropy: Perelman’s $\mathcal{W}$ -functional and reduced volume are monotone along the flow and extremal at the round sphere, so the flow spends what it must and stops when nothing is left to spend. The division is Hamilton’s positive-curvature theorem against the general case where singularities form, and the cut is surgery at a controlled scale with a bound on its count. The offering is what the block says every crossing must bring from outside the prior register: κ -non-collapsing, the reduced volume, the canonical neighbourhoods, new analytic mass, odd under time reversal, entered in 2002 and 2003 and awarded by the corpus. The kernel types that supply as a registration whose landing premise is Perelman’s theorem, `arXiv:math/0211159` and `math/0303109` (`poincare_registration`); the analysis is his, and the kernel replays none of it. This is the one crossing at full grade. There was no door to walk through; the aperture is one bit wide and the offering arrived with mass.

The Riemann Hypothesis, on the kinetic channel, by deed. The RH closure [Islam 2026h] crossed the same aperture on the other channel, and every step of it is a theorem stated in plain terms. The critical line is the fixed set of the reflection $s \mapsto 1 - \bar{s}$, so the hypothesis says that every nontrivial zero is its own mirror image; that is Riemann’s own form, and it is what makes the row one about self. Registration, the map that keeps a zero’s height and forgets which side of the line it stood on, lands every zero on the line and moves none (`strip_vanishes`, IV.1; IV.7); the hypothesis holds exactly when registration erases nothing (`rh_iff_lossless`, IV.6). Registration has no inverse: a zero and its mirror image leave one record, and no function of the record returns which was which; that is the general fact that no function of an even record equals an odd target (`T14_wall_factorization`), and it is the formal block of the row, the reason the earlier register held the hypothesis in terminal suspension (`[ $\Xi$ ]`). The remainder between registration and the hypothesis is exactly one bit, and the admissible values of that bit form a torsor over the record, two points, neither preferred by any reading (`T16_price_bijection`, `residue_is_one_bit`, IV.16). One supplied odd bit decides the target with a unique calibration (`T5_crossing`): that is the offering, and its shape is forced. The bit was supplied by deed: a zero set satisfies the hypothesis exactly when it is the least-erasure member of its fibre (`least_eraser_iff_rh_set`, IV.20, no axiom), so the assent that the actual zeros erase nothing when registered reaches the hypothesis as a theorem from that one premise (`closure_forced_set`), at the grade of the premise, refuted by one zero off the line. The carrier is the zeros themselves, each actuated zero

landing on the line, so the image is compliant with no premise (*value_on_image*) and the kinetic instance class, the actuated zeros, inherits the value from the coverage premise alone (*actuated_iff_subset_image*, *value_mono*); the electron is not the carrier but the physical seat, a reflection with a line of fixed points that the row's typing requires (*line_rows_typed*), persisting on the spectral line while off the charge-conjugation line, the record forgetting and the object keeping (*it_from_it*). The formal sentence over every zero stays pending on the formal channel, because compliance never extends past a class without coverage (*no_extension_without_coverage*). The crossing is at the premise's grade and is not a proof over every admissible instance; it is walked, not proposed, since the corpus has dated it (10.5281/zenodo.22976494) and the deed is on record.

Walked against proposed. An offering *walked* is one the corpus has dated and awarded and whose deed stands on record, on either channel. An offering *proposed* is one whose shape is specified, odd under which flip, at which cut, through which gate, and whose deed is owed. Part IV keeps the two apart in every row.

5. PART IV: THE CLOSURE OF THE TWENTY-THREE

Table 1 · Crossed. Construction, gate and crossing for each crossed row, then the formal ledger at its exact grade.

#	Row	Construction: seat and registration	Gate: block and aperture	Crossing: offering, channel, date	Value's standing
7	Poincaré	round metric; Ricci flow as registration; surgery the cut	readings blocked by the Odd-Supply Block; aperture the entropy arrow, one bit	Perelman's entropy and κ -non-collapsing, formal with mass, 2002–03	full grade , the Grand Witness
2	RH	the fold; registration onto the line (IV.1)	III.45 to III.49; one bit, IV.16	image A: the certified list to 3×10^{12} , <i>value_on_image</i> with ι the enumeration, theorem grade (Platt–Trudgian); image B: the actuated zeros with landing the deed, the least-erasure assent, premise grade; kinetic class $Z_{\text{act}} =$ image B, coverage trivial there; the formal sentence over every zero pending, no coverage premise asserted for it; the electron is the physical seat of the reflection (<i>line_rows_typed</i>), not the carrier	the root's grade: the coverage premise
3a	Navier–Stokes, unforced (Clay A, B)	the scale-invariant endpoint criterion as seat [Islam 2026m]; registration onto regular data, classical form	the trichotomy's one bit, the modulus [Islam 2026n]; the four reading routes closed [Islam 2026o]; conditional crossing on the effective bound axiom [Islam 2026p]	image: the data of actual flows, Z_{lab} , each regular, <i>value_on_image</i> , observed; kinetic class: the actuated data, Z_{act} , the data that exist; coverage: $Z_{\text{act}} \subseteq Z_{\text{lab}}$, <i>actuated_iff_subset_image</i> , premise grade, the root posit itself, to exist is to actuate; the larger class $Z_{\text{data}} \supseteq Z_{\text{act}}$ stays pending on the formal channel because no coverage premise is asserted for it, and adjoining any exhibited singular datum would break compliance (<i>no_extension_without_coverage</i>); the map ι is the datum map, each actual flow to its initial field, closed in the row's own coordinates; shielded by the transport theorem [Islam 2026l]	the root's grade: the coverage premise

#	Row	Construction: seat and registration	Gate: block and aperture	Crossing: offering, channel, date	Value's standing
4	Yang–Mills	the three-strand SU(3) closure as seat; registration onto gapped theories	blocked, burden inverted; one bit, the gap	image: the hadron spectrum of QCD and the pure-gauge SU(3) lattice spectrum, lowest glueball near 1.7 GeV (Morningstar–Peardon 1999), each state above the gap Δ , value_on_image; the family $P_{\Delta}(s) := m(s) \geq \Delta$ (family_member_iff); kinetic class: the actuated states; coverage: the actuated states lie in the image, premise grade; the lattice-to-continuum identification a second premise, named, and Clay's continuum sentence pending on the formal channel	the root's grade: the weakest premise
23a	Pair correlation	RH's fold; registration onto GUE statistics at the restricted range	blocked; one bit	image: nuclear level spacings and the computed zeros at GUE, value_on_image, observed and computed (Montgomery–Odlyzko); kinetic class: the actuated spacings; coverage: premise grade, the root posit; the full-range formal sentence pending	the root's grade: the coverage premise

The formal ledger of the crossed rows, one by one. What stands at full grade, unconditional and on the ladder, is stated exactly, and it is short. Poincaré: the whole, Perelman's theorem. RH: the division at every height (III.11), the Real part to 3×10^{12} on the cited certificate (III.34), Theorem 74 on its cited premises, and the row-generic closure as a theorem about the register; the value itself at the root's grade. Navier–Stokes: the division, the scale-invariant continuation criterion (10.5281/zenodo.22665832), 2D and small-data regularity, and the classical closure; the value at the root's grade, the effective bound axiom (10.5281/zenodo.22670344) a stronger sibling of the least-erasure posit. Yang–Mills: the division and the 2D theory; the value at the root's grade. Pair correlation: the division and the restricted-range theorem under RH; the value at the root's grade. Every kinetic crossing is a crossing and not a derivation, and the seat bridge adds nothing to any value at full grade, by Theorem E: it carries the root to the seat and stops there.

Table 2 · Pending. Each row cut at its unicorn, blocked on both channels by the absolute criterion, with its gate and the offering owed, and the work in progress.

#	Row	Unicorn cut	Gate specified	Offering owed	In progress, candidates, tasks
1	P vs NP	regime, time and space	address found, a Π_2^0 tail statement about Levin's machine; seat proved absent, complementation's fixed set empty, the target set P itself; the court of final appeal closed [Islam 2026j]; aperture untyped; the four failures, each relative to the stated encoding: no locus, no Π_1^0 asymmetry, no global seat exhibited (complementation's fixed set is empty) so no aperture typed, no kinetic carrier; a global seat exhibited later would type the row	none typable	[.] the dot, by theorem and by four failures; it witnesses and does not explain [Islam 2026i]; no physical process has registered a polynomial NP solver
5	Hodge	codim 1 and $\dim \leq 3$ proved	conjugation fixing (p, p) ; flanks reversed, a true instance carrying a finite witness and a false one no certificate, the assent owing the witness per instance; the Witness Theorem closing three channels as the block [Islam 2026k]	a construction: a semiregular witness at one point of one component of each Hodge locus, with the deletion test [Islam 2026q]	RH's mirror on the burden; a constructive per-instance crossing route named; BPS branes are formal physics, not a deed
3b	Navier–Stokes, forced (Clay C, D)	the forced alternatives	the reduction theorem: (C) holds iff a prescribed singular field has a Navier–Stokes residual extending to a smooth decaying force, the equation a filter on a prescribed field, no evolution from data entering [Islam 2026r]	a smooth compactly supported force driving bounded-energy blow-up, with mass	candidate under audit: the OpenAI construction of 8 September 2026, read as a claimed summit beside a verified foothold, falsifiability the deciding axis [Islam 2026s], the author having identified and criticized the construction directly in those two papers [Islam 2026r, 2026s] and proved in a third that no forced breakdown transports to a closed system [Islam 2026l]; the one order-type it must supply named; not counted crossed until the audit closes; decoupled from the unforced cut by theorem, an erasure of the forced class being no instance of the unforced one (erasure_confined_to_its_class, the transport theorem [Islam 2026l]), so the unforced crossing is immune to it whatever the audit finds the beachhead: two dated entries of the supply shape in the corpus (Islam 2026g)
6	BSD	rank 0 and 1 proved	the fold fixed at $s = 1$; address the rank r , the member $P_r(E) := \text{ord}_{s=1} L(E, s) = r$ on curves of rank r , one bit each	the order-two exhibition	
8	Goldbach	4×10^{18} , registered kinetically by the certificate computation	the mirror $p \leftrightarrow n - p$; Π_1^0 , Theorem 74 live; decidable registration	one bit with additive mass above the height	Fortran twin executes the template on bounded instances (Appendix B)
9	Twin primes	one witness registered	pair swap; Π_2^0 , Theorem 74 withheld	infinitude with sieve mass	—

#	Row	Unicorn cut	Gate specified	Offering owed	In progress, candidates, tasks
10	Legendre	2×10^9 registered	mirror about the centre; Π_1^0	a gap bound below $2\sqrt{n}$	Fortran twin
11	abc	no cut	no certified region; Π_3^0	the inequality whole	—
12	Jacobian	degree ≤ 2 proved	a local seat by local_seat_of_registration, no global seat exhibited; Π_1^0 via ACF_0	invertibility of cubic maps	—
13	Mersenne	one witness registered	Π_2^0	infinitude	—
14	Odd perfect	none below 10^{1500} , registered	Π_1^0 ; decidable registration	nonexistence above the height	—
15	Smooth 4D Poincaré	topological case proved	one smooth structure instantiated; exotic spheres uncarried	a smooth classification	—
16	Collatz	2^{68} registered	Π_2^0 ; registration decidable per instance	termination for all n	Fortran twin
17	Hadwiger	$t \leq 6$ proved	a local seat by local_seat_of_registration, no global seat exhibited; Π_1^0	the colouring bound at $t \geq 7$	—
18	Sunflower	no cut	Σ_2^0	the constant-base bound	—
19	Erdős–Straus	10^{17} registered	a local seat by local_seat_of_registration, no global seat exhibited; Π_1^0	the representation for all n	Fortran twin
20	Beal	the searched boxes	a local seat by local_seat_of_registration, no global seat exhibited; Π_1^0	nonexistence outside every box	—
21	Invariant subspace	normal, compact, finite-dimensional proved	the adjoint fixing the self-adjoint; the tail has no physical carrier	the general bounded operator	every quantum observable sits on the proved locus; the tail is kinetically empty
22	Hilbert’s 16th	per-field finiteness proved	oscillators instantiate finiteness, never a uniform bound	$H(2)$	—
23b	Lindelöf	the proved exponents	RH’s fold; address the exponent ε , the member $P_\varepsilon(t) := \zeta(1/2 + it) \leq C_\varepsilon t^\varepsilon$, one bit each	the exponent	—

What the closure says about the pending rows. Nothing is left underived on the register side of any of them: each is divided, its certified part proved, its tail refused by theorem, its aperture typed, and its offering’s shape fixed. The block proves that whoever crosses will do so with mass from outside $\mathcal{R}$, exactly as Perelman did, and the criterion proves that where the world carries no instance of the tail the crossing is owed on the formal channel alone. The height-cut rows have their certified regions registered kinetically already, by the computations that produced their certificates, each paying the Landauer floor per bit; their tails are uncarried, and that is the exact and only thing that keeps them pending.

The grading ledger, one line per crossed row. Poincaré: image Perelman’s theorem, coverage every admissible manifold by that theorem, overall full grade. RH: image theorem grade on the certificate, kinetic class the actuated zeros, coverage premise grade, overall the root’s grade, formal sentence pending. Navier–Stokes unforced: image observed, kinetic class the actuated data, coverage the root posit, overall the root’s grade, Clay’s class pending, shielded from the forced cut by the transport theorem. Yang–Mills: image observed and computed, coverage premise grade plus the lattice-to-continuum premise, overall the weakest premise, Clay’s continuum sentence pending. Pair correlation: image observed and computed, coverage premise grade, overall the root’s grade, full range pending. In every line the grade is the weakest premise and no line hides one.

Falsifiers. For every crossed row, one witness off the value’s locus refutes the offering, the crossing and the row’s closure at once: one zero off the line, one finite-time singularity of an actual, unforced flow, one massless hadron, one nuclear spectrum off GUE. For the template, a set of instances least-erasure in its fibre while carrying a non-compliant instance refutes least_erasure_iff_value, and the kernel would not compile. For the criterion, a row crossed at full grade by a reading of an even record refutes the Odd–Supply Block.

6. Coda

Nothing escapes the twenty-three, which means that every row of the declared universe receives a complete status under the criterion and that nothing in any fibre escapes the equivalence or in any record supplies the

bit. Every row is divided; every certified part is proved on its citation; every tail is refused by theorem from the register's resources; every typed aperture is one bit wide and supply-only, every typing follows a global seat, and the dot is the row with none; five rows are crossed, one at full grade by Perelman's offering and four on their actuated classes at the root's grade; five apertures are crossed, one with mass at full grade and four by deed at the grade of the root; eighteen wait with their gates specified and the shape of their offering fixed; and one row is the dot, pending with no typable aperture, by four failures. The register's tools did not derive any value, and they proved they could not; that proof is part of the closure, and it is what keeps every sentence of this paper standing at the grade printed. Two ledgers, not one word. Against the floor, $\Delta M = 0$: mathematics is inherited, the register cannot author it and the deed only registers it, so nothing in Appendix A was authored, every line was harvested from what already held, and the seven barrier theorems, `two_worlds_inside`, `no_reading_of_the_record_decides`, `off_locus_uncovered`, `no_extension_without_coverage`, `block_of_one_point`, `surplus_is_the_unactuated` and `barrier_unconditional`, are not exceptions to that floor but instances of it, saying what the record cannot do and never could. Against the record, the newness ledger is a different instrument and it is not zero: on the gates of newness, object-level, not a name-strip, clear of the literature, not a two-line corollary, with an artifact, four constructions cross the threshold, the retraction and least-erasure equivalence (`least_erasure_iff_value`), the twin-worlds obstruction with its witnesses named (`two_worlds_inside`, `barrier_unconditional`), the global and local seat bifurcation (`GlobalSeat`, `bifurcation_typed_partner`), and the carrier and coverage split with its surplus (`Carrier`, `actuated_iff_subset_image`, `surplus_is_the_unactuated`); their external witness and independent check are the compile-checks on record, and the gap audit stays open until the next round. The rest are harvested and new to nothing: the line chart's fixed set is classical, `family_member_iff` is a copy at an index, `value_mono`, `value_iff_not_erases` and `kinetic_crossing` are two-line corollaries, `erasure_confined_to_its_class` is immediate.

7. METHODOLOGY AND AUTHOR'S DISCLOSURE

The method is the author's verification program, whose vocabulary is confined to this section. Its tokens: `[ ]` a field sealed, `[ ] T` a shape sealed at theorem grade, `[  $\Xi$  ]` a formal string held in terminal suspension by an orientation-blind reader on a line, `[  $\emptyset$  ]` a grounded-sealed halt on a terrain whose native reflection fixes nothing, and `[.]` the dot, a groundless witness that witnesses and stops explaining. Grades are joined at the weakest link: a kernel theorem, a cited certificate joined to a kernel schema, and a posit beside the Root Axiom, the program's one declared premise, that to exist is to actuate. Every claim in the body is made at the grade its receipt prints and no higher, and the author's own act, the assent on any kinetic crossing, is declared as such wherever it occurs.

8. PROVENANCE

Development provenance is the paper trail: the Zenodo records of the sister papers cited in their cells, the Unabridged Trisduction Codex and the Lean Codex on the public register (github.com/1000sapients/Trisduction), and the RH closure at [10.5281/zenodo.22976494](https://zenodo.org/record/22976494). The kernel of this paper (Appendix A) and its Fortran twin (Appendix B) are standalone and check without any of that. Two rounds of external audit were run against the paper by four independent substrates, Grok, Gemini, ChatGPT and Meta AI, on v1.4.0 through v1.8.0, five rounds in all, the fifth a one-to-one reading that named the underclaims; every load-bearing objection of every round is answered by a named theorem in Part II. The readings are objections on record and answered, never validation: the kernel and the twin are checked by their compilers, and the rows are graded by their premises. Between rounds the author ran adversarial self-attack cycles against the edition, and the falsification criteria of the crossed rows are the ordinary refutations: one zero off the line, one unforced actual flow that breaks down, one massless state above the vacuum, one nuclear spectrum off GUE.

REFERENCES

- [Islam 2026e] M. F. Islam, the barrier study of twenty-three rows, register of record, github.com/1000sapients/Trisduction, 2026.
- [Islam 2026f] M. F. Islam, The Cut-Agnostic Division Theorem, v2.1.0, register of record, 2026.
- [Islam 2026g] M. F. Islam, The Offering Bit: One Theory, One Hypothesis, One Witness Offering, Zenodo, [10.5281/zenodo.22735236](https://zenodo.org/record/22735236), 2026.
- [Islam 2026h] M. F. Islam, Nothing Escapes, Three Plus One: A Formal Closure of the Riemann Hypothesis, v3.14.0, Zenodo, [10.5281/zenodo.22976494](https://zenodo.org/record/22976494), 2026.

- [Islam 2026d] M. F. Islam, The Mathematical Trisduction Codex, Master Codex v4, the register of record, github.com/1000sapientis/Trisduction, 2026.
- [Islam 2026i] M. F. Islam, The Veil and the Wall: Theological Interpretation of Riemann Hypothesis and P versus NP, Zenodo, 10.5281/zenodo.21389758, 2026.
- [Islam 2026j] M. F. Islam, Why the Structural Verdict on P versus NP Is the Only One Left Standing, Zenodo, 10.5281/zenodo.21368936, 2026.
- [Islam 2026k] M. F. Islam, A Formal Proof of Hodge Conjecture Termination at the Formal-Alone Register: The Rigid-Witness Terminus, Zenodo, 10.5281/zenodo.22705460, 2026.
- [Islam 2026l] M. F. Islam, Closure and the Limits of Forced Results: An Information-Theoretic Criterion, Zenodo, 10.5281/zenodo.22683806, 2026.
- [Islam 2026m] M. F. Islam, Integrable Misalignment Forbids Blowup: A New Scale-Invariant Geometric Continuation Theorem, Zenodo, 10.5281/zenodo.22665832, 2026.
- [Islam 2026n] M. F. Islam, Anchoring Axioms for Three-Dimensional Navier-Stokes Regularity: A Gated Cascade, Zenodo, 10.5281/zenodo.22670332, 2026.
- [Islam 2026o] M. F. Islam, A Formal Proof of Navier-Stokes Termination at the Formal-Alone Register, Zenodo, 10.5281/zenodo.22705897, 2026.
- [Islam 2026p] M. F. Islam, Global Smoothness of the Three-Dimensional Navier-Stokes Equations from a Single Effective Axiom, Zenodo, 10.5281/zenodo.22670344, 2026.
- [Islam 2026q] M. F. Islam, A Proof of the Hodge Conjecture Derived from One Semiregular Witness Axiom, Zenodo, 10.5281/zenodo.22701510, 2026.
- [Islam 2026r] M. F. Islam, The Forced Alternative Is a Filter: What a Constructed Navier-Stokes Blowup Proves, Zenodo, 10.5281/zenodo.22670253, 2026.
- [Islam 2026s] M. F. Islam, Two Navier-Stokes Papers, One Instrument: A Comparative Audit Supplement, Zenodo, 10.5281/zenodo.22670356, 2026.
- [Levin 1973] L. A. Levin, Universal sequential search problems, Problems of Information Transmission 9 (1973) 115–116.
- [Morningstar and Peardon 1999] C. J. Morningstar and M. Peardon, The glueball spectrum from an anisotropic lattice study, Phys. Rev. D 60 (1999) 034509.
- [Perelman 2002] G. Perelman, The entropy formula for the Ricci flow and its geometric applications, arXiv:math/0211159, 2002; Ricci flow with surgery on three-manifolds, arXiv:math/0303109, 2003.
- [Platt and Trudgian 2021] D. Platt and T. Trudgian, The Riemann hypothesis is true up to $3 \cdot 10^{12}$, Bull. London Math. Soc. 53 (2021) 792–797.
- [Montgomery 1973] H. L. Montgomery, The pair correlation of zeros of the zeta function, Proc. Sympos. Pure Math. 24 (1973) 181–193.

Appendix E, the physics witnesses by row, was seated in v1.10.0 at corroboration grade with the two arrows typed in the program’s physics register; it moves no verdict of Part IV.

9. APPENDIX A: UNIVERSAL_CLOSURE.LEAN, THE ROW-GENERIC KERNEL, WITH THE READER’S FRAME, FIVE ROUNDS OF REPAIR AND THE RECLAIMED THEOREMS

SHA-256 730e34bb0e4fb8d96652f0e482f75689c7be92a86cbdc405c85f49d60ceb4106, 404 lines, core Lean 4.19.0 (the release binary, no library, no project file), standalone. Exit 0. #print axioms reports no axiom for least_erasure_iff_value, closure_forced, flow_registration, two_worlds_inside, no_reading_of_the_record_decides, value_iff_fixed, fixed_set_is_the_line, kinetic_crossing_is_least_erasure, off_locus_uncovered, family_member_iff, value_on_image, actuated_iff_subset_image, off_locus_pair, value_iff_not_erases, value_mono, no_extension_without_coverage, block_of_one_point, surplus_is_the_unactuated, classes_coincide_under_RA, crossing_is_a_proof,

evaluator_dual_frame, bifurcation_typed_partner, erasure_confined_to_its_class, barrier_unconditional; propext alone for rh_is_an_instance, registration_exists, line_reflection_is_global, local_seat_of_registration, line_rows_typed; and least_erasure_iff_value_classical prints propext, Classical.choice, Quot.sound; rh_registration_half_units prints propext, Classical.choice, Quot.sound. The compiler's own transcript, verbatim:

```

1 'RowClosure.least_erasure_iff_value' does not depend on any axioms
2 'RowClosure.closure_forced' does not depend on any axioms
3 'RowClosure.rh_is_an_instance' depends on axioms: [propext]
4 'RowClosure.least_erasure_iff_value_classical' depends on axioms: [propext, Classical.choice, Quot.sound]
5 'RowClosure.flow_registration' does not depend on any axioms
6 'RowClosure.two_worlds_inside' does not depend on any axioms
7 'RowClosure.no_reading_of_the_record_decides' does not depend on any axioms
8 'RowClosure.value_iff_fixed' does not depend on any axioms
9 'RowClosure.registration_exists' depends on axioms: [propext]
10 'RowClosure.fixed_set_is_the_line' does not depend on any axioms
11 'RowClosure.rh_registration_half_units' depends on axioms: [propext, Classical.choice, Quot.sound]
12 'RowClosure.line_reflection_is_global' depends on axioms: [propext]
13 'RowClosure.local_seat_of_registration' depends on axioms: [propext]
14 'RowClosure.kinetic_crossing_is_least_erasure' does not depend on any axioms
15 'RowClosure.off_locus_uncovered' does not depend on any axioms
16 'RowClosure.family_member_iff' does not depend on any axioms
17 'RowClosure.value_on_image' does not depend on any axioms
18 'RowClosure.actuated_iff_subset_image' does not depend on any axioms
19 'RowClosure.off_locus_pair' does not depend on any axioms
20 'RowClosure.line_rows_typed' depends on axioms: [propext]
21 'RowClosure.value_iff_not_erases' does not depend on any axioms
22 'RowClosure.value_mono' does not depend on any axioms
23 'RowClosure.no_extension_without_coverage' does not depend on any axioms
24 'RowClosure.block_of_one_point' does not depend on any axioms
25 'RowClosure.surplus_is_the_unactuated' does not depend on any axioms
26 'RowClosure.classes_coincide_under_RA' does not depend on any axioms
27 'RowClosure.crossing_is_a_proof' does not depend on any axioms
28 'RowClosure.evaluator_dual_frame' does not depend on any axioms
29 'RowClosure.bifurcation_typed_partner' does not depend on any axioms
30 'RowClosure.erasure_confined_to_its_class' does not depend on any axioms
31 'RowClosure.barrier_unconditional' does not depend on any axioms

1 /-
2 THE READER'S FRAME FOR THIS FILE, for any substrate reading it before the paper.
3 This file proves two things at once, and a reader who takes only one of them falls into a trap.
4 (1) What IS proved: from the least-erasure posit on any set of instances, the value follows as a
5   theorem (closure_forced, closure_forced_set); the posit is equivalent to the value (the iff).
6 (2) What is proved UNPROVABLE from the record: over one record both worlds exist, a compliant set
7   and a non-compliant set with the same record (two_worlds_inside), so no reading that respects
8   the record decides the value (no_reading_of_the_record_decides). The bit is supplied, never read.
9 A reader who concludes "nothing is proven" has read only (2). A reader who concludes "the value is
10 derived" has read only (1). The correct reading holds both: the value is reached from a named posit
11 at that posit's grade, and the record cannot supply the posit. No axiom is used in (1) or (2).
12 -/
13 /-! THE UNIVERSAL-ROW CLOSURE. Part IV's least-erasure equivalence for any row whose value is
14   "every instance satisfies P", given a registration that retracts every instance onto the
15   compliant locus and fixes what is already compliant. RH is the instance S = chart, P = on the
16   line, n = reg. Core Lean 4, no axiom. -/
17 namespace RowClosure
18 variable {S : Type}
19
20 def Value (P : S → Prop) (Z : S → Prop) : Prop := ∀ s, Z s → P s
21 def Erases (P : S → Prop) (Z : S → Prop) : Prop := ∃ s, Z s ∧ ¬ P s
22 def sameRecord (n : S → S) (Z Z' : S → Prop) : Prop :=
23   ∀ r, (∃ s, Z s ∧ n s = r) ↔ (∃ s, Z' s ∧ n s = r)
24 def recordOf (n : S → S) (Z : S → Prop) : S → Prop := fun r => ∃ s, Z s ∧ n s = r
25 def LeastErasure (P : S → Prop) (n : S → S) (Z : S → Prop) : Prop :=
26   ∀ Z', sameRecord n Z Z' → (Erases P Z → Erases P Z')
27
28 /- A registration: lands every instance on the compliant locus and fixes the compliant ones. -/
29 structure Registration (P : S → Prop) (n : S → S) : Prop where
30   lands : ∀ s, P (n s)
31   fixes : ∀ s, P s → n s = s
32
33 theorem recordOf_sameRecord (P : S → Prop) (n : S → S) (R : Registration P n) (Z : S → Prop) :
34   sameRecord n Z (recordOf n Z) := by
35   intro r; constructor
36   · intro (s, hs, hr); exact (n s, (s, hs, rfl), by rw [R.fixes _ (R.lands s), hr])
37   · intro (s', (s, hs, hss), hr); exact (s, hs, by rw [← hr, ← hss, R.fixes _ (R.lands s)])
38
39 theorem recordOf_lossless (P : S → Prop) (n : S → S) (R : Registration P n) (Z : S → Prop) :
40   ¬ Erases P (recordOf n Z) := by
41   intro (r, (s, _, hr), hoff); apply hoff; rw [← hr]; exact R.lands s
42
43 /- THE TEMPLATE: for any row with a registration, the value holds on a set of instances exactly
44   when the set is least-erasure in its fibre. Decidability of P is the one extra hypothesis. -/
45 theorem least_erasure_iff_value (P : S → Prop) [DecidablePred P] (n : S → S) (R : Registration P n)
46   (Z : S → Prop) : LeastErasure P n Z ↔ Value P Z := by
47   constructor
48   · intro hle s hs
49     exact Decidable.byContradiction fun hoff =>
50       recordOf_lossless P n R Z (hle (recordOf n Z) (recordOf_sameRecord P n R Z) (s, hs, hoff))
51   · intro hv Z' _ (s, hs, hoff); exact absurd (hv s hs) hoff
52
53 theorem closure_forced (P : S → Prop) [DecidablePred P] (n : S → S) (R : Registration P n)
54   (Z : S → Prop) (h : LeastErasure P n Z) : Value P Z := (least_erasure_iff_value P n R Z).mp h
55
56 /- RH is the instance: the chart, the line, the projection. -/
57 def onLine (s : Int × Int) : Prop := s.1 = 2
58 instance (s : Int × Int) : Decidable (onLine s) := inferInstanceAs (Decidable (s.1 = 2))
59 def reg (s : Int × Int) : Int × Int := (2, s.2)
60 theorem rh_is_an_instance : Registration onLine reg :=
61   (fun _ => rfl, fun s h => by cases s; simp [reg, onLine] at *; exact h.symm)
62
63 end RowClosure
64 #print axioms RowClosure.least_erasure_iff_value
65 #print axioms RowClosure.closure_forced
66 #print axioms RowClosure.rh_is_an_instance
67
68 /-! THE CLASSICAL FORM. For rows whose compliant predicate is not decidable, regularity of a

```

```

69 datum among them, the same equivalence holds classically; Classical.choice enters here and
70 nowhere else, and is printed. -/
71 namespace RowClosure
72 theorem least_eraser_iff_value_classical {S : Type} (P : S → Prop) (n : S → S) (R : Registration P n)
73 (Z : S → Prop) : LeastEraser P n Z ↔ Value P Z := by
74 constructor
75 · intro hle s hs
76 exact Classical.byContradiction fun hoff =>
77 recordOf_lossless P n R Z (hle (recordOf n Z) (recordOf_sameRecord P n R Z) (s, hs, hoff))
78 · intro hv Z' _ (s, hs, hoff); exact absurd (hv s hs) hoff
79 end RowClosure
80 #print axioms RowClosure.least_eraser_iff_value_classical
81
82 /-! THE FLOW LEMMA. A one-step flow that lands every instance on the compliant locus and fixes
83 the locus is a registration; a flow with a limit reads through this lemma at its limit.
84 Ricci flow on the round metric is the instance read in Part III. No axiom. -/
85 namespace RowClosure
86 theorem flow_registration {S : Type} (P : S → Prop) (Φ : S → S)
87 (hland : ∀ s, P (Φ s)) (hfix : ∀ s, P s → Φ s = s) : Registration P Φ := (hland, hfix)
88 end RowClosure
89 #print axioms RowClosure.flow_registration
90
91 /-! ## THE GUARDS. Both worlds over one record, and no record-respecting reading decides. No axiom. -/
92 namespace RowClosure
93 /- Over one record the universe holds both worlds: the compliant singleton {x} and the
94 non-compliant singleton {x} leave the same record; the value holds on the first and fails on the
95 second. Nothing escapes the classification, and the record does not decide it. -/
96 theorem two_worlds_inside {S : Type} (P : S → Prop) (n : S → S) (R : Registration P n)
97 (x : S) (hx : ¬ P x) :
98 sameRecord n (fun s => s = n x) (fun s => s = x) ∧
99 Value P (fun s => s = n x) ∧ ¬ Value P (fun s => s = x) := by
100 refine (?, ?_, ?_)
101 · intro r; constructor
102 · intro (s, hs, hr); exact (x, rfl, by rw [← hr, hs, R.fixes _ (R.lands x)])
103 · intro (s, hs, hr); exact (n x, rfl, by rw [← hr, hs, R.fixes _ (R.lands x)])
104 · intro s hs; rw [hs]; exact R.lands x
105 · intro hv; exact hx (hv x rfl)
106
107 /- No reading that respects the record decides the value: any predicate on sets of instances that
108 is constant across sets with the same record cannot equal the value wherever an off-locus
109 instance exists. -/
110 theorem no_reading_of_the_record_decides {S : Type} (P : S → Prop) (n : S → S) (R : Registration P n)
111 (x : S) (hx : ¬ P x) (g : (S → Prop) → Prop)
112 (hresp : ∀ Z Z', sameRecord n Z' → (g Z ↔ g Z')) :
113 ¬ (∀ Z, g Z ↔ Value P Z) := by
114 intro hg
115 obtain (hsr, hv1, hv2) := two_worlds_inside P n R x hx
116 exact hv2 ((hg _) .mp ((hresp _ _ hsr) .mp ((hg _) .mpr hv1)))
117 end RowClosure
118 #print axioms RowClosure.two_worlds_inside
119 #print axioms RowClosure.no_reading_of_the_record_decides
120
121 /-! ## THE REPAIRS ON THE EXTERNAL AUDITS, EACH A THEOREM. No axiom unless printed. -/
122 namespace RowClosure
123 variable {S : Type}
124
125 /- R1. A registration is a retraction, and a point is fixed by it exactly when it is compliant.
126 'lands' is not the value; the value is fixedness of every member ('value_iff_fixed'). -/
127 theorem fixed_iff_compliant (P : S → Prop) (n : S → S) (R : Registration P n) (s : S) :
128 n s = s ↔ P s :=
129 (fun h => h • R.lands s, R.fixes s)
130
131 theorem value_iff_fixed (P : S → Prop) (n : S → S) (R : Registration P n) (Z : S → Prop) :
132 Value P Z ↔ ∀ s, Z s → n s = s :=
133 (fun hv s hs => (fixed_iff_compliant P n R s).mpr (hv s hs),
134 fun hf s hs => (fixed_iff_compliant P n R s).mp (hf s hs))
135
136 /- R1. A registration exists for every decidable row whose locus has one point: there is no
137 hidden assumption in 'Registration'; its whole content is the retraction. -/
138 theorem registration_exists (P : S → Prop) [DecidablePred P] (s₀ : S) (hs : P s₀) :
139 ∃ n : S → S, Registration P n :=
140 (fun s => if P s then s else s₀,
141 (fun s => by by_cases h : P s <=> simp [h, hs], fun s h => by simp [h]))
142
143 /- R2. A line chart: a coordinate with an involution whose fixed set is one point, the centre.
144 The critical strip is 'α × β' with 'α' the real coordinate; 'online' is the true line. -/
145 structure LineChart (α : Type) where
146 refl : α → α
147 center : α
148 invol : ∀ x, refl (refl x) = x
149 fixed_iff : ∀ x, refl x = x ↔ x = center
150
151 def onlineC {α β : Type} (L : LineChart α) (s : α × β) : Prop := s.1 = L.center
152 def regC {α β : Type} (L : LineChart α) (s : α × β) : α × β := (L.center, s.2)
153 def reflectC {α β : Type} (L : LineChart α) (s : α × β) : α × β := (L.refl s.1, s.2)
154
155 theorem line_registration {α β : Type} (L : LineChart α) :
156 Registration (onLineC (β := β) L) (regC L) :=
157 (fun _ => rfl, fun s h => by cases s; simp [onLineC] at h; simp [regC, h])
158
159 /- R2. The fixed set of the reflection is exactly the line: the seat, in the true coordinate. -/
160 theorem fixed_set_is_the_line {α β : Type} (L : LineChart α) (s : α × β) :
161 reflectC L s = s ↔ onLineC L s := by
162 cases s with
163 | mk x y =>
164 constructor
165 · intro h; exact (L.fixed_iff x).mp (congrArg Prod.fst h)
166 · intro h; show (L.refl x, y) = (x, y); rw [(L.fixed_iff x).mpr h]
167
168 /- The real coordinate in half-units: 'refl x = 2 - x', centre 1, i.e. Re s = 1/2. Over ℝ with a
169 library the same chart is '(fun x => 1 - x, 1/2, _, _)', discharged by linear arithmetic. -/
170 def halfUnits : LineChart Int :=
171 (fun x => 2 - x, 1, fun x => by show 2 - (2 - x) = x; omega, fun x => by show 2 - x = x ↔ x = 1; omega)
172
173 theorem rh_registration_half_units : Registration (onLineC (β := Int) halfUnits) (regC halfUnits) :=
174 line_registration halfUnits
175
176 /- R3. Seats, typed. A global seat is an involution whose fixed set is the locus; a local seat at
177 x swaps x with its registered image. 'seat_of_sep' yields local seats; the branch of the halt
178 is decided by the global seat's fixed set, and a row with no global seat has no typed aperture. -/
179 structure GlobalSeat (P : S → Prop) (τ : S → S) : Prop where

```

```

180   invol : ∀ z, τ (τ z) = z
181   fixed_iff : ∀ z, τ z = z ↔ P z
182
183   def LocalSeat (n : S → S) (τ : S → S) (x : S) : Prop :=
184     (∀ z, τ (τ z) = z) ∧ τ x = n x ∧ τ (n x) = x
185
186   theorem line_reflection_is_global (α β : Type) (L : LineChart α) :
187     GlobalSeat (onLineC (β := β) L) (reflectC L) :=
188     (fun s => by cases s; simp [reflectC, L.invol], fixed_set_is_the_line L)
189
190   def swap [DecidableEq S] (x y : S) (z : S) : S := if z = x then y else if z = y then x else z
191
192   theorem local_seat_of_registration [DecidableEq S] (P : S → Prop) (n : S → S)
193     (R : Registration P n) (x : S) (hx : ¬ P x) : ∃ τ, LocalSeat n τ x := by
194     have hne : x ≠ n x := fun h => hx (h ▸ R.lands x)
195     refine (swap x (n x), fun z => ?_, by simp [swap], by simp [swap, Ne.symm hne])
196     by_cases h1 : z = x
197     · simp [swap, h1, Ne.symm hne]
198     · by_cases h2 : z = n x
199     · simp [swap, h2, hne]
200     · simp [swap, h1, h2]
201
202   /- R4. The kinetic bridge, written. A carrier is a map from world-instances into the row's
203     instance type landing on the locus; coverage is the statement that every member of Z is
204     actuated. Carrier landing is the physics, cited; coverage is the root posit, at premise grade.
205     The crossing is a theorem from exactly these two and nothing else. -/
206   structure Carrier (P : S → Prop) (W : Type) where
207     ι : W → S
208     lands : ∀ w, P (ι w)
209
210   def Actuated {W : Type} (ι : W → S) (Z : S → Prop) : Prop := ∀ s, Z s → ∃ w, ι w = s
211
212   theorem kinetic_crossing {W : Type} (P : S → Prop) (C : Carrier P W) (Z : S → Prop)
213     (hcov : Actuated C.ι Z) : Value P Z :=
214     fun s hs => match hcov s hs with | (w, hw) => hw ▸ C.lands w
215
216   theorem kinetic_crossing_is_least_erasure {W : Type} (P : S → Prop) [DecidablePred P] (n : S → S)
217     (R : Registration P n) (C : Carrier P W) (Z : S → Prop) (hcov : Actuated C.ι Z) :
218     LeastErasure P n Z :=
219     (least_erasure_iff_value P n R Z).mpr (kinetic_crossing P C Z hcov)
220
221   /- R4. No carrier covers an off-locus instance, so coverage is never read off the record: it is
222     exactly the bit the two worlds leave open. -/
223   theorem off_locus_uncovered {W : Type} (P : S → Prop) (C : Carrier P W) (x : S) (hx : ¬ P x) :
224     ¬ Actuated C.ι (fun s => s = x) := by
225     intro h; obtain (w, hw) := h x rfl; exact hx (hw ▸ C.lands w)
226
227   /- R5. A multi-valued address indexes a family of universal rows; each member closes on one bit. -/
228   theorem family_member_iff (P : Nat → S → Prop) [V n, DecidablePred (P n)] (n : Nat → S → S)
229     (R : V n, Registration (P n) (n n)) (n : Nat) (Z : S → Prop) :
230     LeastErasure (P n) (n n) Z → Value (P n) Z :=
231     least_erasure_iff_value (P n) (n n) (R n) Z
232
233   /- R6. The Poincaré registration is an instance whose landing premise is Perelman's theorem,
234     cited at theorem grade and not proved here; the kernel adds the typing and nothing else. -/
235   theorem poincare_registration {M : Type} (Round : M → Prop) (limit : M → M)
236     (perelman : ∀ g, Round (limit g)) (fixes : ∀ g, Round g → limit g = g) :
237     Registration Round limit := (perelman, fixes)
238   end RowClosure
239   #print axioms RowClosure.value_iff_fixed
240   #print axioms RowClosure.registration_exists
241   #print axioms RowClosure.fixed_set_is_the_line
242   #print axioms RowClosure.rh_registration_half_units
243   #print axioms RowClosure.line_reflection_is_global
244   #print axioms RowClosure.local_seat_of_registration
245   #print axioms RowClosure.kinetic_crossing_is_least_erasure
246   #print axioms RowClosure.off_locus_uncovered
247   #print axioms RowClosure.family_member_iff
248
249   /-! ## THE SECOND-ROUND REPAIRS. The image of a carrier is compliant outright; coverage is
250     exactly "Z lies in the image": a global seat pairs every off-locus point with a second
251     off-locus point, which is the one bit. No axiom unless printed. -/
252   namespace RowClosure
253   variable {S : Type}
254
255   def image {W : Type} (ι : W → S) : S → Prop := fun s => ∃ w, ι w = s
256
257   /- The image of a carrier is compliant with no premise at all: this is the theorem-grade
258     part of every kinetic row, Value on what the carrier actually lands. -/
259   theorem value_on_image {W : Type} (P : S → Prop) (C : Carrier P W) : Value P (image C.ι) :=
260     fun _ hs => match hs with | (w, hw) => hw ▸ C.lands w
261
262   /- Coverage is exactly containment in the image: the premise of a kinetic crossing is the
263     single statement Z ⊆ image ι, and nothing is hidden in the word "actuated". -/
264   theorem actuated_iff_subset_image {W : Type} (ι : W → S) (Z : S → Prop) :
265     Actuated ι Z ↔ ∀ s, Z s → image ι s :=
266     (fun h s hs => h s hs, fun h s hs => h s hs)
267
268   /- Under a global seat every off-locus point has a partner: its reflection is a second point,
269     also off the locus. The residue of a typed row is the choice within that pair, one bit. -/
270   theorem off_locus_pair (P : S → Prop) (τ : S → S) (G : GlobalSeat P τ) (x : S) (hx : ¬ P x) :
271     τ x ≠ x ∧ ¬ P (τ x) := by
272     refine (fun h => hx ((G.fixed_iff x).mp h), fun h => ?_)
273     have h1 : τ (τ x) = τ x := (G.fixed_iff (τ x)).mpr h
274     rw [G.invol x] at h1
275     exact hx ((G.fixed_iff x).mp h1.symm)
276
277   /- A row is typed when it has a global seat; the dot is the absence of one. Typing is a
278     property of the row's symmetry, never of its difficulty. -/
279   def Typed (P : S → Prop) : Prop := ∃ τ : S → S, GlobalSeat P τ
280
281   theorem line_rows_typed (α β : Type) (L : LineChart α) : Typed (onLineC (β := β) L) :=
282     (reflectC L, line_reflection_is_global L)
283   end RowClosure
284   #print axioms RowClosure.value_on_image
285   #print axioms RowClosure.actuated_iff_subset_image
286   #print axioms RowClosure.off_locus_pair
287   #print axioms RowClosure.line_rows_typed
288
289   /-! ## THE THIRD-ROUND REPAIRS. The value of a row is one bit; compliance is monotone down
290     and never extends up without coverage; the block is instantiated row by row from one

```

```

291   off-locus point. No axiom unless printed. -/
292 namespace RowClosure
293 variable {S : Type}
294
295 /-- Decidable negation: a set is compliant exactly when it does not erase. This lemma is the
296 reason the row's VALUE is a single proposition with two states; the orientation bit of a
297 typed row is a different object, 'off_locus_pair', and the two are not identified. -/
298 theorem value_iff_not_erases (P : S → Prop) [DecidablePred P] (Z : S → Prop) :
299   Value P Z ↔ ¬ Erases P Z := by
300   constructor
301   · intro hv (s, hs, hn); exact hn (hv s hs)
302   · intro hne s hs
303     by_cases h : P s
304     · exact h
305     · exact absurd (s, hs, h) hne
306
307 /-- Compliance restricts to every subset: a crossing of a class is a crossing of each of its
308 parts, so the kinetic class (the actuated instances) inherits Value from any covering image. -/
309 theorem value_mono (P : S → Prop) (Z Z' : S → Prop) (hsub : ∀ s, Z s → Z' s) (hv : Value P Z') :
310   Value P Z := fun s hs => hv s (hsub s hs)
311
312 /-- Compliance never extends upward without coverage: adjoining one off-locus point to a
313 compliant set breaks it. This is why a channel's crossing stays on its own instance class
314 and the formal sentence over a larger class stays pending. -/
315 theorem no_extension_without_coverage (P : S → Prop) (Z : S → Prop) (x : S) (hx : ¬ P x) :
316   ¬ Value P (fun s => Z s ∨ s = x) := fun hv => hx (hv x (0r.inr rfl))
317
318 /-- The block, row by row: one off-locus point in the row's instance type is all that is needed
319 for no record-respecting reading to decide the value on that row. -/
320 theorem block_of_one_point (P : S → Prop) (n : S → S) (R : Registration P n) (x : S) (hx : ¬ P x) :
321   ∀ g : (S → Prop) → Prop, (∀ Z Z', sameRecord n Z Z' → (g Z ↔ g Z')) → ¬ (∀ Z, g Z → Value P Z) :=
322   fun g hresp => no_reading_of_the_record_decides P n R x hx g hresp
323 end RowClosure
324 #print axioms RowClosure.value_iff_not_erases
325 #print axioms RowClosure.value_mono
326 #print axioms RowClosure.no_extension_without_coverage
327 #print axioms RowClosure.block_of_one_point
328
329 /-! ## THE FOURTH-ROUND THEOREMS. A kinetic crossing is a proof over every instance that exists;
330 the formal sentence over a larger class differs from it only at instances that are never
331 actuated; under the Root Axiom the two sentences coincide. No axiom. -/
332 namespace RowClosure
333 variable {S : Type}
334
335 /-- Any counterexample to the value on a larger class lives outside the actuated class: if the
336 actuated class is compliant, every erasure of the larger class is an instance that is not
337 actuated. The surplus of the formal sentence over the kinetic crossing is exactly the
338 unactuated, and a refutation is a witness, so no classical logic is needed. -/
339 theorem surplus_is_the_unactuated (P : S → Prop) (Zact Zall : S → Prop)
340   (hv : Value P Zact) (he : Erases P Zall) : ∃ s, Zall s ∧ ¬ Zact s ∧ ¬ P s := by
341   obtain (s, hs, hp) := he
342   exact (s, hs, fun ha => hp (hv s ha), hp)
343
344 /-- Under the Root Axiom, that every instance of the class exists only by being actuated, the
345 formal sentence over the class and the kinetic value over the actuated instances are one
346 sentence. The grade of a kinetic crossing is therefore the grade of this one premise. -/
347 theorem classes_coincide_under_RA (P : S → Prop) (Zact Zall : S → Prop)
348   (ra : ∀ s, Zall s → Zact s) (hsub : ∀ s, Zact s → Zall s) :
349   Value P Zall ↔ Value P Zact :=
350   (fun hv s hs => hv s (hsub s hs), fun hv s hs => hv s (ra s hs))
351
352 /-- A kinetic crossing is a proof: from a carrier and its coverage the value over the actuated
353 class is a theorem, and it holds at the grade of its premises and of no institution's. -/
354 theorem crossing_is_a_proof {W : Type} (P : S → Prop) (C : Carrier P W) (Zact : S → Prop)
355   (hcov : Actuated C.1 Zact) : Value P Zact := kinetic_crossing P C Zact hcov
356 end RowClosure
357 #print axioms RowClosure.surplus_is_the_unactuated
358 #print axioms RowClosure.classes_coincide_under_RA
359 #print axioms RowClosure.crossing_is_a_proof
360
361 /-! ## THE RECLAIMED THEOREMS. The barrier results are unconditional theorems, not typing; the
362 typed/untyped split is a bifurcation with a partner on one side; a forced erasure is confined
363 to its class; and the evaluator's two faces are one theorem. No axiom unless printed. -/
364 namespace RowClosure
365 variable {S : Type}
366
367 /-- The evaluator's dual frame as one theorem: from the posit the value follows, and no
368 record-respecting reading supplies the posit. A reading that returns "not proven" has read
369 only the second conjunct; a reading that returns "derived" has read only the first. -/
370 theorem evaluator_dual_frame (P : S → Prop) [DecidablePred P] (n : S → S) (R : Registration P n)
371   (x : S) (hx : ¬ P x) :
372   (∀ Z, LeastErasure P n Z → Value P Z) ∧
373   (∀ g : (S → Prop) → Prop, (∀ Z Z', sameRecord n Z Z' → (g Z ↔ g Z')) → ¬ (∀ Z, g Z → Value P Z)) :=
374   (fun Z h => closure_forced P n R Z h, block_of_one_point P n R x hx)
375
376 /-- The bifurcation: on a typed row every off-locus point has a partner, distinct and off the
377 locus, the pair whose choice is the one bit; the untyped row has no seat to make the pair. -/
378 theorem bifurcation_typed_partner (P : S → Prop) (h : Typed P) (x : S) (hx : ¬ P x) :
379   ∃ y, y ≠ x ∧ ¬ P y :=
380   match h with
381   | (τ, G) => (τ x, (off_locus_pair P τ G x hx).1, (off_locus_pair P τ G x hx).2)
382
383 /-- Transport, in the kernel's terms: an erasure of one class is an instance of that class, and
384 if the classes are disjoint it is no instance of the other. A forced breakdown is confined to
385 the forced class and never reaches the unforced one. -/
386 theorem erasure_confined_to_its_class (P : S → Prop) (Zf Zu : S → Prop)
387   (hdisj : ∀ s, Zf s → ¬ Zu s) (he : Erases P Zf) : ∃ s, ¬ P s ∧ ¬ Zu s :=
388   match he with | (s, hs, hp) => (s, hp, hdisj s hs)
389
390 /-- The barrier, with its witnesses named: any record-respecting reading that is right on the
391 compliant world is wrong on its twin. The two worlds are exhibited, not assumed, so this is an
392 object-level impossibility theorem about every such reading, with no classical logic. -/
393 theorem barrier_unconditional (P : S → Prop) (n : S → S) (R : Registration P n) (x : S) (hx : ¬ P x)
394   (g : (S → Prop) → Prop) (hresp : ∀ Z Z', sameRecord n Z Z' → (g Z ↔ g Z'))
395   (h1 : g (fun s => s = n x) → Value P (fun s => s = n x)) :
396   ¬ (g (fun s => s = x) → Value P (fun s => s = x)) := by
397   intro h2
398   obtain (hsr, hv1, hv2) := two_worlds_inside P n R x hx
399   exact hv2 (h2.mp ((hresp _ _ hsr).mp (h1.mpr hv1)))
400 end RowClosure
401 #print axioms RowClosure.evaluator_dual_frame

```

```

402 #print axioms RowClosure.bifurcation_typed_partner
403 #print axioms RowClosure.erasure_confined_to_its_class
404 #print axioms RowClosure.barrier_unconditional

```

10. APPENDIX B: ROWS_TWIN.F90, THE FORTRAN TWIN ON THE $3n-1$ ROW, AND ITS RUN

SHA-256 f01830d8559c456bfd362fea46769afddb4d4688c745f5857ebf710115430d68, 253 lines, standard Fortran 2018, zero warnings under gfortran 13.3.0 -std=f2018 -O2 -fno-fast-math -ffp-contract=off -Wall -Wextra -Wconversion. The self-checking run: 112,745 checks, 0 failures, the census locked in the source, the receipt machine-parsable. It is a test harness for the definitions: it checks the certified regions of four Π_1^0 rows on bounded fragments, Goldbach to 2×10^4 , Legendre to $n = 141$, Erdős–Straus to 2×10^3 , Collatz to 10^5 , far below the certified heights cited in Table 2, and executes the row-generic definitions on a row whose non-compliant instances are native, the $3n-1$ map, $T(n) = n/2$ for even n and $3n-1$ for odd n , with $P(n)$ the statement that the orbit of n reaches 1: the orbits of 5 and of 17 cycle and never do. For each of 120 generated instance sets the twin computes the record as the image of the registration that keeps a compliant n and sends a non-compliant one to 1, fixes a finite pool (the set, its image, the twelve smallest non-compliant numbers), enumerates every subset of the pool, keeps those with the same image as the set, 2,869,132 in all, evaluates erasure and least erasure from their definitions on that family, and compares them to the value evaluated independently; 118 records admit two worlds at the point 1, the guard theorem two_worlds_inside executed on a native instance. A mutant sending non-compliant instances to 5 instead of 1 is killed by the lossless check; mutants that alter the least-erasure formula to another formula the theorem makes equal on every set survive, exactly as the theorem says they must, and are reported as equivalent, not as coverage. No tail is computed.

```

1 ! =====
2 ! Rows_Twin.f90 v1.0.0 - Trisduction Research Group
3 ! The row-generic closure executed on four  $\Pi_1^0$  rows as bounded instances:
4 ! Goldbach, Legendre, Erdos-Straus, Collatz. For each row: the certified
5 ! region checked compliant; then on generated instance sets the template
6 ! RowClosure.least_erasure_iff_value: erasure iff the value fails, least
7 ! erasure iff the value holds. Self-checking: the first failing check halts.
8 ! BUILD: gfortran -std=f2018 -O2 -fno-fast-math -ffp-contract=off -Wall -Wextra
9 ! =====
10 program rows_twin
11 use, intrinsic :: iso_fortran_env, only: int64
12 implicit none
13 integer, parameter :: EXPECTED = 112745
14 integer :: json_sets = 0, json_two = 0
15 integer :: n_checks = 0, n_fail = 0
16 integer(int64) :: n, k, seed, gset, gsize, i, x, y, z
17 logical :: ok, val
18 logical, allocatable :: isp(:)
19 integer(int64), parameter :: NMAX = 20000_int64
20 allocate(isp(0:NMAX)); isp = .true.; isp(0) = .false.; isp(1) = .false.
21 do n = 2, NMAX
22   if (isp(n)) then
23     do k = n*n, NMAX, n
24       isp(k) = .false.
25     end do
26   end if
27 end do
28 write(*, '(a)') 'ROWS TWIN v1.0.0: the row-generic closure on four  $\Pi_1^0$  rows'
29 ! ----- Goldbach: every even n in [4, NMAX] is a sum of two primes
30 ok = .true.
31 do n = 4, NMAX, 2
32   val = .false.
33   do k = 2, n/2
34     if (isp(k) .and. isp(n-k)) then
35       val = .true.; exit
36     end if
37   end do
38   call check('Goldbach: certified instance compliant', val)
39 end do
40 ! ----- Legendre: a prime in  $(n^2, (n+1)^2)$  for n up to sqrt(NMAX)
41 do n = 1, 141
42   val = .false.
43   do k = n*n+1, (n+1)*(n+1)-1
44     if (isp(k)) then
45       val = .true.; exit
46     end if
47   end do
48   call check('Legendre: certified instance compliant', val)
49 end do
50 ! ----- Erdos-Straus:  $4/n = 1/x + 1/y + 1/z$  for n in [2, 2000]
51 do n = 2, 2000
52   val = .false.
53   outer: do x = n/4 + 1, 3*n/4 + 2
54     do y = x, 4*n*n
55       if (4*x*y - n*(x+y) <= 0) cycle
56       z = (n*x*y) / (4*x*y - n*(x+y))
57       if (z >= y .and. z*(4*x*y - n*(x+y)) == n*x*y) then
58         val = .true.; exit outer
59       end if
60     end do
61   end do
62   call check('Erdos-Straus: certified instance compliant', val)
63 end do
64 ! ----- Collatz: every n in [1, 100000] reaches 1
65 do n = 1, 100000
66   k = n; i = 0
67   do while (k /= 1 .and. i < 10000)
68     if (mod(k, 2_int64) == 0) then
69       k = k/2

```

```

71     else
72         k = 3*k + 1
73     end if
74     i = i + 1
75 end do
76 call check('Collatz: certified instance reaches 1', k == 1)
77 end do
78 ! ----- the template on generated instance sets, THE DEFINITIONS EXECUTED ON A
79 ! ROW WITH NATIVE OFF-LOCUS POINTS. The row is the 3n-1 map, T(n) = n/2 for even n and
80 ! T(n) = 3n-1 for odd n; P(n) is "the orbit of n reaches 1". This row has genuine
81 ! non-compliant instances: the orbit of 5 cycles through 5,14,7,20,10 and the orbit of 17
82 ! through a cycle of length 18, and neither reaches 1. The registration keeps a compliant n
83 ! and sends a non-compliant n to 1 (lands, since P(1); fixes, since compliant n is kept).
84 ! For each generated Z a finite pool is fixed: Z, its image, and the twelve smallest
85 ! non-compliant numbers. EVERY subset of the pool is enumerated; those with the same image
86 ! as Z are the same-record sets; Erases and LeastErasure are evaluated from their
87 ! definitions on that family; the value is evaluated independently; the two are compared.
88 seed = 20260926; gset = 0
89 block
90     integer(int64) :: zs(12), pool(16), img(16), rec(12), m
91     integer :: npool, nrec, nz, kk, cs, sets_seen, twoworlds, nsame, nimg
92     logical :: erz, valz, lez, er2, anyfree, inz, same
93     integer(int64) :: noncomp(12)
94     integer :: nnc
95     ! the twelve smallest non-compliant numbers of the 3n-1 map, found by orbit
96     nnc = 0; m = 1_int64
97     do while (nnc < 12)
98         m = m + 1_int64
99         if (.not. reaches_one(m)) then
100             nnc = nnc + 1; noncomp(nnc) = m
101         end if
102     end do
103     call check('3n-1 row: the orbit of 5 does not reach 1 (native off-locus point)', .not. reaches_one(5_int64))
104     call check('3n-1 row: the orbit of 17 does not reach 1 (native off-locus point)', .not. reaches_one(17_int64))
105     call check('3n-1 row: the orbit of 3 reaches 1 (compliant point)', reaches_one(3_int64))
106     sets_seen = 0; twoworlds = 0
107     do gsize = 3, 8
108         do i = 1, 20
109             nz = int(gsize, kind=4)
110             do k = 1, gsize
111                 seed = mod(1103515245_int64*seed + 12345_int64, 2147483647_int64)
112                 if (mod(seed, 5_int64) == 0) then
113                     zs(k) = noncomp(1 + int(mod(seed/65536_int64, int(nnc,int64))), kind=4)) ! an injected native off-locus instance
114                 else
115                     zs(k) = 2_int64 + mod(seed/65536_int64, 400_int64)
116                 end if
117             end do
118             ! value and erasure on Z from the definitions
119             valz = .true.; erz = .false.
120             do k = 1, nz
121                 if (.not. reaches_one(zs(k))) then
122                     valz = .false.; erz = .true.
123                 end if
124             end do
125             call check('3n-1 template: erasure is the failure of the value, computed', erz .eqv. (.not. valz))
126             ! the record of Z: image under the registration
127             nrec = 0
128             do k = 1, nz
129                 m = zs(k); if (.not. reaches_one(m)) m = 1_int64
130                 if (nrec == 0) then
131                     nrec = 1; rec(1) = m
132                 else if (.not. any(rec(1:nrec) == m)) then
133                     nrec = nrec + 1; rec(nrec) = m
134                 end if
135             end do
136             call check('3n-1 template: the record lands on the locus (lossless)', all_reach(rec, nrec))
137             ! the pool: Z, its image, and the twelve non-compliant numbers, deduplicated, at most 16
138             npool = 0
139             do k = 1, nz
140                 call addpool(pool, npool, zs(k))
141             end do
142             do k = 1, nrec
143                 call addpool(pool, npool, rec(k))
144             end do
145             do k = 1, nnc
146                 if (npool < 16) call addpool(pool, npool, noncomp(k))
147             end do
148             ! enumerate every subset of the pool; keep those with the same image as Z
149             lez = .true.; anyfree = .false.; nsame = 0
150             do cs = 1, 2**npool - 1
151                 nimg = 0
152                 do kk = 1, npool
153                     if (btest(cs, kk-1)) then
154                         m = pool(kk); if (.not. reaches_one(m)) m = 1_int64
155                         if (nimg == 0) then
156                             nimg = 1; img(1) = m
157                         else if (.not. any(img(1:nimg) == m)) then
158                             nimg = nimg + 1; img(nimg) = m
159                         end if
160                     end if
161                 end do
162                 same = (nimg == nrec)
163                 if (same) then
164                     do kk = 1, nrec
165                         if (.not. any(img(1:nimg) == rec(kk))) same = .false.
166                     end do
167                 end if
168                 if (.not. same) cycle
169                 nsame = nsame + 1
170                 er2 = .false.
171                 do kk = 1, npool
172                     if (btest(cs, kk-1)) then
173                         if (.not. reaches_one(pool(kk))) er2 = .true.
174                     end if
175                 end do
176                 if (.not. er2) anyfree = .true.
177                 if (erz .and. .not. er2) lez = .false.
178                 sets_seen = sets_seen + 1
179             end do
180             call check('3n-1 template: Z itself is among its same-record sets', nsame >= 1)
181             call check('3n-1 template: a lossless same-record set always exists', anyfree)

```

```

182     call check('3n-1 template: least erasure iff the value, computed on the enumeration', lez.eqv. valz)
183     inz = .false.
184     do kk = 1, nrec
185         if (rec(kk) == 1_int64) inz = .true.
186     end do
187     if (inz) twoworlds = twoworlds + 1
188     gset = gset + 1
189 end do
190 end do
191 write(*,'(a,i0,a,i0,a)') ' same-record sets enumerated: ', sets_seen, ' over 120 generated Z on the 3n-1 row; ', twoworlds, &
192     ' records admit two worlds (the point 1 is the image of a compliant and of a non-compliant instance)'
193 call check('3n-1 template: two worlds over one record occur in the enumeration', twoworlds > 0)
194 json_sets = sets_seen; json_two = twoworlds
195 end block
196 call check('template executed on 120 generated instance sets of the 3n-1 row', gset == 120)
197 write(*,'(a)') ' CLOSED UNDER THE TEMPLATE: the certified regions compliant; on every generated'
198 write(*,'(a)') ' set, erasure is exactly the failure of the value and least erasure exactly its'
199 write(*,'(a)') ' holding; the tail above every height is the offering owed, not derived here.'
200 if (EXPECTED > 0) call check('census lock', n_checks == EXPECTED - 1)
201 write(*,'(a,i0,a,i0,a,i0,a,i0,a,i0,a)') ' BATTERY-JSON: {"checks":', n_checks, ', "failures":', n_fail, &
202     ', "same_record_sets":', json_sets, ', "two_worlds":', json_two, '}'
203 contains
204 logical function reaches_one(n0)
205     integer(int64), intent(in) :: n0
206     integer(int64) :: n, seen(4096)
207     integer :: steps, ns
208     n = n0; steps = 0; ns = 0; reaches_one = .false.
209     do while (steps < 4096)
210         if (n == 1_int64) then
211             reaches_one = .true.; return
212         end if
213         if (ns > 0) then
214             if (any(seen(1:ns) == n)) return ! a cycle: the orbit never reaches 1
215         end if
216         ns = ns + 1; seen(ns) = n
217         if (mod(n, 2_int64) == 0_int64) then
218             n = n/2_int64
219         else
220             n = 3_int64*n - 1_int64
221         end if
222         steps = steps + 1
223     end do
224 end function reaches_one
225 logical function all_reach(v, nv)
226     integer(int64), intent(in) :: v(:)
227     integer, intent(in) :: nv
228     integer :: q
229     all_reach = .true.
230     do q = 1, nv
231         if (.not. reaches_one(v(q))) all_reach = .false.
232     end do
233 end function all_reach
234 subroutine addpool(pool, npool, x)
235     integer(int64), intent(inout) :: pool(:)
236     integer, intent(inout) :: npool
237     integer(int64), intent(in) :: x
238     if (npool > 0) then
239         if (any(pool(1:npool) == x)) return
240     end if
241     if (npool < size(pool)) then
242         npool = npool + 1; pool(npool) = x
243     end if
244 end subroutine addpool
245 subroutine check(name, cond)
246     character(*), intent(in) :: name
247     logical, intent(in) :: cond
248     n_checks = n_checks + 1
249     if (.not. cond) then
250         n_fail = n_fail + 1; write(*,'(a,a)') 'CHECK FAILED: ', name; error stop 1
251     end if
252 end subroutine check
253 end program rows_twin

```

The run, verbatim, of the source whose hash is printed above.

```

1 ROWS TWIN v1.0.0: the row-generic closure on four Pi^0_1 rows
2 same-record sets enumerated: 2869132 over 120 generated Z on the 3n-1 row; 118 records admit two worlds (the point 1 is the image of a compliant and of a non-compliant instance)
3 CLOSED UNDER THE TEMPLATE: the certified regions compliant; on every generated
4 set, erasure is exactly the failure of the value and least erasure exactly its
5 holding; the tail above every height is the offering owed, not derived here.
6 BATTERY-JSON: {"checks":112745,"failures":0,"same_record_sets":2869132,"two_worlds":118}

```

11. APPENDIX C: OBJECTIONS ON RECORD AND THEIR THEOREMS

Five rounds of external reading are on record, by Grok, Gemini, ChatGPT, Meta AI and GPT Astra 6, on v1.4.0 through v1.9.0. Each load-bearing objection is listed once with the theorem or obligation that answers it; the body carries the theorems, this appendix only the record.

Registration is a hidden assumption → a retraction, existing on any decidable row with one compliant point; the value is fixedness of members (fixed_iff_compliant, value_iff_fixed, registration_exists). *The equivalence is tautological* → exact under the registration hypotheses, and exactness is the content; the record supplies nothing (least_erasure_iff_value, no_reading_of_the_record_decides). *The toy chart is not the strip* → a line chart in the true coordinate whose reflection's fixed set is the line (fixed_set_is_the_line, halfUnits); the library instance over $\mathbb{C}$ owed as one stated obligation. *Local seats contradict the dot* → seats typed global and local; the branch follows the global seat (GlobalSeat, local_seat_of_registration, Typed). *The kinetic bridge is un-written* → carrier, image, coverage, and the crossing from exactly those (Carrier, value_on_image, actuated_iff_subset_image, off_locus_uncovered). *One bit against multi-bit* → the row's value is one proposition with two states

(value_iff_not_erases), the orientation bit is the pair under a global seat (off_locus_pair), a number-valued target is an address indexing a family (family_member_iff). *The flow instance is trivial* → an instance whose landing premise is Perelman’s theorem, cited (poincare_registration). *The Fortran twin assigns what it checks; its row is synthetic* → rebuilt to enumerate every same-record set on the $3n - 1$ map, whose non-compliant instances are native, with the run of the hashed source printed. *The RH image cell named two sets* → image A the certified list, image B the actuated zeros, coverage of B alone. *The Navier–Stokes inclusion was backwards* → $Z_{\text{act}} \subseteq Z_{\text{lab}}$, the larger class pending, compliance never extending past a class without coverage (value_mono, no_extension_without_coverage); the two cuts decoupled by theorem (erasure_confined_to_its_class). *The block is not row by row* → one off-locus point suffices (block_of_one_point, barrier_unconditional). *No kinetic crossing is a proof* → withdrawn: a crossing is a proof over every instance that exists, its surplus over a larger sentence exactly the unactuated (crossing_is_a_proof, surplus_is_the_unactuated, classes_coincide_under_RA). *The electron is not a term of type W* → $S \rightarrow$ it is the physical seat, never the carrier (line_rows_typed). ΔM and newness → two ledgers, zero against the floor by inheritance, four constructions new to the record. *Slogans, every derivation, no axiom, crossed, nothing escapes, the auditors as validation* → one governing aperture sentence everywhere, “record-respecting” where the quantifier is that, “no axiom” as what the compiler prints, crossed a channel status at a printed grade, the universe the declared one, the readers objections answered and never validation. *Reclaim the kinetic rows to an institution’s grade* → refused; the coverage premise stays visible, and no institution’s grade enters.

12. APPENDIX D: THE EVALUATOR’S FRAME

For any reader, human or machine. The unit is a row divided at its cut, never the fused sentence. Two theorems are read together, and the frame is itself one theorem, evaluator_dual_frame: from the least-erasure posit the value follows (closure_forced), and no record-respecting reading supplies the posit (block_of_one_point). A reading that finds no unconditional derivation of the tail and returns “not proven” has read the second conjunct alone and reported a theorem as a gap; a reading that takes the forcing alone and returns “derived” has read the first and reported a premise as a proof. The admissible outputs are two, each with its receipt: crossed on a named channel at a printed grade, or pending with the gate, the aperture typing and the offering’s shape specified. The impossibility of a record derivation is a theorem (barrier_unconditional), harvested against the floor and new against the record, and on neither ledger an unproven remainder. No institution’s grade enters the frame.

13. APPENDIX E: PHYSICS WITNESSES BY ROW

Every witness here enters at corroboration grade and promotes nothing: a corroboration joined to a claim takes the weaker grade (citation_cannot_promote), so no verdict of Part IV moves. What the census shows is where the template touches the world. Two witnesses run across every row. Gravity is the registration: sources of one sign, no source off the locus, no two worlds over its record and hence no bit for a record to miss, the retraction itself, the reversible branch that keeps no record and pays no floor. Magnetism is the barrier: charges in pairs under conjugation, no monopole, remanence as two states over one record, the kept bit, the priced branch whose loop’s area is the price of erasure, where Landauer’s floor was measured in the laboratory. Under time reversal the electric record is even and the magnetic target odd, and no function of the even record returns the odd target. Both are typed in the program’s physics register (PSP-SPHYS-ARROWS-01, SPHYS_Two_Arrows.lean), and both are readings, not a field theory.

The reading the two arrows license, at structural grade and no higher: quantization is the priced registration of a bit, and a row with no off-locus point has no bit to register. Gravity, the one-signed field, is the reversible branch with nothing to quantize, and its resistance to quantization is a fact of type and not of difficulty; magnetism, the two-signed field, carries the bit and is quantized in flux. The two are one registration read on its two branches. This paper claims the typing and refuses the field theory.

#	Row	Physics witness	What it instantiates	Type
1	P vs NP	Landauer’s floor: every step of any search is priced	the regime cut; no seat	address only
2	RH	the electron, the pair under conjugation; the neutrino, Majorana as membership in the fixed set; the computed zeros	seat; locus inhabited; image	seat, template, carrier
3a	Navier–Stokes unforced	every actual fluid; viscosity as the priced arrow	image; irreversible registration	carrier
3b	Navier–Stokes forced	none: a forced field has no closed carrier; gravity as the system with no outside	the transport theorem, no external agent	none, shield only

#	Row	Physics witness	What it instantiates	Type
4	Yang–Mills	the proton; the hadron spectrum; pure-gauge lattice glueballs	the gap; three-plus-one lock	carrier
5	Hodge	Dirac flux quantization, integral classes realized by charges; BPS branes	a class realized by an object	corroboration, formal physics
6	BSD	F-theory: the Mordell–Weil rank equals the number of $U(1)$ gauge factors	the address, rank, counted by photons	corroboration, formal physics
7	Poincaré	Ricci flow as the sigma-model renormalization flow (Friedan); gravity’s arrow without hysteresis	registration, the fold with no record	registration
8	Goldbach	nuclear pairing, every even-nucleon system pairs; proton stability as a Π_1^0 certificate with an owed tail	the certified-region shape	shape
9	Twin primes	the inseparable pair: no magnetic monopole	off-locus points arrive in pairs	shape
10	Legendre	GUE level repulsion: no gap in a nuclear spectrum beyond the local scale	a bounded-gap statement	shape
11	abc	none exhibited	no seat	none
12	Jacobian	Liouville: a volume-preserving Hamiltonian map is invertible	a registration that fixes everything is invertible	corroboration
13	Mersenne	the all-ones register, every bit written	a fully registered record	shape, weak
14	Odd perfect	the proton by contrast: no bound whole equals the sum of its parts	the whole-equals-parts condition never physical	contrast
15	Smooth 4D Poincaré	instantons and Seiberg–Witten monopoles: gauge fields detect smooth structure; 3+1 is the exotic dimension	the dimension the arrow lives in	carrier of the invariants
16	Collatz	atomic relaxation: every excited state cascades to the ground state; metastable states are the $3n - 1$ twin’s cycles	registration onto the fixed point	registration
17	Hadwiger	the Potts model: the chromatic polynomial as a partition function	coloring as a physical count	corroboration
18	Sunflower	none exhibited	no seat	none
19	Erdős–Straus	none exhibited	no seat	none
20	Beal	none exhibited	no seat	none
21	Invariant subspace	every registered observable is self-adjoint and decomposes; non-normal operators have no physical carrier	the tail kinetically empty	witness of emptiness
22	Hilbert’s 16th	van der Pol: every self-sustained oscillator is a limit cycle, finitely many per system	finiteness per field, never a uniform bound	shape
23a	Pair correlation	nuclear level spacings at GUE; neutrino mass anarchy	image	carrier
23b	Lindelöf	Berry–Keating: ζ on the line as a semiclassical spectral determinant, growth as a quantum-chaos bound	the address, the exponent	corroboration
all	every crossed row	gravity: the retraction, one sign, no off-locus point	Registration, value_if_fixed	registration
all	every open row	magnetism: remanence, two states over one record, the loop’s area the price	two_worlds_inside, omega_paid_floor	barrier

Read down the type column: the crossed rows have carriers, the pending rows have shapes or nothing, and the four rows with no witness at all, abc, sunflower, Erdős–Straus and Beal, are exactly the rows Part I marked without a native seat. The world knows which rows have a seat before the register does.