Inspection Test Record 003

INSITU COLUMNS PREPOUR, PLACEMENT & FINISH



Contract:	Wellington Health Level / Location:				I&D Rep:				
Client:	Maxcon Drawing Reference:				Initial:				
Job No:	IM0124			Date:					
			•	T	,		1		
No.		Process	Pass	Fail	NCR Ref	Initial	Date		
1	Check Setting Out For:							S E	
	RL (top of column) RL may vary depending on location of work.							T O	
	Set-out of all columns.							U T	
2	Check Existing Slab Conditions For:								
	Confirm correct RL of slab below and						F O R M W O R K		
	Confirm column transition below is cor								
3	Check Formwork For:								
	Ensure column formwork has a suitable								
	All penetrations and cast-in items are								
	Formwork has been inspected/signed								
4	Check Reinforcement For:								
	All reinforcement to be placed in accord						R E I N F O R C E M E N T		
	Reinforcement is securely fixed in place.								
	Where reinforcement has been tack w								
	Correct bar spacing.								
	Correct bar diameter.								
	Correct bar lap lengths.								
	Correct concrete cover.								
	Column starter bars comply with size, spacing and projection of columns over.								
5	Check Preparation For Pour:								
	Pour area cleaned before pour to ensure column is free of standing water, debris, oils, objectionable coatings & fragments. Ensure temperatures when pouring are within acceptable criteria.							P	
	Tester ordered - (7 and 28 day samples) 1 batch of tests or thereof for every 50m3 placed or one test sample per day each day Placing of concrete (method) - Chute, Kibble or Pump. Concrete vibration to be completed with use of vibrator motor (minimum requirement of 300rpm).							R E P O U R	
	Concrete is to be finished to the correct	Concrete is to be finished to the correct RL.							
	Check to ensure pour rate/pour height recommendation (if more than a single								
	HOLD	Signature by I&D Representative							
	HOLD	Signature by Client Representative						Ī	
6	Stripping Of Formwork:							P L	
	Visual check on columns once stripped to ensure no cracking has occurred. Visual check on columns once stripped to ensure that there are no boney concrete areas due to lack of vibration.							A C E M E N	
	Ensure patching to columns has been undertaken for any defect areas that are visible.							Ť	
Date Poured:			Total m³:						
Attached:									
Comments:									