

## Inspection and Test Plan - Control and Supervision of the Works

Document # FHC-ITP-025

Revision: 01

Date: 15/09/25

Client: Yarra Trams

Vic & Eliz St Stage 2

Construction Process:

Prepared by: Name:

Date: 15/09/25

Brandon Iredale

Reviewed by :
Name: Patrick Fagan

Approved by :

Name: Shaun Kent

Contract No: 8B5600

Project:

Specifications: AS 3600-2018, VicRoads Standard Specification

Section 606, 607, 610, 611, 614

Structural Concrete Construction

Structure / Component:

Location: Vic and Elizabeth St

Signed :

Signed :

Date : 15/09/25

Signed :

Date : 15/09/25

Lot No: Lot Details: Lot Size/ Quantity:

Item	Task/Activity Description	Inspection / Controls and Verification Detail					HP/ WP/	Responsibility	Checked by:			
No.		Frequency	Acceptance Criteria	Reference Documents	Inspection / Test Method	Record of conformity	MP/ AP/ IP/ TP/ SCP	Project Engineer Site Engineer Superintendent Surveyor Foreman	Client	Fulton Hogan	FH's Sub- contractor	Date
1	Design and Submissions											
1.1	Check for correct documentation	Prior to commencing any activity	Ensure that all employees and subcontractors are: - using the correct and complete set of drawings -all drawings are the latest revision	Drawings and drawing registers	Visual inspection	This ITP signed	HP*	Fulton Hogan Engineer	N/A		N/A	
1.2	Implementation of all measures and controls	Prior to commencing any activity	All necessary measures and controls are being implemented, that is: PSP, EMP, TMP, SWMS & WP	PSP, EMP, TMP, JSEA, SWMS, WP	Visual Inspection	This ITP signed	HP*	Fulton Hogan Engineer	N/A		N/A	
1.3	Approval of mix design	Prior to the first concrete pour	Structural Concrete Design & Submission ITP completed and signed	610.07	Verify	This ITP signed	HP*	Fulton Hogan Engineer	N/A		N/A	
1.4	Reinforcement schedule	Prior to concrete pour	Reinforcement schedule has been prepared for the reinforcement supply, to ensure that it achieves the specified tolerances on member dimensions, concrete cover and specified locations	611.04	Verify	This ITP signed	IP	Fulton Hogan Engineer	N/A		N/A	
2	Construction/Erection of Formwork											
2.1	Excavation	Prior to concrete pour	Excavations shall be to the depths shown on the drawings and that necessary to provide satisfactory foundation	Contract Drawings	Inspect	This ITP signed	IP	Fulton Hogan Engineer	N/A		N/A	
2.2	Construction Methodology	Prior to erection	Constructed in such a manner so it can be removed without damage to the concrete. Formwork/shoring shall be placed in locations where steel reinforcement and other fixtures can be inspected, and sufficiently tight at joints to prevent loss of slurry	614.04 614.06	Verify	This ITP signed	IP	Fulton Hogan Engineer	N/A		N/A	
3	Pre-Pour Planning and Inspection											
3.1	Excavation/Foundation – Blinding, sealing or foundation concrete		Blinding, sealing or foundation concrete shall not be placed until the bottom of the excavation has been reviewed by the Superintendent. Inspected and approved by the Superintendent. Hold Point released by the Superintendent.	602.03	Verify	This ITP signed	НР	Fulton Hogan			N/A	

Item		Inspection / Controls and Verification Detail						Responsibility	Checked by:			
No.	Task/Activity Description	Frequency	Acceptance Criteria	Reference Documents	Inspection / Test Method	Record of conformity	TP/	Project Engineer Site Engineer Superintendent Surveyor Foreman	Client	Fulton Hogan	FH's Sub- contractor	Date
3.2	Formwork levels and position	Prior to concrete pour	formwork within the tolerance. Any errors in the level or positioning of formwork is to be corrected prior to placing concrete	614.06	Verify	This ITP signed	SCP HP*	Fulton Hogan Engineer	N/A		N/A	
3.3	Location of splices	Schedule Review	In lapped splices, the bars shall be placed in contact and the specified cover shall be maintained.	611.11	Inspect	This ITP signed	IP	Fulton Hogan	N/A		N/A	
3.4	Cleaning formwork	Each concrete pour	Concrete shall not be placed until all foreign material has been completely removed from the forms	610.18 (a) (iii)	Verify	This ITP signed	IP	Fulton Hogan	N/A		N/A	
3.5	Correct forms, reinforcements, rag bolt assembly and embedments	Prior to concrete pour	Superintendent confirms that the inspected formwork, reinforcement, rag bolt assembly and embedments comply with the project drawings and specifications.	610.18 (a)	Verify	This ITP signed	НР	Fulton Hogan			N/A	
3.6	Reinforcement assembly of piles	Prior to concrete pour	Reinforcement and/or concrete shall not be placed until the proposed method of removing mud, loose rock or similar materials has been reviewed by the Superintendent.	610.17 (b),( c), (d)	Verify	This ITP signed	НР	Fulton Hogan	N/A		N/A	
3.7	Monitoring weather	Prior to concrete pour	Concrete shall not be place when temperature is <5°C or > 35°C All steel components that are in contact with the concrete shall be cooled to below 32°C before concrete is placed	610.17 (b),( c), (d)	Verify	This ITP signed	IP	Fulton Hogan	N/A		N/A	
4	Placing and Finishing Concrete						!					
4.1	Carry out sampling of concrete	Each concrete pour	Sampling in accordance with 610.16	610.16	Checklist	This ITP signed	IP	Fulton Hogan	N/A		N/A	
4.2	Discharge time	Each concrete pour	Discharge time (concrete placed and compacted) < 90 minutes from batch time unless approved otherwise.		Verify	This ITP signed. Accurate Site Notes & Load Mapping	IP	Fulton Hogan	N/A		N/A	
4.3	Methodology of placement (structural)	Each concrete pour	Concrete shall be tansported, handled and placed in a manner that will prevent segregation or loss of materials Concrete shall not be moved horizontally by vibrators In continuous pours the max. time lag between truckloads on site is 25 minutes	610.18	Verify	This ITP signed	IP	Fulton Hogan	N/A		N/A	
5	Post-Pour Details and Inspection											
5.1	Curing	Each concrete pour	Sufficient time shall be given for the concrete to cure prior to loading.	610.23	Verify	This ITP signed	IP	Fulton Hogan	N/A		N/A	
5.2	Formwork removal	Each concrete pour	Formwork shall be removed carefully and in such a manner as to avoid damage to the member or the concrete surfaces and maintain safety at all stages of removal. Formwork and formwork supports shall not be disturbed or adjusted during the concreting operation	610.25	Verify	This ITP signed	IP	Fulton Hogan	N/A		N/A	
5.3	Positional tolerance and dimensions of concrete members and piles	Each concrete pour	Dimensions within the tolerances given in Cl 17.5 of AS3600 (-10,+40)	AS3600 CI 17.5 607.06	Verify	This ITP signed Post Pour Checklist completed	IP	Fulton Hogan	N/A		N/A	

File Name:

Item		Inspection / Controls and Verification Detail						Responsibility	Checked by:			
No.	Task/Activity Description	Frequency	Acceptance Criteria	Reference Documents	Inspection / Test Method	Record of conformity	AP/ IP/ TP/ SCP	Project Engineer Site Engineer Superintendent Surveyor Foreman	Client	Fulton Hogan	FH's Sub- contractor	Date
	Concrete Sampling and Testing	Prior to lot closure	Concrete sampled and tested for Compressive Strength, and Slump.	610.16	Verify	This ITP signed	TP	Fulton Hogan	N/A		N/A	
5.5	As Built Drawings	Prior to lot closure	Recorded of as-built drawings	Fulton Hogan Procedure	Verify	This ITP signed	IP	Fulton Hogan	N/A		N/A	

## Final Inspection

The signature below verifies that this ITP has been completed in accordance with the FH's Quality system Procedures and verifies lot compliance with specifications.

Print Name: Position: Signature: Date: / /

Legen	Legend										
HP	Hold Point	Work shall not proceed past the HP until released by the Superintendent	IP	Inspection point	Formal Inspection to be done and recorded						
HP*	FH Hold Point	Work shall not proceed past the HP* until released by FH	TP	Test Point	Product compliance test to be undertaken and recorded/reported						
WP	Witness Point	An inspection which must be witnessed by the Superintendent	SCP	Survey conformance point	A qualified surveyor to check product/section/structure and report						
AP	Approval Point	Written or verbal approval given by the Superintendent									