

Data Structures

UCS301

Array

Department of CSE

Thapar Institute of Engineering and Technology, Patiala

Array ADT

`float` marks[10];

- The simplest but useful data structure.
- Assign single name to a homogeneous collection of instances of one abstract data type.
 - All array elements are of same type, so that a pre-defined equal amount of memory is allocated to each one of them.
- Individual elements in the collection have an associated index value that depends on array dimension.


Contd...

- One-dimensional and two-dimensional arrays are commonly used.
- Multi-dimensional arrays can also be defined.
- Usage:
 - Used frequently to store relatively permanent collections of data.
 - Not suitable if the size of the structure or the data in the structure are constantly changing.


Memory Storage

Memory Storage – One Dimensional Array

```
int student[4];
```



```
float marks[3];
```



Memory Storage – Two Dimensional Array

```
int marks[3][5];
```

- Can be visualized in the form of a matrix as

	Col 0	Col 1	Col 2	Col 3	Col 4
Row 0	marks[0][0]	marks[0][1]	marks[0][2]	marks[0][3]	marks[0][4]
Row 1	marks[1][0]	marks[1][1]	marks[1][2]	marks[1][3]	marks[1][4]
Row 2	marks[2][0]	marks[2][1]	marks[2][2]	marks[2][3]	marks[2][4]

Contd...

- Row-major order

(0,0)	(0,1)	(0,2)	(0,3)	(0,4)	(1,0)	(1,1)	(1,2)	(1,3)	(1,4)	(2,0)	(2,1)	(2,2)	(2,3)	(2,4)
Row0					Row1					Row2				

- Column-major order

(0,0)	(1,0)	(2,0)	(0,1)	(1,1)	(2,1)	(0,2)	(1,2)	(2,2)	(0,3)	(1,3)	(2,3)	(0,4)	(1,4)	(2,4)
Col0			Col1			Col2			Col3			Col4		

Array Address Computation

1D array – address calculation

- Let A be a one dimensional array.
- Formula to compute the address of the I^{th} element of an array ($A[I]$) is:

$$\text{Address of } A[I] = B + W * (I - LB)$$


where,

B = Base address/address of first element, i.e. $A[LB]$.

W = Number of bytes used to store a single array element.

I = Subscript of element whose address is to be found.

LB = Lower limit / Lower Bound of subscript, if not specified assume 0 (zero).



1D array – address calculation


- Let A be a one dimensional array.
- Formula to compute the address of the I^{th} element of an array ($A[I]$) is:

$$\text{Address of } A[I] = B + W * (I - LB)$$

Given:

$B = 100$, $W = 4$, and $LB = 0$

$$A[0] = 100 + 4 * (0 - 0) = 100$$



1D array – address calculation

- Let A be a one dimensional array.
- Formula to compute the address of the I^{th} element of an array ($A[I]$) is:

$$\text{Address of } A[I] = B + W * (I - LB)$$

Given:

$$B = 100, W = 4, \text{ and } LB = 0$$


$$A[1] = 100 + 4 * (1 - 0) = 104$$

$$A[2] = 100 + 4 * (2 - 0) = 108$$

$$A[3] = 100 + 4 * (3 - 0) = 112$$

$$A[4] = 100 + 4 * (4 - 0) = 116$$

$$A[5] = 100 + 4 * (5 - 0) = 120$$



Example – 1

- Similarly, for a character array where a single character uses 1 byte of storage.
- If the base address is 1200 then,

$$\text{Address of } A[I] = B + W * (I - LB)$$

$$\text{Address of } A[0] = 1200 + 1 * (0 - 0) = 1200$$

$$\text{Address of } A[1] = 1200 + 1 * (1 - 0) = 1201$$

...

$$\text{Address of } A[10] = 1200 + 1 * (10 - 0) = 1210$$

Example – 2

- If **LB** = 5, **Loc(A[LB])** = 1200, and **W** = 4.
- Find **Loc(A[8])**.

$$\text{Address of } A[I] = B + W * (I - LB)$$

$$\begin{aligned}\text{Loc}(A[8]) &= \text{Loc}(A[5]) + 4 * (8 - 5) \\ &= 1200 + 4 * 3 \\ &= 1200 + 12 \\ &= 1212\end{aligned}$$

Example – 3


- Base address of an array **B[1300.....1900]** is **1020** and size of each element is 2 bytes in the memory. Find the address of **B[1700]**.

$$\text{Address of } A[I] = B + W * (I - LB)$$


- Given: **B** = 1020, **W** = 2, **I** = 1700, **LB** = 1300

$$\begin{aligned}\text{Address of } B[1700] &= 1020 + 2 * (1700 - 1300) \\ &= 1020 + 2 * 400 \\ &= 1020 + 800 \\ &= 1820\end{aligned}$$

Row-major



	[0]	[1]	[2]	[3]
[0]	1	2	3	4
[1]	5	6	7	8
[2]	9	10	11	12



Column-major

2D Array – Address Calculation

- If **A** be a two dimensional array with **M** rows and **N** columns. We can compute the address of an element at **I**th row and **J**th column of an array (**A[I][J]**).

B = Base address/address of first element, i.e. **A[LBR][LBC]**

I = Row subscript of element whose address is to be found

J = Column subscript of element whose address is to be found

W = Number of bytes used to store a single array element

LBR = Lower limit of row/start row index of matrix, if not given
assume 0

LBC = Lower limit of column/start column index of matrix, if not
given assume 0

N = Number of column of the given matrix

M = Number of row of the given matrix

Row-major

1
2
3
4
5
6
7
8
9
10
11
12



	[0]	[1]	[2]	[3]
[0]	1	2	3	4
[1]	5	6	7	8
[2]	9	10	11	12

$$M = 3$$

$$N = 4$$


$$\text{Address of } A[2][1] = B + W * (4 * (2 - 0) + (1 - 0))$$

$$\text{Address of } A[I][J] = B + W * (N * (I - LBR) + (J - LBC))$$

M = 3

N = 4

	[0]	[1]	[2]	[3]
[0]	1	2	3	4
[1]	5	6	7	8
[2]	9	10	11	12



Column-major

Address of A [2][1] =

$$\mathbf{B + W * ((2 - 0) + 3 * (1 - 0))}$$

Address of A [I][J] =

$$\mathbf{B + W * ((I - LBR) + M * (J - LBC))}$$

Contd...

- Row Major

$$\text{Address of } A[I][J] = B + W * (N * (I - LBR) + (J - LBC))$$

- Column Major

$$\text{Address of } A [I][J] = B + W * ((I - LBR) + M * (J - LBC))$$

- Note: **A[LBR...UBR, LBC...UBC]**

$$M = (UBR - LBR) + 1$$

$$N = (UBC - LBC) + 1$$

Example – 4

- Suppose elements of array **A[5][5]** occupies **4** bytes, and the address of the first element is **49**. Find the address of the element **A[4][3]** when the storage is row major.

$$\text{Address of } A[I][J] = B + W * (N * (I - LBR) + (J - LBC))$$

- Given: **B = 49**, **W = 4**, **M = 5**, **N = 5**, **I = 4**, **J = 3**, **LBR = 0**,
LBC = 0.

$$\begin{aligned}\text{Address of } A[4][3] &= 49 + 4 * (5 * (4 - 0) + (3 - 0)) \\ &= 49 + 4 * (23) \\ &= 49 + 92 \\ &= 141\end{aligned}$$

Example – 5

- An array **X [-15...10, 15...40]** requires **one** byte of storage. If beginning location is **1500** determine the location of **X [0][20]** in column major.

$$\text{Address of } A[I][J] = B + W * [(I - LBR) + M * (J - LBC)]$$

- Number of rows (**M**) = (**UBR – LBR**) + 1 = [10 – (- 15)] +1 = 26
- Given: **B** = 1500, **W** = 1, **I** = 0, **J** = 20, **LBR** = -15, **LBC** = 15, **M** = 26

$$\begin{aligned}\text{Address of } X[0][20] &= 1500 + 1 * [(0 - (-15)) + 26 * (20 - 15)] \\ &= 1500 + 1 * [15 + 26 * 5] \\ &= 1500 + 1 * [145] \\ &= 1645\end{aligned}$$

Example – 6

- A two-dimensional array defined as **A [-4 ... 6] [-2 ... 12]** requires **2 bytes** of storage for each element. If the array is stored in row major order form with the address **A[4][8]** as **4142**. Compute the address of **A[0][0]**.

$$\text{Address of } A[I][J] = B + W (N (I - LBR) + (J - LBC))$$

- **Given:**

$$W = 2, LBR = -4, LBC = -2$$

$$\#rows = M = 6 + 4 + 1 = 11 \quad \#columns = N = 12 + 2 + 1 = 15$$

$$\text{Address of } A[4][8] = 4142$$

- **Address of A[4][8] = B + 2 (15 (4 - (-4)) + (8 - (-2)))**

$$4142 = B + 2 (15 (4 + 4) + (8 + 2)) = B + 2 (15 (8) + 10) = B + 2 (120 + 10)$$

$$4142 = B + 260$$

$$\text{Thus, } B = 4142 - 260 = 3882$$

- **Now, Address of A[0][0] = 3882 + 2 (15 (0 - (-4)) + (0 - (-2)))**

$$= 3882 + 2 (15(4) + 2) = 3882 + 2 (62)$$

$$= 3882 + 124$$

$$= 4006$$

Array Basic Operations

Operations on Linear Data Structures

- Traversal
- Search – Linear and Binary.
- Insertion
- Deletion
- Sorting – Different algorithms are there.
- Merging – During the discussion of Merge Sort.

TRAVERSAL

Processing each element in the array.

Example – Print all the array elements.

Algorithm arrayTraverse(A,n)

Input: An array **A** containing **n** integers.

Output: All the elements in **A** get printed.

1. for i = 0 to n-1 do
2. Print A[i]

```
1. int arrayTraverse(int arr[], int n)
2. {
3.     for (int i = 0; i < n; i++)
4.         cout << "\n" << arr[i];
5. }
```

Example – Find minimum element in the array.

Algorithm arrayMinElement(A,n)

Input: An array **A** containing **n** integers.

Output: The minimum element in **A**.

1. min = 0
2. for i = 1 to n-1 do
3. if A[min] > A[i]
4. min = i
5. return A[min]

```
1. int arrayMinElement(int arr[], int n)
2. { int min = 0;
3.   for (int i = 1; i < n; i++)
4.   { if (arr[i] < arr[min])
5.     min = i;
6.   }
7.   return arr[min];
8. }
```

Search

Find the location of the element with
a given value.

Linear Search

- Used if the array is unsorted.
- Example:

Search 7 in the following array

i→0→1→2→3→4→5→6

a[]

10	5	1	6	2	9	7	8	3	4
----	---	---	---	---	---	---	---	---	---

Found at index 6

Search 11 in the following array

i → 0 → 1 → 2 → 3 → 4 → 5 → 6 → 7 → 8 → 9 → 10

a[]	10	5	1	6	2	9	7	8	3	4	Not found
-----	----	---	---	---	---	---	---	---	---	---	-----------

Contd...

Algorithm linearSearch(A,n,num)

Input: An array **A** containing **n** integers and number **num** to be searched.

Output: Index of **num** if found, otherwise -1.

1. for i = 0 to n-1 do
2. if A[i] == num
3. return i
4. return -1

```
1. int linearSearch(int a[], int n, int num)
2. { for (int i = 0; i < n; i++)
3.     if (a[i] == num)
4.         return i;
5.     return -1;
6. }
```

Binary search

Find an element in a sorted array:

- 1. Divide:* Check middle element.
- 2. Conquer:* Recursively search 1 subarray.
- 3. Combine:* Trivial.

Binary search

Find an element in a sorted array:

- 1. Divide:* Check middle element.
- 2. Conquer:* Recursively search 1 subarray.
- 3. Combine:* Trivial.

Example: Find 9

3 5 7 8 9 12 15

Binary search

Find an element in a sorted array:

- 1. Divide:* Check middle element.
- 2. Conquer:* Recursively search 1 subarray.
- 3. Combine:* Trivial.

Example: Find 9



Binary search

Find an element in a sorted array:

- 1. Divide:* Check middle element.
- 2. Conquer:* Recursively search **1** subarray.
- 3. Combine:* Trivial.

Example: Find **9**

3

5

7

8

9

12

15

Binary search

Find an element in a sorted array:

- 1. Divide:* Check middle element.
- 2. Conquer:* Recursively search **1** subarray.
- 3. Combine:* Trivial.

Example: Find **9**

3

5

7

8

9

12

15

Binary search

Find an element in a sorted array:

- 1. Divide:* Check middle element.
- 2. Conquer:* Recursively search 1 subarray.
- 3. Combine:* Trivial.

Example: Find 9

3 5 7 8 9 12 15

Binary search

Find an element in a sorted array:

- 1. Divide:* Check middle element.
- 2. Conquer:* Recursively search 1 subarray.
- 3. Combine:* Trivial.

Example: Find 9

3 5 7 8 9 12 15



Pseudo Code of Binary Search

Iterative

```
BinarySearch(A[1..n], K)
   $l \leftarrow 1$ ;  $r \leftarrow n$ 
  while  $l \leq r$  do
     $m \leftarrow (l + r) / 2$ 
    if  $K = A[m]$  return  $m$ 
    else if  $K < A[m]$   $r \leftarrow m - 1$ 
    else  $l \leftarrow m + 1$ 
  return -1
```

Recursive

```
BinarySearch(A[1..n], l, r, K)
  while  $l \leq r$  do
     $m \leftarrow (l + r) / 2$ 
    if  $K = A[m]$  return  $m$ 
    else if  $K < A[m]$ 
      BinarySearch(A[1..n], l, m-1, K)
    else
      BinarySearch(A[1..n], m+1, r, K)
  return -1
```

Insertion

Insert an element in the array

Deletion

Delete an element from the array

Insertion and Deletion

	0	1	2	3	4	5	6	7	8	9
a[]	8	6	3	4	5					

- Insert 2 at index 1

	0	1	2	3	4	5	6	7	8	9
a[]	8	6	3	4	5					
		2	6	3	4	5				

- Delete the value at index 2

	0	1	2	3	4	5	6	7	8	9
a[]	8	2	6	3	4	5				
			3	4	5					

Algorithm – Insertion

Algorithm insertElement(A,n,num,indx)

Input: An array **A** containing **n** integers and the number **num** to be inserted at index **indx**.

Output: Successful insertion of **num** at **indx**.

1. for $i = n - 1$ to $indx$ do

2. $A[i + 1] = A[i]$

3. $A[indx] = num$

4. $n = n + 1$

```
1. void insert(int a[], int num, int pos)
2. { for(int i = n-1; i >= pos; i--)
3.     a[i+1] = a[i];
4.     a[pos] = num;
5.     n++;
6. }
```

Algorithm – Deletion

Algorithm deleteElement(A,n,indx)

Input: An array **A** containing **n** integers and the index **indx** whose value is to be deleted.

Output: Deleted value stored initially at **indx**.

1. temp = A[indx]

2. for i = indx to n – 2 do

3. A[i] = A[i + 1]


4. n = n – 1

5. return temp


```
1. int deleteElement(int a[], int pos)
2. { int temp = a[pos];
3.   for(int i = pos; i <= n-2; i++)
4.     a[i] = a[i+1];
5.   n--;
6.   return temp;
7. }
```

Bubble Sort

Bubble Sort – Ascending



Bubble Sort – Descending



Algorithm – Bubble Sort

Algorithm bubbleSort(A,n)


Input: An array **A** containing **n** integers.

Output: The elements of **A** get sorted in increasing order.

1. **for** $i = 1$ to $n - 1$ **do**
2. **for** $j = 0$ to $n - i - 1$ **do**
3. **if** $A[j] > A[j + 1]$
4. Exchange $A[j]$ with $A[j+1]$

In all the cases, complexity is of the order of n^2 .

Optimized Bubble Sort?



Algorithm – Optimized Bubble Sort

Algorithm bubbleSortOpt(A,n)

Input: An array **A** containing **n** integers.

Output: The elements of **A** get sorted in increasing order.

```
1.  for i = 1 to n - 1
2.    flag = true
3.    for j = 0 to n - i - 1 do
4.      if A[j] > A[j + 1]
5.        flag = false
6.        Exchange A[j] with A[j+1]
7.    if flag == true
8.      break;
```

The best case complexity reduces to the order of n , but the worst and average is still n^2 . So, overall the complexity is of the order of n^2 again.

Sparse Matrix


Sparse Matrix

- A matrix is sparse if many of its elements are zero.
- A matrix that is not sparse is dense.
- Two possible representations
 - Array (also known as triplet)
 - Linked list

$$\begin{bmatrix} 0 & 0 & 0 & 2 \\ 0 & 6 & 0 & 0 \\ 0 & 0 & 0 & 9 \\ 0 & 5 & 4 & 0 \end{bmatrix}$$

Array representation

	[0]	[1]	[2]	[3]	[4]	[5]
[0]	15	0	0	22	0	-15
[1]	0	11	3	0	0	0
[2]	0	0	0	-6	0	0
[3]	0	0	0	0	0	0
[4]	91	0	0	0	0	0
[5]	0	0	28	0	0	0



Row	Col	Value
6	6	8
0	0	15
0	3	22
0	5	-15
1	1	11
1	2	3
2	3	-6
4	0	91
5	2	28

Operations

- Transpose
- Addition
- Multiplication

Transpose

	[0]	[1]	[2]	[3]	[4]	[5]
[0]	15	0	0	22	0	-15
[1]	0	11	3	0	0	0
[2]	0	0	0	-6	0	0
[3]	0	0	0	0	0	0
[4]	91	0	0	0	0	0
[5]	0	0	28	0	0	0

Row	Col	Value
6	6	8
0	0	15
0	3	22
0	5	-15
1	1	11
1	2	3
2	3	-6
4	0	91
5	2	28

Original

Row	Col	Value
6	6	8
0	0	15
3	0	22
5	0	-15
1	1	11
2	1	3
3	2	-6
0	4	91
2	5	28

Column Major

	[0]	[1]	[2]	[3]	[4]	[5]
[0]	15	0	0	0	91	0
[1]	0	11	0	0	0	0
[2]	0	3	0	0	0	28
[3]	22	0	-6	0	0	0
[4]	0	0	0	0	0	0
[5]	-15	0	0	0	0	0

Row	Col	Value
6	6	8
0	0	15
0	4	91
1	1	11
2	1	3
2	5	28
3	0	22
3	2	-6
5	0	-15

Row Major

Addition

	[0]	[1]	[2]	[3]	[4]	[5]			[0]	[1]	[2]	[3]	[4]	[5]
[0]	15	0	0	22	0	-15	+	[0]	15	0	0	0	91	0
[1]	0	11	3	0	0	0		[1]	0	11	0	0	0	0
[2]	0	0	0	-6	0	0		[2]	0	3	0	0	0	28
[3]	0	0	0	0	0	0		[3]	22	0	-6	0	0	0
[4]	91	0	0	0	0	0		[4]	0	0	0	0	0	0
[5]	0	0	28	0	0	0		[5]	-15	0	0	0	0	0

=		[0]	[1]	[2]	[3]	[4]	[5]
	[0]	30	0	0	22	91	-15
	[1]	0	22	3	0	0	0
	[2]	0	3	0	-6	0	28
	[3]	22	0	-6	0	0	0
	[4]	91	0	0	0	0	0
	[5]	-15	0	28	0	0	0

Addition

Counter = 14

Row	Col	Value
6	6	8
0	0	15
0	3	22
0	5	-15
1	1	11
1	2	3
2	3	-6
4	0	91
5	2	28



Row	Col	Value
6	6	8
0	0	15
0	4	91
1	1	11
2	1	3
2	5	28
3	0	22
3	2	-6
5	0	-15

Row	Col	Value
6	6	14
0	0	30
0	3	22
0	4	91
0	5	-15
1	1	22
1	2	3
2	1	3
2	3	-6
2	5	28
3	0	22
3	2	-6
4	0	91
5	0	-15
5	2	28

Multiplication

- Compute $A \times B$
- First take transpose of B.
- Multiply only if the corresponding elements are present and add them for each position in the resultant matrix.

Multiplication

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]
[0]	0	10	0	12			[0]	0	0	8	0		[0]			
[1]	0	0	0	0	×		[1]	0	0	0	23	=	[1]			
[2]	0	0	5	0			[2]	0	0	9	0		[2]			
[3]	15	12	0	0			[3]	20	25	0	0		[3]			

Multiplication

	[0]	[1]	[2]	[3]															
[0]	0	10	0	12			[0]	0	0	8	0			[0]	240				
[1]	0	0	0	0	×		[1]	0	0	0	23	=		[1]					
[2]	0	0	5	0			[2]	0	0	9	0			[2]					
[3]	15	12	0	0			[3]	20	25	0	0			[3]					

Multiplication

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]
[0]	0	10	0	12	×	[0]	0	0	8	0	=	[0]	240	300		
[1]	0	0	0	0		[1]	0	0	0	23		[1]				
[2]	0	0	5	0		[2]	0	0	9	0		[2]				
[3]	15	12	0	0		[3]	20	25	0	0		[3]				

Multiplication

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]
[0]	0	10	0	12	×	[0]	0	0	8	0	=	[0]	240	300	0	
[1]	0	0	0	0		[1]	0	0	0	23		[1]				
[2]	0	0	5	0		[2]	0	0	9	0		[2]				
[3]	15	12	0	0		[3]	20	25	0	0		[3]				

Multiplication

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]	
[0]	0	10	0	12			[0]	0	0	8	0		[0]	240	300	0	230
[1]	0	0	0	0	×		[1]	0	0	0	23	=	[1]				
[2]	0	0	5	0			[2]	0	0	9	0		[2]				
[3]	15	12	0	0			[3]	20	25	0	0		[3]				

Multiplication

	[0]	[1]	[2]	[3]
[0]	0	10	0	12
[1]	0	0	0	0
[2]	0	0	5	0
[3]	15	12	0	0

 \times

	[0]	[1]	[2]	[3]
[0]	0	0	8	0
[1]	0	0	0	23
[2]	0	0	9	0
[3]	20	25	0	0

 $=$

	[0]	[1]	[2]	[3]
[0]	240	300	0	230
[1]	0			
[2]				
[3]				

Multiplication

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]
[0]	0	10	0	12	×	[0]	0	0	8	0	=	[0]	240	300	0	230
[1]	0	0	0	0		[1]	0	0	0	23		[1]	0	0	0	0
[2]	0	0	5	0		[2]	0	0	9	0		[2]	0	0	45	0
[3]	15	12	0	0		[3]	20	25	0	0		[3]	0	0	120	276

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]
[0]	0	10	0	12	×	[0]	0	0	0	20	=	[0]				
[1]	0	0	0	0		[1]	0	0	0	25		[1]				
[2]	0	0	5	0		[2]	8	0	9	0		[2]				
[3]	15	12	0	0		[3]	0	23	0	0		[3]				

Multiplication

	[0]	[1]	[2]	[3]
[0]	0	10	0	12
[1]	0	0	0	0
[2]	0	0	5	0
[3]	15	12	0	0

×

	[0]	[1]	[2]	[3]
[0]	0	0	8	0
[1]	0	0	0	23
[2]	0	0	9	0
[3]	20	25	0	0

=

	[0]	[1]	[2]	[3]
[0]	240	300	0	230
[1]	0	0	0	0
[2]	0	0	45	0
[3]	0	0	120	276

	[0]	[1]	[2]	[3]
[0]	0	10	0	12
[1]	0	0	0	0
[2]	0	0	5	0
[3]	15	12	0	0

×

	[0]	[1]	[2]	[3]
[0]	0	0	0	20
[1]	0	0	0	25
[2]	8	0	9	0
[3]	0	23	0	0

=

	[0]	[1]	[2]	[3]
[0]	240			
[1]				
[2]				
[3]				

Multiplication

	[0]	[1]	[2]	[3]				[0]	[1]	[2]	[3]				[0]	[1]	[2]	[3]
[0]	0	10	0	12		[0]	0	0	8	0		[0]	240	300	0	230		
[1]	0	0	0	0	×	[1]	0	0	0	23	=	[1]	0	0	0	0		
[2]	0	0	5	0		[2]	0	0	9	0		[2]	0	0	45	0		
[3]	15	12	0	0		[3]	20	25	0	0		[3]	0	0	120	276		

	[0]	[1]	[2]	[3]				[0]	[1]	[2]	[3]				[0]	[1]	[2]	[3]
[0]	0	10	0	12		[0]	0	0	0	20		[0]	240	300				
[1]	0	0	0	0	×	[1]	0	0	0	25	=	[1]						
[2]	0	0	5	0		[2]	8	0	9	0		[2]						
[3]	15	12	0	0		[3]	0	23	0	0		[3]						

Multiplication

	[0]	[1]	[2]	[3]				[0]	[1]	[2]	[3]				[0]	[1]	[2]	[3]
[0]	0	10	0	12		[0]	0	0	8	0		[0]	240	300	0	230		
[1]	0	0	0	0	×	[1]	0	0	0	23	=	[1]	0	0	0	0		
[2]	0	0	5	0		[2]	0	0	9	0		[2]	0	0	45	0		
[3]	15	12	0	0		[3]	20	25	0	0		[3]	0	0	120	276		

	[0]	[1]	[2]	[3]				[0]	[1]	[2]	[3]				[0]	[1]	[2]	[3]
[0]	0	10	0	12		[0]	0	0	0	20		[0]	240	300	0			
[1]	0	0	0	0	×	[1]	0	0	0	25	=	[1]						
[2]	0	0	5	0		[2]	8	0	9	0		[2]						
[3]	15	12	0	0		[3]	0	23	0	0		[3]						

Multiplication

	[0]	[1]	[2]	[3]
[0]	0	10	0	12
[1]	0	0	0	0
[2]	0	0	5	0
[3]	15	12	0	0

×

	[0]	[1]	[2]	[3]
[0]	0	0	8	0
[1]	0	0	0	23
[2]	0	0	9	0
[3]	20	25	0	0

=

	[0]	[1]	[2]	[3]
[0]	240	300	0	230
[1]	0	0	0	0
[2]	0	0	45	0
[3]	0	0	120	276

	[0]	[1]	[2]	[3]
[0]	0	10	0	12
[1]	0	0	0	0
[2]	0	0	5	0
[3]	15	12	0	0

×

	[0]	[1]	[2]	[3]
[0]	0	0	0	20
[1]	0	0	0	25
[2]	8	0	9	0
[3]	0	23	0	0

=

	[0]	[1]	[2]	[3]
[0]	240	300	0	230
[1]				
[2]				
[3]				

Multiplication

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]
[0]	0	10	0	12		[0]	0	0	8	0		[0]	240	300	0	230
[1]	0	0	0	0	×	[1]	0	0	0	23	=	[1]	0	0	0	0
[2]	0	0	5	0		[2]	0	0	9	0		[2]	0	0	45	0
[3]	15	12	0	0		[3]	20	25	0	0		[3]	0	0	120	276

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]
[0]	0	10	0	12		[0]	0	0	0	20		[0]	240	300	0	230
[1]	0	0	0	0	×	[1]	0	0	0	25	=	[1]	0			
[2]	0	0	5	0		[2]	8	0	9	0		[2]				
[3]	15	12	0	0		[3]	0	23	0	0		[3]				

Multiplication

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]
[0]	0	10	0	12	×	[0]	0	0	8	0	=	[0]	240	300	0	230
[1]	0	0	0	0		[1]	0	0	0	23		[1]	0	0	0	0
[2]	0	0	5	0		[2]	0	0	9	0		[2]	0	0	45	0
[3]	15	12	0	0		[3]	20	25	0	0		[3]	0	0	120	276

	[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]			[0]	[1]	[2]	[3]
[0]	0	10	0	12	×	[0]	0	0	0	20	=	[0]	240	300	0	230
[1]	0	0	0	0		[1]	0	0	0	25		[1]	0	0	0	0
[2]	0	0	5	0		[2]	8	0	9	0		[2]	0	0	45	0
[3]	15	12	0	0		[3]	0	23	0	0		[3]	0	0	120	276

Multiplication

Counter = 0

Row	Col	Value
4	4	5
0	1	10
0	3	12
2	2	5
3	0	15
3	1	12

Row	Col	Value
4	4	5
0	3	20
1	3	25
2	0	8
2	2	9
3	1	23

Row	Col	Value
4	4	5
0	2	8
1	3	23
2	2	9
3	0	20
3	1	25

[illegible]

Multiplication

Counter = 6

Row	Col	Value
4	4	5
0	1	10
0	3	12
2	2	5
3	0	15
3	1	12

Row	Col	Value
4	4	5
0	3	20
1	3	25
2	0	8
2	2	9
3	1	23

Row	Col	Value
4	4	6
0	0	240
0	1	300
0	3	230
2	2	45
3	2	120
3	3	276

	[0]	[1]	[2]	[3]
[0]	240	300	0	230
[1]	0	0	0	0
[2]	0	0	45	0
[3]	0	0	120	276