

# Contents

## 1 Basic

### 1.1 vimrc

```
se nu rnu bs=2 ru mouse=a cin et ts=4 sw=4 sts=4
syn on
filetype indent on
inoremap {<CR> {<CR>}<Esc>O
```

### 1.2 IncreaseStackSize

```
//stack resize(change esp to rsp if 64-bit system)
asm( "mov %0,%%esp\n" :: "g"(mem+10000000) );
// craziest way
static void run_stack_sz(void(*func)(),size_t stsize){
    char *stack, *send;
    stack=(char *)malloc(stsize);
    send=stack+stsize-16;
    send=(char *)((uintptr_t)send/16*16);
    asm volatile(
        "mov %%rsp, (%0)\n"
        "mov %0, %%rsp\n"
        :
        : "r" (send));
    func();
    asm volatile(
        "mov (%0), %%rsp\n"
        :
        : "r" (send));
    free(stack);
}
```

### 1.3 Pragma optimization

```
#pragma GCC optimize("Ofast,no-stack-protector")
#pragma GCC optimize("no-math-errno,unroll-loops")
#pragma GCC target("sse,sse2,sse3,ssse3,sse4")
#pragma GCC target("popcnt,abm,mmx,avx,tune=native")
```

### 1.4 Debugger

```
#!/usr/bin/env python3
import subprocess as sp
os_name = __import__('platform').system()
cmd,prefix = [],""
if os_name == 'Windows':
    cmd=["cmd", "/C"]
else:
    cmd = ["bash", "-c"]
    prefix = "./"
def GetTestData(exe):
    myout=sp.check_output(cmd+["%s%s"%(prefix, exe)])
    return myout.decode("utf8")
def Judge(a,b,testdata):
    f = open("test.in", "w+")
    f.write(testdata)
    f.close()
    c=sp.check_output(cmd+["%s%s<test.in"%(prefix, a)])
    d=sp.check_output(cmd+["%s%s<test.in"%(prefix, b)])
    if not c == d:
        print("answer: %s"%c.decode("utf8"),end="")
        print("output: %s"%d.decode("utf8"),end="")
        print("WA!")
        return False
    return True
if __name__ == '__main__':
    cnt = 0
    isOK = True
    while isOK:
        cnt += 1
        print(cnt)
        isOK=Judge("sol", "mysol", GetTestData("gen"))
```

## 1.5 Quick Random

```
template<class T, T x1, T x2, T x3, int y1, int y2, int y3>
struct PRNG {
    using S = typename std::make_signed<T>::type;
    T s;
    PRNG(T _s = 0) : s(_s) {}
    T next() {
        T z = (s += x1);
        z = (z ^ (z >> y1)) * x2;
        z = (z ^ (z >> y2)) * x3;
        return z ^ (z >> y3);
    }
    T next(T n) { return next() % n; }
    S next(S l, S r) { return l + next(r - l + 1); }
    T operator()() { return next(); }
    T operator()(T n) { return next(n); }
    S operator()(S l, S r) { return next(l, r); }
    static T gen(T s) { return PRNG(s)(); }
    template<class U>
    void shuffle(U first, U last) {
        size_t n = last - first;
        for (size_t i = 0; i < n; i++)
            swap(first[i], first[next(i + 1)]);
    }
};
using R32 = PRNG<uint32_t, 0x9E3779B1, 0x85EBCA6B,
0xC2B2AE35, 16, 13, 16>;
R32 r32;
using R64 = PRNG<uint64_t, 0x9E3779B97F4A7C15,
0xBF58476D1CE4E5B9, 0x94D049BB133111EB, 30, 27, 31>;
R64 r64;
```

## 1.6 IO Optimization

```
static inline int gc() {
    static char buf[1 << 20], *p = buf, *end = buf;
    if (p == end) {
        end = buf + fread(buf, 1, 1 << 20, stdin);
        if (end == buf) return EOF;
        p = buf;
    }
    return *p++;
}
template < typename T >
static inline bool gn( T &_ ) {
    register int c = gc(); register T __ = 1; _ = 0;
    while(( '0' < c || c < '9' ) && c != EOF && c != '-' ) c = gc();
    if (c == '-') { __ = -1; c = gc(); }
    if (c == EOF) return false;
    while( '0' <= c && c <= '9' ) _ = _ * 10 + c - '0', c = gc();
    _ *= __;
    return true;
}
template < typename T, typename ...Args >
static inline bool gn( T &x, Args &...args )
{ return gn(x) && gn(args...); }
```

## 2 Data Structure

### 2.1 BigInt

```
class BigInt {
private:
    using lld = int_fast64_t;
    #define PRINTF_ARG PRIdFAST64
    #define LOG_BASE_STR "9"
    static constexpr lld BASE = 1000000000;
    static constexpr int LOG_BASE = 9;
    vector<lld> dig;
    bool neg;
    inline int len() const { return (int) dig.size(); }
    inline int cmp_minus(const BigInt& a) const {
        if (len() == 0 && a.len() == 0) return 0;
        if (neg ^ a.neg) return (int) a.neg * 2 - 1;
        if (len() != a.len())
            return neg ? a.len() - len() : len() - a.len();
        for (int i = len() - 1; i >= 0; i--) if (dig[i] != a.dig[i])
            return neg ? a.dig[i] - dig[i] : dig[i] - a.dig[i];
    }
};
```

```
return 0;
}
inline void trim() {
    while (!dig.empty() && !dig.back()) dig.pop_back();
    if (dig.empty()) neg = false;
}
public:
    BigInt(): dig(vector<lld>()), neg(false) {}
    BigInt(lld a): dig(vector<lld>()) {
        neg = a < 0; dig.push_back(abs(a));
        trim();
    }
    BigInt(const string& a): dig(vector<lld>()) {
        assert(!a.empty()); neg = (a[0] == '-');
        for (int i = ((int) a.size()) - 1; i >= neg; i -= LOG_BASE) {
            lld cur = 0;
            for (int j = min(LOG_BASE - 1, i - neg); j >= 0; j--)
                cur = cur * 10 + a[i - j] - '0';
            dig.push_back(cur);
        } trim();
    }
    inline bool operator<(const BigInt& a) const {
        return cmp_minus(a) < 0;
    }
    inline bool operator<=(const BigInt& a) const {
        return cmp_minus(a) <= 0;
    }
    inline bool operator==(const BigInt& a) const {
        return cmp_minus(a) == 0;
    }
    inline bool operator!=(const BigInt& a) const {
        return cmp_minus(a) != 0;
    }
    inline bool operator>(const BigInt& a) const {
        return cmp_minus(a) > 0;
    }
    inline bool operator>=(const BigInt& a) const {
        return cmp_minus(a) >= 0;
    }
    BigInt operator-() const {
        BigInt ret = *this;
        ret.neg ^= 1;
        return ret;
    }
    BigInt operator+(const BigInt& a) const {
        if (neg) return -(-(*this) + (-a));
        if (a.neg) return (*this) - (-a);
        int n = max(a.len(), len());
        BigInt ret; ret.dig.resize(n);
        lld pro = 0;
        for (int i = 0; i < n; i++) {
            ret.dig[i] = pro;
            if (i < a.len()) ret.dig[i] += a.dig[i];
            if (i < len()) ret.dig[i] += dig[i];
            pro = 0;
            if (ret.dig[i] >= BASE) pro = ret.dig[i] / BASE;
            ret.dig[i] -= BASE * pro;
        }
        if (pro != 0) ret.dig.push_back(pro);
        return ret;
    }
    BigInt operator-(const BigInt& a) const {
        if (neg) return -(-(*this) - (-a));
        if (a.neg) return (*this) + (-a);
        int diff = cmp_minus(a);
        if (diff < 0) return -(a - (*this));
        if (diff == 0) return 0;
        BigInt ret; ret.dig.resize(len(), 0);
        for (int i = 0; i < len(); i++) {
            ret.dig[i] += dig[i];
            if (i < a.len()) ret.dig[i] -= a.dig[i];
            if (ret.dig[i] < 0) {
                ret.dig[i] += BASE;
                ret.dig[i + 1]--;
            }
        }
        ret.trim();
        return ret;
    }
    BigInt operator*(const BigInt& a) const {
        if (!len() || !a.len()) return 0;
        BigInt ret; ret.dig.resize(len() + a.len() + 1);
        ret.neg = neg ^ a.neg;
        for (int i = 0; i < len(); i++)
            for (int j = 0; j < a.len(); j++) {
                ret.dig[i + j] += dig[i] * a.dig[j];
                if (ret.dig[i + j] >= BASE) {
                    lld x = ret.dig[i + j] / BASE;
                    ret.dig[i + j + 1] += x;
                    ret.dig[i + j] -= x * BASE;
                }
            }
        ret.trim();
        return ret;
    }
};
```

```

    ret.trim();
    return ret;
}
BigInt operator/(const BigInt& a) const {
    assert(a.len());
    if(len() < a.len()) return 0;
    BigInt ret; ret.dig.resize(len()-a.len()+1);
    ret.neg = a.neg;
    for(int i=len()-a.len();i>=0;i--){
        lld l = 0, r = BASE;
        while(r-l > 1){
            lld mid = (l+r)>>1;
            ret.dig[i] = mid;
            if(ret*a<=(neg?-(*this):(*this))) l = mid;
            else r = mid;
        }
        ret.dig[i] = l;
    }
    ret.neg ^= neg; ret.trim();
    return ret;
}
BigInt operator%(const BigInt& a) const {
    return (*this) - (*this) / a * a;
}
friend BigInt abs(BigInt a){
    a.neg = 1; return a;
}
friend void swap(BigInt& a, BigInt& b){
    swap(a.dig, b.dig); swap(a.neg, b.neg);
}
friend istream& operator>>(istream& ss, BigInt& a){
    string s; ss >> s; a = s;
    return ss;
}
friend ostream& operator<<(ostream& ss, BigInt& a){
    if(a.len() == 0) return ss << '0';
    if(a.neg) ss << '-';
    ss << a.dig.back();
    for(int i=a.len()-2;i>=0;i--){
        ss<<setw(LOG_BASE)<<setfill('0')<<a.dig[i];
        return ss;
    }
    inline void print() const {
        if(len() == 0){putchar('0');return;}
        if(neg) putchar('-');
        printf("%" PRINTF_ARG, dig.back());
        for(int i=len()-2;i>=0;i--){
            printf("%0" LOG_BASE_STR PRINTF_ARG, dig[i]);
        }
    }
    #undef PRINTF_ARG
    #undef LOG_BASE_STR
};

```

## 2.2 Dark Magic

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/priority_queue.hpp>
using __gnu_pbds::pairing_heap_tag;
using __gnu_pbds::binary_heap_tag;
using __gnu_pbds::binomial_heap_tag;
using __gnu_pbds::rc_binomial_heap_tag;
using __gnu_pbds::thin_heap_tag;
template<typename T>
using pbds_heap=__gnu_pbds::prioity_queue<T,less<T>,\
    pairing_heap_tag>;

using __gnu_pbds::rb_tree_tag;
using __gnu_pbds::ov_tree_tag;
using __gnu_pbds::splay_tree_tag;
template<typename T>
using ordered_set = __gnu_pbds::tree<T,\
    __gnu_pbds::null_type,less<T>,rb_tree_tag,\
    __gnu_pbds::tree_order_statistics_node_update>;
template<typename A,typename B>
using hTable1=__gnu_pbds::cc_hash_table<A,B>;
template<typename A,typename B>
using hTable2=__gnu_pbds::gp_hash_table<A,B>;
int main(){
    ordered_set<int> ss;
    ss.insert(1); ss.insert(5);
    assert(*ss.find_by_order(0)==1);
    assert(ss.order_of_key(-1)==0);
    pbds_heap pq1, pq2;
    pq1.push(1); pq2.push(2);
    pq1.join(pq2);
}

```

```

assert(pq2.size()==0);
auto it = pq1.push(87);
pq1.modify(it, 19);
return 0;
}

```

## 2.3 SkewHeap

```

template < typename T, typename cmp = less< T > >
class SkewHeap{
private:
    struct SkewNode{
        T x;
        SkewNode *lc, *rc;
        SkewNode( T a = 0 ) : x( a ), lc( 0 ), rc( 0 ) {}
    } *root;
    cmp CMP_;
    size_t count;
    SkewNode* Merge( SkewNode* a, SkewNode* b ) {
        if ( !a or !b ) return a ? a : b;
        if ( CMP_( a->x, b->x ) ) swap( a, b );
        a -> rc = Merge( a->rc, b );
        swap( a -> lc, a->rc );
        return a;
    }
public:
    SkewHeap(): root( 0 ), count( 0 ) {}
    size_t size() { return count; }
    bool empty() { return count == 0; }
    T top() { return root->x; }
    void clear(){ root = 0; count = 0; }
    void push ( const T& x ) {
        SkewNode* a = new SkewNode( x );
        count += 1; root = Merge( root, a );
    }
    void join( SkewHeap& a ) {
        count += a.count; a.count = 0;
        root = Merge( root, a.root );
    }
    void pop() {
        count--; root = Merge( root->lc, root->rc );
    }
    friend void swap( SkewHeap& a, SkewHeap& b ) {
        swap( a.root, b.root ); swap( a.count, b.count );
    }
};

```

## 2.4 Disjoint Set

```

class DJS{
private:
    vector< int > fa, sz, sv;
    vector< pair< int*, int > > opt;
    inline void assign( int *k, int v ) {
        opt.emplace_back( k, *k );
        *k = v;
    }
public:
    inline void init( int n ) {
        fa.resize( n ); iota( fa.begin(), fa.end(), 0 );
        sz.resize( n ); fill( sz.begin(), sz.end(), 1 );
        opt.clear();
    }
    int query( int x ) {
        return ( fa[ x ] == x ) ? x : query( fa[ x ] );
    }
    inline void merge( int a, int b ) {
        int af = query( a ), bf = query( b );
        if( af == bf ) return;
        if( sz[ af ] < sz[ bf ] ) swap( af, bf );
        assign( &fa[ bf ], fa[ af ] );
        assign( &sz[ af ], sz[ af ] + sz[ bf ] );
    }
    inline void save() {sv.push_back( (int)opt.size() );}
    inline void undo() {
        int ls = sv.back(); sv.pop_back();
        while ( ( int ) opt.size() > ls ) {
            pair< int*, int > cur = opt.back();
            *cur.first = cur.second;
            opt.pop_back();
        }
    }
};

```

```
};
```

## 2.5 LiChao Segment Tree

```
namespace lichao {
struct line {
    long long a, b;
    line(): a(0), b(0) {}
    line(long long a, long long b): a(a), b(b) {}
    long long operator()(int x) const {return a*x+b;}
};
line st[maxc * 4];
int sz, lc[maxc * 4], rc[maxc * 4];
int gnode() {
    st[sz] = line(1e9, 1e9);
    lc[sz] = -1, rc[sz] = -1;
    return sz++;
}
void init() { sz = 0; }
void add(int l, int r, line tl, int o) {
    bool lcp = st[o](l) > tl(l);
    bool mcp = st[o>((l + r) / 2) > tl((l + r) / 2);
    if (mcp) swap(st[o], tl);
    if (r - l == 1) return;
    if (lcp != mcp) {
        if (lcp == -1) lc[o] = gnode();
        add(l, (l + r) / 2, tl, lc[o]);
    } else {
        if (rc[o] == -1) rc[o] = gnode();
        add((l + r) / 2, r, tl, rc[o]);
    }
}
long long query(int l, int r, int x, int o) {
    if (r - l == 1) return st[o](x);
    if (x < (l + r) / 2) {
        if (lc[o] == -1) return st[o](x);
        return min(st[o](x), query(l, (l+r)>>1, x, lc[o]));
    } else {
        if (rc[o] == -1) return st[o](x);
        return min(st[o](x), query((l+r)>>1, r, x, rc[o]));
    }
}
}
```

## 2.6 Treap

```
namespace Treap{
#define sz( x ) ( ( x ) ? ( ( x )->size ) : 0 )
struct node{
    int size;
    uint32_t pri;
    node *lc, *rc;
    node() : size(0), pri(rand()), lc( 0 ), rc( 0 ) {}
    void pull() {
        size = 1;
        if ( lc ) size += lc->size;
        if ( rc ) size += rc->size;
    }
};
node* merge( node* L, node* R ) {
    if ( not L or not R ) return L ? L : R;
    if ( L->pri > R->pri ) {
        L->rc = merge( L->rc, R );
        L->pull();
        return L;
    } else {
        R->lc = merge( L, R->lc );
        R->pull();
        return R;
    }
}
void split_by_size( node*rt, int k, node*&L, node*&R ) {
    if ( not rt ) L = R = nullptr;
    else if( sz( rt->lc ) + 1 <= k ) {
        L = rt;
        split_by_size( rt->rc, k-sz(rt->lc)-1, L->rc, R );
        L->pull();
    } else {
        R = rt;
        split_by_size( rt->lc, k, L, R->lc );
        R->pull();
    }
}
}
```

```
#undef sz
}
```

## 2.7 SparseTable

```
template < typename T, typename Cmp_ = less< T > >
class SparseTable {
private:
    vector< vector< T > > tbl;
    vector< int > lg;
    T cv( T a, T b ) {
        return Cmp_()( a, b ) ? a : b;
    }
public:
    void init( T arr[], int n ) {
        // 0-base
        lg.resize( n + 1 );
        lg[ 0 ] = -1;
        for( int i=1; i<=n; ++i ) lg[i] = lg[i>>1] + 1;
        tbl.resize( lg[n] + 1 );
        tbl[ 0 ].resize( n );
        copy( arr, arr + n, tbl[ 0 ].begin() );
        for( int i = 1; i <= lg[ n ]; ++i ) {
            int len = 1 << ( i - 1 ), sz = 1 << i;
            tbl[i].resize( n - sz + 1 );
            for( int j = 0; j <= n - sz; ++j )
                tbl[i][j] = cv(tbl[i-1][j], tbl[i-1][j+len]);
        }
    }
    T query( int l, int r ) {
        // 0-base [l, r)
        int wh = lg[ r - l ], len = 1 << wh;
        return cv( tbl[ wh ][ l ], tbl[ wh ][ r - len ] );
    }
};
```

## 2.8 Linear Basis

```
struct LinearBasis {
private:
    int n, sz;
    vector< ll_u > B;
    inline ll_u two( int x ){ return ( ( ll_u ) 1 ) << x; }
public:
    void init( int n_ ) {
        n = n_; B.clear();
        B.resize( n ); sz = 0;
    }
    void insert( ll_u x ) {
        // add x into B
        for( int i = n-1; i >= 0; --i ) if( two(i) & x ){
            if ( B[ i ] ) x ^= B[ i ];
            else {
                B[ i ] = x; sz++;
                for( int j = i - 1; j >= 0; --j )
                    if( B[ j ] && ( two( j ) & B[ i ] ) )
                        B[ i ] ^= B[ j ];
                for( int j = i + 1; j < n; ++j )
                    if ( two( i ) & B[ j ] )
                        B[ j ] ^= B[ i ];
                break;
            }
        }
    }
    inline int size() { return sz; }
    bool check( ll_u x ) {
        // is x in span(B) ?
        for( int i = n-1; i >= 0; --i ) if( two(i) & x )
            if( B[ i ] ) x ^= B[ i ];
        else return false;
        return true;
    }
    ll_u kth_small(ll_u k) {
        // 1-base would always > 0
        // should check it
        // if we choose at least one element
        // but size(B)(vectors in B)=N(original elements)
        // then we can't get 0
        ll_u ret = 0;
        for( int i = 0; i < n; ++i ) if( B[ i ] ) {
            if( k & 1 ) ret ^= B[ i ];
            k >>= 1;
        }
    }
};
```

```

    }
    return ret;
}
} base;

```

## 3 Graph

### 3.1 BCC Edge

```

class BCC{
private:
    vector< int > low, dfn;
    int cnt;
    vector< bool > bridge;
    vector< vector< PII > > G;
    void dfs( int w, int f ) {
        dfn[ w ] = cnt++;
        low[ w ] = dfn[ w ];
        for ( auto [ u, t ] : G[ w ] ) {
            if ( u == f ) continue;
            if ( dfn[ u ] != 0 ) {
                low[ w ] = min( low[ w ], dfn[ u ] );
            } else {
                dfs( u, w );
                low[ w ] = min( low[ w ], low[ u ] );
                if ( low[ u ] > dfn[ w ] ) bridge[ t ] = true;
            }
        }
    }
public:
    void init( int n, int m ) {
        G.resize( n );
        fill( G.begin(), G.end(), vector< PII >() );
        bridge.clear(); bridge.resize( m );
        low.clear(); low.resize( n );
        dfn.clear(); dfn.resize( n );
        cnt = 0;
    }
    void add_edge( int u, int v ) {
        // should check for multiple edge
        G[ u ].emplace_back( v, cnt );
        G[ v ].emplace_back( u, cnt ++ );
    }
    void solve(){ cnt = 1; dfs( 0, 0 ); }
    // the id will be same as insert order, 0-base
    bool is_bridge( int x ) { return bridge[ x ]; }
} bcc;

```

### 3.2 BCC Vertex

```

class BCC{
private:
    int n, ecnt;
    vector< vector< pair< int, int > > > G;
    vector< int > low, dfn, id;
    vector< bool > vis, ap;
    void dfs( int u, int f, int d ) {
        int child = 0;
        dfn[ u ] = low[ u ] = d; vis[ u ] = true;
        for ( auto e : G[ u ] ) if ( e.first != f ) {
            if ( vis[ e.first ] ) {
                low[ u ] = min( low[ u ], dfn[ e.first ] );
            } else {
                dfs( e.first, u, d + 1 ); child ++;
                low[ u ] = min( low[ u ], low[ e.first ] );
                if ( low[ e.first ] >= d ) ap[ u ] = true;
            }
        }
        if ( u == f and child <= 1 ) ap[ u ] = false;
    }
    void mark( int u, int idd ) {
        // really????????
        if ( ap[ u ] ) return;
        for ( auto e : G[ u ] )
            if ( id[ e.second ] != -1 ) {
                id[ e.second ] = idd;
                mark( e.first, idd );
            }
    }
public:

```

```

void init( int n_ ) {
    ecnt = 0, n = n_;
    G.clear(); G.resize( n );
    low.resize( n ); dfn.resize( n );
    ap.clear(); ap.resize( n );
    vis.clear(); vis.resize( n );
}
void add_edge( int u, int v ) {
    G[ u ].emplace_back( v, ecnt );
    G[ v ].emplace_back( u, ecnt ++ );
}
void solve() {
    for ( int i = 0 ; i < n ; ++ i )
        if ( not vis[ i ] ) dfs( i, i, 0 );
    id.resize( ecnt );
    fill( id.begin(), id.end(), -1 );
    ecnt = 0;
    for ( int i = 0 ; i < n ; ++ i )
        if ( ap[ i ] ) for ( auto e : G[ i ] )
            if ( id[ e.second ] != -1 ) {
                id[ e.second ] = ecnt;
                mark( e.first, ecnt ++ );
            }
}
int get_id( int x ) { return id[ x ]; }
int count() { return ecnt; }
bool is_ap( int u ) { return ap[ u ]; }
} bcc;

```

### 3.3 Bipartite Matching

```

class BipartiteMatching{
private:
    vector<int> X[N], Y[N];
    int fX[N], fY[N], n;
    bitset<N> walked;
    bool dfs(int x){
        for(auto i:X[x]){
            if(walked[i])continue;
            walked[i]=1;
            if(fY[i]==-1||dfs(fY[i])){
                fY[i]=x;fX[x]=i;
                return 1;
            }
        }
        return 0;
    }
public:
    void init(int _n){
        n=_n;
        for(int i=0;i<n;i++){
            X[i].clear();
            Y[i].clear();
            fX[i]=fY[i]=-1;
        }
        walked.reset();
    }
    void add_edge(int x, int y){
        X[x].push_back(y);
        Y[y].push_back(x);
    }
    int solve(){
        int cnt = 0;
        for(int i=0;i<n;i++){
            walked.reset();
            if(dfs(i)) cnt++;
        }
        // return how many pair matched
        return cnt;
    }
};

```

### 3.4 Minimum Cost Maximum Flow

```

class MiniCostMaxiFlow{
using CapT = int;
using WeiT = int64_t;
using PCW = pair<CapT,WeiT>;
static constexpr CapT INF_CAP = 1 << 30;
static constexpr WeiT INF_WEI = 1LL<<60;
private:

```

```

struct Edge{
    int to, back;
    WeiT wei;
    CapT cap;
    Edge() {}
    Edge(int a,int b,WeiT c,CapT d):
        to(a),back(b),wei(c),cap(d)
    {}
};
int ori, edd;
vector<vector<Edge>> G;
vector<int> fa, wh;
vector<bool> inq;
vector<WeiT> dis;
PCW SPFA(){
    fill(inq.begin(),inq.end(),false);
    fill(dis.begin(),dis.end(),INF_WEI);
    queue<int> qq; qq.push(ori);
    dis[ori]=0;
    while(!qq.empty()){
        int u=qq.front();qq.pop();
        inq[u] = 0;
        for(int i=0;i<SZ(G[u]);++i){
            Edge e=G[u][i];
            int v=e.to;
            WeiT d=e.wei;
            if(e.cap<=0||dis[v]<=dis[u]+d)
                continue;
            dis[v]=dis[u]+d;
            fa[v]=u,wh[v]=i;
            if(inq[v]) continue;
            qq.push(v);
            inq[v]=1;
        }
    }
    if(dis[edd]==INF_WEI)
        return {-1,-1};
    CapT mw=INF_CAP;
    for(int i=edd;i!=ori;i=fa[i])
        mw=min(mw,G[fa[i]][wh[i]].cap);
    for (int i=edd;i!=ori;i=fa[i]){
        auto &eg=G[fa[i]][wh[i]];
        eg.cap-=mw;
        G[eg.to][eg.back].cap+=mw;
    }
    return {mw,dis[edd]};
}
public:
void init(int a,int b,int n){
    ori=a,edd=b;
    G.clear();G.resize(n);
    fa.resize(n);wh.resize(n);
    inq.resize(n); dis.resize(n);
}
void add_edge(int st,int ed,WeiT w,CapT c){
    G[st].emplace_back(ed,SZ(G[ed]),w,c);
    G[ed].emplace_back(st,SZ(G[st])-1,-w,0);
}
PCW solve(){
    /* might modify to
    cc += ret.first * ret.second
    or
    ww += ret.first * ret.second
    */
    CapT cc=0; WeiT ww=0;
    while(true){
        PCW ret=SPFA();
        if(ret.first==-1) break;
        cc+=ret.first;
        ww+=ret.second;
    }
    return {cc,ww};
}
} mcmf;

```

### 3.5 General Graph Matching

```

const int N = 514, E = (2e5) * 2;
struct Graph{
    int to[E],bro[E],head[N],e;
    int lnk[N],vis[N],stp,n;
    void init( int _n ){
        stp = 0; e = 1; n = _n;
        for( int i = 1 ; i <= n ; i ++ )

```

```

        lnk[i] = vis[i] = 0;
    }
    void add_edge(int u,int v){
        to[e]=v,bro[e]=head[u],head[u]=e++;
        to[e]=u,bro[e]=head[v],head[v]=e++;
    }
    bool dfs(int x){
        vis[x]=stp;
        for(int i=head[x];i;i=bro[i]){
            int v=to[i];
            if(!lnk[v]){
                lnk[x]=v,lnk[v]=x;
                return true;
            }else if(vis[lnk[v]]<stp){
                int w=lnk[v];
                lnk[x]=v,lnk[v]=x,lnk[w]=0;
                if(dfs(w)){
                    return true;
                }
                lnk[w]=v,lnk[v]=w,lnk[x]=0;
            }
        }
        return false;
    }
    int solve(){
        int ans = 0;
        for(int i=1;i<=n;i++)
            if(!lnk[i]){
                stp++; ans += dfs(i);
            }
        return ans;
    }
} graph;

```

### 3.6 Dinic

```

class Dinic{
private:
    using CapT = int64_t;
    struct Edge{
        int to, rev;
        CapT cap;
    };
    int n, st, ed;
    vector<vector<Edge>> G;
    vector<int> lv;
    bool BFS(){
        fill(lv.begin(), lv.end(), -1);
        queue<int> bfs;
        bfs.push(st);
        lv[st] = 0;
        while(!bfs.empty()){
            int u = bfs.front(); bfs.pop();
            for(auto e: G[u]){
                if(e.cap <= 0 or lv[e.to]!=-1) continue;
                lv[e.to] = lv[u] + 1;
                bfs.push(e.to);
            }
        }
        return (lv[ed]!=-1);
    }
    CapT DFS(int u, CapT f){
        if(u == ed) return f;
        CapT ret = 0;
        for(auto& e: G[u]){
            if(e.cap <= 0 or lv[e.to]!=lv[u]+1) continue;
            CapT nf = DFS(e.to, min(f, e.cap));
            ret += nf; e.cap -= nf; f -= nf;
            G[e.to][e.rev].cap += nf;
            if(f == 0) return ret;
        }
        if(ret == 0) lv[u] = -1;
        return ret;
    }
public:
    void init(int n_, int st_, int ed_){
        n = n_, st = st_, ed = ed_;
        G.resize(n); lv.resize(n);
        fill(G.begin(), G.end(), vector<Edge>());
    }
    void add_edge(int u, int v, CapT c){
        G[u].push_back({v, (int)G[v].size(), c});
        G[v].push_back({u, ((int)G[u].size()-1, 0)});
    }
}

```



```

CapT max_flow(){
    CapT ret = 0;
    while(BFS()){
        CapT f = DFS(st, numeric_limits<CapT>::max());
        ret += f;
        if(f == 0) break;
    }
    return ret;
}
} flow;

```

### 3.7 Kuhn Munkres

```

struct KM{
    static constexpr lld INF = 1LL<<60;
    lld w[N][N], lx[N], ly[N], slack[N];
    int match[N], n, vx[N], vy[N], step_;
    void init(int n_){
        n=n_, step_=0;
        memset(w,0,sizeof(w));
        memset(lx,0,sizeof(lx));
        memset(ly,0,sizeof(ly));
        memset(slack,0,sizeof(slack));
        memset(match,0,sizeof(match));
        memset(vx,0,sizeof(vx));
        memset(vy,0,sizeof(vy));
    }
    void add_edge(int u,int v,lld c){w[u][v]=c;}
    bool dfs(int x) {
        vx[x] = step_;
        for (int i = 0; i < n; ++i) {
            if (vy[i]==step_) continue;
            if (lx[x] + ly[i] > w[x][i]) {
                slack[i] = min(slack[i], lx[x] + ly[i] - w[x][i]);
                continue;
            }
            vy[i] = step_;
            if (match[i] == -1 || dfs(match[i])) {
                match[i] = x;
                return true;
            }
        }
        return false;
    }
    lld solve() {
        fill_n(match, n, -1);
        fill_n(lx, n, -INF);
        fill_n(ly, n, 0);
        for (int i = 0; i < n; ++i)
            for (int j = 0; j < n; ++j)
                lx[i] = max(lx[i], w[i][j]);
        for (int i = 0; i < n; ++i) {
            fill_n(slack, n, INF);
            while (true) {
                step_++;
                if (dfs(i)) break;
                lld dlt = INF;
                for (int j = 0; j < n; ++j) if (vy[j] != step_)
                    dlt = min(dlt, slack[j]);
                for (int j = 0; j < n; ++j) {
                    if (vx[j]==step_) lx[j] -= dlt;
                    if (vy[j]==step_) ly[j] += dlt;
                    else slack[j] -= dlt;
                }
            }
        }
        lld res = 0;
        for (int i = 0; i < n; ++i) res += w[match[i]][i];
        return res;
    }
} km;

```

### 3.8 2-SAT

```

class TwoSat{
private:
    int n;
    vector<vector<int>> rG,G,scs;
    vector<int> ord,idx;
    vector<bool> vis,result;

```

```

    void dfs(int u){
        vis[u]=true;
        for(int v:G[u])
            if(!vis[v])
                dfs(v);
        ord.push_back(u);
    }
    void rdfs(int u){
        vis[u]=false;
        idx[u]=scs.size()-1;
        scs.back().push_back(u);
        for(int v:rG[u])
            if(vis[v])
                rdfs(v);
    }
public:
    void init(int n_){
        n=n_;
        G.clear();
        G.resize(n);
        rG.clear();
        rG.resize(n);
        scs.clear();
        ord.clear();
        idx.resize(n);
        result.resize(n);
    }
    void add_edge(int u,int v){
        G[u].push_back(v);
        rG[v].push_back(u);
    }
    void orr(int x,int y){
        if ((x^y)==1)return;
        add_edge(x^1,y);
        add_edge(y^1,x);
    }
    bool solve(){
        vis.clear();
        vis.resize(n);
        for(int i=0;i<n;++i)
            if(not vis[i])
                dfs(i);
        reverse(ord.begin(),ord.end());
        for (int u:ord){
            if(!vis[u])
                continue;
            scs.push_back(vector<int>());
            rdfs(u);
        }
        for(int i=0;i<n;i+=2)
            if(idx[i]==idx[i+1])
                return false;
        vector<bool> c(scs.size());
        for(size_t i=0;i<scs.size();++i){
            for(size_t j=0;j<scs[i].size();++j){
                result[scs[i][j]]=c[i];
                c[idx[scs[i][j]^1]]!=c[i];
            }
        }
        return true;
    }
    bool get(int x){return result[x];}
    inline int get_id(int x){return idx[x];}
    inline int count(){return scs.size();}
} sat2;

```

### 3.9 Lowbit Decomposition

```

class LowbitDecomp{
private:
    int time_, chain_, LOG_N;
    vector< vector< int > > G, fa;
    vector< int > tl, tr, chain, chain_st;
    // chain_ : number of chain
    // tl, tr[ u ] : subtree interval in the seq. of u
    // chain_st[ u ] : head of the chain contains u
    // chain[ u ] : chain id of the chain u is on
    inline int lowbit( int x ) {
        return x & ( -x );
    }
}
void predfs( int u, int f ) {
    chain[ u ] = 0;
    for ( int v : G[ u ] ) {
        if ( v == f ) continue;

```

```

    predfs( v, u );
    if( lowbit( chain[ u ] ) < lowbit( chain[ v ] ) )
        chain[ u ] = chain[ v ];
}
if ( not chain[ u ] )
    chain[ u ] = chain_ ++;
}
void dfschain( int u, int f ) {
    fa[ u ][ 0 ] = f;
    for ( int i = 1 ; i < LOG_N ; ++ i )
        fa[ u ][ i ] = fa[ fa[ u ][ i - 1 ] ][ i - 1 ];
    tl[ u ] = time_++;
    if ( not chain_st[ chain[ u ] ] )
        chain_st[ chain[ u ] ] = u;
    for ( int v : G[ u ] )
        if ( v != f and chain[ v ] == chain[ u ] )
            dfschain( v, u );
    for ( int v : G[ u ] )
        if ( v != f and chain[ v ] != chain[ u ] )
            dfschain( v, u );
    tr[ u ] = time_;
}
inline bool anc( int u, int v ) {
    return tl[ u ] <= tl[ v ] \
        and tr[ v ] <= tr[ u ];
}
public:
    inline int lca( int u, int v ) {
        if ( anc( u, v ) ) return u;
        for ( int i = LOG_N - 1 ; i >= 0 ; -- i )
            if ( not anc( fa[ u ][ i ], v ) )
                u = fa[ u ][ i ];
        return fa[ u ][ 0 ];
    }
    void init( int n ) {
        n ++;
        for ( LOG_N = 0 ; ( 1 << LOG_N ) < n ; ++ LOG_N );
        fa.clear();
        fa.resize( n, vector< int >( LOG_N ) );
        G.clear(); G.resize( n );
        tl.clear(); tl.resize( n );
        tr.clear(); tr.resize( n );
        chain.clear(); chain.resize( n );
        chain_st.clear(); chain_st.resize( n );
    }
    void add_edge( int u , int v ) {
        // 1-base
        G[ u ].push_back( v );
        G[ v ].push_back( u );
    }
    void decompose(){
        chain_ = 1;
        predfs( 1, 1 );
        time_ = 0;
        dfschain( 1, 1 );
    }
    PII get_inter( int u ) { return {tl[ u ], tr[ u ]}; }
    vector< PII > get_path( int u , int v ){
        vector< PII > res;
        int g = lca( u, v );
        while ( chain[ u ] != chain[ g ] ) {
            int s = chain_st[ chain[ u ] ];
            res.emplace_back( tl[ s ], tl[ u ] + 1 );
            u = fa[ s ][ 0 ];
        }
        res.emplace_back( tl[ g ], tl[ u ] + 1 );
        while ( chain[ v ] != chain[ g ] ) {
            int s = chain_st[ chain[ v ] ];
            res.emplace_back( tl[ s ], tl[ v ] + 1 );
            v = fa[ s ][ 0 ];
        }
        res.emplace_back( tl[ g ] + 1, tl[ v ] + 1 );
        return res;
    }
    /* res : List of intervals from u to v
     * ( note only nodes work, not edge )
     * usage :
     * vector< PII > &path = tree.get_path( u , v )
     * for( auto [ l, r ] : path ) {
     *     0-base [ l, r )
     * }
     */
}
} tree;

```

### 3.10 MaxClique

```

#define N 111
struct MaxClique{ // 0-base
    typedef bitset< N > Int;
    Int linkto[ N ], v[ N ];
    int n;
    void init( int _n ){
        n = _n;
        for( int i = 0 ; i < n ; i ++ ){
            linkto[ i ].reset();
            v[ i ].reset();
        }
    }
    void add_edge( int a , int b ){
        v[ a ][ b ] = v[ b ][ a ] = 1;
    }
    int popcount(const Int& val)
    { return val.count(); }
    int lowbit(const Int& val)
    { return val._Find_first(); }
    int ans , stk[ N ];
    int id[ N ] , di[ N ] , deg[ N ];
    Int cans;
    void maxclique(int elem_num, Int candi){
        if(elem_num > ans){
            ans = elem_num;
            cans.reset();
            for( int i = 0 ; i < elem_num ; i ++ )
                cans[ id[ stk[ i ] ] ] = 1;
        }
        int potential = elem_num + popcount(candi);
        if(potential <= ans) return;
        int pivot = lowbit(candi);
        Int smaller_candi = candi & (~linkto[pivot]);
        while(smaller_candi.count() && potential > ans){
            int next = lowbit(smaller_candi);
            candi[ next ] = !candi[ next ];
            smaller_candi[next] = !smaller_candi[next];
            potential --;
            if(next != pivot
                && (smaller_candi & linkto[next]).count())
                continue;
            stk[elem_num] = next;
            maxclique(elem_num+1, candi & linkto[next]);
        }
    }
    int solve(){
        for( int i = 0 ; i < n ; i ++ ){
            id[ i ] = i;
            deg[ i ] = v[ i ].count();
        }
        sort( id , id + n , [&](int id1, int id2){
            return deg[id1] > deg[id2]; } );
        for( int i = 0 ; i < n ; i ++ )
            di[ id[ i ] ] = i;
        for( int i = 0 ; i < n ; i ++ )
            for( int j = 0 ; j < n ; j ++ )
                if( v[ i ][ j ] )
                    linkto[ di[ i ] ][ di[ j ] ] = 1;
        Int cand; cand.reset();
        for( int i = 0 ; i < n ; i ++ )
            cand[ i ] = 1;
        ans = 1;
        cans.reset(); cans[ 0 ] = 1;
        maxclique(0, cand);
        return ans;
    }
} solver;

```

### 3.11 Min-Cut

```

const int maxn = 500 + 5;
int w[maxn][maxn], g[maxn];
bool v[maxn], del[maxn];

void add_edge(int x, int y, int c) {
    w[x][y] += c;
    w[y][x] += c;
}

pair<int, int> phase(int n) {
    memset(v, false, sizeof(v));
}

```



```

memset(g, 0, sizeof(g));
int s = -1, t = -1;
while (true) {
    int c = -1;
    for (int i = 0; i < n; ++i) {
        if (del[i] || v[i]) continue;
        if (c == -1 || g[i] > g[c]) c = i;
    }
    if (c == -1) break;
    v[c] = true;
    s = t, t = c;
    for (int i = 0; i < n; ++i) {
        if (del[i] || v[i]) continue;
        g[i] += w[c][i];
    }
}
return make_pair(s, t);
}

int mincut(int n) {
    int cut = 1e9;
    memset(del, false, sizeof(del));
    for (int i = 0; i < n - 1; ++i) {
        int s, t; tie(s, t) = phase(n);
        del[t] = true;
        cut = min(cut, g[t]);
        for (int j = 0; j < n; ++j) {
            w[s][j] += w[t][j];
            w[j][s] += w[j][t];
        }
    }
    return cut;
}

```

### 3.12 Vitural Tree

```

inline bool cmp(const int &i, const int &j) {
    return dfn[i] < dfn[j];
}

void build(int vectrices[], int k) {
    static int stk[MAX_N];
    sort(vectrices, vectrices + k, cmp);
    stk[sz++] = 0;
    for (int i = 0; i < k; ++i) {
        int u = vectrices[i], lca = LCA(u, stk[sz - 1]);
        if (lca == stk[sz - 1]) stk[sz++] = u;
        else {
            while (sz >= 2 && dep[stk[sz - 2]] >= dep[lca]) {
                addEdge(stk[sz - 2], stk[sz - 1]);
                sz--;
            }
            if (stk[sz - 1] != lca) {
                addEdge(lca, stk[sz - 1]);
                stk[sz++] = lca, vectrices[cnt++] = lca;
            }
            stk[sz++] = u;
        }
    }
    for (int i = 0; i < sz - 1; ++i)
        addEdge(stk[i], stk[i + 1]);
}

```

## 4 Math

### 4.1 Prime Table

```

1002939109, 1020288887, 1028798297, 1038684299,
1041211027, 1051762951, 1058585963, 1063020809,
1147930723, 1172520109, 1183835981, 1187659051,
1241251303, 1247184097, 1255940849, 1272759031,
1287027493, 1288511629, 1294632499, 1312650799,
1868732623, 1884198443, 1884616807, 1885059541,
1909942399, 1914471137, 1923951707, 1925453197,
1979612177, 1980446837, 1989761941, 2007826547,
2008033571, 2011186739, 2039465081, 2039728567,
2093735719, 2116097521, 2123852629, 2140170259,
3148478261, 3153064147, 3176351071, 3187523093,
3196772239, 3201312913, 3203063977, 3204840059,
3210224309, 3213032591, 3217689851, 3218469083,
3219857533, 3231880427, 3235951699, 3273767923,
3276188869, 3277183181, 3282463507, 3285553889,
3319309027, 3327005333, 3327574903, 3341387953,
3373293941, 3380077549, 3380892997, 3381118801

```

### 4.2 $\lfloor \frac{n}{i} \rfloor$ Enumeration

$$T_0 = 1, T_{i+1} = \lfloor \frac{n}{T_i + 1} \rfloor$$

### 4.3 $ax+by=\gcd$

```

// ax+ny = 1, ax+ny == ax == 1 (mod n)
void exgcd(lld x, lld y, lld &g, lld &a, lld &b) {
    if (y == 0) g = x, a = 1, b = 0;
    else
        exgcd(y, x % y, g, b, a), b -= (x / y) * a;
}

```

### 4.4 Pollard Rho

```

// does not work when n is prime
// return any non-trivial factor
llu pollard_rho(llu n) {
    static auto f = [](llu x, llu k, llu m) {
        return add(k, mul(x, x, m), m);
    };
    if (!(n & 1)) return 2;
    mt19937 rnd(120821011);
    while (true) {
        llu y = 2, yy = y, x = rnd() % n, t = 1;
        for (llu sz = 2; t == 1; sz <= 1) {
            for (llu i = 0; i < sz; ++i) {
                if (t != 1) break;
                yy = f(yy, x, n);
                t = gcd(yy > y ? yy - y : y - yy, n);
            }
            y = yy;
        }
        if (t != 1 && t != n) return t;
    }
}

```

### 4.5 Pi Count (Linear Sieve)

```

static constexpr int N = 1000000 + 5;
lld pi[N];
vector<int> primes;
bool sieved[N];
lld cube_root(lld x) {
    lld s = cbrt(x - static_cast<long double>(0.1));
    while (s * s * s <= x) ++s;
    return s - 1;
}
lld square_root(lld x) {
    lld s = sqrt(x - static_cast<long double>(0.1));
    while (s * s <= x) ++s;
    return s - 1;
}

void init() {
    primes.reserve(N);
    primes.push_back(1);
    for (int i = 2; i < N; ++i) {
        if (!sieved[i]) primes.push_back(i);
        pi[i] = !sieved[i] + pi[i - 1];
        for (int p: primes) if (p > 1) {
            if (p * i >= N) break;
            sieved[p * i] = true;
            if (p % i == 0) break;
        }
    }
}

lld phi(lld m, lld n) {
    static constexpr int MM = 80000, NN = 500;
    static lld val[MM][NN];
    if (m < MM && n < NN && val[m][n]) return val[m][n] - 1;
    if (n == 0) return m;
    if (primes[n] >= m) return 1;
    lld ret = phi(m, n - 1) - phi(m / primes[n], n - 1);
    if (m < MM && n < NN) val[m][n] = ret + 1;
    return ret;
}

lld pi_count(lld);
lld P2(lld m, lld n) {
    lld sm = square_root(m), ret = 0;
}

```

```

for(lld i = n+1; primes[i] <= sm; i++)
    ret += pi_count(m/primes[i]) - pi_count(primes[i]) + 1;
return ret;
}

lld pi_count(lld m) {
    if(m < N) return pi[m];
    lld n = pi_count(cube_root(m));
    return phi(m, n) + n - 1 - P2(m, n);
}

```

## 4.6 Range Sieve

```

const int MAX_SQRT_B = 50000;
const int MAX_L = 200000 + 5;

bool is_prime_small[MAX_SQRT_B];
bool is_prime[MAX_L];

void sieve(lld l, lld r) {
    // [l, r)
    for(lld i=2; i<r; i++) is_prime_small[i] = true;
    for(lld i=1; i<r; i++) is_prime[i-1] = true;
    if(l==1) is_prime[0] = false;
    for(lld i=2; i<r; i++) {
        if(!is_prime_small[i]) continue;
        for(lld j=i*i; j<r; j+=i) is_prime_small[j] = false;
        for(lld j=std::max(2LL, (1+i-1)/i)*i; j<r; j+=i)
            is_prime[j-1] = false;
    }
}

```

## 4.7 Miller Rabin

```

bool isprime(llu x) {
    static ll u magic[] = {2, 325, 9375, 28178, \
        450775, 9780504, 1795265022};
    static auto witn = [](llu a, ll u, ll n, int t) {
        a = mpow(a, u, n);
        if(!a) return 0;
        while(t--){
            ll u a2 = mul(a, a, n);
            if(a2==1 && a!=1 && a!=n-1)
                return 1;
            a = a2;
        }
        return a!=1;
    };
    if(x<2) return 0;
    if(!(x&1)) return x==2;
    ll u x1 = x-1; int t=0;
    while(!(x1&1)) x1>>=1, t++;
    for(ll u m: magic)
        if(witn(m, x1, x, t))
            return 0;
    return 1;
}

```

## 4.8 Inverse Element

```

// x's inverse mod k
long long GetInv(long long x, long long k) {
    // k is prime: euler_(k)=k-1
    return qPow(x, euler_phi(k)-1);
}

// if you need [1, x] (most use: [1, k-1])
void solve(int x, long long k) {
    inv[1] = 1;
    for(int i=2; i<x; i++)
        inv[i] = ((long long)(k - k/i) * inv[k % i]) % k;
}

```

## 4.9 Euler Phi Function

```

/*
    extended euler:
    a^b mod p
    if gcd(a, p) == 1: a^(b%phi(p))

```

```

    elif b < phi(p): a^b mod p
    else a^(b%phi(p) + phi(p))
*/
lld euler_phi(int x) {
    lld r=1;
    for(int i=2; i*i<=x; ++i) {
        if(x%i==0) {
            x/=i;
            r*=(i-1);
            while(x%i==0) {
                x/=i;
                r*=i;
            }
        }
    }
    if(x>1) r*=x-1;
    return r;
}

vector<int> primes;
bool notprime[N];
lld phi[N];
void euler_sieve(int n) {
    for(int i=2; i<n; i++) {
        if(!notprime[i]) {
            primes.push_back(i);
            phi[i] = i-1;
        }
        for(auto j: primes) {
            if(i*j >= n) break;
            notprime[i*j] = true;
            phi[i*j] = phi[i] * phi[j];
            if(i % j == 0) {
                phi[i*j] = phi[i] * j;
                break;
            }
        }
    }
}

```

## 4.10 Gauss Elimination

```

typedef long double llf;
const int N = 300;
const llf EPS = 1e-8;

// make m[i][i] = x, m[i][j] = 0
// v is for solving equation:
// for(int i=0; i<n; i++) ans[pos[i]] = val[i]/mtx[i][pos[i]];
// for(int i=0; i<n; i++) cout << ans[i] << '\n';
bool Gauss(llf m[N][N], llf v[N], int n, int pos[N]) {
    for(int i=0; i<n; i++) {
        int x=-1, y=-1; llf e = 0;
        for(int j=i; j<n; j++) for(int k=i; k<n; k++) {
            if(fabs(m[j][pos[k]] > e) {
                e = fabs(m[j][pos[k]]);
                x = j, y = k;
            }
        }
        if(x==-1 || y==-1) return false;
        swap(m[x], m[y]);
        swap(v[x], v[y]);
        swap(pos[y], pos[x]);
        for(int j=i+1; j<n; j++) {
            llf xi = m[j][pos[i]]/m[i][pos[i]];
            for(int k=0; k<n; k++) m[j][pos[k]] -= xi*m[i][pos[k]];
            v[j] -= xi*v[i];
        }
    }
    for(int i=n-1; i>=0; i--) {
        for(int j=i-1; j>=0; j--) {
            llf xi = m[j][pos[i]]/m[i][pos[i]];
            for(int k=0; k<n; k++) m[j][pos[k]] -= xi*m[i][pos[k]];
            v[j] -= xi*v[i];
        }
    }
    return true;
}

```

## 4.11 Fast Fourier Transform

```

/*
    polynomial multiply:
    DFT(a, len); DFT(b, len);
    for(int i=0; i<len; i++) c[i] = a[i]*b[i];
    iDFT(c, len);
    (len must be 2^k and >= 2*(max(a, b)))
    Hand written Cplx would be 2x faster
*/
Cplx omega[2][N];
void init_omega(int n) {
    static constexpr llf PI=acos(-1);
    const llf arg=(PI+PI)/n;
    for(int i=0; i<n; ++i)
        omega[0][i]={cos(arg*i), sin(arg*i)};
    for(int i=0; i<n; ++i)
        omega[1][i]=conj(omega[0][i]);
}
void tran(Cplx arr[], int n, Cplx omg[]) {
    for(int i=0, j=0; i<n; ++i){
        if(i>j) swap(arr[i], arr[j]);
        for(int l=n>>1; (j^=1)<l; l>>=1);
    }
    for (int l=2; l<=n; l<=<=1){
        int m=l>>1;
        for(auto p=arr; p!=arr+n; p+=l){
            for(int i=0; i<m; ++i){
                Cplx t=omg[n/l*i]*p[m+i];
                p[m+i]=p[i]-t;
                p[i]+=t;
            }
        }
    }
}
void DFT(Cplx arr[], int n){
    tran(arr, n, omega[0]);
}
void iDFT(Cplx arr[], int n){
    tran(arr, n, omega[1]);
    for(int i=0; i<n; ++i) arr[i]/=n;
}

```

## 4.12 Chinese Remainder

```

lld crt(lld ans[], lld pri[], int n){
    lld M = 1;
    for(int i=0; i<n; i++) M *= pri[i];
    lld ret = 0;
    for(int i=0; i<n; i++){
        lld inv = (gcd(M/pri[i], pri[i]).first + pri[i])%
            pri[i];
        ret += (ans[i]*(M/pri[i])%M * inv)%M;
        ret %= M;
    }
    return ret;
}
/*
Another:
x = a1 % m1
x = a2 % m2
g = gcd(m1, m2)
assert((a1-a2)%g==0)
[p, q] = exgcd(m2/g, m1/g)
return a2+m2*(p*(a1-a2)/g)
0 <= x < lcm(m1, m2)
*/

```

## 4.13 Berlekamp Massey

```

// x: 1-base, p[]: 0-base
template<size_t N>
vector<llf> BM(llf x[N], size_t n){
    size_t f[N]={0}, t=0; llf d[N];
    vector<llf> p[N];
    for(size_t i=1, b=0; i<=n; ++i) {
        for(size_t j=0; j<p[t].size(); ++j)
            d[i]+=x[i-j-1]*p[t][j];
        if(abs(d[i]-x[i])<EPS) continue;
        f[t]=i; if(!t){p[++t].resize(i); continue;}
        vector<llf> cur(i-f[t]-1);
    }
}

```

```

    llf k=-d[i]/d[f[b]]; cur.PB(-k);
    for(size_t j=0; j<p[b].size(); j++)
        cur.PB(p[b][j]*k);
    if(cur.size()<p[t].size()) cur.resize(p[t].size());
    for(size_t j=0; j<p[t].size(); j++) cur[j]+=p[t][j];
    if(i-f[b]+p[b].size()>p[t].size()) b=t;
    p[++t]=cur;
}
return p[t];
}

```

## 4.14 NTT

```

// Remember coefficient are mod P
/* p=a*2^n+1
n    2^n    p    a    root
16   65536   65537   1    3
20   1048576 7340033 7    3 */
// (must be 2^k)
template<LL P, LL root, int MAXN>
struct NTT{
    static LL bigmod(LL a, LL b) {
        LL res = 1;
        for (LL bs = a; b; b >>= 1, bs = (bs * bs) % P)
            if(b&1) res=(res*bs)%P;
        return res;
    }
    static LL inv(LL a, LL b) {
        if(a==1) return 1;
        return (((LL)(a-inv(b%a,a))*b+1)/a)%b;
    }
    LL omega[MAXN+1];
    NTT() {
        omega[0] = 1;
        LL r = bigmod(root, (P-1)/MAXN);
        for (int i=1; i<=MAXN; i++)
            omega[i] = (omega[i-1]*r)%P;
    }
    // n must be 2^k
    void tran(int n, LL a[], bool inv_ntt=false){
        int basic = MAXN / n, theta = basic;
        for (int m = n; m >= 2; m >>= 1) {
            int mh = m >> 1;
            for (int i = 0; i < mh; i++) {
                LL w = omega[i*theta*MAXN];
                for (int j = i; j < n; j += m) {
                    int k = j + mh;
                    LL x = a[j] - a[k];
                    if (x < 0) x += P;
                    a[j] += a[k];
                    if (a[j] > P) a[j] -= P;
                    a[k] = (w * x) % P;
                }
            }
            theta = (theta * 2) % MAXN;
        }
        int i = 0;
        for (int j = 1; j < n - 1; j++) {
            for (int k = n >> 1; k > (i ^= k); k >>= 1);
            if (j < i) swap(a[i], a[j]);
        }
        if (inv_ntt) {
            LL ni = inv(n, P);
            reverse(a+1, a+n);
            for (i = 0; i < n; i++)
                a[i] = (a[i] * ni) % P;
        }
    }
};
const LL P=2013265921, root=31;
const int MAXN=4194304;
NTT<P, root, MAXN> ntt;

```

## 4.15 Sqrt of Polynomial

```

const int mod = (119 << 23) + 1;
int inv_temp[400010];
void poly_inv(int *f, int *inv, int len) {
    int *inv_t = inv_temp, *g = inv;
    g[0] = get_inv(f[0]);
    for (int l = 2; l <= len; l <= 1, swap(g, inv_t)) {
        for (int i = 0; i < l; i++) {

```

```

    inv_t[i] = f[i];
    g[i + 1] = inv_t[i + 1] = 0;
}
exec_ntt(inv_t, 1 << 1, 1);
exec_ntt(g, 1 << 1, 1);
for (int i = 0; i < 2 * 1; i++)
    inv_t[i] = (1l)inv_t[i] * g[i] % mod;
for (int i = 0; i < 2 * 1; i++) {
    if (inv_t[i])
        inv_t[i] = mod - inv_t[i];
    inv_t[i] += 2, inv_t[i] %= mod;
}
for (int i = 0; i < 2 * 1; i++)
    inv_t[i] = (1l)inv_t[i] * g[i] % mod;
exec_ntt(inv_t, 1 << 1, -1);
for (int i = 0; i < 1; i++)
    inv_t[i + 1] = 0;
}
for (int i = 0; i < len; i++)
    inv[i] = g[i];
}
int sqrt_temp[400010], inv_t[400010];
void poly_sqrt(int *f, int *sqrt_pol, int len) {
    int *g = sqrt_pol, *t = sqrt_temp, inv2 = get_inv(2);
    g[0] = 1;
    for (int l = 2; l <= len; l <= 1, swap(g, t)) {
        for (int i = 0; i < l; i++)
            t[i] = f[i], t[i + 1] = g[i + 1] = inv_t[i] = 0;
        poly_inv(g, inv_t, l);
        for (int i = 1; i < 2 * l; i++)
            inv_t[i] = 0;
        exec_ntt(g, 1 << 1, 1);
        exec_ntt(inv_t, 1 << 1, 1);
        exec_ntt(t, 1 << 1, 1);
        for (int i = 0; i < (1 << 1); i++)
            t[i] = (1l)inv2 * (g[i] + (1l)t[i] * inv_t[i] % mod) % mod;
        exec_ntt(t, 1 << 1, -1);
        for (int i = 0; i < 1; i++)
            t[i + 1] = 0;
    }
    for (int i = 0; i < len; i++)
        sqrt_pol[i] = g[i];
}
int c[400010], inv[400010], sqrt_pol[400010];
int main() {
    int n, m, x;
    scanf("%d%d", &n, &m);
    for (int i = 0; i < n; i++)
    {
        scanf("%d", &x);
        if (x <= m)
            c[x] = mod - 4;
    }
    c[0]++, c[0] %= mod;
    int len = 1;
    while (len <= m) len <= 1;
    poly_sqrt(c, sqrt_pol, len);
    sqrt_pol[0]++, sqrt_pol[0] %= mod;
    poly_inv(sqrt_pol, inv, len);
    for (int i = 1; i <= m; i++)
        printf("%d\n", (inv[i] + inv[i]) % mod);
    puts("");
    return 0;
}

```

#### 4.16 FWT

```

/* xor convolution:
* x = (x0,x1), y = (y0,y1)
* z = (x0y0 + x1y1, x0y1 + x1y0)
* =>
* x' = (x0+x1, x0-x1), y' = (y0+y1, y0-y1)
* z' = ((x0+x1)(y0+y1), (x0-x1)(y0-y1))
* z = (1/2) * z''
* or convolution:
* x = (x0, x0+x1), inv = (x0, x1-x0) w/o final div
* and convolution:
* x = (x0+x1, x1), inv = (x0-x1, x1) w/o final div */
const LL MOD = 1e9+7;
inline void fwt(LL x[ MAXN ], int N, bool inv=0) {
    for (int d = 1; d < N; d <= 1) {
        int d2 = d << 1;
        for (int s = 0; s < N; s += d2)
            for (int i = s, j = s+d; i < s+d; i++, j++) {

```

```

                LL ta = x[i], tb = x[j];
                x[i] = ta+tb;
                x[j] = ta-tb;
                if (x[i] >= MOD) x[i] -= MOD;
                if (x[j] < 0) x[j] += MOD;
            }
        }
    }
    if (inv)
        for (int i = 0; i < N; i++) {
            x[i] *= inv(N, MOD);
            x[i] %= MOD;
        }
}

```

#### 4.17 DiscreteLog

```

// Baby-step Giant-step Algorithm
lld BSGS(lld P, lld B, lld N) {
    // find B^L = N mod P
    unordered_map<lld, int> R;
    lld sq = (lld)sqrt(P);
    lld t = 1;
    for (int i = 0; i < sq; i++) {
        if (t == N)
            return i;
        if (!R.count(t))
            R[t] = i;
        t = (t * B) % P;
    }
    lld f = inverse(t, P);
    for (int i=0; i<sq+1; i++) {
        if (R.count(N))
            return i * sq + R[N];
        N = (N * f) % P;
    }
    return -1;
}

```

#### 4.18 Quadratic residue

```

struct Status {
    ll x, y;
};
ll w;
Status mult(const Status& a, const Status& b, ll mod) {
    Status res;
    res.x = (a.x * b.x + a.y * b.y % mod * w) % mod;
    res.y = (a.x * b.y + a.y * b.x) % mod;
    return res;
}
inline Status qpow(Status _base, ll _pow, ll _mod) {
    Status res;
    res.x = 1, res.y = 0;
    while (_pow > 0) {
        if (_pow & 1) res = mult(res, _base, _mod);
        _base = mult(_base, _base, _mod);
        _pow >>= 1;
    }
    return res;
}
inline ll check(ll x, ll p) {
    return qpow_mod(x, (p-1) >> 1, p);
}
inline ll get_root(ll n, ll p) {
    if (p == 2) return 1;
    if (check(n, p) == p-1) return -1;
    ll a;
    while (true) {
        a = rand() % p;
        w = ((a * a - n) % p + p) % p;
        if (check(w, p) == p-1) break;
    }
    Status res;
    res.x = a;
    res.y = 1;
    res = qpow(res, (p+1) >> 1, p);
    return res.x;
}

```

## 4.19 De-Bruijn

```
int res[maxn], aux[maxn], sz;
void db(int t, int p, int n, int k) {
    if (t > n) {
        if (n % p == 0)
            for (int i = 1; i <= p; ++i)
                res[sz++] = aux[i];
    } else {
        aux[t] = aux[t - p];
        db(t + 1, p, n, k);
        for (int i = aux[t - p] + 1; i < k; ++i) {
            aux[t] = i;
            db(t + 1, t, n, k);
        }
    }
}
int de_bruijn(int k, int n) {
    // return cyclic string of len k^n s.t. every string
    // of len n using k char appears as a substring.
    if (k == 1) {
        res[0] = 0;
        return 1;
    }
    for (int i = 0; i < k * n; i++) aux[i] = 0;
    sz = 0;
    db(1, 1, n, k);
    return sz;
}
```

## 5 Geometry

### 5.1 Point Class

```
template<typename T>
struct Point{
    typedef long double llf;
    static constexpr llf EPS = 1e-8;
    T x, y;
    Point(T __=0, T __=0): x(__), y(__){}
    template<typename T2>
    Point(const Point<T2>& a): x(a.x), y(a.y){}
    inline llf theta() const {
        return atan2((llf)y, (llf)x);
    }
    inline llf dis() const {
        return hypot((llf)x, (llf)y);
    }
    inline llf dis(const Point& o) const {
        return hypot((llf)(x-o.x), (llf)(y-o.y));
    }
    Point operator-(const Point& o) const {
        return Point(x-o.x, y-o.y);
    }
    Point operator+=(const Point& o){
        x+=o.x, y+=o.y;
        return *this;
    }
    Point operator+(const Point& o) const {
        return Point(x+o.x, y+o.y);
    }
    Point operator+=(const Point& o){
        x+=o.x, y+=o.y;
        return *this;
    }
    Point operator*(const T& k) const {
        return Point(x*k, y*k);
    }
    Point operator*=(const T& k){
        x*=k, y*=k;
        return *this;
    }
    Point operator/(const T& k) const {
        return Point(x/k, y/k);
    }
    Point operator/=(const T& k){
        x/=k, y/=k;
        return *this;
    }
    Point operator-() const {
        return Point(-x, -y);
    }
}
```

```
Point rot90() const {
    return Point(-y, x);
}
template<typename T2>
bool in(const Circle<T2>& a) const {
    /* Add struct Circle at top */
    return a.o.dis(*this)+EPS <= a.r;
}
bool equal(const Point& o, true_type) const {
    return fabs(x-o.x) < EPS and fabs(y-o.y) < EPS;
}
bool equal(const Point& o, false_type) const {
    return tie(x, y) == tie(o.x, o.y);
}
bool operator==(const Point& o) const {
    return equal(o, is_floating_point<T>());
}
bool operator!=(const Point& o) const {
    return !(*this == o);
}
bool operator<(const Point& o) const {
    return theta() < o.theta();
    // sort like what pairs did
    // if(is_floating_point<T>()) return fabs(x-o.x)<
    // EPS?y<o.y:x<o.x;
    // else return tie(x, y) < tie(o.x, o.y);
}
friend inline T cross(const Point& a, const Point& b)
{
    return a.x*b.y - b.x*a.y;
}
friend inline T dot(const Point& a, const Point &b){
    return a.x*b.x + a.y*b.y;
}
friend ostream& operator<<(ostream& ss, const Point&
o){
    ss<<"("<<o.x<<" ", "<<o.y<<" )";
    return ss;
}
};
```

### 5.2 Circle Class

```
template<typename T>
struct Circle{
    static constexpr llf EPS = 1e-8;
    Point<T> o;
    T r;
    vector<Point<llf>> operator&(const Circle& aa)const{
        // https://www.cnblogs.com/wangzming/p/8338142.html
        llf d=o.dis(aa.o);
        if(d > r+aa.r+EPS or d < fabs(r-aa.r)-EPS) return
        {};
        llf dt = (r*r - aa.r*aa.r)/d, d1 = (d+dt)/2;
        Point<llf> dir = (aa.o-o); dir /= d;
        Point<llf> pcrs = dir*d1 + o;
        dt=sqrt(max(0.0L, r*r - d1*d1)), dir=dir.rot90();
        return {pcrs + dir*dt, pcrs - dir*dt};
    }
};
```

### 5.3 Line Class

```
const Point<long double> INF_P(-1e20, 1e20);
const Point<long double> NOT_EXIST(1e20, 1e-20);
template<typename T>
struct Line{
    static constexpr long double EPS = 1e-8;
    // ax+by+c = 0
    T a, b, c;
    Line(): a(0), b(1), c(0){}
    Line(T __, T __, T __): a(__), b(__), c(__){
        assert(fabs(a)>EPS or fabs(b)>EPS);
    }
    template<typename T2>
    Line(const Line<T2>& x): a(x.a), b(x.b), c(x.c){}
    typedef Point<long double> Pt;
    bool equal(const Line& o, true_type) const {
        return fabs(a-o.a) < EPS and fabs(b-o.b) < EPS and
        fabs(c-o.c) < EPS;
    }
    bool euqal(const Line& o, false_type) const {
```

```

    return a==o.a and b==o.b and c==o.c;
}
bool operator==(const Line& o) const {
    return euqal(o, is_floating_point<T>());
}
bool operator!=(const Line& o) const {
    return !(*this == o);
}
friend inline bool on_line__(const Point<T>& p, const
    Line& l, true_type){
    return fabs(l.a*p.x + l.b*p.y + l.c) < EPS;
}
friend inline bool on_line__(const Point<T>& p, const
    Line& l, false_type){
    return l.a*p.x + l.b*p.y + l.c == 0;
}
friend inline bool on_line(const Point<T>&p const
    Line& l){
    return on_line__(p, l, is_floating_point<T>());
}
friend inline bool is_parallel__(const Line& x, const
    Line& y, true_type){
    return fabs(x.a*y.b - x.b*y.a) < EPS;
}
friend inline bool is_parallel__(const Line& x, const
    Line& y, false_type){
    return x.a*y.b == x.b*y.a;
}
friend inline bool is_parallel(const Line& x, const
    Line& y){
    return is_parallel__(x, y, is_floating_point<T>());
}
friend inline Pt get_inter(const Line& x, const Line&
    y){
    typedef long double llf;
    if(x==y) return INF_P;
    if(is_parallel(x, y)) return NOT_EXIST;
    llf delta = x.a*y.b - x.b*y.a;
    llf delta_x = x.b*y.c - x.c*y.b;
    llf delta_y = x.c*y.a - x.a*y.c;
    return Pt(delta_x / delta, delta_y / delta);
}
friend ostream& operator<<(ostream& ss, const Line& o
    ){
    ss<<o.a<<"x+"<<o.b<<"y+"<<o.c<<"=0";
    return ss;
}
};
template<typename T>
inline Line<T> get_line(const Point<T>& a, const Point<
    T>& b){
    return Line<T>(a.y-b.y, b.x-a.x, (b.y-a.y)*a.x-(b.x-a
        .x)*a.y);
}

```

## 5.4 Triangle Circumcentre

```

template<typename T>
Circle<llf> get_circum(const Point<T>& a, const Point<T>
    & b, const Point<T>& c){
    llf a1 = a.x-b.x;
    llf b1 = a.y-b.y;
    llf c1 = (a.x+b.x)/2 * a1 + (a.y+b.y)/2 * b1;
    llf a2 = a.x-c.x;
    llf b2 = a.y-c.y;
    llf c2 = (a.x+c.x)/2 * a2 + (a.y+c.y)/2 * b2;

    Circle<llf> cc;
    cc.o.x = (c1*b2-b1*c2)/(a1*b2-b1*a2);
    cc.o.y = (a1*c2-c1*a2)/(a1*b2-b1*a2);
    cc.r = hypot(cc.o.x-a.x, cc.o.y-a.y);
    return cc;
}

```

## 5.5 2D Convex Hull

```

template<typename T>
class ConvexHull_2D{
private:
    typedef Point<T> PT;
    vector<PT> dots;
    struct myhash{

```

```

uint64_t operator()(const PT& a) const {
    uint64_t xx=0, yy=0;
    memcpy(&xx, &a.x, sizeof(a.x));
    memcpy(&yy, &a.y, sizeof(a.y));
    uint64_t ret = xx*17+yy*31;
    ret = (ret ^ (ret >> 16))*0x9E3779B1;
    ret = (ret ^ (ret >> 13))*0xC2B2AE35;
    ret = ret ^ xx;
    return (ret ^ (ret << 3)) * yy;
}
};
unordered_set<PT, myhash> in_hull;
public:
    inline void init(){in_hull.clear();dots.clear();}
    void insert(const PT& x){dots.PB(x);}
    void solve(){
        sort(ALL(dots), [](const PT& a, const PT& b){
            return tie(a.x, a.y) < tie(b.x, b.y);
        });
        vector<PT> stk(SZ(dots)<<1);
        int top = 0;
        for(auto p: dots){
            while(top >= 2 and cross(p-stk[top-2], stk[top
                -1]-stk[top-2]) <= 0)
                top--;
            stk[top++] = p;
        }
        for(int i=SZ(dots)-2, t = top+1;i>=0;i--){
            while(top >= t and cross(dots[i]-stk[top-2], stk[
                top-1]-stk[top-2]) <= 0)
                top--;
            stk[top++] = dots[i];
        }
        stk.resize(top-1);
        swap(stk, dots);
        for(auto i: stk) in_hull.insert(i);
    }
    vector<PT> get(){return dots;}
    inline bool in_it(const PT& x){
        return in_hull.find(x)!=in_hull.end();
    }
};

```

## 5.6 2D Farthest Pair

```

// stk is from convex hull
n = (int)(stk.size());
int pos = 1, ans = 0; stk.push_back(arr[0]);
for(int i=0;i<n;i++){
    while(abs(cross(stk[i+1]-stk[i], stk[(pos+1)%n]-stk[i
        ])))\
        > abs(cross(stk[i+1]-stk[i], stk[pos]-stk[i]))) pos
        = (pos+1)%n;
    ans = max({ans, dis(stk[i], stk[pos]), dis(stk[i+1],
        stk[pos])});
}

```

## 5.7 2D Coset Pair

```

struct Point{
    llf x, y;
    llf dis;
} arr[N];

inline llf get_dis(Point a, Point b){
    return hypot(a.x-b.x, a.y-b.y);
}

llf solve(){
    int cur = rand()%n;
    for(int i=0;i<n;i++) arr[i].dis = get_dis(arr[cur],
        arr[i]);
    sort(arr, arr+n, [](Point a, Point b){return a.dis <
        b.dis;});
    llf ans = 1e50;
    for(int i=0;i<n;i++){
        for(int j=i+1;j<n;j++){
            if(arr[j].dis - arr[i].dis > ans) break;
            ans = min(ans, get_dis(arr[i], arr[j]));
        }
    }
    return ans;
}

```



```

}

```

## 5.8 SimulateAnnealing

```

double getY(double);
int main(){
    int rr, ll;
    default_random_engine rEng(time(NULL));
    uniform_real_distribution<double> Range(-1,1);
    uniform_real_distribution<double> expR(0,1);
    auto Random=bind(Range,rEng), expRand=bind(expR,rEng);
    ;
    int step=0;
    double pace=rr-ll, mini=0.95; // need to search for it
    double x=max(min(Random()*pace+ll, rr), ll), y=getY(x);
    while(pace>=1e-7){
        double newX = max(min(x + Random()*pace, rr), ll);
        double newY = getY(newX);
        if(newY < y || expRand() < exp(-step))
            x=newX, y=newY;
        step++;
        pace*=mini;
    }
}

```

## 5.9 Ternary Search on Integer

```

int TernarySearch(int l, int r) {
    // (l, r]
    while (r - l > 1){
        int mid = (l + r)>>1;
        if (f(mid) > f(mid + 1)) r = mid;
        else l = mid;
    }
    return l+1;
}

```

## 5.10 Minimum Covering Circle

```

template<typename T>
Circle<llf> MinCircleCover(const vector<Point<T>>& pts)
{
    random_shuffle(ALL(pts));
    Circle<llf> c = {pts[0], 0};
    int n = SZ(pts);
    for(int i=0;i<n;i++){
        if(pts[i].in(c)) continue;
        c = {pts[i], 0};
        for(int j=0;j<i;j++){
            if(pts[j].in(c)) continue;
            c.o = (pts[i] + pts[j]) / 2;
            c.r = pts[i].dis(c.o);
            for(int k=0;k<j;k++){
                if(pts[k].in(c)) continue;
                c = get_circum(pts[i], pts[j], pts[k]);
            }
        }
    }
    return c;
}

```

## 5.11 KDTree (Nearest Point)

```

const int MXN = 100005;
struct KDTree {
    struct Node {
        int x,y,x1,y1,x2,y2;
        int id,f;
        Node *L, *R;
    }tree[MXN];
    int n;
    Node *root;
    LL dis2(int x1, int y1, int x2, int y2) {
        LL dx = x1-x2;
        LL dy = y1-y2;

```

```

        return dx*dx+dy*dy;
    }
    static bool cmpx(Node& a, Node& b){ return a.x<b.x; }
    static bool cmpy(Node& a, Node& b){ return a.y<b.y; }
    void init(vector<pair<int,int>> ip) {
        n = ip.size();
        for (int i=0; i<n; i++) {
            tree[i].id = i;
            tree[i].x = ip[i].first;
            tree[i].y = ip[i].second;
        }
        root = build_tree(0, n-1, 0);
    }
    Node* build_tree(int L, int R, int dep) {
        if (L>R) return nullptr;
        int M = (L+R)/2;
        tree[M].f = dep%2;
        nth_element(tree+L, tree+M, tree+R+1, tree[M].f ?
            cmpy : cmpx);
        tree[M].x1 = tree[M].x2 = tree[M].x;
        tree[M].y1 = tree[M].y2 = tree[M].y;

        tree[M].L = build_tree(L, M-1, dep+1);
        if (tree[M].L) {
            tree[M].x1 = min(tree[M].x1, tree[M].L->x1);
            tree[M].x2 = max(tree[M].x2, tree[M].L->x2);
            tree[M].y1 = min(tree[M].y1, tree[M].L->y1);
            tree[M].y2 = max(tree[M].y2, tree[M].L->y2);
        }
        tree[M].R = build_tree(M+1, R, dep+1);
        if (tree[M].R) {
            tree[M].x1 = min(tree[M].x1, tree[M].R->x1);
            tree[M].x2 = max(tree[M].x2, tree[M].R->x2);
            tree[M].y1 = min(tree[M].y1, tree[M].R->y1);
            tree[M].y2 = max(tree[M].y2, tree[M].R->y2);
        }
        return tree+M;
    }
    int touch(Node* r, int x, int y, LL d2){
        LL dis = sqrt(d2)+1;
        if (x<r->x1-dis || x>r->x2+dis ||
            y<r->y1-dis || y>r->y2+dis)
            return 0;
        return 1;
    }
    void nearest(Node* r, int x, int y,
        int &mID, LL &md2){
        if (!r || !touch(r, x, y, md2)) return;
        LL d2 = dis2(r->x, r->y, x, y);
        if (d2 < md2 || (d2 == md2 && mID < r->id)) {
            mID = r->id;
            md2 = d2;
        }
        // search order depends on split dim
        if ((r->f == 0 && x < r->x) ||
            (r->f == 1 && y < r->y)) {
            nearest(r->L, x, y, mID, md2);
            nearest(r->R, x, y, mID, md2);
        } else {
            nearest(r->R, x, y, mID, md2);
            nearest(r->L, x, y, mID, md2);
        }
    }
    int query(int x, int y) {
        int id = 1029384756;
        LL d2 = 102938475612345678LL;
        nearest(root, x, y, id, d2);
        return id;
    }
}tree;

```

## 6 Stringology

### 6.1 Hash

```

class Hash{
private:
    static const int N = 1000000;
    const int p = 127, q = 1208220623;
    int sz, prefix[N], power[N];
    inline int add(int x, int y){return x+y>=q?x+y-q:x+y;
}

```

```

inline int sub(int x, int y){return x-y<0?x-y+q:x-y;}
inline int mul(int x, int y){return 1LL*x*y%q;}
public:
void init(const std::string &x){
    sz = x.size();
    prefix[0]=0;
    for(int i=1;i<=sz;i++) prefix[i]=add(mul(prefix[i-1], p), x[i-1]);
    power[0]=1;
    for(int i=1;i<=sz;i++) power[i]=mul(power[i-1], p);
}
int query(int l, int r){
    // 1-base (L, r]
    return sub(prefix[r], mul(prefix[l], power[r-l]));
}
};

```

## 6.2 Suffix Array

```

//help by http://www.geeksforgeeks.org/suffix-array-set-2-a-nlognlogn-algorithm/
struct sfx{
    int index;
    int r,nr;
};
char str[N + 10];
int len;
vector<sfx> srs[N + 10];
int mapping[N + 10];
sfx sa[N + 10];
bool cmp(sfx a,sfx b){
    if(a.r==b.r){
        return a.nr<b.nr;
    }else{
        return a.r<b.r;
    }
}
void SA(){
    len = strlen(str);
    for(int i=0;i<len;i++){
        sa[i].index = i;
        sa[i].r=str[i];
        sa[i].nr=(i+1>=len)?0:str[i+1];
    }
    //sort(sa,sa+len,cmp);
    radixSort();
    for(int j=2;j<=len;j*=2){
        int cnt=1;
        int rr = sa[0].r;
        sa[0].r=cnt;
        mapping[sa[0].index]=0;
        for(int i=1;i<len;i++){
            if(sa[i].r == rr && sa[i].nr == sa[i-1].nr){
                rr=sa[i].r;
                sa[i].r=cnt;
            }else{
                rr=sa[i].r;
                sa[i].r=++cnt;
            }
            mapping[sa[i].index]=i;
        }
        for(int i=0;i<len;i++){
            int nn = sa[i].index+j;
            sa[i].nr = (nn>=len)?0:sa[mapping[nn]].r;
        }
        //sort(sa, sa+len, cmp);
        radixSort();
    }
}
void radixSort(){
    int m = 0;
    for(int i=0;i<len;i++){
        srs[sa[i].nr].PB(sa[i]);
        m=max(m,sa[i].nr);
    }
    int cnt=0;
    for(int i=0;i<=m;i++){
        if(srs[i].empty())continue;
        for(auto j:srs[i]){
            sa[cnt++] = j;
        }
        srs[i].clear();
    }
    m = 0;
}

```

```

for(int i=0;i<len;i++){
    srs[sa[i].r].PB(sa[i]);
    m=max(m,sa[i].r);
}
cnt=0;
for(int i=0;i<=m;i++){
    if(srs[i].empty())continue;
    for(auto j:srs[i]){
        sa[cnt++] = j;
    }
    srs[i].clear();
}
}
}

```

## 6.3 Aho-Corasick Algorithm

```

class AhoCorasick{
private:
    static constexpr int Z = 26;
    struct node{
        node *nxt[ Z ], *fail;
        vector< int > data;
        node(): fail( nullptr ) {
            memset( nxt, 0, sizeof( nxt ) );
            data.clear();
        }
    } *rt;
    inline int Idx( char c ) { return c - 'a'; }
public:
    void init() { rt = new node(); }
    void add( const string& s, int d ) {
        node* cur = rt;
        for ( auto c : s ) {
            if ( not cur->nxt[ Idx( c ) ] )
                cur->nxt[ Idx( c ) ] = new node();
            cur = cur->nxt[ Idx( c ) ];
        }
        cur->data.push_back( d );
    }
    void compile() {
        vector< node* > bfs;
        size_t ptr = 0;
        for ( int i = 0 ; i < Z ; ++ i ) {
            if ( not rt->nxt[ i ] )
                continue;
            rt->nxt[ i ]->fail = rt;
            bfs.push_back( rt->nxt[ i ] );
        }
        while ( ptr < bfs.size() ) {
            node* u = bfs[ ptr ++ ];
            for ( int i = 0 ; i < Z ; ++ i ) {
                if ( not u->nxt[ i ] )
                    continue;
                node* u_f = u->fail;
                while ( u_f ) {
                    if ( not u_f->nxt[ i ] ) {
                        u_f = u_f->fail;
                        continue;
                    }
                    u->nxt[ i ]->fail = u_f->nxt[ i ];
                    break;
                }
                if ( not u_f ) u->nxt[ i ]->fail = rt;
                bfs.push_back( u->nxt[ i ] );
            }
        }
    }
    void match( const string& s, vector< int >& ret ) {
        node* u = rt;
        for ( auto c : s ) {
            while ( u != rt and not u->nxt[ Idx( c ) ] )
                u = u->fail;
            u = u->nxt[ Idx( c ) ];
            if ( not u ) u = rt;
            node* tmp = u;
            while ( tmp != rt ) {
                for ( auto d : tmp->data )
                    ret.push_back( d );
                tmp = tmp->fail;
            }
        }
    }
} ac;

```

## 6.4 Suffix Automaton

```

struct Node{
    Node *green, *edge[26];
    int max_len;
    Node(const int _max_len)
        : green(NULL), max_len(_max_len){
        memset(edge,0,sizeof(edge));
    }
} *ROOT, *LAST;
void Extend(const int c) {
    Node *cursor = LAST;
    LAST = new Node((LAST->max_len) + 1);
    for(; cursor && cursor->edge[c]; cursor=cursor->green)
        cursor->edge[c] = LAST;
    if (!cursor)
        LAST->green = ROOT;
    else {
        Node *potential_green = cursor->edge[c];
        if((potential_green->max_len)==(cursor->max_len+1))
            LAST->green = potential_green;
        else {
            //assert(potential_green->max_len>(cursor->max_len+1));
            Node *wish = new Node((cursor->max_len) + 1);
            for(; cursor && cursor->edge[c]==potential_green;
                cursor = cursor->green)
                cursor->edge[c] = wish;
            for (int i = 0; i < 26; i++)
                wish->edge[i] = potential_green->edge[i];
            wish->green = potential_green->green;
            potential_green->green = wish;
            LAST->green = wish;
        }
    }
}
char S[1000001], A[1000001];
int N;
int main(){
    scanf("%d%s", &N, S);
    ROOT = LAST = new Node(0);
    for (int i = 0; S[i]; i++)
        Extend(S[i] - 'a');
    while (N--){
        scanf("%s", A);
        Node *cursor = ROOT;
        bool ans = true;
        for (int i = 0; A[i]; i++){
            cursor = cursor->edge[A[i] - 'a'];
            if (!cursor) {
                ans = false;
                break;
            }
        }
        puts(ans ? "Yes" : "No");
    }
    return 0;
}

```

## 6.5 KMP

```

int F[N<<1];
void KMP(char s1[], char s2[], int n, int m){
    // make F[] for s1+'\0'+s2;
    char ss[N<<1];
    int len = n+m+1;
    for(int i=0;i<n;i++) ss[i] = s1[i];
    ss[n] = '\0';
    for(int i=0;i<m;i++) ss[i+n] = s2[i];
    F[0] = F[1] = 0;
    for(int i=1;i<len;i++){
        int j = F[i];
        while(j > 0 and ss[i]!=ss[j]) j = F[j];
        F[i+1] = (ss[i]==ss[j]?j+1:0);
    }
    // just find (F[len2+i] == len2)
    // i from 1 to len+1 for matching
}
/*
[0, i]是個循環字串，且循環節為i-f[i]:
if(f[i]>0 and i%(i-f[i])==0)
cout << i << " " << i/(i-f[i]) << '\n';
*/

```

## 6.6 Z value

```

char s[MAXN];
int len,z[MAXN];
void Z_value() {
    int i,j,left,right;
    left=right=0; z[0]=len;
    for(i=1;i<len;i++) {
        j=max(min(z[i-left],right-i),0);
        for(;i+j<len&&s[i+j]==s[j];j++);
        z[i]=j;
        if(i+z[i]>right) {
            right=i+z[i];
            left=i;
        }
    }
}

```

## 6.7 Lexicographically Smallest Rotation

```

string mcp(string s){
    int n = s.length();
    s += s;
    int i=0, j=1;
    while (i<n && j<n){
        int k = 0;
        while (k < n && s[i+k] == s[j+k]) k++;
        if (s[i+k] <= s[j+k]) j += k+1;
        else i += k+1;
        if (i == j) j++;
    }
    int ans = i < n ? i : j;
    return s.substr(ans, n);
}

```

## 6.8 BWT

```

struct BurrowsWheeler{
#define SIGMA 26
#define BASE 'a'
    vector<int> v[ SIGMA ];
    void BWT(char* ori, char* res){
        // make ori -> ori + ori
        // then build suffix array
    }
    void iBWT(char* ori, char* res){
        for( int i = 0 ; i < SIGMA ; i ++ )
            v[ i ].clear();
        int len = strlen( ori );
        for( int i = 0 ; i < len ; i ++ )
            v[ ori[i] - BASE ].push_back( i );
        vector<int> a;
        for( int i = 0 , ptr = 0 ; i < SIGMA ; i ++ )
            for( auto j : v[ i ] ){
                a.push_back( j );
                ori[ ptr ++ ] = BASE + i;
            }
        for( int i = 0 , ptr = 0 ; i < len ; i ++ ){
            res[ i ] = ori[ a[ ptr ] ];
            ptr = a[ ptr ];
        }
        res[ len ] = 0;
    }
} bwt;

```

## 6.9 Palindromic Tree

```

struct palindromic_tree{
    struct node{
        int next[26],fail,len;
        int cnt,num,st,ed;
        node(int l=0):fail(0),len(1),cnt(0),num(0){
            for(int i=0;i<26;++i)next[i]=0;
        }
    };
    vector<node> state;
    vector<char> s;
    int last,n;
}

```

```

void init(){
    state.clear();
    s.clear();
    last=1;
    n=0;
    state.push_back(0);
    state.push_back(-1);
    state[0].fail=1;
    s.push_back(-1);
}
int get_fail(int x){
    while(s[n-state[x].len-1]!=s[n])x=state[x].fail;
    return x;
}
void add(int c){
    s.push_back(c-'a');
    ++n;
    int cur=get_fail(last);
    if(!state[cur].next[c]){
        int now=state.size();
        state.push_back(state[cur].len+2);
        state[now].fail=get_fail(state[cur].fail).next[c];
        state[cur].next[c]=now;
        state[now].num=state[state[now].fail].num+1;
    }
    last=state[cur].next[c];
    ++state[last].cnt;
}
int size(){
    return state.size()-2;
}
}pt;

int main() {
    string s;
    cin >> s;
    pt.init();
    for (int i=0; i<SZ(s); i++) {
        int prvsz = pt.size();
        pt.add(s[i]);
        if (prvsz != pt.size()) {
            int r = i;
            int l = r - pt.state[pt.last].len + 1;
            cout << "Find pal @ [" << l << " " << r << "]" : "
                << s.substr(l,r-l+1) << endl;
        }
    }
    return 0;
}

```

## 7 Misc

### 7.1 Degree Sequence Validity

#### 7.1.1 Erdős–Gallai Theorem

$d_1 \geq \dots \geq d_n$  is a valid degree sequence iff

$$\sum_{k=1}^n d_k \equiv 0 \pmod{2}$$

$$\wedge \forall 1 \leq k \leq n, \sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$$

#### 7.1.2 Havel–Hakimi algorithm

find the vertex who has greatest degree unused, connect it with other greatest vertex.

### 7.2 MaximumEmptyRect

```

int max_empty_rect(int n, int m, bool blocked[N][N]){
    static int mxu[2][N], me=0, he=1, ans=0;
    for(int i=0; i<m; i++) mxu[he][i]=0;
    for(int i=0; i<n; i++){
        stack<PII> st;
        for(int j=0; j<m; j++){
            if(blocked[i][j]) mxu[me][j]=0;
            else mxu[me][j]=mxu[he][j]+1;
            int la = j;
            while(!stk.empty() && stk.top().FF > mxu[me][j]){

```

```

                int x1 = i - stk.top().FF, x2 = i;
                int y1 = stk.top().SS, y2 = j;
                la = stk.top().SS; stk.pop();
                ans=max(ans, (x2-x1)*(y2-y1));
            }
            if(stk.empty() || stk.top().FF < mxu[me][j])
                stk.push({mxu[me][j], la});
        }
        while(!stk.empty()){
            int x1 = i - stk.top().FF, x2 = i;
            int y1 = stk.top().SS-1, y2 = m-1;
            stk.pop();
            ans=max(ans, (x2-x1)*(y2-y1));
        }
        swap(me, he);
    }
    return ans;
}

```

### 7.3 DP-opt Condition

#### 7.3.1 totally monotone (concave/convex)

$$\forall i < i', j < j', B[i][j] \leq B[i'][j] \implies B[i][j'] \leq B[i'][j']$$

$$\forall i < i', j < j', B[i][j] \geq B[i'][j] \implies B[i][j'] \geq B[i'][j']$$

#### 7.3.2 monge condition (concave/convex)

$$\forall i < i', j < j', B[i][j] + B[i'][j'] \geq B[i][j'] + B[i'][j]$$

$$\forall i < i', j < j', B[i][j] + B[i'][j'] \leq B[i][j'] + B[i'][j]$$

### 7.4 Convex 1D/1D DP

```

struct segment {
    int i, l, r;
    segment() {}
    segment(int a, int b, int c): i(a), l(b), r(c) {}
};

inline long long f(int l, int r) {
    return dp[l] + w(l + 1, r);
}

void solve() {
    dp[0] = 0;
    deque<segment> deq; deq.push_back(segment(0, 1, n));
    for (int i = 1; i <= n; ++i) {
        dp[i] = f(deq.front().i, i);
        while (deq.size() && deq.front().r < i + 1) deq.pop_front();
        deq.front().l = i + 1;
        segment seg = segment(i, i + 1, n);
        while (deq.size() && f(i, deq.back().l) < f(deq.back().i, deq.back().l)) deq.pop_back();
        if (deq.size()) {
            int d = 1048576, c = deq.back().l;
            while (d >= 1) if (c + d <= deq.back().r) {
                if (f(i, c + d) > f(deq.back().i, c + d)) c += d;
            }
            deq.back().r = c; seg.l = c + 1;
        }
        if (seg.l <= n) deq.push_back(seg);
    }
}

```

### 7.5 Josephus Problem

```

// n people kill m for each turn
int f(int n, int m) {
    int s = 0;
    for (int i = 2; i <= n; i++)
        s = (s + m) % i;
    return s;
}

// died at kth
int kth(int n, int m, int k){
    if (m == 1) return n-1;
    for (k = k*m+m-1; k >= n; k = k-n+(k-n)/(m-1));
    return k;
}

```

```

}
```

## 7.6 Cactus Matching

```

const int maxn=200010;
vector<int> init_g[maxn],g[maxn*2];
int dfn[maxn],low[maxn],par[maxn],dfs_idx,bcc_id;
int n;
void tarjan(int u){
    dfn[u]=low[u]=++dfs_idx;
    for(int i=0;i<(int)init_g[u].size();i++){
        int v=init_g[u][i];
        if(v==par[u]) continue;
        if(!dfn[v]){
            par[v]=u;
            tarjan(v);
            low[u]=min(low[u],low[v]);
            if(dfn[u]<low[v]){
                g[u].push_back(v);
                g[v].push_back(u);
            }
        }else{
            low[u]=min(low[u],dfn[v]);
            if(dfn[v]<dfn[u]){
                int temp_v=u;
                bcc_id++;
                while(temp_v!=v){
                    g[bcc_id+n].push_back(temp_v);
                    g[temp_v].push_back(bcc_id+n);
                    temp_v=par[temp_v];
                }
                g[bcc_id+n].push_back(v);
                g[v].push_back(bcc_id+n);
                reverse(g[bcc_id+n].begin(),g[bcc_id+n].end());
            }
        }
    }
}
int dp[maxn][2],min_dp[2][2],tmp[2][2],tp[2];
void dfs(int u,int fa){
    if(u<=n){
        for(int i=0;i<(int)g[u].size();i++){
            int v=g[u][i];
            if(v==fa) continue;
            dfs(v,u);
            memset(tp,0x8f,sizeof tp);
            if(v<=n){
                tp[0]=dp[u][0]+max(dp[v][0],dp[v][1]);
                tp[1]=max(
                    dp[u][0]+dp[v][0]+1,
                    dp[u][1]+max(dp[v][0],dp[v][1])
                );
            }else{
                tp[0]=dp[u][0]+dp[v][0];
                tp[1]=max(dp[u][0]+dp[v][1],dp[u][1]+dp[v][0]);
            }
            dp[u][0]=tp[0],dp[u][1]=tp[1];
        }
    }else{
        for(int i=0;i<(int)g[u].size();i++){
            int v=g[u][i];
            if(v==fa) continue;
            dfs(v,u);
        }
        min_dp[0][0]=0;
        min_dp[1][1]=1;
        min_dp[0][1]=min_dp[1][0]=-0x3f3f3f3f;
        for(int i=0;i<(int)g[u].size();i++){
            int v=g[u][i];
            if(v==fa) continue;
            memset(tmp,0x8f,sizeof tmp);
            tmp[0][0]=max(
                min_dp[0][0]+max(dp[v][0],dp[v][1]),
                min_dp[0][1]+dp[v][0]
            );
            tmp[0][1]=min_dp[0][0]+dp[v][0]+1;
            tmp[1][0]=max(
                min_dp[1][0]+max(dp[v][0],dp[v][1]),
                min_dp[1][1]+dp[v][0]
            );
            tmp[1][1]=min_dp[1][0]+dp[v][0]+1;
            memcpy(min_dp,tmp,sizeof tmp);
        }
        dp[u][1]=max(min_dp[0][1],min_dp[1][0]);
    }
}
```

```

        dp[u][0]=min_dp[0][0];
    }
}
int main(){
    int m,a,b;
    scanf("%d%d",&n,&m);
    for(int i=0;i<m;i++){
        scanf("%d%d",&a,&b);
        init_g[a].push_back(b);
        init_g[b].push_back(a);
    }
    par[1]=-1;
    tarjan(1);
    dfs(1,-1);
    printf("%d\n",max(dp[1][0],dp[1][1]));
    return 0;
}
```