

Contents

1 Basic	
1.1 Default Code	1
1.2 IncreaseStackSize	2
1.3 Pragma optimization	2
1.4 Quick Random	2
1.5 IO Optimization	2
2 Data Structure	
2.1 BigInt	2
2.2 Fraction	3
2.3 ScientificNotation	4
2.4 unordered_map	4
2.5 extc_balance_tree	4
2.6 extc_heap	4
2.7 PairingHeap	5
2.8 Disjoint Set	5
2.9 Treap	5
2.10 SparseTable	6
2.11 FenwickTree	6
3 Graph	
3.1 BCC Edge	7
3.2 BCC Vertex	7
3.3 Strongly Connected Components	7
3.4 Bipartite Matching	8
3.5 MinimumCostMaximumFlow	8
3.6 MaximumFlow	8
4 Math	
4.1 Prime Table	9
4.2 ax+by=gcd	9
4.3 Pollard Rho	9
4.4 Linear Sieve	9
4.5 NloglogN Sieve	10
4.6 Range Sieve	10
4.7 Miller Rabin	10
4.8 Inverse Element	10
4.9 Euler Phi Function	10
4.10 Gauss Elimination	10
4.11 Fast Fourier Transform	11
4.12 Chinese Remainder	11
4.13 NTT	11
5 Geometry	
5.1 Point Class	12
5.2 2D Convex Hull	12
5.3 SimulateAnnealing	14
6 Stringology	
6.1 Hash	14
6.2 Suffix Array	14
6.3 KMP	15

1 Basic

1.1 Default Code

```

#include <iostream>
#include <iomanip>
#include <string>
#include <algorithm>
#include <vector>
#include <queue>
#include <bitset>
#include <map>
#include <set>
#include <unordered_map>
#include <unordered_set>
#include <cstdio>
#include <cstdlib>
#include <cstring>
#include <ctime>
#include <random>
#include <utility>
#include <stack>
#include <sstream>
#include <functional>
#include <deque>
#include <cassert>
using namespace std;
/* include everything for Kotori~ <3 */

typedef long long lld;
typedef unsigned long long llu;
typedef long double llf;
typedef pair<int,int> PII;
typedef pair<int,lld> PIL;
typedef pair<lld,int> PLI;
typedef pair<lld,lld> PLL;
template<typename T>
using maxHeap = priority_queue<T,vector<T>,less<T>>;
template<typename T>
using minHeap = priority_queue<T,vector<T>,greater<T>>;
/* define some types for Ruby! */

#define FF first
#define SS second
#define SZ(x) (int)(x.size())
#define ALL(x) begin(x), end(x)
#define PB push_back
#define WC(x) while(x--)
/* make code shorter for Di~a~ */

template<typename Iter>
ostream& _out(ostream& s, Iter b, Iter e) {
    s<<"[";
    for ( auto it=b; it!=e; it++ ) s<<(it==b?"":" ")<<*it
    ;
    s<<"]";
    return s;
}

template<typename A, typename B>
ostream& operator << ( ostream& s, const pair<A,B> &p )
{ return s<<"("<<p.FF<<","<<p.SS<<")"; }
template<typename T>
ostream& operator << ( ostream& s, const vector<T> &c )
{ return _out(s,ALL(c)); }
/* make output easier for Ainyan~n~ */

bool debug = 0;
#define DUMP(x) if(debug) cerr<<__PRETTY_FUNCTION__<<":\n"
/*<<__LINE__<<" - "<<#x<<"="<<x<<"\n"
template<typename T>
void DEBUG(const T& x){if(debug) cerr<<x;}
template<typename T, typename... Args>
void DEBUG(const T& head,const Args&...tail){
    if(debug){cerr<<head; DEBUG(tail...);}
}
/* Let's debug with Nico~Nico~Ni */

int main(int argc, char* argv[]){
    if(argc>1 and string(argv[1])=="-D") debug=1;
    if(!debug){ios_base::sync_with_stdio(0);cin.tie(0);}
    return 0;
}

```

1.2 IncreaseStackSize

```
//stack resize
asm( "mov %0,%esp\n" ::"g"(mem+10000000) );
//change esp to rsp if 64-bit system

//stack resize (linux)
#include <sys/resource.h>
void increase_stack_size() {
    const rlim_t ks = 64*1024*1024;
    struct rlimit rl;
    int res=getrlimit(RLIMIT_STACK, &rl);
    if(res==0){
        if(rl.rlim_cur<ks){
            rl.rlim_cur=ks;
            res=setrlimit(RLIMIT_STACK, &rl);
        }
    }
}
```

1.3 Pragma optimization

```
#pragma GCC optimize("Ofast,no-stack-protector,no-math-errno")
#pragma GCC optimize("unroll-loops")
#pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,abm,mmx,avx,tune=native")
```

1.4 Quick Random

```
// PRNG {{{
template<class T, T x1, T x2, T x3, int y1, int y2, int y3>
struct PRNG {
    using S = typename std::make_signed<T>::type;
    T s;
    PRNG(T _s = 0) : s(_s) {}
    T next() {
        T z = (s += x1);
        z = (z ^ (z >> y1)) * x2;
        z = (z ^ (z >> y2)) * x3;
        return z ^ (z >> y3);
    }
    T next(T n) { return next() % n; }
    S next(S l, S r) { return l + next(r - l + 1); }
    T operator()() { return next(); }
    T operator()(T n) { return next(n); }
    S operator()(S l, S r) { return next(l, r); }
    static T gen(T s) { return PRNG(s)(); }
    template<class U>
    void shuffle(U first, U last) {
        size_t n = last - first;
        for (size_t i = 0; i < n; i++) swap(first[i], first[next(i + 1)]);
    }
};

using R32 = PRNG<uint32_t, 0x9E3779B1, 0x85EBCA6B, 0xC2B2AE35, 16, 13, 16>;
R32 r32;

using R64 = PRNG<uint64_t, 0x9E3779B97F4A7C15, 0xBF58476D1CE4E5B9, 0x94D049BB133111EB, 30, 27, 31>;
R64 r64;
// }}}

```

1.5 IO Optimization

```
// I/O optimization start {{{
static inline int_fast32_t fastAtoi(const char *p,
    uint_fast32_t len) {
    uint_fast32_t res = 0;
    uint_fast8_t neg = *p == '-';
    if (neg) p++, len--;
    switch (len) {
        case 10: res += (*p++ & 15) * 1000000000;
        case 9: res += (*p++ & 15) * 100000000;
        case 8: res += (*p++ & 15) * 10000000;
    }
}
```

```
    case 7: res += (*p++ & 15) * 1000000;
    case 6: res += (*p++ & 15) * 100000;
    case 5: res += (*p++ & 15) * 10000;
    case 4: res += (*p++ & 15) * 1000;
    case 3: res += (*p++ & 15) * 100;
    case 2: res += (*p++ & 15) * 10;
    case 1: res += (*p & 15);
}
return res * (neg ? -1 : 1);
}

static inline bool getRawChar(char *c) {
    static char buf[1 << 20], *p = buf, *end = buf;
    if (p == end) {
        if ((end = buf + fread(buf, 1, 1 << 20, stdin)) == buf) return false;
        p = buf;
    }
    *c = *p++;
    return true;
}

static inline bool getInt(int32_t *x) {
    static char buf[12];
    uint_fast32_t i = 0;
    while (getRawChar(buf + i)) {
        if ((unsigned)(buf[i] - '0') > 10U && buf[i] != '-') {
            if (i) break;
            else continue;
        }
        i++;
    }
    if (!i) return false;
    *x = fastAtoi(buf, i);
    return true;
}
// I/O optimization end }}}

```

2 Data Structure

2.1 BigInt

```
struct BigInt{
    static const int LEN = 60;
    static const int BIGMOD = 10000;

    int s;
    int vl, v[LEN];
    // vector<int> v;
    BigInt() : s(1) { vl = 0; }
    BigInt(long long a) {
        s = 1; vl = 0;
        if (a < 0) { s = -1; a = -a; }
        while (a) {
            push_back(a % BIGMOD);
            a /= BIGMOD;
        }
    }
    BigInt(string str) {
        s = 1; vl = 0;
        int stPos = 0, num = 0;
        if (!str.empty() && str[0] == '-') {
            stPos = 1;
            s = -1;
        }
        for (int i=SZ(str)-1, q=1; i>=stPos; i--) {
            num += (str[i] - '0') * q;
            if ((q *= 10) >= BIGMOD) {
                push_back(num);
                num = 0; q = 1;
            }
        }
        if (num) push_back(num);
        n();
    }

    int len() const {
        return vl;
        // return SZ(v);
    }
    bool empty() const { return len() == 0; }
}
```

```

void push_back(int x) {
    v[vl++] = x;
    //    v.PB(x);
}
void pop_back() {
    vl--;
    //    v.pop_back();
}
int back() const {
    return v[vl-1];
    //    return v.back();
}
void n() {
    while (!empty() && !back()) pop_back();
}
void resize(int nl) {
    vl = nl;
    fill(v, v+vl, 0);
    //    v.resize(nl);
    //    fill(ALL(v), 0);
}

void print() const {
    if (empty()) { putchar('0'); return; }
    if (s == -1) putchar('-');
    printf("%d", back());
    for (int i=len()-2; i>=0; i--) printf("%.4d", v[i]);
}
friend ostream& operator << (ostream& out,
    const Bigint &a) {
    if (a.empty()) { out << "0"; return out; }
    if (a.s == -1) out << "-";
    out << a.back();
    for (int i=a.len()-2; i>=0; i--) {
        char str[10];
        sprintf(str, 5, "%.4d", a.v[i]);
        out << str;
    }
    return out;
}

int cp3(const Bigint &b) const {
    if (s != b.s) return s - b.s;
    if (s == -1) return -(*this).cp3(-b);
    if (len() != b.len()) return len() - b.len(); //int
    for (int i=len()-1; i>=0; i--)
        if (v[i] != b.v[i]) return v[i] - b.v[i];
    return 0;
}

bool operator < (const Bigint &b) const { return cp3(b) < 0; }
bool operator <= (const Bigint &b) const { return cp3(b) <= 0; }
bool operator == (const Bigint &b) const { return cp3(b) == 0; }
bool operator != (const Bigint &b) const { return cp3(b) != 0; }
bool operator > (const Bigint &b) const { return cp3(b) > 0; }
bool operator >= (const Bigint &b) const { return cp3(b) >= 0; }

Bigint operator - () const {
    Bigint r = (*this);
    r.s = -r.s;
    return r;
}
Bigint operator + (const Bigint &b) const {
    if (s == -1) return -(*this) + (-b);
    if (b.s == -1) return (*this) - (-b);
    Bigint r;
    int nl = max(len(), b.len());
    r.resize(nl + 1);
    for (int i=0; i<nl; i++) {
        if (i < len()) r.v[i] += v[i];
        if (i < b.len()) r.v[i] += b.v[i];
        if (r.v[i] >= BIGMOD) {
            r.v[i+1] += r.v[i] / BIGMOD;
            r.v[i] %= BIGMOD;
        }
    }
    r.n();
    return r;
}
Bigint operator - (const Bigint &b) const {

```

```

    if (s == -1) return -(*this) - (-b);
    if (b.s == -1) return (*this) + (-b);
    if ((*this) < b) return -(-(*this));
    Bigint r;
    r.resize(len());
    for (int i=0; i<len(); i++) {
        r.v[i] += v[i];
        if (i < b.len()) r.v[i] -= b.v[i];
        if (r.v[i] < 0) {
            r.v[i] += BIGMOD;
            r.v[i+1]--;
        }
    }
    r.n();
    return r;
}
Bigint operator * (const Bigint &b) {
    Bigint r;
    r.resize(len() + b.len() + 1);
    r.s = s * b.s;
    for (int i=0; i<len(); i++) {
        for (int j=0; j<b.len(); j++) {
            r.v[i+j] += v[i] * b.v[j];
            if (r.v[i+j] >= BIGMOD) {
                r.v[i+j+1] += r.v[i+j] / BIGMOD;
                r.v[i+j] %= BIGMOD;
            }
        }
    }
    r.n();
    return r;
}
Bigint operator / (const Bigint &b) {
    Bigint r;
    r.resize(max(1, len() - b.len() + 1));
    int oriS = s;
    Bigint b2 = b; // b2 = abs(b)
    s = b2.s = r.s = 1;
    for (int i=r.len()-1; i>=0; i--) {
        int d=0, u=BIGMOD-1;
        while (d<u) {
            int m = (d+u+1)>>1;
            r.v[i] = m;
            if ((r*b2) > (*this)) u = m-1;
            else d = m;
        }
        r.v[i] = d;
    }
    s = oriS;
    r.s = s * b.s;
    r.n();
    return r;
}
Bigint operator % (const Bigint &b) {
    return (*this) - (*this) / b * b;
}
};

```

2.2 Fraction

```

/*****
n為分子，d為分母
若分數為0則n=0,d=1
若為負數則負號加在分子
必定約到最簡分數
*****/
#ifndef SUNMOON_FRACTION
#define SUNMOON_FRACTION
#include <algorithm>
template <typename T>
struct fraction {
    T n, d;
    fraction(const T &n=0, const T &d=1) : n(n), d(d) {
        T t = std::__gcd(n, d);
        n /= t, d /= t;
        if (d < 0) n = -n, d = -d;
    }
    fraction operator-() const {
        return fraction(-n, d);
    }
    fraction operator+(const fraction &b) const {
        return fraction(n*b.d+b.n*d, d*b.d);
    }
}

```

```

fraction operator-(const fraction &b) const{
    return fraction(n*b.d-b.n*d,d*b.d);
}
fraction operator*(const fraction &b) const{
    return fraction(n*b.n,d*b.d);
}
fraction operator/(const fraction &b) const{
    return fraction(n*b.d,d*b.n);
}
fraction operator+=(const fraction &b){
    return *this=fraction(n*b.d+b.n*d,d*b.d);
}
fraction operator-=(const fraction &b){
    return *this=fraction(n*b.d-b.n*d,d*b.d);
}
fraction operator*=(const fraction &b){
    return *this=fraction(n*b.n,d*b.d);
}
fraction operator/=(const fraction &b){
    return *this=fraction(n*b.d,d*b.n);
}
bool operator <(const fraction &b) const{
    return n*b.d<b.n*d;
}
bool operator >(const fraction &b) const{
    return n*b.d>b.n*d;
}
bool operator ==(const fraction &b) const{
    return n*b.d==b.n*d;
}
bool operator <=(const fraction &b) const{
    return n*b.d<=b.n*d;
}
bool operator >=(const fraction &b) const{
    return n*b.d>=b.n*d;
}
};
#endif

```

2.3 ScientificNotation

```

#include <cmath>
#include <cstdio>
#include <iostream>
#include <algorithm>

struct SciFi{
    typedef double base_t;
    base_t x; int p;
    SciFi(){x=0;p=0;}
    SciFi(base_t k){
        p = floor(log10(k));
        x = k / pow((base_t)10, p);
    }
    SciFi(base_t a, int b){
        x=a;p=b;
    }
    SciFi operator=(base_t k){
        p = floor(log10(k));
        x = k / pow((base_t)10, p);
        return *this;
    }
    SciFi operator*(SciFi k) const{
        int nP = p+k.p;
        base_t nX = x*k.x;
        int tp = floor(log10(nX));
        return SciFi(nX/pow((base_t)10, tp), nP+tp);
    }
    SciFi operator+=(SciFi k){
        p+=k.p;
        x*=k.x;
        int tp = floor(log10(x));
        p+=tp;
        x/=pow((base_t)10, tp);
        return *this;
    }
    SciFi operator+(SciFi k) const{
        int newP = std::min(k.p, p);
        base_t x1 = x*pow((base_t)10, p-newP);
        base_t x2 = k.x*pow((base_t)10, k.p-newP);
        x1+=x2;
        int tp = floor(log10(x1));
        newP+=tp;
        x1 /= pow((base_t)10, tp);
    }
};

```

```

        return SciFi(x1, newP);
    }
    SciFi operator+=(SciFi k){
        int newP = std::min(k.p, p);
        base_t x1 = x*pow((base_t)10, p-newP);
        base_t x2 = k.x*pow((base_t)10, k.p-newP);
        x1+=x2;
        int tp = floor(log10(x1));
        newP+=tp;
        x1 /= pow((base_t)10, tp);
        x=x1;p=newP;
        return *this;
    }
    bool operator<(SciFi a) const{
        if(p == a.p) return x<a.x;
        return p<a.p;
    }
    bool operator>(SciFi a) const{
        if(p == a.p) return x>a.x;
        return p>a.p;
    }
    bool operator==(SciFi a) const{
        return p==a.p and x==a.x;
    }
};

int main(){
    double a; scanf("%lf",&a);
    SciFi aa=a, x;
    x = aa*SciFi(2);
    printf("%.21fe%c%03d\n", x.x, "+-"[x.p<0], abs(x.p));
    return 0;
}

```

2.4 unordered_map

```

#include <ext/pb_ds/assoc_container.hpp>
using __gnu_pbds::cc_hash_table;
using __gnu_pbds::gp_hash_table;
template<typename A, typename B> using hTable1 =
    cc_hash_table<A,B>;
template<typename A, typename B> using hTable2 =
    gp_hash_table<A,B>;

```

2.5 extc_balance_tree

```

#include <functional>
#include <ext/pb_ds/assoc_container.hpp>
using std::less;
using std::greater;
using __gnu_pbds::tree;
using __gnu_pbds::rb_tree_tag;
using __gnu_pbds::ov_tree_tag;
using __gnu_pbds::splay_tree_tag;
using __gnu_pbds::null_type;
using __gnu_pbds::tree_order_statistics_node_update;

template<typename T>
using ordered_set = tree<T, null_type, less<T>,
    rb_tree_tag, tree_order_statistics_node_update>;

template<typename A, B>
using ordered_map = tree<A, B, less<A>, rb_tree_tag,
    tree_order_statistics_node_update>;

int main(){
    ordered_set<int> ss;
    ordered_map<int,int> mm;
    ss.insert(1);
    ss.insert(5);
    assert(*ss.find_by_order(0)==1);
    assert(ss.order_of_key(-1)==0);
    assert(ss.order_of_key(87)==2);
    return 0;
}

```

2.6 extc_heap

```
#include <functional>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/priority_queue.hpp>
using std::less;
using std::greater;
using __gnu_pbds::priority_queue;
using __gnu_pbds::pairing_heap_tag;
using __gnu_pbds::binary_heap_tag;
using __gnu_pbds::binomial_heap_tag;
using __gnu_pbds::rc_binomial_heap_tag;
using __gnu_pbds::thin_heap_tag;

int main() {
    priority_queue<int, less<int>, pairing_heap_tag> pq1,
        pq2;
    pq1.push(1);
    pq2.push(2);
    pq1.join(pq2);
    assert(pq2.size() == 0);
    auto it = pq1.push(87);
    pq1.modify(it, 19);
    while (!pq1.empty()) {
        pq1.top();
        pq1.pop();
    }
    return 0;
}
```

2.7 PairingHeap

```
#include <vector>
using std::vector;

template<class __type, class __cmp=less<__type>>
class pairingHeap {
private:
    struct pairingNode {
        __type val;
        vector<pairingNode*> child;
        pairingNode() {
            val = 0;
            child.clear();
        }
        pairingNode(int x): val(x) {
            child.clear();
        }
    };
    pairingNode* root;
    int count;
    __cmp __cp;
    void remove(pairingNode* cur) {
        if (cur == nullptr) return;
        for (auto i: cur->child) remove(i);
        delete cur;
    }
public:
    pairingHeap() { root = nullptr; count = 0; }
    inline bool empty() { return count == 0; }
    inline __type top() { return root->val; }
    inline int size() { return count; }
    inline void clear() { remove(root); root = nullptr; count = 0; }
    inline void push(__type a) {
        count++;
        auto mynode = new pairingNode(a);
        if (root == nullptr) root = mynode;
        else {
            if (__cp(root->val, mynode->val)) swap(root, mynode);
            root->child.push_back(mynode);
        }
    }
    inline void pop() {
        count--;
        queue<pairingNode*> que;
        for (auto i: root->child) que.push(i);
        delete root;
        while (que.size() > 1) {
            auto tp1 = que.front(); que.pop();
            auto tp2 = que.front(); que.pop();
            if (__cp(tp1->val, tp2->val)) swap(tp1, tp2);
            tp1->child.push_back(tp2);
            que.push(tp1);
        }
    }
}
```

```
if (que.empty()) root = nullptr;
else root = que.front();
}
inline void join(pairingHeap<__type, __cmp>& pq2) {
    if (__cp(root->val, pq2.root->val)) swap(root, pq2.root);
    root->child.push_back(pq2.root);
    count += pq2.count;
    pq2.root = nullptr;
    pq2.count = 0;
}
};

int main() {
    pairingHeap<int> pq1, pq2;
    for (int i = 0; i < 1e5; i++) pq1.push(i);
    for (int i = 1e5; i < 2e5; i++) pq2.push(i);
    pq1.join(pq2);
    while (!pq1.empty()) {
        // cout << pq1.top() << " ";
        pq1.pop();
    }
    return 0;
}
```

2.8 Disjoint Set

```
class DJS {
private:
    vector<int> fa, sz, sv;
    vector<pair<int*, int*>> opt;
    inline void assign(int *k, int v) {
        opt.PB({k, *k});
        *k = v;
    }
public:
    inline void init(int n) {
        fa.resize(n);
        sz.resize(n);
        for (int i = 0; i < n; i++) {
            fa[i] = i;
            sz[i] = 1;
        }
        opt.clear();
    }
    int query(int x) {
        if (fa[x] == x) return x;
        return query(fa[x]);
    }
    inline void merge(int a, int b) {
        int af = query(a), bf = query(b);
        if (af == bf) return;
        if (sz[af] < sz[bf]) swap(af, bf);
        assign(&fa[bf], fa[af]);
        assign(&sz[af], sz[af] + sz[bf]);
    }
    inline void save() { sv.PB(SZ(opt)); }
    inline void undo() {
        int ls = sv.back(); sv.pop_back();
        while (SZ(opt) > ls) {
            pair<int*, int*> cur = opt.back();
            *cur.FF = cur.SS;
            opt.pop_back();
        }
    }
}
```

2.9 Treap

```
#include <cstdlib>

class Treap {
private:
    const int MEM = 500000 + 5;
    unsigned seed;
    inline unsigned myrand() {
        static unsigned seed = time(NULL);
        seed = seed * seed * 127 + seed * 227 + 2147483587;
        seed ^= seed * 97;
        seed /= 7123;
        return seed;
    }
}
```

```

struct node{
    node *lc, *rc;
    int pri, size, val;
    node(){}
    node(int x):
        lc(nullptr),
        rc(nullptr),
        pri(myrand()),
        size(1),
        val(x)
    {}
    inline void pull(){
        size = 1;
        if(lc) size += lc->size;
        if(rc) size += rc->size;
    }
} *root, pool[MEM];
int mem_;
inline node* new_node(int x){
    static int mem_ = 0;
    assert(mem_ < MEM);
    pool[mem_] = node(x);
    return &pool[mem_++];
}
inline int sz(node* x){return x?x->size:0;}
node* merge(node *a, node *b){
    if(!a or !b) return a?a:b;
    if(a->pri > b->pri){
        a->rc = merge(a->rc, b);
        a->pull();
        return a;
    }else{
        b->lc = merge(a, b->lc);
        b->pull();
        return b;
    }
}
void split(Treap* t, int k, Treap*& a, Treap*& b){
    if(!t) a=b=nullptr;
    else if(sz(t->lc) < k){
        a = t;
        split(t->rc, k - sz(t->lc) - 1, a->rc, b);
        a->pull();
    }else{
        b = t;
        split(t->lc, k, a, b->lc);
        b->pull();
    }
}
int oOk(node* rr, int x){
    if(rr==NULL) return 0;
    if((rr->val) < x) return gSize(rr->l)+oOk(rr->r, x)+1;
    else return oOk(rr->l, x);
}
public:
Treap() {root=nullptr; seed=time(NULL); mem_=0;}
void do_something_at(int l, int r){
    // 1-base [l, r]
    split(root, l-1, tl, root);
    split(root, r-l+1, root, tr);
    root = merge(tl, merge(root, tr));
}
void insert(int x){
    node *a, *b;
    split(root, x, a, b);
    root = merge(merge(a, new_node(x)), b);
    root->size = gSize(root->l)+gSize(root->r)+1;
}
void remove(int x){
    //need debug may contain bugs
    node *a, *b, *c, *d;
    split(root, x, a, b);
    a->size = gSize(a->l)+gSize(a->r);
    split(a, x-1, c, d);
    root = merge(b, c);
    root->size = gSize(root->l)+gSize(root->r);
    delete d;
}
int order_of_key(int x){return oOk(root, x);}
};

int main(){
    return 0;
}

```

2.10 SparseTable

```

template<typename T, typename Cmp_=std::less<T>>
class SparseTable{
private:
    vector<vector<T>> table;
    vector<int> lg;
    T cmp_(T a, T b){
        return Cmp_(a, b)?a:b;
    }
public:
    void init(T arr[], int n){
        // 0-base
        lg.resize(n+1);
        lg[0] = -1, lg[1] = 0;
        for(int i=2; i<=n; i++) lg[i] = lg[i>>1]+1;
        table.resize(lg[n]+1);
        table[0].resize(n);
        for(int i=0; i<n; i++) table[0][i] = arr[i];
        for(int i=1; i<=lg[n]; i++){
            int len = 1<<(i-1), sz = 1<<i;
            table[i].resize(n-sz+1);
            for(int j=0; j<=n-sz; j++){
                table[i][j] = cmp_(table[i-1][j], table[i-1][j+len]);
            }
        }
    }
    T query(int l, int r){
        // 0-base [l, r]
        int wh = lg[r-l], len=1<<wh;
        return cmp_(table[wh][l], table[wh][r-len]);
    }
};

```

2.11 FenwickTree

```

#include <vector>
using std::vector;

template<typename T>
class BIT{
#define ALL(x) begin(x), end(x)
private:
    vector<T> arr;
    int n;
    inline int lowbit(int x){return x & (-x);}
    T query(int x){
        T ret = 0;
        while(x > 0){
            ret += arr[x];
            x -= lowbit(x);
        }
        return ret;
    }
public:
    void init(int n){
        n = n;
        arr.resize(n);
        fill(ALL(arr), 0);
    }
    void modify(int pos, T v){
        while(pos < n){
            arr[pos] += v;
            pos += lowbit(pos);
        }
    }
    T query(int l, int r){
        // 1-base [l, r]
        return query(r) - query(l);
    }
#undef ALL
};

template<typename T>
class BIT{
#define ALL(x) begin(x), end(x)
private:
    vector<T> arr;
    int n;
    inline int lowbit(int x){return x & (-x);}
    void add(int s, int v){
        while(s){

```

```

        arr[s] += v;
        s -= lowbit(s);
    }
}
public:
    void init(int n_) {
        n = n_;
        arr.resize(n);
        fill(ALL(arr), 0);
    }
    void add(int l, int r, T v) {
        // 1-base [l, r]
        add(l, -v);
        add(r, v);
    }
    T query(int x) {
        T r = 0;
        while(x < size) {
            r += arr[x];
            x += lowbit(x);
        }
        return r;
    }
}
#undef ALL
};

```

3 Graph

3.1 BCC Edge

```

class BCC {
private:
    int low[N], dfn[N], cnt;
    bool bcc[N];
    vector<PII> G[N];
    void dfs(int w, int f) {
        dfn[w] = cnt++;
        low[w] = dfn[w];
        for(auto i: G[w]) {
            int u = i.FF, t = i.SS;
            if(u == f) continue;
            if(dfn[u] != 0) {
                low[w] = min(low[w], dfn[u]);
            } else {
                dfs(u, w);
                low[w] = min(low[w], low[u]);
                if(low[u] > dfn[w]) bcc[t] = true;
            }
        }
    }
public:
    void init(int n, int m) {
        for(int i = 0; i < n; i++) G[i].clear();
        fill(bcc, bcc + m, false);
        cnt = 0;
    }
    void add_edge(int u, int v) {
        G[u].PB({v, cnt});
        G[v].PB({u, cnt});
        cnt++;
    }
    void solve() { cnt = 1; dfs(0, 0); }
    // the id will be same as insert order, 0-base
    bool is_bcc(int x) { return bcc[x]; }
} bcc;

```

3.2 BCC Vertex

```

class BCC {
private:
    int n, m, cnt, bcnt, curoot;
    vector<vector<PII>> G;
    vector<int> low, dfn, ids, sz;
    vector<bool> ap;
    stack<int> stk;
    void dfs(int w, int f) {
        dfn[w] = cnt++;
        low[w] = dfn[w];
        int son = 0;
        for(auto i: G[w]) {

```

```

            int u = i.FF, t = i.SS;
            if(u == f) continue;
            if(dfn[u] == -1) {
                stk.push(t);
                dfs(u, w);
                if(low[u] >= dfn[w]) {
                    if(u != curoot) ap[u] = true;
                    while(stk.top() != t) {
                        assert(!stk.empty());
                        ids[stk.top()] = bcnt;
                        sz[bcnt]++;
                        stk.pop();
                    }
                    ids[stk.top()] = bcnt;
                    sz[bcnt]++;
                    stk.pop();
                    bcnt++;
                }
                low[w] = min(low[w], low[u]);
            } else {
                if(dfn[u] < dfn[w]) stk.push(t);
                low[w] = min(low[w], dfn[u]);
            }
        }
        if (w == curoot && son > 1) ap[w] = true;
    }
public:
    void init(int n_, int m_) {
        n = n_, m = m_, cnt = 0;
        G.resize(n); fill(ALL(G), vector<PII>());
        low.resize(n);
        dfn.resize(n); fill(ALL(dfn), -1);
        ids.resize(m); sz.resize(m);
        ap.resize(n); fill(ALL(ap), false);
    }
    void add_edge(int u, int v) {
        assert(0 <= u && u < n);
        assert(0 <= v && v < n);
        G[u].PB({v, cnt});
        G[v].PB({u, cnt});
        cnt++;
    }
    void solve() {
        assert(cnt == m);
        cnt = 1, bcnt = 0;
        for(int i = 0; i < n; i++) {
            if(dfn[i] != -1) continue;
            while(!stk.empty()) stk.pop();
            curoot = i;
            dfs(i, i);
        }
    }
    int count() { return bcnt; }
    // get bcc_id of edges, same as inserting order (0-base)
    int get_id(int t) { return ids[t]; }
    int get_size(int x) { return sz[x]; }
    bool isAP(int x) { return ap[x]; }
} bcc;

```

3.3 Strongly Connected Components

```

class SCC {
private:
    int n, num_;
    vector<int> G[N], rG[N], ord, num;
    bool vis[N];
    void dfs(int u) {
        if(vis[u]) return;
        vis[u] = 1;
        for(auto v: G[u]) dfs(v);
        ord.PB(u);
    }
    void rdfs(int u) {
        if(vis[u]) return;
        num[u] = num_;
        vis[u] = 1;
        for(auto v: rG[u]) rdfs(v);
    }
public:
    inline void init(int n_) {
        n = n_, num_ = 0;
        num.resize(n);
        for(int i = 0; i < n; i++) G[i].clear();

```



```

    for(int i=0;i<n;i++) rG[i].clear();
}
inline void add_edge(int st, int ed){
    G[st].PB(ed);
    rG[ed].PB(st);
}
void solve(){
    memset(vis, 0, sizeof(vis));
    for(int i=0;i<n;i++){
        if(!vis[i]) dfs(i);
    }
    reverse(ALL(ord));
    memset(vis, 0, sizeof(vis));
    for(auto i: ord){
        if(!vis[i]){
            rdfs(i);
            num_++;
        }
    }
    inline int get_id(int x){return num[x];}
    inline int count(){return num_;}
} scc;

```

3.4 Bipartite Matching

```

#include <bits/stdc++.h>
using namespace std;
#define N 500

class BipartiteMatching{
private:
    vector<int> X[N], Y[N];
    int fX[N], fY[N], n;
    bitset<N> walked;
    bool dfs(int x){
        for(auto i:X[x]){
            if(walked[i]) continue;
            walked[i]=1;
            if(fY[i]==-1||dfs(fY[i])){
                fY[i]=x;fX[x]=i;
                return 1;
            }
        }
        return 0;
    }
public:
    void init(int _n){
        n=_n;
        for(int i=0;i<n;i++){
            X[i].clear();
            Y[i].clear();
            fX[i]=fY[i]=-1;
        }
        walked.reset();
    }
    void AddEdge(int x, int y){
        X[x].push_back(y);
        Y[y].push_back(x);
    }
    int solve(){
        int cnt = 0;
        for(int i=0;i<n;i++){
            walked.reset();
            if(dfs(i)) cnt++;
        }
        // return how many pair matched
        return cnt;
    }
};

```

3.5 MinimumCostMaximumFlow

```

class MiniCostMaxiFlow{
    typedef int CapT;
    typedef lld WeiT;
    typedef pair<CapT, WeiT> PCW;
    const CapT INF_CAP = 1<<30;
    const WeiT INF_WEI = 1LL<<60;
    const int MAXV = N;
private:
    struct Edge{

```

```

        int to, back;
        WeiT wei;
        CapT cap;
        Edge(){
            Edge(int a, int b, WeiT c, CapT d): to(a), back(b), wei(c), cap(d) {}
        };
        int ori, edd, V;
        vector<Edge> G[MAXV];
        int fa[MAXV], wh[MAXV];
        bool inq[MAXV];
        WeiT dis[MAXV];
        PCW SPFA(){
            for(int i=0;i<V;i++) inq[i]=0;
            for(int i=0;i<V;i++) dis[i]=INF_WEI;
            queue<int> qq;
            qq.push(ori);
            dis[ori]=0;
            while(!qq.empty()){
                int u = qq.front(); qq.pop();
                inq[u]=0;
                for(int i=0;i<SZ(G[u]);i++){
                    Edge e = G[u][i];
                    int v = e.to;
                    WeiT d = e.wei;
                    if(e.cap > 0 and dis[v] > dis[u]+d){
                        dis[v]=dis[u]+d;
                        fa[v]=u;
                        wh[v] = i;
                        if(inq[v]) continue;
                        qq.push(v);
                        inq[v]=1;
                    }
                }
            }
            if(dis[edd]==INF_WEI) return {-1, -1};
            CapT mw=INF_CAP;
            for(int i=edd;i!=ori;i=fa[i]){
                mw = min(mw, G[fa[i]][wh[i]].cap);
            }
            for(int i=edd;i!=ori;i=fa[i]){
                auto &eg = G[fa[i]][wh[i]];
                eg.cap -= mw;
                G[eg.to][eg.back].cap += mw;
            }
            return {mw, dis[edd]};
        }
public:
    void init(int a, int b, int n=MAXV){
        V=n;
        ori = a;
        edd = b;
        for(int i=0;i<n;i++) G[i].clear();
    }
    void addEdge(int st, int ed, WeiT w, CapT c){
        G[st].PB(Edge(ed, SZ(G[ed]), w, c));
        G[ed].PB(Edge(st, SZ(G[st])-1, -w, 0));
    }
    PCW solve(){
        CapT cc=0; WeiT ww=0;
        while(true){
            PCW ret = SPFA();
            if(ret.FF==-1) break;
            cc += ret.FF;
            ww += ret.SS;
        }
        return {cc, ww};
    }
} mcmf;

```

3.6 MaximumFlow

```

class Dinic{
private:
    using CapT = int64_t;
    struct Edge{
        int to, rev;
        CapT cap;
    };
    int n, st, ed;
    vector<vector<Edge>> G;
    vector<int> lv;
    bool BFS(){
        fill(lv.begin(), lv.end(), -1);

```



```

queue<int> bfs;
bfs.push(st);
lv[st] = 0;
while(!bfs.empty()){
    int u = bfs.front(); bfs.pop();
    for(auto e: G[u]){
        if(e.cap <= 0 or lv[e.to] != -1) continue;
        lv[e.to] = lv[u] + 1;
        bfs.push(e.to);
    }
}
return (lv[ed] != -1);
}
CapT DFS(int u, CapT f){
    if(u == ed) return f;
    CapT ret = 0;
    for(auto& e: G[u]){
        if(e.cap <= 0 or lv[e.to] != lv[u]+1) continue;
        CapT nf = DFS(e.to, min(f, e.cap));
        ret += nf; e.cap -= nf; f -= nf;
        G[e.to][e.rev].cap += nf;
        if(f == 0) return ret;
    }
    if(ret == 0) lv[u] = -1;
    return ret;
}
public:
    void init(int n_, int st_, int ed_){
        n = n_; st = st_; ed = ed_;
        G.resize(n); lv.resize(n);
        fill(G.begin(), G.end(), vector<Edge>());
    }
    void add_edge(int u, int v, CapT c){
        G[u].push_back({v, (int)(G[v].size()), c});
        G[v].push_back({u, (int)(G[u].size())-1, 0});
    }
    CapT max_flow(){
        CapT ret = 0;
        while(BFS()){
            CapT f = DFS(st, numeric_limits<CapT>::max());
            ret += f;
            if(f == 0) break;
        }
        return ret;
    }
} flow;

```

4 Math

4.1 Prime Table

```

// 1000000000 < primes < 2147483647
1002939109, 1020288887, 1028798297, 1038684299,
1041211027, 1051762951, 1058585963, 1063020809,
1094763083, 1106384353, 1120154459, 1140593173,
1147930723, 1172520109, 1183835981, 1187659051,
1241251303, 1247184097, 1255940849, 1272759031,
1287027493, 1288511629, 1294632499, 1312650799,
1314753281, 1320080669, 1321970357, 1333133947,
1337684419, 1353508067, 1358715989, 1364961029,
1366046831, 1376536367, 1381705499, 1410637769,
1411311571, 1422795043, 1437499801, 1495803851,
1511764363, 1526710979, 1538018089, 1542373769,
1545326953, 1549429633, 1556212739, 1575971759,
1586465261, 1608336427, 1609783001, 1620728569,
1643267081, 1652401603, 1656717203, 1660920671,
1666858577, 1669260361, 1670240317, 1678791131,
1685583143, 1725964619, 1734856421, 1743134179,
1761537223, 1774260193, 1778872889, 1781930609,
1803000149, 1814256623, 1834876331, 1839154463,
1840044389, 1843241713, 1856039431, 1868564531,
1868732623, 1884198443, 1884616807, 1885059541,
1909942399, 1914471137, 1923951707, 1925453197,
1937719153, 1954649041, 1958915237, 1970709803,
1979612177, 1980446837, 1989761941, 2007826547,
2008033571, 2011186739, 2039465081, 2039728567,
2093735719, 2116097521, 2123852629, 2140170259

// 2147483647 < primes < 4000000000
3148478261, 3153064147, 3176351071, 3187523093,
3196772239, 3201312913, 3203063977, 3204840059,

```

```

3210224309, 3213032591, 3217689851, 3218469083,
3219857533, 3231880427, 3235951699, 3273767923,
3276188869, 3277183181, 3282463507, 3285553889,
3319309027, 3327005333, 3327574903, 3341387953,
3373293941, 3380077549, 3380892997, 3381118801,
3384716479, 3386991323

```

4.2 ax+by=gcd

```

// By Adrien1018 (not knowing how to use.
// ax+ny = 1, ax+ny == ax == 1 (mod n)
tuple<int, int, int> extended_gcd(int a, int b) {
    if (!b) return make_tuple(a, 1, 0);
    int d, x, y;
    tie(d, x, y) = extended_gcd(b, a % b);
    return make_tuple(d, y, x - (a / b) * y);
}
// ax+by = gcd (by Eddy1021
PII gcd(int a, int b){
    if(b == 0) return {1, 0};
    PII q = gcd(b, a % b);
    return {q.second, q.first - q.second * (a / b)};
}

```

4.3 Pollard Rho

```

// coded by hanhanW
// does not work when n is prime
long long modit(long long x, long long mod) {
    if(x >= mod) x -= mod;
    //if(x < 0) x += mod;
    return x;
}
long long mult(long long x, long long y, long long mod) {
    long long s = 0, m = x % mod;
    while(y) {
        if(y & 1) s = modit(s + m, mod);
        y >>= 1;
        m = modit(m + m, mod);
    }
    return s;
}
long long f(long long x, long long mod) {
    return modit(mult(x, x, mod) + 1, mod);
}
long long pollard_rho(long long n) {
    if(!(n & 1)) return 2;
    while (true) {
        long long y = 2, x = rand() % (n - 1) + 1, res = 1;
        for (int sz = 2; res == 1; sz *= 2) {
            for (int i = 0; i < sz && res == 1; i++) {
                x = f(x, n);
                res = __gcd(abs(x - y), n);
            }
            y = x;
        }
        if (res != 0 && res != n) return res;
    }
}

```

4.4 Linear Sieve

```

const int N = 20000000;
bool sieve[N];

void linear_sieve(){
    vector<int> prime;
    for (int i = 2; i < N; i++){
        if (!sieve[i]) prime.push_back(i);
        for (int j = 0; i * prime[j] < N; j++) {
            sieve[i * prime[j]] = true;
            if (i % prime[j] == 0) break;
        }
    }
}

```

4.5 NloglogN Sieve

```
bool notprime[N];
vector<int> primes;

void Sieve(int n){
    // reverse true false for quicker
    for(int i=2;i<=n;i++){
        if(!notprime[i]){
            primes.push_back(i);
            for(int j=i*i;j<=n;j+=i) notprime[j]=true;
        }
    }
}
```

4.6 Range Sieve

```
#include <algorithm>
typedef long long lld;
const int MAX_SQRT_B = 50000;
const int MAX_L = 200000 + 5;

bool is_prime_small[MAX_SQRT_B];
bool is_prime[MAX_L];
void sieve(lld, lld);

void sieve(lld l, lld r){
    // [1, r)
    for(lld i=2;i*i<r;i++) is_prime_small[i] = true;
    for(lld i=l;i<r;i++) is_prime[i-1] = true;
    if(l==1) is_prime[0] = false;
    for(lld i=2;i*i<r;i++){
        if(!is_prime_small[i]) continue;
        for(lld j=i*i;j<r;j+=i) is_prime_small[j]=false;
        for(lld j=std::max(2LL, (l+i-1)/i)*i;j<r;j+=i)
            is_prime[j-1]=false;
    }
}
```

4.7 Miller Rabin

```
lld modu(lld a, lld m){
    while(a >= m) a -= m;
    return a;
}

lld mul(lld a, lld b, lld m){
    if(a < b) swap(a, b);
    lld ret = 0;
    while(b){
        if(b & 1) ret = modu(ret+a, m);
        a = modu(a+a, m);
        b >>= 1;
    }
    return ret;
}

lld qPow(lld a, lld k, lld m){
    lld ret = 1;
    a %= m;
    while(k){
        if(k & 1) ret = mul(ret, a, m);
        a = mul(a, a, m);
        k >>= 1;
    }
    return modu(ret, m);
}

bool witness(lld a, lld s, int t, lld n){
    lld b = qPow(a, s, n);
    if(b == 0) return false;
    while(t--){
        lld bb = mul(b, b, n);
        if(bb == 1 and b != 1 and b != n-1) return true;
        b = bb;
    }
    return b != 1;
}

bool miller_rabin(lld n){
    if(n < 2) return false;
    if(!(n & 1)) return (n==2);
    lld x = n-1; int t = 0;
    while(!(x&1)) x >>= 1, t++;
}
```

```
lld sprp[] =
    {2,325,9375,28178,450775,9780504,1795265022};
for(int i=0;i<7;i++){
    if(witness(srp[i]%n, x, t, n)) return false;
}
return true;
}
```

4.8 Inverse Element

```
// x's inverse mod k
// if k is prime
long long GetInv(long long x, long long k){
    return qPow(x, k-2);
}

// x's inverse mod k
// if k is not prime
long long GetInv(long long x, long long k){
    return qPow(x, Euler(k)-1);
}

// or extended_gcd(x, k).second
// if you need [1, x] (most use: [1, k-1])
void solve(int x, long long k){
    inv[1] = 1;
    for(int i=2;i<x;i++){
        inv[i] = ((long long)(k - k/i) * inv[k % i]) % k;
    }
}
```

4.9 Euler Phi Function

```
inline int64_t Euler(int x){
    int64_t r=1;
    for(int i=2;i*i<=x;i++){
        if(x%i==0){
            x/=i;
            r*=(i-1);
            while(x%i==0){
                x/=i;
                r*=i;
            }
        }
    }
    if(x>1) r*=x-1;
    return r;
}

vector<int> primes;
bool notprime[N];
int64_t phi[N];
inline void euler_sieve(int n){
    for(int i=2;i<n;i++){
        if(!notprime[i]){
            primes.push_back(i);
            phi[i] = i-1;
        }
        for(auto j: primes){
            if(i*j >= n) break;
            notprime[i*j] = true;
            phi[i*j] = phi[i] * phi[j];
            if(i % j == 0){
                phi[i*j] = phi[i] * j;
                break;
            }
        }
    }
}
```

4.10 Gauss Elimination

```
#include <cmath>
#include <algorithm>
typedef long double llf;
const int N = 300;
const llf EPS = 1e-8;

// make m[i][i] = x, m[i][j] = 0
// v is for solving equation
bool Gauss(llf m[N][N], llf v[N], int n){
}
```

```

// right-top
for(int i=0;i<n;i++){
    int pos = -1;
    for(int j=i;j<n;j++){
        if(fabsl(m[j][i]) > EPS){
            swap(m[i], m[j]);
            swap(v[i], v[j]);
            pos = j;
            break;
        }
    }
    if(pos == -1) return false;
    for(int j=i+1;j<n;j++){
        llf xi = m[j][i]/m[i][i];
        for(int k=0;k<n;k++){
            m[j][k] -= m[i][k]*xi;
        }
        v[j] -= v[i]*xi;
    }
}
// left-bottom
for(int i=n-1;i>=0;i--){
    int pos = -1;
    for(int j=i;j>=0;j--){
        if(fabsl(m[j][i]) > EPS){
            swap(m[i], m[j]);
            swap(v[i], v[j]);
            pos = j;
            break;
        }
    }
    if(pos == -1) return false;
    for(int j=i-1;j>=0;j--){
        llf xi = m[j][i]/m[i][i];
        for(int k=n-1;k>=0;k--){
            m[j][k] -= m[i][k]*xi;
        }
        v[j] -= v[i]*xi;
    }
}
return true;
}

```

4.11 Fast Fourier Transform

```

/*
polynomial multiply:
FFT(a, N, true);
FFT(b, N, true);
for(int i=0;i<MAXN;i++) c[i] = a[i]*b[i];
FFT(c, N, false);
yeah~ go result in c
(N must be 2^k and >= len(a)+len(b))
*/
typedef long double llf;
typedef complex<llf> cplx;
const int MAXN = 262144;
const llf PI = acos((llf)-1);

cplx A[MAXN], B[MAXN], C[MAXN], omega[MAXN+1];

void init_omega(){
    const cplx I = {0, 1};
    for(int i=0;i<=MAXN;i++) omega[i] = exp(i*2*PI/MAXN*I);
}

void FFT(cplx arr[], int n, bool ori){
    // n must be 2^k
    int theta = MAXN / n;
    for(int len=n;len>=2;len>>=1){
        int tot = len>>1;
        for(int i=0;i<tot;i++){
            cplx omg = omega[ori*i*theta%MAXN:MAXN-(i*theta%MAXN)];
            for(int j=i;j<n;j+=len){
                int k = j+tot;
                cplx x = arr[j] - arr[k];
                arr[j] += arr[k];
                arr[k] = omg * x;
            }
        }
        theta = (theta * 2) % MAXN;
    }
}

```

```

int i = 0;
for(int j=1;j<n-1;j++){
    for(int k=n>>1;k>(i^=k);k>>=1);
    if(j < i) swap(arr[j], arr[i]);
}
if(ori) return;
for(int i=0;i<n;i++) arr[i] /= n;
}

```

4.12 Chinese Remainder

```

// ax+ny = 1, ax+ny == ax == 1 (mod n)
pair<lld, lld> gcd(lld a, lld b){
    if(b == 0) return {1, 0};
    pair<lld, lld> q = gcd(b, a % b);
    return {q.second, q.first - q.second * (a / b)};
}

lld crt(lld ans[], lld pri[], int n){
    lld M = 1;
    for(int i=0;i<n;i++) M *= pri[i];
    lld ret = 0;
    for(int i=0;i<n;i++){
        lld inv = (gcd(M/pri[i], pri[i]).first + pri[i])%pri[i];
        ret += (ans[i]*(M/pri[i])%M * inv)%M;
        ret %= M;
    }
    return ret;
}

```

4.13 NTT

```

typedef long long LL;
// Remember coefficient are mod P
/* p=a*2^n+1
n    2^n    p    a    root
5    32    97    3    5
6    64    193    3    5
7    128    257    2    3
8    256    257    1    3
9    512    7681    15    17
10   1024    12289    12    11
11   2048    12289    6    11
12   4096    12289    3    11
13   8192    40961    5    3
14   16384    65537    4    3
15   32768    65537    2    3
16   65536    65537    1    3
17   131072    786433    6    10
18   262144    786433    3    10 (605028353,
    2308, 3)
19   524288    5767169    11    3
20   1048576    7340033    7    3
21   2097152    23068673    11    3
22   4194304    104857601    25    3
23   8388608    167772161    20    3
24   16777216    167772161    10    3
25   33554432    167772161    5    3 (1107296257, 33,
    10)
26   67108864    469762049    7    3
27   134217728    2013265921    15    31 */
// (must be 2^k)
// To implement poly. multiply:
// NTT<P, root, MAXN> ntt;
// ntt(n, a); // or ntt.tran(n, a);
// ntt(n, b);
// for(int i=0; i<n; i++)
//   c[i] = a[i] * b[i];
// ntt(n, c, 1);
//
// then you have the result in c :: [LL]

template<LL P, LL root, int MAXN>
struct NTT{
    static LL bigmod(LL a, LL b) {
        LL res = 1;
        for (LL bs = a; b >= 1; bs = (bs * bs) % P) {
            if(b&1) res=(res*bs)%P;
        }
        return res;
    }
}

```

```

static LL inv(LL a, LL b) {
    if(a==1) return 1;
    return ((LL) (a-inv(b%a,a))*b+1)/a%b;
}
LL omega[MAXN+1];
NTT() {
    omega[0] = 1;
    LL r = bigmod(root, (P-1)/MAXN);
    for (int i=1; i<=MAXN; i++)
        omega[i] = (omega[i-1]*r)%P;
}
// n must be 2^k
void tran(int n, LL a[], bool inv_ntt=false) {
    int basic = MAXN / n;
    int theta = basic;
    for (int m = n; m >= 2; m >>= 1) {
        int mh = m >> 1;
        for (int i = 0; i < mh; i++) {
            LL w = omega[i*theta%MAXN];
            for (int j = i; j < n; j += m) {
                int k = j + mh;
                LL x = a[j] - a[k];
                if (x < 0) x += P;
                a[j] += a[k];
                if (a[j] > P) a[j] -= P;
                a[k] = (w * x) % P;
            }
        }
        theta = (theta * 2) % MAXN;
    }
    int i = 0;
    for (int j = 1; j < n - 1; j++) {
        for (int k = n >> 1; k > (i ^ k); k >>= 1);
        if (j < i) swap(a[i], a[j]);
    }
    if (inv_ntt) {
        LL ni = inv(n,P);
        reverse(a+1, a+n);
        for (i = 0; i < n; i++)
            a[i] = (a[i] * ni) % P;
    }
}
void operator()(int n, LL a[], bool inv_ntt=false) {
    tran(n, a, inv_ntt);
}
};

const LL P=2013265921,root=31;
const int MAXN=4194304;
NTT<P, root, MAXN> ntt;

```

5 Geometry

5.1 Point Class

```

namespace Geometry{
    const long double EPS = 1e-8;
    const long double PI = acos((long double)-1);
    template<typename T>
    struct Point{
        typedef long double llf;
        T x, y;
        Point(): x(0), y(0){}
        Point(T __, T __): x(__), y(__){}
        template<typename T2>
        Point(const Point<T2>& a): x(a.x), y(a.y){}
        inline llf theta() const {
            return atan2((llf)y, (llf)x);
        }
        inline llf dis() const {
            return hypot((llf)x, (llf)y);
        }
        inline llf dis(const Point& o) const {
            return hypot((llf)(x-o.x), (llf)(y-o.y));
        }
        Point operator-(const Point& o) const {
            return Point(x-o.x, y-o.y);
        }
        Point operator+=(const Point& o){
            x+=o.x, y+=o.y;
            return *this;
        }
    }
}

```

```

Point operator+(const Point& o) const {
    return Point(x+o.x, y+o.y);
}
Point operator+=(const Point& o){
    x+=o.x, y+=o.y;
    return *this;
}
Point operator*(const T& k) const {
    return Point(x*k, y*k);
}
Point operator*=(const T& k){
    x*=k, y*=k;
    return *this;
}
Point operator/(const T& k) const {
    return Point(x/k, y/k);
}
Point operator/=(const T& k){
    x/=k, y/=k;
    return *this;
}
Point operator-() const {
    return Point(-x, -y);
}
bool equal(const Point& o, true_type) const {
    return fabs(x-o.x) < EPS and fabs(y-o.y) < EPS;
}
bool equal(const Point& o, false_type) const {
    return x==o.x and y==o.y;
}
bool operator==(const Point& o) const {
    return equal(o, is_floating_point<T>());
}
bool operator!=(const Point& o) const {
    return !(*this == o);
}
bool operator<(const Point& o) const {
    return theta() < o.theta();
    // sort like what pairs did
    // return fabs(x-o.x)<EPS?y<o.y:x<o.x;
}
friend inline T cross(const Point& a, const Point&
    b){
    return a.x*b.y - b.x*a.y;
}
friend inline T dot(const Point& a, const Point &b)
    {
    return a.x*b.x + a.y*b.y;
}
friend ostream& operator<<(ostream& ss, const Point
    & o){
    ss<<"("<<o.x<<" , "<<o.y<<")";
    return ss;
}
};
template<typename T>
struct Circle{
    Point<T> o;
    T r;
    vector<Point<llf>> operator&(const Circle& aa)
        const {
        llf d=o.dis(aa.o);
        if(d > r+aa.r+EPS or d < fabs(r-aa.r)-EPS) return
            {};
        llf dt = (r*r - aa.r*aa.r)/d, d1 = (d+dt)/2;
        Point<llf> dir = (aa.o-o); dir /= d;
        Point<llf> pcrs = dir*d1 + o;
        dt=sqrt(max(0.0L, r*r - d1*d1)), dir=dir.rot90();
        return {pcrs + dir*dt, pcrs - dir*dt};
    }
};
const Point<long double> INF P(-1e20, 1e20);
const Point<long double> NOT_EXIST(1e20, 1e-20);
template<typename T>
struct Line{
    // ax+by+c = 0
    T a, b, c;
    Line(): a(0), b(1), c(0){}
    Line(T __, T __, T __): a(__), b(__), c(__){
        assert(fabs(a)>EPS or fabs(b)>EPS);
    }
    template<typename T2>
    Line(const Line<T2>& x): a(x.a), b(x.b), c(x.c){}
    typedef Point<long double> Pt;
    template<class = typename is_floating_point<T>::
        type>

```

```

bool operator==(const Line& o) const {
    return fabs(a-o.a) < EPS and fabs(b-o.b) < EPS
        and fabs(c-o.c) < EPS;
}
bool operator==(const Line& o) const {
    return a==o.a and b==o.b and c==o.c;
}
bool operator!=(const Line& o) const {
    return !(*this == o);
}
template<class = typename is_floating_point<T>::
    type>
friend inline bool on_line(const Point<T>& p, const
    Line& l){
    return fabs(l.a*p.x + l.b*p.y + l.c) < EPS;
}
friend inline bool on_line(const Point<T>& p, const
    Line& l){
    return l.a*p.x + l.b*p.y + l.c == 0;
}
template<class = typename is_floating_point<T>::
    type>
friend inline bool is_parallel(const Line& x, const
    Line& y){
    return fabs(x.a*y.b - x.b*y.a) < EPS;
}
friend inline bool is_parallel(const Line& x, const
    Line& y){
    return x.a*y.b == x.b*y.a;
}
friend inline Pt get_inter(const Line& x, const
    Line& y){
    typedef long double llf;
    if(x==y) return INF_P;
    if(is_parallel(x, y)) return NOT_EXIST;
    llf delta = x.a*y.b - x.b*y.a;
    llf delta_x = x.b*y.c - x.c*y.b;
    llf delta_y = x.c*y.a - x.a*y.c;
    return Pt(delta_x / delta, delta_y / delta);
}
friend ostream& operator<<(ostream& ss, const Line&
    o){
    ss<<o.a<<"x+"<<o.b<<"y+"<<o.c<<"=0";
    return ss;
}
};
template<typename T>
inline Line<T> get_line(const Point<T>& a, const
    Point<T>& b){
    return Line<T>(a.y-b.y, b.x-a.x, (b.y-a.y)*a.x-(b.x
        -a.x)*a.y);
}
template<typename T>
struct Segment{
    // p1.x < p2.x
    Line<T> base;
    Point<T> p1, p2;
    Segment(): base(Line<T>()), p1(Point<T>()), p2(
        Point<T>()){
        assert(on_line(p1, base) and on_line(p2, base));
    }
    Segment(Line<T> _, Point<T> __, Point<T> ___): base
        (_, p1(__), p2(___)){
        assert(on_line(p1, base) and on_line(p2, base));
    }
    template<typename T2>
    Segment(const Segment<T2>& _): base(_.base), p1(
        _.p1), p2(_.p2) {}
    typedef Point<long double> Pt;
    friend bool on_segment(const Point<T>& p, const
        Segment& l){
        if(on_line(p, l.base))
            return (l.p1.x-p.x)*(p.x-l.p2.x)>=0 and (l.p1.y
                -p.y)*(p.y-l.p2.y)>=0;
        return false;
    }
    friend bool have_inter(const Segment& a, const
        Segment& b){
        if(is_parallel(a.base, b.base)){
            return on_segment(a.p1, b) or on_segment(a.p2,
                b) or on_segment(b.p1, a) or on_segment(b.
                p2, a);
        }
        Pt inter = get_inter(a.base, b.base);
        return on_segment(inter, a) and on_segment(inter,
            b);
    }
};

```

```

}
friend inline Pt get_inter(const Segment& a, const
    Segment& b){
    if(!have_inter(a, b)){
        return NOT_EXIST;
    }else if(is_parallel(a.base, b.base)){
        if(a.p1 == b.p1){
            if(on_segment(a.p2, b) or on_segment(b.p2, a)
                ) return INF_P;
            else return a.p1;
        }else if(a.p1 == b.p2){
            if(on_segment(a.p1, b) or on_segment(b.p1, a)
                ) return INF_P;
            else return a.p1;
        }else if(a.p2 == b.p1){
            if(on_segment(a.p1, b) or on_segment(b.p2, a)
                ) return INF_P;
            else return a.p2;
        }else if(a.p2 == b.p2){
            if(on_segment(a.p1, b) or on_segment(b.p1, a)
                ) return INF_P;
            else return a.p2;
        }
    }
    return INF_P;
}
return get_inter(a.base, b.base);
}
friend ostream& operator<<(ostream& ss, const
    Segment& o){
    ss<<o.base<<" "<<o.p1<<" ~ "<<o.p2;
    return ss;
}
};
template<typename T>
inline Segment<T> get_segment(const Point<T>& a,
    const Point<T>& b){
    return Segment<T>(get_line(a, b), a, b);
}
};

```

5.2 2D Convex Hull

```

template<typename T>
class ConvexHull_2D{
private:
    typedef Point<T> PT;
    vector<PT> dots;
    struct myhash{
        uint64_t operator()(const PT& a) const {
            uint64_t xx=0, yy=0;
            memcpy(&xx, &a.x, sizeof(a.x));
            memcpy(&yy, &a.y, sizeof(a.y));
            uint64_t ret = xx*17+yy*31;
            ret = (ret ^ (ret >> 16))*0x9E3779B1;
            ret = (ret ^ (ret >> 13))*0xC2B2AE35;
            ret = ret ^ xx;
            return (ret ^ (ret << 3)) * yy;
        }
    };
    unordered_set<PT, myhash> in_hull;
public:
    inline void init(){in_hull.clear();dots.clear();}
    void insert(const PT& x){dots.PB(x);}
    void solve(){
        sort(ALL(dots), [](const PT& a, const PT& b){
            return tie(a.x, a.y) < tie(b.x, b.y);
        });
        vector<PT> stk(SZ(dots)<<1);
        int top = 0;
        for(auto p: dots){
            while(top >= 2 and cross(p-stk[top-2], stk[top
                -1]-stk[top-2]) <= 0)
                top --;
            stk[top++] = p;
        }
        for(int i=SZ(dots)-2, t = top+1; i>=0; i--){
            while(top >= t and cross(dots[i]-stk[top-2],
                stk[top-1]-stk[top-2]) <= 0)
                top --;
            stk[top++] = dots[i];
        }
        stk.resize(top-1);
        swap(stk, dots);
        for(auto i: stk) in_hull.insert(i);
    }
};

```

```

    }
    vector<PT> get(){return dots;}
    inline bool in_it(const PT& x){
        return in_hull.find(x)!=in_hull.end();
    }
};

```

5.3 SimulateAnnealing

```

#include <random>
#include <functional>
#include <utility>
#include <algorithm>
using namespace std;

double getY(double);

int main(){
    int rr, ll;
    default_random_engine rEng(time(NULL));
    uniform_real_distribution<double> Range(-1,1);
    uniform_real_distribution<double> expR(0,1);
    auto Random=bind(Range,rEng);
    auto expRand=bind(expR,rEng);
    int step=0;
    double pace=rr-ll, mini=0.95; // need to search for
    it
    double x=max(min(Random()*pace+ll, rr), ll), y=getY(x);
    while(pace>=1e-7){
        double newX = max(min(x + Random()*pace, rr), ll);
        double newY = getY(newX);
        if(newY < y || expRand() < exp(-step))
            x=newX, y=newY;
        step++;
        pace*=mini;
    }

    double getY(double x){
        // get y using x
        return x;
    }
}

```

6 Stringology

6.1 Hash

```

#include <string>
typedef long long lld;
const int N = 1000000;
class Hash{
private:
    const lld p = 127, q = 1208220623;
    int sz;
    lld prefix[N], power[N];
public:
    void init(const std::string &x){
        sz = x.size();
        prefix[0]=0;
        for(int i=1;i<=sz;i++) prefix[i]=(prefix[i-1]*p+q+x[i-1])%q;
        power[0]=1;
        for(int i=1;i<=sz;i++) power[i]=(power[i-1]*p)%q;
    }
    lld query(int l, int r){
        // 1-base (l, r)
        return (prefix[r] - (prefix[l]*power[r-l])%
            q + q)%q;
    }
};

```

6.2 Suffix Array

```

//help by http://www.geeksforgeeks.org/suffix-array-set
-2-a-nlognlogn-algorithm/
#include <bits/stdc++.h>

```

```

using namespace std;
#define PB push_back

struct sfx{
    int index;
    int r,nr;
};

char str[N + 10];
int len;

vector<sfx> srs[N + 10];
int mapping[N + 10];
sfx sa[N + 10];

bool cmp(sfx a,sfx b){
    if(a.r==b.r){
        return a.nr<b.nr;
    }else{
        return a.r<b.r;
    }
}

void SA();
void radixSort();

int main(){
    gets(str);
    len = strlen(str);
    SA();
    for(int i=0;i<len;i++){
        printf("%d\n",sa[i].index);
    }
    return 0;
}

void SA(){
    for(int i=0;i<len;i++){
        sa[i].index = i;
        sa[i].r=str[i];
        sa[i].nr=(i+1>=len)?0:str[i+1];
    }
    //sort(sa,sa+len,cmp);
    radixSort();
    for(int j=2;j<=len;j*=2){
        int cnt=1;
        int rr = sa[0].r;
        sa[0].r=cnt;
        mapping[sa[0].index]=0;
        for(int i=1;i<len;i++){
            if(sa[i].r == rr && sa[i].nr == sa[i-1].nr){
                rr=sa[i].r;
                sa[i].r=cnt;
            }else{
                rr=sa[i].r;
                sa[i].r=++cnt;
            }
            mapping[sa[i].index]=i;
        }
        for(int i=0;i<len;i++){
            int nn = sa[i].index+j;
            sa[i].nr = (nn>=len)?0:sa[mapping[nn]].r;
        }
        //sort(sa, sa+len, cmp);
        radixSort();
    }
}

void radixSort(){
    int m = 0;
    for(int i=0;i<len;i++){
        srs[sa[i].nr].PB(sa[i]);
        m=max(m,sa[i].nr);
    }
    int cnt=0;
    for(int i=0;i<=m;i++){
        if(srs[i].empty()) continue;
        for(auto j:srs[i]){
            sa[cnt++] = j;
        }
        srs[i].clear();
    }
    m = 0;
    for(int i=0;i<len;i++){
        srs[sa[i].r].PB(sa[i]);
        m=max(m,sa[i].r);
    }
}

```

```

    }
    cnt=0;
    for(int i=0;i<=m;i++){
        if(srs[i].empty()) continue;
        for(auto j:srs[i]){
            sa[cnt++] = j;
        }
        srs[i].clear();
    }
}

```

6.3 KMP

```

int F[N<<1];
void KMP(char s1[], char s2[], int n, int m){
    // make F[] for s1+'\0'+s2;
    char ss[N<<1];
    int len = n+m+1;
    for(int i=0;i<n;i++) ss[i] = s1[i];
    ss[n] = '\0';
    for(int i=0;i<m;i++) ss[i+1+n] = s2[i];
    F[0] = F[1] = 0;
    for(int i=1;i<len;i++){
        int j = F[i];
        while(j > 0 and ss[i]!=ss[j]) j = F[j];
        F[i+1] = (ss[i]==ss[j]?j+1:0);
    }
    // just find (F[len2+i] == len2), i from 1 to len+1
    // for matching
}

```