

# Contents

<b>1 Basic</b>	<b>1</b>	<b>8 Misc</b>	<b>22</b>
1.1 vimrc	1	8.1 Theorems	22
1.2 IncreaseStackSize	1	8.1.1 Kirchhoff's Theorem	22
1.3 Pragma optimization	1	8.1.2 Tutte's Matrix	22
1.4 Debugger	1	8.1.3 Cayley's Formula	22
1.5 Quick Random	2	8.1.4 Erdős-Gallai theorem	22
1.6 IO Optimization	2	8.1.5 Havel-Hakimi algorithm	23
<b>2 Data Structure</b>	<b>2</b>	8.1.6 Hall's marriage theorem	23
2.1 Bigint	2	8.1.7 Euler's planar graph formula	23
2.2 Dark Magic	3	8.1.8 Pick's theorem	23
2.3 SkewHeap	3	8.2 MaximumEmptyRect	23
2.4 Disjoint Set	3	8.3 DP-opt Condition	23
2.5 Link-Cut Tree	4	8.3.1 totally monotone (concave/convex)	23
2.6 LiChao Segment Tree	4	8.3.2 monge condition (concave/convex)	23
2.7 Treap	5	8.4 Convex 1D/1D DP	23
2.8 SparseTable	5	8.5 ConvexHull Optimization	23
2.9 Linear Basis	5	8.6 Josephus Problem	23
<b>3 Graph</b>	<b>5</b>	8.7 Cactus Matching	24
3.1 Euler Circuit	5	8.8 DLX	24
3.2 BCC Edge	6	8.9 Tree Knapsack	25
3.3 BCC Vertex	6		
3.4 2-SAT (SCC)	6		
3.5 Lowbit Decomposition	7		
3.6 MaxClique	7		
3.7 Virtual Tree	8		
3.8 Tree Hashing	8		
3.9 Minimum Mean Cycle	8		
3.10 Mo's Algorithm on Tree	8		
3.11 Minimum Steiner Tree	9		
<b>4 Matching &amp; Flow</b>	<b>9</b>		
4.1 Kuhn Munkres	9		
4.2 Bipartite Matching	10		
4.3 General Graph Matching	10		
4.4 Minimum Weight Matching (Clique version)	10		
4.5 Flow Models	11		
4.6 Dinic	11		
4.7 Minimum Cost Maximum Flow	11		
4.8 Global Min-Cut	12		
<b>5 Math</b>	<b>12</b>		
5.1 Prime Table	12		
5.2 $\lfloor \frac{n}{i} \rfloor$ Enumeration	12		
5.3 ax+by=gcd	12		
5.4 Pollard Rho	12		
5.5 Pi Count (Linear Sieve)	12		
5.6 Range Sieve	13		
5.7 Miller Rabin	13		
5.8 Inverse Element	13		
5.9 Euler Phi Function	13		
5.10 Gauss Elimination	13		
5.11 Fast Fourier Transform	13		
5.12 High Speed Linear Recurrence	14		
5.13 Chinese Remainder	14		
5.14 Berlekamp Massey	15		
5.15 NTT	15		
5.16 Polynomial Sqrt	15		
5.17 Polynomial Division	16		
5.18 FWT	16		
5.19 Discrete Log	16		
5.20 Quadratic residue	16		
5.21 De Bruijn	16		
5.22 Simplex Construction	17		
5.23 Simplex	17		
<b>6 Geometry</b>	<b>17</b>		
6.1 Point Class	17		
6.2 Circle Class	18		
6.3 Triangle Circumcentre	18		
6.4 2D Convex Hull	18		
6.5 2D Farthest Pair	18		
6.6 2D Closest Pair	18		
6.7 Simulate Annealing	19		
6.8 Half Plane Intersection	19		
6.9 Ternary Search on Integer	19		
6.10 Minimum Covering Circle	19		
6.11 KDTree (Nearest Point)	19		
<b>7 Stringology</b>	<b>20</b>		
7.1 Hash	20		
7.2 Suffix Array	20		
7.3 Aho-Corasick Algorithm	21		
7.4 Suffix Automaton	21		
7.5 KMP	21		
7.6 Z value	21		
7.7 Manacher	22		
7.8 Lexicographically Smallest Rotation	22		
7.9 BWI	22		
7.10 Palindromic Tree	22		

## 1 Basic

### 1.1 vimrc

```
se is nu rnu bs=2 ru mouse=a encoding=utf-8
se cin et ts=4 sw=4 sts=4 t_Co=256
syn on
colorscheme ron
filetype indent on
```

### 1.2 IncreaseStackSize

```
//stack resize(change esp to rsp if 64-bit system)
asm( "mov %0,%esp\n" ::"g"(mem+1000000) );
// craziest way
static void run_stack_sz(void(*func)(),size_t stsize){
    char *stack, *send;
    stack=(char *)malloc(stsize);
    send=stack+stsize-16;
    send=(char *)((uintptr_t)send/16*16);
    asm volatile(
        "mov %%rsp, (%0)\n"
        "mov %0, %%rsp\n"
        :
        : "r" (send));
    func();
    asm volatile(
        "mov (%0), %%rsp\n"
        :
        : "r" (send));
    free(stack);
}
```

### 1.3 Pragma optimization

```
#pragma GCC optimize("Ofast,no-stack-protector")
#pragma GCC optimize("no-math-errno,unroll-loops")
#pragma GCC target("sse,sse2,sse3,ssse3,sse4")
#pragma GCC target("popcnt,abm,mmx,avx,tune=native")
```

### 1.4 Debugger

```
#!/usr/bin/env python3
import subprocess as sp
os_name = __import__('platform').system()
cmd,prefix = [],""
if os_name == 'Windows':
    cmd=["cmd", "/C"]
else:
    cmd = ["bash", "-c"]
    prefix = "./"
def GetTestData(exe):
    myout=sp.check_output(cmd+["%s%s"%(prefix, exe)])
    return myout.decode("utf8")
def Judge(a,b,testdata):
    f = open("test.in", "w+")
    f.write(testdata)
    f.close()
    c=sp.check_output(cmd+["%s%s<test.in"%(prefix, a)])
    d=sp.check_output(cmd+["%s%s<test.in"%(prefix, b)])
```

```

if not c == d:
    print("answer: %s"%c.decode("utf8"),end="")
    print("output: %s"%d.decode("utf8"),end="")
    print("WA!")
    return False
return True
if __name__ == '__main__':
    cnt = 0
    isOK = True
    while isOK:
        cnt += 1
        print(cnt)
        isOK=Judge("sol", "mysol", GetTestData("gen"))

```

## 1.5 Quick Random

```

template<class T,T x1,T x2,T x3,int y1,int y2,int y3>
struct PRNG {
    using S = typename std::make_signed<T>::type;
    T s;
    PRNG(T _s = 0) : s(_s) {}
    T next() {
        T z = (s += x1);
        z = (z ^ (z >> y1)) * x2;
        z = (z ^ (z >> y2)) * x3;
        return z ^ (z >> y3);
    }
    T next(T n) { return next() % n; }
    S next(S l, S r){return l+next(r-l+1);}
    T operator()() { return next(); }
    T operator()(T n) { return next(n); }
    S operator()(S l, S r) { return next(l, r); }
    static T gen(T s) { return PRNG(s)(); }
    template<class U>
    void shuffle(U first,U last){
        size_t n=last-first;
        for(size_t i=0;i<n;i++){
            swap(first[i],first[next(i+1)]);
        }
    };
    using R32=PRNG<uint32_t,0x9E3779B1,0x85EBCA6B,
    0xC2B2AE35,16,13,16>;
    R32 r32;
    using R64=PRNG<uint64_t,0x9E3779B97F4A7C15,
    0xBF58476D1CE4E5B9,0x94D0498B133111EB,30,27,31>;
    R64 r64;

```

## 1.6 IO Optimization

```

static inline int gc() {
    static char buf[ 1 << 20 ], *p = buf, *end = buf;
    if ( p == end ) {
        end = buf + fread( buf, 1, 1 << 20, stdin );
        if ( end == buf ) return EOF;
        p = buf;
    }
    return *p++;
}
template < typename T >
static inline bool gn( T &_ ) {
    register int c = gc(); register T __ = 1; _ = 0;
    while(( '0'>c||c>'9') && c!=EOF && c!='-') c = gc();
    if(c == '-') { __ = -1; c = gc(); }
    if(c == EOF) return false;
    while('0'<=c&&c<='9') _ = _ * 10 + c - '0', c = gc();
    _ *= __;
    return true;
}
template < typename T, typename ...Args >
static inline bool gn( T &x, Args &...args )
{ return gn(x) && gn(args...); }

```

## 2 Data Structure

### 2.1 Bigint

```

class BigInt{
private:
    using lld = int_fast64_t;

```

```

#define PRINTF_ARG PRIuFAST64
#define LOG_BASE_STR "9"
static constexpr lld BASE = 1000000000;
static constexpr int LOG_BASE = 9;
vector<lld> dig;
bool neg;
inline int len() const { return (int) dig.size(); }
inline int cmp_minus(const BigInt& a) const {
    if(len() == 0 && a.len() == 0) return 0;
    if(neg ^ a.neg)return (int)a.neg*2 - 1;
    if(len()!=a.len())
        return neg?a.len()-len():len()-a.len();
    for(int i=len()-1;i>=0;i--) if(dig[i]!=a.dig[i])
        return neg?a.dig[i]-dig[i]:dig[i]-a.dig[i];
    return 0;
}
inline void trim(){
    while(!dig.empty()&&!dig.back())dig.pop_back();
    if(dig.empty()) neg = false;
}
public:
    BigInt(): dig(vector<lld>()), neg(false){}
    BigInt(lld a): dig(vector<lld>()){
        neg = a<0; dig.push_back(abs(a));
        trim();
    }
    BigInt(const string& a): dig(vector<lld>()){
        assert(!a.empty()); neg = (a[0]=='-');
        for(int i=((int)a.size()-1;i>=neg;i-=LOG_BASE){
            lld cur = 0;
            for(int j=min(LOG_BASE-1,i-neg);j>=0;j--)
                cur = cur*10+a[i-j]-'0';
            dig.push_back(cur);
        } trim();
    }
    inline bool operator<(const BigInt& a)const
    {return cmp_minus(a)<0;}
    inline bool operator<=(const BigInt& a)const
    {return cmp_minus(a)<=0;}
    inline bool operator==(const BigInt& a)const
    {return cmp_minus(a)==0;}
    inline bool operator!=(const BigInt& a)const
    {return cmp_minus(a)!=0;}
    inline bool operator>(const BigInt& a)const
    {return cmp_minus(a)>0;}
    inline bool operator>=(const BigInt& a)const
    {return cmp_minus(a)>=0;}
    BigInt operator-() const {
        BigInt ret = *this;
        ret.neg ^= 1;
        return ret;
    }
    BigInt operator+(const BigInt& a) const {
        if(neg) return -(-( *this )+(-a));
        if(a.neg) return ( *this )-(-a);
        int n = max(a.len(), len());
        BigInt ret; ret.dig.resize(n);
        lld pro = 0;
        for(int i=0;i<n;i++){
            ret.dig[i] = pro;
            if(i < a.len()) ret.dig[i] += a.dig[i];
            if(i < len()) ret.dig[i] += dig[i];
            pro = 0;
            if(ret.dig[i] >= BASE) pro = ret.dig[i]/BASE;
            ret.dig[i] -= BASE*pro;
        }
        if(pro != 0) ret.dig.push_back(pro);
        return ret;
    }
    BigInt operator-(const BigInt& a) const {
        if(neg) return -(-( *this ) - (-a));
        if(a.neg) return ( *this ) + (-a);
        int diff = cmp_minus(a);
        if(diff < 0) return -(a - ( *this ));
        if(diff == 0) return 0;
        BigInt ret; ret.dig.resize(len(), 0);
        for(int i=0;i<len();i++){
            ret.dig[i] += dig[i];
            if(i < a.len()) ret.dig[i] -= a.dig[i];
            if(ret.dig[i] < 0){
                ret.dig[i] += BASE;
                ret.dig[i+1]--;
            }
        }
    }

```

```

    }
}
ret.trim();
return ret;
}
BigInt operator*(const BigInt& a) const {
    if(!len()||!a.len()) return 0;
    BigInt ret; ret.dig.resize(len()+a.len()+1);
    ret.neg = neg ^ a.neg;
    for(int i=0;i<len();i++){
        for(int j=0;j<a.len();j++){
            ret.dig[i+j] += dig[i] * a.dig[j];
            if(ret.dig[i+j] >= BASE) {
                lld x = ret.dig[i+j] / BASE;
                ret.dig[i+j+1] += x;
                ret.dig[i+j] -= x * BASE;
            }
        }
    }
    ret.trim();
    return ret;
}
BigInt operator/(const BigInt& a) const {
    assert(a.len());
    if(len() < a.len()) return 0;
    BigInt ret; ret.dig.resize(len()-a.len()+1);
    ret.neg = a.neg;
    for(int i=len()-a.len();i>=0;i--){
        lld l = 0, r = BASE;
        while(r-l > 1){
            lld mid = (l+r)>>1;
            ret.dig[i] = mid;
            if(ret*a<=(neg?-( *this):( *this))) l = mid;
            else r = mid;
        }
        ret.dig[i] = l;
    }
    ret.neg ^= neg; ret.trim();
    return ret;
}
BigInt operator%(const BigInt& a) const {
    return (*this) - (*this) / a * a;
}
friend BigInt abs(BigInt a){
    a.neg = 1; return a;
}
friend void swap(BigInt& a, BigInt& b){
    swap(a.dig, b.dig); swap(a.neg, b.neg);
}
friend istream& operator>>(istream& ss, BigInt& a){
    string s; ss >> s; a = s;
    return ss;
}
friend ostream& operator<<(ostream& o, const BigInt& a){
    if(a.len() == 0) return o << '0';
    if(a.neg) o << '-';
    ss << o.dig.back();
    for(int i=a.len()-2;i>=0;i--){
        o<<setw(LOG_BASE)<<setfill('0')<<a.dig[i];
        return o;
    }
}
inline void print() const {
    if(len() == 0){putchar('0');return;}
    if(neg) putchar('-');
    printf("%" PRINTF_ARG, dig.back());
    for(int i=len()-2;i>=0;i--){
        printf("%0" LOG_BASE_STR PRINTF_ARG, dig[i]);
    }
}
#undef PRINTF_ARG
#undef LOG_BASE_STR
};

```

## 2.2 Dark Magic

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/priority_queue.hpp>
using __gnu_pbds::pairing_heap_tag;
using __gnu_pbds::binary_heap_tag;
using __gnu_pbds::binomial_heap_tag;
using __gnu_pbds::rc_binomial_heap_tag;
using __gnu_pbds::thin_heap_tag;
template<typename T>

```

```

using pbds_heap=__gnu_pbds::priority_queue<T,less<T>,\
pairing_heap_tag>;
using __gnu_pbds::rb_tree_tag;
using __gnu_pbds::ov_tree_tag;
using __gnu_pbds::splay_tree_tag;
template<typename T>
using ordered_set = __gnu_pbds::tree<T,\
__gnu_pbds::null_type,less<T>,rb_tree_tag,\
__gnu_pbds::tree_order_statistics_node_update>;
template<typename A,typename B>
using hTable1=__gnu_pbds::cc_hash_table<A,B>;
template<typename A,typename B>
using hTable2=__gnu_pbds::gp_hash_table<A,B>;
int main(){
    ordered_set<int> ss;
    ss.insert(1); ss.insert(5);
    assert(*ss.find_by_order(0)==1);
    assert(ss.order_of_key(-1)==0);
    pbds_heap pq1, pq2;
    pq1.push(1); pq2.push(2);
    pq1.join(pq2);
    assert(pq2.size()==0);
    auto it = pq1.push(87);
    pq1.modify(it, 19);
    return 0;
}

```

## 2.3 SkewHeap

```

template < typename T, typename cmp = less< T > >
class SkewHeap{
private:
    struct SkewNode{
        T x;
        SkewNode *lc, *rc;
        SkewNode( T a = 0 ) : x( a ), lc( 0 ), rc( 0 ) {}
    } *root;
    cmp CMP_;
    size_t count;
    SkewNode* Merge( SkewNode* a, SkewNode* b ) {
        if ( !a or !b ) return a ? a : b;
        if ( CMP_( a->x, b->x ) ) swap( a, b );
        a -> rc = Merge( a->rc, b );
        swap( a -> lc, a->rc );
        return a;
    }
public:
    SkewHeap(): root( 0 ), count( 0 ) {}
    size_t size() { return count; }
    bool empty() { return count == 0; }
    T top() { return root->x; }
    void clear(){ root = 0; count = 0; }
    void push ( const T& x ) {
        SkewNode* a = new SkewNode( x );
        count += 1; root = Merge( root, a );
    }
    void join( SkewHeap& a ) {
        count += a.count; a.count = 0;
        root = Merge( root, a.root );
    }
    void pop() {
        count--; root = Merge( root->lc, root->rc );
    }
    friend void swap( SkewHeap& a, SkewHeap& b ) {
        swap( a.root, b.root ); swap( a.count, b.count );
    }
};

```

## 2.4 Disjoint Set

```

class DJS{
private:
    vector< int > fa, sz, sv;
    vector< pair< int*, int > > opt;
    inline void assign( int *k, int v ) {
        opt.emplace_back( k, *k );
        *k = v;
    }
public:
    inline void init( int n ) {

```

```

    fa.resize( n ); iota( fa.begin(), fa.end(), 0 );
    sz.resize( n ); fill( sz.begin(), sz.end(), 1 );
    opt.clear();
}
int query( int x ) {
    return ( fa[ x ] == x ) ? x : query( fa[ x ] );
}
inline void merge( int a, int b ) {
    int af = query( a ), bf = query( b );
    if( af == bf ) return;
    if( sz[ af ] < sz[ bf ] ) swap( af, bf );
    assign( &fa[ bf ], fa[ af ] );
    assign( &sz[ af ], sz[ af ] + sz[ bf ] );
}
inline void save() {sv.push_back( (int)opt.size() );}
inline void undo() {
    int ls = sv.back(); sv.pop_back();
    while ( ( int ) opt.size() > ls ) {
        pair< int*, int > cur = opt.back();
        *cur.first = cur.second;
        opt.pop_back();
    }
}
};

```

## 2.5 Link-Cut Tree

```

struct Node{
    Node *par,*ch[2];
    int xor_sum,v;
    bool is_rev;
    Node(int _v){
        v=xor_sum=_v;is_rev=false;
        par=ch[0]=ch[1]=nullptr;
    }
    inline void set_rev(){is_rev^=1;swap(ch[0],ch[1]);}
    inline void down(){
        if(is_rev){
            if(ch[0]!=nullptr) ch[0]->set_rev();
            if(ch[1]!=nullptr) ch[1]->set_rev();
            is_rev=false;
        }
    }
    inline void up(){
        xor_sum=v;
        if(ch[0]!=nullptr){
            xor_sum^=ch[0]->xor_sum;
            ch[0]->par=this;
        }
        if(ch[1]!=nullptr){
            xor_sum^=ch[1]->xor_sum;
            ch[1]->par=this;
        }
    }
    inline bool is_root(){
        return par==nullptr ||\
            (par->ch[0]!=this && par->ch[1]!=this);
    }
    bool is_rch(){return !is_root() && par->ch[1]==this;}
} *node[maxn],*stk[maxn];
int top;
void to_child(Node* p,Node* c,bool dir){
    p->ch[dir]=c;
    p->up();
}
inline void rotate(Node* node){
    Node* par=node->par;
    Node* par_par=par->par;
    bool dir=node->is_rch();
    bool par_dir=par->is_rch();
    to_child(par,node->ch[!dir],dir);
    to_child(node,par,!dir);
    if(par_par!=nullptr && par_par->ch[par_dir]==par)
        to_child(par_par,node,par_dir);
    else node->par=par_par;
}
inline void splay(Node* node){
    Node* tmp=node;
    stk[top++]=node;
    while(!tmp->is_root()){
        tmp=tmp->par;
    }
    stk[top++]=tmp;
    while(top) stk[--top]->down();
    for(Node *fa=node->par;
        !node->is_root();
        rotate(node),fa=node->par)
        if(!fa->is_root())
            rotate(fa->is_rch()==node->is_rch()?fa:node);
}
inline void access(Node* node){
    Node* last=nullptr;
    while(node!=nullptr){
        splay(node);
        to_child(node,last,true);
        last=node;
        node=node->par;
    }
}
inline void change_root(Node* node){
    access(node);splay(node);node->set_rev();
}
inline void link(Node* x,Node* y){
    change_root(x);splay(x);x->par=y;
}
inline void split(Node* x,Node* y){
    change_root(x);access(y);splay(x);
    to_child(x,nullptr,true);y->par=nullptr;
}
inline void change_val(Node* node,int v){
    access(node);splay(node);node->v=v;node->up();
}
inline int query(Node* x,Node* y){
    change_root(x);access(y);splay(y);
    return y->xor_sum;
}
inline Node* find_root(Node* node){
    access(node);splay(node);
    Node* last=nullptr;
    while(node!=nullptr){
        node->down();last=node;node=node->ch[0];
    }
    return last;
}
set<pii> dic;
inline void add_edge(int u,int v){
    if(u>v) swap(u,v);
    if(find_root(node[u])==find_root(node[v])) return;
    dic.insert(pii(u,v));
    link(node[u],node[v]);
}
inline void del_edge(int u,int v){
    if(u>v) swap(u,v);
    if(dic.find(pii(u,v))==dic.end()) return;
    dic.erase(pii(u,v));
    split(node[u],node[v]);
}

```

```

    stk[top++]=tmp;
    while(top) stk[--top]->down();
    for(Node *fa=node->par;
        !node->is_root();
        rotate(node),fa=node->par)
        if(!fa->is_root())
            rotate(fa->is_rch()==node->is_rch()?fa:node);
}
inline void access(Node* node){
    Node* last=nullptr;
    while(node!=nullptr){
        splay(node);
        to_child(node,last,true);
        last=node;
        node=node->par;
    }
}
inline void change_root(Node* node){
    access(node);splay(node);node->set_rev();
}
inline void link(Node* x,Node* y){
    change_root(x);splay(x);x->par=y;
}
inline void split(Node* x,Node* y){
    change_root(x);access(y);splay(x);
    to_child(x,nullptr,true);y->par=nullptr;
}
inline void change_val(Node* node,int v){
    access(node);splay(node);node->v=v;node->up();
}
inline int query(Node* x,Node* y){
    change_root(x);access(y);splay(y);
    return y->xor_sum;
}
inline Node* find_root(Node* node){
    access(node);splay(node);
    Node* last=nullptr;
    while(node!=nullptr){
        node->down();last=node;node=node->ch[0];
    }
    return last;
}
set<pii> dic;
inline void add_edge(int u,int v){
    if(u>v) swap(u,v);
    if(find_root(node[u])==find_root(node[v])) return;
    dic.insert(pii(u,v));
    link(node[u],node[v]);
}
inline void del_edge(int u,int v){
    if(u>v) swap(u,v);
    if(dic.find(pii(u,v))==dic.end()) return;
    dic.erase(pii(u,v));
    split(node[u],node[v]);
}

```

## 2.6 LiChao Segment Tree

```

struct Line{
    int m, k, id;
    Line() : id( -1 ) {}
    Line( int a, int b, int c )
        : m( a ), k( b ), id( c ) {}
    int at( int x ) { return m * x + k; }
};
class LiChao {
private:
    int n; vector< Line > nodes;
    inline int lc( int x ) { return 2 * x + 1; }
    inline int rc( int x ) { return 2 * x + 2; }
    void insert( int l, int r, int id, Line ln ) {
        int m = ( l + r ) >> 1;
        if ( nodes[ id ].id == -1 ) {
            nodes[ id ] = ln;
            return;
        }
        bool atLeft = nodes[ id ].at( l ) < ln.at( l );
        if ( nodes[ id ].at( m ) < ln.at( m ) ) {
            atLeft ^= 1; swap( nodes[ id ], ln );
        }
    }
}

```

```

    if ( r - 1 == 1 ) return;
    if ( atLeft ) insert( l, m, lc( id ), ln );
    else insert( m, r, rc( id ), ln );
}
int query( int l, int r, int id, int x ) {
    int ret = 0;
    if ( nodes[ id ].id != -1 )
        ret = nodes[ id ].at( x );
    int m = ( l + r ) >> 1;
    if ( r - 1 == 1 ) return ret;
    else if ( x < m )
        return max( ret, query( l, m, lc( id ), x ) );
    else
        return max( ret, query( m, r, rc( id ), x ) );
}
public:
    void build( int n_ ) {
        n = n_; nodes.clear();
        nodes.resize( n << 2, Line() );
    }
    void insert( Line ln ) { insert( 0, n, 0, ln ); }
    int query( int x ) { return query( 0, n, 0, x ); }
} lichao;

```

## 2.7 Treap

```

namespace Treap{
#define sz( x ) ( ( x ) ? ( ( x )->size ) : 0 )
struct node{
    int size;
    uint32_t pri;
    node *lc, *rc;
    node() : size(0), pri(rand()), lc( 0 ), rc( 0 ) {}
    void pull() {
        size = 1;
        if ( lc ) size += lc->size;
        if ( rc ) size += rc->size;
    }
};
node* merge( node* L, node* R ) {
    if ( not L or not R ) return L ? L : R;
    if ( L->pri > R->pri ) {
        L->rc = merge( L->rc, R ); L->pull();
        return L;
    } else {
        R->lc = merge( L, R->lc ); R->pull();
        return R;
    }
}
void split_by_size( node*rt, int k, node*&L, node*&R ) {
    if ( not rt ) L = R = nullptr;
    else if ( sz( rt->lc ) + 1 <= k ) {
        L = rt;
        split_by_size( rt->rc, k-sz(rt->lc)-1, L->rc, R );
        L->pull();
    } else {
        R = rt;
        split_by_size( rt->lc, k, L, R->lc );
        R->pull();
    }
}
#undef sz
}

```

## 2.8 SparseTable

```

template < typename T, typename Cmp_ = less< T > >
class SparseTable {
private:
    vector< vector< T > > tbl;
    vector< int > lg;
    T cv( T a, T b ) {
        return Cmp_()( a, b ) ? a : b;
    }
public:
    void init( T arr[], int n ) {
        // 0-base
        lg.resize( n + 1 );
        lg[ 0 ] = -1;
        for( int i=1; i<=n; ++i ) lg[i] = lg[i>>1] + 1;
    }

```

```

tbl.resize( lg[n] + 1 );
tbl[ 0 ].resize( n );
copy( arr, arr + n, tbl[ 0 ].begin() );
for ( int i = 1; i <= lg[ n ]; ++i ) {
    int len = 1 << ( i - 1 ), sz = 1 << i;
    tbl[ i ].resize( n - sz + 1 );
    for ( int j = 0; j <= n - sz; ++j )
        tbl[i][j] = cv(tbl[i-1][j], tbl[i-1][j+len]);
}
T query( int l, int r ) {
    // 0-base [l, r)
    int wh = lg[ r - l ], len = 1 << wh;
    return cv( tbl[ wh ][ l ], tbl[ wh ][ r - len ] );
}
};

```

## 2.9 Linear Basis

```

struct LinearBasis {
private:
    int n, sz;
    vector< ll_u > B;
    inline ll_u two( int x ) { return ( ( ll_u ) 1 ) << x; }
public:
    void init( int n_ ) {
        n = n_; B.clear(); B.resize( n ); sz = 0;
    }
    void insert( ll_u x ) {
        // add x into B
        for ( int i = n-1; i >= 0; --i ) if( two(i) & x ){
            if ( B[ i ] ) x ^= B[ i ];
            else {
                B[ i ] = x; sz++;
                for ( int j = i - 1; j >= 0; --j )
                    if( B[ j ] && ( two( j ) & B[ i ] ) )
                        B[ i ] ^= B[ j ];
                for ( int j = i + 1; j < n; ++j )
                    if ( two( i ) & B[ j ] )
                        B[ j ] ^= B[ i ];
                break;
            }
        }
    }
    inline int size() { return sz; }
    bool check( ll_u x ) {
        // is x in span(B) ?
        for ( int i = n-1; i >= 0; --i ) if( two(i) & x )
            if( B[ i ] ) x ^= B[ i ];
        else return false;
        return true;
    }
    ll_u kth_small( ll_u k ) {
        /** 1-base would always > 0 **/
        /** should check it **/
        /** if we choose at least one element
            but size(B)(vectors in B)==N(original elements)
            then we can't get 0 */
        ll_u ret = 0;
        for ( int i = 0; i < n; ++i ) if( B[ i ] ) {
            if ( k & 1 ) ret ^= B[ i ];
            k >>= 1;
        }
        return ret;
    }
} base;

```

## 3 Graph

### 3.1 Euler Circuit

```

bool vis[ N ]; size_t la[ K ];
void dfs( int u, vector< int >&vec ) {
    while ( la[ u ] < G[ u ].size() ) {
        if( vis[ G[ u ][ la[ u ] ].second ] ) {
            ++ la[ u ];
            continue;
        }
        int v = G[ u ][ la[ u ] ].first;
        vis[ G[ u ][ la[ u ] ].second ] = true;
    }
}

```

```

    ++ la[ u ]; dfs( v, vec );
    vec.push_back( v );
}
}

```

### 3.2 BCC Edge

```

class BCC{
private:
    vector< int > low, dfn;
    int cnt;
    vector< bool > bridge;
    vector< vector< PII > > G;
    void dfs( int w, int f ) {
        dfn[ w ] = cnt++;
        low[ w ] = dfn[ w ];
        for ( auto [ u, t ] : G[ w ] ) {
            if ( u == f ) continue;
            if ( dfn[ u ] != 0 ) {
                low[ w ] = min( low[ w ], dfn[ u ] );
            } else {
                dfs( u, w );
                low[ w ] = min( low[ w ], low[ u ] );
                if ( low[ u ] > dfn[ w ] ) bridge[ t ] = true;
            }
        }
    }
public:
    void init( int n, int m ) {
        G.resize( n );
        fill( G.begin(), G.end(), vector< PII >() );
        bridge.clear(); bridge.resize( m );
        low.clear(); low.resize( n );
        dfn.clear(); dfn.resize( n );
        cnt = 0;
    }
    void add_edge( int u, int v ) {
        // should check for multiple edge
        G[ u ].emplace_back( v, cnt );
        G[ v ].emplace_back( u, cnt ++ );
    }
    void solve(){ cnt = 1; dfs( 0, 0 ); }
    // the id will be same as insert order, 0-base
    bool is_bridge( int x ) { return bridge[ x ]; }
} bcc;

```

### 3.3 BCC Vertex

```

class BCC{
private:
    int n, ecnt;
    vector< vector< pair< int, int > > > G;
    vector< int > low, dfn, id;
    vector< bool > vis, ap;
    void dfs( int u, int f, int d ) {
        int child = 0;
        dfn[ u ] = low[ u ] = d; vis[ u ] = true;
        for ( auto e : G[ u ] ) if ( e.first != f ) {
            if ( vis[ e.first ] ) {
                low[ u ] = min( low[ u ], dfn[ e.first ] );
            } else {
                dfs( e.first, u, d + 1 ); child ++;
                low[ u ] = min( low[ u ], low[ e.first ] );
                if ( low[ e.first ] >= d ) ap[ u ] = true;
            }
        }
        if ( u == f and child <= 1 ) ap[ u ] = false;
    }
    void mark( int u, int idd ) {
        // really????????
        if ( ap[ u ] ) return;
        for ( auto e : G[ u ] )
            if ( id[ e.second ] != -1 ) {
                id[ e.second ] = idd;
                mark( e.first, idd );
            }
    }
public:
    void init( int n_ ) {
        ecnt = 0, n = n_;
    }

```

```

        G.clear(); G.resize( n );
        low.resize( n ); dfn.resize( n );
        ap.clear(); ap.resize( n );
        vis.clear(); vis.resize( n );
    }
    void add_edge( int u, int v ) {
        G[ u ].emplace_back( v, ecnt );
        G[ v ].emplace_back( u, ecnt ++ );
    }
    void solve() {
        for ( int i = 0 ; i < n ; ++ i )
            if ( not vis[ i ] ) dfs( i, i, 0 );
        id.resize( ecnt );
        fill( id.begin(), id.end(), -1 );
        ecnt = 0;
        for ( int i = 0 ; i < n ; ++ i )
            if ( ap[ i ] ) for ( auto e : G[ i ] )
                if ( id[ e.second ] != -1 ) {
                    id[ e.second ] = ecnt;
                    mark( e.first, ecnt ++ );
                }
    }
    int get_id( int x ) { return id[ x ]; }
    int count() { return ecnt; }
    bool is_ap( int u ) { return ap[ u ]; }
} bcc;

```

### 3.4 2-SAT (SCC)

```

class TwoSat{
private:
    int n;
    vector<vector<int>> rG,G,sccs;
    vector<int> ord,idx;
    vector<bool> vis,result;
    void dfs(int u){
        vis[u]=true;
        for(int v:G[u])
            if(!vis[v]) dfs(v);
        ord.push_back(u);
    }
    void rdfs(int u){
        vis[u]=false;idx[u]=sccs.size()-1;
        sccs.back().push_back(u);
        for(int v:rG[u])
            if(vis[v])rdfs(v);
    }
public:
    void init(int n_){
        n=n_;G.clear();G.resize(n);
        rG.clear();rG.resize(n);
        sccs.clear();ord.clear();
        idx.resize(n);result.resize(n);
    }
    void add_edge(int u,int v){
        G[u].push_back(v);rG[v].push_back(u);
    }
    void orr(int x,int y){
        if ((x^y)==1)return;
        add_edge(x^1,y); add_edge(y^1,x);
    }
    bool solve(){
        vis.clear();vis.resize(n);
        for(int i=0;i<n;++i)
            if(not vis[i])dfs(i);
        reverse(ord.begin(),ord.end());
        for (int u:ord){
            if(!vis[u])continue;
            sccs.push_back(vector<int>());
            rdfs(u);
        }
        for(int i=0;i<n;i+=2)
            if(idx[i]==idx[i+1])
                return false;
        vector<bool> c(sccs.size());
        for(size_t i=0;i<sccs.size();++i){
            for(size_t j=0;j<sccs[i].size();++j){
                result[sccs[i][j]]=c[i];
                c[idx[sccs[i][j]^1]]=!c[i];
            }
        }
    }
}

```



```

    return true;
}
bool get(int x){return result[x];}
inline int get_id(int x){return idx[x];}
inline int count(){return sccs.size();}
} sat2;

```

### 3.5 Lowbit Decomposition

```

class LowbitDecomp{
private:
    int time_, chain_, LOG_N;
    vector< vector< int > > G, fa;
    vector< int > tl, tr, chain, chain_st;
    // chain_ : number of chain
    // tl, tr[ u ] : subtree interval in the seq. of u
    // chain_st[ u ] : head of the chain contains u
    // chain[ u ] : chain id of the chain u is on
    inline int lowbit( int x ) {
        return x & ( -x );
    }
    void predfs( int u, int f ) {
        chain[ u ] = 0;
        for ( int v : G[ u ] ) {
            if ( v == f ) continue;
            predfs( v, u );
            if( lowbit( chain[ u ] ) < lowbit( chain[ v ] ) )
                chain[ u ] = chain[ v ];
        }
        if ( not chain[ u ] )
            chain[ u ] = chain_ ++;
    }
    void dfschain( int u, int f ) {
        fa[ u ][ 0 ] = f;
        for ( int i = 1 ; i < LOG_N ; ++ i )
            fa[ u ][ i ] = fa[ fa[ u ][ i - 1 ] ][ i - 1 ];
        tl[ u ] = time_ ++;
        if ( not chain_st[ chain[ u ] ] )
            chain_st[ chain[ u ] ] = u;
        for ( int v : G[ u ] )
            if ( v != f and chain[ v ] == chain[ u ] )
                dfschain( v, u );
        for ( int v : G[ u ] )
            if ( v != f and chain[ v ] != chain[ u ] )
                dfschain( v, u );
        tr[ u ] = time_;
    }
    inline bool anc( int u, int v ) {
        return tl[ u ] <= tl[ v ] \
            and tr[ v ] <= tr[ u ];
    }
public:
    inline int lca( int u, int v ) {
        if ( anc( u, v ) ) return u;
        for ( int i = LOG_N - 1 ; i >= 0 ; -- i )
            if ( not anc( fa[ u ][ i ], v ) )
                u = fa[ u ][ i ];
        return fa[ u ][ 0 ];
    }
    void init( int n ) {
        n ++;
        for ( LOG_N = 0 ; ( 1 << LOG_N ) < n ; ++ LOG_N );
        fa.clear();
        fa.resize( n, vector< int >( LOG_N ) );
        G.clear(); G.resize( n );
        tl.clear(); tl.resize( n );
        tr.clear(); tr.resize( n );
        chain.clear(); chain.resize( n );
        chain_st.clear(); chain_st.resize( n );
    }
    void add_edge( int u , int v ) {
        // 1-base
        G[ u ].push_back( v );
        G[ v ].push_back( u );
    }
    void decompose(){
        chain_ = 1;
        predfs( 1, 1 );
        time_ = 0;
        dfschain( 1, 1 );
    }
}

```

```

PII get_inter( int u ) { return {tl[ u ], tr[ u ]}; }
vector< PII > get_path( int u , int v ){
    vector< PII > res;
    int g = lca( u, v );
    while ( chain[ u ] != chain[ g ] ) {
        int s = chain_st[ chain[ u ] ];
        res.emplace_back( tl[ s ], tl[ u ] + 1 );
        u = fa[ s ][ 0 ];
    }
    res.emplace_back( tl[ g ], tl[ u ] + 1 );
    while ( chain[ v ] != chain[ g ] ) {
        int s = chain_st[ chain[ v ] ];
        res.emplace_back( tl[ s ], tl[ v ] + 1 );
        v = fa[ s ][ 0 ];
    }
    res.emplace_back( tl[ g ] + 1, tl[ v ] + 1 );
    return res;
}
/* res : list of intervals from u to v
 * ( note only nodes work, not edge )
 * usage :
 * vector< PII >& path = tree.get_path( u , v )
 * for( auto [ l, r ] : path ) {
 *     0-base [ l, r )
 * }
 */
} tree;

```

### 3.6 MaxClique

```

#define N 111
struct MaxClique{ // 0-base
    typedef bitset< N > Int;
    Int linkto[ N ], v[ N ];
    int n;
    void init( int _n ){
        n = _n;
        for( int i = 0 ; i < n ; i ++ ){
            linkto[ i ].reset();
            v[ i ].reset();
        }
    }
    void add_edge( int a , int b ){
        v[ a ][ b ] = v[ b ][ a ] = 1;
    }
    int popcount(const Int& val)
    { return val.count(); }
    int lowbit(const Int& val)
    { return val._Find_first(); }
    int ans , stk[ N ];
    int id[ N ] , di[ N ] , deg[ N ];
    Int cans;
    void maxclique(int elem_num, Int candi){
        if(elem_num > ans){
            ans = elem_num;
            cans.reset();
            for( int i = 0 ; i < elem_num ; i ++ )
                cans[ id[ stk[ i ] ] ] = 1;
        }
        int potential = elem_num + popcount(candi);
        if(potential <= ans) return;
        int pivot = lowbit(candi);
        Int smaller_candi = candi & (~linkto[pivot]);
        while(smaller_candi.count() && potential > ans){
            int next = lowbit(smaller_candi);
            candi[ next ] = !candi[ next ];
            smaller_candi[next] = !smaller_candi[next];
            potential --;
            if(next!=pivot
                &&!(smaller_candi&linkto[next]).count())
                continue;
            stk[elem_num] = next;
            maxclique(elem_num+1, candi&linkto[next]);
        }
    }
    int solve(){
        for( int i = 0 ; i < n ; i ++ ){
            id[ i ] = i;
            deg[ i ] = v[ i ].count();
        }
        sort( id , id + n , [&](int id1, int id2){

```

```

        return deg[id1] > deg[id2]; } );
for( int i = 0 ; i < n ; i ++ )
    di[ id[ i ] ] = i;
for( int i = 0 ; i < n ; i ++ )
    for( int j = 0 ; j < n ; j ++ )
        if( v[ i ][ j ] )
            linkto[ di[ i ] ][ di[ j ] ] = 1;
Int cand; cand.reset();
for( int i = 0 ; i < n ; i ++ )
    cand[ i ] = 1;
ans = 1;
cans.reset(); cans[ 0 ] = 1;
maxclique(0, cand);
return ans;
}
} solver;

```

### 3.7 Virtual Tree

```

inline bool cmp(const int &i, const int &j) {
    return dfn[i] < dfn[j];
}
void build(int vectrices[], int k) {
    static int stk[MAX_N];
    sort(vectrices, vectrices + k, cmp);
    stk[sz++] = 0;
    for (int i = 0; i < k; ++i) {
        int u = vectrices[i], lca = LCA(u, stk[sz - 1]);
        if (lca == stk[sz - 1]) stk[sz++] = u;
        else {
            while (sz >= 2 && dep[stk[sz - 2]] >= dep[lca]) {
                addEdge(stk[sz - 2], stk[sz - 1]);
                sz--;
            }
            if (stk[sz - 1] != lca) {
                addEdge(lca, stk[sz - 1]);
                stk[sz++] = lca, vectrices[cnt++] = lca;
            }
            stk[sz++] = u;
        }
    }
    for (int i = 0; i < sz - 1; ++i)
        addEdge(stk[i], stk[i + 1]);
}

```

### 3.8 Tree Hashing

```

uint64_t hsah( int u, int f ) {
    uint64_t r = 127;
    for ( int v : G[ u ] ) {
        if ( v == f ) continue;
        uint64_t hh = hsah( v, u );
        r = r + ( hh * hh ) % mod;
    }
    return r;
}

```

### 3.9 Minimum Mean Cycle

```

/* minimum mean cycle O(VE) */
struct MMC{
#define FZ(n) memset((n),0,sizeof(n))
#define E 101010
#define V 1021
#define inf 1e9
    struct Edge { int v,u; double c; };
    int n, m, prv[V][V], prve[V][V], vst[V];
    Edge e[E];
    vector<int> edgeID, cycle, rho;
    double d[V][V];
    void init( int _n ) { n = _n; m = 0; }
    // WARNING: TYPE matters
    void add_edge( int vi , int ui , double ci )
    { e[ m ++ ] = { vi , ui , ci }; }
    void bellman_ford() {
        for(int i=0; i<n; i++) d[0][i]=0;
        for(int i=0; i<n; i++) {
            fill(d[i+1], d[i+1]+n, inf);
            for(int j=0; j<m; j++) {

```

```

                int v = e[j].v, u = e[j].u;
                if(d[i][v]<inf && d[i+1][u]>d[i][v]+e[j].c) {
                    d[i+1][u] = d[i][v]+e[j].c;
                    prv[i+1][u] = v;
                    prve[i+1][u] = j;
                }
            }
        }
    }
    double solve(){
        // returns inf if no cycle, mmc otherwise
        double mmc=inf;
        int st = -1;
        bellman_ford();
        for(int i=0; i<n; i++) {
            double avg=-inf;
            for(int k=0; k<n; k++) {
                if(d[n][i]<inf-eps)
                    avg=max(avg,(d[n][i]-d[k][i])/(n-k));
                else avg=max(avg,inf);
            }
            if (avg < mmc) tie(mmc, st) = tie(avg, i);
        }
        FZ(vst); edgeID.clear(); cycle.clear(); rho.clear();
        for (int i=n; !vst[st]; st=prv[i--][st]) {
            vst[st]++;
            edgeID.PB(prve[i][st]);
            rho.PB(st);
        }
        while (vst[st] != 2) {
            int v = rho.back(); rho.pop_back();
            cycle.PB(v);
            vst[v]++;
        }
        reverse(ALL(edgeID));
        edgeID.resize(SZ(cycle));
        return mmc;
    }
} mmc;

```

### 3.10 Mo's Algorithm on Tree

```

int n, q, nxt[ N ], to[ N ], hd[ N ];
struct Que{
    int u, v, id;
} que[ N ];
void init() {
    cin >> n >> q;
    for ( int i = 1 ; i < n ; ++ i ) {
        int u, v; cin >> u >> v;
        nxt[ i << 1 | 0 ] = hd[ u ];
        to[ i << 1 | 0 ] = v;
        hd[ u ] = i << 1 | 0;
        nxt[ i << 1 | 1 ] = hd[ v ];
        to[ i << 1 | 1 ] = u;
        hd[ v ] = i << 1 | 1;
    }
    for ( int i = 0 ; i < q ; ++ i ) {
        cin >> que[ i ].u >> que[ i ].v; que[ i ].id = i;
    }
}
int dfn[N], dfn_, block_id[N], block_, stk[N], stk_;
void dfs( int u, int f ) {
    dfn[ u ] = dfn_++; int saved_rbp = stk_;
    for ( int v_ = hd[ u ] ; v_ ; v_ = nxt[ v_ ] ) {
        if ( to[ v_ ] == f ) continue;
        dfs( to[ v_ ], u );
        if ( stk_ - saved_rbp < SQRT_N ) continue;
        for ( ++ block_ ; stk_ != saved_rbp ; )
            block_id[ stk_ -- ] = block_;
    }
    stk[ stk_ ++ ] = u;
}
bool inPath[ N ];
void Diff( int u ) {
    if ( inPath[ u ] ^ 1 )
        // remove this edge
    else
        // add this edge
}

```



```

void traverse( int& origin_u, int u ) {
    for ( int g = lca( origin_u, u );
          origin_u != g ; origin_u = parent_of[ origin_u ] )
        Diff( origin_u );
    for ( int v = u ; v != origin_u ; v = parent_of[ v ] )
        Diff( v );
    origin_u = u;
}

void solve() {
    dfs( 1, 1 );
    while ( stk_ ) block_id[ stk[ --stk_ ] ] = block_;
    sort( que, que + q, [] ( const Que& x, const Que& y )
        {
            return tie( block_id[ x.u ], dfn[ x.v ] )
                < tie( block_id[ y.u ], dfn[ y.v ] );
        } );
    int U = 1, V = 1;
    for ( int i = 0 ; i < q ; ++ i ) {
        pass( U, que[ i ].u );
        pass( V, que[ i ].v );
        // we could get our answer of que[ i ].id
    }
}

/*
Method 2:
dfs u:
    push u
    iterate subtree
    push u
Let P = LCA(u, v), and St(u) <= St(v)
if (P == u) query[St(u), St(v)]
else query[Ed(u), St(v)], query[St(P), St(P)]
*/

```

### 3.11 Minimum Steiner Tree

```

// Minimum Steiner Tree
// O(V 3^T + V^2 2^T)
struct SteinerTree{
#define V 33
#define T 8
#define INF 1023456789
    int n, dst[V][V], dp[1 << T][V], tdst[V];
    void init( int _n ){
        n = _n;
        for( int i = 0 ; i < n ; i ++ ){
            for( int j = 0 ; j < n ; j ++ )
                dst[ i ][ j ] = INF;
            dst[ i ][ i ] = 0;
        }
    }
    void add_edge( int ui, int vi, int wi ){
        dst[ ui ][ vi ] = min( dst[ ui ][ vi ], wi );
        dst[ vi ][ ui ] = min( dst[ vi ][ ui ], wi );
    }
    void shortest_path(){
        for( int k = 0 ; k < n ; k ++ )
            for( int i = 0 ; i < n ; i ++ )
                for( int j = 0 ; j < n ; j ++ )
                    dst[ i ][ j ] = min( dst[ i ][ j ],
                        dst[ i ][ k ] + dst[ k ][ j ] );
    }
    int solve( const vector<int>& ter ){
        int t = (int)ter.size();
        for( int i = 0 ; i < ( 1 << t ) ; i ++ )
            for( int j = 0 ; j < n ; j ++ )
                dp[ i ][ j ] = INF;
        for( int i = 0 ; i < n ; i ++ )
            dp[ 0 ][ i ] = 0;
        for( int msk = 1 ; msk < ( 1 << t ) ; msk ++ ){
            if( msk == ( msk & (-msk) ) ){
                int who = __lg( msk );
                for( int i = 0 ; i < n ; i ++ )
                    dp[ msk ][ i ] = dst[ ter[ who ] ][ i ];
                continue;
            }
            for( int i = 0 ; i < n ; i ++ )
                for( int submsk = ( msk - 1 ) & msk ; submsk ;
                    submsk = ( submsk - 1 ) & msk )
                    dp[ msk ][ i ] = min( dp[ msk ][ i ],

```

```

                        dp[ submsk ][ i ] +
                        dp[ msk ^ submsk ][ i ] );
        for( int i = 0 ; i < n ; i ++ ){
            tdst[ i ] = INF;
            for( int j = 0 ; j < n ; j ++ )
                tdst[ i ] = min( tdst[ i ],
                    dp[ msk ][ j ] + dst[ j ][ i ] );
        }
        for( int i = 0 ; i < n ; i ++ )
            dp[ msk ][ i ] = tdst[ i ];
    }
    int ans = INF;
    for( int i = 0 ; i < n ; i ++ )
        ans = min( ans, dp[ ( 1 << t ) - 1 ][ i ] );
    return ans;
}

} solver;

```

## 4 Matching & Flow

### 4.1 Kuhn Munkres

```

class KM {
private:
    static constexpr lld INF = 1LL << 60;
    vector<lld> hl, hr, slk;
    vector<int> fl, fr, pre, qu;
    vector<vector<lld>> w;
    vector<bool> vl, vr;
    int n, ql, qr;
    bool check(int x) {
        if (vl[x] = true, fl[x] != -1)
            return vr[qu[qr++]] = fl[x] = true;
        while (x != -1) swap(x, fr[fl[x] = pre[x]]);
        return false;
    }
    void bfs(int s) {
        fill(slk.begin(), slk.end(), INF);
        fill(vl.begin(), vl.end(), false);
        fill(vr.begin(), vr.end(), false);
        ql = qr = 0;
        qu[qr++] = s;
        vr[s] = true;
        while (true) {
            lld d;
            while (ql < qr) {
                for (int x = 0, y = qu[ql++]; x < n; ++x) {
                    if (!vl[x] && slk[x] >= (d = hl[x] + hr[y] - w[x][y]))
                        if (pre[x] = y, d) slk[x] = d;
                    else if (!check(x)) return;
                }
            }
            d = INF;
            for (int x = 0; x < n; ++x)
                if (!vl[x] && d > slk[x]) d = slk[x];
            for (int x = 0; x < n; ++x) {
                if (vl[x]) hl[x] += d;
                else slk[x] -= d;
                if (vr[x]) hr[x] -= d;
            }
            for (int x = 0; x < n; ++x)
                if (!vl[x] && !slk[x] && !check(x)) return;
        }
    }
public:
    void init( int _n ) {
        n = _n; qu.resize(n);
        fl.clear(); fl.resize(n, -1);
        fr.clear(); fr.resize(n, -1);
        hr.clear(); hr.resize(n); hl.resize(n);
        w.clear(); w.resize(n, vector<lld>(n));
        slk.resize(n); pre.resize(n);
        vl.resize(n); vr.resize(n);
    }
    void set_edge( int u, int v, lld x ) { w[u][v] = x; }
    lld solve() {
        for (int i = 0; i < n; ++i)
            hl[i] = *max_element(w[i].begin(), w[i].end());
    }
}

```

```

    for (int i = 0; i < n; ++i) bfs(i);
    lld res = 0;
    for (int i = 0; i < n; ++i) res += w[i][f1[i]];
    return res;
}
} km;

```

## 4.2 Bipartite Matching

```

class BipartiteMatching{
private:
    vector<int> X[N], Y[N];
    int fX[N], fY[N], n;
    bitset<N> walked;
    bool dfs(int x){
        for(auto i:X[x]){
            if(walked[i])continue;
            walked[i]=1;
            if(fY[i]==-1||dfs(fY[i])){
                fY[i]=x;fX[x]=i;
                return 1;
            }
        }
        return 0;
    }
public:
    void init(int _n){
        n=_n;
        for(int i=0;i<n;i++){
            X[i].clear();
            Y[i].clear();
            fX[i]=fY[i]=-1;
        }
        walked.reset();
    }
    void add_edge(int x, int y){
        X[x].push_back(y);
        Y[y].push_back(x);
    }
    int solve(){
        int cnt = 0;
        for(int i=0;i<n;i++){
            walked.reset();
            if(dfs(i)) cnt++;
        }
        // return how many pair matched
        return cnt;
    }
};

```

## 4.3 General Graph Matching

```

const int N = 514, E = (2e5) * 2;
struct Graph{
    int to[E],bro[E],head[N],e;
    int lnk[N],vis[N],stp,n;
    void init( int _n ){
        stp = 0; e = 1; n = _n;
        for( int i = 0 ; i <= n ; i ++ )
            head[i] = lnk[i] = vis[i] = 0;
    }
    void add_edge(int u,int v){
        // 1-base
        to[e]=v,bro[e]=head[u],head[u]=e++;
        to[e]=u,bro[e]=head[v],head[v]=e++;
    }
    bool dfs(int x){
        vis[x]=stp;
        for(int i=head[x];i;i=bro[i]){
            int v=to[i];
            if(!lnk[v]){
                lnk[x]=v,lnk[v]=x;
                return true;
            }else if(vis[lnk[v]]<stp){
                int w=lnk[v];
                lnk[x]=v,lnk[v]=x,lnk[w]=0;
                if(dfs(w)) return true;
                lnk[w]=v,lnk[v]=w,lnk[x]=0;
            }
        }
    }
};

```

```

    return false;
}
int solve(){
    int ans = 0;
    for(int i=1;i<=n;i++){
        if(not lnk[i]){
            stp++; ans += dfs(i);
        }
    }
    return ans;
}
} graph;

```

## 4.4 Minimum Weight Matching (Clique version)

```

struct Graph {
    // 0-base (Perfect Match)
    int n, edge[MXN][MXN];
    int match[MXN],dis[MXN],onstk[MXN];
    vector<int> stk;
    void init(int _n) {
        n = _n;
        for (int i=0; i<n; i++)
            for (int j=0; j<n; j++)
                edge[i][j] = 0;
    }
    void set_edge(int u, int v, int w) {
        edge[u][v] = edge[v][u] = w;
    }
    bool SPFA(int u){
        if (onstk[u]) return true;
        stk.PB(u);
        onstk[u] = 1;
        for (int v=0; v<n; v++){
            if (u != v && match[u] != v && !onstk[v]){
                int m = match[v];
                if (dis[m] > dis[u] - edge[v][m] + edge[u][v]){
                    dis[m] = dis[u] - edge[v][m] + edge[u][v];
                    onstk[v] = 1;
                    stk.PB(v);
                    if (SPFA(m)) return true;
                    stk.pop_back();
                    onstk[v] = 0;
                }
            }
        }
        onstk[u] = 0;
        stk.pop_back();
        return false;
    }
}

int solve() {
    // find a match
    for (int i=0; i<n; i+=2){
        match[i] = i+1;
        match[i+1] = i;
    }
    while (true){
        int found = 0;
        for (int i=0; i<n; i++){
            dis[i] = onstk[i] = 0;
        }
        for (int i=0; i<n; i++){
            stk.clear();
            if (!onstk[i] && SPFA(i)){
                found = 1;
                while (SZ(stk)>=2){
                    int u = stk.back(); stk.pop_back();
                    int v = stk.back(); stk.pop_back();
                    match[u] = v;
                    match[v] = u;
                }
            }
            if (!found) break;
        }
        int ret = 0;
        for (int i=0; i<n; i++)
            ret += edge[i][match[i]];
        return ret>>1;
    }
}
} graph;

```

## 4.5 Flow Models

- Maximum/Minimum flow with lower/upper bound from  $s$  to  $t$ 
  - Construct super source  $S$  and sink  $T$
  - For each edge  $(x, y, l, u)$ , connect  $x \rightarrow y$  with capacity  $u - l$
  - For each vertex  $v$ , denote  $in(v)$  as the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds
  - If  $in(v) > 0$ , connect  $S \rightarrow v$  with capacity  $in(v)$ , otherwise, connect  $v \rightarrow T$  with capacity  $-in(v)$ 
    - To maximize, connect  $t \rightarrow s$  with capacity  $\infty$ , and let  $f$  be the maximum flow from  $S$  to  $T$ . If  $f \neq \sum_{v \in V, in(v) > 0} in(v)$ , there's no solution. Otherwise, the maximum flow from  $s$  to  $t$  is the answer.
    - To minimize, let  $f$  be the maximum flow from  $S$  to  $T$ . Connect  $t \rightarrow s$  with capacity  $\infty$  and let the flow from  $S$  to  $T$  be  $f'$ . If  $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$ , there's no solution. Otherwise,  $f'$  is the answer.
  - The solution of each edge  $e$  is  $l_e + f_e$ , where  $f_e$  corresponds to the flow on the graph
- Construct minimum vertex cover from maximum matching  $M$  on bipartite graph  $(X, Y)$ 
  - Redirect every edge  $(y \rightarrow x \text{ if } (x, y) \in M, x \rightarrow y \text{ otherwise})$
  - DFS from unmatched vertices in  $X$
  - $x \in X$  is chosen iff  $x$  is unvisited
  - $y \in Y$  is chosen iff  $y$  is visited
- Minimum cost cyclic flow
  - Construct super source  $S$  and sink  $T$
  - For each edge  $(x, y, c)$ , connect  $x \rightarrow y$  with  $(cost, cap) = (c, 1)$  if  $c > 0$ , otherwise connect  $y \rightarrow x$  with  $(cost, cap) = (-c, 1)$
  - For each edge with  $c < 0$ , sum these cost as  $K$ , then increase  $d(y)$  by 1, decrease  $d(x)$  by 1
  - For each vertex  $v$  with  $d(v) > 0$ , connect  $S \rightarrow v$  with  $(cost, cap) = (0, d(v))$
  - For each vertex  $v$  with  $d(v) < 0$ , connect  $v \rightarrow T$  with  $(cost, cap) = (0, -d(v))$
  - Flow from  $S$  to  $T$ , the answer is the cost of the flow  $C + K$
- Maximum density induced subgraph
  - Binary search on answer, suppose we're checking answer  $T$
  - Construct a max flow model, let  $K$  be the sum of all weights
  - Connect source  $s \rightarrow v, v \in G$  with capacity  $K$
  - For each edge  $(u, v, w)$  in  $G$ , connect  $u \rightarrow v$  and  $v \rightarrow u$  with capacity  $w$
  - For  $v \in G$ , connect it with sink  $v \rightarrow t$  with capacity  $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
  - $T$  is a valid answer if the maximum flow  $f < K|V|$

## 4.6 Dinic

```
class Dinic{
private:
    using CapT = int64_t;
    struct Edge{
        int to, rev;
        CapT cap;
    };
    int n, st, ed;
    vector<vector<Edge>> G;
    vector<int> lv;
    bool BFS(){
        fill(lv.begin(), lv.end(), -1);
        queue<int> bfs;
        bfs.push(st);
        lv[st] = 0;
        while(!bfs.empty()){
            int u = bfs.front(); bfs.pop();
            for(auto e: G[u]){
                if(e.cap <= 0 or lv[e.to] != -1) continue;
                lv[e.to] = lv[u] + 1;
                bfs.push(e.to);
            }
        }
        return (lv[ed] != -1);
    }
    CapT DFS(int u, CapT f){
```

```
        if(u == ed) return f;
        CapT ret = 0;
        for(auto& e: G[u]){
            if(e.cap <= 0 or lv[e.to] != lv[u]+1) continue;
            CapT nf = DFS(e.to, min(f, e.cap));
            ret += nf; e.cap -= nf; f -= nf;
            G[e.to][e.rev].cap += nf;
            if(f == 0) return ret;
        }
        if(ret == 0) lv[u] = -1;
        return ret;
    }
public:
    void init(int n_, int st_, int ed_){
        n = n_, st = st_, ed = ed_;
        G.resize(n); lv.resize(n);
        fill(G.begin(), G.end(), vector<Edge>());
    }
    void add_edge(int u, int v, CapT c){
        G[u].push_back({v, (int)G[v].size(), c});
        G[v].push_back({u, ((int)G[u].size()-1), 0});
    }
    CapT max_flow(){
        CapT ret = 0;
        while(BFS()){
            CapT f = DFS(st, numeric_limits<CapT>::max());
            ret += f;
            if(f == 0) break;
        }
        return ret;
    }
} flow;
```

## 4.7 Minimum Cost Maximum Flow

```
class MiniCostMaxiFlow{
    using CapT = int;
    using WeiT = int64_t;
    using PCW = pair<CapT, WeiT>;
    static constexpr CapT INF_CAP = 1 << 30;
    static constexpr WeiT INF_WEI = 1LL << 60;
private:
    struct Edge{
        int to, back;
        WeiT wei;
        CapT cap;
        Edge() {}
        Edge(int a, int b, WeiT c, CapT d):
            to(a), back(b), wei(c), cap(d)
        {}
    };
    int ori, edd;
    vector<vector<Edge>> G;
    vector<int> fa, wh;
    vector<bool> inq;
    vector<WeiT> dis;
    PCW SPFA(){
        fill(inq.begin(), inq.end(), false);
        fill(dis.begin(), dis.end(), INF_WEI);
        queue<int> qq; qq.push(ori);
        dis[ori] = 0;
        while(!qq.empty()){
            int u = qq.front(); qq.pop();
            inq[u] = 0;
            for(int i = 0; i < SZ(G[u]); ++i){
                Edge e = G[u][i];
                int v = e.to;
                WeiT d = e.wei;
                if(e.cap <= 0 || dis[v] <= dis[u] + d)
                    continue;
                dis[v] = dis[u] + d;
                fa[v] = u, wh[v] = i;
                if(inq[v]) continue;
                qq.push(v);
                inq[v] = 1;
            }
        }
        if(dis[edd] == INF_WEI)
            return {-1, -1};
        CapT mw = INF_CAP;
        for(int i = edd; i != ori; i = fa[i])
```

```

        mw=min(mw,G[fa[i]][wh[i]].cap);
    for (int i=edd;i!=ori;i=fa[i]){
        auto &eg=G[fa[i]][wh[i]];
        eg.cap-=mw;
        G[eg.to][eg.back].cap+=mw;
    }
    return {mw,dis[edd]};
}
public:
    void init(int a,int b,int n){
        ori=a,edd=b;
        G.clear();G.resize(n);
        fa.resize(n);wh.resize(n);
        inq.resize(n); dis.resize(n);
    }
    void add_edge(int st,int ed,WeiT w,CapT c){
        G[st].emplace_back(ed,SZ(G[ed]),w,c);
        G[ed].emplace_back(st,SZ(G[st])-1,-w,0);
    }
    PCW solve(){
        /* might modify to
        cc += ret.first * ret.second
        or
        ww += ret.first * ret.second
        */
        CapT cc=0; WeiT ww=0;
        while(true){
            PCW ret=SPFA();
            if(ret.first==-1) break;
            cc+=ret.first;
            ww+=ret.second;
        }
        return {cc,ww};
    }
} mcmf;

```

## 4.8 Global Min-Cut

```

const int maxn = 500 + 5;
int w[maxn][maxn], g[maxn];
bool v[maxn], del[maxn];

void add_edge(int x, int y, int c) {
    w[x][y] += c;
    w[y][x] += c;
}

pair<int, int> phase(int n) {
    memset(v, false, sizeof(v));
    memset(g, 0, sizeof(g));
    int s = -1, t = -1;
    while (true) {
        int c = -1;
        for (int i = 0; i < n; ++i) {
            if (del[i] || v[i]) continue;
            if (c == -1 || g[i] > g[c]) c = i;
        }
        if (c == -1) break;
        v[c] = true;
        s = t, t = c;
        for (int i = 0; i < n; ++i) {
            if (del[i] || v[i]) continue;
            g[i] += w[c][i];
        }
    }
    return make_pair(s, t);
}

int mincut(int n) {
    int cut = 1e9;
    memset(del, false, sizeof(del));
    for (int i = 0; i < n - 1; ++i) {
        int s, t; tie(s, t) = phase(n);
        del[t] = true;
        cut = min(cut, g[t]);
        for (int j = 0; j < n; ++j) {
            w[s][j] += w[t][j];
            w[j][s] += w[j][t];
        }
    }
    return cut;
}

```

```

}

```

## 5 Math

### 5.1 Prime Table

```

1002939109, 1020288887, 1028798297, 1038684299,
1041211027, 1051762951, 1058585963, 1063020809,
1147930723, 1172520109, 1183835981, 1187659051,
1241251303, 1247184097, 1255940849, 1272759031,
1287027493, 1288511629, 1294632499, 1312650799,
1868732623, 1884198443, 1884616807, 1885059541,
1909942399, 1914471137, 1923951707, 1925453197,
1979612177, 1980446837, 1989761941, 2007826547,
2008033571, 2011186739, 2039465081, 2039728567,
2093735719, 2116097521, 2123852629, 2140170259,
3148478261, 3153064147, 3176351071, 3187523093,
3196772239, 3201312913, 3203063977, 3204840059,
3210224309, 3213032591, 3217689851, 3218469083,
3219857533, 3231880427, 3235951699, 3273767923,
3276188869, 3277183181, 3282463507, 3285553889,
3319309027, 3327005333, 3327574903, 3341387953,
3373293941, 3380077549, 3380892997, 3381118801

```

### 5.2 $\lfloor \frac{n}{i} \rfloor$ Enumeration

$T_0 = 1, T_{i+1} = \lfloor \frac{n}{T_i + 1} \rfloor$

### 5.3 ax+by=gcd

```

// ax+ny = 1, ax+ny == ax == 1 (mod n)
void exgcd(lld x, lld y, lld &g, lld &a, lld &b) {
    if (y == 0) g=x, a=1, b=0;
    else
        exgcd(y, x%y, g, b, a), b-=(x/y)*a;
}

```

### 5.4 Pollard Rho

```

// does not work when n is prime
// return any non-trivial factor
llu pollard_rho(llu n){
    static auto f=[](llu x,llu k,llu m){
        return add(k,mul(x,x,m),m);
    };
    if (!(n&1)) return 2;
    mt19937 rnd(120821011);
    while(true){
        llu y=2,yy=y,x=rnd()%n,t=1;
        for(llu sz=2;t==1;sz<=1){
            for(llu i=0;i<sz;++i){
                if(t!=1)break;
                yy=f(yy,x,n);
                t=gcd(yy-y?yy-y:y-yy,n);
            }
            y=yy;
        }
        if(t!=1&&t!=n) return t;
    }
}

```

### 5.5 Pi Count (Linear Sieve)

```

static constexpr int N = 1000000 + 5;
lld pi[N];
vector<int> primes;
bool sieved[N];
lld cube_root(lld x){
    lld s=cbrt(x-static_cast<long double>(0.1));
    while(s*s*s <= x) ++s;
    return s-1;
}
lld square_root(lld x){
    lld s=sqrt(x-static_cast<long double>(0.1));
    while(s*s <= x) ++s;
    return s-1;
}
void init(){
    primes.reserve(N);
    primes.push_back(1);
    for(int i=2;i<N;i++){
        if(!sieved[i]) primes.push_back(i);
    }
}

```

```

    pi[i] = !sieved[i] + pi[i-1];
    for(int p: primes) if(p > 1) {
        if(p * i >= N) break;
        sieved[p * i] = true;
        if(p % i == 0) break;
    }
}
}

lld phi(lld m, lld n) {
    static constexpr int MM = 80000, NN = 500;
    static lld val[MM][NN];
    if(m < MM && n < NN && val[m][n]) return val[m][n]-1;
    if(n == 0) return m;
    if(primes[n] >= m) return 1;
    lld ret = phi(m, n-1) - phi(m/primes[n], n-1);
    if(m < MM && n < NN) val[m][n] = ret+1;
    return ret;
}

lld pi_count(lld);
lld P2(lld m, lld n) {
    lld sm = square_root(m), ret = 0;
    for(lld i = n+1; primes[i] <= sm; i++)
        ret += pi_count(m/primes[i]) - pi_count(primes[i]+1);
    return ret;
}

lld pi_count(lld m) {
    if(m < N) return pi[m];
    lld n = pi_count(cube_root(m));
    return phi(m, n) + n - 1 - P2(m, n);
}

```

## 5.6 Range Sieve

```

const int MAX_SQRT_B = 50000;
const int MAX_L = 200000 + 5;

bool is_prime_small[MAX_SQRT_B];
bool is_prime[MAX_L];

void sieve(lld l, lld r){
    // [L, r)
    for(lld i=2; i*i<r; i++) is_prime_small[i] = true;
    for(lld i=1; i<r; i++) is_prime[i-1] = true;
    if(l==1) is_prime[0] = false;
    for(lld i=2; i*i<r; i++){
        if(!is_prime_small[i]) continue;
        for(lld j=i*i; j<r; j+=i) is_prime_small[j]=false;
        for(lld j=std::max(2LL, (l+i-1)/i)*i; j<r; j+=i)
            is_prime[j-1]=false;
    }
}

```

## 5.7 Miller Rabin

```

bool isprime(llu x){
    static llm magic[]={2,325,9375,28178,\
        450775,9780504,1795265022};
    static auto witn=[](llu a, llm u, llm n, int t){
        a = mpow(a, u, n);
        if (!a) return 0;
        while(t--){
            llm a2=mul(a, a, n);
            if(a2==1 && a!=1 && a!=n-1)
                return 1;
            a = a2;
        }
        return a!=1;
    };
    if(x<2) return 0;
    if(!(x&1)) return x==2;
    llm x1=x-1; int t=0;
    while(!(x1&1)) x1>>=1, t++;
    for(llm m: magic)
        if(witn(m, x1, x, t))
            return 0;
    return 1;
}

```

## 5.8 Inverse Element

```

// x's inverse mod k
long long GetInv(long long x, long long k){
    // k is prime: euler_(k)=k-1
    return qPow(x, euler_phi(k)-1);
}

// if you need [1, x] (most use: [1, k-1])
void solve(int x, long long k){
    inv[1] = 1;
    for(int i=2; i<x; i++){
        inv[i] = ((long long)(k - k/i) * inv[k % i]) % k;
    }
}

```

## 5.9 Euler Phi Function

```

/*
    extended euler:
    a^b mod p
    if gcd(a, p)==1: a^(b%phi(p))
    elif b < phi(p): a^b mod p
    else a^(b%phi(p) + phi(p))
*/
lld euler_phi(int x){
    lld r=1;
    for(int i=2; i*i<=x; ++i){
        if(x%i==0){
            x/=i;
            r*=(i-1);
            while(x%i==0){
                x/=i;
                r*=i;
            }
        }
    }
    if(x>1) r*=x-1;
    return r;
}

vector<int> primes;
bool notprime[N];
lld phi[N];
void euler_sieve(int n){
    for(int i=2; i<n; i++){
        if(!notprime[i]){
            primes.push_back(i);
            phi[i] = i-1;
        }
        for(auto j: primes){
            if(i*j >= n) break;
            notprime[i*j] = true;
            phi[i*j] = phi[i] * phi[j];
            if(i % j == 0){
                phi[i*j] = phi[i] * j;
                break;
            }
        }
    }
}

```

## 5.10 Gauss Elimination

```

void gauss(vector<vector<double>> &d) {
    int n = d.size(), m = d[0].size();
    for (int i = 0; i < m; ++i) {
        int p = -1;
        for (int j = i; j < n; ++j) {
            if (fabs(d[j][i]) < eps) continue;
            if (p == -1 || fabs(d[j][i]) > fabs(d[p][i])) p=j;
        }
        if (p == -1) continue;
        for (int j = 0; j < m; ++j) swap(d[p][j], d[i][j]);
        for (int j = 0; j < n; ++j) {
            if (i == j) continue;
            double z = d[j][i] / d[i][i];
            for (int k = 0; k < m; ++k) d[j][k] -= z*d[i][k];
        }
    }
}

```

## 5.11 Fast Fourier Transform

```

/*
    polynomial multiply:
    DFT(a, len); DFT(b, len);
    for(int i=0;i<len;i++) c[i] = a[i]*b[i];
    iDFT(c, len);
    (len must be 2^k and >= 2*(max(a, b)))
    Hand written Cplx would be 2x faster
*/
Cplx omega[2][N];
void init_omega(int n) {
    static constexpr llf PI=acos(-1);
    const llf arg=(PI+PI)/n;
    for(int i=0;i<n;++i)
        omega[0][i]={cos(arg*i),sin(arg*i)};
    for(int i=0;i<n;++i)
        omega[1][i]=conj(omega[0][i]);
}
void tran(Cplx arr[],int n,Cplx omg[]) {
    for(int i=0,j=0;i<n;++i){
        if(i>j)swap(arr[i],arr[j]);
        for(int l=n>>1;(j^=1)<1;l>>=1);
    }
    for (int l=2;l<=n;l<=1){
        int m=l>>1;
        for(auto p=arr;p!=arr+n;p+=1){
            for(int i=0;i<m;++i){
                Cplx t=omg[n/l*i]*p[m+i];
                p[m+i]=p[i]-t;
                p[i]+=t;
            }
        }
    }
}
void DFT(Cplx arr[],int n){
    tran(arr,n,omega[0]);
}
void iDFT(Cplx arr[],int n){
    tran(arr,n,omega[1]);
    for(int i=0;i<n;++i)arr[i]/=n;
}

```

## 5.12 High Speed Linear Recurrence

```

#define mod 998244353
const int N=1000010;
int n,k,m,f[N],h[N],a[N],b[N],ib[N];
int pw(int x,int y){
    int re=1;
    if(y<0)y+=mod-1;
    while(y){
        if(y&1)re=(ll)re*x%mod;
        y>>=1;x=(ll)x*x%mod;
    }
    return re;
}
void inc(int&x,int y){x+=y;if(x>=mod)x-=mod;}
namespace poly{
    const int G=3;
    int rev[N],L;
    void ntt(int*A,int len,int f){
        for(L=0;(1<L)<len;L+=1);
        for(int i=0;i<len;++i){
            rev[i]=(rev[i>>1]>>1)|((i&1)<<(L-1));
            if(i<rev[i])swap(A[i],A[rev[i]]);
        }
        for(int i=1;i<len;i<=1){
            int wn=pw(G,f*(mod-1)/(i<<1));
            for(int j=0;j<len;j+=i<<1){
                int w=1;
                for(int k=0;k<i;++k,w=(ll)w*wn%mod){
                    int x=A[j+k],y=(ll)w*A[j+k+i]%mod;
                    A[j+k]=(x+y)%mod,A[j+k+i]=(x-y+mod)%mod;
                }
            }
        }
        if(!f){
            int iv=pw(len,mod-2);
            for(int i=0;i<len;++i)A[i]=(ll)A[i]*iv%mod;
        }
    }
    void cls(int*A,int l,int r){

```

```

        for(int i=l;i<r;++i)A[i]=0;}
    void cpy(int*A,int*B,int l){
        for(int i=0;i<l;++i)A[i]=B[i];}
    void inv(int*A,int*B,int l){
        if(l==1){B[0]=pw(A[0],mod-2);return;}
        static int t[N];
        int len=l<<1;
        inv(A,B,l>>1);
        cpy(t,A,l);cls(t,l,len);
        ntt(t,len,1);ntt(B,len,1);
        for(int i=0;i<len;++i)
            B[i]=(ll)B[i]*(2-(ll)t[i]*B[i]%mod+mod)%mod;
        ntt(B,len,-1);cls(B,l,len);
    }
    void pmod(int*A){
        static int t[N];
        int l=k+1,len=1;while(len<=(k<<1))len<=1;
        cpy(t,A,(k<<1)+1);
        reverse(t,t+(k<<1)+1);
        cls(t,l,len);
        ntt(t,len,1);
        for(int i=0;i<len;++i)t[i]=(ll)t[i]*ib[i]%mod;
        ntt(t,len,-1);
        cls(t,l,len);
        reverse(t,t+1);
        ntt(t,len,1);
        for(int i=0;i<len;++i)t[i]=(ll)t[i]*b[i]%mod;
        ntt(t,len,-1);
        cls(t,l,len);
        for(int i=0;i<k;++i)A[i]=(A[i]-t[i]+mod)%mod;
        cls(A,k,len);
    }
    void pow(int*A,int n){
        if(n==1){cls(A,0,k+1);A[1]=1;return;}
        pow(A,n>>1);
        int len=1;while(len<=(k<<1))len<=1;
        ntt(A,len,1);
        for(int i=0;i<len;++i)A[i]=(ll)A[i]*A[i]%mod;
        ntt(A,len,-1);
        pmod(A);
        if(n&1){
            for(int i=k;i;--i)A[i]=A[i-1];A[0]=0;
            pmod(A);
        }
    }
}
int main(){
    n=rd();k=rd();
    for(int i=1;i<=k;++i)f[i]=(mod+rd())%mod;
    for(int i=0;i<k;++i)h[i]=(mod+rd())%mod;
    for(int i=a[k]=b[k]=1;i<=k;++i)
        a[k-i]=b[k-i]=(mod-f[i])%mod;
    int len=1;while(len<=(k<<1))len<=1;
    reverse(a,a+k+1);
    poly::inv(a,ib,len);
    poly::cls(ib,k+1,len);
    poly::ntt(b,len,1);
    poly::ntt(ib,len,1);
    poly::pow(a,n);
    int ans=0;
    for(int i=0;i<k;++i)inc(ans,(ll)a[i]*h[i]%mod);
    printf("%d\n",ans);
    return 0;
}

```

## 5.13 Chinese Remainder

```

lld crt(lld ans[], lld pri[], int n){
    lld M = 1;
    for(int i=0;i<n;i++) M *= pri[i];
    lld ret = 0;
    for(int i=0;i<n;i++){
        lld inv = (gcd(M/pri[i], pri[i]).first + pri[i])%
            pri[i];
        ret += (ans[i]*(M/pri[i])%M * inv)%M;
        ret %= M;
    }
    return ret;
}
/*
Another:

```



```

x = a1 % m1
x = a2 % m2
g = gcd(m1, m2)
assert((a1-a2)%g==0)
[p, q] = exgcd(m2/g, m1/g)
return a2+m2*(p*(a1-a2)/g)
0 <= x < lcm(m1, m2)
*/

```

## 5.14 Berlekamp Massey

```

// x: 1-base, p[]: 0-base
template<size_t N>
vector<llf> BM(llf x[N], size_t n){
    size_t f[N]={0}, t=0; llf d[N];
    vector<llf> p[N];
    for(size_t i=1, b=0; i<=n; ++i) {
        for(size_t j=0; j<p[t].size(); ++j)
            d[i] += x[i-j-1]*p[t][j];
        if(abs(d[i]-x[i])<=EPS) continue;
        f[t]=i; if(!t){p[++t].resize(i); continue;}
        vector<llf> cur(i-f[b]-1);
        llf k=-d[i]/d[f[b]]; cur.PB(-k);
        for(size_t j=0; j<p[b].size(); j++)
            cur.PB(p[b][j]*k);
        if(cur.size()<p[t].size()) cur.resize(p[t].size());
        for(size_t j=0; j<p[t].size(); j++) cur[j] += p[t][j];
        if(i-f[b]+p[b].size()>=p[t].size()) b=t;
        p[++t]=cur;
    }
    return p[t];
}

```

## 5.15 NTT

```

// Remember coefficient are mod P
/* p=a*2^n+1
n    2^n    p    a    root
16   65536   65537   1    3
20   1048576 7340033 7    3 */
// (must be 2^k)
template<LL P, LL root, int MAXN>
struct NTT{
    static LL bigmod(LL a, LL b) {
        LL res = 1;
        for (LL bs = a; b; b >= 1, bs = (bs * bs) % P)
            if(b&1) res=(res*bs)%P;
        return res;
    }
    static LL inv(LL a, LL b) {
        if(a==1) return 1;
        return (((LL)(a-inv(b%a,a))*b+1)/a)%b;
    }
    LL omega[MAXN+1];
    NTT() {
        omega[0] = 1;
        LL r = bigmod(root, (P-1)/MAXN);
        for (int i=1; i<=MAXN; i++)
            omega[i] = (omega[i-1]*r)%P;
    }
    // n must be 2^k
    void tran(int n, LL a[], bool inv_ntt=false){
        int basic = MAXN / n, theta = basic;
        for (int m = n; m >= 2; m >= 1) {
            int mh = m >> 1;
            for (int i = 0; i < mh; i++) {
                LL w = omega[i*theta%MAXN];
                for (int j = i; j < n; j += m) {
                    int k = j + mh;
                    LL x = a[j] - a[k];
                    if (x < 0) x += P;
                    a[j] += a[k];
                    if (a[j] > P) a[j] -= P;
                    a[k] = (w * x) % P;
                }
            }
            theta = (theta * 2) % MAXN;
        }
        int i = 0;
        for (int j = 1; j < n - 1; j++) {

```

```

            for (int k = n >> 1; k > (i ^= k); k >= 1);
            if (j < i) swap(a[i], a[j]);
        }
        if (inv_ntt) {
            LL ni = inv(n,P);
            reverse(a+1, a+n);
            for (i = 0; i < n; i++)
                a[i] = (a[i] * ni) % P;
        }
    }
};
const LL P=2013265921, root=31;
const int MAXN=4194304;
NTT<P, root, MAXN> ntt;

```

## 5.16 Polynomial Sqrt

```

const int mod = (119 << 23) + 1;
int inv_temp[400010];
void poly_inv(int *f, int *inv, int len) {
    int *inv_t = inv_temp, *g = inv;
    g[0] = get_inv(f[0]);
    for (int l = 2; l <= len; l <= 1, swap(g, inv_t)) {
        for (int i = 0; i < l; i++) {
            inv_t[i] = f[i];
            g[i+1] = inv_t[i+1] = 0;
        }
        exec_ntt(inv_t, l << 1, 1);
        exec_ntt(g, l << 1, 1);
        for (int i = 0; i < 2 * l; i++)
            inv_t[i] = (ll)inv_t[i] * g[i] % mod;
        for (int i = 0; i < 2 * l; i++) {
            if (inv_t[i])
                inv_t[i] = mod - inv_t[i];
            inv_t[i] += 2, inv_t[i] %= mod;
        }
        for (int i = 0; i < 2 * l; i++)
            inv_t[i] = (ll)inv_t[i] * g[i] % mod;
        exec_ntt(inv_t, l << 1, -1);
        for (int i = 0; i < l; i++)
            inv_t[i+1] = 0;
    }
    for (int i = 0; i < len; i++)
        inv[i] = g[i];
}
int sqrt_temp[400010], inv_t[400010];
void poly_sqrt(int *f, int *sqrt_pol, int len) {
    int *g = sqrt_pol, *t = sqrt_temp, inv2 = get_inv(2);
    g[0] = 1;
    for (int l = 2; l <= len; l <= 1, swap(g, t)) {
        for (int i = 0; i < l; i++)
            t[i] = f[i], t[i+1] = g[i+1] = inv_t[i] = 0;
        poly_inv(g, inv_t, l);
        for (int i = 1; i < 2 * l; i++)
            inv_t[i] = 0;
        exec_ntt(g, l << 1, 1);
        exec_ntt(inv_t, l << 1, 1);
        exec_ntt(t, l << 1, 1);
        for (int i = 0; i < (l << 1); i++)
            t[i] = (ll)inv2*(g[i]+(ll)t[i]*inv_t[i] % mod)%mod;
        exec_ntt(t, l << 1, -1);
        for (int i = 0; i < l; i++)
            t[i+1] = 0;
    }
    for (int i = 0; i < len; i++)
        sqrt_pol[i] = g[i];
}
int c[400010], inv[400010], sqrt_pol[400010];
int main(){
    int n, m, x;
    scanf("%d%d", &n, &m);
    for (int i = 0; i < n; i++)
    {
        scanf("%d", &x);
        if (x <= m)
            c[x] = mod - 4;
    }
    c[0]++, c[0] %= mod;
    int len = 1;
    while (len <= m) len <= 1;
    poly_sqrt(c, sqrt_pol, len);
}

```

```

sqrt_pol[0]++, sqrt_pol[0] %= mod;
poly_inv(sqrt_pol, inv, len);
for (int i = 1; i <= m; i++)
    printf("%d\n", (inv[i] + inv[i]) % mod);
puts("");
return 0;
}

```

## 5.17 Polynomial Division

```

VI inverse(const VI &v, int n) {
    VI q(1, fpow(v[0], mod - 2));
    for (int i = 2; i <= n; i <= 1) {
        VI fv(v.begin(), v.begin() + i);
        VI fq(q.begin(), q.end());
        fv.resize(2 * i), fq.resize(2 * i);
        ntt(fv, 2 * i), ntt(fq, 2 * i);
        for (int j = 0; j < 2 * i; ++j)
            fv[j] = fv[j]*111*fq[j]%mod*fq[j]%mod;
        intt(fv, 2 * i);
        VI res(i);
        for (int j = 0; j < i; ++j) {
            res[j] = mod - fv[j];
            if (j < (i>>1)) (res[j] += 2*q[j]%mod) %= mod;
        }
        q = res;
    }
    return q;
}
VI divide(const VI &a, const VI &b) {
    // Leading zero should be trimmed
    int n = (int)a.size(), m = (int)b.size();
    int k = 2;
    while (k < n - m + 1) k <= 1;
    VI ra(k), rb(k);
    for (int i = 0; i < min(n, k); ++i) ra[i] = a[n-i-1];
    for (int i = 0; i < min(m, k); ++i) rb[i] = b[m-i-1];
    VI rbi = inverse(rb, k);
    VI res = convolution(rbi, ra);
    res.resize(n - m + 1);
    reverse(res.begin(), res.end());
    return res;
}

```

## 5.18 FWT

```

/* xor convolution:
* x = (x0,x1) , y = (y0,y1)
* z = ( x0y0 + x1y1 , x0y1 + x1y0 )
* =>
* x' = ( x0+x1 , x0-x1 ) , y' = ( y0+y1 , y0-y1 )
* z' = ( ( x0+x1 )( y0+y1 ) , ( x0-x1 )( y0-y1 ) )
* z = (1/2) * z''
* or convolution:
* x = (x0, x0+x1), inv = (x0, x1-x0) w/o final div
* and convolution:
* x = (x0+x1, x1), inv = (x0-x1, x1) w/o final div */
const LL MOD = 1e9+7;
inline void fwt( LL x[ MAXN ] , int N , bool inv=0 ) {
    for( int d = 1 ; d < N ; d <= 1 ) {
        int d2 = d<<1;
        for( int s = 0 ; s < N ; s += d2 )
            for( int i = s , j = s+d ; i < s+d ; i++, j++ ){
                LL ta = x[ i ] , tb = x[ j ];
                x[ i ] = ta+tb;
                x[ j ] = ta-tb;
                if( x[ i ] >= MOD ) x[ i ] -= MOD;
                if( x[ j ] < 0 ) x[ j ] += MOD;
            }
    }
    if( inv )
        for( int i = 0 ; i < N ; i++ ) {
            x[ i ] *= inv( N , MOD );
            x[ i ] %= MOD;
        }
}

```

## 5.19 DiscreteLog

```

// Baby-step Giant-step Algorithm
l1d BSGS(l1d P, l1d B, l1d N) {
    // find B^L = N mod P
    unordered_map<l1d, int> R;
    l1d sq = (l1d)sqrt(P);
    l1d t = 1;
    for (int i = 0; i < sq; i++) {
        if (t == N) return i;
        if (!R.count(t)) R[t] = i;
        t = (t * B) % P;
    }
    l1d f = inverse(t, P);
    for(int i=0;i<=sq+1;i++) {
        if (R.count(N))
            return i * sq + R[N];
        N = (N * f) % P;
    }
    return -1;
}

```

## 5.20 Quadratic residue

```

struct Status{
    l1 x,y;
};
l1 w;
Status mult(const Status& a,const Status& b,l1 mod){
    Status res;
    res.x=(a.x*b.x+a.y*b.y%mod*w)%mod;
    res.y=(a.x*b.y+a.y*b.x)%mod;
    return res;
}
inline Status qpow(Status _base,l1 _pow,l1 _mod){
    Status res;
    res.x=1,res.y=0;
    while(_pow>0){
        if(_pow&1) res=mult(res,_base,_mod);
        _base=mult(_base,_base,_mod);
        _pow>>=1;
    }
    return res;
}
inline l1 check(l1 x,l1 p){
    return qpow_mod(x,(p-1)>>1,p);
}
inline l1 get_root(l1 n,l1 p){
    if(p==2) return 1;
    if(check(n,p)==p-1) return -1;
    l1 a;
    while(true){
        a=rand()%p;
        w=((a*a-n)%p+p)%p;
        if(check(w,p)==p-1) break;
    }
    Status res;
    res.x=a;
    res.y=1;
    res=qpow(res,(p+1)>>1,p);
    return res.x;
}

```

## 5.21 De-Bruijn

```

int res[maxn], aux[maxn], sz;
void db(int t, int p, int n, int k) {
    if (t > n) {
        if (n % p == 0)
            for (int i = 1; i <= p; ++i)
                res[sz++] = aux[i];
    } else {
        aux[t] = aux[t - p];
        db(t + 1, p, n, k);
        for (int i = aux[t - p] + 1; i < k; ++i) {
            aux[t] = i;
            db(t + 1, t, n, k);
        }
    }
}
int de_bruijn(int k, int n) {
    // return cyclic string of len k^n s.t. every string
}

```

```
// of Len n using k char appears as a substring.
if (k == 1) {
    res[0] = 0;
    return 1;
}
for (int i = 0; i < k * n; i++) aux[i] = 0;
sz = 0;
db(1, 1, n, k);
return sz;
}
```

## 5.22 Simplex Construction

Standard form: maximize  $\sum_{1 \leq i \leq n} c_i x_i$  such that for all  $1 \leq j \leq m$ ,  $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$  and  $x_i \geq 0$  for all  $1 \leq i \leq n$ .

1. In case of minimization, let  $c'_i = -c_i$
2.  $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j \rightarrow \sum_{1 \leq i \leq n} -A_{ji} x_i \leq -b_j$
3.  $\sum_{1 \leq i \leq n} A_{ji} x_i = b_j$ 
  - $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$
  - $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j$
4. If  $x_i$  has no lower bound, replace  $x_i$  with  $x_i - x'_i$

## 5.23 Simplex

```
namespace simplex {
// maximize c^T x under Ax <= B
// return vector<double>(n, -inf) if the solution doesn't exist
// return vector<double>(n, +inf) if the solution is unbounded
using VD = vector<double>;
using VVD = vector<vector<double>>;
const double eps = 1e-9;
const double inf = 1e+9;
int n, m;
VVD d;
vector<int> p, q;
void pivot(int r, int s) {
    double inv = 1.0 / d[r][s];
    for (int i = 0; i < m + 2; ++i) {
        for (int j = 0; j < n + 2; ++j) {
            if (i != r && j != s)
                d[i][j] -= d[r][j] * d[i][s] * inv;
        }
    }
    for (int i = 0; i < m + 2; ++i) if (i != r) d[i][s] *= -inv;
    for (int j = 0; j < n + 2; ++j) if (j != s) d[r][j] *= +inv;
    d[r][s] = inv;
    swap(p[r], q[s]);
}
bool phase(int z) {
    int x = m + z;
    while (true) {
        int s = -1;
        for (int i = 0; i <= n; ++i) {
            if (!z && q[i] == -1) continue;
            if (s == -1 || d[x][i] < d[x][s]) s = i;
        }
        if (d[x][s] > -eps) return true;
        int r = -1;
        for (int i = 0; i < m; ++i) {
            if (d[i][s] < eps) continue;
            if (r == -1 || \
                d[i][n+1]/d[i][s] < d[r][n+1]/d[r][s]) r = i;
        }
        if (r == -1) return false;
        pivot(r, s);
    }
}
VD solve(const VVD &a, const VD &b, const VD &c) {
    m = b.size(), n = c.size();
    d = VVD(m + 2, VD(n + 2));
    for (int i = 0; i < m; ++i) {
        for (int j = 0; j < n; ++j) d[i][j] = a[i][j];
    }
    p.resize(m), q.resize(n + 1);
}
```

```
for (int i = 0; i < m; ++i)
    p[i] = n + i, d[i][n] = -1, d[i][n + 1] = b[i];
for (int i = 0; i < n; ++i) q[i] = i, d[m][i] = -c[i];
q[n] = -1, d[m + 1][n] = 1;
int r = 0;
for (int i = 1; i < m; ++i)
    if (d[i][n + 1] < d[r][n + 1]) r = i;
if (d[r][n + 1] < -eps) {
    pivot(r, n);
    if (!phase(1) || d[m + 1][n + 1] < -eps)
        return VD(n, -inf);
    for (int i = 0; i < m; ++i) if (p[i] == -1) {
        int s = min_element(d[i].begin(), d[i].end() - 1)
            - d[i].begin();
        pivot(i, s);
    }
}
if (!phase(0)) return VD(n, inf);
VD x(n);
for (int i = 0; i < m; ++i)
    if (p[i] < n) x[p[i]] = d[i][n + 1];
return x;
}}
```

## 6 Geometry

### 6.1 Point Class

```
template<typename T>
struct Point {
    typedef long double llf;
    static constexpr llf EPS = 1e-8;
    T x, y;
    Point(T _x=0, T _y=0): x(_x), y(_y){}
    template<typename T2>
    Point(const Point<T2>& a): x(a.x), y(a.y){}
    inline llf theta() const {
        return atan2((llf)y, (llf)x);
    }
    inline llf dis() const {
        return hypot((llf)x, (llf)y);
    }
    inline llf dis(const Point& o) const {
        return hypot((llf)(x-o.x), (llf)(y-o.y));
    }
    Point operator-(const Point& o) const {
        return Point(x-o.x, y-o.y);
    }
    Point operator+=(const Point& o) {
        x+=o.x, y+=o.y;
        return *this;
    }
    Point operator+(const Point& o) const {
        return Point(x+o.x, y+o.y);
    }
    Point operator+=(const Point& o) {
        x+=o.x, y+=o.y;
        return *this;
    }
    Point operator*(const T& k) const {
        return Point(x*k, y*k);
    }
    Point operator*=(const T& k) {
        x*=k, y*=k;
        return *this;
    }
    Point operator/(const T& k) const {
        return Point(x/k, y/k);
    }
    Point operator/=(const T& k) {
        x/=k, y/=k;
        return *this;
    }
    Point operator-() const {
        return Point(-x, -y);
    }
    Point rot90() const {
        return Point(-y, x);
    }
};
template<typename T2>
```

```

bool in(const Circle<T2>& a) const {
    /* Add struct Circle at top */
    return a.o.dis(*this)+EPS <= a.r;
}
bool equal(const Point& o, true_type) const {
    return fabs(x-o.x) < EPS and fabs(y-o.y) < EPS;
}
bool equal(const Point& o, false_type) const {
    return tie(x, y) == tie(o.x, o.y);
}
bool operator==(const Point& o) const {
    return equal(o, is_floating_point<T>());
}
bool operator!=(const Point& o) const {
    return !(*this == o);
}
bool operator<(const Point& o) const {
    return theta() < o.theta();
    // sort like what pairs did
    // if(is_floating_point<T>()) return fabs(x-o.x)<
    EPS?y<o.y:x<o.x;
    // else return tie(x, y) < tie(o.x, o.y);
}
friend inline T cross(const Point& a, const Point& b)
{
    return a.x*b.y - b.x*a.y;
}
friend inline T dot(const Point& a, const Point &b){
    return a.x*b.x + a.y*b.y;
}
friend ostream& operator<<(ostream& ss, const Point&
o){
    ss<<"("<<o.x<<"", "<<o.y<<"")";
    return ss;
}
};

```

## 6.2 Circle Class

```

template<typename T>
struct Circle{
    static constexpr llf EPS = 1e-8;
    Point<T> o; T r;
    vector<Point<llf>> operator&(const Circle& aa) const{
        // https://www.cnblogs.com/wangzming/p/8338142.html
        llf d=o.dis(aa.o);
        if(d > r+aa.r+EPS or d < fabs(r-aa.r)-EPS) return
        {};
        llf dt = (r*r - aa.r*aa.r)/d, d1 = (d+dt)/2;
        Point<llf> dir = (aa.o-o); dir /= d;
        Point<llf> pcrs = dir*d1 + o;
        dt=sqrt(max(0.0L, r*r - d1*d1)), dir=dir.rot90();
        return {pcrs + dir*dt, pcrs - dir*dt};
    }
};

```

## 6.3 Triangle Circumcentre

```

template<typename T>
Circle<llf> get_circum(const Point<T>& a, const Point<T>
>& b, const Point<T>& c){
    llf a1 = a.x-b.x;
    llf b1 = a.y-b.y;
    llf c1 = (a.x+b.x)/2 * a1 + (a.y+b.y)/2 * b1;
    llf a2 = a.x-c.x;
    llf b2 = a.y-c.y;
    llf c2 = (a.x+c.x)/2 * a2 + (a.y+c.y)/2 * b2;

    Circle<llf> cc;
    cc.o.x = (c1*b2-b1*c2)/(a1*b2-b1*a2);
    cc.o.y = (a1*c2-c1*a2)/(a1*b2-b1*a2);
    cc.r = hypot(cc.o.x-a.x, cc.o.y-a.y);
    return cc;
}

```

## 6.4 2D Convex Hull

```

template<typename T>
class ConvexHull_2D{

```

```

private:
    typedef Point<T> PT;
    vector<PT> dots;
    struct myhash{
        uint64_t operator()(const PT& a) const {
            uint64_t xx=0, yy=0;
            memcpy(&xx, &a.x, sizeof(a.x));
            memcpy(&yy, &a.y, sizeof(a.y));
            uint64_t ret = xx*17+yy*31;
            ret = (ret ^ (ret >> 16))*0x9E3779B1;
            ret = (ret ^ (ret >> 13))*0xC2B2AE35;
            ret = ret ^ xx;
            return (ret ^ (ret << 3)) * yy;
        }
    };
    unordered_set<PT, myhash> in_hull;
public:
    inline void init(){in_hull.clear();dots.clear();}
    void insert(const PT& x){dots.PB(x);}
    void solve(){
        sort(ALL(dots), [](const PT& a, const PT& b){
            return tie(a.x, a.y) < tie(b.x, b.y);
        });
        vector<PT> stk(SZ(dots)<<1);
        int top = 0;
        for(auto p: dots){
            while(top >= 2 and cross(p-stk[top-2], stk[top
-1]-stk[top-2]) <= 0)
                top--;
            stk[top++] = p;
        }
        for(int i=SZ(dots)-2, t = top+1; i>=0; i--){
            while(top >= t and cross(dots[i]-stk[top-2], stk[
top-1]-stk[top-2]) <= 0)
                top--;
            stk[top++] = dots[i];
        }
        stk.resize(top-1);
        swap(stk, dots);
        for(auto i: stk) in_hull.insert(i);
    }
    vector<PT> get(){return dots;}
    inline bool in_it(const PT& x){
        return in_hull.find(x)!=in_hull.end();
    }
};

```

## 6.5 2D Farthest Pair

```

// stk is from convex hull
n = (int)(stk.size());
int pos = 1, ans = 0; stk.push_back(arr[0]);
for(int i=0; i<n; i++){
    while(abs(cross(stk[i+1]-stk[i], stk[(pos+1)%n]-stk[i
]))\
    > abs(cross(stk[i+1]-stk[i], stk[pos]-stk[i]))) pos
    = (pos+1)%n;
    ans = max({ans, dis(stk[i], stk[pos]), dis(stk[i+1],
stk[pos])});
}

```

## 6.6 2D Closest Pair

```

struct Point{
    llf x, y;
    llf dis;
} arr[N];

inline llf get_dis(Point a, Point b){
    return hypot(a.x-b.x, a.y-b.y);
}

llf solve(){
    int cur = rand()%n;
    for(int i=0; i<n; i++) arr[i].dis = get_dis(arr[cur],
arr[i]);
    sort(arr, arr+n, [](Point a, Point b){return a.dis <
b.dis;});
    llf ans = 1e50;
    for(int i=0; i<n; i++){

```

```

    for(int j=i+1;j<n;j++){
        if(arr[j].dis - arr[i].dis > ans) break;
        ans = min(ans, get_dis(arr[i], arr[j]));
    }
    return ans;
}

```

## 6.7 SimulateAnnealing

```

llf anneal() {
    mt19937 rnd_engine( seed );
    uniform_real_distribution< llf > rnd( 0, 1 );
    const llf dT = 0.001;
    // Argument p
    llf S_cur = calc( p ), S_best = S_cur;
    for ( llf T = 2000 ; T > EPS ; T -= dT ) {
        // Modify p to p_prime
        const llf S_prime = calc( p_prime );
        const llf delta_c = S_prime - S_cur;
        llf prob = min( ( llf ) 1, exp( -delta_c / T ) );
        if ( rnd( rnd_engine ) <= prob ) {
            S_cur = S_prime;
            p = p_prime;
        }
        if ( S_prime < S_best ) {
            S_best = S_prime;
            p_best = p_prime;
        }
    }
    return S_best;
}

```

## 6.8 Half Plane Intersection

```

inline int dcmp ( double x ) {
    if( fabs( x ) < eps ) return 0;
    return x > 0 ? 1 : -1;
}
struct Line {
    Point st, ed;
    double ang;
    Line( Point _st=Point(), Point _ed=Point()):
        st(_st),ed(_ed),ang(atan2(_ed.y-_st.y,_ed.x-_st.x))
    {}
    inline bool operator< ( const Line& rhs ) const {
        if(dcmp( ang - rhs.ang ) != 0) return ang < rhs.ang;
        return dcmp( cross( st, ed, rhs.st ) ) < 0;
    }
};
// cross(pt, Line.ed-Line.st) >= 0 <-> pt in half plane
vector< Line > lines;
deque< Line > que;
deque< Point > pt;
double HPI() {
    sort( lines.begin(), lines.end() );
    que.clear();
    pt.clear();
    que.push_back( lines[ 0 ] );
    for ( int i = 1 ; i < (int)lines.size() ; i ++ ) {
        if(!dcmp(lines[i].ang - lines[i - 1].ang)) continue;
        while ( pt.size() > 0 &&
            dcmp(cross(lines[i].st,lines[i].ed,pt.back()))<0){
            pt.pop_back();
            que.pop_back();
        }
        while ( pt.size() > 0 &&
            dcmp(cross(lines[i].st,lines[i].ed,pt.front()))<0)
            {
                pt.pop_front();
                que.pop_front();
            }
        pt.push_back( get_point( que.back(), lines[ i ] ) );
        que.push_back( lines[ i ] );
    }
    while ( pt.size() > 0 &&
        dcmp(cross(que[0].st, que[0].ed, pt.back()))<0){

```

```

        que.pop_back();
        pt.pop_back();
    }
    while ( pt.size() > 0 &&
        dcmp(cross(que.back().st, que.back().ed, pt[0]))<0)
        {
            que.pop_front();
            pt.pop_front();
        }
    pt.push_back( get_point( que.front(), que.back() ) );
    vector< Point > conv;
    for ( int i = 0 ; i < (int)pt.size() ; i ++ )
        conv.push_back( pt[ i ] );
    double ret = 0;
    for ( int i = 1 ; i + 1 < (int)conv.size() ; i ++ )
        ret += abs(cross(conv[0], conv[i], conv[i + 1]));
    return ret / 2.0;
}

```

## 6.9 Ternary Search on Integer

```

int TernarySearch(int l, int r) {
    // (l, r)
    while (r - l > 1){
        int mid = (l + r)>>1;
        if (f(mid) > f(mid + 1)) r = mid;
        else l = mid;
    }
    return l+1;
}

```

## 6.10 Minimum Covering Circle

```

template<typename T>
Circle<llf> MinCircleCover(const vector<Point<T>>& pts)
{
    random_shuffle(ALL(pts));
    Circle<llf> c = {pts[0], 0};
    int n = SZ(pts);
    for(int i=0;i<n;i++){
        if(pts[i].in(c)) continue;
        c = {pts[i], 0};
        for(int j=0;j<i;j++){
            if(pts[j].in(c)) continue;
            c.o = (pts[i] + pts[j]) / 2;
            c.r = pts[i].dis(c.o);
            for(int k=0;k<j;k++){
                if(pts[k].in(c)) continue;
                c = get_circum(pts[i], pts[j], pts[k]);
            }
        }
    }
    return c;
}

```

## 6.11 KDTree (Nearest Point)

```

const int MXN = 100005;
struct KDTree {
    struct Node {
        int x,y,x1,y1,x2,y2;
        int id,f;
        Node *L, *R;
    }tree[MXN];
    int n;
    Node *root;
    LL dis2(int x1, int y1, int x2, int y2) {
        LL dx = x1-x2;
        LL dy = y1-y2;
        return dx*dx+dy*dy;
    }
    static bool cmpx(Node& a, Node& b){ return a.x<b.x; }
    static bool cmpy(Node& a, Node& b){ return a.y<b.y; }
    void init(vector<pair<int,int>> ip) {
        n = ip.size();
        for (int i=0; i<n; i++) {
            tree[i].id = i;
            tree[i].x = ip[i].first;
            tree[i].y = ip[i].second;

```

```

    }
    root = build_tree(0, n-1, 0);
}
Node* build_tree(int L, int R, int dep) {
    if (L>R) return nullptr;
    int M = (L+R)/2;
    tree[M].f = dep%2;
    nth_element(tree+L, tree+M, tree+R+1, tree[M].f ?
        cmpy : cmpx);
    tree[M].x1 = tree[M].x2 = tree[M].x;
    tree[M].y1 = tree[M].y2 = tree[M].y;

    tree[M].L = build_tree(L, M-1, dep+1);
    if (tree[M].L) {
        tree[M].x1 = min(tree[M].x1, tree[M].L->x1);
        tree[M].x2 = max(tree[M].x2, tree[M].L->x2);
        tree[M].y1 = min(tree[M].y1, tree[M].L->y1);
        tree[M].y2 = max(tree[M].y2, tree[M].L->y2);
    }
    tree[M].R = build_tree(M+1, R, dep+1);
    if (tree[M].R) {
        tree[M].x1 = min(tree[M].x1, tree[M].R->x1);
        tree[M].x2 = max(tree[M].x2, tree[M].R->x2);
        tree[M].y1 = min(tree[M].y1, tree[M].R->y1);
        tree[M].y2 = max(tree[M].y2, tree[M].R->y2);
    }
    return tree+M;
}
int touch(Node* r, int x, int y, LL d2){
    LL dis = sqrt(d2)+1;
    if (x<r->x1-dis || x>r->x2+dis ||
        y<r->y1-dis || y>r->y2+dis)
        return 0;
    return 1;
}
void nearest(Node* r, int x, int y,
    int &mID, LL &md2){
    if (!r || !touch(r, x, y, md2)) return;
    LL d2 = dis2(r->x, r->y, x, y);
    if (d2 < md2 || (d2 == md2 && mID < r->id)) {
        mID = r->id;
        md2 = d2;
    }
    // search order depends on split dim
    if ((r->f == 0 && x < r->x) ||
        (r->f == 1 && y < r->y)) {
        nearest(r->L, x, y, mID, md2);
        nearest(r->R, x, y, mID, md2);
    } else {
        nearest(r->R, x, y, mID, md2);
        nearest(r->L, x, y, mID, md2);
    }
}
int query(int x, int y) {
    int id = 1029384756;
    LL d2 = 102938475612345678LL;
    nearest(root, x, y, id, d2);
    return id;
}
}tree;

```

## 7 Stringology

### 7.1 Hash

```

class Hash{
private:
    const int p = 127, q = 1208220623;
    int sz, prefix[N], power[N];
    inline int add(int x, int y){return x+y>=q?x+y-q:x+y;}
    inline int sub(int x, int y){return x-y<0?x-y+q:x-y;}
    inline int mul(int x, int y){return 1LL*x*y%q;}
public:
    void init(const string &x){
        sz = x.size();prefix[0]=0;power[0]=1;
        for(int i=1;i<=sz;i++)
            prefix[i]=add(mul(prefix[i-1], p), x[i-1]);
        for(int i=1;i<=sz;i++) power[i]=mul(power[i-1], p);
    }
}

```

```

int query(int l, int r){
    // 1-base (l, r)
    return sub(prefix[r], mul(prefix[l], power[r-l]));
}
};

```

### 7.2 Suffix Array

```

namespace sfxarray {
bool t[maxn * 2];
int hi[maxn], rev[maxn];
int _s[maxn * 2], sa[maxn * 2], c[maxn * 2];
int x[maxn], p[maxn], q[maxn * 2];
// sa[i]: sa[i]-th suffix is the \
// i-th lexicographically smallest suffix.
// hi[i]: longest common prefix \
// of suffix sa[i] and suffix sa[i - 1].
void pre(int *sa, int *c, int n, int z) {
    memset(sa, 0, sizeof(int) * n);
    memcpy(x, c, sizeof(int) * z);
}
void induce(int *sa, int *c, int *s, bool *t, int n, int z){
    memcpy(x + 1, c, sizeof(int) * (z - 1));
    for (int i = 0; i < n; ++i)
        if (sa[i] && !t[sa[i] - 1])
            sa[x[sa[i] - 1]++] = sa[i] - 1;
    memcpy(x, c, sizeof(int) * z);
    for (int i = n - 1; i >= 0; --i)
        if (sa[i] && t[sa[i] - 1])
            sa[--x[sa[i] - 1]] = sa[i] - 1;
}
void sais(int *s, int *sa, int *p, int *q,
    bool *t, int *c, int n, int z) {
    bool uniq = t[n - 1] = true;
    int nn=0, nmzx=-1, *nsa = sa+n, *ns=s+n, last=-1;
    memset(c, 0, sizeof(int) * z);
    for (int i = 0; i < n; ++i) uniq &= ++c[s[i]] < 2;
    for (int i = 0; i < z - 1; ++i) c[i + 1] += c[i];
    if (uniq) {
        for (int i = 0; i < n; ++i) sa[--c[s[i]]] = i;
        return;
    }
    for (int i = n - 2; i >= 0; --i)
        t[i] = (s[i]==s[i + 1] ? t[i + 1] : s[i]<s[i + 1]);
    pre(sa, c, n, z);
    for (int i = 1; i <= n - 1; ++i)
        if (t[i] && !t[i - 1])
            sa[--x[s[i]]] = p[q[i] = nn++] = i;
    induce(sa, c, s, t, n, z);
    for (int i = 0; i < n; ++i) {
        if (sa[i] && t[sa[i]] && !t[sa[i] - 1]) {
            bool neq = last < 0 || \
                memcmp(s + sa[i], s + last,
                    (p[q[sa[i]] + 1] - sa[i]) * sizeof(int));
            ns[q[last = sa[i]]] = nmzx += neq;
        }
    }
    sais(ns, nsa, p+nn, q+n, t+n, c+z, nn, nmzx+1);
    pre(sa, c, n, z);
    for (int i = nn - 1; i >= 0; --i)
        sa[--x[s[p[nsa[i]]]]] = p[nsa[i]];
    induce(sa, c, s, t, n, z);
}
void build(const string &s) {
    for (int i = 0; i < (int)s.size(); ++i) _s[i] = s[i];
    _s[(int)s.size()] = 0; // s shouldn't contain 0
    sais(_s, sa, p, q, t, c, (int)s.size() + 1, 256);
    for(int i = 0; i < (int)s.size(); ++i) sa[i]=sa[i+1];
    for(int i = 0; i < (int)s.size(); ++i) rev[sa[i]]=i;
    int ind = 0; hi[0] = 0;
    for (int i = 0; i < (int)s.size(); ++i) {
        if (!rev[i]) {
            ind = 0;
            continue;
        }
        while (i + ind < (int)s.size() && \
            s[i + ind] == s[sa[rev[i] - 1] + ind]) ++ind;
        hi[rev[i]] = ind ? ind - 1 : 0;
    }
}
}

```



## 7.3 Aho-Corasick Algorithm

```
class AhoCorasick{
private:
    static constexpr int Z = 26;
    struct node{
        node *nxt[ Z ], *fail;
        vector< int > data;
        node(): fail( nullptr ) {
            memset( nxt, 0, sizeof( nxt ) );
            data.clear();
        }
    } *rt;
    inline int Idx( char c ) { return c - 'a'; }
public:
    void init() { rt = new node(); }
    void add( const string& s, int d ) {
        node* cur = rt;
        for ( auto c : s ) {
            if ( not cur->nxt[ Idx( c ) ] )
                cur->nxt[ Idx( c ) ] = new node();
            cur = cur->nxt[ Idx( c ) ];
        }
        cur->data.push_back( d );
    }
    void compile() {
        vector< node* > bfs;
        size_t ptr = 0;
        for ( int i = 0; i < Z; ++i ) {
            if ( not rt->nxt[ i ] )
                continue;
            rt->nxt[ i ]->fail = rt;
            bfs.push_back( rt->nxt[ i ] );
        }
        while ( ptr < bfs.size() ) {
            node* u = bfs[ ptr++ ];
            for ( int i = 0; i < Z; ++i ) {
                if ( not u->nxt[ i ] )
                    continue;
                node* u_f = u->fail;
                while ( u_f ) {
                    if ( not u_f->nxt[ i ] ) {
                        u_f = u_f->fail; continue;
                    }
                    u->nxt[ i ]->fail = u_f->nxt[ i ];
                    break;
                }
                if ( not u_f ) u->nxt[ i ]->fail = rt;
                bfs.push_back( u->nxt[ i ] );
            }
        }
    }
    void match( const string& s, vector< int >& ret ) {
        node* u = rt;
        for ( auto c : s ) {
            while ( u != rt and not u->nxt[ Idx( c ) ] )
                u = u->fail;
            u = u->nxt[ Idx( c ) ];
            if ( not u ) u = rt;
            node* tmp = u;
            while ( tmp != rt ) {
                for ( auto d : tmp->data )
                    ret.push_back( d );
                tmp = tmp->fail;
            }
        }
    }
} ac;
```

## 7.4 Suffix Automaton

```
struct Node{
    Node *green, *edge[26];
    int max_len;
    Node(const int _max_len)
        : green(NULL), max_len(_max_len){
        memset(edge,0,sizeof(edge));
    }
} *ROOT, *LAST;
void Extend(const int c) {
    Node *cursor = LAST;
```

```
    LAST = new Node((LAST->max_len) + 1);
    for(; cursor&&!cursor->edge[c]; cursor=cursor->green)
        cursor->edge[c] = LAST;
    if (!cursor)
        LAST->green = ROOT;
    else {
        Node *potential_green = cursor->edge[c];
        if((potential_green->max_len)==(cursor->max_len+1))
            LAST->green = potential_green;
        else {
            //assert(potential_green->max_len>(cursor->max_len+1));
            Node *wish = new Node((cursor->max_len) + 1);
            for(; cursor && cursor->edge[c]==potential_green;
                cursor = cursor->green)
                cursor->edge[c] = wish;
            for (int i = 0; i < 26; i++)
                wish->edge[i] = potential_green->edge[i];
            wish->green = potential_green->green;
            potential_green->green = wish;
            LAST->green = wish;
        }
    }
}
char S[10000001], A[10000001];
int N;
int main(){
    scanf("%d%s", &N, S);
    ROOT = LAST = new Node(0);
    for (int i = 0; S[i]; i++)
        Extend(S[i] - 'a');
    while (N--){
        scanf("%s", A);
        Node *cursor = ROOT;
        bool ans = true;
        for (int i = 0; A[i]; i++){
            cursor = cursor->edge[A[i] - 'a'];
            if (!cursor) {
                ans = false;
                break;
            }
        }
        puts(ans ? "Yes" : "No");
    }
    return 0;
}
```

## 7.5 KMP

```
int F[N<<1];
void KMP(char s1[], char s2[], int n, int m){
    // make F[] for s1+'0'+s2;
    char ss[N<<1];
    int len = n+m+1;
    for(int i=0;i<n;i++) ss[i] = s1[i];
    ss[n] = '0';
    for(int i=0;i<m;i++) ss[i+n] = s2[i];
    F[0] = F[1] = 0;
    for(int i=1;i<len;i++){
        int j = F[i];
        while(j > 0 and ss[i]!=ss[j]) j = F[j];
        F[i+1] = (ss[i]==ss[j]?j+1:0);
    }
    // just find (F[len2+i] == len2)
    // i from 1 to len+1 for matching
}
/*
[0, i]是個循環字串，且循環節為i-f[i]:
if(f[i]>0 and i%(i-f[i])==0)
cout << i << " " << i/(i-f[i]) << '\n';
*/
```

## 7.6 Z value

```
char s[MAXN];
int len, z[MAXN];
void Z_value() {
    int i, j, left, right;
    left=right=0; z[0]=len;
    for(i=1;i<len;i++) {
        j=max(min(z[i-left],right-i),0);
```

```

    for(;i+j<len&&s[i+j]==s[j];j++);
    z[i]=j;
    if(i+z[i]>right) {
        right=i+z[i];
        left=i;
    }
}
}

```

## 7.7 Manacher

```

int z[maxn];
int manacher(const string& s) {
    string t = ".";
    for(char c:s) t += c, t += '.';
    int l = 0, r = 0, ans = 0;
    for (int i = 1; i < t.length(); ++i) {
        z[i] = (r > i ? min(z[2 * l - i], r - i) : 1);
        while (i - z[i] >= 0 && i + z[i] < t.length()) {
            if(t[i - z[i]] == t[i + z[i]]) ++z[i];
            else break;
        }
        if (i + z[i] > r) r = i + z[i], l = i;
    }
    for(int i=1;i<t.length();++i) ans = max(ans, z[i]-1);
    return ans;
}

```

## 7.8 Lexicographically Smallest Rotation

```

string mcp(string s){
    int n = s.length();
    s += s;
    int i=0, j=1;
    while (i<n && j<n){
        int k = 0;
        while (k < n && s[i+k] == s[j+k]) k++;
        if (s[i+k] <= s[j+k]) j += k+1;
        else i += k+1;
        if (i == j) j++;
    }
    int ans = i < n ? i : j;
    return s.substr(ans, n);
}

```

## 7.9 BWT

```

struct BurrowsWheeler{
#define SIGMA 26
#define BASE 'a'
    vector<int> v[ SIGMA ];
    void BWT(char* ori, char* res){
        // make ori -> ori + ori
        // then build suffix array
    }
    void iBWT(char* ori, char* res){
        for( int i = 0 ; i < SIGMA ; i ++ )
            v[ i ].clear();
        int len = strlen( ori );
        for( int i = 0 ; i < len ; i ++ )
            v[ ori[i] - BASE ].push_back( i );
        vector<int> a;
        for( int i = 0 , ptr = 0 ; i < SIGMA ; i ++ )
            for( auto j : v[ i ] ){
                a.push_back( j );
                ori[ ptr ++ ] = BASE + i;
            }
        for( int i = 0 , ptr = 0 ; i < len ; i ++ ){
            res[ i ] = ori[ a[ ptr ] ];
            ptr = a[ ptr ];
        }
        res[ len ] = 0;
    }
} bwt;

```

## 7.10 Palindromic Tree

```

struct palindromic_tree{
    struct node{
        int next[26],f,len;
        int cnt,num,st,ed;
        node(int l=0):f(0),len(l),cnt(0),num(0){
            memset(next, 0, sizeof(next));
        }
    };
    vector<node> state;
    vector<char> s;
    int last,n;
    void init(){
        state.clear();s.clear();last=1; n=0;
        state.push_back(0);state.push_back(-1);
        state[0].f=1;s.push_back(-1);
    }
    int getFail(int x){
        while(s[n-state[x].len-1]!=s[n])x=state[x].f;
        return x;
    }
    void add(int c){
        s.push_back(c-'a'); ++n;
        int cur=getFail(last);
        if(!state[cur].next[c]){
            int now=state.size();
            state.push_back(state[cur].len+2);
            state[now].f=state[getFail(state[cur].f)].next[c];
            state[cur].next[c]=now;
            state[now].num=state[state[now].f].num+1;
        }
        last=state[cur].next[c];
        ++state[last].cnt;
    }
    int size(){
        return state.size()-2;
    }
} pt;
int main() {
    string s; cin >> s; pt.init();
    for (int i=0; i<SZ(s); i++) {
        int prvsz = pt.size(); pt.add(s[i]);
        if (prvsz != pt.size()) {
            int r = i, l = r - pt.state[pt.last].len + 1;
            // pal @ [l,r]: s.substr(l, r-l+1)
        }
    }
    return 0;
}

```

## 8 Misc

### 8.1 Theorems

#### 8.1.1 Kirchhoff's Theorem

Denote  $L$  be a  $n \times n$  matrix as the Laplacian matrix of graph  $G$ , where  $L_{ii} = d(i)$ ,  $L_{ij} = -c$  where  $c$  is the number of edge  $(i, j)$  in  $G$ .

- The number of undirected spanning in  $G$  is  $|\det(\tilde{L}_{11})|$ .
- The number of directed spanning tree rooted at  $r$  in  $G$  is  $|\det(\tilde{L}_{rr})|$ .

#### 8.1.2 Tutte's Matrix

Let  $D$  be a  $n \times n$  matrix, where  $d_{ij} = x_{ij}$  ( $x_{ij}$  is chosen uniform randomly) if  $i < j$  and  $(i, j) \in E$ , otherwise  $d_{ij} = -d_{ji}$ .  $\frac{\text{rank}(D)}{2}$  is the maximum matching on  $G$ .

#### 8.1.3 Cayley's Formula

- Given a degree sequence  $d_1, d_2, \dots, d_n$  for each labeled vertices, there're  $\frac{(n-2)!}{(d_1-1)!(d_2-1)!\dots(d_n-1)!}$  spanning trees.
- Let  $T_{n,k}$  be the number of labeled forests on  $n$  vertices with  $k$  components, such that vertex  $1, 2, \dots, k$  belong to different components. Then  $T_{n,k} = kn^{n-k-1}$ .

#### 8.1.4 Erdős-Gallai theorem

A sequence of non-negative integers  $d_1 \geq d_2 \geq \dots \geq d_n$  can be represented as the degree sequence of a finite simple graph on  $n$  vertices if and only if  $d_1 + d_2 + \dots + d_n$  is even and

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$$

holds for all  $1 \leq k \leq n$ .

### 8.1.5 Havel-Hakimi algorithm

find the vertex who has greatest degree unused, connect it with other greatest vertex.

### 8.1.6 Hall's marriage theorem

Let  $G$  be a finite bipartite graph with bipartite sets  $X$  and  $Y$ . For a subset  $W$  of  $X$ , let  $N_G(W)$  denote the set of all vertices in  $Y$  adjacent to some element of  $W$ . Then there is an  $X$ -saturating matching iff  $\forall W \subseteq X, |W| \leq |N_G(W)|$

### 8.1.7 Euler's planar graph formula

$$V - E + F = C + 1, E \leq 3V - 6(?)$$

### 8.1.8 Pick's theorem

For simple polygon, when points are all integer, we have  $A = \#\{\text{lattice points in the interior}\} + \frac{\#\{\text{lattice points on the boundary}\}}{2} - 1$

## 8.2 MaximumEmptyRect

```
int max_empty_rect(int n, int m, bool blocked[N][N]){
    static int mxu[2][N], me=0, he=1, ans=0;
    for(int i=0; i<m; i++){
        for(int j=0; j<n; j++){
            if(blocked[i][j]) mxu[me][j]=0;
            else mxu[me][j]=mxu[he][j]+1;
            int la = j;
            while(!stk.empty() && stk.top().FF > mxu[me][j]){
                int x1 = i - stk.top().FF, x2 = i;
                int y1 = stk.top().SS, y2 = j;
                la = stk.top().SS; stk.pop();
                ans = max(ans, (x2-x1)*(y2-y1));
            }
            if(stk.empty() || stk.top().FF < mxu[me][j])
                stk.push({mxu[me][j], la});
        }
        while(!stk.empty()){
            int x1 = i - stk.top().FF, x2 = i;
            int y1 = stk.top().SS-1, y2 = m-1;
            stk.pop();
            ans = max(ans, (x2-x1)*(y2-y1));
        }
        swap(me, he);
    }
    return ans;
}
```

## 8.3 DP-opt Condition

### 8.3.1 totally monotone (concave/convex)

$$\forall i < i', j < j', B[i][j] \leq B[i'][j] \implies B[i][j'] \leq B[i'][j']$$

$$\forall i < i', j < j', B[i][j] \geq B[i'][j] \implies B[i][j'] \geq B[i'][j']$$

### 8.3.2 monge condition (concave/convex)

$$\forall i < i', j < j', B[i][j] + B[i'][j'] \geq B[i][j'] + B[i'][j]$$

$$\forall i < i', j < j', B[i][j] + B[i'][j'] \leq B[i][j'] + B[i'][j]$$

## 8.4 Convex 1D/1D DP

```
struct segment {
    int i, l, r;
    segment() {}
    segment(int a, int b, int c): i(a), l(b), r(c) {}
};
inline lld f(int l, int r) {return dp[l] + w(l+1, r);}
void solve() {
    dp[0] = 0;
    deque<segment> deq; deq.push_back(segment(0, 1, n));
    for (int i = 1; i <= n; ++i) {
        dp[i] = f(deq.front().i, i);
        while(deq.size() && deq.front().r < i+1) deq.pop_front();
        deq.front().l = i+1;
        segment seg = segment(i, i+1, n);
        while (deq.size() && f(i, deq.back().l) < f(deq.back().i, deq.back().l))
```

```
            deq.pop_back();
        if (deq.size()) {
            int d = 1048576, c = deq.back().l;
            while (d >= 1) if (c + d <= deq.back().r)
                if (f(i, c + d) > f(deq.back().i, c + d)) c += d;
            deq.back().r = c; seg.l = c + 1;
        }
        if (seg.l <= n) deq.push_back(seg);
    }
}
```

## 8.5 ConvexHull Optimization

```
inline lld DivCeil(lld n, lld d) { // ceil(n/d)
    return n / d + ((n < 0) != (d > 0)) && (n % d);
}
struct Line {
    static bool flag;
    lld a, b, l, r; // y=ax+b in [l, r)
    lld operator()(lld x) const { return a * x + b; }
    bool operator<(const Line& i) const {
        return flag ? tie(a, b) < tie(i.a, i.b) : l < i.l;
    }
    lld operator&(const Line& i) const {
        return DivCeil(b - i.b, i.a - a);
    }
};
bool Line::flag = true;
class ConvexHullMax {
    set<Line> L;
public:
    ConvexHullMax() { Line::flag = true; }
    void InsertLine(lld a, lld b) { // add y = ax + b
        Line now = {a, b, -INF, INF};
        if (L.empty()) {
            L.insert(now);
            return;
        }
        Line::flag = true;
        auto it = L.lower_bound(now);
        auto prv = it == L.begin() ? it : prev(it);
        if (it != L.end() && ((it != L.begin() &&
            (*it)(it->r) >= now(it->r) &&
            (*prv)(prv->r - 1) >= now(prv->r - 1)) ||
            (it == L.begin() && it->a == now.a))) return;
        if (it != L.begin()) {
            while (prv != L.begin() &&
                (*prv)(prv->l) <= now(prv->l))
                prv = --L.erase(prv);
            if (prv == L.begin() && now.a == prv->a)
                L.erase(prv);
        }
        if (it != L.end())
            while (it != --L.end() &&
                (*it)(it->r) <= now(it->r))
                it = L.erase(it);
        if (it != L.begin()) {
            prv = prev(it);
            const_cast<Line*>(&*prv)->r = now.l;
        }
        if (it != L.end())
            const_cast<Line*>(&*it)->l = now.r;
        L.insert(it, now);
    }
    lld Query(lld a) const { // query max at x=a
        if (L.empty()) return -INF;
        Line::flag = false;
        auto it = --L.upper_bound({0, 0, a, 0});
        return (*it)(a);
    }
};
```

## 8.6 Josephus Problem

```
// n people kill m for each turn
int f(int n, int m) {
    int s = 0;
    for (int i = 2; i <= n; ++i)
        s = (s + m) % i;
```

```

    return s;
}
// died at kth
int kth(int n, int m, int k){
    if (m == 1) return n-1;
    for (k = k*m+m-1; k >= n; k = k-n+(k-n)/(m-1));
    return k;
}

```

## 8.7 Cactus Matching

```

vector<int> init_g[maxn], g[maxn*2];
int n, dfn[maxn], low[maxn], par[maxn], dfs_idx, bcc_id;
void tarjan(int u){
    dfn[u]=low[u]=++dfs_idx;
    for(int i=0; i<(int)init_g[u].size(); i++){
        int v=init_g[u][i];
        if(v==par[u]) continue;
        if(!dfn[v]){
            par[v]=u;
            tarjan(v);
            low[u]=min(low[u], low[v]);
            if(dfn[u]<low[v]){
                g[u].push_back(v);
                g[v].push_back(u);
            }
        }else{
            low[u]=min(low[u], dfn[v]);
            if(dfn[v]<dfn[u]){
                int temp_v=u;
                bcc_id++;
                while(temp_v!=v){
                    g[bcc_id+n].push_back(temp_v);
                    g[temp_v].push_back(bcc_id+n);
                    temp_v=par[temp_v];
                }
                g[bcc_id+n].push_back(v);
                g[v].push_back(bcc_id+n);
                reverse(g[bcc_id+n].begin(), g[bcc_id+n].end());
            }
        }
    }
}
int dp[maxn][2], min_dp[2][2], tmp[2][2], tp[2];
void dfs(int u, int fa){
    if(u<=n){
        for(int i=0; i<(int)g[u].size(); i++){
            int v=g[u][i];
            if(v==fa) continue;
            dfs(v, u);
            memset(tp, 0x8f, sizeof tp);
            if(v<=n){
                tp[0]=dp[u][0]+max(dp[v][0], dp[v][1]);
                tp[1]=max(
                    dp[u][0]+dp[v][0]+1,
                    dp[u][1]+max(dp[v][0], dp[v][1])
                );
            }else{
                tp[0]=dp[u][0]+dp[v][0];
                tp[1]=max(dp[u][0]+dp[v][1], dp[u][1]+dp[v][0]);
            }
            dp[u][0]=tp[0], dp[u][1]=tp[1];
        }
    }else{
        for(int i=0; i<(int)g[u].size(); i++){
            int v=g[u][i];
            if(v==fa) continue;
            dfs(v, u);
        }
        min_dp[0][0]=0;
        min_dp[1][1]=1;
        min_dp[0][1]=min_dp[1][0]=-0x3f3f3f3f;
        for(int i=0; i<(int)g[u].size(); i++){
            int v=g[u][i];
            if(v==fa) continue;
            memset(tmp, 0x8f, sizeof tmp);
            tmp[0][0]=max(
                min_dp[0][0]+max(dp[v][0], dp[v][1]),
                min_dp[0][1]+dp[v][0]
            );
            tmp[0][1]=min_dp[0][0]+dp[v][0]+1;

```

```

            tmp[1][0]=max(
                min_dp[1][0]+max(dp[v][0], dp[v][1]),
                min_dp[1][1]+dp[v][0]
            );
            tmp[1][1]=min_dp[1][0]+dp[v][0]+1;
            memcpy(min_dp, tmp, sizeof tmp);
        }
        dp[u][1]=max(min_dp[0][1], min_dp[1][0]);
        dp[u][0]=min_dp[0][0];
    }
}
int main(){
    int m, a, b;
    scanf("%d%d", &n, &m);
    for(int i=0; i<m; i++){
        scanf("%d%d", &a, &b);
        init_g[a].push_back(b);
        init_g[b].push_back(a);
    }
    par[1]=-1;
    tarjan(1);
    dfs(1, -1);
    printf("%d\n", max(dp[1][0], dp[1][1]));
    return 0;
}

```

## 8.8 DLX

```

struct DLX {
    const static int maxn=210;
    const static int maxm=210;
    const static int maxnode=210*210;
    int n, m, size, row[maxnode], col[maxnode];
    int U[maxnode], D[maxnode], L[maxnode], R[maxnode];
    int H[maxn], S[maxm], ansd, ans[maxn];
    void init(int _n, int _m) {
        n = _n, m = _m;
        for(int i = 0; i <= m; ++i) {
            S[i] = 0;
            U[i] = D[i] = i;
            L[i] = i-1, R[i] = i+1;
        }
        R[L[0] = size = m] = 0;
        for(int i = 1; i <= n; ++i) H[i] = -1;
    }
    void Link(int r, int c) {
        ++S[col[++size] = c];
        row[size] = r; D[size] = D[c];
        U[D[c]] = size; U[size] = c; D[c] = size;
        if(H[r] < 0) H[r] = L[size] = R[size] = size;
        else {
            R[size] = R[H[r]];
            L[R[H[r]]] = size;
            L[size] = H[r];
            R[H[r]] = size;
        }
    }
    void remove(int c) {
        L[R[c]] = L[c]; R[L[c]] = R[c];
        for(int i = D[c]; i != c; i = D[i])
            for(int j = R[i]; j != i; j = R[j]) {
                U[D[j]] = U[j];
                D[U[j]] = D[j];
                --S[col[j]];
            }
    }
    void resume(int c) {
        L[R[c]] = c; R[L[c]] = c;
        for(int i = U[c]; i != c; i = U[i])
            for(int j = L[i]; j != i; j = L[j]) {
                U[D[j]] = j;
                D[U[j]] = j;
                ++S[col[j]];
            }
    }
    void dance(int d) {
        if(d>=ansd) return;
        if(R[0] == 0) {
            ansd = d;
            return;
        }
    }
}

```

```

int c = R[0];
for(int i = R[0]; i; i = R[i])
    if(S[i] < S[c]) c = i;
remove(c);
for(int i = D[c]; i != c; i = D[i]) {
    ans[d] = row[i];
    for(int j = R[i]; j != i; j = R[j])
        remove(col[j]);
    dance(d+1);
    for(int j = L[i]; j != i; j = L[j])
        resume(col[j]);
}
resume(c);
}
} sol;

```

## 8.9 Tree Knapsack

```

int dp[N][K]; PII obj[N];
vector<int> G[N];
void dfs(int u, int mx){
    for(int s: G[u]) {
        if(mx < obj[s].first) continue;
        for(int i=0; i<=mx-obj[s].FF; i++){
            dp[s][i] = dp[u][i];
            dfs(s, mx - obj[s].first);
        }
        for(int i=obj[s].FF; i<=mx; i++){
            dp[u][i] = max(dp[u][i],
                dp[s][i - obj[s].FF] + obj[s].SS);
        }
    }
}
int main(){
    int n, k; cin >> n >> k;
    for(int i=1; i<=n; i++){
        int p; cin >> p;
        G[p].push_back(i);
        cin >> obj[i].FF >> obj[i].SS;
    }
    dfs(0, k); int ans = 0;
    for(int i=0; i<=k; i++) ans = max(ans, dp[0][i]);
    cout << ans << '\n';
    return 0;
}

```