

Contents

1 Basic

1.1 vimrc	1
1.2 Debug Macro	1
1.3 SVG Writer	1
1.4 Pragma Optimization	1
1.5 IO Optimization	2

2 Data Structure

2.1 Dark Magic	2
2.2 Link-Cut Tree	2
2.3 LiChao Segtree	2
2.4 Treap*	2
2.5 Linear Basis*	3
2.6 <atcoder/lazysegtree>*	3
2.7 Binary Search on Segtree	3
2.8 Interval Container* ..	3

3 Graph

3.1 SCC (IRZck)*	4
3.2 2-SAT (IRZck)*	4
3.3 BCC	4
3.4 Round Square Tree ..	4
3.5 Edge TCC	4
3.6 Bipolar Orientation ..	5
3.7 DMST	5
3.8 Dominator Tree	5
3.9 Edge Coloring	6
3.10 Centroid Decomp.* ..	6
3.11 Heavy-Light De-comp.*	6
3.12 Virtual Tree	7
3.13 Tree Hashing	7
3.14 Mo's Algo on Tree ...	7
3.15 Count Cycles	7
3.16 Maximal Clique	7
3.17 Maximum Clique ...	7
3.18 Min Mean Cycle	8
3.19 Eulerian Trail	8

4 Flow & Matching

4.1 HopcroftKarp*	8
4.2 Kuhn Munkres	8
4.3 Flow Models	8
4.4 Dinic	9
4.5 Global Min-Cut	9
4.6 GomoryHu Tree	9
4.7 MCMF	9
4.8 Dijkstra Cost Flow ...	9
4.9 Min Cost Circulation ..	10
4.10 General Matching ...	10
4.11 Weighted Matching ...	10

5 Math

5.1 Common Bounds ...	12
5.2 Equations	12
5.3 Integer Division*	12
5.4 FloorSum	12
5.5 ModMin	12
5.6 Floor Monoid Product ..	12
5.7 $ax+by=gcd$	12
5.8 Chinese Remainder ..	12
5.9 DiscreteLog	12
5.10 Quadratic Residue ..	12
5.11 FWT*	13
5.12 Packed FFT	13
5.13 CRT for arbitrary mod ..	13
5.14 NTT / FFT*	13
5.15 Formal Power Series* ..	13
5.16 Partition Number ...	14
5.17 Pi Count	14
5.18 Min 25 Sieve*	14
5.19 Miller Rabin	15
5.20 Pollard Rho	15
5.21 Montgomery	15
5.22 Berlekamp Massey ..	15
5.23 Gauss Elimination ...	15
5.24 CharPoly	15
5.25 Simplex	15

5.26 Simplex Construction ..	16
5.27 Adaptive Simpson ..	16
5.28 Golden Ratio Search ..	16

6 Geometry

6.1 Basic Geometry	16
6.2 2D Convex Hull	16
6.3 2D Farthest Pair	16
6.4 MinMax Enclosing Rect	16
6.5 Minkowski Sum	17
6.6 Segment Intersection ..	17
6.7 Halfplane Intersection	17
6.8 HPI Alternative Form ..	17
6.9 SegmentDist (Sausage)	17
6.10 Rotating Sweep Line ..	17
6.11 Hull Cut	18
6.12 Point In Hull	18
6.13 Point In Polygon	18
6.14 Point In Polygon (Fast)	18
6.15 Cyclic Ternary Search ..	18
6.16 Tangent of Points to Hull	18
6.17 Direction In Poly* ...	18
6.18 Circle Class & Intersection	18
6.19 Circle Common Tangent	19
6.20 Line-Circle Intersection	19
6.21 Poly-Circle Intersection	19
6.22 Min Covering Circle ..	19
6.23 Circle Union	19
6.24 Polygon Union	19
6.25 3D Point	20
6.26 3D Convex Hull	20
6.27 3D Projection	20
6.28 3D Skew Line Near-est Point	20
6.29 Delaunay	20
6.30 Build Voronoi	21
6.31 Simulated Annealing* ..	21
6.32 Triangle Centers* ...	21

7 Stringology

7.1 Hash	21
7.2 Suffix Array	21
7.3 Suffix Array Tools* ...	21
7.4 Ex SAM*	22
7.5 KMP	22
7.6 Z value	22
7.7 Manacher	22
7.8 Lyndon Factorization ..	22
7.9 Main Lorentz*	22
7.10 BWT*	23
7.11 Palindromic Tree* ...	23

8 Misc

8.1 Theorems	23
8.2 Stable Marriage	24
8.3 Weight Matroid Intersection*	24
8.4 Bitset LCS	24
8.5 Prefix Substring LCS ..	24
8.6 Convex ID/ID DP	24
8.7 ConvexHull Optimization	24
8.8 Min Plus Convolution ..	24
8.9 SMAWK	24
8.10 De-Bruijn	25
8.11 Josephus Problem ..	25
8.12 N Queens Problem ..	25
8.13 Manhattan MST	25
8.14 Binary Search On Fraction	25
8.15 Cartesian Tree	25
8.16 Nim Product	25
8.17 Grid	25

1 Basic

1.1 vimrc

```
se is nu ru et tgc sc hls cin cino+=j1 sw=4 sts=4 bs=2
mouse=a "encoding=utf-8 ls=2
syn on | colo desert | filetype indent on
map <leader>b <ESC>:w<CR>:!g++ "%" -o "%<" -g -std=gnu
++20 -DCKISEKI -Wall -Wextra -Wshadow -Wfatal-
errors -Wconversion -fsanitize=address,undefined,
float-divide-by-zero,float-cast-overflow && echo
success<CR>
map <leader>z <ESC>:w<CR>:!g++ "%" -o "%<" -O2 -g -std=
gnu++20 && echo success<CR>
map <leader>i <ESC>:!. / "%<"<CR>
map <leader>r <ESC>:!cat 01.in && echo "---" && ./ "%<"
< 01.in<CR>
map <leader>l :%d<bar>0r ~/t.cpp<CR>
ca Hash w !cpp -dD -P -fpreprocessed \ | tr -d "[:space
:]" \ | md5sum \ | cut -c-6
let c_no_curly_error=1
" setxkbmap -option caps:ctrl_modifier
```

1.2 Debug Macro [a45c59]

```
#define all(x) begin(x), end(x)
#ifdef CKISEKI
#include <experimental/iterator>
#define safe cerr<<__PRETTY_FUNCTION__<<" line "<<
__LINE__<<" safe\n"
#define debug(a...) debug_(#a, a)
#define orange(a...) orange_(#a, a)
void debug_(auto s, auto ...a) {
    cerr << "\e[1;32m(" << s << ") = (" ;
    int f = 0;
    (... , (cerr << (f++ ? ", " : "") << a));
    cerr << ")\e[0m\n";
}
void orange_(auto s, auto L, auto R) {
    cerr << "\e[1;33m[ " << s << " ] = [ ";
    using namespace experimental;
    copy(L, R, make_ostream_joiner(cerr, ", "));
    cerr << "]\e[0m\n";
}
#else
#define safe ((void)0)
#define debug(...) safe
#define orange(...) safe
#endif
```

1.3 SVG Writer [85759e]

```
#ifdef CKISEKI
class SVG {
    void p(string_view s) { o << s; }
    void p(string_view s, auto v, auto... vs) {
        auto i = s.find('$');
        o << s.substr(0, i) << v, p(s.substr(i + 1), vs...);
    }
    ostream o; string c = "red";
public:
    SVG(auto f, auto x1, auto y1, auto x2, auto y2) : o(f) {
        p("<svg xmlns='http://www.w3.org/2000/svg' "
        "viewBox='$ $ $ $'>\n"
        "<style>{*stroke-width:0.5%;}</style>\n",
        x1, -y2, x2 - x1, y2 - y1);
    }
    ~SVG() { p("</svg>\n"); }
    void color(string nc) { c = nc; }
    void line(auto x1, auto y1, auto x2, auto y2) {
        p("<line x1='$' y1='$' x2='$' y2='$' stroke='$'>\n",
        x1, -y1, x2, -y2, c);
    }
    void circle(auto x, auto y, auto r) {
        p("<circle cx='$' cy='$' r='$' stroke='$' "
        "fill='none'/>\n", x, -y, r, c);
    }
    void text(auto x, auto y, string s, int w = 12) {
        p("<text x='$' y='$' font-size='$px'>$</text>\n",
        x, -y, w, s);
    }; // write wrapper for complex if use complex
#else
struct SVG { SVG(auto ...) {} }; // you know how to
#endif
```

1.4 Pragma Optimization [6006f6]

```
#pragma GCC optimize("Ofast,no-stack-protector")
#pragma GCC optimize("no-math-errno,unroll-loops")
#pragma GCC target("sse, sse3, sse4")
#pragma GCC target("popcnt,abm,mmx,avx,arch=skylake")
__builtin_ia32_ldmxcsr(__builtin_ia32_stmxcsr()|0x8040)
```

1.5 IO Optimization [c9494b]

```
static inline int gc() {
    constexpr int B = 1<<20; static char buf[B], *p, *q;
    if (p == q) q = (p = buf) + fread(buf, 1, B, stdin);
    return q == buf ? EOF : *p++;
}
```

2 Data Structure

2.1 Dark Magic [095f25]

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/priority_queue.hpp>
using namespace __gnu_pbds;
// heap tags: pairing/binary/binomial/rc_binomial/thin
template<typename T>
using pbds_heap=__gnu_pbds::prioity_queue<T,less<T>, \
    pairing_heap_tag>;
// pbds_heap::point_iterator
// x = pq.push(10); pq.modify(x, 87); a.join(b);
// tree tags: rb_tree_tag/ov_tree_tag/splay_tree_tag
template<typename T>
using ordered_set = tree<T, null_type, less<T>,
    rb_tree_tag, tree_order_statistics_node_update>;
// find_by_order, order_of_key
// hash tables: cc_hash_table/gp_hash_table
```

2.2 Link-Cut Tree [2aaa19] - 0d97f7/f05d4f/642331

```
template <typename Val, typename SVal> class LCT {
    struct node {
        int pa, ch[2]; bool rev;
        Val v, prod, rprod; SVal sv, sub, vir;
        node() : pa{0}, ch{0, 0}, rev{false}, v{},
            prod{}, rprod{}, sv{}, sub{}, vir{} {}
    };
    #define cur o[u]
    #define lc cur.ch[0]
    #define rc cur.ch[1]
    vector<node> o;
    bool is_root(int u) const {
        return o[cur.pa].ch[0]!=u && o[cur.pa].ch[1]!=u; }
    bool is_rch(int u) const {
        return o[cur.pa].ch[1] == u && !is_root(u); }
    void down(int u) {
        if (not cur.rev) return;
        for (int c : {lc, rc}) if (c) set_rev(c);
        cur.rev = false;
    }
    void up(int u) {
        cur.prod = o[lc].prod * cur.v * o[rc].prod;
        cur.rprod = o[rc].rprod * cur.v * o[lc].rprod;
        cur.sub = cur.vir + o[lc].sub + o[rc].sub + cur.sv;
    }
    void set_rev(int u) {
        swap(lc, rc), swap(cur.prod, cur.rprod);
        cur.rev ^= 1;
    }
    /* SPLIT_HASH_HERE */
    void rotate(int u) {
        int f = cur.pa, g = o[f].pa, l = is_rch(u);
        if (cur.ch[l ^ 1]) o[cur.ch[l ^ 1]].pa = f;
        if (not is_root(f)) o[g].ch[is_rch(f)] = u;
        o[f].ch[l] = cur.ch[l ^ 1], cur.ch[l ^ 1] = f;
        cur.pa = g, o[f].pa = u; up(f);
    }
    void splay(int u) {
        vector<int> stk = {u};
        while (not is_root(stk.back()))
            stk.push_back(o[stk.back()].pa);
        while (not stk.empty())
            down(stk.back()), stk.pop_back();
        for (int f = cur.pa; not is_root(u); f = cur.pa) {
            if (!is_root(f))
                rotate(is_rch(u) == is_rch(f) ? f : u);
            rotate(u);
        }
        up(u);
    }
    void access(int x) {
        for (int u = x, last = 0; u; u = cur.pa) {
            splay(u);
            cur.vir = cur.vir + o[rc].sub - o[last].sub;
            rc = last; up(last = u);
        }
        splay(x);
    }
    int find_root(int u) {
        int la = 0;
        for (access(u); u; u = lc) down(la = u);
        return la;
    }
    void split(int x, int y) { chroot(x); access(y); }
    void chroot(int u) { access(u); set_rev(u); }
    /* SPLIT_HASH_HERE */
public:
    LCT(int n = 0) : o(n + 1) {}
    void set_val(int u, const Val &v) {
        splay(++u); cur.v = v; up(u); }
    void set_sval(int u, const SVal &v) {
        access(++u); cur.sv = v; up(u); }
    Val query(int x, int y) {
        split(++x, ++y); return o[y].prod; }
    SVal subtree(int p, int u) {
        chroot(++p); access(++u); return cur.vir + cur.sv; }
    bool connected(int u, int v) {
        return find_root(++u) == find_root(++v); }
    void link(int x, int y) {
        chroot(++x); access(++y);
        o[y].vir = o[y].vir + o[x].sub; up(o[x].pa = y);
    }
    void cut(int x, int y) {
        split(++x, ++y); o[y].ch[0] = o[x].pa = 0; up(y); }
    #undef cur
    #undef lc
    #undef rc
};
```

2.3 LiChao Segtree [8e1eaf]

```
// cmp(l, r, i) := is l better than r at i?
template <typename L, typename Cmp> class LiChao {
    int n; vector<L> T; Cmp cmp;
    void insert(int l, int r, int o, L ln) {
        // if (ln is empty line) return; // constant
        int m = (l + r) >> 1;
        bool atL = cmp(ln, T[o], l);
        if (cmp(ln, T[o], m)) atL ^= 1, swap(T[o], ln);
        if (r - l == 1) return;
        if (atL) insert(l, m, o << 1, ln);
        else insert(m, r, o << 1 | 1, ln);
    }
    L query(int x, int l, int r, int o) {
        if (r - l == 1) return T[o];
        int m = (l + r) >> 1;
        L s = (x < m ? query(x, l, m, o << 1)
            : query(x, m, r, o << 1 | 1));
        return cmp(s, T[o], x) ? s : T[o];
    }
public:
    LiChao(int n_, L init, Cmp &&c) : n(n_), T(n * 4, init),
        cmp(c) {}
    void insert(L ln) { insert(0, n, 1, ln); }
    L query(int x) { return query(x, 0, n, 1); }
};
// struct Line { lld a, b; };
// LiChao lct(
//     int(xs.size()), Line{0, INF},
//     [&](const Line &l, const Line &r, int i) {
//         lld x = xs[i];
//         return l.a * x + l.b < r.a * x + r.b;
//     });
2.4 Treap* [ae576c]
__gnu_cxx::sfmt19937 rnd(7122); // <ext/random>
namespace Treap {
    struct node {
        int size, pri; node *lc, *rc, *pa;
        node() : size(1), pri(rnd()), lc(0), rc(0), pa(0) {}
    }
    void pull() {
        size = 1; pa = 0;
        if (lc) { size += lc->size; lc->pa = this; }
        if (rc) { size += rc->size; rc->pa = this; }
    }
    int SZ(node *x) { return x ? x->size : 0; }
    node *merge(node *L, node *R) {
        if (not L or not R) return L ? L : R;
        if (L->pri > R->pri)
            return L->rc = merge(L->rc, R), L->pull(), L;
        else
    }
```

```

    return R->lc = merge(L, R->lc), R->pull(), R;
}
void splitBySize(node *o, int k, node *&L, node *&R) {
    if (not o) L = R = 0;
    else if (int s = SZ(o->lc) + 1; s <= k)
        L=o, splitBySize(o->rc, k-s, L->rc, R), L->pull();
    else
        R=o, splitBySize(o->lc, k, L, R->lc), R->pull();
} // SZ(L) == k
int getRank(node *o) { // 1-base
    int r = SZ(o->lc) + 1;
    for (; o->pa; o = o->pa)
        if (o->pa->rc == o) r += SZ(o->pa->lc) + 1;
    return r;
} // namespace Treap

```

2.5 Linear Basis* [138d5d]

```

template <int BITS, typename S = int> struct Basis {
    static constexpr S MIN = numeric_limits<S>::min();
    array<pair<llu, S>, BITS> b;
    Basis() { b.fill({0, MIN}); }
    void add(llu x, S p) {
        for (int i = BITS-1; i>=0; i--) if (x >> i & 1) {
            if (b[i].first == 0) return b[i]={x, p}, void();
            if (b[i].second < p)
                swap(b[i].first, x), swap(b[i].second, p);
            x ^= b[i].first;
        }
    }
    optional<llu> query_kth(llu v, llu k) {
        vector<pair<llu, int>> o;
        for (int i = 0; i < BITS; i++)
            if (b[i].first) o.emplace_back(b[i].first, i);
        if (k >= (1ULL << o.size())) return {};
        for (int i = int(o.size()) - 1; i >= 0; i--)
            if ((k >> i & 1) ^ (v >> o[i].second & 1))
                v ^= o[i].first;
        return v;
    }
    Basis filter(S l) {
        Basis res = *this;
        for (int i = 0; i < BITS; i++)
            if (res.b[i].second < l) res.b[i] = {0, MIN};
        return res;
    }
};

```

2.6 <atcoder/lazysegtree>* [e78041]

```

template <typename S, auto op, auto e,
          typename F, auto mapping, auto composition, auto id>
struct lazy_segtree {
    int n, sz, lg; vector<S> d; vector<F> lz;
    void upd(int i, F f) {
        d[i] = mapping(f, d[i]);
        if (i < sz) lz[i] = composition(f, lz[i]);
    }
    void pull(int p) {
        while (p >= 1) {
            d[p] = op(d[p << 1], d[p << 1 | 1]);
            d[p] = mapping(lz[p], d[p]);
        }
    }
    void push(int p) {
        for (int h = lg; h >= 0; h--)
            if (int i = p >> h; i > 1) {
                upd(i, lz[i >> 1]);
                upd(i ^ 1, lz[i >> 1]);
                lz[i >> 1] = id();
            }
    }
    void set(int p, S v) {
        assert(0 <= p && p < n);
        p += sz, push(p), d[p] = v, pull(p);
    }
    S get(int p) {
        assert(0 <= p && p < n);
        return p += sz, push(p), d[p];
    }
    void apply(int l, int r, F f) {
        assert(0 <= l && l < r && r <= n);
        int tl = l, tr = r;
        push(l + sz), push(r - 1 + sz);

```

```

        for (l += sz, r += sz; l < r; l >>= 1, r >>= 1) {
            if (l & 1) upd(l++, f);
            if (r & 1) upd(--r, f);
        }
        pull(tl + sz), pull(tr - 1 + sz);
    }
    S prod(int l, int r) {
        assert(0 <= l && l < r && r <= n);
        push(l + sz), push(r - 1 + sz);
        S resl = e(), resr = e();
        for (l += sz, r += sz; l < r; l >>= 1, r >>= 1) {
            if (l & 1) resl = op(resl, d[l++]);
            if (r & 1) resr = op(d[--r], resr);
        }
        return op(resl, resr);
    }
    S all_prod() const { return d[1]; }
    lazy_segtree(const vector<S> &v) : n((int)v.size()),
        sz((int)bit_ceil(v.size())), lg(_lg(sz)),
        d(sz * 2, e()), lz(sz, id()) {
        for (int i = 0; i < n; i++)
            d[i + sz] = v[i];
        for (int i = sz - 1; i > 0; i--)
            d[i] = op(d[i << 1], d[i << 1 | 1]);
    }
};

```

// <https://judge.yosupo.jp/submission/247007>

// <https://judge.yosupo.jp/submission/247009>

2.7 Binary Search on Segtree [6c61c0]

```

// find_first = l -> minimal x s.t. check( [l, x) )
// find_last = r -> maximal x s.t. check( [x, r) )
int find_first(int l, auto &&check) {
    if (l >= n) return n + 1;
    l += sz; push(l); Monoid sum; // identity
    do {
        while ((l & 1) == 0) l >>= 1;
        if (auto s = sum + nd[l]; check(s)) {
            while (l < sz) {
                prop(l); l = (l << 1);
                if (auto nxt = sum + nd[l]; not check(nxt))
                    sum = nxt, l++;
            }
            return l + 1 - sz;
        } else sum = s, l++;
    } while (lowbit(l) != l);
    return n + 1;
}
int find_last(int r, auto &&check) {
    if (r <= 0) return -1;
    r += sz; push(r - 1); Monoid sum; // identity
    do {
        r--;
        while (r > 1 and (r & 1)) r >>= 1;
        if (auto s = nd[r] + sum; check(s)) {
            while (r < sz) {
                prop(r); r = (r << 1) | 1;
                if (auto nxt = nd[r] + sum; not check(nxt))
                    sum = nxt, r--;
            }
            return r - sz;
        } else sum = s;
    } while (lowbit(r) != r);
    return -1;
}

```

2.8 Interval Container* [edce47]

```

set<pii>::iterator addInterval(set<pii>& is, int L, int
    R) {
    if (L == R) return is.end();
    auto it = is.lower_bound({L, R}), before = it;
    while (it != is.end() && it->first <= R) {
        R = max(R, it->second);
        before = it = is.erase(it);
    }
    if (it != is.begin() && (--it)->second >= L) {
        L = min(L, it->first);
        R = max(R, it->second);
        is.erase(it);
    }
    return is.insert(before, {L, R});
}
void removeInterval(set<pii>& is, int L, int R) {
    if (L == R) return;

```

```

auto it = addInterval(is, L, R);
auto r2 = it->second;
if (it->first == L) is.erase(it);
else (int&)it->second = L;
if (R != r2) is.emplace(R, r2);
}

```

3 Graph

3.1 SCC (1RZck)* [d48cfe]

```

struct SCC {
    int n, cnt = 0, cur = 0;
    vector<int> id, dfn, low, stk;
    vector<vector<int>> adj, comps;
    void addEdge(int u, int v) { adj[u].push_back(v); }
    SCC(int n) : n(n), id(n, -1), dfn(n, -1), low(n, -1),
        adj(n) {}
    void build() {
        auto dfs = [&](auto dfs, int u) -> void {
            dfn[u] = low[u] = cur++;
            stk.push_back(u);
            for (auto v : adj[u]) {
                if (dfn[v] == -1) {
                    dfs(dfs, v);
                    low[u] = min(low[u], low[v]);
                } else if (id[v] == -1) {
                    low[u] = min(low[u], dfn[v]);
                }
            }
            if (dfn[u] == low[u]) {
                int v;
                comps.emplace_back();
                do {
                    v = stk.back();
                    comps.back().push_back(v);
                    id[v] = cnt;
                    stk.pop_back();
                } while (u != v);
                cnt++;
            }
        };
        for (int i = 0; i < n; i++) { if (dfn[i] == -1) { dfs(dfs, i); } }
        for (int i = 0; i < n; i++) { id[i] = cnt - 1 - id[i]; }
        reverse(comps.begin(), comps.end());
    }
    // the comps are in topological sorted order
};

```

3.2 2-SAT (1RZck)* [196934]

```

struct TwoSat {
    int n, N;
    vector<vector<int>> adj;
    vector<int> ans;
    TwoSat(int n) : n(n), N(n), adj(2 * n) {}
    // u == x
    void addClause(int u, bool x) { adj[2 * u + !x].push_back(2 * u + x); }
    // u == x || v == y
    void addClause(int u, bool x, int v, bool y) {
        adj[2 * u + !x].push_back(2 * v + y);
        adj[2 * v + !y].push_back(2 * u + x);
    }
    // u == x -> v == y
    void addImPLY(int u, bool x, int v, bool y) {
        addClause(u, !x, v, y);
    }
    void addVar() {
        adj.emplace_back(), adj.emplace_back();
        N++;
    }
    // at most one in var is true
    // adds prefix or as supplementary variables
    void atMostOne(const vector<pair<int, bool>> &vars) {
        int sz = vars.size();
        for (int i = 0; i < sz; i++) {
            addVar();
            auto [u, x] = vars[i];
            addImPLY(u, x, N - 1, true);
            if (i > 0) {
                addImPLY(N - 2, true, N - 1, true);
                addClause(u, !x, N - 2, false);
            }
        }
    }
};

```

```

}
// does not return supplementary variables from atMostOne()
bool satisfiable() {
    // run tarjan scc on 2 * N
    for (int i = 0; i < 2 * N; i++) { if (dfn[i] == -1) { dfs(dfs, i); } }
    for (int i = 0; i < N; i++) { if (id[2 * i] == id[2 * i + 1]) { return false; } }
    ans.resize(n);
    for (int i = 0; i < n; i++) { ans[i] = id[2 * i] > id[2 * i + 1]; }
    return true;
}
};

```

3.3 BCC [6ac6db]

```

class BCC {
    int n, ecnt, bcnt;
    vector<vector<pair<int, int>>> g;
    vector<int> dfn, low, bcc, stk;
    vector<bool> ap, bridge;
    void dfs(int u, int f) {
        dfn[u] = low[u] = dfn[f] + 1;
        int ch = 0;
        for (auto [v, t] : g[u]) if (bcc[t] == -1) {
            bcc[t] = 0; stk.push_back(t);
            if (dfn[v]) {
                low[u] = min(low[u], dfn[v]);
                continue;
            }
            ++ch, dfs(v, u);
            low[u] = min(low[u], low[v]);
            if (low[v] > dfn[u]) bridge[t] = true;
            if (low[v] < dfn[u]) continue;
            ap[u] = true;
            while (not stk.empty()) {
                int o = stk.back(); stk.pop_back();
                bcc[o] = bcnt;
                if (o == t) break;
            }
            bcnt += 1;
        }
        ap[u] = ap[u] and (ch != 1 or u != f);
    }
public:
    BCC(int n_) : n(n_), ecnt(0), bcnt(0), g(n), dfn(n),
        low(n), stk(), ap(n) {}
    void addEdge(int u, int v) {
        g[u].emplace_back(v, ecnt);
        g[v].emplace_back(u, ecnt++);
    }
    void solve() {
        bridge.assign(ecnt, false); bcc.assign(ecnt, -1);
        for (int i = 0; i < n; ++i) if (!dfn[i]) dfs(i, i);
    }
    int bcc_id(int x) const { return bcc[x]; }
    bool is_ap(int x) const { return ap[x]; }
    bool is_bridge(int x) const { return bridge[x]; }
};

```

3.4 Round Square Tree [cf6d74]

```

struct RST { // be careful about isolate point
    int n; vector<vector<int>> T;
    RST(auto &G) : n(int(G.size())), T(n) {
        vector<int> stk, vis(n), low(n);
        auto dfs = [&](auto self, int u, int d) -> void {
            low[u] = vis[u] = d; stk.push_back(u);
            for (int v : G[u]) if (!vis[v]) {
                self(self, v, d + 1);
                if (low[v] == vis[u]) {
                    int cnt = int(T.size()); T.emplace_back();
                    for (int x = -1; x != v; stk.pop_back())
                        T[cnt].push_back(x = stk.back());
                    T[u].push_back(cnt); // T is rooted
                } else low[u] = min(low[u], low[v]);
            } else low[u] = min(low[u], vis[v]);
        };
        for (int u = 0; u < n; u++)
            if (!vis[u]) dfs(dfs, u, 1);
    } // T may be forest; after dfs, stk are the roots
}; // test @ 2020 Shanghai K

```

3.5 Edge TCC [5a2668]


```
vector<vector<int>> ETCC(auto &adj) {
    const int n = static_cast<int>(adj.size());
    vector<int> up(n), low(n), in, out, nx, id;
    in = out = nx = id = vector<int>(n, -1);
    int dfc = 0, cnt = 0; Dsu dsu(n);
    auto merge = [&](int u, int v) {
        dsu.join(u, v); up[u] += up[v]; };
    auto dfs = [&](auto self, int u, int p) -> void {
        in[u] = low[u] = dfc++;
        for (int v : adj[u]) if (v != u) {
            if (v == p) { p = -1; continue; }
            if (in[v] == -1) {
                self(self, v, u);
                if (nx[v] == -1 && up[v] <= 1) {
                    up[u] += up[v]; low[u] = min(low[u], low[v]);
                    continue;
                }
                if (up[v] == 0) v = nx[v];
                if (low[u] > low[v])
                    low[u] = low[v], swap(nx[u], v);
                for (; v != -1; v = nx[v]) merge(u, v);
            } else if (in[v] < in[u]) {
                low[u] = min(low[u], in[v]); up[u]++;
            } else {
                for (int &x = nx[u]; x != -1 &&
                    in[x] <= in[v] && in[v] < out[x]; x = nx[x])
                    merge(u, x);
                up[u]--;
            }
        }
        out[u] = dfc;
    };
    for (int i = 0; i < n; i++)
        if (in[i] == -1) dfs(dfs, i, -1);
    for (int i = 0; i < n; i++)
        if (dsu.anc(i) == i) id[i] = cnt++;
    vector<vector<int>> comps(cnt);
    for (int i = 0; i < n; i++)
        comps[id[dsu.anc(i)]] .push_back(i);
    return comps;
} // test @ yosupo judge
```

3.6 Bipolar Orientation [b50cd3]

```
struct BipolarOrientation {
    int n; vector<vector<int>> g;
    vector<int> vis, low, pa, sgn, ord;
    BipolarOrientation(int n_) : n(n_),
        g(n), vis(n), low(n), pa(n, -1), sgn(n) {}
    void dfs(int i) {
        ord.push_back(i); low[i] = vis[i] = int(ord.size());
        for (int j : g[i])
            if (!vis[j])
                pa[j] = i, dfs(j), low[i] = min(low[i], low[j]);
            else low[i] = min(low[i], vis[j]);
    }
    vector<int> solve(int S, int T) {
        g[S].insert(g[S].begin(), T); dfs(S);
        vector<int> nxt(n + 1, n), prv = nxt;
        nxt[S] = T; prv[T] = S; sgn[S] = -1;
        for (int i : ord) if (i != S && i != T) {
            int p = pa[i], l = ord[low[i] - 1];
            if (sgn[l] > 0) // insert after
                nxt[i] = nxt[prv[i] = p], nxt[p] = prv[nxt[p]] = i;
            else
                prv[i] = prv[nxt[i] = p], prv[p] = nxt[prv[p]] = i;
            sgn[p] = -sgn[l];
        }
        vector<int> v;
        for (int x = S; x != n; x = nxt[x]) v.push_back(x);
        return v;
    } // S, T are unique source / unique sink
    void add_edge(int a, int b) {
        g[a].emplace_back(b); g[b].emplace_back(a);
    }; // 存在 ST 雙極定向 iff 連接 (S,T) 後整張圖點雙連通
```

3.7 DMST [f4317e]

```
using lld = int64_t;
struct E { int s, t; lld w; }; // 0-base
struct PQ {
    struct P {
        lld v; int i;
        bool operator<(const P &b) const { return v > b.v; }
    };
    min_heap<P> pq; lld tag;
```

```
void push(P p) { p.v -= tag; pq.emplace(p); }
P top() { P p = pq.top(); p.v += tag; return p; }
void join(PQ &b) {
    if (pq.size() < b.pq.size())
        swap(pq, b.pq), swap(tag, b.tag);
    while (!b.pq.empty()) push(b.top()), b.pq.pop();
};
vector<int> dmst(const vector<E> &e, int n, int root) {
    vector<PQ> h(n * 2);
    for (int i = 0; i < int(e.size()); ++i)
        h[e[i].t].push({e[i].w, i});
    vector<int> a(n * 2); iota(all(a), 0);
    vector<int> v(n * 2, -1), pa(n * 2, -1), r(n * 2);
    auto o = [&](auto Y, int x) -> int {
        return x == a[x] ? x : a[x] = Y(Y, a[x]); };
    auto S = [&](int i) { return o(o, e[i].s); };
    int pc = v[root] = n;
    for (int i = 0; i < n; ++i) if (v[i] == -1)
        for (int p = i; v[p] < 0 || v[p] == i; p = S(r[p])) {
            if (v[p] == i)
                for (int q = pc++; p != q; p = S(r[p])) {
                    h[p].tag -= h[p].top().v; h[q].join(h[p]);
                    pa[p] = a[p] = q;
                }
            while (S(h[p].top().i) == p) h[p].pq.pop();
            v[p] = i; r[p] = h[p].top().i;
        }
    vector<int> ans;
    for (int i = pc - 1; i >= 0; i--) if (v[i] != n) {
        for (int f = e[r[i]].t; f != -1 && v[f] != n; f = pa[f])
            v[f] = n;
        ans.push_back(r[i]);
    }
    return ans; // default minimize, returns edgeid array
```

3.8 Dominator Tree [ea5b7c]

```
struct Dominator {
    vector<vector<int>> g, r, rdom; int tk;
    vector<int> dfn, rev, fa, sdom, dom, val, rp;
    Dominator(int n) : g(n), r(n), rdom(n), tk(0) {
        dfn = rev = fa = sdom = dom =
            val = rp = vector<int>(n, -1);
    }
    void add_edge(int x, int y) { g[x].push_back(y); }
    void dfs(int x) {
        rev[dfn[x] = tk] = x;
        fa[tk] = sdom[tk] = val[tk] = tk; tk++;
        for (int u : g[x]) {
            if (dfn[u] == -1) dfs(u), rp[dfn[u]] = dfn[x];
            r[dfn[u]].push_back(dfn[x]);
        }
    }
    void merge(int x, int y) { fa[x] = y; }
    int find(int x, int c = 0) {
        if (fa[x] == x) return c ? -1 : x;
        if (int p = find(fa[x], 1); p != -1) {
            if (sdom[val[x]] > sdom[val[fa[x]]])
                val[x] = val[fa[x]];
            fa[x] = p;
            return c ? p : val[x];
        } else return c ? fa[x] : val[x];
    }
    vector<int> build(int s, int n) {
        // return the father of each node in dominator tree
        dfs(s); // p[i] = -2 if i is unreachable from s
        for (int i = tk - 1; i >= 0; --i) {
            for (int u : r[i])
                sdom[i] = min(sdom[i], sdom[find(u)]);
            if (i) rdom[sdom[i]].push_back(i);
            for (int u : rdom[i]) {
                int p = find(u);
                dom[u] = (sdom[p] == i ? i : p);
            }
            if (i) merge(i, rp[i]);
        }
        vector<int> p(n, -2); p[s] = -1;
        for (int i = 1; i < tk; ++i)
            if (sdom[i] != dom[i]) dom[i] = dom[dom[i]];
        for (int i = 1; i < tk; ++i)
            p[rev[i]] = rev[dom[i]];
        return p;
    } // test @ yosupo judge
```

3.9 Edge Coloring [029763]

```
// max(d,u) + 1 edge coloring, time: O(NM)
int C[kN][kN], G[kN][kN]; // 1-based, G: ans
void clear(int N) {
    for (int i = 0; i <= N; i++)
        for (int j = 0; j <= N; j++)
            C[i][j] = G[i][j] = 0;
}
void solve(vector<pair<int, int>> &E, int N) {
    int X[kN] = {}, a;
    auto update = [&](int u) {
        for (X[u] = 1; C[u][X[u]]; X[u]++);
    };
    auto color = [&](int u, int v, int c) {
        int p = G[u][v];
        G[u][v] = G[v][u] = c;
        C[u][c] = v, C[v][c] = u;
        C[u][p] = C[v][p] = 0;
        if (p) X[u] = X[v] = p;
        else update(u), update(v);
        return p;
    };
    auto flip = [&](int u, int c1, int c2) {
        int p = C[u][c1];
        swap(C[u][c1], C[u][c2]);
        if (p) G[u][p] = G[p][u] = c2;
        if (!C[u][c1]) X[u] = c1;
        if (!C[u][c2]) X[u] = c2;
        return p;
    };
    for (int i = 1; i <= N; i++) X[i] = 1;
    for (int t = 0; t < E.size(); t++) {
        auto [u, v] = E[t];
        int v0 = v, c = X[u], c0 = c, d;
        vector<pair<int, int>> L; int vst[kN] = {};
        while (!G[u][v0]) {
            L.emplace_back(v, d = X[v]);
            if (!C[v][c]) for (a=L.size()-1; a>=0; a--)
                c = color(u, L[a].first, c);
            else if (!C[u][d]) for (a=L.size()-1; a>=0; a--)
                color(u, L[a].first, L[a].second);
            else if (vst[d]) break;
            else vst[d] = 1, v = C[u][d];
        }
        if (!G[u][v0]) {
            for (; v; v = flip(v, c, d), swap(c, d));
            if (C[u][c0]) { a = int(L.size()) - 1;
                while (--a >= 0 && L[a].second != c);
                for (; a>=0; a--) color(u, L[a].first, L[a].second);
            } else t--;
        }
    }
}
```

3.10 Centroid Decomp.* [670cdd]

```
class Centroid {
    vector<vector<pair<int, int>>> g; // g[u] = {(v, w)}
    vector<int> pa, dep, vis, sz, mx;
    vector<vector<int64_t>> Dist;
    vector<int64_t> Sub, Sub2;
    vector<int> Cnt, Cnt2;
    void DfsSz(vector<int> &tmp, int x) {
        vis[x] = true, sz[x] = 1, mx[x] = 0;
        for (auto [u, w] : g[x]) if (not vis[u]) {
            DfsSz(tmp, u); sz[x] += sz[u];
            mx[x] = max(mx[x], sz[u]);
        }
        tmp.push_back(x);
    }
    void DfsDist(int x, int64_t D = 0) {
        Dist[x].push_back(D); vis[x] = true;
        for (auto [u, w] : g[x])
            if (not vis[u]) DfsDist(u, D + w);
    }
    void DfsCen(int x, int D, int p) {
        vector<int> tmp; DfsSz(tmp, x);
        int M = int(tmp.size()), C = -1;
        for (int u : tmp)
            if (max(M - sz[u], mx[u]) * 2 <= M) C = u;
        for (int u : tmp) vis[u] = false;
        DfsDist(C);
        for (int u : tmp) vis[u] = false;
    }
};
```

```
pa[C] = p, vis[C] = true, dep[C] = D;
for (auto [u, w] : g[C])
    if (not vis[u]) DfsCen(u, D + 1, C);
}
public:
Centroid(int N) : g(N), pa(N), dep(N),
    vis(N), sz(N), mx(N), Dist(N),
    Sub(N), Sub2(N), Cnt(N), Cnt2(N) {}
void AddEdge(int u, int v, int w) {
    g[u].emplace_back(v, w);
    g[v].emplace_back(u, w);
}
void Build() { DfsCen(0, 0, -1); }
void Mark(int v) {
    int x = v, z = -1;
    for (int i = dep[v]; i >= 0; --i) {
        Sub[x] += Dist[v][i], Cnt[x]++;
        if (z != -1)
            Sub2[z] += Dist[v][i], Cnt2[z]++;
        x = pa[z = x];
    }
}
int64_t Query(int v) {
    int64_t res = 0;
    int x = v, z = -1;
    for (int i = dep[v]; i >= 0; --i) {
        res += Sub[x] + 1LL * Cnt[x] * Dist[v][i];
        if (z != -1)
            res -= Sub2[z] + 1LL * Cnt2[z] * Dist[v][i];
        x = pa[z = x];
    }
    return res;
}; // pa, dep are centroid tree attributes
3.11 Heavy-Light Decomp.* [c550b3]
struct HLD {
    int n, cur = 0;
    vector<int> sz, top, dep, par, tin, tout, seq;
    vector<vector<int>> adj;
    HLD(int n) : n(n), sz(n, 1), top(n), dep(n), par(n),
        tin(n), tout(n), seq(n), adj(n) {}
    void add_edge(int u, int v) { adj[u].push_back(v), adj[v].push_back(u); }
    void build(int root = 0) {
        top[root] = root, dep[root] = 0, par[root] = -1;
        dfs1(root), dfs2(root);
    }
    void dfs1(int u) {
        if (auto it = find(adj[u].begin(), adj[u].end(), par[u]); it != adj[u].end()) { adj[u].erase(it); }
        for (auto &v : adj[u]) {
            par[v] = u; dep[v] = dep[u] + 1; dfs1(v);
            sz[u] += sz[v];
            if (sz[v] > sz[adj[u][0]]) { swap(v, adj[u][0]); }
        }
    }
    void dfs2(int u) {
        tin[u] = cur++; seq[tin[u]] = u;
        for (auto v : adj[u]) { top[v] = v == adj[u][0] ? top[u] : v; dfs2(v); }
        tout[u] = cur;
    }
    int lca(int u, int v) {
        while (top[u] != top[v]) {
            if (dep[top[u]] > dep[top[v]]) { u = par[top[u]]; }
            else { v = par[top[v]]; }
        }
        return dep[u] < dep[v] ? u : v;
    }
    int dist(int u, int v) { return dep[u] + dep[v] - 2 * dep[lca(u, v)]; }
    int jump(int u, int k) {
        if (dep[u] < k) { return -1; }
        int d = dep[u] - k;
        while (dep[top[u]] > d) { u = par[top[u]]; }
        return seq[tin[u] - dep[u] + d];
    }
    // u is v's ancestor
    bool is_ancestor(int u, int v) { return tin[u] <= tin[v] && tin[v] < tout[u]; }
    // root's parent is itself
    int rooted_parent(int r, int u) {
```

```

if (r == u) { return u; }
if (is_ancestor(r, u)) { return par[u]; }
auto it = upper_bound(adj[u].begin(), adj[u].end(), r
, [&](int x, int y) {
    return tin[x] < tin[y];
}) - 1;
return *it;
}
// rooted at u, v's subtree size
int rooted_size(int r, int u) {
    if (r == u) { return n; }
    if (is_ancestor(u, r)) { return sz[u]; }
    return n - sz[rooted_parent(r, u)];
}
int rooted_lca(int r, int a, int b) { return lca(a, b)
    ^ lca(a, r) ^ lca(b, r); }
};

```

3.12 Virtual Tree [44f764]

```

vector<pair<int, int>> build(vector<int> vs, int r) {
    vector<pair<int, int>> res;
    sort(vs.begin(), vs.end(), [](int i, int j) {
        return dfn[i] < dfn[j]; });
    vector<int> s = {r};
    for (int v : vs) if (v != r) {
        if (int o = lca(v, s.back()); o != s.back()) {
            while (s.size() >= 2) {
                if (dfn[s[s.size() - 2]] < dfn[o]) break;
                res.emplace_back(s[s.size() - 2], s.back());
                s.pop_back();
            }
            if (s.back() != o)
                res.emplace_back(o, s.back()), s.back() = o;
        }
        s.push_back(v);
    }
    for (size_t i = 1; i < s.size(); ++i)
        res.emplace_back(s[i - 1], s[i]);
    return res; // (x, y): x->y
} // 記得建虛樹會多出 `vs` 以外的點

```

3.13 Tree Hashing [d6a9f9]

```

vector<int> g[maxn]; ll u h[maxn];
ll F(ll u) { // xorshift64star from iwiwi
    u ^= u >> 12; u ^= u << 25; u ^= u >> 27;
    return u * 2685821657736338717LL;
}
ll hsah(int u, int f) {
    ll r = 127; // bigger?
    for (int v : g[u]) if (v != f) r += hsah(v, u);
    return h[u] = F(r);
} // test @ UOJ 763 & yosupo library checker

```

3.14 Mo's Algo on Tree

```

dfs u:
    push u
    iterate subtree
    push u
Let P = LCA(u, v) with St(u) <= St(v)
if (P == u) query[St(u), St(v)]
else query[Ed(u), St(v)], query[St(P), St(P)]

```

3.15 Count Cycles [c7e8f2]

```

// ord = sort by deg decreasing, rk[ord[i]] = i
// D[i] = edge point from rk small to rk big
for (int x : ord) { // c3
    for (int y : D[x]) vis[y] = 1;
    for (int y : D[x]) for (int z : D[y]) c3 += vis[z];
    for (int y : D[x]) vis[y] = 0;
}
for (int x : ord) { // c4
    for (int y : D[x]) for (int z : adj[y])
        if (rk[z] > rk[x]) c4 += vis[z]++;
    for (int y : D[x]) for (int z : adj[y])
        if (rk[z] > rk[x]) --vis[z];
} // both are O(M*sqrt(M)), test @ 2022 CCPC guangzhou

```

3.16 Maximal Clique [2da556]

```

#define iter(u, B) for (size_t u = B._Find_first(); \
    u < n; u = B._Find_next(u))
// contain a self loop u to u, than u won't in clique
template <size_t maxn> class MaxClique {
private:
    using bits = bitset<maxn>;
    bits popped, G[maxn], ans;
    size_t deg[maxn], deo[maxn], n;

```

```

void sort_by_degree() {
    popped.reset();
    for (size_t i = 0; i < n; ++i) deg[i] = G[i].count();
    for (size_t i = 0; i < n; ++i) {
        size_t mi = maxn, id = 0;
        for (size_t j = 0; j < n; ++j)
            if (!popped[j] and deg[j] < mi) mi = deg[id = j];
        popped[deo[i] = id] = 1;
        iter(u, G[i]) --deg[u];
    }
}
void BK(bits R, bits P, bits X) {
    if (R.count() + P.count() <= ans.count()) return;
    if (not P.count() and not X.count()) {
        if (R.count() > ans.count()) ans = R;
        return;
    }
    /* greedily choose max degree as pivot
    bits cur = P | X; size_t pv = 0, sz = 0;
    iter(u, cur) if (deg[u] > sz) sz = deg[pv = u];
    cur = P & ~G[pv] & ~R; */ // or simply choose first
    bits cur = P & (~G[(P | X)._Find_first()]) & ~R;
    iter(u, cur) {
        R[u] = 1; BK(R, P & G[u], X & G[u]);
        R[u] = P[u] = 0, X[u] = 1;
    }
}
public:
void init(size_t n_) {
    n = n_; ans.reset();
    for (size_t i = 0; i < n; ++i) G[i].reset();
}
void add_edges(int u, bits S) { G[u] = S; }
void add_edge(int u, int v) { G[u][v] = G[v][u] = 1; }
int solve() {
    sort_by_degree(); // or simply iota( deo... )
    for (size_t i = 0; i < n; ++i) deg[i] = G[i].count();
    bits pob, nob = 0; pob.set();
    for (size_t i = n; i < maxn; ++i) pob[i] = 0;
    for (size_t i = 0; i < n; ++i) {
        size_t v = deo[i]; bits tmp; tmp[v] = 1;
        BK(tmp, pob & G[v], nob & G[v]);
        pob[v] = 0, nob[v] = 1;
    }
    return static_cast<int>(ans.count());
}
};

```

3.17 Maximum Clique [aee5d8]

```

constexpr size_t kN = 150; using bits = bitset<kN>;
struct MaxClique {
    bits G[kN], cs[kN];
    int ans, sol[kN], q, cur[kN], d[kN], n;
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i) G[i].reset();
    }
    void add_edge(int u, int v) { G[u][v] = G[v][u] = 1; }
    void pre_dfs(vector<int> &v, int i, bits mask) {
        if (i < 4) {
            for (int x : v) d[x] = (int)(G[x] & mask).count();
            sort(all(v), [&](int x, int y) {
                return d[x] > d[y]; });
        }
        vector<int> c(v.size());
        cs[1].reset(), cs[2].reset();
        int l = max(ans - q + 1, 1), r = 2, tp = 0, k;
        for (int p : v) {
            for (k = 1; (cs[k] & G[p]).any(); ++k);
            if (k >= r) cs[++r].reset();
            cs[k][p] = 1;
            if (k < l) v[tp++] = p;
        }
        for (k = l; k < r; ++k)
            for (auto p = cs[k]._Find_first();
                p < kN; p = cs[k]._Find_next(p))
                v[tp] = (int)p, c[tp] = k, ++tp;
        dfs(v, c, i + 1, mask);
    }
    void dfs(vector<int> &v, vector<int> &c,
        int i, bits mask) {
        while (!v.empty()) {
            int p = v.back(); v.pop_back(); mask[p] = 0;

```

```

    if (q + c.back() <= ans) return;
    cur[q++] = p;
    vector<int> nr;
    for (int x : v) if (G[p][x]) nr.push_back(x);
    if (!nr.empty()) pre_dfs(nr, i, mask & G[p]);
    else if (q > ans) ans = q, copy_n(cur, q, sol);
    c.pop_back(); --q;
}
}
int solve() {
    vector<int> v(n); iota(all(v), 0);
    ans = q = 0; pre_dfs(v, 0, bits(string(n, '1')));
    return ans; // sol[0 ~ ans-1]
}
} cliq; // test @ yosupo judge

```

3.18 Min Mean Cycle [e23bc0]

```

// WARNING: TYPE matters
struct Edge { int s, t; llf c; };
llf solve(vector<Edge> &e, int n) {
    // O(VE), returns inf if no cycle, mmc otherwise
    vector<VI> prv(n + 1, VI(n)), prve = prv;
    vector<vector<llf>> d(n + 1, vector<llf>(n, inf));
    d[0] = vector<llf>(n, 0);
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < (int)e.size(); j++) {
            auto [s, t, c] = e[j];
            if (d[i][s] < inf && d[i + 1][t] > d[i][s] + c) {
                d[i + 1][t] = d[i][s] + c;
                prv[i + 1][t] = s; prve[i + 1][t] = j;
            }
        }
    }
    llf mmc = inf; int st = -1;
    for (int i = 0; i < n; i++) {
        llf avg = -inf;
        for (int k = 0; k < n; k++) {
            if (d[n][i] < inf - eps)
                avg = max(avg, (d[n][i] - d[k][i]) / (n - k));
            else avg = inf;
        }
        if (avg < mmc) tie(mmc, st) = tie(avg, i);
    }
    if (st == -1) return inf;
    vector<int> vst(n), eid, cycle, rho;
    for (int i = n; !vst[st]; st = prv[i--][st]) {
        vst[st]++; eid.emplace_back(prve[i][st]);
        rho.emplace_back(st);
    }
    while (vst[st] != 2) {
        int v = rho.back(); rho.pop_back();
        cycle.emplace_back(v); vst[v]++;
    }
    reverse(all(eid)); eid.resize(cycle.size());
    return mmc;
}

```

3.19 Eulerian Trail [8a70bf]

```

// g[i] = list of (edge.to, edge.id)
auto euler(int N, int M, int S, const auto &g) {
    vector<int> iter(N), vis(M), vv, ee;
    auto dfs = [&](auto self, int i) -> void {
        while (iter[i] < ssize(g[i])) {
            auto [j, eid] = g[i][iter[i]++];
            if (vis[eid]) continue;
            vis[eid] = true; self(self, j);
            vv.push_back(j); ee.push_back(eid);
        }
    };
    dfs(dfs, S); vv.push_back(S);
    reverse(all(vv)); reverse(all(ee));
    return pair{vv, ee};
} // 需要保證傳入的 g, S degree 符合條件; 小心孤點奇點

```

4 Flow & Matching

4.1 HopcroftKarp* [397c39]

```

struct HK {
    vector<int> l, r, d, p; int ans;
    HK(int n, int m, auto &g) : l(n, -1), r(m, -1), ans(0) {
        while (true) {
            queue<int> q; d.assign(n, -1);
            for (int i = 0; i < n; i++)
                if (l[i] == -1) q.push(i), d[i] = 0;
            while (!q.empty()) {

```

```

                int x = q.front(); q.pop();
                for (int y : g[x])
                    if (r[y] != -1 && d[r[y]] == -1)
                        d[r[y]] = d[x] + 1, q.push(r[y]);
            }
            bool match = false;
            for (int i = 0; i < n; i++)
                if (l[i] == -1 && dfs(g, i)) ++ans, match = true;
            if (!match) break;
        }
    }
    bool dfs(const auto &g, int x) {
        for (int y : g[x]) if (r[y] == -1 ||
            (d[r[y]] == d[x] + 1 && dfs(g, r[y])))
            return l[x] = y, r[y] = x, d[x] = -1, true;
        return d[x] = -1, false;
    }
};

```

4.2 Kuhn Munkres [74bf6d]

```

struct KM { // maximize, test @ UOJ 80
    int n, l, r; llf ans; // fl and fr are the match
    vector<llf> hl, hr; vector<int> fl, fr, pre, q;
    void bfs(const auto &w, int s) {
        vector<int> vl(n), vr(n); vector<llf> slk(n, INF);
        l = r = 0; vr[q[r++] = s] = true;
        auto check = [&](int x) -> bool {
            if (vl[x] || slk[x] > 0) return true;
            vl[x] = true; slk[x] = INF;
            if (fl[x] != -1) return (vr[q[r++] = fl[x]] = true);
            while (x != -1) swap(x, fr[fl[x] = pre[x]]);
            return false;
        };
        while (true) {
            while (l < r)
                for (int x = 0, y = q[l++]; x < n; ++x) if (!vl[x])
                    if (chmin(slk[x], hl[x] + hr[y] - w[x][y]))
                        if (pre[x] = y, !check(x)) return;
            llf d = ranges::min(slk);
            for (int x = 0; x < n; ++x)
                vl[x] ? hl[x] += d : slk[x] -= d;
            for (int x = 0; x < n; ++x) if (vr[x]) hr[x] -= d;
            for (int x = 0; x < n; ++x) if (!check(x)) return;
        }
    }
    KM(int n_, const auto &w) : n(n_), ans(0),
        hl(n), hr(n), fl(n, -1), fr(fr), pre(n), q(n) {
        for (int i = 0; i < n; ++i) hl[i] = ranges::max(w[i]);
        for (int i = 0; i < n; ++i) bfs(w, i);
        for (int i = 0; i < n; ++i) ans += w[i][fl[i]];
    }
}; // find maximum perfect matching
// To obtain the max match of exactly K edges for
// K = 1 ... N, initialize hl[i] = INF and bfs from all
// unmatched right part point (fr[i] == -1)

```

4.3 Flow Models

- Maximum/Minimum flow with lower bound / Circulation problem
 - Construct super source S and sink T .
 - For each edge (x, y, l, u) , connect $x \rightarrow y$ with capacity $u - l$.
 - For each vertex v , denote by $in(v)$ the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.
 - If $in(v) > 0$, connect $S \rightarrow v$ with capacity $in(v)$, otherwise, connect $v \rightarrow T$ with capacity $-in(v)$.
 - To maximize, connect $t \rightarrow s$ with capacity ∞ (skip this in circulation problem), and let f be the maximum flow from S to T . If $f \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, the maximum flow from s to t is the answer. Also, f is a mincost valid flow.
 - To minimize, let f be the maximum flow from S to T . Connect $t \rightarrow s$ with capacity ∞ and let the flow from S to T be f' . If $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, f' is the answer.
 - The solution of each edge e is $l_e + f_e$, where f_e corresponds to the flow of edge e on the graph.
- Construct minimum vertex cover from maximum matching M on bipartite graph (X, Y)
 - Redirect every edge: $y \rightarrow x$ if $(x, y) \in M$, $x \rightarrow y$ otherwise.
 - Dfs from unmatched vertices in X .
 - $x \in X$ is chosen iff x is unvisited; $y \in Y$ is chosen iff y is visited.
- Minimum cost cyclic flow
 - Construct super source S and sink T
 - For each edge (x, y, c) , connect $x \rightarrow y$ with $(cost, cap) = (c, 1)$ if $c > 0$, otherwise connect $y \rightarrow x$ with $(cost, cap) = (-c, 1)$
 - For each edge with $c < 0$, sum these cost as K , then increase $d(y)$ by 1, decrease $d(x)$ by 1
 - For each vertex v with $d(v) > 0$, connect $S \rightarrow v$ with $(cost, cap) = (0, d(v))$
 - For each vertex v with $d(v) < 0$, connect $v \rightarrow T$ with $(cost, cap) = (0, -d(v))$

- Flow from S to T , the answer is the cost of the flow $C + K$
- Maximum density induced subgraph
 - Binary search on answer, suppose we're checking answer T
 - Construct a max flow model, let K be the sum of all weights
 - Connect source $s \rightarrow v, v \in G$ with capacity K
 - For each edge (u, v, w) in G , connect $u \rightarrow v$ and $v \rightarrow u$ with capacity w
 - For $v \in G$, connect it with sink $v \rightarrow t$ with capacity $K + 2T - \left(\sum_{e \in E(v)} w(e)\right) - 2w(v)$
- T is a valid answer if the maximum flow $f < K|V|$
- Minimum weight edge cover
 - For each $v \in V$ create a copy v' , and connect $u' \rightarrow v'$ with weight $w(u, v)$.
 - Connect $v \rightarrow v'$ with weight $2\mu(v)$, where $\mu(v)$ is the cost of the cheapest edge incident to v .
 - Find the minimum weight perfect matching on G' .
- Project selection cheat sheet: S, T 分別代表 0, 1 側, 最小化總花費。

i 為 0 時花費 c	(i, T, c)
i 為 1 時花費 c	(S, i, c)
$i \in I$ 有任何一個為 0 時花費 c	$(i, w, \infty), (w, T, c)$
$i \in I$ 有任何一個為 1 時花費 c	$(S, w, c), (w, i, \infty)$
i 為 0 時得到 c	直接得到 $c; (S, i, c)$
i 為 1 時得到 c	直接得到 $c; (i, T, c)$
i 為 0, j 為 1 時花費 c	(i, j, c)
i, j 不同時花費 c	$(i, j, c), (j, i, c)$
i, j 同時是 0 時得到 c	直接得到 $c; (S, w, c), (w, i, \infty), (w, j, \infty)$
i, j 同時是 1 時得到 c	直接得到 $c; (i, w, \infty), (j, w, \infty), (w, T, c)$
- Submodular functions minimization
 - For a function $f: 2^V \rightarrow \mathbb{R}$, f is a submodular function iff
 - $\forall S, T \subseteq V, f(S) + f(T) \geq f(S \cup T) + f(S \cap T)$, or
 - $\forall X \subseteq Y \subseteq V, x \notin Y, f(X \cup \{x\}) - f(X) \geq f(Y \cup \{x\}) - f(Y)$.
 - To minimize $\sum_i \theta_i(x_i) + \sum_{i < j} \phi_{ij}(x_i, x_j) + \sum_{i < j < k} \psi_{ijk}(x_i, x_j, x_k)$
 - If $\theta_i(1) \geq \theta_i(0)$, add edge $(S, i, \theta_i(1) - \theta_i(0))$ and $\theta_i(0)$ to answer; otherwise, $(i, T, \theta_i(0) - \theta_i(1))$ and $\theta_i(1)$.
 - Add edges $(i, j, \phi_{ij}(0, 1) + \phi_{ij}(1, 0) - \phi_{ij}(0, 0) - \phi_{ij}(1, 1))$.
 - Denote x_{ijk} as helper nodes. Let $P = \psi_{ijk}(0, 0, 0) + \psi_{ijk}(0, 1, 1) + \psi_{ijk}(1, 0, 1) + \psi_{ijk}(1, 1, 0) - \psi_{ijk}(0, 0, 1) - \psi_{ijk}(0, 1, 0) - \psi_{ijk}(1, 0, 0) - \psi_{ijk}(1, 1, 1)$. Add $-P$ to answer. If $P \geq 0$, add edges $(i, x_{ijk}, P), (j, x_{ijk}, P), (k, x_{ijk}, P), (x_{ijk}, T, P)$; otherwise $(x_{ijk}, i, -P), (x_{ijk}, j, -P), (x_{ijk}, k, -P), (S, x_{ijk}, -P)$.
 - The minimum cut of this graph will be the the minimum value of the function above.

4.4 Dinic [32c53e]

```
template <typename Cap> struct Dinic {
private:
    struct E { int to; rev; Cap cap; }; int n, st, ed;
    vector<vector<E>> G; vector<size_t> lv, idx;
    bool BFS(int k) {
        lv.assign(n, 0); idx.assign(n, 0);
        queue<int> bfs; bfs.push(st); lv[st] = 1;
        while (not bfs.empty() and not lv[ed]) {
            int u = bfs.front(); bfs.pop();
            for (auto e: G[u]) if (e.cap >> k and !lv[e.to])
                bfs.push(e.to), lv[e.to] = lv[u] + 1;
        }
        return lv[ed];
    }
    Cap DFS(int u, Cap f = numeric_limits<Cap>::max()) {
        if (u == ed) return f;
        Cap ret = 0;
        for (auto &i = idx[u]; i < G[u].size(); ++i) {
            auto &[to, rev, cap] = G[u][i];
            if (cap <= 0 or lv[to] != lv[u] + 1) continue;
            Cap nf = DFS(to, min(f, cap));
            ret += nf; cap -= nf; f -= nf;
            G[to][rev].cap += nf;
            if (f == 0) return ret;
        }
        if (ret == 0) lv[u] = 0;
        return ret;
    }
public:
    void init(int n_) { G.assign(n = n_, vector<E>()); }
    void add_edge(int u, int v, Cap c) {
        G[u].push_back({v, int(G[v].size()), c});
        G[v].push_back({u, int(G[u].size())-1, 0});
    }
    Cap max_flow(int st_, int ed_) {
        st = st_, ed = ed_; Cap ret = 0;
        for (int i = 63; i >= 0; --i)
            while (BFS(i)) ret += DFS(st);
        return ret;
    }
}; // test @ luogu P3376
```

4.5 Global Min-Cut [ae7013]

```
void add_edge(auto &w, int u, int v, int c) {
    w[u][v] += c; w[v][u] += c; }
auto phase(const auto &w, int n, vector<int> id) {
```

```
vector<ll> g(n); int s = -1, t = -1;
while (!id.empty()) {
    int c = -1;
    for (int i: id) if (c == -1 || g[i] > g[c]) c = i;
    s = t; t = c;
    id.erase(ranges::find(id, c));
    for (int i: id) g[i] += w[c][i];
}
return tuple{s, t, g[t]};
}
ll mincut(auto w, int n) {
    ll cut = numeric_limits<ll>::max();
    vector<int> id(n); iota(all(id), 0);
    for (int i = 0; i < n - 1; ++i) {
        auto [s, t, gt] = phase(w, n, id);
        id.erase(ranges::find(id, t));
        cut = min(cut, gt);
        for (int j = 0; j < n; ++j)
            w[s][j] += w[t][j], w[j][s] += w[j][t];
    }
    return cut;
} // O(V^3), can be O(VE + V^2 log V)?
```

4.6 GomoryHu Tree [245ce3]

```
auto GomoryHu(int n, const auto &flow) {
    vector<tuple<int, int, int>> rt; vector<int> g(n);
    for (int i = 1; i < n; ++i) {
        int t = g[i]; auto f = flow;
        rt.emplace_back(f.max_flow(i, t), i, t);
        f.walk(i); // bfs from i use edges with .cap > 0
        for (int j = i + 1; j < n; ++j)
            if (g[j] == t && f.connect(j)) g[j] = i;
    }
    return rt;
} // for our dinic:
// void walk(int) { BFS(0); }
// bool connect(int i) { return lv[i]; }
```

4.7 MCMF [0df510]

```
template <typename F, typename C> class MCMF {
    static constexpr F INF_F = numeric_limits<F>::max();
    static constexpr C INF_C = numeric_limits<C>::max();
    struct E { int to, r; F f; C c; };
    vector<vector<E>> G; vector<pair<int, int>> f;
    vector<int> inq; vector<F> up; vector<C> d;
    optional<pair<F, C>> step(int S, int T) {
        queue<int> q;
        for (q.push(S), d[S] = 0, up[S] = INF_F;
            not q.empty(); q.pop()) {
            int u = q.front(); inq[u] = false;
            if (up[u] == 0) continue;
            for (int i = 0; i < int(G[u].size()); ++i) {
                auto e = G[u][i]; int v = e.to;
                if (e.f <= 0 or d[v] <= d[u] + e.c) continue;
                d[v] = d[u] + e.c; f[v] = {u, i};
                up[v] = min(up[u], e.f);
                if (not inq[v]) q.push(v);
                inq[v] = true;
            }
        }
        if (d[T] == INF_C) return nullopt;
        for (int i = T; i != S; i = f[i].first) {
            auto &eg = G[f[i].first][f[i].second];
            eg.f -= up[T]; g[eg.to][eg.r].f += up[T];
        }
        return pair{up[T], d[T]};
    }
public:
    MCMF(int n) : G(n), f(n), inq(n), up(n), d(n, INF_C) {}
    void add_edge(int s, int t, F c, C w) {
        G[s].emplace_back(t, int(G[t].size()), c, w);
        G[t].emplace_back(s, int(G[s].size()) - 1, 0, -w);
    }
    pair<F, C> solve(int a, int b) {
        F c = 0; C w = 0;
        while (auto r = step(a, b)) {
            c += r->first, w += r->first * r->second;
            ranges::fill(inq, false); ranges::fill(d, INF_C);
        }
        return {c, w};
    }
};
```

4.8 Dijkstra Cost Flow [d0cfd9]

```

template <typename F, typename C> class MCMF {
    static constexpr F INF_F = numeric_limits<F>::max();
    static constexpr C INF_C = numeric_limits<C>::max();
    struct E { int to; F f; C c; };
    vector<vector<E>> g; vector<pair<int, int>> f;
    vector<F> up; vector<C> d, h;
    optional<pair<F, C>> step(int S, int T) {
        priority_queue<pair<C, int>> q;
        q.emplace(d[S] = 0, S), up[S] = INF_F;
        while (not q.empty()) {
            auto [l, u] = q.top(); q.pop();
            if (up[u] == 0 or l != -d[u]) continue;
            for (int i = 0; i < int(g[u].size()); ++i) {
                auto e = g[u][i]; int v = e.to;
                auto nd = d[u] + e.c + h[u] - h[v];
                if (e.f <= 0 or d[v] <= nd) continue;
                f[v] = {u, i}; up[v] = min(up[u], e.f);
                q.emplace(-(d[v] = nd), v);
            }
        }
        if (d[T] == INF_C) return nullopt;
        for (size_t i = 0; i < d.size(); ++i) h[i] += d[i];
        for (int i = T; i != S; i = f[i].first) {
            auto &eg = g[f[i].first][f[i].second];
            eg.f -= up[T]; g[eg.to][eg.r].f += up[T];
        }
        return pair{up[T], h[T]};
    }
public:
    MCMF(int n) : g(n), f(n), up(n), d(n, INF_C) {}
    void add_edge(int s, int t, F c, C w) {
        g[s].emplace_back(t, int(g[t].size()), c, w);
        g[t].emplace_back(s, int(g[s].size()) - 1, 0, -w);
    }
    pair<F, C> solve(int a, int b) {
        h.assign(g.size(), 0);
        F c = 0; C w = 0;
        while (auto r = step(a, b)) {
            c += r->first, w += r->first * r->second;
            fill(d.begin(), d.end(), INF_C);
        }
        return {c, w};
    }
};

```

4.9 Min Cost Circulation [ea0477]

```

template <typename F, typename C>
struct MinCostCirculation {
    struct ep { int to; F flow; C cost; };
    int n; vector<int> vis; int visc;
    vector<int> fa, fae; vector<vector<int>> g;
    vector<ep> e; vector<C> pi;
    MinCostCirculation(int n) : n(n), vis(n), visc(0), g(n), pi(n) {}
    void add_edge(int u, int v, F fl, C cs) {
        g[u].emplace_back((int)e.size(), (int)e.size(), fl, cs);
        e.emplace_back(v, fl, cs);
        g[v].emplace_back((int)e.size(), (int)e.size(), 0, -cs);
        e.emplace_back(u, 0, -cs);
    }
    C phi(int x) {
        if (fa[x] == -1) return 0;
        if (vis[x] == visc) return pi[x];
        vis[x] = visc;
        return pi[x] = phi(fa[x]) - e[fae[x]].cost;
    }
    int lca(int u, int v) {
        for (; u != -1 || v != -1; swap(u, v)) if (u != -1) {
            if (vis[u] == visc) return u;
            vis[u] = visc; u = fa[u];
        }
        return -1;
    }
    void pushflow(int x, C &cost) {
        int v = e[x ^ 1].to, u = e[x].to; ++visc;
        if (int w = lca(u, v); w == -1) {
            while (v != -1)
                swap(x ^= 1, fae[v]), swap(u, fa[v]), swap(u, v);
        } else {
            int z = u, dir = 0; F f = e[x].flow;
            vector<int> cyc = {x};
            for (int d : {0, 1})
                for (int i = (d ? u : v); i != w; i = fa[i]) {

```

```

                    cyc.push_back(fae[i] ^ d);
                    if (chmin(f, e[fae[i] ^ d].flow)) z = i, dir = d;
                }
            }
            for (int i : cyc) {
                e[i].flow -= f; e[i ^ 1].flow += f;
                cost += f * e[i].cost;
            }
            if (dir) x ^= 1, swap(u, v);
            while (u != z)
                swap(x ^= 1, fae[v]), swap(u, fa[v]), swap(u, v);
        }
    }
    void dfs(int u) {
        vis[u] = visc;
        for (int i : g[u])
            if (int v = e[i].to; vis[v] != visc and e[i].flow)
                fa[v] = u, fae[v] = i, dfs(v);
    }
    C simplex() {
        fa.assign(g.size(), -1); fae.assign(g.size(), -1);
        C cost = 0; ++visc; dfs(0);
        for (int fail = 0; fail < ssize(e); )
            for (int i = 0; i < ssize(e); i++)
                if (e[i].flow and e[i].cost < phi(e[i] ^ 1).to -
                    phi(e[i].to))
                    fail = 0, pushflow(i, cost), ++visc;
                else ++fail;
        return cost;
    }
};

```

4.10 General Matching [5f2293]

```

struct Matching {
    queue<int> q; int ans, n;
    vector<int> fa, s, v, pre, match;
    int Find(int u) {
        return u == fa[u] ? u : fa[u] = Find(fa[u]);
    }
    int LCA(int x, int y) {
        static int tk = 0; tk++; x = Find(x); y = Find(y);
        for (; swap(x, y)) if (x != n) {
            if (v[x] == tk) return x;
            v[x] = tk;
            x = Find(pre[match[x]]);
        }
    }
    void Blossom(int x, int y, int l) {
        for (; Find(x) != l; x = pre[y]) {
            pre[x] = y, y = match[x];
            if (s[y] == 1) q.push(y), s[y] = 0;
            for (int z : {x, y}) if (fa[z] == z) fa[z] = l;
        }
    }
    bool Bfs(auto &&g, int r) {
        iota(all(fa), 0); ranges::fill(s, -1);
        q = queue<int>(); q.push(r); s[r] = 0;
        for (; !q.empty(); q.pop()) {
            for (int x = q.front(); int u : g[x])
                if (s[u] == -1) {
                    if (pre[u] = x, s[u] = 1, match[u] == n) {
                        for (int a = u, b = x, last;
                             b != n; a = last, b = pre[a])
                            last = match[b], match[b] = a, match[a] = b;
                        return true;
                    }
                    q.push(match[u]); s[match[u]] = 0;
                } else if (!s[u] && Find(u) != Find(x)) {
                    int l = LCA(u, x);
                    Blossom(x, u, l); Blossom(u, x, l);
                }
            }
        }
        return false;
    }
    Matching(auto &&g) : ans(0), n(int(g.size())),
        fa(n+1), s(n+1), v(n+1), pre(n+1, n), match(n+1, n) {
        for (int x = 0; x < n; ++x)
            if (match[x] == n) ans += Bfs(g, x);
        // match[x] == n means not matched
    }
}; // test @ yosupo judge

```

4.11 Weighted Matching [900530]- b4872b/

7890f1/28fed9

```

#define pb emplace_back
#define REP(i, l, r) for (int i=(l); i<=(r); ++i)

```

```

struct WeightGraph { // 1-based
    static const int inf = INT_MAX;
    struct edge { int u, v, w; }; int n, nx;
    vector<int> lab; vector<vector<edge>> g;
    vector<int> slack, match, st, pa, S, vis;
    vector<vector<int>> flo, flo_from; queue<int> q;
    WeightGraph(int n_) : n(n_), nx(n * 2), lab(nx + 1),
        g(nx + 1, vector<edge>(nx + 1)), slack(nx + 1),
        flo(nx + 1), flo_from(nx + 1, vector(n + 1, 0)) {
        match = st = pa = S = vis = slack;
        REP(u, 1, n) REP(v, 1, n) g[u][v] = {u, v, 0};
    }
    int ED(edge e) {
        return lab[e.u] + lab[e.v] - g[e.u][e.v].w * 2;
    }
    void update_slack(int u, int x, int &s) {
        if (!s || ED(g[u][x]) < ED(g[s][x])) s = u;
    }
    void set_slack(int x) {
        slack[x] = 0;
        REP(u, 1, n)
            if (g[u][x].w > 0 && st[u] != x && S[st[u]] == 0)
                update_slack(u, x, slack[x]);
    }
    void q_push(int x) {
        if (x <= n) q.push(x);
        else for (int y : flo[x]) q_push(y);
    }
    void set_st(int x, int b) {
        st[x] = b;
        if (x > n) for (int y : flo[x]) set_st(y, b);
    }
    vector<int> split_flo(auto &f, int xr) {
        auto it = find(all(f), xr);
        if (auto pr = it - f.begin(); pr % 2 == 1)
            reverse(1 + all(f), it = f.end() - pr);
        auto res = vector(f.begin(), it);
        return f.erase(f.begin(), it), res;
    }
    void set_match(int u, int v) {
        match[u] = g[u][v].v;
        if (u <= n) return;
        int xr = flo_from[u][g[u][v].u];
        auto &f = flo[u], z = split_flo(f, xr);
        REP(i, 0, int(z.size())-1) set_match(z[i], z[i ^ 1]);
        set_match(xr, v); f.insert(f.end(), all(z));
    }
    void augment(int u, int v) {
        for (;;) {
            int xnv = st[match[u]]; set_match(u, v);
            if (!xnv) return;
            set_match(v = xnv, u = st[pa[xnv]]);
        }
    }
    /* SPLIT_HASH_HERE */
    int lca(int u, int v) {
        static int t = 0; ++t;
        for (++t; u || v; swap(u, v)) if (u) {
            if (vis[u] == t) return u;
            vis[u] = t; u = st[match[u]];
            if (u) u = st[pa[u]];
        }
        return 0;
    }
    void add_blossom(int u, int o, int v) {
        int b = int(find(n + 1 + all(st), 0) - begin(st));
        lab[b] = 0, S[b] = 0; match[b] = match[o];
        vector<int> f = {o};
        for (int x : {u, v}) {
            for (int y; x != o; x = st[pa[y]])
                f.pb(x), f.pb(y = st[match[x]]), q_push(y);
            reverse(1 + all(f));
        }
        flo[b] = f; set_st(b, b);
        REP(x, 1, nx) g[b][x].w = g[x][b].w = 0;
        REP(x, 1, n) flo_from[b][x] = 0;
        for (int xs : flo[b]) {
            REP(x, 1, nx)
                if (g[b][x].w == 0 || ED(g[xs][x]) < ED(g[b][x]))
                    g[b][x] = g[xs][x], g[x][b] = g[x][xs];
            REP(x, 1, n)
                if (flo_from[xs][x]) flo_from[b][x] = xs;
        }
        set_slack(b);
    }
    void expand_blossom(int b) {
        for (int x : flo[b]) set_st(x, x);
        int xr = flo_from[b][g[b][pa[b]].u], xs = -1;
        for (int x : split_flo(flo[b], xr)) {
            if (xs == -1) { xs = x; continue; }
            pa[xs] = g[x][xs].u; S[xs] = 1, S[x] = 0;
            slack[xs] = 0; set_slack(x); q_push(x); xs = -1;
        }
        for (int x : flo[b])
            if (x == xr) S[x] = 1, pa[x] = pa[b];
            else S[x] = -1, set_slack(x);
        st[b] = 0;
    }
    bool on_found_edge(const edge &e) {
        if (int u = st[e.u], v = st[e.v]; S[v] == -1) {
            int nu = st[match[v]]; pa[v] = e.u; S[v] = 1;
            slack[v] = slack[nu] = 0; S[nu] = 0; q_push(nu);
        } else if (S[v] == 0) {
            if (int o = lca(u, v)) add_blossom(u, o, v);
            else return augment(u, v), augment(v, u), true;
        }
        return false;
    }
    /* SPLIT_HASH_HERE */
    bool matching() {
        ranges::fill(S, -1); ranges::fill(slack, 0);
        q = queue<int>();
        REP(x, 1, nx) if (st[x] == x && !match[x])
            pa[x] = 0, S[x] = 0, q_push(x);
        if (q.empty()) return false;
        for (;;) {
            while (q.size()) {
                int u = q.front(); q.pop();
                if (S[st[u]] == 1) continue;
                REP(v, 1, n)
                    if (g[u][v].w > 0 && st[u] != st[v]) {
                        if (ED(g[u][v]) != 0)
                            update_slack(u, st[v], slack[st[v]]);
                        else if (on_found_edge(g[u][v])) return true;
                    }
            }
            int d = inf;
            REP(b, n + 1, nx) if (st[b] == b && S[b] == 1)
                d = min(d, lab[b] / 2);
            REP(x, 1, nx)
                if (int s = slack[x]; st[x] == x && s && S[x] <= 0)
                    d = min(d, ED(g[s][x]) / (S[x] + 2));
            REP(u, 1, n)
                if (S[st[u]] == 1) lab[u] += d;
                else if (S[st[u]] == 0) {
                    if (lab[u] <= d) return false;
                    lab[u] -= d;
                }
            REP(b, n + 1, nx) if (st[b] == b && S[b] >= 0)
                lab[b] += d * (2 - 4 * S[b]);
            REP(x, 1, nx)
                if (int s = slack[x]; st[x] == x &&
                    s && st[s] != x && ED(g[s][x]) == 0)
                    if (on_found_edge(g[s][x])) return true;
            REP(b, n + 1, nx)
                if (st[b] == b && S[b] == 1 && lab[b] == 0)
                    expand_blossom(b);
        }
        return false;
    }
    pair<lld, int> solve() {
        ranges::fill(match, 0);
        REP(u, 0, n) st[u] = u, flo[u].clear();
        int w_max = 0;
        REP(u, 1, n) REP(v, 1, n) {
            flo_from[u][v] = (u == v ? u : 0);
            w_max = max(w_max, g[u][v].w);
        }
        REP(u, 1, n) lab[u] = w_max;
        int n_matches = 0; lld tot_weight = 0;
        while (matching()) ++n_matches;
        REP(u, 1, n) if (match[u] && match[u] < u)
            tot_weight += g[u][match[u]].w;
        return make_pair(tot_weight, n_matches);
    }
    void set_edge(int u, int v, int w) {

```

```
g[u][v].w = g[v][u].w = w; }
```

5. Math

5.1 Common Bounds

n	2	3	4	5	6	7	8	9	20	30	40	50	100
$p(n)$	2	3	5	7	11	15	22	30	627	5604	4e4	2e5	2e8
n	100	1e3	1e6	1e9	1e12	1e15	1e18						
$d(i)$	12	32	240	1344	6720	26880	103680						
n	1	2	3	4	5	6	7	8	9	10	11	12	13
$\binom{2n}{n}$	2	6	20	70	252	924	3432	12870	48620	184756	7e5	2e6	1e7
n	2	3	4	5	6	7	8	9	10	11	12	13	
B_n	2	5	15	52	203	877	4140	21147	115975	7e5	4e6	3e7	

5.2 Equations

Stirling Number of the First Kind

$S_1(n, k)$ counts the number of permutations of n elements with k disjoint cycles.

- $S_1(n, k) = (n-1) \cdot S_1(n-1, k) + S_1(n-1, k-1)$
- $S_1(n, i) = [x^i] \left(\prod_{i=0}^{n-1} (x+i) \right)$, use D&Q and taylor shift.

$$S_1(i, k) = \frac{i!}{k!} [x^i] \left(\sum_{j \geq 1} \frac{x^j}{j} \right)^k$$

Stirling Number of the Second Kind

$S_2(n, k)$ counts the number of ways to partition a set of n elements into k nonempty sets.

- $S_2(n, k) = S_2(n-1, k-1) + k \cdot S_2(n-1, k)$
- $S_2(n, k) = \sum_{i=0}^k \binom{k}{i} i^n (-1)^{k-i} = \sum_{i=0}^k \frac{(-1)^i}{i!} \cdot \frac{(k-i)^n}{(k-i)!}$
- $S_2(i, k) = \frac{i!}{k!} [x^i] (e^x - 1)^k$

Derivatives/Integrals

$$\text{Integration by parts: } \int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

$$\left| \begin{array}{l} \frac{d}{dx} \sin^{-1} x = \frac{1}{\sqrt{1-x^2}} \\ \frac{d}{dx} \cos^{-1} x = -\frac{1}{\sqrt{1-x^2}} \\ \frac{d}{dx} \tan x = 1 + \tan^2 x \\ \int \tan ax = -\frac{\ln |\cos ax|}{a} \\ \int e^{-x^2} = \frac{\sqrt{\pi}}{2} \text{erf}(x) \\ \int x e^{ax} dx = \frac{e^{ax}}{a^2} (ax - 1) \end{array} \right| \frac{d}{dx} \tan^{-1} x = \frac{1}{1+x^2}$$

$$\int \sqrt{a^2 + x^2} = \frac{1}{2} \left(x \sqrt{a^2 + x^2} + a^2 \text{asin}(x/a) \right)$$

Extended Euler

$$a^b \equiv \begin{cases} a^{(b \bmod \varphi(m)) + \varphi(m)} & \text{if } (a, m) \neq 1 \wedge b \geq \varphi(m) \\ a^{b \bmod \varphi(m)} & \text{otherwise} \end{cases} \pmod{m}$$

Pentagonal Number Theorem

$$\prod_{n=1}^{\infty} (1 - x^n) = \sum_{k=-\infty}^{\infty} (-1)^k x^{k(3k-1)/2} = \left(\sum p(n) x^n \right)^{-1}$$

5.3 Integer Division* [cd017d]

```
lld fdiv(lld a, lld b)
{ return a / b - (a % b && (a < 0) ^ (b < 0)); }
lld cdiv(lld a, lld b)
{ return a / b + (a % b && (a < 0) ^ (b > 0)); }
```

5.4 FloorSum [fb5917]

```
// @param n `n < 2^32`
// @param m `1 <= m < 2^32`
// @return sum_{i=0}^{n-1} floor((ai + b)/m) mod 2^64
llu floor_sum_unsigned(llu n, llu m, llu a, llu b) {
    llu ans = 0;
    while (true) {
        if (a >= m) ans += n*(n-1)/2 * (a/m), a %= m;
        if (b >= m) ans += n * (b/m), b %= m;
        if ((llu) y_max = a * n + b; y_max >= m) {
            n = (llu)(y_max / m), b = (llu)(y_max % m);
            swap(m, a);
        } else break;
    }
    return ans;
}
lld floor_sum(lld n, lld m, lld a, lld b) {
    llu ans = 0;
    if (a < 0) {
        llu a2 = (a % m + m), d = (a2 - a) / m;
        ans -= 1ULL * n * (n - 1) / 2 * d; a = a2;
    }
    if (b < 0) {
        llu b2 = (b % m + m), d = (b2 - b) / m;
        ans -= 1ULL * n * d; b = b2;
    }
    return ans + floor_sum_unsigned(n, m, a, b);
}
```

5.5 ModMin [2c021c]

```
// min{k | l <= ((ak) mod m) <= r}
optional<llu> mod_min(u32 a, u32 m, u32 l, u32 r) {
    if (a == 0) return l ? nullopt : optional{0};
    if (auto k = llu(l + a - 1) / a; k * a <= r)
        return k;
    auto b = m / a, c = m % a;
    if (auto y = mod_min(c, a, a - r % a, a - l % a))
```

```
    return (l + *y * c + a - 1) / a + *y * b;
    return nullopt;
}
```

5.6 Floor Monoid Product [416e89]

```
/* template <typename T>
T brute(llu a, llu b, llu c, llu n, T U, T R) {
    T res;
    for (llu i = 1, l = 0; i <= n; i++, res = res * R)
        for (llu r = (a*i+b)/c; l < r; ++l) res = res * U;
    return res;
} */
template <typename T>
T euclid(llu a, llu b, llu c, llu n, T U, T R) {
    if (!n) return T{};
    if (b >= c)
        return mpow(U, b / c) * euclid(a, b % c, c, n, U, R);
    if (a >= c)
        return euclid(a % c, b, c, n, U, mpow(U, a / c) * R);
    llu m = (u128(a) * n + b) / c;
    if (!m) return mpow(R, n);
    return mpow(R, (c - b - 1) / a) * U
        * euclid(c, (c - b - 1) % a, a, m - 1, R, U)
        * mpow(R, n - (u128(c) * m - b - 1) / a);
}
// time complexity is O(log max(a, b, c))
// UUUU R UUUUU R ... UUU R 共 N 個 R，最後一個必是 R
// 一直到第 k 個 R 前總共有 (ak+b)/c 個 U
```

5.7 ax+by=gcd [6c70e4]

```
// ax+ny = 1, ax+ny == ax == 1 (mod n)
tuple<lld, lld, lld> exgcd(lld x, lld y) {
    if (y == 0) return {x, 1, 0};
    auto [g, b, a] = exgcd(y, x % y);
    return {g, a, b - (x / y) * a};
}
```

5.8 Chinese Remainder [ab86df]

```
// please ensure r_i \in [0, m_i)
bool crt(lld &m1, lld &r1, lld m2, lld r2) {
    if (m2 > m1) swap(m1, m2), swap(r1, r2);
    auto [g, a, b] = exgcd(m1, m2);
    if ((r2 - r1) % g != 0) return false;
    m2 /= g; lld D = (r2 - r1) / g % m2 * a % m2;
    r1 += (D < 0 ? D + m2 : D) * m1; m1 *= m2;
    assert(r1 >= 0 && r1 < m1);
    return true;
}
```

5.9 DiscreteLog [86e463]

```
template<typename Int>
Int BSGS(Int x, Int y, Int M) {
    // x^? \equiv y (mod M)
    Int t = 1, c = 0, g = 1;
    for (Int M_ = M; M_ > 0; M_ >= 1) g = g * x % M;
    for (g = gcd(g, M); t % g != 0; ++c) {
        if (t == y) return c;
        t = t * x % M;
    }
    if (y % g != 0) return -1;
    t /= g, y /= g, M /= g;
    Int h = 0, gs = 1;
    for (; h * h < M; ++h) gs = gs * x % M;
    unordered_map<Int, Int> bs;
    for (Int s = 0; s < h; bs[y] = ++s) y = y * x % M;
    for (Int s = 0; s < M; s += h) {
        t = t * gs % M;
        if (bs.count(t)) return c + s + h - bs[t];
    }
    return -1;
}
```

5.10 Quadratic Residue [f0baec]

```
int get_root(int n, int P) { // ensure 0 <= n < p
    if (P == 2 || n == 0) return n;
    auto check = [&](lld x) {
        return modpow(int(x), (P - 1) / 2, P);
    };
    if (check(n) != 1) return -1;
    mt19937 rnd(7122); lld z = 1, w;
    while (check(w = (z * z - n + P) % P) != P - 1)
        z = rnd() % P;
    const auto M = [P, w](auto &u, auto &v) {
        auto [a, b] = u; auto [c, d] = v;
        return make_pair((a * c + b * d % P * w) % P,
            (a * d + b * c) % P);
    };
};
```



```
pair<lld, lld> r(1, 0), e(z, 1);
for (int q = (P + 1) / 2; q; q >>= 1, e = M(e, e))
    if (q & 1) r = M(r, e);
return int(r.first); // sqrt(n) mod P where P is prime
}
```

5.11 FWT* [eb4330]

```
/* or convolution:
 * x = (x0, x0+x1), inv = (x0, x1-x0) w/o final div
 * and convolution:
 * x = (x0+x1, x1), inv = (x0-x1, x1) w/o final div */
template <typename T>
void fwt(T x[], int N, bool inv = false) {
    for (int d = 1; d < N; d <= 1)
        for (int s = 0; s < N; s += d * 2)
            for (int i = s; i < s + d; i++) {
                int j = i + d;
                T ta = x[i], tb = x[j];
                x[i] = ta + tb; x[j] = ta - tb;
            }
    if (!inv) return;
    const T invn = T(N).inv();
    for (int i = 0; i < N; i++) x[i] *= invn;
}
```

5.12 Packed FFT [0a6af5]

```
VL convolution(const VI &a, const VI &b) {
    if (a.empty() || b.empty()) return {};
    const int sz = bit_ceil(a.size() + b.size() - 1);
    // Should be able to handle N <= 10^5, C <= 10^4
    vector<P> v(sz);
    for (size_t i = 0; i < a.size(); ++i) v[i].RE(a[i]);
    for (size_t i = 0; i < b.size(); ++i) v[i].IM(b[i]);
    fft(v.data(), sz, /*inv=*/false);
    auto rev = v; reverse(1 + all(rev));
    for (int i = 0; i < sz; ++i) {
        P A = (v[i] + conj(rev[i])) / P(2, 0);
        P B = (v[i] - conj(rev[i])) / P(0, 2);
        v[i] = A * B;
    }
    VL c(sz); fft(v.data(), sz, /*inv=*/true);
    for (int i = 0; i < sz; ++i) c[i] = roundl(RE(v[i]));
    return c;
}
```

```
VI convolution_mod(const VI &a, const VI &b) {
    if (a.empty() || b.empty()) return {};
    const int sz = bit_ceil(a.size() + b.size() - 1);
    vector<P> fa(sz), fb(sz);
    for (size_t i = 0; i < a.size(); ++i)
        fa[i] = P(a[i] & ((1 << 15) - 1), a[i] >> 15);
    for (size_t i = 0; i < b.size(); ++i)
        fb[i] = P(b[i] & ((1 << 15) - 1), b[i] >> 15);
    fft(fa.data(), sz); fft(fb.data(), sz);
    auto rfa = fa; reverse(1 + all(rfa));
    for (int i = 0; i < sz; ++i) fa[i] *= fb[i];
    for (int i = 0; i < sz; ++i) fb[i] *= conj(rfa[i]);
    fft(fa.data(), sz, true); fft(fb.data(), sz, true);
    vector<int> res(sz);
    for (int i = 0; i < sz; ++i) {
        lld A = (lld)roundl(RE((fa[i] + fb[i]) / P(2, 0)));
        lld C = (lld)roundl(IM((fa[i] - fb[i]) / P(0, 2)));
        lld B = (lld)roundl(IM(fa[i])); B %= p; C %= p;
        res[i] = (A + (B << 15) + (C << 30)) % p;
    }
    return res;
} // test @ yosupo judge with long double
```

5.13 CRT for arbitrary mod [e4dde7]

```
const int mod = 1000000007;
const int M1 = 985661441; // G = 3 for M1, M2, M3
const int M2 = 998244353;
const int M3 = 1004535809;
int superBigCRT(lld A, lld B, lld C) {
    static_assert(M1 < M2 && M2 < M3);
    constexpr lld r12 = modpow(M1, M2-2, M2);
    constexpr lld r13 = modpow(M1, M3-2, M3);
    constexpr lld r23 = modpow(M2, M3-2, M3);
    constexpr lld M1M2 = 1LL * M1 * M2 % mod;
    B = (B - A + M2) * r12 % M2;
    C = (C - A + M3) * r13 % M3;
    C = (C - B + M3) * r23 % M3;
    return (A + B * M1 + C * M1M2) % mod;
}
```

5.14 NTT / FFT* [e2e54e]

```
struct NTT {
    static_assert(maxn == (maxn & -maxn));
    Mint roots[maxn];
    NTT() {
        Mint r = Mint(G).qpow((mod - 1) / maxn);
        for (int i = maxn >> 1; i; i >>= 1) {
            roots[i] = 1;
            for (int j = 1; j < i; j++)
                roots[i + j] = roots[i + j - 1] * r;
            r = r * r;
            // for (int j = 0; j < i; j++) // FFT (tested)
            // roots[i+j] = polar<lld>(1, PI * j / i);
        }
        // n must be 2^k, and 0 <= f[i] < mod
    }
    void operator()(Mint f[], int n, bool inv = false) {
        for (int i = 0, j = 0; i < n; i++) {
            if (i < j) swap(f[i], f[j]);
            for (int k = n >> 1; (j ^= k) < k; k >>= 1);
        }
        for (int s = 1; s < n; s *= 2)
            for (int i = 0; i < n; i += s * 2)
                for (int j = 0; j < s; j++) {
                    Mint a = f[i+j], b = f[i+j+s] * roots[s+j];
                    f[i+j] = a + b; f[i+j+s] = a - b;
                }
        if (!inv) return;
        const Mint invn = Mint(n).inv();
        for (int i = 0; i < n; i++) f[i] *= invn;
        reverse(f + 1, f + n);
    }
};

5.15 Formal Power Series* [5f27d9]
#define fi(l, r) for (size_t i = (l); i < (r); i++)
struct S : vector<Mint> {
    using V = vector<Mint>; using V::V;
    friend S operator*(S a, S b) { // 4a6cfe
        if (a.empty() || b.empty()) return S();
        const auto k = a.size() + b.size() - 1;
        const int sz = (int)bit_ceil(k);
        a.resize(sz), b.resize(sz);
        ntt(a.data(), sz); ntt(b.data(), sz);
        fi(0, a.size()) a[i] *= b[i];
        return ntt(a.data(), sz, true), a.resize(k), a;
    } // hash end.
    S newton(Mint init, auto &&iter) const { // 53fb8b
        S Q = { init };
        for (int sz = 2; Q.size() < size(); sz *= 2) {
            S A(begin(), begin() + min(sz, int(size())));
            iter(Q, A, sz); Q.resize(sz);
        }
        return Q.resize(size()), Q;
    } // hash end.
    S inv() const { // 515d9f; coef[0] != 0
        return newton(front().inv(), [](S &X, S &A, int sz) {
            sz *= 2; X.resize(sz); A.resize(sz);
            ntt(X.data(), sz), ntt(A.data(), sz);
            for (int i = 0; i < sz; i++) X[i] *= 2 - X[i]*A[i];
            ntt(X.data(), sz, true); });
    } // hash end.
    S derivative() const { // 99f0b8
        S A = *this;
        fi(1, A.size()) A[i - 1] = i * A[i];
        return A.empty() ? A : (A.pop_back(), A);
    } // hash end.
    S integral() const { // 57c798
        S A = *this; A.insert(A.begin(), 0);
        fi(1, A.size()) A[i] /= i;
        return A;
    } // hash end.
    S log() const { // cle077; coef[0] == 1; res[0] == 0
        auto B = (derivative() * inv()).integral();
        return B.resize(size()), B;
    } // hash end.
    S exp() const { // 98bdf4; coef[0] == 0; res[0] == 1
        return newton(1, [](S &X, S &A, int sz) {
            X.resize(sz); A.resize(sz); S Y = X.log();
            fi(0, Y.size()) Y[i] = A[i] - Y[i];
            Y[0] += 1; X = X * Y; });
    } // hash end.
    S mulT(S b, size_t k) const { // 80fee1
        assert(b.size()); reverse(b.begin(), b.end());
```

```

    auto R = (*this) * b;
    R = S(R.begin() + b.size() - 1, R.end());
    return R.resize(k), R;
} // hash end.
V evaluate(const V &x) { // e45c8d
    if (empty()) return V(x.size());
    const int n = int(max(x.size(), size()));
    vector<S> q(n * 2, S{1}); V ans(n);
    fi(0, x.size()) q[i + n] = S{1, -x[i]};
    for (int i = n - 1; i > 0; i--)
        q[i] = q[i < 1] * q[i < 1 | 1];
    q[1] = mulT(q[1].inv(), n);
    for (int i = 1; i < n; i++) {
        auto L = q[i < 1], R = q[i < 1 | 1];
        q[i < 1 | 0] = q[i].mulT(R, L.size());
        q[i < 1 | 1] = q[i].mulT(L, R.size());
    }
    for (int i = 0; i < n; i++) ans[i] = q[i + n][0];
    return ans.resize(x.size()), ans;
} // hash end.
friend S operator*(S a, Mint s) {
    for (Mint &x : a) x *= s;
    return a;
}
};
S pow(S a, lld M) { // fbd17b; period mod*(mod-1)
    assert(!a.empty() && a[0] != 0);
    Mint c = a[0]; a = (a * c.inv()).log() * (M % mod);
    return a.exp() * c.ppow(M % (mod - 1));
} // hash end. mod x^N where N=a.size()
S sqrt(S v) { // lba6a7; need: QuadraticResidue
    assert(!v.empty() && v[0] != 0);
    const int r = get_root((int)v[0]); assert(r != -1);
    return v.newton(r,
        [inv2 = (mod + 1) / 2](S &X, S &A, int sz) {
            X.resize(sz); A.resize(sz);
            auto B = A * X.inv();
            for (int i = 0; i < sz; i++)
                X[i] = (X[i] + B[i]) * inv2; });
} // hash end.
pair<S, S> divmod(const S &A, const S &B) { // b35efd
    assert(!B.empty() && B.back() != 0);
    if (A.size() < B.size()) return {{}, A};
    const auto sz = A.size() - B.size() + 1;
    S X = B; reverse(all(X)); X.resize(sz);
    S Y = A; reverse(all(Y)); Y.resize(sz);
    S Q = X.inv() * Y; Q.resize(sz); reverse(all(Q));
    X = Q * B; Y = A;
    fi(0, Y.size()) Y[i] -= X[i];
    while (Y.size() && Y.back() == 0) Y.pop_back();
    while (Q.size() && Q.back() == 0) Q.pop_back();
    return {Q, Y};
} // hash end. empty means zero polynomial
Mint linear_recursion_kth(S a, S c, int64_t k) { // 4b7416
    const auto d = a.size(); assert(c.size() == d + 1);
    const int sz = (int)bit_ceil(2 * d + 1), o = sz / 2;
    S q = c; for (Mint &x: q) x = -x; q[0] = 1;
    S p = a * q; p.resize(sz); q.resize(sz);
    for (int r; r = (k & 1), k; k >= 1) {
        fill(d + all(p), 0); fill(d + 1 + all(q), 0);
        ntt(p.data(), sz); ntt(q.data(), sz);
        for (int i = 0; i < sz; i++)
            p[i] *= q[(i + o) & (sz - 1)];
        for (int i = 0, j = o; j < sz; i++, j++)
            q[i] = q[j] = q[i] * q[j];
        ntt(p.data(), sz, true); ntt(q.data(), sz, true);
        for (size_t i = 0; i < d; i++) p[i] = p[i < 1 | r];
        for (size_t i = 0; i <= d; i++) q[i] = q[i < 1];
    } // Bostan-Mori
    return p[0] / q[0];
} // hash end. a_n = \sum c_j a_{n-j}, c_0 is not used

```

5.16 Partition Number [9bb845]

```

ans[0] = tmp[0] = 1;
for (int i = 1; i * i <= n; i++) {
    for (int rep = 0; rep < 2; rep++)
        for (int j = i; j <= n - i * i; j++)
            modadd(tmp[j], tmp[j - i]);
    for (int j = i * i; j <= n; j++)
        modadd(ans[j], tmp[j - i * i]);
}

```

5.17 Pi Count [715863]

```

struct S { int rough; lld large; int id; };
lld PrimeCount(lld n) { // n ~ 10^13 => < 1s
    if (n <= 1) return 0;
    const int v = static_cast<int>(sqrtl(n)); int pc = 0;
    vector<int> smalls(v + 1), skip(v + 1); vector<S> z;
    for (int i = 2; i <= v; ++i) smalls[i] = (i + 1) / 2;
    for (int i : views::iota(0, (v + 1) / 2))
        z.emplace_back(2*i+1, (n / (2*i+1) + 1) / 2, i);
    for (int p = 3; p <= v; ++p)
        if (smalls[p] > smalls[p - 1]) {
            const int q = p * p; ++pc;
            if (1LL * q * q > n) break;
            skip[p] = 1;
            for (int i = q; i <= v; i += 2 * p) skip[i] = 1;
            int ns = 0;
            for (auto e : z) if (!skip[e.rough]) {
                lld d = 1LL * e.rough * p;
                e.large += pc - (d <= v ? z[smalls[d] - pc].large :
                    smalls[n / d]);
                e.id = ns; z[ns++] = e;
            }
            z.resize(ns);
            for (int j = v / p; j >= p; --j) {
                int c = smalls[j] - pc, e = min(j * p + p, v + 1);
                for (int i = j * p; i < e; ++i) smalls[i] -= c;
            }
        }
    lld ans = z[0].large; z.erase(z.begin());
    for (auto &[rough, large, k] : z) {
        const lld m = n / rough; --k;
        ans -= large - (pc + k);
        for (auto [p, _, l] : z)
            if (l >= k || p * p > m) break;
        else ans += smalls[m / p] - (pc + l);
    }
    return ans;
} // test @ yosupo library checker w/ n=1e11, 68ms

```

5.18 Min 25 Sieve* [45f26b]

```

template <typename U, typename V> struct min25 {
    lld n; int sq;
    vector<U> Ss, Sl, Spre; vector<V> Rs, Rl;
    Sieve sv; vector<lld> quo;
    U &S(lld d) { return d < sq ? Ss[d] : Sl[n / d]; }
    V &R(lld d) { return d < sq ? Rs[d] : Rl[n / d]; }
    min25(lld n_) : n(n_), sq((int)sqrt(n) + 1),
        Ss(sq), Sl(sq), Spre(sq), Rs(sq), Rl(sq), sv(sq) {
        for (lld i = 1, Q; i <= n; i = n / Q + 1)
            quo.push_back(Q = n / i);
    }
    U F_prime(auto &&f, auto &&F) {
        for (lld p : sv.primes) Spre[p] = f(p);
        for (int i = 1; i < sq; i++) Spre[i] += Spre[i - 1];
        for (lld i : quo) S(i) = F(i) - F(1);
        for (lld p : sv.primes)
            for (lld i : quo) {
                if (p * p > i) break;
                S(i) -= f(p) * (S(i / p) - Spre[p - 1]);
            }
        return S(n);
    }
    // F_prime: \sum_{p is prime, p <= n} f(p)
    V F_comp(auto &&g, auto &&h) {
        for (lld i : quo) R(i) = h(S(i));
        for (lld p : sv.primes | views::reverse)
            for (lld i : quo) {
                if (p * p > i) break;
                lld prod = p;
                for (int c = 1; prod * p <= i; ++c, prod *= p) {
                    R(i) += g(p, c) * (R(i / prod) - h(Spre[p]));
                    R(i) += g(p, c + 1);
                }
            }
        return R(n);
    }
    // F_comp: \sum_{2 <= i <= n} g(i)
}; // O(n^{3/4}) / log n
/* U, V 都是環，要求 f: lld -> U 是完全積性；
g 是積性函數且 h(f(p)) = g(p) 對於質數 p；
h(x + y) = h(x) + h(y)。
呼叫 F_comp 前需要先呼叫 F_prime 得到 S(i)。
S(i), R(i) 是 F_prime 和 F_comp 在 n/k 點的值。
F(i) = \sum_{j <= i} f(j) 和 f(i) 需要快速求值。
g(p, c) := g(pow(p, c)) 需要快速求值。

```

例如若 $g(p)$ 是度數 d 的多項式則可以構造 $f(p)$ 是維護 $\text{pow}(p, c)$ 的 $(d+1)$ -tuple $*$

5.19 Miller Rabin [fbd812]

```
bool isprime(llu x) {
    auto witn = [&](llu a, int t) {
        for (llu a2; t--; a = a2) {
            a2 = mmul(a, a, x);
            if (a2 == 1 && a != 1 && a != x - 1) return true;
        }
        return a != 1;
    };
    if (x <= 2 || ~x & 1) return x == 2;
    int t = countr_zero(x-1); llu odd = (x-1) >> t;
    for (llu m: {2, 325, 9375, 28178, 450775, 9780504, 1795265022})
        if (m % x != 0 && witn(mpow(m % x, odd, x), t))
            return false;
    return true;
} // test @ luogu 143 & yosupo judge, ~1700ms for Q=1e5
// if use montgomery, ~250ms for Q=1e5
```

5.20 Pollard Rho [57ad88]

```
// does not work when n is prime or n == 1
// return any non-trivial factor
llu pollard_rho(llu n) {
    static mt19937_64 rnd(120821011);
    if (!(n & 1)) return 2;
    ll y = 2, z = y, c = rnd() % n, p = 1, i = 0, t;
    auto f = [&](llu x) {
        return madd(mmul(x, x, n), c, n);
    };
    do {
        p = mmul(msub(z = f(f(z)), y = f(y), n), p, n);
        if (++i &= 63) if (i == (i & -i)) t = gcd(p, n);
    } while (t == 1);
    return t == n ? pollard_rho(n) : t;
} // test @ yosupo judge, ~270ms for Q=100
// if use montgomery, ~70ms for Q=100
```

5.21 Montgomery [648fb3]

```
struct Mont { // Montgomery multiplication
    constexpr static int W = 64, L = 6;
    ll mod, R1, R2, xinv;
    void set_mod(llu _mod) {
        mod = _mod; assert(mod & 1); xinv = 1;
        for (int j = 0; j < L; j++) xinv *= 2 - xinv * mod;
        assert(xinv * mod == 1);
        const u128 R = (u128(1) << W) % mod;
        R1 = ll(R); R2 = ll(R*R % mod);
    }
    llu redc(llu a, llu b) const {
        u128 T = u128(a) * b, m = -llu(T) * xinv;
        T += m * mod; T >>= W;
        return ll(T >= mod ? T - mod : T);
    }
    llu from(llu x) const {
        assert(x < mod); return redc(x, R2);
    }
    llu get(llu a) const { return redc(a, 1); }
    llu one() const { return R1; }
} mont;
// a * b % mod == get(redc(from(a), from(b)))
```

5.22 Berlekamp Massey [a94d00]

```
template <typename T>
vector<T> BerlekampMassey(const vector<T> &output) {
    vector<T> d(output.size() + 1), me, he;
    for (size_t f = 0, i = 1; i <= output.size(); ++i) {
        for (size_t j = 0; j < me.size(); ++j)
            d[i] += output[i - j - 2] * me[j];
        if ((d[i] - output[i - 1]) == 0) continue;
        if (me.empty()) {
            me.resize(f = i);
            continue;
        }
        vector<T> o(i - f - 1);
        T k = -d[i] / d[f]; o.push_back(-k);
        for (T x : he) o.push_back(x * k);
        if (o.size() < me.size()) o.resize(me.size());
        for (size_t j = 0; j < me.size(); ++j) o[j] += me[j];
        if (i - f + he.size() >= me.size()) he = me, f = i;
        me = o;
    }
    return me;
}
```

5.23 Gauss Elimination [fa0977]

```
using VI = vector<int>; // be careful if A.empty()
using VVI = vector<VI>; // ensure that 0 <= x < mod
pair<VI, VVI> gauss(VVI A, VI b) { // solve Ax=b
    const int N = (int)A.size(), M = (int)A[0].size();
    vector<int> depv, free(M, true); int rk = 0;
    for (int i = 0; i < M; i++) {
        int p = -1;
        for (int j = rk; j < N; j++)
            if (p == -1 || abs(A[j][i]) > abs(A[p][i]))
                p = j;
        if (p == -1 || A[p][i] == 0) continue;
        swap(A[p], A[rk]); swap(b[p], b[rk]);
        const int inv = modinv(A[rk][i]);
        for (int &x : A[rk]) x = mul(x, inv);
        b[rk] = mul(b[rk], inv);
        for (int j = 0; j < N; j++) if (j != rk) {
            int z = A[j][i];
            for (int k = 0; k < M; k++)
                A[j][k] = sub(A[j][k], mul(z, A[rk][k]));
            b[j] = sub(b[j], mul(z, b[rk]));
        }
        depv.push_back(i); free[i] = false; ++rk;
    }
    for (int i = rk; i < N; i++)
        if (b[i] != 0) return {{}, {}}; // not consistent
    VI x(M); VVI h;
    for (int i = 0; i < rk; i++) x[depv[i]] = b[i];
    for (int i = 0; i < M; i++) if (free[i]) {
        h.emplace_back(M); h.back()[i] = 1;
        for (int j = 0; j < rk; j++)
            h.back()[depv[j]] = sub(0, A[j][i]);
    }
    return {x, h}; // solution = x + span(h[i])
}
```

5.24 CharPoly [cd559d]

```
#define rep(x, y, z) for (int x=y; x<z; x++)
using VI = vector<int>; using VVI = vector<VI>;
void Hessenberg(VVI &H, int N) {
    for (int i = 0; i < N - 2; ++i) {
        for (int j = i + 1; j < N; ++j) if (H[j][i]) {
            rep(k, i, N) swap(H[i+1][k], H[j][k]);
            rep(k, 0, N) swap(H[k][i+1], H[k][j]);
            break;
        }
        if (!H[i + 1][i]) continue;
        for (int j = i + 2; j < N; ++j) {
            int co = mul(modinv(H[i + 1][i]), H[j][i]);
            rep(k, i, N) subeq(H[j][k], mul(H[i+1][k], co));
            rep(k, 0, N) addeq(H[k][i+1], mul(H[k][j], co));
        }
    }
}
VI CharacteristicPoly(VVI A) {
    int N = (int)A.size(); Hessenberg(A, N);
    VVI P(N + 1, VI(N + 1)); P[0][0] = 1;
    for (int i = 1; i <= N; ++i) {
        rep(j, 0, i+1) P[i][j] = j ? P[i-1][j-1] : 0;
        for (int j = i - 1, val = 1; j >= 0; --j) {
            int co = mul(val, A[j][i - 1]);
            rep(k, 0, j+1) subeq(P[i][k], mul(P[j][k], co));
            if (j) val = mul(val, A[j][j - 1]);
        }
    }
    if (N & 1) for (int &x: P[N]) x = sub(0, x);
    return P[N]; // test: 2021 PTZ Korea K
}
```

5.25 Simplex [c9c93b]

```
namespace simplex {
    // maximize c^T x under Ax <= B and x >= 0
    // return VD(n, -inf) if the solution doesn't exist
    // return VD(n, +inf) if the solution is unbounded
    using VD = vector<llf>;
    using VVD = vector<vector<llf>>;
    const llf eps = 1e-9, inf = 1e+9;
    int n, m; VVD d; vector<int> p, q;
    void pivot(int r, int s) {
        llf inv = 1.0 / d[r][s];
        for (int i = 0; i < m + 2; ++i)
            for (int j = 0; j < n + 2; ++j)
                if (i != r && j != s)
                    d[i][j] -= d[r][j] * d[i][s] * inv;
        for (int i=0; i<m+2; ++i) if (i != r) d[i][s] *= -inv;
    }
}
```

```

for(int j=0;j<n+2;++j) if (j != s) d[r][j] *= +inv;
d[r][s] = inv; swap(p[r], q[s]);
}
bool phase(int z) {
    int x = m + z;
    while (true) {
        int s = -1;
        for (int i = 0; i <= n; ++i) {
            if (!z && q[i] == -1) continue;
            if (s == -1 || d[x][i] < d[x][s]) s = i;
        }
        if (s == -1 || d[x][s] > -eps) return true;
        int r = -1;
        for (int i = 0; i < m; ++i) {
            if (d[i][s] < eps) continue;
            if (r == -1 ||
                d[i][n+1]/d[i][s] < d[r][n+1]/d[r][s]) r = i;
        }
        if (r == -1) return false;
        pivot(r, s);
    }
}
VD solve(const VVD &a, const VD &b, const VD &c) {
    m = (int)b.size(), n = (int)c.size();
    d = VVD(m + 2, VD(n + 2));
    for (int i = 0; i < m; ++i)
        for (int j = 0; j < n; ++j) d[i][j] = a[i][j];
    p.resize(m), q.resize(n + 1);
    for (int i = 0; i < m; ++i)
        p[i] = n + i, d[i][n] = -1, d[i][n + 1] = b[i];
    for (int i = 0; i < n; ++i) q[i] = i, d[m][i] = -c[i];
    q[n] = -1, d[m + 1][n] = 1;
    int r = 0;
    for (int i = 1; i < m; ++i)
        if (d[i][n + 1] < d[r][n + 1]) r = i;
    if (d[r][n + 1] < -eps) {
        pivot(r, n);
        if (!phase(1) || d[m + 1][n + 1] < -eps)
            return VD(n, -inf);
        for (int i = 0; i < m; ++i) if (p[i] == -1) {
            int s = min_element(d[i].begin(), d[i].end() - 1)
                - d[i].begin();
            pivot(i, s);
        }
    }
    if (!phase(0)) return VD(n, inf);
    VD x(n);
    for (int i = 0; i < m; ++i)
        if (p[i] < n) x[p[i]] = d[i][n + 1];
    return x;
}
// use double instead of long double if possible

```

5.26 Simplex Construction

Standard form: maximize $\sum_{1 \leq i \leq n} c_i x_i$ such that $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$ for all $1 \leq j \leq m$ and $x_i \geq 0$ for all $1 \leq i \leq n$.

1. In case of minimization, let $c'_i = -c_i$
2. $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j \rightarrow \sum_{1 \leq i \leq n} -A_{ji} x_i \leq -b_j$
3. $\sum_{1 \leq i \leq n} A_{ji} x_i = b_j \rightarrow \text{add } \leq \text{ and } \geq$.
4. If x_i has no lower bound, replace x_i with $x_i - x'_i$

5.27 Adaptive Simpson [b8cef9]

```

llf integrate(auto &&f, llf L, llf R) {
    auto simp = [&](llf l, llf r) {
        llf m = (l + r) / 2;
        return (f(l) + f(r) + 4.0 * f(m)) * (r - l) / 6.0;
    };
    auto F = [&](auto Y, llf l, llf r, llf v, llf eps) {
        llf m = (l+r)/2, vl = simp(l, m), vr = simp(m, r);
        if (abs(vl + vr - v) <= 15 * eps)
            return vl + vr + (vl + vr - v) / 15.0;
        return Y(Y, l, m, vl, eps / 2.0) +
            Y(Y, m, r, vr, eps / 2.0);
    };
    return F(F, L, R, simp(L, R), 1e-6);
}

```

5.28 Golden Ratio Search [376bcb]

```

llf gss(llf a, llf b, auto &&f) {
    llf r = (sqrt(5)-1)/2, eps = 1e-7;
    llf x1 = b - r*(b-a), x2 = a + r*(b-a);
    llf f1 = f(x1), f2 = f(x2);
    while (b-a > eps)
        if (f1 < f2) { //change to > to find maximum
            b = x2; x2 = x1; f2 = f1;

```

```

        x1 = b - r*(b-a); f1 = f(x1);
    } else {
        a = x1; x1 = x2; f1 = f2;
        x2 = a + r*(b-a); f2 = f(x2);
    }
    return a;
}

```

6 Geometry

6.1 Basic Geometry [1d2d70]

```

#define IM imag
#define RE real
using lld = int64_t;
using llf = long double;
using PT = complex<lld>;
using PF = complex<llf>;
using P = PT;
llf abs(P p) { return sqrtl(norm(p)); }
PF toPF(PT p) { return PF(RE(p), IM(p)); }
int sgn(lld x) { return (x > 0) - (x < 0); }
lld dot(P a, P b) { return RE(conj(a) * b); }
lld cross(P a, P b) { return IM(conj(a) * b); }
int ori(P a, P b, P c) {
    return sgn(cross(b - a, c - a));
}
int quad(P p) {
    return (IM(p) == 0) // use sgn for PF
        ? (RE(p) < 0 ? 3 : 1) : (IM(p) < 0 ? 0 : 2);
}
int argCmp(P a, P b) {
    // returns 0/+-1, starts from theta = -PI
    int qa = quad(a), qb = quad(b);
    if (qa != qb) return sgn(qa - qb);
    return sgn(cross(b, a));
}
P rot90(P p) { return P{-IM(p), RE(p)}; }
template <typename V> llf area(const V &pt) {
    lld ret = 0; // BE CAREFUL OF TYPE!
    for (int i = 1; i + 1 < (int)pt.size(); i++)
        ret += cross(pt[i] - pt[0], pt[i+1] - pt[0]);
    return ret / 2.0;
}
template <typename V> PF center(const V &pt) {
    P ret = 0; lld A = 0; // BE CAREFUL OF TYPE!
    for (int i = 1; i + 1 < (int)pt.size(); i++) {
        lld cur = cross(pt[i] - pt[0], pt[i+1] - pt[0]);
        ret += (pt[i] + pt[i + 1] + pt[0]) * cur; A += cur;
    }
    return toPF(ret) / llf(A * 3);
}
PF project(PF p, PF q) { // p onto q
    return dot(p, q) * q / dot(q, q); // dot<llf>
}

```

6.2 2D Convex Hull [ecba37]

```

// from NaCl, counterclockwise, be careful of n<=2
vector<P> convex_hull(vector<P> v) { // n==0 will RE
    sort(all(v)); // by X then Y
    if (v[0] == v.back()) return {v[0]};
    int t = 0, s = 1; vector<P> h(v.size() + 1);
    for (int _ = 2; _--; s = t--, reverse(all(v)))
        for (P p : v) {
            while (t > s && ori(p, h[t-1], h[t-2]) >= 0) t--;
            h[t++] = p;
        }
    return h.resize(t), h;
}

```

6.3 2D Farthest Pair [8b5844]

```

// p is CCW convex hull w/o colinear points
int n = (int)p.size(), pos = 1; lld ans = 0;
for (int i = 0; i < n; i++) {
    P e = p[(i + 1) % n] - p[i];
    while (cross(e, p[(pos + 1) % n] - p[i]) >
        cross(e, p[pos] - p[i]))
        pos = (pos + 1) % n;
    for (int j: {i, (i + 1) % n})
        ans = max(ans, norm(p[pos] - p[j]));
} // tested @ AOJ CGL_4_B

```

6.4 MinMax Enclosing Rect [e4470c]

```

// from 8BQube, plz ensure p is strict convex hull
const llf INF = 1e18, qi = acos(-1) / 2 * 3;
pair<llf, llf> solve(const vector<P> &p) {
    llf mx = 0, mn = INF; int n = (int)p.size();

```



```

for (int i = 0, u = 1, r = 1, l = 1; i < n; ++i) {
#define Z(v) (p[(v) % n] - p[i])
    P e = Z(i + 1);
    while (cross(e, Z(u + 1)) > cross(e, Z(u))) ++u;
    while (dot(e, Z(r + 1)) > dot(e, Z(r))) ++r;
    if (!i) l = r + 1;
    while (dot(e, Z(l + 1)) < dot(e, Z(l))) ++l;
    P D = p[r % n] - p[l % n];
    llf H = cross(e, Z(u)) / llf(norm(e));
    mn = min(mn, dot(e, D) * H);
    llf B = sqrt(norm(D)) * sqrt(norm(Z(u)));
    llf deg = (qi - acos(dot(D, Z(u)) / B)) / 2;
    mx = max(mx, B * sin(deg) * sin(deg));
}
return {mn, mx};
} // test @ UVA 819

```

6.5 Minkowski Sum [602806]

// A, B are strict convex hull rotate to min by (X, Y)

```

vector<P> Minkowski(vector<P> A, vector<P> B) {
    const int N = (int)A.size(), M = (int)B.size();
    vector<P> sa(N), sb(M), C(N + M + 1);
    for (int i = 0; i < N; ++i) sa[i] = A[(i+1)%N]-A[i];
    for (int i = 0; i < M; ++i) sb[i] = B[(i+1)%M]-B[i];
    C[0] = A[0] + B[0];
    for (int i = 0, j = 0; i < N || j < M; ) {
        P e = (j>=M || (i<N && cross(sa[i], sb[j])>=0))
            ? sa[i++] : sb[j++];
        C[i + j] = e;
    }
    partial_sum(all(C), C.begin()); C.pop_back();
    return convex_hull(C); // just to remove colinear
} // be careful if min(|A|,|B|)<=2

```

6.6 Segment Intersection [f98db8]

```

struct Seg { // closed segment
    P st, dir; // represent st + t*dir for 0<=t<=1
    Seg(P s, P e) : st(s), dir(e - s) {}
    static bool valid(lld p, lld q) {
        // is there t s.t. 0 <= t <= 1 && qt == p ?
        if (q < 0) q = -q, p = -p;
        return sgn(0 - p) <= 0 && sgn(p - q) <= 0;
    }
    vector<P> ends() const { return { st, st + dir }; }
};

template <typename T> bool isInter(T A, P p) {
    if (sgn(norm(A.dir)) == 0)
        return sgn(norm(p - A.st)) == 0; // BE CAREFUL
    return sgn(cross(p - A.st, A.dir)) == 0 &&
        T::valid(dot(p - A.st, A.dir), norm(A.dir));
}

template <typename U, typename V>
bool isInter(U A, V B) {
    if (sgn(cross(A.dir, B.dir)) == 0) { // BE CAREFUL
        bool res = false;
        for (P p: A.ends()) res |= isInter(B, p);
        for (P p: B.ends()) res |= isInter(A, p);
        return res;
    }
    P D = B.st - A.st; lld C = cross(A.dir, B.dir);
    return U::valid(cross(D, B.dir), C) &&
        V::valid(cross(D, A.dir), C);
}

```

6.7 Halfplane Intersection [f2bd8f]

```

struct Line {
    P st, ed, dir;
    Line(P s, P e) : st(s), ed(e), dir(e - s) {}
}; using LN = const Line &;
PF intersect(LN A, LN B) {
    llf t = cross(B.st - A.st, B.dir) /
        llf(cross(A.dir, B.dir));
    return toPF(A.st) + toPF(A.dir) * t; // C^3 / C^2
}

bool cov(LN l, LN A, LN B) {
    i128 u = cross(B.st-A.st, B.dir);
    i128 v = cross(A.dir, B.dir);
    // ori(l.st, l.ed, A.st + A.dir*(u/v)) <= 0?
    i128 x = RE(A.dir) * u + RE(A.st - l.st) * v;
    i128 y = IM(A.dir) * u + IM(A.st - l.st) * v;
    return sgn(x*IM(l.dir) - y*RE(l.dir)) * sgn(v) >= 0;
} // x, y are C^3, also sgn<i128> is needed
bool operator<(LN a, LN b) {
    if (int c = argCmp(a.dir, b.dir)) return c == -1;
}

```

```

return ori(a.st, a.ed, b.st) < 0;
}

// cross(pt-line.st, line.dir)<=0 <-> pt in half plane
// the half plane is the LHS when going from st to ed
llf HPI(vector<Line> &q) {
    sort(q.begin(), q.end());
    int n = (int)q.size(), l = 0, r = -1;
    for (int i = 0; i < n; ++i) {
        if (i && !argCmp(q[i].dir, q[i-1].dir)) continue;
        while (l < r && cov(q[i], q[r-1], q[r])) --r;
        while (l < r && cov(q[i], q[l], q[l+1])) ++l;
        q[++r] = q[i];
    }
    while (l < r && cov(q[l], q[r-1], q[r])) --r;
    while (l < r && cov(q[r], q[l], q[l+1])) ++l;
    n = r - l + 1; // q[l .. r] are the lines
    if (n <= 2 || !argCmp(q[l].dir, q[r].dir)) return 0;
    vector<PF> pt(n);
    for (int i = 0; i < n; ++i)
        pt[i] = intersect(q[i+l], q[(i+1)%n+l]);
    return area(pt);
} // test @ 2020 Nordic NCP C : BigBrother

```

6.8 HPI Alternative Form [8b0892]

```

struct Line {
    lld a, b, c; // ax + by + c <= 0
    P dir() const { return P(a, b); }
    Line(lld ta, lld tb, lld tc) : a(ta), b(tb), c(tc) {}
    Line(P S, P T) : a(IM(T-S)), b(-RE(T-S)), c(cross(T,S)) {}
}; using LN = const Line &;
PF intersect(LN A, LN B) {
    llf c = cross(A.dir(), B.dir());
    i128 a = i128(A.c) * B.a - i128(B.c) * A.a;
    i128 b = i128(A.c) * B.b - i128(B.c) * A.b;
    return PF(-b / c, a / c);
}

bool cov(LN l, LN A, LN B) {
    i128 c = cross(A.dir(), B.dir());
    i128 a = i128(A.c) * B.a - i128(B.c) * A.a;
    i128 b = i128(A.c) * B.b - i128(B.c) * A.b;
    return sgn(a * l.b - b * l.a + c * l.c) * sgn(c) >= 0;
}

bool operator<(LN a, LN b) {
    if (int c = argCmp(a.dir(), b.dir())) return c == -1;
    return i128(abs(b.a) + abs(b.b)) * a.c >
        i128(abs(a.a) + abs(a.b)) * b.c;
}

```

6.9 SegmentDist (Sausage) [9d8603]

// be careful of abs<complex<int>> (replace _abs below)

```

llf PointSegDist(P A, Seg B) {
    if (B.dir == P(0)) return _abs(A - B.st);
    if (sgn(dot(A - B.st, B.dir)) *
        sgn(dot(A - B.ed, B.dir)) <= 0)
        return abs(cross(A - B.st, B.dir)) / _abs(B.dir);
    return min(_abs(A - B.st), _abs(A - B.ed));
}

llf SegSegDist(const Seg &s1, const Seg &s2) {
    if (isInter(s1, s2)) return 0;
    return min({
        PointSegDist(s1.st, s2),
        PointSegDist(s1.ed, s2),
        PointSegDist(s2.st, s1),
        PointSegDist(s2.ed, s1) });
} // test @ QOJ2444 / PTZ19 Summer.D3

```

6.10 Rotating Sweep Line [8aff27]

```

struct Event {
    P d; int u, v;
    bool operator<(const Event &b) const {
        return sgn(cross(d, b.d)) > 0;
    }
};

P makePositive(P z) { return cmpxy(z, 0) ? -z : z; }
void rotatingSweepLine(const vector<P> &p) {
    const int n = (int)p.size();
    vector<Event> e; e.reserve(n * (n - 1) / 2);
    for (int i = 0; i < n; ++i)
        for (int j = i + 1; j < n; ++j)
            e.emplace_back(makePositive(p[i] - p[j]), i, j);
    sort(all(e));
    vector<int> ord(n), pos(n);
    iota(all(ord), 0);
    sort(all(ord), [&p](int i, int j) {
        return cmpxy(p[i], p[j]);
    });
}

```

```

for (int i = 0; i < n; i++) pos[ord[i]] = i;
const auto makeReverse = [](auto &v) {
    sort(all(v)); v.erase(unique(all(v)), v.end());
    vector<pair<int, int>> segs;
    for (size_t i = 0, j = 0; i < v.size(); i = j) {
        for (; j < v.size() && v[j] - v[i] <= j - i; j++);
        segs.emplace_back(v[i], v[j] - 1 + 1 + 1);
    }
    return segs;
};
for (size_t i = 0, j = 0; i < e.size(); i = j) {
    /* do here */
    vector<size_t> tmp;
    for (; j < e.size() && !(e[i] < e[j]); j++)
        tmp.push_back(min(pos[e[j].u], pos[e[j].v]));
    for (auto [l, r] : makeReverse(tmp)) {
        reverse(ord.begin() + l, ord.begin() + r);
        for (int t = l; t < r; t++) pos[ord[t]] = t;
    }
}

```

6.11 Hull Cut [2106b1]

```

vector<P> cut(const vector<P> &p, P s, P e) {
    vector<P> res;
    for (size_t i = 0; i < p.size(); i++) {
        P cur = p[i], prv = i ? p[i-1] : p.back();
        bool side = ori(s, e, cur) > 0;
        if (side != (ori(s, e, prv) > 0))
            res.push_back(intersect({s, e}, {cur, prv}));
        if (side) res.push_back(cur);
    } // P is complex<llf>
    return res; // hull intersection with halfplane
} // left of the line s -> e

```

6.12 Point In Hull [13edeb]

```

bool isAnti(P a, P b) {
    return cross(a, b) == 0 && dot(a, b) <= 0;
}
bool PIH(const vector<P> &h, P z, bool strict = true) {
    int n = (int)h.size(), a = 1, b = n - 1, r = !strict;
    if (n < 3) return r && isAnti(h[0] - z, h[n-1] - z);
    if (ori(h[0], h[a], h[b]) > 0) swap(a, b);
    if (ori(h[0], h[a], z) >= r || ori(h[0], h[b], z) <= -r)
        return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (ori(h[0], h[c], z) > 0 ? b : a) = c;
    }
    return ori(h[a], h[b], z) < r;
}

```

6.13 Point In Polygon [037c52]

```

bool PIP(const vector<P> &p, P z, bool strict = true) {
    int cnt = 0, n = (int)p.size();
    for (int i = 0; i < n; i++) {
        P A = p[i], B = p[(i + 1) % n];
        if (isInter(Seg(A, B), z)) return !strict;
        auto zy = IM(z), Ay = IM(A), By = IM(B);
        cnt ^= ((zy < Ay) - (zy < By)) * ori(z, A, B) > 0;
    }
    return cnt;
}

```

6.14 Point In Polygon (Fast) [2cd3d6]

```

vector<int> PIPfast(vector<P> p, vector<P> q) {
    const int N = (int)p.size(), Q = (int)q.size();
    vector<pair<P, int>> evt; vector<Seg> edge;
    for (int i = 0; i < N; i++) {
        int a = i, b = (i + 1) % N;
        P A = p[a], B = p[b];
        assert(A < B || B < A); // std::operator<
        if (B < A) swap(A, B);
        evt.emplace_back(A, i); evt.emplace_back(B, ~i);
        edge.emplace_back(A, B);
    }
    for (int i = 0; i < Q; i++)
        evt.emplace_back(q[i], i + N);
    sort(all(evt));
    auto vtx = p; sort(all(vtx));
    auto eval = [](const Seg &a, lld x) -> lld {
        if (RE(a.dir) == 0) {
            assert(x == RE(a.st));
            return IM(a.st) + llf(IM(a.dir)) / 2;
        }
    }
}

```

```

llf t = (x - RE(a.st)) / llf(RE(a.dir));
return IM(a.st) + IM(a.dir) * t;
};
lld cur_x = 0;
auto cmp = [](const Seg &a, const Seg &b) -> bool {
    if (int s = sgn(eval(a, cur_x) - eval(b, cur_x)))
        return s == -1; // be careful: sgn<llf>, sgn<lld>
    int s = sgn(cross(b.dir, a.dir));
    if (cur_x != RE(a.st) && cur_x != RE(b.st)) s *= -1;
    return s == -1;
};
namespace pbds = __gnu_pbds;
pbds::tree<Seg, int, decltype(cmp),
    pbds::rb_tree_tag,
    pbds::tree_order_statistics_node_update> st(cmp);
auto answer = [&](P ep) {
    if (binary_search(all(vtx), ep))
        return 1; // on vertex
    Seg H(ep, ep); // ??
    auto it = st.lower_bound(H);
    if (it != st.end() && isInter(it->first, ep))
        return 1; // on edge
    if (it != st.begin() && isInter(prev(it)->first, ep))
        return 1; // on edge
    auto rk = st.order_of_key(H);
    return rk % 2 == 0 ? 0 : 2; // 0: outside, 2: inside
};
vector<int> ans(Q);
for (auto [ep, i] : evt) {
    cur_x = RE(ep);
    if (i < 0) { // remove
        st.erase(edge[~i]);
    } else if (i < N) { // insert
        auto [it, succ] = st.insert({edge[i], i});
        assert(succ);
        if (i == N) ans[i - N] = answer(ep);
    }
    return ans;
} // test @ AOJ CGL_3_C

```

6.15 Cyclic Ternary Search [162adf]

```

int cyclic_ternary_search(int N, auto &&lt;lt_) {
    auto lt = [&](int x, int y) {
        return lt_(x % N, y % N);
    };
    int l = 0, r = N; bool up = lt(0, 1);
    while (r - l > 1) {
        int m = (l + r) / 2;
        if (lt(m, 0) ? up : !lt(m, m+1)) r = m;
        else l = m;
    }
    return (lt(l, r) ? r : l) % N;
} // find maximum; be careful if N == 0

```

6.16 Tangent of Points to Hull [8e1343]

```

pair<int, int> get_tangent(const vector<P> &v, P p) {
    auto gao = [&](int s) {
        return cyclic_ternary_search(v.size(),
            [&](int x, int y) {
                return ori(p, v[x], v[y]) == s;
            });
    };
    // test @ codeforces.com/gym/101201/problem/E
    return {gao(1), gao(-1)}; // (a,b):ori(p,v[a],v[b])<0
} // plz ensure that point strictly out of hull
// if colinear, returns arbitrary point on line

```

6.17 Direction In Poly* [a52f3a]

```

bool DIP(const auto &p, int i, P dir) {
    const int n = (int)p.size();
    P A = p[i+1==n ? 0 : i+1] - p[i];
    P B = p[i==0 ? n-1 : i-1] - p[i];
    if (auto C = cross(A, B); C < 0)
        return cross(A, dir) >= 0 || cross(dir, B) >= 0;
    else
        return cross(A, dir) >= 0 && cross(dir, B) >= 0;
} // is Seg(p[i], p[i+dir*eps]) in p? (non-strict)
// p is counterclockwise simple polygon

```

6.18 Circle Class & Intersection [d5df51]

```

llf FMOD(llf x) {
    if (x < -PI) x += PI * 2;
    if (x > PI) x -= PI * 2;
    return x;
}
struct Cir { PF o; llf r; };
// be carefule when tangent
vector<llf> intersectAngle(Cir a, Cir b) {
}

```

```

PF dir = b.o - a.o; llf d2 = norm(dir);
if (norm(a.r - b.r) >= d2) { // norm(x) := |x|^2
    if (a.r < b.r) return {-PI, PI}; // a in b
    else return {}; // b in a
} else if (norm(a.r + b.r) <= d2) return {};
llf dis = abs(dir), theta = arg(dir);
llf phi = acos((a.r * a.r + d2 - b.r * b.r) /
    (2 * a.r * dis)); // is acos_safe needed?
llf L = FMOD(theta - phi), R = FMOD(theta + phi);
return {L, R};
}
vector<PF> intersectPoint(Cir a, Cir b) {
    llf d = abs(a.o - b.o);
    if (d > b.r + a.r || d < abs(b.r - a.r)) return {};
    llf dt = (b.r * b.r - a.r * a.r) / d, d1 = (d + dt) / 2;
    PF dir = (a.o - b.o) / d;
    PF u = dir * d1 + b.o;
    PF v = rot90(dir) * sqrt(max(0.0L, b.r * b.r - d1 * d1));
    return {u + v, u - v};
} // test @ AOJ CGL probs
6.19 Circle Common Tangent [d97f1c]
// be careful of tangent / exact same circle
// sign1 = 1 for outer tang, -1 for inter tang
vector<Line> common_tan(const Cir &a, const Cir &b, int
    sign1) {
    if (norm(a.o - b.o) < eps) return {};
    llf d = abs(a.o - b.o), c = (a.r - sign1 * b.r) / d;
    PF v = (b.o - a.o) / d;
    if (c * c > 1) return {};
    if (abs(c * c - 1) < eps) {
        PF p = a.o + c * v * a.r;
        return {Line(p, p + rot90(b.o - a.o))};
    }
    vector<Line> ret; llf h = sqrt(max(0.0L, 1 - c * c));
    for (int sign2 : {1, -1}) {
        PF n = c * v + sign2 * h * rot90(v);
        PF p1 = a.o + n * a.r;
        PF p2 = b.o + n * (b.r * sign1);
        ret.emplace_back(p1, p2);
    }
    return ret;
}
6.20 Line-Circle Intersection [10786a]
vector<PF> LineCircleInter(PF p1, PF p2, PF o, llf r) {
    PF ft = p1 + project(o - p1, p2 - p1), vec = p2 - p1;
    llf dis = abs(o - ft);
    if (abs(dis - r) < eps) return {ft};
    if (dis > r) return {};
    vec = vec * sqrt(r * r - dis * dis) / abs(vec);
    return {ft + vec, ft - vec}; // sqrt_safe?
}
6.21 Poly-Circle Intersection [8e5133]
// Divides into multiple triangle, and sum up
// from 8BQube, test by HDU2892 & AOJ CGL_7_H
llf _area(PF pa, PF pb, llf r) {
    if (abs(pa) < abs(pb)) swap(pa, pb);
    if (abs(pb) < eps) return 0;
    llf S, h, theta;
    llf a = abs(pb), b = abs(pa), c = abs(pb - pa);
    llf cB = dot(pb, pb - pa) / a / c, B = acos_safe(cB);
    llf cC = dot(pa, pb) / a / b, C = acos_safe(cC);
    if (a > r) {
        S = (C / 2) * r * r; h = a * b * sin(C) / c;
        if (h < r && B < PI / 2)
            S -= (acos_safe(h/r) * r * r - h * sqrt_safe(r * r - h * h));
    } else if (b > r) {
        theta = PI - B - asin_safe(sin(B) / r * a);
        S = 0.5 * a * r * sin(theta) + (C - theta) / 2 * r * r;
    } else
        S = 0.5 * sin(C) * a * b;
    return S;
}
llf area_poly_circle(const vector<PF> &v, PF O, llf r)
{
    llf S = 0;
    for (size_t i = 0, N = v.size(); i < N; ++i)
        S += _area(v[i] - O, v[(i + 1) % N] - O, r) *
            ori(O, v[i], v[(i + 1) % N]);
    return abs(S);
}
6.22 Min Covering Circle [054ee0]

```

```

Cir getCircum(P a, P b, P c) { // P = complex<llf>
    P z1 = a - b, z2 = a - c; llf D = cross(z1, z2) * 2;
    auto c1 = dot(a + b, z1), c2 = dot(a + c, z2);
    P o = rot90(c2 * z1 - c1 * z2) / D;
    return {o, abs(o - a)};
}
Cir minCircleCover(vector<P> p) { // what if p.empty?
    Cir c = {0, 0}; shuffle(all(p), mt19937(114514));
    for (size_t i = 0; i < p.size(); i++) {
        if (abs(p[i] - c.o) <= c.r) continue;
        c = {p[i], 0};
        for (size_t j = 0; j < i; j++) {
            if (abs(p[j] - c.o) <= c.r) continue;
            c.o = (p[i] + p[j]) / llf(2);
            c.r = abs(p[i] - c.o);
            for (size_t k = 0; k < j; k++) {
                if (abs(p[k] - c.o) <= c.r) continue;
                c = getCircum(p[i], p[j], p[k]);
            }
        }
    }
    return c;
} // test @ TIOJ 1093 & luogu P1742
6.23 Circle Union [073c1c]
#define eb emplace_back
struct Teve { // test @ SPOJ N=1000, 0.3~0.5s
    PF p; llf a; int add; // point, ang, add
    Teve(PF x, llf y, int z) : p(x), a(y), add(z) {}
    bool operator<(Teve &b) const { return a < b.a; }
};
// strict: x = 0, otherwise x = -1
bool disjunct(Cir &a, Cir &b, int x)
{ return sgn(abs(a.o - b.o) - a.r - b.r) > x; }
bool contain(Cir &a, Cir &b, int x)
{ return sgn(a.r - b.r - abs(a.o - b.o)) > x; }
vector<llf> CircleUnion(vector<Cir> &c) {
    // area[i] : area covered by at least i circles
    int N = (int)c.size(); vector<llf> area(N + 1);
    vector<vector<int>> overlap(N, vector<int>(N));
    auto g = overlap; // use simple 2darray to speedup
    for (int i = 0; i < N; ++i)
        for (int j = 0; j < N; ++j) {
            /* c[j] is non-strictly in c[i]. */
            overlap[i][j] = i != j &&
                (sgn(c[i].r - c[j].r) > 0 ||
                 (sgn(c[i].r - c[j].r) == 0 && i < j)) &&
                contain(c[i], c[j], -1);
        }
    for (int i = 0; i < N; ++i)
        for (int j = 0; j < N; ++j)
            g[i][j] = i != j && !(overlap[i][j] ||
                overlap[j][i] || disjunct(c[i], c[j], -1));
    for (int i = 0; i < N; ++i) {
        vector<Teve> eve; int cnt = 1;
        for (int j = 0; j < N; ++j) cnt += overlap[j][i];
        // if (cnt > 1) continue; (if only need area[1])
        for (int j = 0; j < N; ++j) if (g[i][j]) {
            auto IP = intersectPoint(c[i], c[j]);
            PF aa = IP[1], bb = IP[0];
            llf A = arg(aa - c[i].o), B = arg(bb - c[i].o);
            eve.eb(bb, B, 1); eve.eb(aa, A, -1);
            if (B > A) ++cnt;
        }
        if (eve.empty()) area[cnt] += PI * c[i].r * c[i].r;
        else {
            sort(eve.begin(), eve.end());
            eve.eb(eve[0]); eve.back().a += PI * 2;
            for (size_t j = 0; j + 1 < eve.size(); j++) {
                cnt += eve[j].add;
                area[cnt] += cross(eve[j].p, eve[j+1].p) * .5;
                llf t = eve[j + 1].a - eve[j].a;
                area[cnt] += (t - sin(t)) * c[i].r * c[i].r * .5;
            }
        }
    }
    return area;
}
6.24 Polygon Union [42e75b]
llf polyUnion(const vector<vector<P>> &p) {
    vector<tuple<P, P, int>> seg;
    for (int i = 0; i < ssize(p); i++)
        for (int j = 0, m = int(p[i].size()); j < m; j++)

```

```

    seg.emplace_back(p[i][j], p[i][(j + 1) % m], i);
    llf ret = 0; // area of p[i] must be non-negative
    for (auto [A, B, i] : seg) {
        vector<pair<llf, int>> evt{{0, 0}, {1, 0}};
        for (auto [C, D, j] : seg) {
            int sc = ori(A, B, C), sd = ori(A, B, D);
            if (sc != sd && i != j && min(sc, sd) < 0) {
                llf sa = cross(D-C, A-C), sb = cross(D-C, B-C);
                evt.emplace_back(sa / (sa - sb), sgn(sc - sd));
            } else if (!sc && !sd && j < i
                && sgn(dot(B - A, D - C)) > 0) {
                evt.emplace_back(real((C - A) / (B - A)), 1);
                evt.emplace_back(real((D - A) / (B - A)), -1);
            }
        }
        for (auto &[q, _] : evt) q = clamp<llf>(q, 0, 1);
        sort(evt.begin(), evt.end());
        llf sum = 0, last = 0; int cnt = 0;
        for (auto [q, c] : evt) {
            if (!cnt) sum += q - last;
            cnt += c; last = q;
        }
        ret += cross(A, B) * sum;
    }
    return ret / 2;
}

```

6.25 3D Point [46b73b]

```

struct P3 {
    lld x, y, z;
    P3 operator^(const P3 &b) const {
        return {y*b.z-b.y*z, z*b.x-b.z*x, x*b.y-b.x*y};
    }
    //Azimuthal angle (longitude) to x-axis. \in [-pi, pi]
    llf phi() const { return atan2(y, x); }
    //Zenith angle (latitude) to the z-axis. \in [0, pi]
    llf theta() const { return atan2(sqrt(x*x+y*y), z); }
};
P3 ver(P3 a, P3 b, P3 c) { return (b - a) ^ (c - a); }
lld volume(P3 a, P3 b, P3 c, P3 d) {
    return dot(ver(a, b, c), d - a);
}
P3 rotate_around(P3 p, llf angle, P3 axis) {
    llf s = sin(angle), c = cos(angle);
    P3 u = normalize(axis);
    return u*dot(u, p)*(1-c) + p * c + cross(u, p)*s;
}

```

6.26 3D Convex Hull [01652a]

```

struct Face {
    int a, b, c;
    Face(int ta, int tb, int tc) : a(ta), b(tb), c(tc) {}
};
auto preprocess(const vector<P3> &pt) {
    auto G = pt.begin();
    auto a = find_if(all(pt), [&](P3 z) {
        return z != *G; }) - G;
    auto b = find_if(all(pt), [&](P3 z) {
        return ver(*G, pt[a], z) != P3(0, 0, 0); }) - G;
    auto c = find_if(all(pt), [&](P3 z) {
        return volume(*G, pt[a], pt[b], z) != 0; }) - G;
    vector<size_t> id;
    for (size_t i = 0; i < pt.size(); i++)
        if (i != a && i != b && i != c) id.push_back(i);
    return tuple{a, b, c, id};
}
// return the faces with pt indexes
// all points coplanar case will WA
vector<Face> convex_hull_3D(const vector<P3> &pt) {
    const int n = int(pt.size());
    if (n <= 3) return {}; // be careful about edge case
    vector<Face> now;
    vector<vector<int>> z(n, vector<int>(n));
    auto [a, b, c, ord] = preprocess(pt);
    now.emplace_back(a, b, c); now.emplace_back(c, b, a);
    for (auto i : ord) {
        vector<Face> next;
        for (const auto &f : now) {
            lld v = volume(pt[f.a], pt[f.b], pt[f.c], pt[i]);
            if (v <= 0) next.push_back(f);
            z[f.a][f.b] = z[f.b][f.c] = z[f.c][f.a] = sgn(v);
        }
        const auto F = [&](int x, int y) {
            if (z[x][y] > 0 && z[y][x] <= 0)

```

```

        next.emplace_back(x, y, i);
    };
    for (const auto &f : now)
        F(f.a, f.b), F(f.b, f.c), F(f.c, f.a);
    now = next;
}
return now;
}
// n^2 delaunay: facets with negative z normal of
// convexhull of (x, y, x^2 + y^2), use a pseudo-point
// (0, 0, inf) to avoid degenerate case
// test @ SPOJ CH3D
// llf area = 0, vol = 0; // surface area / volume
// for (auto [a, b, c]: faces)
// area += abs(ver(p[a], p[b], p[c]))/2.0,
// vol += volume(P3(0, 0, 0), p[a], p[b], p[c])/6.0;

```

6.27 3D Projection [68f350]

```

using P3F = valarray<llf>;
P3F toP3F(P3 p) { return {p.x, p.y, p.z}; }
llf dot(P3F a, P3F b) {
    return a[0]*b[0]+a[1]*b[1]+a[2]*b[2];
}
P3F housev(P3 A, P3 B, int s) {
    const llf a = abs(A), b = abs(B);
    return toP3F(A) / a + s * toP3F(B) / b;
}
P project(P3 p, P3 q) {
    P3 o(0, 0, 1);
    P3F u = housev(q, o, q.z > 0 ? 1 : -1);
    auto pf = toP3F(p);
    auto np = pf - 2 * u * dot(u, pf) / dot(u, u);
    return P(np[0], np[1]);
}
// project p onto the plane q^Tx = 0

```

6.28 3D Skew Line Nearest Point

- $L_1 : v_1 = p_1 + t_1 d_1, L_2 : v_2 = p_2 + t_2 d_2$
- $n = d_1 \times d_2$
- $n_1 = d_1 \times n, n_2 = d_2 \times n$
- $c_1 = p_1 + \frac{(p_2 - p_1) \cdot n_2}{d_1 \cdot n_2} d_1, c_2 = p_2 + \frac{(p_1 - p_2) \cdot n_1}{d_2 \cdot n_1} d_2$

6.29 Delaunay [3a4ff1] - 1ae24/19ec42

```

/* please ensure input points are unique */
/* A triangulation such that no points will strictly
inside circumcircle of any triangle. C should be big
enough s.t. the initial triangle contains all points */
#define L(i) ((i)==0 ? 2 : (i)-1)
#define R(i) ((i)==2 ? 0 : (i)+1)
#define F3 for (int i = 0; i < 3; i++)
bool is_inf(P z) { return RE(z) <= -C || RE(z) >= C; }
bool in_cc(const array<P,3> &p, P q) {
    i128 inf_det = 0, det = 0, inf_N, N;
    F3 {
        if (is_inf(p[i]) && is_inf(q)) continue;
        else if (is_inf(p[i])) inf_N = 1, N = -norm(q);
        else if (is_inf(q)) inf_N = -1, N = norm(p[i]);
        else inf_N = 0, N = norm(p[i]) - norm(q);
        lld D = cross(p[R(i)] - q, p[L(i)] - q);
        inf_det += inf_N * D; det += N * D;
    }
    return inf_det != 0 ? inf_det > 0 : det > 0;
}
P v[maxn];
struct Tri;
struct E {
    Tri *t; int side;
    E(Tri *t_=0, int side_=0) : t(t_), side(side_) {}
};
struct Tri {
    array<int,3> p; array<Tri*,3> ch; array<E,3> e;
    Tri(int a=0, int b=0, int c=0) : p{a, b, c}, ch{} {}
    bool has_chd() const { return ch[0] != nullptr; }
    bool contains(int q) const {
        F3 if (ori(v[p[i]], v[p[R(i)]], v[q]) < 0)
            return false;
        return true;
    }
    bool check(int q) const {
        return in_cc({v[p[0]], v[p[1]], v[p[2]]}, v[q]);
    }
} pool[maxn * 10], *it, *root;
/* SPLIT_HASH_HERE */
void link(const E &a, const E &b) {
    if (a.t) a.t->e[a.side] = b;
    if (b.t) b.t->e[b.side] = a;
}

```



```

}
void flip(Tri *A, int a) {
    auto [B, b] = A->e[a]; /* flip edge between A,B */
    if (!B || !A->check(B->p[b])) return;
    Tri *X = new (it++) Tri(A->p[R(a)], B->p[b], A->p[a]);
    Tri *Y = new (it++) Tri(B->p[R(b)], A->p[a], B->p[b]);
    link(E(X, 0), E(Y, 0));
    link(E(X, 1), A->e[L(a)]); link(E(X, 2), B->e[R(b)]);
    link(E(Y, 1), B->e[L(b)]); link(E(Y, 2), A->e[R(a)]);
    A->ch = B->ch = {X, Y, nullptr};
    flip(X, 1); flip(X, 2); flip(Y, 1); flip(Y, 2);
}

void add_point(int p) {
    Tri *r = root;
    while (r->has_chd()) for (Tri *c: r->ch)
        if (c && c->contains(p)) { r = c; break; }
    array<Tri*, 3> t; /* split into 3 triangles */
    F3 t[i] = new (it++) Tri(r->p[i], r->p[R(i)], p);
    F3 link(E(t[i], 0), E(t[R(i)], 1));
    F3 link(E(t[i], 2), r->e[L(i)]);
    r->ch = t;
    F3 flip(t[i], 2);
}

auto build(const vector<P> &p) {
    it = pool; int n = (int)p.size();
    vector<int> ord(n); iota(all(ord), 0);
    shuffle(all(ord), mt19937(114514));
    root = new (it++) Tri(n, n + 1, n + 2);
    copy_n(p.data(), n, v); v[n++] = P(-C, -C);
    v[n++] = P(C * 2, -C); v[n++] = P(-C, C * 2);
    for (int i : ord) add_point(i);
    vector<array<int, 3>> res;
    for (Tri *now = pool; now != it; now++)
        if (!now->has_chd()) res.push_back(now->p);
    return res;
}

```

6.30 Build Voronoi [94f000]

```

void build_voronoi_cells(auto &&p, auto &&res) {
    vector<vector<int>> adj(p.size());
    for (auto f: res) F3 {
        int a = f[i], b = f[R(i)];
        if (a >= p.size() || b >= p.size()) continue;
        adj[a].emplace_back(b);
    }
    // use `adj` and `p` and HPI to build cells
    for (size_t i = 0; i < p.size(); i++) {
        vector<Line> ls = frame; // the frame
        for (int j : adj[i]) {
            P m = p[i] + p[j], d = rot90(p[j] - p[i]);
            assert(norm(d) != 0);
            ls.emplace_back(m, m + d); // doubled coordinate
        } // HPI(ls)
    }
}

```

6.31 Simulated Annealing* [4e0fe5]

```

llf anneal() {
    mt19937 rnd_engine(seed);
    uniform_real_distribution<llf> rnd(0, 1);
    const llf dT = 0.001;
    // Argument p
    llf S_cur = calc(p), S_best = S_cur;
    for (llf T = 2000; T > EPS; T -= dT) {
        // Modify p to p_prime
        const llf S_prime = calc(p_prime);
        const llf delta_c = S_prime - S_cur;
        llf prob = min((llf)1, exp(-delta_c / T));
        if (rnd(rnd_engine) <= prob)
            S_cur = S_prime, p = p_prime;
        if (S_prime < S_best) // find min
            S_best = S_prime, p_best = p_prime;
    }
    return S_best;
}

```

6.32 Triangle Centers* [adb146]

```

O = ... // see min circle cover
G = (A + B + C) / 3;
H = G * 3 - O * 2; // orthogonal center
llf a = abs(B - C), b = abs(A - C), c = abs(A - B);
I = (a * A + b * B + c * C) / (a + b + c);
// FermatPoint: minimizes sum of distance
// if max. angle >= 120 deg then vertex

```

// otherwise, make eq. triangle AB'C, CA'B, BC'A
// line AA', BB', CC' intersects at P

7 Stringology

7.1 Hash [37b06a]

```

template<int P = 127, int Q = 1051762951>
class RH {
    vector<int> h, p;
public:
    RH(const auto &s) : h(s.size()+1), p(s.size()+1) {
        for (size_t i = 0; i < s.size(); ++i)
            h[i + 1] = add(mul(h[i], P), s[i]);
        generate(all(p), [x = 1, y = 1, this]() mutable {
            return y = x, x = mul(x, P), y; });
    }
    int query(int l, int r) const { // 0-base [l, r)
        return sub(h[r], mul(h[l], p[r - l]));
    }
};

```

7.2 Suffix Array [a1d8fe] - 9603d1/eb7a2f

```

auto sais(const auto &s) {
    const int n = (int)s.size(), z = ranges::max(s) + 1;
    if (n == 1) return vector{0};
    vector<int> c(z); for (int x : s) ++c[x];
    partial_sum(all(c), begin(c));
    vector<int> sa(n); auto I = views::iota(0, n);
    vector<bool> t(n); t[n - 1] = true;
    for (int i = n - 2; i >= 0; --i)
        t[i] = (s[i] == s[i + 1] ? t[i + 1] : s[i] < s[i + 1]);
    auto is_lms = views::filter([&t](int x) {
        return x && t[x] && !t[x - 1]; });
    auto induce = [&] {
        for (auto x = c; int y : sa)
            if (y-- if (!t[y]) sa[x[s[y] - 1]++] = y;
        for (auto x = c; int y : sa | views::reverse)
            if (y-- if (t[y]) sa[--x[s[y]]] = y;
    };
    vector<int> lms, q(n); lms.reserve(n);
    for (auto x = c; int i : I | is_lms) {
        q[i] = int(lms.size());
        lms.push_back(sa[--x[s[i]]] = i);
    }
    induce(); vector<int> ns(lms.size());
    for (int j = -1, nz = 0; int i : sa | is_lms) {
        if (j >= 0) {
            int len = min({n - i, n - j, lms[q[i] + 1] - i});
            ns[q[i]] = nz += lexicographical_compare(
                begin(s) + j, begin(s) + j + len,
                begin(s) + i, begin(s) + i + len);
        }
        j = i;
    }
    ranges::fill(sa, 0); auto nsa = sais(ns);
    for (auto x = c; int y : nsa | views::reverse)
        y = lms[y], sa[--x[s[y]]] = y;
    return induce(), sa;
}

// SPLIT_HASH_HERE sa[i]: sa[i]-th suffix is the
// i-th lexicographically smallest suffix.
// hi[i]: LCP of suffix sa[i] and suffix sa[i - 1].
struct Suffix {
    int n; vector<int> sa, hi, rev;
    Suffix(const auto &s) : n((int)s.size()),
        hi(n), rev(n) {
        vector<int> _s(n + 1); // _s[n] = 0;
        copy(all(s), begin(_s)); // s shouldn't contain 0
        sa = sais(_s); sa.erase(sa.begin());
        for (int i = 0; i < n; ++i) rev[sa[i]] = i;
        for (int i = 0, h = 0; i < n; ++i) {
            if (!rev[i]) { h = 0; continue; }
            for (int j = sa[rev[i] - 1]; i + h < n && j + h < n
                && s[i + h] == s[j + h];) ++h;
            hi[rev[i]] = h ? h-- : 0;
        }
    }
};

```

7.3 Suffix Array Tools* [8e08c8]

```

template<int LG = 20> struct SparseTableSA : Suffix {
    array<vector<int>, LG> mn;
    SparseTableSA(const auto &s) : Suffix(s), mn[hi] {
        for (int l = 0; l + 1 < LG; l++) { mn[l+1].resize(n);
            for (int i = 0, len = 1 << l; i + len < n; i++)

```

```

    mn[l + 1][i] = min(mn[l][i], mn[l][i + len]);
}
}
int lcp(int a, int b) {
    if (a == b) return n - a;
    a = rev[a] + 1, b = rev[b] + 1;
    if (a > b) swap(a, b);
    const int lg = __lg(b - a);
    return min(mn[lg][a], mn[lg][b - (1 << lg)]);
} // equivalent to lca on the kruskal tree
pair<int, int> get_range(int x, int len) { // WIP
    int a = rev[x] + 1, b = rev[x] + 1;
    for (int l = LG - 1; l >= 0; l--) {
        const int s = 1 << l;
        if (a + s <= n && mn[l][a] >= len) a += s;
        if (b - s >= 0 && mn[l][b - s] >= len) b -= s;
    }
    return {b - 1, a};
} // if offline, solve get_range with DSU
};

```

7.4 Ex SAM* [58374b]

```

struct exSAM {
    int len[maxn * 2], link[maxn * 2]; // maxlen, suflink
    int next[maxn * 2][maxc], tot; // [0, tot), root = 0
    int ord[maxn * 2]; // topo. order (sort by length)
    int cnt[maxn * 2]; // occurrence
    int newnode() {
        fill_n(next[tot], maxc, 0);
        return len[tot] = cnt[tot] = link[tot] = 0, tot++;
    }
    void init() { tot = 0, newnode(), link[0] = -1; }
    int insertSAM(int last, int c) {
        int cur = next[last][c];
        len[cur] = len[last] + 1;
        int p = link[last];
        while (p != -1 && !next[p][c])
            next[p][c] = cur, p = link[p];
        if (p == -1) return link[cur] = 0, cur;
        int q = next[p][c];
        if (len[p] + 1 == len[q]) return link[cur] = q, cur;
        int clone = newnode();
        for (int i = 0; i < maxc; ++i)
            next[clone][i] = len[next[q][i]] ? next[q][i] : 0;
        len[clone] = len[p] + 1;
        while (p != -1 && next[p][c] == q)
            next[p][c] = clone, p = link[p];
        link[link[cur] = clone] = link[q];
        link[q] = clone;
        return cur;
    }
    void insert(const string &s) {
        int cur = 0;
        for (char ch : s) {
            int &nxt = next[cur][int(ch - 'a')];
            if (!nxt) nxt = newnode();
            cnt[cur = nxt] += 1;
        }
    }
    void build() {
        queue<int> q; q.push(0);
        while (!q.empty()) {
            int cur = q.front(); q.pop();
            for (int i = 0; i < maxc; ++i)
                if (next[cur][i]) q.push(insertSAM(cur, i));
        }
        vector<int> lc(tot);
        for (int i = 1; i < tot; ++i) ++lc[len[i]];
        partial_sum(all(lc), lc.begin());
        for (int i = 1; i < tot; ++i) ord[--lc[len[i]]] = i;
    }
    void solve() {
        for (int i = tot - 2; i >= 0; --i)
            cnt[link[ord[i]]] += cnt[ord[i]];
    }
};

```

7.5 KMP [3727f3]

```

vector<int> kmp(const auto &s) {
    vector<int> f(s.size());
    for (int i = 1, k = 0; i < (int)s.size(); ++i) {
        while (k > 0 && s[i] != s[k]) k = f[k - 1];
        f[i] = (k += (s[i] == s[k]));
    }
}

```

```

return f;
}
vector<int> search(const auto &s, const auto &t) {
    // return 0-indexed occurrence of t in s
    vector<int> f = kmp(t), r;
    for (int i = 0, k = 0; i < (int)s.size(); ++i) {
        while (k > 0 && s[i] != t[k]) k = f[k - 1];
        k += (s[i] == t[k]);
        if (k == (int)t.size())
            r.push_back(i - t.size() + 1), k = f[k - 1];
    }
    return r;
}

```

7.6 Z value [6a7fd0]

```

vector<int> Zalgo(const string &s) {
    vector<int> z(s.size(), s.size());
    for (int i = 1, l = 0, r = 0; i < z[0]; ++i) {
        int j = clamp(r - i, 0, z[i - l]);
        for (; i + j < z[0] and s[i + j] == s[j]; ++j);
        if (i + (z[i] = j) > r) r = i + z[i];
    }
    return z;
}

```

7.7 Manacher [c938a9]

```

vector<int> manacher(const string &S) {
    const int n = (int)S.size(), m = n * 2 + 1;
    vector<int> z(m);
    string t = "."; for (char c : S) t += c, t += '.';
    for (int i = 1, l = 0, r = 0; i < m; ++i) {
        z[i] = (r > i ? min(z[2 * l - i], r - i) : 1);
        while (i - z[i] >= 0 && i + z[i] < m) {
            if (t[i - z[i]] == t[i + z[i]]) ++z[i];
            else break;
        }
        if (i + z[i] > r) r = i + z[i], l = i;
    }
    return z; // the palindrome lengths are z[i] - 1
}

```

```

/* for (int i = 1; i + 1 < m; ++i) {
    int l = (i - z[i] + 2) / 2, r = (i + z[i]) / 2;
    if (l != r) // [l, r) is maximal palindrome
} */

```

7.8 Lyndon Factorization [d22cc9]

```

// partition s = w[0] + w[1] + ... + w[k-1],
// w[0] >= w[1] >= ... >= w[k-1]
// each w[i] strictly smaller than all its suffix
void duval(const auto &s, auto &&report) {
    for (int n = (int)s.size(), i = 0, j, k; i < n; ) {
        for (j = i + 1, k = i; j < n && s[k] <= s[j]; j++)
            k = (s[k] < s[j] ? i : k + 1);
        // if (i < n / 2 && j >= n / 2) {
        // for min cyclic shift, call duval(s + s)
        // then here s.substr(i, n / 2) is min cyclic shift
        // }
        for (; i <= k; i += j - k)
            report(i, j - k); // s.substr(l, len)
    }
} // tested @ luogu 6114, 1368 & UVA 719

```

7.9 Main Lorentz* [615b8f]

```

vector<pair<int, int>> rep[kN]; // 0-base [l, r]
void main_lorentz(const string &s, int sft = 0) {
    const int n = s.size();
    if (n == 1) return;
    const int nu = n / 2, nv = n - nu;
    const string u = s.substr(0, nu), v = s.substr(nu);
    ru(u.rbegin(), u.rend()), rv(v.rbegin(), v.rend());
    main_lorentz(u, sft), main_lorentz(v, sft + nu);
    const auto z1 = Zalgo(ru), z2 = Zalgo(v + '#' + u),
        z3 = Zalgo(ru + '#' + rv), z4 = Zalgo(v);
    auto get_z = [](const vector<int> &z, int i) {
        return (0 <= i and i < (int)z.size()) ? z[i] : 0;
    };
    auto add_rep = [&](bool left, int c, int l, int k1,
        int k2) {
        const int L = max(1, l - k2), R = min(l - left, k1);
        if (L > R) return;
        if (left) rep[l].emplace_back(sft + c - R, sft + c - L);
        else rep[l].emplace_back(sft + c - R - l + 1, sft + c - L - l + 1);
    };
    for (int cntr = 0; cntr < n; cntr++) {

```

```

int l, k1, k2;
if (cntr < nu) {
    l = nu - cntr;
    k1 = get_z(z1, nu - cntr);
    k2 = get_z(z2, nv + 1 + cntr);
} else {
    l = cntr - nu + 1;
    k1 = get_z(z3, nu + 1 + nv - 1 - (cntr - nu));
    k2 = get_z(z4, (cntr - nu) + 1);
}
if (k1 + k2 >= l)
    add_rep(cntr < nu, cntr, l, k1, k2);
}
}

```

7.10 BWT* [a8287e]

```

void BWT(char *ori, char *res) {
    // make ori -> ori + ori then build suffix array
}
void iBWT(char *ori, char *res) {
    vector<int> v[SIGMA], a;
    const int len = strlen(ori); res[len] = 0;
    for (int i = 0; i < len; i++) v[ori[i] - 'a'].pb(i);
    for (int i = 0, ptr = 0; i < SIGMA; i++)
        for (int j : v[i]) a.pb(j), ori[ptr++] = 'a' + i;
    for (int i = 0, ptr = 0; i < len; i++)
        res[i] = ori[a[ptr]], ptr = a[ptr];
}

```

7.11 Palindromic Tree* [c4be59]

```

struct PalindromicTree {
    struct node {
        int nxt[26], f, len; // num = depth of fail link
        int cnt, num; // = #pal_suffix of this node
        node(int l = 0) : nxt{}, f(0), len(l), cnt(0), num(0) {}
    };
    vector<node> st; vector<int> s; int last, n;
    void init() {
        st.clear(); s.clear(); last = 1; n = 0;
        st.push_back(0); st.push_back(-1);
        st[0].f = 1; s.push_back(-1);
    }
    int getFail(int x) {
        while (s[n - st[x].len - 1] != s[n]) x = st[x].f;
        return x;
    }
    void add(int c) {
        s.push_back(c - 'a'); ++n;
        int cur = getFail(last);
        if (!st[cur].nxt[c]) {
            int now = (int)st.size();
            st.push_back(st[cur].len + 2);
            st[now].f = st[getFail(st[cur].f)].nxt[c];
            st[cur].nxt[c] = now;
            st[now].num = st[st[now].f].num + 1;
        }
        last = st[cur].nxt[c]; ++st[last].cnt;
    }
    void dpcnt() { // cnt = #occurrence in whole str
        for (auto nd : st | views::reverse)
            st[nd.f].cnt += nd.cnt;
    }
    int size() { return (int)st.size() - 2; }
} pt; /* string s; cin >> s; pt.init();
for (int i = 0; i < SZ(s); i++) {
    int prvsz = pt.size(); pt.add(s[i]);
    if (prvsz != pt.size()) {
        int r = i, l = r - pt.st[pt.last].len + 1;
        // pal @ [l,r]: s.substr(l, r-l+1)
    }
} */


```

8 Misc

8.1 Theorems

Spherical Coordinate

$$\begin{aligned}
 x &= r \sin \theta \cos \phi \\
 y &= r \sin \theta \sin \phi \\
 z &= r \cos \theta
 \end{aligned}$$



$$\begin{aligned}
 r &= \sqrt{x^2 + y^2 + z^2} \\
 \theta &= \arccos(z / \sqrt{x^2 + y^2 + z^2}) \\
 \phi &= \operatorname{atan2}(y, x)
 \end{aligned}$$

Spherical Cap

• A portion of a sphere cut off by a plane.

- r : sphere radius, a : radius of the base of the cap, h : height of the cap, θ : $\arcsin(a/r)$.
- Volume = $\pi h^2(3r - h)/3 = \pi h(3a^2 + h^2)/6 = \pi r^3(2 + \cos \theta)(1 - \cos \theta)^2/3$.
- Area = $2\pi r h = \pi(a^2 + h^2) = 2\pi r^2(1 - \cos \theta)$.

Sherman-Morrison formula

$$(A + uv^T)^{-1} = A^{-1} - \frac{A^{-1}uv^TA^{-1}}{1 + v^TA^{-1}u}$$

Kirchhoff's Theorem

Denote L be a $n \times n$ matrix as the Laplacian matrix of graph G , where $L_{ii} = d(i)$, $L_{ij} = -c$ where c is the number of edge (i, j) in G .

- The number of undirected spanning in G is $\det(\tilde{L}_{11})$.
- The number of directed spanning tree rooted at r in G is $\det(\tilde{L}_{rr})$.

BEST Theorem

If G is (strongly) connected and indegree equals outdegree, then $\#\{\text{Eulerian circuits}\} = \#\{\text{arborescences rooted at } 1\} \cdot \prod_{v \in V} (\deg(v) - 1)!$

Random Walk on Graph

Let P be the transition matrix of a strongly connected directed graph, $\sum_j P_{i,j} = 1$. Let $F_{i,j}$ be the expected time to reach j from i . Let g_i be the expected time from i to i , $G = \text{diag}(g)$ and J be a matrix all of 1, i.e. $J_{i,j} = 1$. Then, $F = J - G + PF$

First solve G : let $\pi P = \pi$ be a stationary distribution. Then $\pi_i g_i = 1$. The rank of $I - P$ is $n - 1$, so we first solve a special solution X such that $(I - P)X = J - G$ and adjust X to F by $F_{i,j} = X_{i,j} - X_{j,j}$.

Tutte Matrix

For $i < j$, $d_{ij} = x_{ij}$ (in practice, a random number) if $(i, j) \in E$, otherwise $d_{ij} = 0$. For $i \geq j$, $d_{ij} = -d_{ji} \cdot \frac{\text{rank}(D)}{2}$ is the maximum matching.

Cayley's Formula

- Given a degree sequence d_1, d_2, \dots, d_n for each labeled vertices, there're $\frac{(n-2)!}{(d_1-1)!(d_2-1)!\dots(d_n-1)!}$ spanning trees.
- Let $T_{n,k}$ be the number of labeled forests on n vertices with k components, such that vertex $1, 2, \dots, k$ belong to different components. Then $T_{n,k} = kn^{n-k-1}$.

Erdős-Gallai theorem

A sequence of non-negative integers $d_1 \geq d_2 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only if $d_1 + d_2 + \dots + d_n$ is even and $\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$ holds for all $1 \leq k \leq n$.

Havel-Hakimi algorithm

Find the vertex who has greatest degree unused, connect it with other greatest vertex.

Gale-Ryser theorem

A pair of sequences of nonnegative integers $a_1 \geq \dots \geq a_n$ and b_1, \dots, b_n is bigraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

Fulkerson-Chen-Anstee theorem

A sequence $(a_1, b_1), \dots, (a_n, b_n)$ of nonnegative integer pairs with $a_1 \geq \dots \geq a_n$ is digraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^k \min(b_i, k-1) + \sum_{i=k+1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

Euler's planar graph formula

$$V - E + F = C + 1. \quad E \leq 3V - 6 \quad (\text{when } V \geq 3)$$

Pick's theorem

For simple polygon, when points are all integer, we have $A = \#\{\text{lattice points in the interior}\} + \frac{1}{2}\#\{\text{lattice points on the boundary}\} - 1$

Matroid

- $B \subseteq A \wedge A \in \mathcal{I} \Rightarrow B \in \mathcal{I}$.
- If $A, B \in \mathcal{I}$ and $|A| > |B|$, then $\exists x \in A \setminus B, B \cup \{x\} \in \mathcal{I}$.

Linear matroid	$A \in \mathcal{I}$ iff linear indep.
Graphic matroid	\mathcal{I} = forests of undirected graph
Colorful matroid (EX)	Each color c has an upper bound R_c .
Transversal matroid	$A \in \mathcal{I}$ iff \exists matching M whose right part is A .
Bond matroid	$A \in \mathcal{I}$ iff G is connected after removing edges A .
Dual matroid	$A \in \mathcal{I}^*$ iff there is a basis $\subseteq E \setminus A$
Truncated matroid	$A \in \mathcal{I}'$ iff $A \in \mathcal{I} \wedge A \leq k$

Matroid Intersection

Given matroids $M_1 = (G, \mathcal{I}_1), M_2 = (G, \mathcal{I}_2)$, find maximum $S \in \mathcal{I}_1 \cap \mathcal{I}_2$. For each iteration, build the directed graph and find a shortest path from s to t .

- $s \rightarrow x : S \cup \{x\} \in \mathcal{I}_1$
- $x \rightarrow t : S \cup \{x\} \in \mathcal{I}_2$
- $y \rightarrow x : S \setminus \{y\} \cup \{x\} \in \mathcal{I}_1$ (y is in the unique circuit of $S \cup \{x\}$)
- $x \rightarrow y : S \setminus \{y\} \cup \{x\} \in \mathcal{I}_2$ (y is in the unique circuit of $S \cup \{x\}$)

Alternate the path, and $|S|$ will increase by 1. In each iteration, $|E| = O(RN)$, where $R = \min(\text{rank}(\mathcal{I}_1), \text{rank}(\mathcal{I}_2)), N = |G|$. For weighted case, assign weight $-w(x)$ and $w(x)$ to $x \in S$ and $x \notin S$, resp. Find the shortest path by Bellman-Ford. The maximum iteration of Bellman-Ford is $2R + 1$.

Dual of LP

Primal	Dual
Maximize $c^T x$ s.t. $Ax \leq b, x \geq 0$	Minimize $b^T y$ s.t. $A^T y \geq c, y \geq 0$
Maximize $c^T x$ s.t. $Ax \leq b$	Minimize $b^T y$ s.t. $A^T y = c, y \geq 0$
Maximize $c^T x$ s.t. $Ax = b, x \geq 0$	Minimize $b^T y$ s.t. $A^T y \geq c$

Dual of Min Cost b-Flow

- Capacity c_{uv} , Flow f_{uv} , Cost w_{uv} , Required Flow difference for vertex b_u .
- If all w_{uv} are integers, then optimal solution can happen when all p_u are integers.

$$\min \sum_{uv} w_{uv} f_{uv} \text{ s.t. } -f_{uv} \geq -c_{uv}, \sum_v f_{vu} - \sum_v f_{uv} = -b_u$$

$$\Leftrightarrow \min \sum_u b_u p_u + \sum_{uv} c_{uv} \max(0, p_v - p_u - w_{uv}) \text{ s.t. } p_u \geq 0$$

Minimax Theorem

Let $f: X \times Y \rightarrow \mathbb{R}$ be continuous where $X \subseteq \mathbb{R}^n, Y \subseteq \mathbb{R}^m$ are compact and convex. If $f(\cdot, y): X \rightarrow \mathbb{R}$ is concave for fixed y , and $f(x, \cdot): Y \rightarrow \mathbb{R}$ is convex for fixed x , then $\max_{x \in X} \min_{y \in Y} f(x, y) = \min_{y \in Y} \max_{x \in X} f(x, y)$, e.g. $f(x, y) = x^T A y$ for zero-sum matrix game.

Parallel Axis Theorem

The second moment of area is $I_z = \iint x^2 + y^2 dA$. $I_{z'} = I_z + A d^2$ where d is the distance between two parallel axis z, z' .

8.2 Stable Marriage

```
1: Initialize  $m \in M$  and  $w \in W$  to free
2: while  $\exists$  free man  $m$  who has a woman  $w$  to propose to do
3:    $w \leftarrow$  first woman on  $m$ 's list to whom  $m$  has not yet proposed
4:   if  $\exists$  some pair  $(m', w)$  then
5:     if  $w$  prefers  $m$  to  $m'$  then
6:        $m' \leftarrow$  free
7:        $(m, w) \leftarrow$  engaged
8:     end if
9:   else
10:     $(m, w) \leftarrow$  engaged
11:   end if
12: end while
```

8.3 Weight Matroid Intersection* [d00ee8]

```
struct Matroid {
    Matroid(bitset<N>); // init from an independent set
    bool can_add(int); // check if break independence
    Matroid remove(int); // removing from the set
};

auto matroid_intersection(const vector<int> &w) {
    const int n = (int)w.size(); bitset<N> S;
    for (int sz = 1; sz <= n; sz++) {
        Matroid M1(S), M2(S); vector<vector<pii>> e(n + 2);
        for (int j = 0; j < n; j++) if (!S[j]) {
            if (M1.can_add(j)) e[n].eb(j, -w[j]);
            if (M2.can_add(j)) e[j].eb(n + 1, 0);
        }
        for (int i = 0; i < n; i++) if (S[i]) {
            Matroid T1 = M1.remove(i), T2 = M2.remove(i);
            for (int j = 0; j < n; j++) if (!S[j]) {
                if (T1.can_add(j)) e[i].eb(j, -w[j]);
                if (T2.can_add(j)) e[j].eb(i, w[i]);
            }
        }
        // maybe implicit build graph for more speed
        vector<pii> d(n + 2, {INF, 0}); d[n] = {0, 0};
        vector<int> prv(n + 2, -1);
        // change to SPFA for more speed, if necessary
        for (int upd = 1; upd--;)
            for (int u = 0; u < n + 2; u++)
                for (auto [v, c] : e[u]) {
                    pii x(d[u].first + c, d[u].second + 1);
                    if (x < d[v]) d[v] = x, prv[v] = u, upd = 1;
                }
        if (d[n + 1].first >= INF) break;
        for (int x = prv[n + 1]; x != n; x = prv[x]) S.flip(x);
        // S is the max-weighted independent set w/ size sz
    }
    return S;
} // from Nacl
```

8.4 Bitset LCS [4155ab]

```
cin >> n >> m;
for (int i = 1, x; i <= n; ++i)
    cin >> x, p[x].set(i);
for (int i = 1, x; i <= m; ++i) {
    cin >> x, (g = f) |= p[x];
    f.shiftLeftByOne(), f.set(0);
    ((f = g - f) ^= g) &= g;
}
```

```
cout << f.count() << '\n';
```

8.5 Prefix Substring LCS [7d8faf]

```
void all_lcs(string S, string T) { // 0-base
    vector<size_t> h(T.size()); iota(all(h), 1);
    for (size_t a = 0; a < S.size(); ++a) {
        for (size_t c = 0, v = 0; c < T.size(); ++c)
            if (S[a] == T[c] || h[c] < v) swap(h[c], v);
        // here, LCS(s[0, a], t[b, c]) =
        // c - b + 1 - sum([h[i] > b] | i <= c)
    }
} // test @ yosupo judge
```

8.6 Convex 1D/1D DP [2c667e]

```
struct S { int i, l, r; };
void solve(int n, auto &dp, auto &f) {
    deque<S> dq; dq.emplace_back(0, 1, n);
    for (int i = 1; i <= n; ++i) {
        dp[i] = f(dq.front().i, i);
```

```
while (!dq.empty() && dq.front().r <= i)
    dq.pop_front();
dq.front().l = i + 1;
while (!dq.empty() &&
    f(i, dq.back().l) >= f(dq.back().i, dq.back().l))
    dq.pop_back();
int p = i + 1;
if (!dq.empty()) {
    auto [j, l, r] = dq.back();
    for (int s = 1 << 20; s; s >= 1)
        if (l+s <= n && f(i, l+s) < f(j, l+s)) l += s;
    dq.back().r = l; p = l + 1;
}
if (p <= n) dq.emplace_back(i, p, n);
} // dp[i] = max(dp[j] + w(j + 1, i) | j < i)
} // test @ tioj 烏龜疊疊樂
// vector<int64_t> dp(n + 1); dp[0] = 0;
// auto f = [&](int l, int r) -> int64_t {
//     if (r - l > k) return -INF;
//     return dp[l] + w(l + 1, r);
// };
```

8.7 ConvexHull Optimization [b4318e]

```
struct L {
    mutable lld a, b, p;
    bool operator<(const L &r) const {
        return a < r.a; /* here */
    }
    bool operator<(lld x) const { return p < x; }
};

lld Div(lld a, lld b) {
    return a / b - ((a ^ b) < 0 && a % b);
}

struct DynamicHull : multiset<L, less<>> {
    static const lld kInf = 1e18;
    bool Isect(iterator x, iterator y) {
        if (y == end()) { x->p = kInf; return false; }
        if (x->a == y->a)
            x->p = x->b > y->b ? kInf : -kInf; /* here */
        else x->p = Div(y->b - x->b, x->a - y->a);
        return x->p >= y->p;
    }

    void Insert(lld a, lld b) {
        auto z = insert({a, b, 0}), y = z++, x = y;
        while (Isect(y, z)) z = erase(z);
        if (x != begin() && Isect(--x, y)) Isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            Isect(x, erase(y));
    }

    lld Query(lld x) { // default chmax
        auto l = *lower_bound(x); // to chmin:
        return l.a * x + l.b; // modify the 2 "<>"
    }
};
```

8.8 Min Plus Convolution [464dcd]

```
// a is convex a[i+1]-a[i] <= a[i+2]-a[i+1]
vector<int> min_plus_convolution(auto &a, auto &b) {
    const int n = (int)a.size(), m = (int)b.size();
    vector<int> c(n + m - 1, numeric_limits<int>::max());
    auto dc = [&](auto Y, int l, int r, int jl, int jr) {
        if (l > r) return;
        int mid = (l + r) / 2, from = -1, &best = c[mid];
        for (int j = jl; j <= jr; ++j)
            if (int i = mid - j; i >= 0 && i < n)
                if (best > a[i] + b[j]) best = a[i] + b[j], from = j;
        Y(Y, l, mid-1, jl, from); Y(Y, mid+1, r, from, jr);
    };
    return dc(dc, 0, n-1+m-1, 0, m-1), c;
}
```

8.9 SMAWK [f37761]

```
// For all 2x2 submatrix:
// If M[1][0] < M[1][1], M[0][0] < M[0][1]
// If M[1][0] == M[1][1], M[0][0] <= M[0][1]
// M[i][ans_i] is the best value in the i-th row
VI smawk(int N, int M, auto &&select) {
    auto dc = [&](auto self, const VI &r, const VI &c) {
        if (r.empty()) return VI{};
        const int n = (int)r.size(); VI ans(n), nr, nc;
        for (int i : c) {
            while (!nc.empty() &&
                select(r[nc.size() - 1], nc.back(), i))
                nc.pop_back();
            if ((int)nc.size() < n) nc.push_back(i);
        }
    };
}
```



```

for (int i = 1; i < n; i += 2) nr.push_back(r[i]);
const auto na = self(self, nr, nc);
for (int i = 1; i < n; i += 2) ans[i] = na[i >> 1];
for (int i = 0, j = 0; i < n; i += 2) {
    ans[i] = nc[j];
    const int end = i + 1 == n ? nc.back() : ans[i + 1];
    while (nc[j] != end)
        if (select(r[i], ans[i], nc[++j])) ans[i] = nc[j];
}
return ans;
};

VI R(N), C(M); iota(all(R), 0), iota(all(C), 0);
return dc(dc, R, C);
}

bool min_plus_conv_select(int r, int u, int v) {
    auto f = [](int i, int j) {
        if (0 <= i - j && i - j < n) return b[j] + a[i - j];
        return 2100000000 + (i - j);
    };
    return f(r, u) > f(r, v);
} // if f(r, v) is better than f(r, u), return true

```

8.10 De-Bruijn [aa7700]

```
vector<int> de_bruijn(int k, int n) {
    // return cyclic string of len k^n s.t. every string
    // of len n using k char appears as a substring.
    vector<int> aux(n + 1), res;
    auto db = [&](auto self, int t, int p) -> void {
        if (t <= n)
            for (int i = aux[t - p]; i < k; ++i, p = t)
                aux[t] = i, self(self, t + 1, p);
        else if (n % p == 0) for (int i = 1; i <= p; ++i)
            res.push_back(aux[i]);
    };
    return db(db, 1, 1), res;
}
```

8.11 Josephus Problem [7f9ceb]

```

l1ld f(l1ld n, l1ld m, l1ld k) { // n 人每间隔 m-1 個殺
l1ld s = (m - 1) % (n - k); // O(k)
for (l1ld i = n - k + 1; i <= n; i++) s = (s + m) % i;
return s;
}

l1ld kth(l1ld n, l1ld m, i128 k) { // died at kth
if (m == 1) return k; // O(m log(n))
for (k = k*m+m-1; k >= n; k = k-n + (k-n)/(m-1));
return k;
} // k and result are 0-based, test @ CF 101955

```

8.12 N Queens Problem

```
def solve(n)
  if n % 6 == 2 then
    (2..n).step(2) + [3,1] + (7..n).step(2) + [5]
  elsif n % 6 == 3 then
    (4..n).step(2) + [2] + (5..n).step(2) + [1,3]
  else
    (2..n).step(2) + (1..n).step(2)
  end
end
```

8.13 Manhattan MST [1008bc]

```
vector<array<int, 3>> manhattanMST(vector<P> ps) {
    vector<int> id(ps.size()); iota(all(id), 0);
    vector<array<int, 3>> edges;
    for (int k = 0; k < 4; k++) {
        sort(all(id), [&](int i, int j) {
            return (ps[i] - ps[j]).x < (ps[j] - ps[i]).y; });
        map<int, int> sweep;
        for (int i : id) {
            for (auto it = sweep.lower_bound(-ps[i].y);
                 it != sweep.end(); sweep.erase(it++)) {
                if (P d = ps[i] - ps[it->second]; d.y > d.x) break;
                else edges.push_back({d.y + d.x, i, it->second});
            }
            sweep[-ps[i].y] = i;
        }
    }
    for (P &p : ps)
        if (k & 1) p.x = -p.x;
        else swap(p.x, p.y);
}
return edges; // [{w, i, j}, ...]
} // test @ vosupo judge
```

8.14 Binary Search On Fraction [ff3abd]

```
struct Q {
    lld p, q; // p / q
};
```

```

Q go(Q b, lld d) { return {p + b.p*d, q + b.q*d}; }
};

// returns smallest p/q in [lo, hi] such that
// pred(p/q) is true, and 0 <= p,q <= N
Q frac_bs(lld N, auto &&pred) {
    Q lo{0, 1}, hi{1, 0};
    if (pred(lo)) return lo;
    assert(pred(hi));
    bool dir = 1, L = 1, H = 1;
    for (; L || H; dir = !dir) {
        lld len = 0, step = 1;
        for (int t = 0; t < 2 && (t ? step/=2 : step*=2));
            if (Q mid = hi.go(lo, len + step);
                mid.p > N || mid.q > N || dir ^ pred(mid))
                t++;
            else len += step;
        swap(lo, hi = hi.go(lo, len));
        (dir ? L : H) = !len;
    }
    return dir ? hi : lo;
}

```

8.15 Cartesian Tree [2ed09d]

```

auto CartesianTree(const auto &a) {
    const int n = (int)a.size(); vector<int> pa(n+1, -1);
    for (int i = 1; i < n; i++) {
        int &p = pa[i] = i - 1, l = n;
        while (p != -1 && a[i] < a[p])
            tie(l, pa[l], p, pa[p]) = tuple(p, p, pa[p], i);
    }
    return pa.pop_back(), pa;
} // root is minimum

```

8.16 Nim Product [4ac1ce]

```
#define rep(i, r) for (int i = 0; i < r; i++)
struct NimProd {
    llu bit_prod[64][64] {}, prod[8][8][256][256] {};
    NimProd() {
        rep(i, 64) rep(j, 64) if (i & j) {
            int a = lowbit(i & j);
            bit_prod[i][j] = bit_prod[i ^ a][j] ^
                bit_prod[(i ^ a) | (a-1)][(j ^ a) | (i & (a-1))];
        } else bit_prod[i][j] = 1ULL << (i | j);
        rep(e, 8) rep(f, 8) rep(x, 256) rep(y, 256)
            rep(i, 8) if (x >> i & 1) rep(j, 8) if (y >> j & 1)
                prod[e][f][x][y] ^= bit_prod[e * 8 + i][f * 8 + j];
    }
    llu operator()(llu a, llu b) const {
        llu r = 0;
        rep(e, 8) rep(f, 8)
            r ^= prod[e][f][a >> (e*8) & 255][b >> (f*8) & 255];
        return r;
    }
};
```

8.17 Grid

[illegible]