

Contents

1 Basic	1
1.1 vimrc	1
1.2 Default code	1
1.3 Fast Integer Input	1
1.4 Pragma optimization	1
2 Flows, Matching	1
2.1 Flow	1
2.2 MCMF	2
2.3 GomoryHu Tree	2
2.4 Global Minimum Cut	2
2.5 Bipartite Matching	2
2.6 GeneralMatching	3
2.7 Kuhn Munkres	3
2.8 Flow Models	3
3 Data Structure	3
3.1 <ext/pbds>	3
3.2 Li Chao Tree	4
3.3 Link-Cut Tree	4
4 Graph	4
4.1 2-Edge-Connected Components	4
4.2 2-Vertex-Connected Components	4
4.3 3-Edge-Connected Components	5
4.4 Heavy-Light Decomposition	5
4.5 Centroid Decomposition	5
4.6 Strongly Connected Components	5
4.7 2-SAT	6
4.8 count 3-cycles and 4-cycles	6
4.9 Minimum Mean Cycle	6
4.10 Directed Minimum Spanning Tree	6
4.11 Maximum Clique	6
4.12 Dominator Tree	6
4.13 Edge Coloring	7
5 String	7
5.1 Prefix Function	7
5.2 Z Function	7
5.3 Suffix Array	7
5.4 Manacher's Algorithm	8
5.5 Aho-Corasick Automaton	8
5.6 Suffix Automaton	8
5.7 Lexicographically Smallest Rotation	8
5.8 EER Tree	8
6 Math	9
6.1 Extended GCD	9
6.2 Chinese Remainder Theorem	9
6.3 NTT and polynomials	9
6.4 Any Mod NTT	10
6.5 Newton's Method	10
6.6 Fast Walsh-Hadamard Transform	10
6.7 Simplex Algorithm	10
6.7.1 Construction	10
6.8 Subset Convolution	10
6.9 Berlekamp Massey Algorithm	11
6.10 Fast Linear Recurrence	11
6.11 Prime check and factorize	11
6.12 Count Primes leq n	11
6.13 Discrete Logarithm	11
6.14 Quadratic Residue	12
6.15 Characteristic Polynomial	12
6.16 Linear Sieve Related	12
6.17 De Bruijn Sequence	12
6.18 Floor Sum	12
6.19 More Floor Sum	12
6.20 Min Mod Linear	12
6.21 Count of subsets with sum (mod P)	13
6.22 Theorem	13
6.22.1 Kirchhoff's Theorem	13
6.22.2 Tutte's Matrix	13
6.22.3 Cayley's Formula	13
6.22.4 Erdős-Gallai Theorem	13
7 Dynamic Programming	13
7.1 Dynamic Convex Hull	13
7.2 1D/1D Convex Optimization	13
7.3 Conditon	13
7.3.1 Totally Monotone (Concave/Convex)	13
7.3.2 Monge Condition (Concave/Convex)	13
7.3.3 Optimal Split Point	13
8 Geometry	13
8.1 Basic	13
8.2 Convex Hull and related	14
8.3 Half Plane Intersection	14
8.4 Triangle Centers	14
8.5 Circle	14
8.6 3D Convex Hull	15
8.7 Delaunay Triangulation	15

9 Miscellaneous	16
9.1 Cactus 1	16
9.2 Cactus 2	16
9.3 Dancing Links	16
9.4 Offline Dynamic MST	17
9.5 Matroid Intersection	17
9.6 Euler Tour	17
9.7 SegTree Beats	17
9.8 unorganized	18

1 Basic

1.1 vimrc

```
set nu rnu cin ts=4 sw=4 autoread hls
sy on
map<leader>b :w<bar>!g++ -std=c++17 '%' -
    DKEV -fsanitize=undefined -o /tmp/.
    run<CR>
map<leader>r :w<bar>!cat 01.in && echo "
    ---" && /tmp/.run < 01.in<CR>
map<leader>i !:/tmp/.run<CR>
map<leader>c I//<Esc>
map<leader>y :%y+<CR>
map<leader>l :%d<bar>0r ~/t.cpp<CR>
```

1.2 Default code

```
#include <bits/stdc++.h>
using namespace std;
using i64 = long long;
using ll = long long;
#define SZ(v) (ll)((v).size())
#define pb emplace_back
#define AI(i) begin(i), end(i)
#define X first
#define Y second
template<class T> bool chmin(T &a, T b) {
    return b < a && (a = b, true); }
template<class T> bool chmax(T &a, T b) {
    return a < b && (a = b, true); }
#ifdef KEV
#define DE(args...) kout("[ " + string(#
    args) + " ] = ", args)
void kout() { cerr << endl; }
template<class T, class ...U> void kout(T
    a, U ...b) { cerr << a << ' ', kout
    (b...); }
template<class T> void debug(T l, T r) {
    while (l != r) cerr << *l << " \n" [
        next(l)++] , ++l; }
#else
#define DE(...) 0
#define debug(...) 0
#endif
int main() {
    cin.tie(nullptr)->sync_with_stdio(false);
    return 0;
}
```

1.3 Fast Integer Input

```
char buf[1 << 16], *p1 = buf, *p2 = buf;
char get() {
    if (p1 == p2) {
        p1 = buf;
        p2 = p1 + fread(buf, 1, sizeof(buf),
            stdin);
    }
    if (p1 == p2)
        return -1;
    return *p1++;
}
char readChar() {
    char c = get();
    while (isspace(c))
        c = get();
    return c;
}
int readInt() {
    int x = 0;
    char c = get();
    while (!isdigit(c))
        c = get();
    while (isdigit(c)) {
```

```
x = 10 * x + c - '0';
c = get();
}
return x;
}
```

1.4 Pragma optimization

```
#pragma GCC optimize("Ofast", "no-stack-
    protector", "no-math-errno", "unroll
    -loops")
#pragma GCC target("sse,sse2,sse3,ssse3,
    sse4,sse4.2,popcnt,abm,mmx,avx,tune=
    native,arch=core-avx2,tune=core-avx2
    ")
#pragma GCC ivdep
```

2 Flows, Matching

2.1 Flow

```
template <typename F>
struct Flow {
    static constexpr F INF = numeric_limits
        <F>::max() / 2;
    struct Edge {
        int to;
        F cap;
        Edge(int to, F cap) : to(to), cap(cap)
        {}
    };
    int n;
    vector<Edge> e;
    vector<vector<int>> adj;
    vector<int> cur, h;
    Flow(int n) : n(n), adj(n) {}
    bool bfs(int s, int t) {
        h.assign(n, -1);
        queue<int> q;
        h[s] = 0;
        q.push(s);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (int i : adj[u]) {
                auto [v, c] = e[i];
                if (c > 0 && h[v] == -1) {
                    h[v] = h[u] + 1;
                    if (v == t) { return true; }
                    q.push(v);
                }
            }
        }
        return false;
    }
    F dfs(int u, int t, F f) {
        if (u == t) { return f; }
        F r = f;
        for (int &i = cur[u]; i < int(adj[u].
            size()); i++) {
            int j = adj[u][i];
            auto [v, c] = e[j];
            if (c > 0 && h[v] == h[u] + 1) {
                F a = dfs(v, t, min(r, c));
                e[j].cap -= a;
                e[j ^ 1].cap += a;
                r -= a;
                if (r == 0) { return f; }
            }
        }
        return f - r;
    }
    // can be bidirectional
    void addEdge(int u, int v, F cf = INF,
        F cb = 0) {
        adj[u].push_back(e.size(), e.
            emplace_back(v, cf));
        adj[v].push_back(e.size(), e.
            emplace_back(u, cb));
    }
    F maxFlow(int s, int t) {
        F ans = 0;
        while (bfs(s, t)) {
            cur.assign(n, 0);
            ans += dfs(s, t, INF);
        }
    }
};
```

```

    }
    return ans;
}
// do max flow first
vector<int> minCut() {
    vector<int> res(n);
    for (int i = 0; i < n; i++) { res[i]
        = h[i] != -1; }
    return res;
}
};

```

2.2 MCMF

```

template <class Flow, class Cost>
struct MinCostMaxFlow {
public:
    static constexpr Flow flowINF =
        numeric_limits<Flow>::max();
    static constexpr Cost costINF =
        numeric_limits<Cost>::max();
    MinCostMaxFlow() {}
    MinCostMaxFlow(int n) : n(n), g(n) {}
    int addEdge(int u, int v, Flow cap,
        Cost cost) {
        int m = int(pos.size());
        pos.push_back({u, int(g[u].size())});
        g[u].push_back({v, int(g[v].size()),
            cap, cost});
        g[v].push_back({u, int(g[u].size()) -
            1, 0, -cost});
        return m;
    }
    struct edge {
        int u, v;
        Flow cap, flow;
        Cost cost;
    };
    edge getEdge(int i) {
        auto _e = g[pos[i].first][pos[i].
            second];
        auto _re = g[_e.v][_e.rev];
        return {pos[i].first, _e.v, _e.cap +
            _re.cap, _re.cap, _e.cost};
    }
    vector<edge> edges() {
        int m = int(pos.size());
        vector<edge> result(m);
        for (int i = 0; i < m; i++) { result[
            i] = getEdge(i); }
        return result;
    }
    pair<Flow, Cost> maxFlow(int s, int t,
        Flow flow_limit = flowINF) {
        return slope(s, t, flow_limit).
            back();
    }
    vector<pair<Flow, Cost>> slope(int s,
        int t, Flow flow_limit = flowINF)
    {
        vector<Cost> dual(n, 0), dis(n);
        vector<int> pv(n), pe(n), vis(n);
        auto dualRef = [&]() {
            fill(dis.begin(), dis.end(),
                costINF);
            fill(pv.begin(), pv.end(), -1);
            fill(pe.begin(), pe.end(), -1);
            fill(vis.begin(), vis.end(), false);
        };
        struct Q {
            Cost key;
            int u;
            bool operator<(Q o) const {
                return key > o.key;
            }
        };
        priority_queue<Q> h;
        dis[s] = 0;
        h.push({0, s});
        while (!h.empty()) {
            int u = h.top().u;
            h.pop();
            if (vis[u]) { continue; }
            vis[u] = true;
            if (u == t) { break; }
            for (int i = 0; i < int(g[u].size())
                ; i++) {
                auto e = g[u][i];

```

```

                if (vis[e.v] || e.cap == 0)
                    continue;
                Cost cost = e.cost - dual[e.v]
                    + dual[u];
                if (dis[e.v] - dis[u] > cost) {
                    dis[e.v] = dis[u] + cost;
                    pv[e.v] = u;
                    pe[e.v] = i;
                    h.push({dis[e.v], e.v});
                }
            }
            if (!vis[t]) { return false; }
            for (int v = 0; v < n; v++) {
                if (!vis[v]) continue;
                dual[v] -= dis[t] - dis[v];
            }
            return true;
        };
        Flow flow = 0;
        Cost cost = 0, prevCost = -1;
        vector<pair<Flow, Cost>> result;
        result.push_back({flow, cost});
        while (flow < flow_limit) {
            if (!dualRef()) break;
            Flow c = flow_limit - flow;
            for (int v = t; v != s; v = pv[v])
                {
                    c = min(c, g[pv[v]][pe[v]].cap);
                }
            for (int v = t; v != s; v = pv[v])
                {
                    auto& e = g[pv[v]][pe[v]];
                    e.cap -= c;
                    g[v][e.rev].cap += c;
                }
            Cost d = -dual[s];
            flow += c;
            cost += c * d;
            if (prevCost == d) { result.
                pop_back(); }
            result.push_back({flow, cost});
            prevCost = cost;
        }
        return result;
    }
private:
    int n;
    struct _edge {
        int v, rev;
        Flow cap;
        Cost cost;
    };
    vector<pair<int, int>> pos;
    vector<vector<_edge>> g;
};

```

2.3 GomoryHu Tree

```

auto gomory(int n, vector<array<int, 3>>
    e) {
    Flow<int, int> mf(n);
    for (auto [u, v, c] : e) { mf.addEdge(u,
        v, c, c); }
    vector<array<int, 3>> res;
    vector<int> p(n);
    for (int i = 1; i < n; i++) {
        for (int j = 0; j < int(e.size()); j
            ++ ) { mf.e[j][0] = mf.e[j]
                << 1 | 1].cap = e[j][2]; }
        int f = mf.maxFlow(i, p[i]);
        auto cut = mf.minCut();
        for (int j = i + 1; j < n; j++) { if
            (cut[i] == cut[j] && p[i] == p[j]
                ) { p[j] = i; } }
        res.push_back({f, i, p[i]});
    }
    return res;
}

```

2.4 Global Minimum Cut

```

// O(V ^ 3)
template <typename F>
struct GlobalMinCut {
    static constexpr int INF =
        numeric_limits<F>::max() / 2;

```

```

    int n;
    vector<int> vis, wei;
    vector<vector<int>> adj;
    GlobalMinCut(int n) : n(n), vis(n), wei
        (n), adj(n, vector<int>(n)) {}
    void addEdge(int u, int v, int w) {
        adj[u][v] += w;
        adj[v][u] += w;
    }
    int solve() {
        int sz = n;
        int res = INF, x = -1, y = -1;
        auto search = [&]() {
            fill(vis.begin(), vis.begin() + sz,
                0);
            fill(wei.begin(), wei.begin() + sz,
                0);
            x = y = -1;
            int mx, cur;
            for (int i = 0; i < sz; i++) {
                mx = -1, cur = 0;
                for (int j = 0; j < sz; j++) {
                    if (wei[j] > mx) {
                        mx = wei[j], cur = j;
                    }
                }
                vis[cur] = 1, wei[cur] = -1;
                x = y;
                y = cur;
                for (int j = 0; j < sz; j++) {
                    if (!vis[j]) {
                        wei[j] += adj[cur][j];
                    }
                }
            }
            return mx;
        };
        while (sz > 1) {
            res = min(res, search());
            for (int i = 0; i < sz; i++) {
                adj[x][i] += adj[y][i];
                adj[i][x] = adj[x][i];
            }
            for (int i = 0; i < sz; i++) {
                adj[y][i] = adj[sz - 1][i];
                adj[i][y] = adj[i][sz - 1];
            }
            sz--;
        }
        return res;
    }
};

```

2.5 Bipartite Matching

```

struct BipartiteMatching {
    int n, m;
    vector<vector<int>> adj;
    vector<int> l, r, dis, cur;
    BipartiteMatching(int n, int m) : n(n),
        m(m), adj(n), l(n, -1), r(m, -1),
        dis(n), cur(n) {}
    void addEdge(int u, int v) { adj[u].
        push_back(v); }
    void bfs() {
        vector<int> q;
        for (int u = 0; u < n; u++) {
            if (l[u] == -1) {
                q.push_back(u), dis[u] = 0;
            } else {
                dis[u] = -1;
            }
        }
        for (int i = 0; i < int(q.size()); i
            ++ ) {
            int u = q[i];
            for (auto v : adj[u]) {
                if (r[v] != -1 && dis[r[v]] ==
                    -1) {
                    dis[r[v]] = dis[u] + 1;
                    q.push_back(r[v]);
                }
            }
        }
    }
    bool dfs(int u) {

```

```

for (int &i = cur[u]; i < int(adj[u].
    size()); i++) {
    int v = adj[u][i];
    if (r[v] == -1 || dis[r[v]] == dis[
        u] + 1 && dfs(r[v])) {
        l[u] = v, r[v] = u;
        return true;
    }
}
return false;
}
int maxMatching() {
    int match = 0;
    while (true) {
        bfs();
        fill(cur.begin(), cur.end(), 0);
        int cnt = 0;
        for (int u = 0; u < n; u++) {
            if (l[u] == -1) {
                cnt += dfs(u);
            }
        }
        if (cnt == 0) {
            break;
        }
        match += cnt;
    }
    return match;
}
auto minVertexCover() {
    vector<int> L, R;
    for (int u = 0; u < n; u++) {
        if (dis[u] == -1) {
            L.push_back(u);
        } else if (l[u] != -1) {
            R.push_back(l[u]);
        }
    }
    return pair(L, R);
}
};

```

2.6 GeneralMatching

```

struct GeneralMatching {
    int n;
    vector<vector<int>> adj;
    vector<int> match;
    GeneralMatching(int n) : n(n), adj(n),
        match(n, -1) {}
    void addEdge(int u, int v) {
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    int maxMatching() {
        vector<int> vis(n), link(n), f(n),
            dep(n);
        auto find = [&](int u) {
            while (f[u] != u) { u = f[u] = f[f[
                u]]; }
            return u;
        };
        auto lca = [&](int u, int v) {
            u = find(u);
            v = find(v);
            while (u != v) {
                if (dep[u] < dep[v]) { swap(u, v)
                    ; }
                u = find(link[match[u]]);
            }
            return u;
        };
        queue<int> q;
        auto blossom = [&](int u, int v, int
            p) {
            while (find(u) != p) {
                link[u] = v;
                v = match[u];
                if (vis[v] == 0) {
                    vis[v] = 1;
                    q.push(v);
                }
                f[u] = f[v] = p;
                u = link[v];
            }
        };
        auto augment = [&](int u) {

```

```

while (!q.empty()) { q.pop(); }
iota(f.begin(), f.end(), 0);
fill(vis.begin(), vis.end(), -1);
q.push(u), vis[u] = 1, dep[u] = 0;
while (!q.empty()) {
    int u = q.front();
    q.pop();
    for (auto v : adj[u]) {
        if (vis[v] == -1) {
            vis[v] = 0;
            link[v] = u;
            dep[v] = dep[u] + 1;
            if (match[v] == -1) {
                for (int x = v, y = u, tmp;
                    y != -1; x = tmp, y =
                        x == -1 ? -1 : link[x]
                ) {
                    tmp = match[y], match[x]
                        = y, match[y] = x;
                }
                return true;
            }
            q.push(match[v]), vis[match[v]] =
                dep[u] + 2;
        } else if (vis[v] == 1 && find(
            v) != find(u)) {
            int p = lca(u, v);
            blossom(u, v, p), blossom(v,
                u, p);
        }
    }
    return false;
};
int res = 0;
for (int u = 0; u < n; ++u) { if (
    match[u] == -1) { res += augment
        (u); } }
return res;
}
};

```

2.7 Kuhn Munkres

```

// need perfect matching or not : w
// initialize with -INF / 0
template <typename Cost>
struct KM {
    static constexpr Cost INF =
        numeric_limits<Cost>::max() / 2;
    int n;
    vector<Cost> hl, hr, slk;
    vector<int> l, r, pre, vl, vr;
    queue<int> q;
    vector<vector<Cost>> w;
    KM(int n) : n(n), hl(n), hr(n), slk(n),
        l(n, -1), r(n, -1), pre(n), vl(n),
        vr(n),
        w(n, vector<Cost>(n, -INF)) {}
    bool check(int x) {
        vl[x] = true;
        if (l[x] != -1) {
            q.push(l[x]);
            return vr[l[x]] == true;
        }
        while (x != -1) { swap(x, r[l[x] =
            pre[x]]); }
        return false;
    }
    void bfs(int s) {
        fill(slk.begin(), slk.end(), INF);
        fill(vl.begin(), vl.end(), false);
        fill(vr.begin(), vr.end(), false);
        q = {};
        q.push(s);
        vr[s] = true;
        while (true) {
            Cost d;
            while (!q.empty()) {
                int y = q.front();
                q.pop();
                for (int x = 0; x < n; ++x) {
                    if (!vl[x] && slk[x] >= (d = hl
                        [x] + hr[y] - w[x][y])) {
                        pre[x] = y;
                        if (d != 0) {

```

```

slk[x] = d;
} else if (!check(x)) {
    return;
}
}
d = INF;
for (int x = 0; x < n; ++x) { if (!
    vl[x] && d > slk[x]) { d = slk
        [x]; } }
for (int x = 0; x < n; ++x) {
    if (vl[x]) {
        hl[x] += d;
    } else {
        slk[x] -= d;
    }
    if (vr[x]) { hr[x] -= d; }
}
for (int x = 0; x < n; ++x) { if (!
    vl[x] && !slk[x] && !check(x))
    { return; } }
}
void addEdge(int u, int v, Cost x) { w[
    u][v] = max(w[u][v], x); }
Cost solve() {
    for (int i = 0; i < n; ++i) { hl[i] =
        *max_element(w[i].begin(), w[i]
            .end()); }
    for (int i = 0; i < n; ++i) { bfs(i);
    }
    Cost res = 0;
    for (int i = 0; i < n; ++i) { res +=
        w[i][l[i]]; }
    return res;
}
};

```

2.8 Flow Models

- Maximum density induced subgraph
 - Binary search on answer, suppose we're checking answer T
 - Construct a max flow model, let K be the sum of all weights
 - Connect source $s \rightarrow v$, $v \in G$ with capacity K
 - For each edge (u, v, w) in G , connect $u \rightarrow v$ and $v \rightarrow u$ with capacity w
 - For $v \in G$, connect it with sink $v \rightarrow t$ with capacity $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
 - T is a valid answer if the maximum flow $f < K|V|$

3 Data Structure

3.1 <ext/pbds>

```

#include <bits/extc++.h>
#include <ext/rope>
using namespace __gnu_pbds;
using namespace __gnu_cxx;
#include <ext/pb_ds/assoc_container.hpp>
typedef tree<int, null_type, std::less<
    int>, rb_tree_tag,
    tree_order_statistics_node_update>
    tree_set;
typedef cc_hash_table<int, int> umap;
typedef priority_queue<int> heap;

int main() {
    // rb tree
    tree_set s;
    s.insert(71); s.insert(22);
    assert(*s.find_by_order(0) == 22);
    assert(*s.find_by_order(1) == 71);
    assert(s.order_of_key(22) == 0); assert(
        s.order_of_key(71) == 1);
    s.erase(22);
    assert(*s.find_by_order(0) == 71);
    assert(s.order_of_key(71) == 0);
    // mergable heap
    heap a, b; a.join(b);
    // persistant
    rope<char> r[2];

```

```

r[1] = r[0];
std::string st = "abc";
r[1].insert(0, st.c_str());
r[1].erase(1, 1);
std::cout << r[1].substr(0, 2) << std::endl;
return 0;
}

```

3.2 Li Chao Tree

```

constexpr i64 INF = 4e18;
struct Line {
    i64 a, b;
    Line() : a(0), b(INF) {}
    Line(i64 a, i64 b) : a(a), b(b) {}
    i64 operator()(i64 x) { return a * x + b; }
};
// [, ) !!!!!!!!!!!!!!!
struct Lichao {
    int n;
    vector<int> vals;
    vector<Line> lines;
    Lichao() {}
    void init(const vector<int> &v) {
        n = v.size();
        vals = v;
        sort(vals.begin(), vals.end());
        vals.erase(unique(vals.begin(), vals.end()), vals.end());
        lines.assign(4 * n, {});
    }
    int get(int x) { return lower_bound(vals.begin(), vals.end(), x) - vals.begin(); }
    void apply(Line p, int id, int l, int r) {
        Line &q = lines[id];
        if (p(vals[l]) < q(vals[l])) { swap(p, q); }
        if (l + 1 == r) { return; }
        int m = l + r >> 1;
        if (p(vals[m]) < q(vals[m])) {
            swap(p, q);
            apply(p, id << 1, l, m);
        } else {
            apply(p, id << 1 | 1, m, r);
        }
    }
    void add(int ql, int qr, Line p) {
        ql = get(ql), qr = get(qr);
        auto go = [&](auto go, int id, int l, int r) -> void {
            if (qr <= l || r <= ql) { return; }
            if (ql <= l && r <= qr) {
                apply(p, id, l, r);
                return;
            }
            int m = l + r >> 1;
            go(go, id << 1, l, m);
            go(go, id << 1 | 1, m, r);
        };
        go(go, 1, 0, n);
    }
    i64 query(int p) {
        p = get(p);
        auto go = [&](auto go, int id, int l, int r) -> i64 {
            if (l + 1 == r) { return lines[id](vals[p]); }
            int m = l + r >> 1;
            return min(lines[id](vals[p]), p < m ? go(go, id << 1, l, m) : go(go, id << 1 | 1, m, r));
        };
        return go(go, 1, 0, n);
    }
};

```

3.3 Link-Cut Tree

```

struct Splay {
    array<Splay*, 2> ch = {nullptr, nullptr};
};
Splay* fa = nullptr;
int sz = 1;

```

```

bool rev = false;
Splay() {}
void applyRev(bool x) {
    if (x) {
        swap(ch[0], ch[1]);
        rev ^= 1;
    }
}
void push() {
    for (auto k : ch) {
        if (k) {
            k->applyRev(rev);
        }
    }
    rev = false;
}
void pull() {
    sz = 1;
    for (auto k : ch) {
        if (k) {
            pull();
        }
    }
}
int relation() { return this == fa->ch[1]; }
bool isRoot() { return !fa || fa->ch[0] != this && fa->ch[1] != this; }
void rotate() {
    Splay *p = fa;
    bool x = !relation();
    p->ch[!x] = ch[x];
    if (ch[x]) { ch[x]->fa = p; }
    fa = p->fa;
    if (!p->isRoot()) { p->fa->ch[p->relation()] = this; }
    ch[x] = p;
    p->fa = this;
    p->pull();
}
void splay() {
    vector<Splay*> s;
    for (Splay *p = this; !p->isRoot(); p = p->fa) { s.push_back(p->fa); }
    while (!s.empty()) {
        s.back()->push();
        s.pop_back();
    }
    push();
    while (!isRoot()) {
        if (!fa->isRoot()) {
            if (relation() == fa->relation()) {
                fa->rotate();
            } else {
                rotate();
            }
        }
        rotate();
    }
    pull();
}
void access() {
    for (Splay *p = this, *q = nullptr; p; q = p, p = p->fa) {
        p->splay();
        p->ch[1] = q;
        p->pull();
    }
    splay();
}
void makeRoot() {
    access();
    applyRev(true);
}
Splay* findRoot() {
    access();
    Splay *p = this;
    while (p->ch[0]) { p = p->ch[0]; }
    p->splay();
    return p;
}
friend void split(Splay *x, Splay *y) {
    x->makeRoot();
    y->access();
}

```

```

// link if not connected
friend void link(Splay *x, Splay *y) {
    x->makeRoot();
    if (y->findRoot() != x) {
        x->fa = y;
    }
}
// delete edge if doesn't exist
friend void cut(Splay *x, Splay *y) {
    split(x, y);
    if (x->fa == y && !x->ch[1]) {
        x->fa = y->ch[0] = nullptr;
        x->pull();
    }
}
bool connected(Splay *x, Splay *y) {
    return x->findRoot() == y->findRoot();
}
};

```

4 Graph

4.1 2-Edge-Connected Components

```

struct EBCC {
    int n, cnt = 0, T = 0;
    vector<vector<int>> adj, comps;
    vector<int> stk, dfn, low, id;
    EBCC(int n) : n(n), adj(n), dfn(n, -1), low(n), id(n, -1) {}
    void addEdge(int u, int v) { adj[u].push_back(v), adj[v].push_back(u); }
    void build() { for (int i = 0; i < n; i++) { if (dfn[i] == -1) { dfs(i, -1); } } }
    void dfs(int u, int p) {
        dfn[u] = low[u] = T++;
        stk.push_back(u);
        for (auto v : adj[u]) {
            if (v == p) { continue; }
            if (dfn[v] == -1) {
                dfs(v, u);
                low[u] = min(low[u], low[v]);
            } else if (id[v] == -1) {
                low[u] = min(low[u], dfn[v]);
            }
        }
        if (dfn[u] == low[u]) {
            int x;
            comps.emplace_back();
            do {
                x = stk.back();
                comps.back().push_back(x);
                id[x] = cnt;
                stk.pop_back();
            } while (x != u);
            cnt++;
        }
    }
};

```

4.2 2-Vertex-Connected Components

```

// is articulation point if appear in >= 2 comps
auto dfs = [&](auto dfs, int u, int p) -> void {
    dfn[u] = low[u] = T++;
    for (auto v : adj[u]) {
        if (v == p) { continue; }
        if (dfn[v] == -1) {
            stk.push_back(v);
            dfs(dfs, v, u);
            low[u] = min(low[u], low[v]);
            if (low[v] >= dfn[u]) {
                comps.emplace_back();
                int x;
                do {
                    x = stk.back();
                    comps.back().push_back(x);
                    cnt[x]++;
                } while (x != u);
            }
        }
    }
};

```



```

    stk.pop_back();
} while (x != v);
comps.back().push_back(u);
cnt[u]++;
}
} else {
    low[u] = min(low[u], dfn[v]);
}
}
};
for (int i = 0; i < n; i++) {
    if (!adj[i].empty()) {
        dfs(dfs, i, -1);
    } else {
        comps.push_back({i});
    }
}
}

```

4.3 3-Edge-Connected Components

```

// DSU
struct ETCC {
    int n, cnt = 0;
    vector<vector<int>> adj, comps;
    vector<int> in, out, low, up, nx, id;
    ETCC(int n) : n(n), adj(n), in(n, -1),
        out(n), low(n), up(n), nx(n), id(n) {}
    void addEdge(int u, int v) {
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    void build() {
        int T = 0;
        DSU d(n);
        auto merge = [&](int u, int v) {
            d.join(u, v);
            up[u] += up[v];
        };
        auto dfs = [&](auto dfs, int u, int p)
            -> void {
            in[u] = low[u] = T++;
            for (auto v : adj[u]) {
                if (v == u) { continue; }
                if (v == p) {
                    p = -1;
                    continue;
                }
                if (in[v] == -1) {
                    dfs(dfs, v, u);
                    if (nx[v] == -1 && up[v] <= 1) {
                        up[u] += up[v];
                        low[u] = min(low[u], low[v]);
                        continue;
                    }
                    if (up[v] == 0) { v = nx[v]; }
                    if (low[u] > low[v]) { low[u] = low[v]; swap(nx[u], v); }
                    while (v != -1) { merge(u, v); v = nx[v]; }
                } else if (in[v] < in[u]) {
                    low[u] = min(low[u], in[v]);
                    up[u]++;
                } else {
                    for (int &x = nx[u]; x != -1 && in[x] <= in[v] && in[v] < out[x]; x = nx[x]) {
                        merge(u, x);
                    }
                    up[u]--;
                }
            }
            out[u] = T;
        };
        for (int i = 0; i < n; i++) { if (in[i] == -1) { dfs(dfs, i, -1); } }
        for (int i = 0; i < n; i++) { if (d.find(i) == i) { id[i] = cnt++; } }
        comps.resize(cnt);
        for (int i = 0; i < n; i++) { comps[id[d.find(i)]] .push_back(i); }
    }
};

```

4.4 Heavy-Light Decomposition

```

struct HLD {
    int n, cur = 0;
    vector<int> sz, top, dep, par, tin, tout, seq;
    vector<vector<int>> adj;
    HLD(int n) : n(n), sz(n, 1), top(n), dep(n), par(n), tin(n), tout(n), seq(n), adj(n) {}
    void addEdge(int u, int v) { adj[u].push_back(v); adj[v].push_back(u); }
    void build(int root = 0) {
        top[root] = root, dep[root] = 0, par[root] = -1;
        dfs1(root), dfs2(root);
    }
    void dfs1(int u) {
        if (auto it = find(adj[u].begin(), adj[u].end(), par[u]); it != adj[u].end()) {
            adj[u].erase(it);
        }
        for (auto &v : adj[u]) {
            par[v] = u;
            dep[v] = dep[u] + 1;
            dfs1(v);
            sz[u] += sz[v];
            if (sz[v] > sz[adj[u][0]]) { swap(v, adj[u][0]); }
        }
    }
    void dfs2(int u) {
        tin[u] = cur++;
        seq[tin[u]] = u;
        for (auto v : adj[u]) {
            top[v] = v == adj[u][0] ? top[u] : v;
            dfs2(v);
        }
        tout[u] = cur - 1;
    }
    int lca(int u, int v) {
        while (top[u] != top[v]) {
            if (dep[top[u]] > dep[top[v]]) {
                u = par[top[u]];
            } else {
                v = par[top[v]];
            }
            return dep[u] < dep[v] ? u : v;
        }
    }
    int dist(int u, int v) { return dep[u] + dep[v] - 2 * dep[lca(u, v)]; }
    int jump(int u, int k) {
        if (dep[u] < k) { return -1; }
        int d = dep[u] - k;
        while (dep[top[u]] > d) { u = par[top[u]]; }
        return seq[tin[u] - dep[u] + d];
    }
    // u is v's ancestor
    bool isAncestor(int u, int v) { return tin[u] <= tin[v] && tin[v] <= tout[u]; }
    // root's parent is itself
    int rootedParent(int r, int u) {
        if (r == u) { return u; }
        if (isAncestor(r, u)) { return par[u]; }
        auto it = upper_bound(adj[u].begin(), adj[u].end(), r, [&](int x, int y) {
            return tin[x] < tin[y];
        }) - 1;
        return *it;
    }
    // rooted at u, v's subtree size
    int rootedSize(int r, int u) {
        if (r == u) { return n; }
        if (isAncestor(u, r)) { return sz[u]; }
        return n - sz[rootedParent(r, u)];
    }
};

```

```

int rootedLca(int r, int a, int b) {
    return lca(a, b) ^ lca(a, r) ^ lca(b, r);
};

```

4.5 Centroid Decomposition

```

vector<int> sz(n), vis(n);
auto build = [&](auto build, int u, int p)
    -> void {
    sz[u] = 1;
    for (auto v : g[u]) {
        if (v != p && !vis[v]) {
            build(build, v, u);
            sz[u] += sz[v];
        }
    }
};
auto find = [&](auto find, int u, int p, int tot)
    -> int {
    for (auto v : g[u]) {
        if (v != p && !vis[v] && 2 * sz[v] > tot) {
            return find(find, v, u, tot);
        }
    }
    return u;
};
auto dfs = [&](auto dfs, int cen) -> void {
    build(build, cen, -1);
    cen = find(find, cen, -1, sz[cen]);
    vis[cen] = 1;
    build(build, cen, -1);
    for (auto v : g[cen]) {
        if (!vis[v]) {
            dfs(dfs, v);
        }
    }
};
dfs(dfs, 0);

```

4.6 Strongly Connected Components

```

struct SCC {
    int n, cnt = 0, cur = 0;
    vector<int> id, dfn, low, stk;
    vector<vector<int>> adj, comps;
    void addEdge(int u, int v) { adj[u].push_back(v); }
    SCC(int n) : n(n), id(n, -1), dfn(n, -1), low(n, -1), adj(n) {}
    void build() {
        auto dfs = [&](auto dfs, int u) -> void {
            void {
                dfn[u] = low[u] = cur++;
                stk.push_back(u);
                for (auto v : adj[u]) {
                    if (dfn[v] == -1) {
                        dfs(dfs, v);
                        low[u] = min(low[u], low[v]);
                    } else if (id[v] == -1) {
                        low[u] = min(low[u], dfn[v]);
                    }
                }
            }
            if (dfn[u] == low[u]) {
                int v;
                comps.emplace_back();
                do {
                    v = stk.back();
                    comps.back().push_back(v);
                    id[v] = cnt;
                    stk.pop_back();
                } while (u != v);
                cnt++;
            }
        };
        for (int i = 0; i < n; i++) { if (dfn[i] == -1) { dfs(dfs, i); } }
        for (int i = 0; i < n; i++) { id[i] = cnt - 1 - id[i]; }
        reverse(comps.begin(), comps.end());
    }
};

```

```
// the comps are in topological sorted
// order
};
```

4.7 2-SAT

```
struct TwoSat {
    int n, N;
    vector<vector<int>> adj;
    vector<int> ans;
    TwoSat(int n) : n(n), N(n), adj(2 * n) {}
    // u == x
    void addClause(int u, bool x) { adj[2 * u + !x].push_back(2 * u + x); }
    // u == x || v == y
    void addClause(int u, bool x, int v, bool y) {
        adj[2 * u + !x].push_back(2 * v + y);
        adj[2 * v + !y].push_back(2 * u + x);
    }
    // u == x -> v == y
    void addImPLY(int u, bool x, int v, bool y) { addClause(u, !x, v, y); }
    void addVar() {
        adj.emplace_back(), adj.emplace_back();
        N++;
    }
    // at most one in var is true
    // adds prefix or as supplementary
    // variables
    void atMostOne(const vector<pair<int, bool>> &vars) {
        int sz = vars.size();
        for (int i = 0; i < sz; i++) {
            addVar();
            auto [u, x] = vars[i];
            addImPLY(u, x, N - 1, true);
            if (i > 0) {
                addImPLY(N - 2, true, N - 1, true);
            }
            addClause(u, !x, N - 2, false);
        }
    }
    // does not return supplementary
    // variables from atMostOne()
    bool satisfiable() {
        // run tarjan scc on 2 * N
        for (int i = 0; i < 2 * N; i++) { if (dfn[i] == -1) { dfs(dfs, i); } }
        for (int i = 0; i < N; i++) { if (id[2 * i] == id[2 * i + 1]) {
            return false; } }
        ans.resize(n);
        for (int i = 0; i < n; i++) { ans[i] = id[2 * i] > id[2 * i + 1]; }
        return true;
    }
};
```

4.8 count 3-cycles and 4-cycles

```
sort(ord.begin(), ord.end(), [&](auto i, auto j) { return pair(deg[i], i) > pair(deg[j], j); });
for (int i = 0; i < n; i++) { rnk[ord[i]] = i; }
if (rnk[u] < rnk[v]) { dag[u].push_back(v); }
// c3
for (int x = 0; x < n; x++) {
    for (auto y : dag[x]) { vis[y] = 1; }
    for (auto y : dag[x]) { for (auto z : dag[y]) { ans += vis[z]; } }
    for (auto y : dag[x]) { vis[y] = 0; }
}
// c4
for (int x = 0; x < n; x++) {
    for (auto y : dag[x]) { for (auto z : adj[y]) { if (rnk[z] > rnk[x]) {
        ans += vis[z]++; } } }
```

```
for (auto y : dag[x]) { for (auto z : adj[y]) { if (rnk[z] > rnk[x]) {
    vis[z]--; } } }
}
```

4.9 Minimum Mean Cycle

create a new vertex S , connect S to all vertices with arbitrary weight (0). Let $f_i(u)$ be the shortest path from S to u with exactly i edges.

$$ans = \min_{f_{n+1}(i) \neq \infty} \max_{j=1}^n \frac{f_{n+1}(i) - f_j(i)}{n + 1 - j}$$

4.10 Directed Minimum Spanning Tree

```
// DSU with rollback
template <typename Cost>
struct DMST {
    int n;
    vector<int> s, t, lc, rc, h;
    vector<Cost> c, tag;
    DMST(int n) : n(n), h(n, -1) {}
    void addEdge(int u, int v, Cost w) {
        int id = s.size();
        s.push_back(u), t.push_back(v), c.push_back(w);
        lc.push_back(-1), rc.push_back(-1);
        tag.emplace_back();
        h[v] = merge(h[v], id);
    }
    pair<Cost, vector<int>> build(int root = 0) {
        DSU d(n);
        Cost res{};
        vector<int> vis(n, -1), path(n), q(n, in(n, -1));
        vis[root] = root;
        vector<pair<int, vector<int>>> cycles;
        for (auto r = 0; r < n; ++r) {
            auto u = r, b = 0, w = -1;
            while (!vis[u]) {
                if (!h[u]) { return {-1, {}}; }
                push(h[u]);
                int e = h[u];
                res += c[e], tag[h[u]] -= c[e];
                h[u] = pop(h[u]);
                q[b] = e, path[b++] = u, vis[u] = r;
                u = d.find(s[e]);
                if (vis[u] == r) {
                    int cycle = -1, e = b;
                    do {
                        w = path[--b];
                        cycle = merge(cycle, h[w]);
                    } while (d.join(u, w));
                    u = d.find(u);
                    h[u] = cycle, vis[u] = -1;
                    cycles.emplace_back(u, vector<int>(q.begin() + b, q.begin() + e));
                }
            }
            for (auto i = 0; i < b; ++i) { in[d.find(t[q[i]])] = q[i]; }
        }
        reverse(cycles.begin(), cycles.end());
        for (const auto &[u, comp] : cycles) {
            int count = int(comp.size()) - 1;
            d.back(count);
            int ine = in[u];
            for (auto e : comp) { in[d.find(t[e])] = e; }
            in[d.find(t[ine])] = ine;
        }
        vector<int> par;
        par.reserve(n);
        for (auto i : in) { par.push_back(i != -1 ? s[i] : -1); }
        return {res, par};
    }
    void push(int u) {
```

```
c[u] += tag[u];
if (int l = lc[u]; l != -1) { tag[l] += tag[u]; }
if (int r = rc[u]; r != -1) { tag[r] += tag[u]; }
tag[u] = 0;
}
int merge(int u, int v) {
    if (u == -1 || v == -1) { return u != -1 ? u : v; }
    push(u);
    push(v);
    if (c[u] > c[v]) { swap(u, v); }
    rc[u] = merge(v, rc[u]);
    swap(lc[u], rc[u]);
    return u;
}
int pop(int u) {
    push(u);
    return merge(lc[u], rc[u]);
}
};
```

4.11 Maximum Clique

```
pair<int, vector<int>> maxClique(int n, const vector<bitset<N>> adj) {
    int mx = 0;
    vector<int> ans, cur;
    auto rec = [&](auto rec, bitset<N> s) -> void {
        int sz = s.count();
        if (int(cur.size()) > mx) { mx = cur.size(), ans = cur; }
        if (int(cur.size()) + sz <= mx) { return; }
        int e1 = -1, e2 = -1;
        vector<int> d(n);
        for (int i = 0; i < n; i++) {
            if (s[i]) {
                d[i] = (adj[i] & s).count();
                if (e1 == -1 || d[i] > d[e1]) { e1 = i; }
                if (e2 == -1 || d[i] < d[e2]) { e2 = i; }
            }
        }
        if (d[e1] >= sz - 2) {
            cur.push_back(e1);
            auto s1 = adj[e1] & s;
            rec(rec, s1);
            cur.pop_back();
            return;
        }
        cur.push_back(e2);
        auto s2 = adj[e2] & s;
        rec(rec, s2);
        cur.pop_back();
        s.reset(e2);
        rec(rec, s);
    };
    bitset<N> all;
    for (int i = 0; i < n; i++) { all.set(i); }
    rec(rec, all);
    return pair(mx, ans);
}
```

4.12 Dominator Tree

```
// res : parent of each vertex in
// dominator tree, -1 is root, -2 if
// not in tree
struct DominatorTree {
    int n, cur = 0;
    vector<int> dfn, rev, fa, sdom, dom, val, rp, res;
    vector<vector<int>> adj, rdom, r;
    DominatorTree(int n) : n(n), dfn(n, -1), res(n, -2), adj(n), rdom(n), r(n) {}
    rev = fa = sdom = dom = val = rp = dfn;
}
void addEdge(int u, int v) {
```

```

    adj[u].push_back(v);
}
void dfs(int u) {
    dfn[u] = cur;
    rev[cur] = u;
    fa[cur] = sdom[cur] = val[cur] = cur;
    cur++;
    for (int v : adj[u]) {
        if (dfn[v] == -1) {
            dfs(v);
            rp[dfn[v]] = dfn[u];
        }
        r[dfn[v]].push_back(dfn[u]);
    }
}
int find(int u, int c) {
    if (fa[u] == u) { return c != 0 ? -1 : u; }
    int p = find(fa[u], 1);
    if (p == -1) { return c != 0 ? fa[u] : val[u]; }
    if (sdom[val[u]] > sdom[val[fa[u]]]) {
        val[u] = val[fa[u]];
    }
    fa[u] = p;
    return c != 0 ? p : val[u];
}
void build(int s = 0) {
    dfs(s);
    for (int i = cur - 1; i >= 0; i--) {
        for (int u : r[i]) { sdom[i] = min(sdom[i], sdom[find(u, 0)]); }
        if (i > 0) { rdom[sdom[i]].push_back(i); }
        for (int u : rdom[i]) {
            int p = find(u, 0);
            if (sdom[p] == i) {
                dom[u] = i;
            } else {
                dom[u] = p;
            }
        }
        if (i > 0) { fa[i] = rp[i]; }
    }
    res[s] = -1;
    for (int i = 1; i < cur; i++) { if (sdom[i] != dom[i]) { dom[i] = dom[dom[i]]; } }
    for (int i = 1; i < cur; i++) { res[rev[i]] = rev[dom[i]]; }
}
};

```

4.13 Edge Coloring

```

// bipartite
e[i] = pair(u, v + a), deg[u]++, deg[v + a]++;
int col = *max_element(deg.begin(), deg.end());
vector<int> ans(m, -1);
vector<has> has(a + b, vector<pair<int, int>>(col, {-1, -1}));
for (int i = 0; i < m; i++) {
    auto [u, v] = e[i];
    vector<int> c;
    for (auto x : {u, v}) {
        c.push_back(0);
        while (has[x][c.back()].first != -1) {
            c.back()++;
        }
    }
    if (c[0] != c[1]) {
        auto dfs = [&](auto dfs, int u, int x) -> void {
            auto [v, i] = has[u][c[x]];
            if (v != -1) {
                if (has[v][c[x ^ 1]].first != -1) {
                    dfs(dfs, v, x ^ 1);
                } else {
                    has[v][c[x]] = {-1, -1};
                }
                has[u][c[x ^ 1]] = {v, i}, has[v][c[x ^ 1]] = {u, i};
                ans[i] = c[x ^ 1];
            }
        };
    }
};

```

```

dfs(dfs, v, 0);
}
has[u][c[0]] = {v, i};
has[v][c[0]] = {u, i};
ans[i] = c[0];
}
// general
auto vizing(int n, const vector<pair<int, int>> &e) {
    vector<int> deg(n);
    for (auto [u, v] : e) {
        deg[u]++, deg[v]++;
    }
    int col = *max_element(deg.begin(), deg.end()) + 1;
    vector<int> free(n);
    vector ans(n, vector<int>(n, -1));
    vector at(n, vector<int>(col, -1));
    auto update = [&](int u) {
        free[u] = 0;
        while (at[u][free[u]] != -1) {
            free[u]++;
        }
    };
    auto color = [&](int u, int v, int c1) {
        int c2 = ans[u][v];
        ans[u][v] = ans[v][u] = c1;
        at[u][c1] = v, at[v][c1] = u;
        if (c2 != -1) {
            at[u][c2] = at[v][c2] = -1;
            free[u] = free[v] = c2;
        } else {
            update(u), update(v);
        }
        return c2;
    };
    auto flip = [&](int u, int c1, int c2) {
        int v = at[u][c1];
        swap(at[u][c1], at[u][c2]);
        if (v != -1) {
            ans[u][v] = ans[v][u] = c2;
        }
        if (at[u][c1] == -1) {
            free[u] = c1;
        }
        if (at[u][c2] == -1) {
            free[u] = c2;
        }
        return v;
    };
    for (int i = 0; i < int(e.size()); i++) {
        auto [u, v1] = e[i];
        int v2 = v1, c1 = free[u], c2 = c1, d = v1;
        vector<pair<int, int>> fan;
        vector<int> vis(col);
        while (ans[u][v1] == -1) {
            fan.emplace_back(v2, d = free[v2]);
            if (at[v2][c2] == -1) {
                for (int j = int(fan.size()) - 1; j >= 0; j--) {
                    c2 = color(u, fan[j].first, c2);
                }
            } else if (at[u][d] == -1) {
                for (int j = int(fan.size()) - 1; j >= 0; j--) {
                    color(u, fan[j].first, fan[j].second);
                }
            } else if (vis[d] == 1) {
                break;
            } else {
                vis[d] = 1, v2 = at[u][d];
            }
        }
        if (ans[u][v1] == -1) {
            while (v2 != -1) {
                v2 = flip(v2, c2, d);
                swap(c2, d);
            }
            if (at[u][c1] != -1) {
                int j = int(fan.size()) - 2;

```

```

                while (j >= 0 && fan[j].second != c2) {
                    j--;
                }
                while (j >= 0) {
                    color(u, fan[j].first, fan[j].second);
                    j--;
                }
            } else {
                i--;
            }
        }
    }
    return pair(col, ans);
}

```

5 String

5.1 Prefix Function

```

template <typename T>
vector<int> prefixFunction(const T &s) {
    int n = int(s.size());
    vector<int> p(n);
    for (int i = 1; i < n; i++) {
        int j = p[i - 1];
        while (j > 0 && s[i] != s[j]) { j = p[j - 1]; }
        if (s[i] == s[j]) { j++; }
        p[i] = j;
    }
    return p;
}

```

5.2 Z Function

```

template <typename T>
vector<int> zFunction(const T &s) {
    int n = int(s.size());
    if (n == 0) return {};
    vector<int> z(n);
    for (int i = 1, j = 0; i < n; i++) {
        int &k = z[i];
        k = j + z[j] <= i ? 0 : min(j + z[j] - i, z[i - j]);
        while (i + k < n && s[k] == s[i + k]) { k++; }
        if (j + z[j] < i + z[i]) { j = i; }
    }
    z[0] = n;
    return z;
}

```

5.3 Suffix Array

```

// need to discretize
struct SuffixArray {
    int n;
    vector<int> sa, as, ha;
    template <typename T>
    vector<int> sais(const T &s) {
        int n = s.size(), m = *max_element(s.begin(), s.end()) + 1;
        vector<int> pos(m + 1), f(n);
        for (auto ch : s) { pos[ch + 1]++; }
        for (int i = 0; i < m; i++) { pos[i + 1] += pos[i]; }
        for (int i = n - 2; i >= 0; i--) { f[i] = s[i] != s[i + 1] ? s[i] < s[i + 1] : f[i + 1]; }
        vector<int> x(m), sa(n);
        auto induce = [&](const vector<int> &ls) {
            fill(sa.begin(), sa.end(), -1);
            auto l = [&](int i) { if (i >= 0 && !f[i]) { sa[x[s[i]]++] = i; } };
            auto S = [&](int i) { if (i >= 0 && f[i]) { sa[--x[s[i]]] = i; } };
            for (int i = 0; i < m; i++) { x[i] = pos[i + 1]; }
            for (int i = int(ls.size()) - 1; i >= 0; i--) { S(ls[i]); }
        };
    }
};

```

```

    for (int i = 0; i < m; i++) { x[i]
        = pos[i]; }
    L(n - 1);
    for (int i = 0; i < n; i++) { L(sa[
        i] - 1); }
    for (int i = 0; i < m; i++) { x[i]
        = pos[i + 1]; }
    for (int i = n - 1; i >= 0; i--) {
        S(sa[i] - 1); }
};
auto ok = [&](int i) { return i == n
    || !f[i - 1] && f[i]; };
auto same = [&](int i, int j) {
    do { if (s[i++] != s[j++]) { return
        false; } } while (!ok(i) && !
        ok(j));
    return ok(i) && ok(j);
};
vector<int> val(n), lms;
for (int i = 1; i < n; i++) { if (ok(
    i)) { lms.push_back(i); } }
induce(lms);
if (!lms.empty()) {
    int p = -1, w = 0;
    for (auto v : sa) {
        if (v != 0 && ok(v)) {
            if (p != -1 && same(p, v)) { w
                --; }
            val[p = v] = w++;
        }
    }
    auto b = lms;
    for (auto &v : b) { v = val[v]; }
    b = sa[s(b)];
    for (auto &v : b) { v = lms[v]; }
    induce(b);
}
return sa;
}
template <typename T>
SuffixArray(const T &s) : n(s.size()),
    sa(sa(s)), as(n), ha(n - 1) {
    for (int i = 0; i < n; i++) { as[sa[i]
        ] = i; }
    for (int i = 0, j = 0; i < n; ++i) {
        if (as[i] == 0) {
            j = 0;
        } else {
            for (j -= j > 0; i + j < n && sa[
                as[i] - 1] + j < n && s[i +
                j] == s[sa[as[i] - 1] + j];
                ) { ++j; }
            ha[as[i] - 1] = j;
        }
    }
}
};

```

5.4 Manacher's Algorithm

```

// returns radius of t, length of s : rad
(t) - 1, radius of s : rad(t) / 2
vector<int> manacher(string s) {
    string t = "#";
    for (auto c : s) { t += c, t += '#'; }
    int n = t.size();
    vector<int> r(n);
    for (int i = 0, j = 0; i < n; i++) {
        if (2 * j - i >= 0 && j + r[j] > i) {
            r[i] = min(r[2 * j - i], j + r[
                j] - i);
        }
        while (i - r[i] >= 0 && i + r[i] < n
            && t[i - r[i]] == t[i + r[i]]) {
            r[i]++;
        }
        if (i + r[i] > j + r[j]) { j = i; }
    }
    return r;
}

```

5.5 Aho-Corasick Automaton

```

constexpr int K = 26;
struct Node {
    array<int, K> nxt;
    int fail = -1;
};

```

```

// other vars
Node() { nxt.fill(-1); }
};
vector<Node> aho(1);
for (int i = 0; i < n; i++) {
    string s;
    cin >> s;
    int u = 0;
    for (auto ch : s) {
        int c = ch - 'a';
        if (aho[u].nxt[c] == -1) {
            aho[u].nxt[c] = aho.size();
            aho.emplace_back();
        }
        u = aho[u].nxt[c];
    }
}
vector<int> q;
for (auto &i : aho[0].nxt) {
    if (i == -1) {
        i = 0;
    } else {
        q.push_back(i);
        aho[i].fail = 0;
    }
}
for (int i = 0; i < int(q.size()); i++) {
    int u = q[i];
    if (u > 0) {
        // maintain
    }
    for (int c = 0; c < K; c++) {
        if (int v = aho[u].nxt[c]; v != -1) {
            aho[v].fail = aho[aho[u].fail].nxt[
                c];
            q.push_back(v);
        } else {
            aho[u].nxt[c] = aho[aho[u].fail].
                nxt[c];
        }
    }
}
}

```

5.6 Suffix Automaton

```

struct SAM {
    static constexpr int A = 26;
    struct Node {
        int len = 0, link = -1, cnt = 0;
        array<int, A> nxt;
        Node() { nxt.fill(-1); }
    };
    vector<Node> t;
    SAM() : t(1) {}
    int size() { return t.size(); }
    Node& operator[](int i) { return t[i]; }
    int newNode() {
        t.emplace_back();
        return t.size() - 1;
    }
    int extend(int p, int c) {
        int cur = newNode();
        t[cur].len = t[p].len + 1;
        t[cur].cnt = 1;
        while (p != -1 && t[p].nxt[c] == -1) {
            t[p].nxt[c] = cur;
            p = t[p].link;
        }
        if (p == -1) {
            t[cur].link = 0;
        } else {
            int q = t[p].nxt[c];
            if (t[p].len + 1 == t[q].len) {
                t[cur].link = q;
            } else {
                int clone = newNode();
                t[clone].len = t[p].len + 1;
                t[clone].link = t[q].link;
                t[clone].nxt = t[q].nxt;
                while (p != -1 && t[p].nxt[c] ==
                    q) {
                    t[p].nxt[c] = clone;
                    p = t[p].link;
                }
            }
        }
    }
};

```

```

    t[q].link = t[cur].link = clone;
}
}
return cur;
}
};

```

5.7 Lexicographically Smallest Rotation

```

template <typename T>
T minRotation(T s) {
    int n = s.size();
    int i = 0, j = 1;
    s.insert(s.end(), s.begin(), s.end());
    while (i < n && j < n) {
        int k = 0;
        while (k < n && s[i + k] == s[j + k]) {
            k++;
        }
        if (s[i + k] <= s[j + k]) {
            j += k + 1;
        } else {
            i += k + 1;
        }
        if (i == j) {
            j++;
        }
    }
    int ans = i < n ? i : j;
    return T(s.begin() + ans, s.begin() +
        ans + n);
}

```

5.8 EER Tree

```

// cnt : occurrences, (dfs fail tree)
// num : number of pal ending here
struct PAM {
    static constexpr int A = 26;
    struct Node {
        int len = 0, link = 0, cnt = 0, num =
            0;
        array<int, A> nxt{};
        Node() {}
    };
    vector<Node> t;
    int suf = 1;
    string s;
    PAM() : t(2) { t[0].len = -1; }
    int size() { return t.size(); }
    Node& operator[](int i) { return t[i]; }
    int newNode() {
        t.emplace_back();
        return t.size() - 1;
    }
    bool add(int c, char offset = 'a') {
        int pos = s.size();
        s += c + offset;
        int cur = suf, curlen = 0;
        while (true) {
            curlen = t[cur].len;
            if (pos - 1 - curlen >= 0 && s[pos
                - 1 - curlen] == s[pos]) {
                break;
            }
            cur = t[cur].link;
        }
        if (t[cur].nxt[c]) {
            suf = t[cur].nxt[c];
            t[suf].cnt++;
            return false;
        }
        suf = newNode();
        t[suf].len = t[cur].len + 2;
        t[suf].cnt = t[suf].num = 1;
        t[cur].nxt[c] = suf;
        if (t[suf].len == 1) {
            t[suf].link = 1;
            return true;
        }
        while (true) {
            cur = t[cur].link;
            curlen = t[cur].len;
        }
    }
};

```



```

    if (pos - 1 - curlen >= 0 && s[pos]
        - 1 - curlen] == s[pos]) {
        t[suf].link = t[cur].nxt[c];
        break;
    }
}
t[suf].num += t[t[suf].link].num;
return true;
}
};

```

6 Math

6.1 Extended GCD

```

array<i64, 3> extgcd(i64 a, i64 b) {
    if (b == 0) { return {a, 1, 0}; }
    auto [g, x, y] = extgcd(b, a % b);
    return {g, y, x - a / b * y};
}

```

6.2 Chinese Remainder Theorem

```

// returns (rem, mod), n = 0 return (0, 1), no solution return (0, 0)
pair<i64, i64> crt(vector<i64> r, vector<i64> m) {
    int n = r.size();
    for (int i = 0; i < n; i++) {
        r[i] %= m[i];
        if (r[i] < 0) { r[i] += m[i]; }
    }
    i64 r0 = 0, m0 = 1;
    for (int i = 0; i < n; i++) {
        i64 r1 = r[i], m1 = m[i];
        if (m0 < m1) { swap(r0, r1), swap(m0, m1); }
        if (m0 % m1 == 0) {
            if (r0 % m1 != r1) { return {0, 0}; }
            continue;
        }
        auto [g, a, b] = extgcd(m0, m1);
        i64 u1 = m1 / g;
        if ((r1 - r0) % g != 0) { return {0, 0}; }
        i64 x = (r1 - r0) / g % u1 * a % u1;
        r0 += x * m0;
        m0 *= u1;
        if (r0 < 0) { r0 += m0; }
    }
    return {r0, m0};
}

```

6.3 NTT and polynomials

```

template<int P>
struct Modint {
    int v;
    // need constexpr, constructor, +-, qpow, inv()
};

template<int P>
constexpr Modint<P> findPrimitiveRoot() {
    Modint<P> i = 2;
    int k = __builtin_ctz(P - 1);
    while (true) {
        if (i.qpow((P - 1) / 2).v != 1) {
            break;
        }
        i = i + 1;
    }
    return i.qpow(P - 1 >> k);
}

template<int P>
constexpr Modint<P> primitiveRoot =
    findPrimitiveRoot<P>();

vector<int> rev;
template<int P>
vector<Modint<P>> roots{0, 1};
template<int P>
void dft(vector<Modint<P>> &a) {
    int n = a.size();
    if (n == 1) { return; }
    if (int(rev.size()) != n) {

```

```

        int k = __builtin_ctz(n) - 1;
        rev.resize(n);
        for (int i = 0; i < n; i++) { rev[i]
            = rev[i >> 1] >> 1 | (i & 1) <<
                k; }
    }
    for (int i = 0; i < n; i++) { if (rev[i]
        < i) { swap(a[i], a[rev[i]]); } }
    if (roots<P>.size() < n) {
        int k = __builtin_ctz(roots<P>.size())
            ;
        roots<P>.resize(n);
        while ((1 << k) < n) {
            auto e = Modint<P>(primitiveRoot<P>
                >.qpow(P - 1 >> k + 1));
            for (int i = 1 << k - 1; i < 1 << k
                ; i++) {
                roots<P>[2 * i] = roots<P>[i];
                roots<P>[2 * i + 1] = roots<P>[i]
                    * e;
            }
            k++;
        }
    }
    // fft : just do roots[i] = exp(2 * PI
    // / n * i * complex<double>(0, 1))
    for (int k = 1; k < n; k *= 2) {
        for (int i = 0; i < n; i += 2 * k) {
            for (int j = 0; j < k; j++) {
                Modint<P> u = a[i + j];
                Modint<P> v = a[i + j + k] *
                    roots<P>[k + j];
                // fft : v = a[i + j + k] * roots
                // [n / (2 * k) * j]
                a[i + j] = u + v;
                a[i + j + k] = u - v;
            }
        }
    }
}

template<int P>
void idft(vector<Modint<P>> &a) {
    int n = a.size();
    reverse(a.begin() + 1, a.end());
    dft(a);
    Modint<P> x = (1 - P) / n;
    for (int i = 0; i < n; i++) { a[i] = a[
        i] * x; }
}

template<int P>
struct Poly : vector<Modint<P>> {
    using Mint = Modint<P>;
    Poly() {}
    explicit Poly(int n) : vector<Mint>(n) {}
    explicit Poly(const vector<Mint> &a) :
        vector<Mint>(a) {}
    explicit Poly(const initializer_list<
        Mint> &a) : vector<Mint>(a) {}
};

template<class F>
explicit Poly(int n, F f) : vector<Mint>
    >(n) { for (int i = 0; i < n; i++) {
        (*this)[i] = f(i); } }

template<class InputIt>
explicit Poly(InputIt first, InputIt last) :
    vector<Mint>(first, last) {}

Poly mulxk(int k) {
    auto b = *this;
    b.insert(b.begin(), k, 0);
    return b;
}

Poly modxk(int k) {
    k = min(k, int(this->size()));
    return Poly(this->begin(), this->
        begin() + k);
}

Poly divxk(int k) {
    if (this->size() <= k) { return Poly
        (); }
    return Poly(this->begin() + k, this->
        end());
}

friend Poly operator+(const Poly &a,
    const Poly &b) {
    Poly res(max(a.size(), b.size()));

```

```

    for (int i = 0; i < int(a.size()); i
        ++){ res[i] = res[i] + a[i]; }
    for (int i = 0; i < int(b.size()); i
        ++){ res[i] = res[i] + b[i]; }
    return res;
}

friend Poly operator-(const Poly &a,
    const Poly &b) {
    Poly res(max(a.size(), b.size()));
    for (int i = 0; i < int(a.size()); i
        ++){ res[i] = res[i] + a[i]; }
    for (int i = 0; i < int(b.size()); i
        ++){ res[i] = res[i] - b[i]; }
    return res;
}

friend Poly operator*(Poly a, Poly b) {
    if (a.empty() || b.empty()) { return
        Poly(); }
    int sz = 1, tot = a.size() + b.size()
        - 1;
    while (sz < tot) { sz *= 2; }
    a.resize(sz);
    b.resize(sz);
    dft(a);
    dft(b);
    for (int i = 0; i < sz; i++) { a[i] =
        a[i] * b[i]; }
    idft(a);
    a.resize(tot);
    return a;
}

friend Poly operator*(Poly a, Mint b) {
    for (int i = 0; i < int(a.size()); i
        ++){ a[i] = a[i] * b; }
    return a;
}

Poly derivative() {
    if (this->empty()) { return Poly(); }
    Poly res(this->size() - 1);
    for (int i = 0; i < this->size() - 1;
        ++i) { res[i] = (i + 1) * (*
        this)[i + 1]; }
    return res;
}

Poly integral() {
    Poly res(this->size() + 1);
    for (int i = 0; i < this->size(); ++i)
        { res[i + 1] = (*this)[i] *
            Mint(i + 1).inv(); }
    return res;
}

Poly inv(int m) {
    // a[0] != 0
    Poly x({(*this)[0].inv()});
    int k = 1;
    while (k < m) {
        k *= 2;
        x = (x * (Poly({2}) - modxk(k) * x)
            ).modxk(k);
    }
    return x.modxk(m);
}

Poly log(int m) {
    return (derivative() * inv(m)).
        integral().modxk(m);
}

Poly exp(int m) {
    Poly x({1});
    int k = 1;
    while (k < m) {
        k *= 2;
        x = (x * (Poly({1}) - x.log(k) +
            modxk(k))).modxk(k);
    }
    return x.modxk(m);
}

Poly pow(i64 k, int m) {
    if (k == 0) { return Poly(m, [&](int
        i) { return i == 0; }); }
    int i = 0;
    while (i < this->size() && (*this)[i]
        .v == 0) { i++; }
    if (i == this->size() || __int128(i)
        * k >= m) { return Poly(m); }
    Mint v = (*this)[i];
    auto f = divxk(i) * v.inv();

```

```

    return (f.log(m - i * k) * k).exp(m -
        i * k).mulxk(i * k) * v.qpow(k)
    );
}
Poly sqrt(int m) {
    // a[0] == 1, otherwise quadratic
    // residue?
    Poly x({1});
    int k = 1;
    while (k < m) {
        k *= 2;
        x = (x + (modxk(k) * x.inv(k)).
            modxk(k)) * ((P + 1) / 2);
    }
    return x.modxk(m);
}
Poly mult(Poly b) const {
    if (b.empty()) { return Poly(); }
    int n = b.size();
    reverse(b.begin(), b.end());
    return (*this * b).divxk(n - 1);
}
vector<Mint> evaluate(vector<Mint> x) {
    if (this->empty()) { return vector<
        Mint>(x.size()); }
    int n = max(x.size(), this->size());
    vector<Poly> q(4 * n);
    vector<Mint> ans(x.size());
    x.resize(n);
    auto build = [&](auto build, int id,
        int l, int r) -> void {
        if (r - l == 1) {
            q[id] = Poly({1, -x[l].v});
        } else {
            int m = (l + r) / 2;
            build(build, 2 * id, l, m);
            build(build, 2 * id + 1, m, r);
            q[id] = q[2 * id] * q[2 * id +
                1];
        }
    };
    build(build, 1, 0, n);
    auto work = [&](auto work, int id,
        int l, int r, const Poly &num)
        -> void {
        if (r - l == 1) {
            if (l < int(ans.size())) { ans[l]
                = num[0]; }
        } else {
            int m = (l + r) / 2;
            work(work, 2 * id, l, m, num.mult
                (q[2 * id + 1]).modxk(m - l)
                );
            work(work, 2 * id + 1, m, r, num.
                mult(q[2 * id])).modxk(r - m)
                );
        }
    };
    work(work, 1, 0, n, mult(q[1].inv(n))
        );
    return ans;
}
};
template <int P>
Poly<P> interpolate(vector<Modint<P>> x,
    vector<Modint<P>> y) {
    // f(xi) = yi
    int n = x.size();
    vector<Poly<P>> p(4 * n), q(4 * n);
    auto dfs1 = [&](auto dfs1, int id, int
        l, int r) -> void {
        if (l == r) {
            p[id] = Poly<P>({-x[l].v, 1});
            return;
        }
        int m = l + r >> 1;
        dfs1(dfs1, id << 1, l, m);
        dfs1(dfs1, id << 1 | 1, m + 1, r);
        p[id] = p[id << 1] * p[id << 1 | 1];
    };
    dfs1(dfs1, 1, 0, n - 1);
    Poly<P> f = Poly<P>(p[1].derivative().
        evaluate(x));
    auto dfs2 = [&](auto dfs2, int id, int
        l, int r) -> void {
        if (l == r) {

```

```

        q[id] = Poly<P>({y[l] * f[l].inv()
            });
        return;
    }
    int m = l + r >> 1;
    dfs2(dfs2, id << 1, l, m);
    dfs2(dfs2, id << 1 | 1, m + 1, r);
    q[id] = q[id << 1] * p[id << 1 | 1] +
        q[id << 1 | 1] * p[id << 1];
    };
    dfs2(dfs2, 1, 0, n - 1);
    return q[1];
}

```

6.4 Any Mod NTT

```

constexpr int P0 = 998244353, P1 =
    1004535809, P2 = 469762049;
constexpr i64 P01 = 1LL * P0 * P1;
constexpr int inv0 = Modint<P1>(P0).inv()
    .v;
constexpr int inv01 = Modint<P2>(P01).inv
    ().v;
for (int i = 0; i < int(c.size()); i++) {
    i64 x = 1LL * (c1[i] - c0[i] + P1) % P1
        * inv0 % P1 * P0 + c0[i];
    c[i] = ((c2[i] - x % P2 + P2) % P2 *
        inv01 % P2 * (P01 % P) % P + x) %
        P;
}

```

6.5 Newton's Method

$$Q_{k+1} = Q_k - \frac{F(Q_k)}{F'(Q_k)} \pmod{x^{2^{k+1}}}$$

6.6 Fast Walsh-Hadamard Transform

- XOR Convolution
 - $f(A) = (f(A_0) + f(A_1), f(A_0) - f(A_1))$
 - $f^{-1}(A) = (f^{-1}(\frac{A_0+A_1}{2}), f^{-1}(\frac{A_0-A_1}{2}))$
- OR Convolution
 - $f(A) = (f(A_0), f(A_0) + f(A_1))$
 - $f^{-1}(A) = (f^{-1}(A_0), f^{-1}(A_1) - f^{-1}(A_0))$
- AND Convolution
 - $f(A) = (f(A_0) + f(A_1), f(A_1))$
 - $f^{-1}(A) = (f^{-1}(A_0), f^{-1}(A_0) - f^{-1}(A_1), f^{-1}(A_1))$

6.7 Simplex Algorithm

Description: maximize $c^T x$ subject to $Ax \leq b$ and $x \geq 0$. Returns $-\infty$ if infeasible and ∞ if unbounded.

```

const double eps = 1e-9;
const double inf = 1e+9;
int n, m;
vector<vector<double>> d;
vector<int> p, q;
void pivot(int r, int s) {
    double inv = 1.0 / d[r][s];
    for (int i = 0; i < m + 2; ++i) {
        for (int j = 0; j < n + 2; ++j) {
            if (i != r && j != s) d[i][j] -= d[
                r][j] * d[i][s] * inv;
        }
    }
    for (int i = 0; i < m + 2; ++i) if (i
        != r) d[i][s] *= -inv;
    for (int j = 0; j < n + 2; ++j) if (j
        != s) d[r][j] *= inv;
    d[r][s] = inv;
    swap(p[r], q[s]);
}
bool phase(int z) {
    int x = m + z;
    while (true) {
        int s = -1;
        for (int i = 0; i <= n; ++i) {
            if (!z && q[i] == -1) continue;

```

```

        if (s == -1 || d[x][i] < d[x][s]) s
            = i;
    }
    if (d[x][s] > -eps) return true;
    int r = -1;
    for (int i = 0; i < m; ++i) {
        if (d[i][s] < eps) continue;
        if (r == -1 || d[i][n + 1] / d[i][s]
            < d[r][n + 1] / d[r][s]) r =
            i;
    }
    if (r == -1) return false;
    pivot(r, s);
}
vector<double> solve(const vector<vector<
    double>> &a, const vector<double> &b
    , const vector<double> &c) {
    m = b.size(), n = c.size();
    d = vector<vector<double>>(m + 2,
        vector<double>(n + 2));
    for (int i = 0; i < m; ++i) {
        for (int j = 0; j < n; ++j) d[i][j] =
            a[i][j];
    }
    p.resize(m), q.resize(n + 1);
    for (int i = 0; i < m; ++i) p[i] = n +
        i, d[i][n] = -1, d[i][n + 1] = b[i]
        ];
    for (int i = 0; i < n; ++i) q[i] = i, d
        [m][i] = -c[i];
    q[n] = -1, d[m + 1][n] = 1;
    int r = 0;
    for (int i = 1; i < m; ++i) if (d[i][n
        + 1] < d[r][n + 1]) r = i;
    if (d[r][n + 1] < -eps) {
        pivot(r, n);
        if (!phase(1) || d[m + 1][n + 1] < -
            eps) return vector<double>(n, -
            inf);
        for (int i = 0; i < m; ++i) if (p[i]
            == -1) {
            int s = min_element(d[i].begin(), d
                [i].end() - 1) - d[i].begin();
            pivot(i, s);
        }
    }
    if (!phase(0)) return vector<double>(n,
        inf);
    vector<double> x(n);
    for (int i = 0; i < m; ++i) if (p[i] <
        n) x[p[i]] = d[i][n + 1];
    return x;
}

```

6.7.1 Construction

Standard form: maximize $c^T x$ subject to $Ax \leq b$ and $x \geq 0$.

Dual LP: minimize $b^T y$ subject to $A^T y \geq c$ and $y \geq 0$.

\bar{x} and \bar{y} are optimal if and only if for all $i \in [1, n]$, either $\bar{x}_i = 0$ or $\sum_{j=1}^m A_{ji} \bar{y}_j = c_i$ holds and for all $i \in [1, m]$ either $\bar{y}_i = 0$ or $\sum_{j=1}^n A_{ij} \bar{x}_j = b_j$ holds.

- In case of minimization, let $c'_i = -c_i$
- $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j \rightarrow \sum_{1 \leq i \leq n} -A_{ji} x_i \leq -b_j$
- $\sum_{1 \leq i \leq n} A_{ji} x_i = b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j$
- If x_i has no lower bound, replace x_i with $x_i - x'_i$

6.8 Subset Convolution

Description: $h(s) = \sum_{s' \subseteq s} f(s')g(s \setminus s')$

```

vector<int> SubsetConv(int n, const
    vector<int> &f, const vector<int> &g
    ) {
    const int m = 1 << n;
    vector<vector<int>> a(n + 1, vector<int>
        (m));
    for (int i = 0; i < m; ++i) {
        a[builtin_popcount(i)][i] = f[i];

```

```

    b[__builtin_popcount(i)][i] = g[i];
}
for (int i = 0; i <= n; ++i) {
    for (int j = 0; j < n; ++j) {
        for (int s = 0; s < m; ++s) {
            if (s >> j & 1) {
                a[i][s] += a[i][s ^ (1 << j)];
                b[i][s] += b[i][s ^ (1 << j)];
            }
        }
    }
}
vector<vector<int>> c(n + 1, vector<int>
    >(m));
for (int s = 0; s < m; ++s) {
    for (int i = 0; i <= n; ++i) {
        for (int j = 0; j <= i; ++j) c[i][s]
            += a[j][s] * b[i - j][s];
    }
}
for (int i = 0; i <= n; ++i) {
    for (int j = 0; j < n; ++j) {
        for (int s = 0; s < m; ++s) {
            if (s >> j & 1) c[i][s] -= c[i][s
                ^ (1 << j)];
        }
    }
}
vector<int> res(m);
for (int i = 0; i < m; ++i) res[i] = c[
    __builtin_popcount(i)][i];
return res;
}

```

6.9 Berlekamp Massey Algorithm

```

// find \sum a_{i-j}c_j = 0 for d <= i
template <typename T>
vector<T> berlekampMassey(const vector<T>
    &a) {
    vector<T> c(1, 1), oldC(1);
    int oldI = -1;
    T oldD = 1;
    for (int i = 0; i < int(a.size()); i++) {
        T d = 0;
        for (int j = 0; j < int(c.size()); j
            ++){ d += c[j] * a[i - j]; }
        if (d == 0) { continue; }
        T mul = d / oldD;
        vector<T> nc = c;
        nc.resize(max(int(c.size()), i - oldI
            + int(oldC.size())));
        for (int j = 0; j < int(oldC.size());
            j++){ nc[j + i - oldI] -= oldC
            [j] * mul; }
        if (i - int(c.size()) > oldI - int(
            oldC.size())) {
            oldI = i;
            oldD = d;
            swap(oldC, c);
        }
        swap(c, nc);
    }
    return c;
}

```

6.10 Fast Linear Recurrence

```

// p : a[0] ~ a[d - 1]
// q : a[i] = \sum a[i - j]q[j]
template <typename T>
T linearRecurrence(vector<T> p, vector<T>
    q, i64 n) {
    int d = q.size() - 1;
    assert(int(p.size()) == d);
    p = p * q;
    p.resize(d);
    while (n > 0) {
        auto nq = q;
        for (int i = 1; i <= d; i += 2) {
            nq[i] *= -1;
        }
        auto np = p * nq;
        nq = q * nq;
        for (int i = 0; i < d; i++) {

```

```

            p[i] = np[i * 2 + n % 2];
        }
        for (int i = 0; i <= d; i++) {
            q[i] = nq[i * 2];
        }
        n /= 2;
    }
    return p[0] / q[0];
}

```

6.11 Prime check and factorize

```

i64 mul(i64 a, i64 b, i64 mod) {
    i64 apow(i64 x, i64 p, i64 mod) {
    bool isPrime(i64 n) {
        if (n == 1) { return false; }
        int r = __builtin_ctzll(n - 1);
        i64 d = n - 1 >> r;
        auto checkComposite = [&](i64 p) {
            i64 x = apow(p, d, n);
            if (x == 1 || x == n - 1) { return
                false; }
            for (int i = 1; i < r; i++) {
                x = mul(x, x, n);
                if (x == n - 1) { return false; }
            }
            return true;
        };
        for (auto p : {2, 3, 5, 7, 11, 13, 17,
            19, 23, 29, 31, 37}) {
            if (n == p) {
                return true;
            } else if (checkComposite(p)) {
                return false;
            }
        }
        return true;
    }
}
vector<i64> pollardRho(i64 n) {
    vector<i64> res;
    auto work = [&](auto work, i64 n) {
        if (n <= 10000) {
            for (int i = 2; i * i <= n; i++) {
                while (n % i == 0) {
                    res.push_back(i);
                    n /= i;
                }
            }
            if (n > 1) { res.push_back(n); }
            return;
        } else if (isPrime(n)) {
            res.push_back(n);
            return;
        }
        i64 x0 = 2;
        auto f = [&](i64 x) { return (mul(x,
            x, n) + 1) % n; };
        while (true) {
            i64 x = x0, y = x0, d = 1, power =
                1, lam = 0, v = 1;
            while (d == 1) {
                y = f(y);
                ++lam;
                v = mul(v, abs(x - y), n);
                if (lam % 127 == 0) {
                    d = gcd(v, n);
                    v = 1;
                }
            }
            if (power == lam) {
                x = y;
                power *= 2;
                lam = 0;
                d = gcd(v, n);
                v = 1;
            }
        }
        if (d != n) {
            work(work, d);
            work(work, n / d);
            return;
        }
        ++x0;
    };
    work(work, n);
    sort(res.begin(), res.end());
}

```

```

        return res;
    }
}

```

6.12 Count Primes $\leq n$

```

// __attribute__((target("avx2"),
//     optimize("O3", "unroll-loops")))
i64 primeCount(const i64 n) {
    if (n <= 1) { return 0; }
    if (n == 2) { return 1; }
    const int v = sqrtl(n);
    int s = (v + 1) / 2;
    vector<int> smalls(s), roughs(s), skip(
        v + 1);
    vector<i64> larges(s);
    iota(smalls.begin(), smalls.end(), 0);
    for (int i = 0; i < s; i++) {
        roughs[i] = 2 * i + 1;
        larges[i] = (n / roughs[i] - 1) / 2;
    }
    const auto half = [](int n) -> int {
        return (n - 1) >> 1; };
    int pc = 0;
    for (int p = 3; p <= v; p += 2) {
        if (skip[p]) { continue; }
        int q = p * p;
        if (1LL * q * q > n) { break; }
        skip[p] = true;
        for (int i = q; i <= v; i += 2 * p)
            skip[i] = true;
        int ns = 0;
        for (int k = 0; k < s; k++) {
            int i = roughs[k];
            if (skip[i]) { continue; }
            i64 d = 1LL * i * p;
            larges[ns] = larges[k] - (d <= v ?
                larges[smalls[d / 2] - pc] :
                smalls[half(n / d)] + pc;
            roughs[ns++] = i;
        }
        s = ns;
        for (int i = half(v), j = v / p - 1 |
            1; j >= p; j -= 2) {
            int c = smalls[j / 2] - pc;
            for (int e = j * p / 2; i >= e; i
                --){ smalls[i] -= c; }
        }
        pc++;
    }
    larges[0] += 1LL * (s + 2 * (pc - 1)) *
        (s - 1) / 2;
    for (int k = 1; k < s; k++) { larges[0]
        -= larges[k]; }
    for (int l = 1; l < s; l++) {
        i64 q = roughs[l];
        i64 M = n / q;
        int e = smalls[half(M / q)] - pc;
        if (e <= 1) { break; }
        i64 t = 0;
        for (int k = l + 1; k <= e; k++) { t
            += smalls[half(M / roughs[k])]; }
        larges[0] += t - 1LL * (e - 1) * (pc
            + l - 1);
    }
    return larges[0] + 1;
}

```

6.13 Discrete Logarithm

```

// return min x >= 0 s.t. a ^ x = b mod m
// , 0 ^ 0 = 1, -1 if no solution
// (I think) if you want x > 0 (m != 1),
//     remove if (b == k) return add;
int discreteLog(int a, int b, int m) {
    if (m == 1) {
        return 0;
    }
    a %= m, b %= m;
    int k = 1, add = 0, g;
    while ((g = gcd(a, m)) > 1) {
        if (b == k) {
            return add;
        } else if (b % g) {
            return -1;
        }
    }
    b /= g, m /= g, ++add;
}

```

```

    k = 1LL * k * a / g % m;
}
if (b == k) {
    return add;
}
int n = sqrt(m) + 1;
int an = 1;
for (int i = 0; i < n; ++i) {
    an = 1LL * an * a % m;
}
unordered_map<int, int> vals;
for (int q = 0, cur = b; q < n; ++q) {
    vals[cur] = q;
    cur = 1LL * a * cur % m;
}
for (int p = 1, cur = k; p <= n; ++p) {
    cur = 1LL * cur * an % m;
    if (vals.count(cur)) {
        int ans = n * p - vals[cur] + add;
        return ans;
    }
}
return -1;
}

```

6.14 Quadratic Residue

```

// rng
int jacobi(int a, int m) {
    int s = 1;
    while (m > 1) {
        a %= m;
        if (a == 0) { return 0; }
        int r = __builtin_ctz(a);
        if (r % 2 == 1 && (m + 2 & 4) != 0) {
            s = -s;
        }
        a >>= r;
        if ((a & m & 2) != 0) { s = -s; }
        swap(a, m);
    }
    return s;
}

int quadraticResidue(int a, int p) {
    if (p == 2) { return a % 2; }
    int j = jacobi(a, p);
    if (j == 0 || j == -1) { return j; }
    int b, d;
    while (true) {
        b = rng() % p;
        d = (1LL * b * b + p - a) % p;
        if (jacobi(d, p) == -1) { break; }
    }
    int f0 = b, f1 = 1, g0 = 1, g1 = 0, tmp;
    for (int e = p + 1 >> 1; e > 0; e >>= 1) {
        if (e % 2 == 1) {
            tmp = (1LL * g0 * f0 + 1LL * d * g1
                % p * f1 % p) % p;
            g1 = (1LL * g0 * f1 + 1LL * g1 * f0
                % p) % p;
            g0 = tmp;
        }
        tmp = (1LL * f0 * f0 + 1LL * d * f1 %
            p * f1 % p) % p;
        f1 = 2LL * f0 * f1 % p;
        f0 = tmp;
    }
    return g0;
}

```

6.15 Characteristic Polynomial

```

vector<vector<int>>> Hessenberg(const
    vector<vector<int>>> &A) {
    int N = A.size();
    vector<vector<int>>> H = A;
    for (int i = 0; i < N - 2; ++i) {
        if (H[i + 1][i]) {
            for (int j = i + 2; j < N; ++j) {
                if (H[j][i]) {
                    for (int k = i; k < N; ++k)
                        swap(H[i + 1][k], H[j][k]);
                }
            }
            for (int k = 0; k < N; ++k)
                swap(H[k][i + 1], H[k][j]);
        }
    }
}

```

```

        break;
    }
}
if (!H[i + 1][i]) continue;
int val = fpow(H[i + 1][i], kP - 2);
for (int j = i + 2; j < N; ++j) {
    int coef = 1LL * val * H[j][i] % kP;
    for (int k = i; k < N; ++k) H[j][k]
        = (H[j][k] + 1LL * H[i + 1][k]
            * (kP - coef)) % kP;
    for (int k = 0; k < N; ++k) H[k][i
        + 1] = (H[k][i + 1] + 1LL * H[
            k][j] * coef) % kP;
}
}
return H;
}

vector<int> CharacteristicPoly(const
    vector<vector<int>>> &A) {
    int N = A.size();
    auto H = Hessenberg(A);
    for (int i = 0; i < N; ++i) {
        for (int j = 0; j < N; ++j) H[i][j] =
            kP - H[i][j];
    }
    vector<vector<int>>> P(N + 1, vector<int>
        >(N + 1));
    P[0][0] = 1;
    for (int i = 1; i <= N; ++i) {
        P[i][0] = 0;
        for (int j = 1; j <= i; ++j) P[i][j]
            = P[i - 1][j - 1];
        int val = 1;
        for (int j = i - 1; j >= 0; --j) {
            int coef = 1LL * val * H[j][i - 1]
                % kP;
            for (int k = 0; k <= j; ++k) P[i][k]
                = (P[i][k] + 1LL * P[j][k] *
                    coef) % kP;
            if (j) val = 1LL * val * (kP - H[j
                ][j - 1]) % kP;
        }
        if (N & 1) {
            for (int i = 0; i <= N; ++i) P[N][i]
                = kP - P[N][i];
        }
        return P[N];
    }
}

```

6.16 Linear Sieve Related

```

vector<int> minp(N + 1), primes, mobius(N
    + 1);
mobius[1] = 1;
for (int i = 2; i <= N; ++i) {
    if (!minp[i]) {
        primes.push_back(i);
        minp[i] = i;
        mobius[i] = -1;
    }
    for (int p : primes) {
        if (p > N / i) {
            break;
        }
        minp[p * i] = p;
        mobius[p * i] = -mobius[i];
        if (i % p == 0) {
            mobius[p * i] = 0;
            break;
        }
    }
}
}

```

6.17 De Bruijn Sequence

```

int res[kN], aux[kN], a[kN], sz;
void Rec(int t, int p, int n, int k) {
    if (t > n) {
        if (n % p == 0)
            for (int i = 1; i <= p; ++i) res[sz
                ++] = aux[i];
    } else {
        aux[t] = aux[t - p];
        Rec(t + 1, p, n, k);
    }
}

```

```

    for (aux[t] = aux[t - p] + 1; aux[t]
        < k; ++aux[t]) Rec(t + 1, t, n,
            k);
}
}
int DeBruijn(int k, int n) {
    // return cyclic string of length k^n
    // such that every string of length n
    // using k character appears as a
    // substring.
    if (k == 1) return res[0] = 0, 1;
    fill(aux, aux + k * n, 0);
    return sz = 0, Rec(1, 1, n, k), sz;
}

```

6.18 Floor Sum

```

// \sum_{i=0}^{n-1} floor((a * i + b) / c)
i64 floorSum(i64 a, i64 b, i64 c, i64 n)
{
    if (n < 0) { return 0; }
    if (n == 0) { return b / c; }
    if (a == 0) { return b / c * (n + 1); }
    i64 res = 0;
    if (a >= c) { res += a / c * n * (n +
        1) / 2, a %= c; }
    if (b >= c) { res += b / c * (n + 1), b
        %= c; }
    i64 m = (a * n + b) / c;
    return res + n * m - (m == 0 ? 0 :
        floorSum(c, c - b - 1, a, m - 1));
}

```

6.19 More Floor Sum

$$\begin{aligned}
 & \bullet \quad m = \lfloor \frac{an+b}{c} \rfloor \\
 g(a, b, c, n) &= \sum_{i=0}^n i \lfloor \frac{ai+b}{c} \rfloor \\
 &= \begin{cases} \lfloor \frac{a}{c} \rfloor \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor \cdot \frac{n(n+1)}{2} \\ + g(a \bmod c, b \bmod c, c, n), \\ 0, \\ \frac{1}{2} \cdot (n(n+1)m - f(c, c-b-1, a, m-1) \\ - h(c, c-b-1, a, m-1)), \end{cases} \\
 h(a, b, c, n) &= \sum_{i=0}^n \lfloor \frac{ai+b}{c} \rfloor^2 \\
 &= \begin{cases} \lfloor \frac{a}{c} \rfloor^2 \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor^2 \cdot (n+1) \\ + \lfloor \frac{a}{c} \rfloor \cdot \lfloor \frac{b}{c} \rfloor \cdot n(n+1) \\ + h(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{a}{c} \rfloor \cdot g(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{b}{c} \rfloor \cdot f(a \bmod c, b \bmod c, c, n), \\ 0, \\ nm(m+1) - 2g(c, c-b-1, a, m-1) \\ - 2f(c, c-b-1, a, m-1) - f(a, b, c, n) \end{cases}
 \end{aligned}$$

6.20 Min Mod Linear

```

// \min_{i: [0, n)} (a * i + b) % m
// ok in 1e9
int minModLinear(int n, int m, int a, int
    b, int cnt = 1, int p = 1, int q =
    1) {
    if (a == 0) { return b; }
    if (cnt % 2 == 1) {
        if (b >= a) {
            int t = (m - b + a - 1) / a;
            int c = (t - 1) * p + q;
            if (n <= c) { return b; }
            n -= c;
            b += a * t - m;
        }
        b = a - 1 - b;
    } else {
        if (b < m - a) {
            int t = (m - b - 1) / a;
            int c = t * p;
            if (n <= c) { return (n - 1) / p *
                a + b; }
            n -= c;
            b += a * t;
        }
        b = m - 1 - b;
    }
    cnt++;
}

```



```

int d = m / a;
int c = minModLinear(n, a, m % a, b,
    cnt, (d - 1) * p + q, d * p + q);
return cnt % 2 == 1 ? m - 1 - c : a - 1 - c;
}

```

6.21 Count of subsets with sum (mod P) leq T

```

int n, T;
cin >> n >> T;
vector<int> cnt(T + 1);
for (int i = 0; i < n; i++) {
    int a;
    cin >> a;
    cnt[a]++;
}
vector<Mint> inv(T + 1);
for (int i = 1; i <= T; i++) {
    inv[i] = i == 1 ? 1 : -P / i * inv[P % i];
}
FPS f(T + 1);
for (int i = 1; i <= T; i++) {
    for (int j = 1; j * i <= T; j++) {
        f[i * j] = f[i * j] + (j % 2 == 1 ? 1 : -1) * cnt[i] * inv[j];
    }
}
f = f.exp(T + 1);

```

6.22 Theorem

6.22.1 Kirchhoff's Theorem

Denote L be a $n \times n$ matrix as the Laplacian matrix of graph G , where $L_{ii} = d(i)$, $L_{ij} = -c$ where c is the number of edge (i, j) in G .

- The number of undirected spanning in G is $|\det(\tilde{L}_{11})|$.
- The number of directed spanning tree rooted at r in G is $|\det(\tilde{L}_{rr})|$.

6.22.2 Tutte's Matrix

Let D be a $n \times n$ matrix, where $d_{ij} = x_{ij}$ (x_{ij} is chosen uniformly at random) if $i < j$ and $(i, j) \in E$, otherwise $d_{ij} = -d_{ji}$. $\frac{\text{rank}(D)}{2}$ is the maximum matching on G .

6.22.3 Cayley's Formula

- Given a degree sequence d_1, d_2, \dots, d_n for each labeled vertices, there are $\frac{(n-2)!}{(d_1-1)!(d_2-1)!\dots(d_n-1)!}$ spanning trees.
- Let $T_{n,k}$ be the number of labeled forests on n vertices with k components, such that vertex $1, 2, \dots, k$ belong to different components. Then $T_{n,k} = kn^{n-k-1}$.

6.22.4 Erdős–Gallai Theorem

A sequence of non-negative integers $d_1 \geq d_2 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only if $d_1 + d_2 + \dots + d_n$ is even and

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$$

holds for all $1 \leq k \leq n$.

7 Dynamic Programming

7.1 Dynamic Convex Hull

```

struct Line {
    // kx + b
    mutable i64 k, b, p;
    bool operator<(const Line& o) const {
        return k < o.k; }
    bool operator<(i64 x) const { return p < x; }
};
struct DynamicConvexHullMax : multiset<
    Line, less<>> {
    // (for doubles, use INF = 1/.0, div(a, b) = a/b)
    static constexpr i64 INF =
        numeric_limits<i64>::max();
    i64 div(i64 a, i64 b) {
        // floor
        return a / b - ((a ^ b) < 0 && a % b);
    }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = INF, 0;
        if (x->k == y->k) x->p = x->b > y->b ? INF : -INF;
        else x->p = div(y->b - x->b, x->k - y->k);
        return x->p >= y->p;
    }
    void add(i64 k, i64 b) {
        auto z = insert({k, b, 0}), y = z++,
            x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y))
            isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    i64 query(i64 x) {
        if (empty()) {
            return -INF;
        }
        auto l = *lower_bound(x);
        return l.k * x + l.b;
    }
};

```

7.2 1D/1D Convex Optimization

```

struct segment {
    int i, l, r;
    segment(int a, int b, int c): i(a), l(b), r(c) {}
};
inline long long f(int l, int r) { return dp[l] + w(l + 1, r); }
void solve() {
    dp[0] = 0;
    deque<segment> deq; deq.push_back(segment(0, 1, n));
    for (int i = 1; i <= n; ++i) {
        dp[i] = f(deq.front().i, i);
        while (deq.size() && deq.front().r < i + 1) deq.pop_front();
        deq.front().l = i + 1;
        segment seg = segment(i, i + 1, n);
        while (deq.size() && f(i, deq.back().l) < f(deq.back().i, deq.back().l)) deq.pop_back();
        if (deq.size()) {
            int d = 1048576, c = deq.back().l;
            while (d >= 1) if (c + d <= deq.back().r) {
                if (f(i, c + d) > f(deq.back().i, c + d)) c += d;
            }
            deq.back().r = c; seg.l = c + 1;
        }
        if (seg.l <= n) deq.push_back(seg);
    }
}

```

7.3 Conditon

7.3.1 Totally Monotone (Concave/Convex)

$\forall i < i', j < j', B[i][j] \leq B[i'][j] \implies B[i][j'] \leq B[i'][j']$
 $\forall i < i', j < j', B[i][j] \geq B[i'][j] \implies B[i][j'] \geq B[i'][j']$

7.3.2 Monge Condition (Concave/Convex)

$\forall i < i', j < j', B[i][j] + B[i'][j'] \geq B[i][j'] + B[i'][j]$
 $\forall i < i', j < j', B[i][j] + B[i'][j'] \leq B[i][j'] + B[i'][j]$

7.3.3 Optimal Split Point

If

$B[i][j] + B[i+1][j+1] \geq B[i][j+1] + B[i+1][j]$

then

$$H_{i,j-1} \leq H_{i,j} \leq H_{i+1,j}$$

8 Geometry

8.1 Basic

```

using Real = double; // modify these if needed
constexpr Real eps = 1e-9;
int sign(T x) { return (x > 0) - (x < 0); }
int sign(Real x) { return (x > eps) - (x < -eps); }
int cmp(T a, T b) { return sign(a - b); }
struct P {
    T x = 0, y = 0;
    P(T x = 0, T y = 0): x(x), y(y) {}
    -, +, *, /=, ==, !=, <, >, <=, >= (unary)
};
struct L {
    P<T> a, b;
    L(P<T> a = {}, P<T> b = {}) : a(a), b(b) {}
};
T dot(P<T> a, P<T> b) { return a.x * b.x + a.y * b.y; }
T square(P<T> a) { return dot(a, a); }
Real length(P<T> a) { return sqrtl(square(a)); }
Real dist(P<T> a, P<T> b) { return length(a - b); }
T cross(P<T> a, P<T> b) { return a.x * b.y - a.y * b.x; }
T cross(P<T> p, P<T> a, P<T> b) { return cross(a - p, b - p); }
P<Real> normal(P<T> a) {
    Real len = length(a);
    return P<Real>(a.x / len, a.y / len);
}
bool up(P<T> a) { return sign(a.y) > 0 || sign(a.y) == 0 && sign(a.x) > 0; }
// 3 colinear? please remember to remove (0, 0)
bool polar(P<T> a, P<T> b) {
    bool ua = up(a), ub = up(b);
    return ua != ub ? ua : sign(cross(a, b)) == 1;
}
bool sameDirection(P<T> a, P<T> b) {
    return sign(cross(a, b)) == 0 && sign(dot(a, b)) == 1; }
// 1/0/1 if on a->b's left/right
int side(P<T> p, P<T> a, P<T> b) { return sign(cross(p, a, b)); }
int side(P<T> p, L<T> l) { return side(p, l.a, l.b); }
P<T> rotate90(P<T> p) { return {-p.y, p.x}; }
P<Real> rotate(P<Real> p, Real ang) {
    return {p.x * cos(ang) - p.y * sin(ang), p.x * sin(ang) + p.y * cos(ang)}; }

```



```

Real angle(P<T> p) { return atan2(p.y, p.x); }
P<T> direction(L<T> l) { return l.b - l.a; }
bool sameDirection(L<T> l1, L<T> l2) { return sameDirection(direction(l1), direction(l2)); }
P<Real> projection(P<Real> p, L<Real> l) {
    auto d = direction(l);
    return l.a + d * (dot(p - l.a, d) / square(d));
}
P<Real> reflection(P<Real> p, L<Real> l) { return projection(p, l) * 2 - p; }
Real pointToLineDist(P<Real> p, L<Real> l) { return dist(p, projection(p, l)); }
// better use integers if you don't need exact coordinate
// l <= r is not explicitly required
P<Real> lineIntersection(L<T> l1, L<T> l2) { return l1.a - direction(l1) * (Real(cross(direction(l2), l1.a - l2.a)) / cross(direction(l2), direction(l1))); }
bool between(T m, T l, T r) { return cmp(l, m) == 0 || cmp(m, r) == 0 || l < m != r < m; }
bool pointOnSeg(P<T> p, L<T> l) { return side(p, l) == 0 && between(p.x, l.a.x, l.b.x) && between(p.y, l.a.y, l.b.y); }
bool pointStrictlyOnSeg(P<T> p, L<T> l) { return side(p, l) == 0 && sign(dot(p - l.a, direction(l))) * sign(dot(p - l.b, direction(l))) < 0; }
bool overlap(T l1, T r1, T l2, T r2) { if (l1 > r1) { swap(l1, r1); } if (l2 > r2) { swap(l2, r2); } return cmp(r1, l2) != -1 && cmp(r2, l1) != -1; }
bool segIntersect(L<T> l1, L<T> l2) {
    auto [p1, p2] = l1;
    auto [q1, q2] = l2;
    return overlap(p1.x, p2.x, q1.x, q2.x) && overlap(p1.y, p2.y, q1.y, q2.y) && side(p1, l2) * side(p2, l2) <= 0 && side(q1, l1) * side(q2, l1) <= 0;
}
// parallel intersecting is false
bool segStrictlyIntersect(L<T> l1, L<T> l2) {
    auto [p1, p2] = l1;
    auto [q1, q2] = l2;
    return side(p1, l2) * side(p2, l2) < 0 && side(q1, l1) * side(q2, l1) < 0;
}
// parallel or intersect at source doesn't count
bool rayIntersect(L<T> l1, L<T> l2) {
    int x = sign(cross(l1.b - l1.a, l2.b - l2.a));
    return x == 0 ? false : side(l1.a, l2) == x && side(l2.a, l1) == -x;
}
Real pointToSegDist(P<T> p, L<T> l) {
    auto d = direction(l);
    if (sign(dot(p - l.a, d)) >= 0 && sign(dot(p - l.b, d)) <= 0) {
        return 1.0L * cross(p, l.a, l.b) / dist(l.a, l.b);
    } else {
        return min(dist(p, l.a), dist(p, l.b));
    }
}
Real segDist(L<T> l1, L<T> l2) {
    if (segIntersect(l1, l2)) { return 0; }
    return min({pointToSegDist(l1.a, l2), pointToSegDist(l1.b, l2), pointToSegDist(l2.a, l1), pointToSegDist(l2.b, l1)});
}

```

```

}
// 2 times area
T area(vector<P<T>> a) {
    T res = 0;
    int n = a.size();
    for (int i = 0; i < n; i++) { res += cross(a[i], a[(i + 1) % n]); }
    return res;
}
bool pointInPoly(P<T> p, vector<P<T>> a) {
    int n = a.size(), res = 0;
    for (int i = 0; i < n; i++) {
        P<T> u = a[i], v = a[(i + 1) % n];
        if (pointOnSeg(p, {u, v})) { return 1; }
        if (cmp(u.y, v.y) <= 0) { swap(u, v); }
        if (cmp(p.y, u.y) > 0 || cmp(p.y, v.y) <= 0) { continue; }
        res ^= cross(p, u, v) > 0;
    }
    return res;
}

```

8.2 Convex Hull and related

```

vector<P<T>> convexHull(vector<P<T>> a) {
    int n = a.size();
    if (n <= 1) { return a; }
    sort(a.begin(), a.end());
    a.resize(unique(a.begin(), a.end()), a.end());
    vector<P<T>> b(2 * n);
    int j = 0;
    for (int i = 0; i < n; b[j++] = a[i++]) {
        while (j >= 2 && side(b[j - 2], b[j - 1], a[i]) <= 0) { j--; }
    }
    for (int i = n - 2, k = j; i >= 0; b[j++] = a[i--]) {
        while (j > k && side(b[j - 2], b[j - 1], a[i]) <= 0) { j--; }
    }
    b.resize(j - 1);
    return b;
}
// nonstrict : change <= 0 to < 0
// warning : if all point on same line will return {1, 2, 3, 2}

```

8.3 Half Plane Intersection

```

vector<P<Real>> halfPlaneIntersection(vector<L<Real>> a) {
    sort(a.begin(), a.end(), [&](auto l1, auto l2) {
        if (sameDirection(l1, l2)) { return side(l1.a, l2) > 0; }
        else { return polar(direction(l1), direction(l2)); }
    });
    deque<L<Real>> dq;
    auto check = [&](L<Real> l, L<Real> l1, L<Real> l2) { return side(lineIntersection(l1, l2), l) > 0; };
    for (int i = 0; i < int(a.size()); i++) {
        if (i > 0 && sameDirection(a[i], a[i - 1])) { continue; }
        while (int(dq.size()) > 1 && !check(a[i], dq.end()[-2], dq.back())) { dq.pop_back(); }
        while (int(dq.size()) > 1 && !check(a[i], dq[1], dq[0])) { dq.pop_front(); }
        dq.push_back(a[i]);
    }
    while (int(dq.size()) > 2 && !check(dq[0], dq.end()[-2], dq.back())) { dq.pop_back(); }
}

```

```

while (int(dq.size()) > 2 && !check(dq.back(), dq[1], dq[0])) { dq.pop_front(); }
vector<P<Real>> res;
dq.push_back(dq[0]);
for (int i = 0; i + 1 < int(dq.size()); i++) { res.push_back(lineIntersection(dq[i], dq[i + 1])); }
return res;
}

```

8.4 Triangle Centers

```

// radius: (a + b + c) * r / 2 = A or pointToLineDist
P<Real> inCenter(P<Real> a, P<Real> b, P<Real> c) {
    Real la = length(b - c), lb = length(c - a), lc = length(a - b);
    return (a * la + b * lb + c * lc) / (la + lb + lc);
}
// used in min enclosing circle
P<Real> circumCenter(P<Real> a, P<Real> b, P<Real> c) {
    P<Real> ba = b - a, ca = c - a;
    Real db = square(ba), dc = square(ca), d = 2 * cross(ba, ca);
    return a - P<Real>(ba.y * dc - ca.y * db, ca.x * db - ba.x * dc) / d;
}
P<Real> orthoCenter(P<Real> a, P<Real> b, P<Real> c) {
    L<Real> u(c, P<Real>(c.x - a.y + b.y, c.y + a.x - b.x));
    L<Real> v(b, P<Real>(b.x - a.y + c.y, b.y + a.x - c.x));
    return lineIntersection(u, v);
}

```

8.5 Circle

```

const Real PI = acos(-1);
struct Circle {
    P<Real> o;
    Real r;
    Circle(P<Real> o = {}, Real r = 0) : o(o), r(r) {}
};
// actually counts number of tangent lines
int typeOfCircles(Circle c1, Circle c2) {
    auto [o1, r1] = c1;
    auto [o2, r2] = c2;
    Real d = dist(o1, o2);
    if (cmp(d, r1 + r2) == 1) { return 4; }
    if (cmp(d, r1 + r2) == 0) { return 3; }
    if (cmp(d, abs(r1 - r2)) == 1) { return 2; }
    if (cmp(d, abs(r1 - r2)) == 0) { return 1; }
    return 0;
}
// aligned l.a -> l.b;
vector<P<Real>> circleLineIntersection(Circle c, L<Real> l) {
    P<Real> p = projection(c.o, l);
    Real h = c.r * c.r - square(p - c.o);
    if (sign(h) < 0) { return {}; }
    P<Real> q = normal(direction(l)) * sqrtl(c.r * c.r - square(p - c.o));
    return {p - q, p + q};
}
// circles shouldn't be identical
// duplicated if only one intersection, aligned c1 counterclockwise
vector<P<Real>> circleIntersection(Circle c1, Circle c2) {
    int type = typeOfCircles(c1, c2);
    if (type == 0 || type == 4) { return {}; }
    auto [o1, r1] = c1;
    auto [o2, r2] = c2;
    Real d = clamp(dist(o1, o2), abs(r1 - r2), r1 + r2);
}

```

```

Real y = (r1 * r1 + d * d - r2 * r2) /
(2 * d), x = sqrt(1 - y * y);
P<Real> dir = normal(o2 - o1), q1 = o1
+ dir * y, q2 = rotate90(dir) * x;
return {q1 - q2, q1 + q2};
}
// counterclockwise, on circle -> no
tangent
vector<P<Real>> pointCircleTangent(P<Real>
> p, Circle c) {
Real x = square(p - c.o), d = x - c.r *
c.r;
if (sign(d) <= 0) { return {}; }
P<Real> q1 = c.o + (p - c.o) * (c.r * c
.r / x), q2 = rotate90(p - c.o) *
(c.r * sqrt(d) / x);
return {q1 - q2, q1 + q2};
}
// one-point tangent lines are not
returned
vector<L<Real>> externalTangent(Circle c1
, Circle c2) {
auto [o1, r1] = c1;
auto [o2, r2] = c2;
vector<L<Real>> res;
if (cmp(r1, r2) == 0) {
P dr = rotate90(normal(o2 - o1)) * r1
;
res.emplace_back(o1 + dr, o2 + dr);
res.emplace_back(o1 - dr, o2 - dr);
} else {
P p = (o2 * r1 - o1 * r2) / (r1 - r2)
;
auto ps = pointCircleTangent(p, c1),
qs = pointCircleTangent(p, c2);
for (int i = 0; i < int(min(ps.size(),
qs.size())); i++) { res.
emplace_back(ps[i], qs[i]); }
}
return res;
}
vector<L<Real>> internalTangent(Circle c1
, Circle c2) {
auto [o1, r1] = c1;
auto [o2, r2] = c2;
vector<L<Real>> res;
P<Real> p = (o1 * r2 + o2 * r1) / (r1 +
r2);
auto ps = pointCircleTangent(p, c1), qs
= pointCircleTangent(p, c2);
for (int i = 0; i < int(min(ps.size(),
qs.size())); i++) { res.
emplace_back(ps[i], qs[i]); }
return res;
}
// OAB and circle directed area
Real triangleCircleIntersectionArea(P<
Real> p1, P<Real> p2, Real r) {
auto angle = [&](P<Real> p1, P<Real> p2
) { return atan2(cross(p1, p2),
dot(p1, p2)); };
vector<P<Real>> v =
circleLineIntersection(Circle(P<
Real>(), r), L<Real>(p1, p2));
if (v.empty()) { return r * r * angle(
p1, p2) / 2; }
bool b1 = cmp(square(p1), r * r) == 1,
b2 = cmp(square(p2), r * r) == 1;
if (b1 && b2) {
if (sign(dot(p1 - v[0], p2 - v[0]))
<= 0 && sign(dot(p1 - v[0], p2 -
v[0])) <= 0) {
return r * r * (angle(p1, v[0]) +
angle(v[1], p2)) / 2 + cross(v
[0], v[1]) / 2;
} else {
return r * r * angle(p1, p2) / 2;
}
} else if (b1) {
return (r * r * angle(p1, v[0]) +
cross(v[0], p2)) / 2;
} else if (b2) {
return (cross(p1, v[1]) + r * r *
angle(v[1], p2)) / 2;
} else {
return cross(p1, p2) / 2;
}
}

```

```

}
Real polyCircleIntersectionArea(const
vector<P<Real>> &a, Circle c) {
int n = a.size();
Real ans = 0;
for (int i = 0; i < n; i++) {
ans += triangleCircleIntersectionArea
(a[i], a[(i + 1) % n], c.r);
}
return ans;
}
Real circleIntersectionArea(Circle a,
Circle b) {
int t = typeOfCircles(a, b);
if (t >= 3) {
return 0;
} else if (t <= 1) {
Real r = min(a.r, b.r);
return r * r * PI;
}
Real res = 0, d = dist(a.o, b.o);
for (int i = 0; i < 2; ++i) {
Real alpha = acos((b.r * b.r + d * d
- a.r * a.r) / (2 * b.r * d));
Real s = alpha * b.r * b.r;
Real t = b.r * b.r * sin(alpha) * cos
(alpha);
res += s - t;
swap(a, b);
}
return res;
}

```

8.6 3D Convex Hull

```

double absvol(const P a, const P b, const P
c, const P d) {
return abs(((b-a)^(c-a))^(d-a))/6;
}
struct convex3D {
static const int maxn=1010;
struct T {
int a, b, c;
bool res;
T() {}
T(int a, int b, int c, bool res=1):a(a),
b(b), c(c), res(res) {}
};
int n, m;
P p[maxn];
T f[maxn*8];
int id[maxn][maxn];
bool on(T &t, P &q) {
return ((p[t.c]-p[t.b])^(p[t.a]-p[t.b
]))*(q-p[t.a])>eps;
}
void meow(int q, int a, int b) {
int g=id[a][b];
if (f[g].res) {
if (on(f[g], p[q])) dfs(q, g);
else {
id[q][b]=id[a][q]=id[b][a]=m;
f[m++]=T(b, a, q, 1);
}
}
}
void dfs(int p, int i) {
f[i].res=0;
meow(p, f[i].b, f[i].a);
meow(p, f[i].c, f[i].b);
meow(p, f[i].a, f[i].c);
}
void operator()() {
if (n<4) return;
if ([&]() {
for (int i=1; i<n; ++i) if (abs(p[0]-p
[i])>eps) return swap(p[1], p[i]), 0;
}() || [&]() {
for (int i=2; i<n; ++i) if (abs((p[0]-
p[i])^(p[1]-p[i]))>eps)
return swap(p[2], p[i]), 0;
return 1;
}() || [&]() {

```

```

for (int i=3; i<n; ++i) if (abs(((p
[1]-p[0])^(p[2]-p[0]))*(p[i
]-p[0]))>eps) return swap(p
[3], p[i]), 0;
return 1;
}() return;
for (int i=0; i<4; ++i) {
T t((i+1)%4, (i+2)%4, (i+3)%4, 1);
if (on(t, p[i])) swap(t.b, t.c);
id[t.a][t.b]=id[t.b][t.c]=id[t.c][t
.a]=m;
f[m++]=t;
}
for (int i=4; i<n; ++i) for (int j=0; j<m
; ++j) if (f[j].res && on(f[j], p[i
])) {
dfs(i, j);
break;
}
int mm=m; m=0;
for (int i=0; i<mm; ++i) if (f[i].res) f[m
++]=f[i];
}
bool same(int i, int j) {
return !(absvol(p[f[i].a], p[f[i].b], p
[f[i].c], p[f[j].a], p[f[j].b], p[f[j
].c])>eps || absvol(p[f[i].a], p[f[i].b], p[f[i].c], p[f[j].a], p[f[j].b], p[f[j].c])>eps);
}
int faces() {
int r=0;
for (int i=0; i<m; ++i) {
int iden=1;
for (int j=0; j<i; ++j) if (same(i, j))
iden=0;
r+=iden;
}
return r;
}
}
}

```

8.7 Delaunay Triangulation

```

const P<i64> pINF = P<i64>(1e18, 1e18);
using i128 = __int128_t;
struct Quad {
P<i64> origin;
Quad *rot = nullptr, *onext = nullptr;
bool used = false;
Quad* rev() const { return rot->rot; }
Quad* lnext() const { return rot->rev()
->onext->rot; }
Quad* oprev() const { return rot->onext
->rot; }
P<i64> dest() const { return rev()->
origin; }
};
Quad* makeEdge(P<i64> from, P<i64> to) {
Quad *e1 = new Quad, *e2 = new Quad, *
e3 = new Quad, *e4 = new Quad;
e1->origin = from;
e2->origin = to;
e3->origin = e4->origin = pINF;
e1->rot = e3;
e2->rot = e4;
e3->rot = e2;
e4->rot = e1;
e1->onext = e1;
e2->onext = e2;
e3->onext = e4;
e4->onext = e3;
return e1;
}
void splice(Quad *a, Quad *b) {
swap(a->onext->rot->onext, b->onext->
rot->onext);
swap(a->onext, b->onext);
}
void delEdge(Quad *e) {
splice(e, e->oprev());
splice(e->rev(), e->rev()->oprev());
delete e->rev()->rot;
delete e->rev();
delete e->rot;
delete e;
}
}

```

```

Quad *connect(Quad *a, Quad *b) {
    Quad *e = makeEdge(a->dest(), b->origin
    );
    splice(e, a->lnext());
    splice(e->rev(), b);
    return e;
}
bool onLeft(P<i64> p, Quad *e) { return
    side(p, e->origin, e->dest()) > 0; }
bool onRight(P<i64> p, Quad *e) { return
    side(p, e->origin, e->dest()) < 0; }
template <class T>
T det3(T a1, T a2, T a3, T b1, T b2, T b3
    , T c1, T c2, T c3) {
    return a1 * (b2 * c3 - c2 * b3) - a2 *
        (b1 * c3 - c1 * b3) + a3 * (b1 *
        c2 - c1 * b2);
}
bool inCircle(P<i64> a, P<i64> b, P<i64>
    c, P<i64> d) {
    auto f = [&](P<i64> a, P<i64> b, P<i64>
        c) {
        return det3<i128>(a.x, a.y, square(a)
            , b.x, b.y, square(b), c.x, c.y,
            square(c));
        };
    i128 det = f(a, c, d) + f(a, b, c) - f(
        b, c, d) - f(a, b, d);
    return det > 0;
}
pair<Quad*, Quad*> build(int l, int r,
    vector<P<i64>> &p) {
    if (r - l == 2) {
        Quad *res = makeEdge(p[l], p[l + 1]);
        return pair(res, res->rev());
    } else if (r - l == 3) {
        Quad *a = makeEdge(p[l], p[l + 1]), *
            b = makeEdge(p[l + 1], p[l + 2])
            ;
        splice(a->rev(), b);
        int sg = sign(cross(p[l], p[l + 1], p
            [l + 2]));
        if (sg == 0) { return pair(a, b->rev
            ()); }
        Quad *c = connect(b, a);
        if (sg == 1) {
            return pair(a, b->rev());
        } else {
            return pair(c->rev(), c);
        }
    }
    int m = l + r >> 1;
    auto [ldo, ldi] = build(l, m, p);
    auto [rdo, rdi] = build(m, r, p);
    while (true) {
        if (onLeft(rdi->origin, ldi)) {
            ldi = ldi->lnext();
            continue;
        }
        if (onRight(ldi->origin, rdi)) {
            rdi = rdi->rev()->onext;
            continue;
        }
        break;
    }
    Quad *basel = connect(rdi->rev(), ldi);
    auto valid = [&](Quad *e) { return
        onRight(e->dest(), basel); };
    if (ldi->origin == ldo->origin) { ldo =
        basel->rev(); }
    if (rdi->origin == rdo->origin) { rdo =
        basel; }
    while (true) {
        Quad *lcand = basel->rev()->onext;
        if (valid(lcand)) {
            while (inCircle(basel->dest(),
                basel->origin, lcand->dest(),
                lcand->onext->dest())) {
                Quad *t = lcand->onext;
                delEdge(lcand);
                lcand = t;
            }
        }
        Quad *rcand = basel->oprev();
        if (valid(rcand)) {
            while (inCircle(basel->dest(),
                basel->origin, rcand->dest(),

```

```

        rcand->oprev()->dest())) {
            Quad *t = rcand->oprev();
            delEdge(rcand);
            rcand = t;
        }
    }
    if (!valid(lcand) && !valid(rcand)) {
        break;
    }
    if (!valid(lcand) || valid(rcand) &&
        inCircle(lcand->dest(), lcand->
        origin, rcand->origin, rcand->
        dest())) {
        basel = connect(rcand, basel->rev()
        );
    } else {
        basel = connect(basel->rev(), lcand
        ->rev());
    }
    return pair(ldo, rdo);
}
vector<array<P<i64>, 3>> delaunay(vector<
    P<i64>> p) {
    sort(p.begin(), p.end());
    auto res = build(0, p.size(), p);
    Quad *e = res.first;
    vector<Quad*> edges = {e};
    while (sign(cross(e->onext->dest(), e->
        dest(), e->origin)) == -1) { e = e
        ->onext; }
    auto add = [&]() {
        Quad *cur = e;
        do {
            cur->used = true;
            p.push_back(cur->origin);
            edges.push_back(cur->rev());
            cur = cur->lnext();
        } while (cur != e);
    };
    add();
    p.clear();
    int i = 0;
    while (i < int(edges.size())) { if (!(e
        = edges[i++])->used) { add(); } }
    vector<array<P<i64>, 3>> ans(p.size() /
        3);
    for (int i = 0; i < int(p.size()); i++)
        { ans[i / 3][i % 3] = p[i]; }
    return ans;
}

```

9 Miscellaneous

9.1 Cactus 1

```

auto work = [&](const vector<int> cycle)
    {
        // merge cycle info to u?
        int len = cycle.size(), u = cycle[0];
    };
auto dfs = [&](auto dfs, int u, int p) {
    par[u] = p;
    vis[u] = 1;
    for (auto v : adj[u]) {
        if (v == p) { continue; }
        if (vis[v] == 0) {
            dfs(dfs, v, u);
            if (!cyc[v]) { // merge dp }
        } else if (vis[v] == 1) {
            for (int w = u; w != v; w = par[w])
                {
                    cyc[w] = 1;
                }
        } else {
            vector<int> cycle = {u};
            for (int w = v; w != u; w = par[w])
                { cycle.push_back(w); }
            work(cycle);
        }
    }
    vis[u] = 2;
};

```

9.2 Cactus 2

```

// a component contains no articulation
// point, so P2 is a component
// but not a vertex biconnected component
// by definition
// resulting bct is rooted
struct BlockCutTree {
    int n, square = 0, cur = 0;
    vector<int> low, dfn, stk;
    vector<vector<int>> adj, bct;
    BlockCutTree(int n) : n(n), low(n), dfn
        (n, -1), adj(n), bct(n) {}
    void build() { dfs(0); }
    void addEdge(int u, int v) { adj[u].
        push_back(v), adj[v].push_back(u);
    }
    void dfs(int u) {
        low[u] = dfn[u] = cur++;
        stk.push_back(u);
        for (auto v : adj[u]) {
            if (dfn[v] == -1) {
                dfs(v);
                low[u] = min(low[u], low[v]);
                if (low[v] == dfn[u]) {
                    bct.emplace_back();
                    int x;
                    do {
                        x = stk.back();
                        stk.pop_back();
                        bct.back().push_back(x);
                    } while (x != v);
                    bct[u].push_back(n + square);
                    square++;
                }
            } else {
                low[u] = min(low[u], dfn[v]);
            }
        }
    }
};

```

9.3 Dancing Links

```

#include <bits/stdc++.h>
using namespace std;
// tioj 1333
#define TRAV(i, link, start) for (int i =
    link[start]; i != start; i = link[i
    ])
const int NN = 40000, RR = 200;
template<bool E> // E: Exact, NN: num of
    1s, RR: num of rows
struct DLX {
    int lt[NN], rg[NN], up[NN], dn[NN], rw[
        NN], cl[NN], bt[NN], s[NN], head,
        sz, ans;
    int rows, columns;
    bool vis[NN];
    bitset<RR> sol, cur; // not sure
    void remove(int c) {
        if (E) lt[rg[c]] = lt[c], rg[lt[c]] =
            rg[c];
        TRAV(i, dn, c) {
            if (E) {
                TRAV(j, rg, i)
                    up[dn[j]] = up[j], dn[up[j]] =
                        dn[j], --s[cl[j]];
            } else {
                lt[rg[i]] = lt[i], rg[lt[i]] = rg
                    [i];
            }
        }
    }
    void restore(int c) {
        TRAV(i, up, c) {
            if (E) {
                TRAV(j, lt, i)
                    ++s[cl[j]], up[dn[j]] = j, dn[
                        up[j]] = j;
            } else {
                lt[rg[i]] = rg[lt[i]] = i;
            }
        }
    }
    if (E) lt[rg[c]] = c, rg[lt[c]] = c;
}
void init(int c) {
    rows = 0, columns = c;
}

```

```

for (int i = 0; i < c; ++i) {
    up[i] = dn[i] = bt[i] = i;
    lt[i] = i == 0 ? c : i - 1;
    rg[i] = i == c - 1 ? c : i + 1;
    s[i] = 0;
}
rg[c] = 0, lt[c] = c - 1;
up[c] = dn[c] = -1;
head = c, sz = c + 1;
}
void insert(const vector<int> &col) {
    if (col.empty()) return;
    int f = sz;
    for (int i = 0; i < (int)col.size(); ++i) {
        int c = col[i], v = sz++;
        dn[bt[c]] = v;
        up[v] = bt[c], bt[c] = v;
        rg[v] = (i + 1 == (int)col.size() ? f : v + 1);
        rw[v] = rows, cl[v] = c;
        ++s[c];
        if (i > 0) lt[v] = v - 1;
    }
    ++rows, lt[f] = sz - 1;
}
int h() {
    int ret = 0;
    fill_n(vis, sz, false);
    TRAV(x, rg, head) {
        if (vis[x]) continue;
        vis[x] = true, ++ret;
        TRAV(i, dn, x) TRAV(j, rg, i) vis[cl[j]] = true;
    }
    return ret;
}
void dfs(int dep) {
    if (dep + (E ? 0 : h()) >= ans) return;
    if (rg[head] == head) return sol = cur, ans = dep, void();
    if (dn[rg[head]] == rg[head]) return;
    int w = rg[head];
    TRAV(x, rg, head) if (s[x] < s[w]) w = x;
    if (E) remove(w);
    TRAV(i, dn, w) {
        if (!E) remove(i);
        TRAV(j, rg, i) remove(E ? cl[j] : j);
        cur.set(rw[i], dfs(dep + 1), cur.reset(rw[i]));
        TRAV(j, lt, i) restore(E ? cl[j] : j);
        if (!E) restore(i);
    }
    if (E) restore(w);
}
int solve() {
    for (int i = 0; i < columns; ++i) dn[bt[i]] = i, up[i] = bt[i];
    ans = 1e9, sol.reset(), dfs(0);
    return ans;
}
int main() {
    int n, m; cin >> n >> m;
    DLX<true> solver;
    solver.init(m);
    for (int i = 0; i < n; ++i) {
        vector<int> add;
        for (int j = 0; j < m; ++j) {
            int x; cin >> x;
            if (x == 1) {
                add.push_back(j);
            }
        }
        solver.insert(add);
    }
    cout << solver.solve() << '\n';
    return 0;
}

```

9.4 Offline Dynamic MST

```

int cnt[maxn], cost[maxn], st[maxn], ed[
    maxn];
pair<int, int> qr[maxn];
// qr[i].first = id of edge to be changed
// qr[i].second = weight after operation
// cnt[i] = number of operation on edge i
// call solve(0, q - 1, v, 0), where v
// contains edges i such that cnt[i] == 0
void contract(int l, int r, vector<int> v,
    vector<int> &x, vector<int> &y) {
    sort(v.begin(), v.end(), [&](int i, int j) {
        if (cost[i] == cost[j]) return i < j;
        return cost[i] < cost[j];
    });
    djs.save();
    for (int i = l; i <= r; ++i) djs.merge(st[qr[i].first], ed[qr[i].first]);
    for (int i = 0; i < (int)v.size(); ++i) {
        if (djs.find(st[v[i]]) != djs.find(ed[v[i]])) {
            x.push_back(v[i]);
            djs.merge(st[v[i]], ed[v[i]]);
        }
    }
    djs.undo();
    djs.save();
    for (int i = 0; i < (int)x.size(); ++i) djs.merge(st[x[i]], ed[x[i]]);
    for (int i = 0; i < (int)v.size(); ++i) {
        if (djs.find(st[v[i]]) != djs.find(ed[v[i]])) {
            y.push_back(v[i]);
            djs.merge(st[v[i]], ed[v[i]]);
        }
    }
    djs.undo();
}
void solve(int l, int r, vector<int> v, long long c) {
    if (l == r) {
        cost[qr[l].first] = qr[l].second;
        if (st[qr[l].first] == ed[qr[l].first]) {
            printf("%lld\n", c);
            return;
        }
        int minv = qr[l].second;
        for (int i = 0; i < (int)v.size(); ++i) minv = min(minv, cost[v[i]]);
        printf("%lld\n", c + minv);
        return;
    }
    int m = (l + r) >> 1;
    vector<int> lv = v, rv = v;
    vector<int> x, y;
    for (int i = m + 1; i <= r; ++i) {
        cnt[qr[i].first]--;
        if (cnt[qr[i].first] == 0) lv.push_back(qr[i].first);
    }
    contract(l, m, lv, x, y);
    long long lc = c, rc = c;
    djs.save();
    for (int i = 0; i < (int)x.size(); ++i) {
        lc += cost[x[i]];
        djs.merge(st[x[i]], ed[x[i]]);
    }
    solve(l, m, y, lc);
    djs.undo();
    x.clear(), y.clear();
    for (int i = m + 1; i <= r; ++i) cnt[qr[i].first]++;
    for (int i = l; i <= m; ++i) {
        cnt[qr[i].first]--;
        if (cnt[qr[i].first] == 0) rv.push_back(qr[i].first);
    }
    contract(m + 1, r, rv, x, y);
}

```

```

djs.save();
for (int i = 0; i < (int)x.size(); ++i) {
    rc += cost[x[i]];
    djs.merge(st[x[i]], ed[x[i]]);
}
solve(m + 1, r, y, rc);
djs.undo();
for (int i = l; i <= m; ++i) cnt[qr[i].first]++;
}

```

9.5 Matroid Intersection

- $x \rightarrow y$ if $S - \{x\} \cup \{y\} \in I_1$ with $cost(\{y\})$.
- $source \rightarrow y$ if $S \cup \{y\} \in I_1$ with $cost(\{y\})$.
- $y \rightarrow x$ if $S - \{x\} \cup \{y\} \in I_2$ with $-cost(\{y\})$.
- $y \rightarrow sink$ if $S \cup \{y\} \in I_2$ with $-cost(\{y\})$.

Augmenting path is shortest path from source to sink.

9.6 Euler Tour

```

vector<int> euler, vis(V);
auto dfs = [&](auto dfs, int u) -> void {
    while (!adj[u].empty()) {
        while (!adj[u].empty() && del[adj[u].back()[1]]) {
            adj[u].pop_back();
        }
        if (!adj[u].empty()) {
            auto [v, i] = adj[u].back();
            del[i] = true;
            dfs(dfs, v);
        }
    }
    euler.push_back(u);
};
dfs(dfs, 0);
reverse(euler.begin(), euler.end());

```

9.7 SegTree Beats

```

struct SegmentTree {
    int n;
    struct node {
        i64 mx1, mx2, mxc;
        i64 mn1, mn2, mnc;
        i64 add;
        i64 sum;
        node(i64 v = 0) {
            mx1 = mn1 = sum = v;
            mxc = mnc = 1;
            add = 0;
            mx2 = -9e18, mn2 = 9e18;
        }
    };
    vector<node> t;
    // build
    void push(int id, int l, int r) {
        auto& c = t[id];
        int m = l + r >> 1;
        if (c.add != 0) {
            apply_add(id << 1, l, m, c.add);
            apply_add(id << 1 | 1, m + 1, r, c.add);
            c.add = 0;
        }
        apply_min(id << 1, l, m, c.mn1);
        apply_min(id << 1 | 1, m + 1, r, c.mn1);
        apply_max(id << 1, l, m, c.mx1);
        apply_max(id << 1 | 1, m + 1, r, c.mx1);
    }
    void apply_add(int id, int l, int r, i64 v) {
        if (v == 0) {
            return;
        }
        auto& c = t[id];
        c.add += v;
        c.sum += v * (r - l + 1);
        c.mx1 += v;
        c.mn1 += v;
        if (c.mx2 != -9e18) {
            c.mx2 += v;
        }
    }
}

```



```

    if (c.mn2 != 9e18) {
        c.mn2 += v;
    }
}
void apply_min(int id, int l, int r,
               i64 v) {
    auto& c = t[id];
    if (v <= c.mn1) {
        return;
    }
    c.sum -= c.mn1 * c.mnc;
    c.mn1 = v;
    c.sum += c.mn1 * c.mnc;
    if (l == r || v >= c.mx1) {
        c.mx1 = v;
    } else if (v > c.mx2) {
        c.mx2 = v;
    }
}
void apply_max(int id, int l, int r,
               i64 v) {
    auto& c = t[id];
    if (v >= c.mx1) {
        return;
    }
    c.sum -= c.mx1 * c.mxc;
    c.mx1 = v;
    c.sum += c.mx1 * c.mxc;
    if (l == r || v <= c.mn1) {
        c.mn1 = v;
    } else if (v < c.mn2) {
        c.mn2 = v;
    }
}
void pull(int id) {
    auto &c = t[id], &lc = t[id << 1], &rc = t[id << 1 | 1];
    c.sum = lc.sum + rc.sum;
    if (lc.mn1 == rc.mn1) {
        c.mn1 = lc.mn1;
        c.mn2 = min(lc.mn2, rc.mn2);
        c.mnc = lc.mnc + rc.mnc;
    } else if (lc.mn1 < rc.mn1) {
        c.mn1 = lc.mn1;
        c.mn2 = min(lc.mn2, rc.mn1);
        c.mnc = lc.mnc;
    } else {
        c.mn1 = rc.mn1;
        c.mn2 = min(lc.mn1, rc.mn2);
        c.mnc = rc.mnc;
    }
    if (lc.mx1 == rc.mx1) {
        c.mx1 = lc.mx1;
        c.mx2 = max(lc.mx2, rc.mx2);
        c.mxc = lc.mxc + rc.mxc;
    } else if (lc.mx1 > rc.mx1) {
        c.mx1 = lc.mx1;
        c.mx2 = max(lc.mx2, rc.mx1);
        c.mxc = lc.mxc;
    } else {
        c.mx1 = rc.mx1;
        c.mx2 = max(lc.mx1, rc.mx2);
        c.mxc = rc.mxc;
    }
}
void range_chmin(int id, int l, int r,
                 int ql, int qr, i64 v) {
    if (r < ql || l > qr || v >= t[id].mx1) {
        return;
    }
    if (ql <= l && r <= qr && v > t[id].mx2) {
        apply_max(id, l, r, v);
        return;
    }
    push(id, l, r);
    int m = l + r >> 1;
    range_chmin(id << 1, l, m, ql, qr, v);
    range_chmin(id << 1 | 1, m + 1, r, ql, qr, v);
    pull(id);
}
void range_chmin(int ql, int qr, i64 v) {
    range_chmin(1, 0, n - 1, ql, qr, v);
}

```

```

void range_chmax(int id, int l, int r,
                 int ql, int qr, i64 v) {
    if (r < ql || l > qr || v <= t[id].mn1) {
        return;
    }
    if (ql <= l && r <= qr && v < t[id].mn2) {
        apply_min(id, l, r, v);
        return;
    }
    push(id, l, r);
    int m = l + r >> 1;
    range_chmax(id << 1, l, m, ql, qr, v);
    range_chmax(id << 1 | 1, m + 1, r, ql, qr, v);
    pull(id);
}
void range_chmax(int ql, int qr, i64 v) {
    range_chmax(1, 0, n - 1, ql, qr, v);
}
void range_add(int id, int l, int r,
               int ql, int qr, i64 v) {
    if (r < ql || l > qr) {
        return;
    }
    if (ql <= l && r <= qr) {
        apply_add(id, l, r, v);
        return;
    }
    push(id, l, r);
    int m = l + r >> 1;
    range_add(id << 1, l, m, ql, qr, v);
    range_add(id << 1 | 1, m + 1, r, ql, qr, v);
    pull(id);
}
void range_add(int ql, int qr, i64 v) {
    range_add(1, 0, n - 1, ql, qr, v);
}
i64 range_sum(int id, int l, int r, int ql, int qr) {
    if (r < ql || l > qr) {
        return 0;
    }
    if (ql <= l && r <= qr) {
        return t[id].sum;
    }
    push(id, l, r);
    int m = l + r >> 1;
    return range_sum(id << 1, l, m, ql, qr) + range_sum(id << 1 | 1, m + 1, r, ql, qr);
}
i64 range_sum(int ql, int qr) {
    return range_sum(1, 0, n - 1, ql, qr);
}

```

9.8 unorganized

```

const int N = 1021;
struct CircleCover {
    int C;
    Cir c[N];
    bool g[N][N], overlap[N][N];
    // Area[i] : area covered by at least i circles
    double Area[N];
    void init(int _C) { C = _C; }
    struct Teve {
        pdd p; double ang; int add;
        Teve(pdd _a, double _b, int _c):p(_a), ang(_b), add(_c) {}
        bool operator<(const Teve &a) const {
            return ang < a.ang;
        }
    };
    Teve[N * 2];
    // strict: x = 0, otherwise x = -1
    bool disjunct(Cir &a, Cir &b, int x) {
        return sign(abs(a.0 - b.0) - a.R - b.R) > x;
    }
    bool contain(Cir &a, Cir &b, int x)

```

```

{
    return sign(a.R - b.R - abs(a.0 - b.0)) > x;
}
bool contain(int i, int j) {
    /* c[j] is non-strictly in c[i]. */
    return (sign(c[i].R - c[j].R) > 0 || (sign(c[i].R - c[j].R) == 0 && i < j)) && contain(c[i], c[j], -1);
}
void solve() {
    fill_n(Area, C + 2, 0);
    for (int i = 0; i < C; ++i)
        for (int j = 0; j < C; ++j)
            overlap[i][j] = contain(i, j);
    for (int i = 0; i < C; ++i)
        for (int j = 0; j < C; ++j)
            g[i][j] = !(overlap[i][j] || overlap[j][i] || disjunct(c[i], c[j], -1));
    for (int i = 0; i < C; ++i) {
        int E = 0, cnt = 1;
        for (int j = 0; j < C; ++j)
            if (j != i && overlap[j][i]) ++cnt;
        for (int j = 0; j < C; ++j)
            if (i != j && g[i][j]) {
                pdd aa, bb;
                CCInter(c[i], c[j], aa, bb);
                double A = atan2(aa.Y - c[i].0.X, aa.X - c[i].0.X);
                double B = atan2(bb.Y - c[i].0.X, bb.X - c[i].0.X);
                eve[E++] = Teve(bb, B, 1), eve[E++] = Teve(aa, A, -1);
                if (B > A) ++cnt;
            }
        if (E == 0) Area[cnt] += pi * c[i].R * c[i].R;
    }
    else {
        sort(eve, eve + E);
        eve[E] = eve[0];
        for (int j = 0; j < E; ++j) {
            cnt += eve[j].add;
            Area[cnt] += cross(eve[j].p, eve[j + 1].p) * .5;
            double theta = eve[j + 1].ang - eve[j].ang;
            if (theta < 0) theta += 2. * pi;
            Area[cnt] += (theta - sin(theta)) * c[i].R * c[i].R * .5;
        }
    }
}
// p, q is convex
double TwoConvexHullMinDist(Point P[], Point Q[], int n, int m) {
    int YMinP = 0, YMaxQ = 0;
    double tmp, ans = 999999999;
    for (i = 0; i < n; ++i) if (P[i].y < P[YMinP].y) YMinP = i;
    for (i = 0; i < m; ++i) if (Q[i].y > Q[YMaxQ].y) YMaxQ = i;
    P[n] = P[0], Q[m] = Q[0];
    for (int i = 0; i < n; ++i) {
        while (tmp = Cross(Q[YMaxQ + 1] - P[YMinP + 1], P[YMinP + 1] - P[YMinP + 1]) > Cross(Q[YMaxQ] - P[YMinP + 1], P[YMinP + 1] - P[YMinP + 1]))
            YMaxQ = (YMaxQ + 1) % m;
        if (tmp < 0) ans = min(ans, PointToSegDist(P[YMinP], P[YMinP + 1], Q[YMaxQ]));
        else ans = min(ans, TwoSegMinDist(P[YMinP], P[YMinP + 1], Q[YMaxQ], Q[YMaxQ + 1]));
        YMinP = (YMinP + 1) % n;
    }
    return ans;
}
template <typename F, typename C> class MCMF {
    static constexpr F INF_F = numeric_limits<F>::max();

```



```

static constexpr C INF_C =
    numeric_limits<C>::max();
vector<tuple<int, int, F, C>> es;
vector<vector<int>> g;
vector<F> f;
vector<C> d;
vector<int> pre, inq;
void spfa(int s) {
    fill(inq.begin(), inq.end(), 0);
    fill(d.begin(), d.end(), INF_C);
    fill(pre.begin(), pre.end(), -1);

    queue<int> q;
    d[s] = 0;
    q.push(s);
    while (!q.empty()) {
        int u = q.front();
        inq[u] = false;
        q.pop();
        for (int j : g[u]) {
            int to = get<1>(es[j]);
            C w = get<3>(es[j]);
            if (f[j] == 0 || d[to] <= d[u] +
                w)
                continue;
            d[to] = d[u] + w;
            pre[to] = j;
            if (!inq[to]) {
                inq[to] = true;
                q.push(to);
            }
        }
    }
}
public:
MCMF(int n) : g(n), pre(n), inq(n) {}
void add_edge(int s, int t, F c, C w) {
    g[s].push_back(es.size());
    es.emplace_back(s, t, c, w);
    g[t].push_back(es.size());
    es.emplace_back(t, s, 0, -w);
}
pair<F, C> solve(int s, int t, C mx =
    INF_C / INF_F) {
    add_edge(t, s, INF_F, -mx);
    f.resize(es.size()), d.resize(es.size());
    for (F I = INF_F ^ (INF_F / 2); I; I
        >>= 1) {
        for (auto &fi : f)
            fi *= 2;
        for (size_t i = 0; i < f.size(); i
            += 2) {
            auto [u, v, c, w] = es[i];
            if ((c & I) == 0)
                continue;
            if (f[i]) {
                f[i] += 1;
                continue;
            }
            spfa(v);
            if (d[u] == INF_C || d[u] + w >=
                0) {
                f[i] += 1;
                continue;
            }
            f[i + 1] += 1;
            while (u != v) {
                int x = pre[u];
                f[x] -= 1;
                f[x ^ 1] += 1;
                u = get<0>(es[x]);
            }
        }
        C w = 0;
        for (size_t i = 1; i + 2 < f.size();
            i += 2)
            w -= f[i] * get<3>(es[i]);
        return {f.back(), w};
    }
}
auto [f, c] = mcmf.solve(s, t, 1e12);
cout << f << ' ' << c << '\n';

void MoAlgoOnTree() {

```

```

Dfs(0, -1);
vector<int> euler(tk);
for (int i = 0; i < n; ++i) {
    euler[tin[i]] = i;
    euler[tout[i]] = i;
}
vector<int> l(q), r(q), qr(q), sp(q,
    -1);
for (int i = 0; i < q; ++i) {
    if (tin[u[i]] > tin[v[i]]) swap(u[i],
        v[i]);
    int z = GetLCA(u[i], v[i]);
    sp[i] = z[i];
    if (z == u) l[i] = tin[u[i]], r[i] =
        tin[v[i]];
    else l[i] = tout[u[i]], r[i] = tin[v[
        i]];
    qr[i] = i;
}
sort(qr.begin(), qr.end(), [&](int i,
    int j) {
    if (l[i] / kB == l[j] / kB) return
        r[i] < r[j];
    return l[i] / kB < l[j] / kB;
});
vector<bool> used(n);
// Add(v): add/remove v to/from the
// path based on used[v]
for (int i = 0, tl = 0, tr = -1; i < q;
    ++i) {
    while (tl < l[qr[i]]) Add(euler[tl
        ++]);
    while (tl > l[qr[i]]) Add(euler[tl
        --]);
    while (tr > r[qr[i]]) Add(euler[tr
        --]);
    while (tr < r[qr[i]]) Add(euler[tr
        ++]);
    // add/remove LCA(u, v) if necessary
}
for (int l = 0, r = -1; auto [ql, qr, i]
    : qs) {
    if (ql / B == qr / B) {
        for (int j = ql; j <= qr; j++) {
            cntSmall[a[j]]++;
            ans[i] = max(ans[i], 1LL * b[
                a[j]] * cntSmall[a[j]]);
        }
        for (int j = ql; j <= qr; j++) {
            cntSmall[a[j]]--;
        }
        continue;
    }
    if (int block = ql / B; block != lst)
        {
            int x = min((block + 1) * B, n);
            while (r + 1 < x) { add(++r); }
            while (r >= x) { del(r--); }
            while (l < x) { del(l++); }
            mx = 0;
            lst = block;
        }
    while (r < qr) { add(++r); }
    i64 tmpMx = mx;
    int tmpL = l;
    while (l > ql) { add(--l); }
    ans[i] = mx;
    mx = tmpMx;
    while (l < tmpL) { del(l++); }
}
typedef pair<ll, int> T;
typedef struct heap* ph;
struct heap { // min heap
    ph l = NULL, r = NULL;
    int s = 0; T v; // s: path to leaf
    heap(T _v):v(_v) {}
};
ph meld(ph p, ph q) {
    if (!p || !q) return p?:q;
    if (p->v > q->v) swap(p, q);
    ph P = new heap(*p); P->r = meld(P->r, q
        );
    if (!P->l || P->l->s < P->r->s) swap(P
        ->l, P->r);
}

```

```

P->s = (P->r?P->r->s:0)+1; return P;
}
ph ins(ph p, T v) { return meld(p, new
    heap(v)); }
ph pop(ph p) { return meld(p->l, p->r); }
int N, M, src, des, K;
ph cand[MX];
vector<array<int, 3>> adj[MX], radj[MX];
pi pre[MX];
ll dist[MX];
struct state {
    int vert; ph p; ll cost;
    bool operator<(const state& s) const {
        return cost > s.cost; }
};
int main() {
    setIO(); re(N, M, src, des, K);
    FOR(i, M) {
        int u, v, w; re(u, v, w);
        adj[u].pb({v, w, i}); radj[v].pb({u, w, i
            }); // vert, weight, label
    }
    priority_queue<state> ans;
    {
        FOR(i, N) dist[i] = INF, pre[i] =
            {-1, -1};
        priority_queue<T, vector<T>, greater<T
            >> pq;
        auto ad = [&](int a, ll b, pi ind) {
            if (dist[a] <= b) return;
            pre[a] = ind; pq.push({dist[a] = b,
                a});
        };
        ad(des, 0, {-1, -1});
        vi seq;
        while (sz(pq)) {
            auto a = pq.top(); pq.pop();
            if (a.f > dist[a.s]) continue;
            seq.pb(a.s); trav(t, radj[a.s]) ad(t
                [0], a.f+t[1], {t[2], a.s}); //
            edge index, vert
        }
        trav(t, seq) {
            trav(u, adj[t]) if (u[2] != pre[t].f
                && dist[u[0]] != INF) {
                ll cost = dist[u[0]]+u[1]-dist[t
                    ];
                cand[t] = ins(cand[t], {cost, u
                    [0]});
            }
            if (pre[t].f != -1) cand[t] = meld(
                cand[t], cand[pre[t].s]);
            if (t == src) {
                ps(dist[t]); K--;
                if (cand[t]) ans.push(state{t,
                    cand[t], dist[t]+cand[t]->v.f
                    });
            }
        }
    }
    FOR(i, K) {
        if (!sz(ans)) {
            ps(-1);
            continue;
        }
        auto a = ans.top(); ans.pop();
        int vert = a.vert;
        ps(a.cost);
        if (a.p->l) {
            ans.push(state{vert, a.p->l, a.cost+a
                .p->l->v.f-a.p->v.f});
        }
        if (a.p->r) {
            ans.push(state{vert, a.p->r, a.cost+a
                .p->r->v.f-a.p->v.f});
        }
        int V = a.p->v.s;
        if (cand[V]) ans.push(state{V, cand[V
            ], a.cost+cand[V]->v.f});
    }
}
Pt LinesInter(Line a, Line b) {
    double abc = (a.b - a.a) ^ (b.a - a.a
        );
}

```

```

double abd = (a.b - a.a) ^ (b.b - a.a
);
if (sign(abc - abd) == 0) return b.b;
// no inter
return (b.b * abc - b.a * abd) / (abc
- abd);
}
vector<Pt> SegsInter(Line a, Line b) {
    if (btw(a.a, a.b, b.a)) return {b.a};
    if (btw(a.a, a.b, b.b)) return {b.b};
    if (btw(b.a, b.b, a.a)) return {a.a};
    if (btw(b.a, b.b, a.b)) return {a.b};
    if (ori(a.a, a.b, b.a) * ori(a.a, a.b
, b.b) == -1 && ori(b.a, b.b, a
.a) * ori(b.a, b.b, a.b) == -1) {
        return {LinesInter(a, b)};
    }
    return {};
}
double polyUnion(vector<vector<Pt>>
poly) {
    int n = poly.size();
    double ans = 0;
    auto solve = [&](Pt a, Pt b, int cid)
    {
        vector<pair<Pt, int>> event;
        for (int i = 0; i < n; ++i) {
            int st = 0, sz = poly[i].size
();
            while (st < sz && ori(poly[i
][st], a, b) != 1) st++;
            if (st == sz) continue;
            for (int j = 0; j < sz; ++j)
            {
                Pt c = poly[i][(j + st) %
sz], d = poly[i][(j
+ st + 1) % sz];
                if (sign((a - b) ^ (c - d
)) != 0) {
                    int ok1 = ori(c, a, b
) == 1;
                    int ok2 = ori(d, a, b
) == 1;
                    if (ok1 & ok2) event.
emplace_back(
LinesInter({a, b
}, {c, d}), ok1
? 1 : -1);
                } else if (ori(c, a, b)
== 0 && sign((a - b)
* (c - d)) > 0 && i
<= cid) {
                    event.emplace_back(c,
-1);
                    event.emplace_back(d,
1);
                }
            }
        }
        sort(all(event), [&](pair<Pt,
int> i, pair<Pt, int> j) {
            return ((a - i.first) * (a -
b)) < ((a - j.first) * (
a - b));
        });
        int now = 0;
        Pt lst = a;
        for (auto [x, y] : event) {
            if (btw(a, b, lst) && btw(a,
b, x) && now == 0) ans
+= lst ^ x;
            now += y, lst = x;
        }
    };
    for (int i = 0; i < n; ++i) for (int
j = 0; j < poly[i].size(); ++j)
    {
        Pt a = poly[i][j], b = poly[i][(j
+ 1) % int(poly[i].size())
];
        solve(a, b, i);
    }
    return ans / 2;
}
// Minimum Steiner Tree,  $O(V^3 \log V + V^2 \log^2 V)$ 

```

```

struct SteinerTree { // 0-base
    static const int T = 10, N = 105, INF =
1e9;
    int n, dst[N][N], dp[1 << T][N], tdst[N]
];
    int vcost[N]; // the cost of vertexs
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i) {
            for (int j = 0; j < n; ++j) dst[i][
j] = INF;
            dst[i][i] = vcost[i] = 0;
        }
    }
    void add_edge(int ui, int vi, int wi) {
        dst[ui][vi] = min(dst[ui][vi], wi);
    }
    void shortest_path() {
        for (int k = 0; k < n; ++k)
            for (int i = 0; i < n; ++i)
                for (int j = 0; j < n; ++j)
                    dst[i][j] =
min(dst[i][j], dst[i][k] +
dst[k][j]);
    }
    int solve(const vector<int> &ter) {
        shortest_path();
        int t = SZ(ter);
        for (int i = 0; i < (1 << t); ++i)
            for (int j = 0; j < n; ++j) dp[i][j]
= INF;
        for (int i = 0; i < n; ++i) dp[0][i]
= vcost[i];
        for (int msk = 1; msk < (1 << t); ++
msk) {
            if (!(msk & (msk - 1))) {
                int who = __lg(msk);
                for (int i = 0; i < n; ++i)
                    dp[msk][i] =
vcost[ter[who]] + dst[ter[who
]][i];
            }
            for (int i = 0; i < n; ++i)
                for (int submsk = (msk - 1) & msk
; submsk;
                    submsk = (submsk - 1) & msk)
                    dp[msk][i] = min(dp[msk][i],
dp[submsk][i] + dp[msk ^
submsk][i] -
vcost[i]);
            for (int i = 0; i < n; ++i) {
                tdst[i] = INF;
                for (int j = 0; j < n; ++j)
                    tdst[i] =
min(tdst[i], dp[msk][j] + dst
[j][i]);
            }
            for (int i = 0; i < n; ++i) dp[msk
][i] = tdst[i];
        }
        int ans = INF;
        for (int i = 0; i < n; ++i)
            ans = min(ans, dp[(1 << t) - 1][i])
;
        return ans;
    }
};

```