

This module defines a binary search algorithm for finding an item in a sorted sequence, and contains a *TLAPS*-checked proof of its safety property. We assume a sorted sequence *seq* with elements in some set *Values* of integers and a number *val* in *Values*, it sets the value *result* to either a number *i* with $seq[i] = val$, or to 0 if there is no such *i*.

It is surprisingly difficult to get such a binary search algorithm correct without making errors that have to be caught by debugging. I suggest trying to write a correct *PlusCal* binary search algorithm yourself before looking at this one.

This algorithm is one of the examples in Section 7.3 of “Proving Safety Properties”, which is at

<http://lamport.azurewebsites.net/tla/proving-safety.pdf>

EXTENDS *Integers*, *Sequences*, *TLAPS*

CONSTANT *Values*

ASSUME $ValAssump \triangleq Values \subseteq Int$

$SortedSeqs \triangleq \{ss \in Seq(Values) : \forall i, j \in 1..Len(ss) : (i < j) \Rightarrow (ss[i] \leq ss[j])\}$

```
--fair algorithm BinarySearch{
  variables seq ∈ SortedSeqs, val ∈ Values,
             low = 1, high = Len(seq), result = 0;
  { a: while ( low ≤ high ∧ result = 0 ) {
    with ( mid = (low + high) ÷ 2, mval = seq[mid] ) {
      if ( mval = val ) { result := mid }
      else if ( val < mval ) { high := mid - 1 }
      else { low := mid + 1 }
    } } } }
```

BEGIN TRANSLATION

VARIABLES *seq*, *val*, *low*, *high*, *result*, *pc*

$vars \triangleq \langle seq, val, low, high, result, pc \rangle$

$Init \triangleq$ Global variables
 $\wedge seq \in SortedSeqs$
 $\wedge val \in Values$
 $\wedge low = 1$
 $\wedge high = Len(seq)$
 $\wedge result = 0$
 $\wedge pc = \text{“a”}$

$a \triangleq$ $\wedge pc = \text{“a”}$
 \wedge IF $low \leq high \wedge result = 0$
 THEN \wedge LET $mid \triangleq (low + high) \div 2$ IN
 LET $mval \triangleq seq[mid]$ IN

$$\begin{aligned}
& \text{IF } mval = val \\
& \quad \text{THEN } \wedge result' = mid \\
& \quad \quad \wedge \text{UNCHANGED } \langle low, high \rangle \\
& \quad \text{ELSE } \wedge \text{IF } val < mval \\
& \quad \quad \quad \text{THEN } \wedge high' = mid - 1 \\
& \quad \quad \quad \quad \wedge low' = low \\
& \quad \quad \quad \text{ELSE } \wedge low' = mid + 1 \\
& \quad \quad \quad \quad \wedge high' = high \\
& \quad \quad \wedge \text{UNCHANGED } result \\
& \quad \wedge pc' = \text{"a"} \\
& \text{ELSE } \wedge pc' = \text{"Done"} \\
& \quad \wedge \text{UNCHANGED } \langle low, high, result \rangle \\
& \wedge \text{UNCHANGED } \langle seq, val \rangle \\
Next & \triangleq a \\
& \vee \text{Disjunct to prevent deadlock on termination} \\
& \quad (pc = \text{"Done"} \wedge \text{UNCHANGED } vars) \\
Spec & \triangleq \wedge Init \wedge \square [Next]_{vars} \\
& \quad \wedge WF_{vars}(Next) \\
Termination & \triangleq \diamond (pc = \text{"Done"})
\end{aligned}$$

END TRANSLATION

Partial correctness of the algorithm is expressed by invariance of formula *resultCorrect*. To get *TLC* to check this property, we use a model that overrides the definition of *Seq* so *Seq(S)* is the set of sequences of elements of *S* having at most some small length. For example,

$$Seq(S) \triangleq \text{UNION } \{[1 \dots i \rightarrow S] : i \in 0 \dots 3\}$$

is the set of such sequences with length at most 3.

$$\begin{aligned}
resultCorrect & \triangleq \\
& (pc = \text{"Done"}) \Rightarrow \text{IF } \exists i \in 1 \dots Len(seq) : seq[i] = val \\
& \quad \text{THEN } seq[result] = val \\
& \quad \text{ELSE } result = 0
\end{aligned}$$

Proving the invariance of *resultCorrect* requires finding an inductive invariant that implies it. A suitable inductive invariant *Inv* is defined here. You can use *TLC* to check that *Inv* is an inductive invariant.

$$\begin{aligned}
TypeOK & \triangleq \wedge seq \in SortedSeqs \\
& \quad \wedge val \in Values \\
& \quad \wedge low \in 1 \dots (Len(seq) + 1) \\
& \quad \wedge high \in 0 \dots Len(seq) \\
& \quad \wedge result \in 0 \dots Len(seq) \\
& \quad \wedge pc \in \{\text{"a"}, \text{"Done"}\}
\end{aligned}$$

$$\begin{aligned}
Inv & \triangleq \wedge TypeOK \\
& \quad \wedge (result \neq 0) \Rightarrow (Len(seq) > 0) \wedge (seq[result] = val)
\end{aligned}$$

$$\begin{aligned}
& \wedge (pc = \text{"a"}) \Rightarrow \\
& \quad \text{IF } \exists i \in 1 \dots \text{Len}(seq) : seq[i] = val \\
& \quad \quad \text{THEN } \exists i \in low \dots high : seq[i] = val \\
& \quad \quad \text{ELSE } result = 0 \\
& \wedge (pc = \text{"Done"}) \Rightarrow (result \neq 0) \vee (\forall i \in 1 \dots \text{Len}(seq) : seq[i] \neq val)
\end{aligned}$$

Here is the invariance proof.

THEOREM $Spec \Rightarrow \Box resultCorrect$

$\langle 1 \rangle 1. Init \Rightarrow Inv$

BY DEF $Init, Inv, TypeOK$

$\langle 1 \rangle 2. Inv \wedge [Next]_{vars} \Rightarrow Inv'$

$\langle 2 \rangle$ SUFFICES ASSUME $Inv,$

$[Next]_{vars}$

PROVE Inv'

OBVIOUS

$\langle 2 \rangle 1. \text{CASE } a$

$\langle 3 \rangle 1. \text{CASE } low \leq high \wedge result = 0$

$\langle 4 \rangle$ DEFINE $mid \triangleq (low + high) \div 2$
 $mval \triangleq seq[mid]$

$\langle 4 \rangle (low \leq mid) \wedge (mid \leq high) \wedge (mid \in 1 \dots \text{Len}(seq))$

BY $\langle 3 \rangle 1, Z3$ DEF $Inv, TypeOK$

$\langle 4 \rangle 1. TypeOK'$

$\langle 5 \rangle 1. seq' \in SortedSeqs$

BY $\langle 2 \rangle 1$ DEF $a, Inv, TypeOK$

$\langle 5 \rangle 2. val' \in Values$

BY $\langle 2 \rangle 1$ DEF $a, Inv, TypeOK$

$\langle 5 \rangle 3. (low \in 1 \dots (\text{Len}(seq) + 1))'$

$\langle 6 \rangle 1. \text{CASE } seq[mid] = val$

BY $\langle 6 \rangle 1, \langle 2 \rangle 1, \langle 3 \rangle 1, Z3$ DEF $Inv, TypeOK, a$

$\langle 6 \rangle 2. \text{CASE } seq[mid] \neq val$

BY $\langle 6 \rangle 2, \langle 2 \rangle 1, \langle 3 \rangle 1, Z3$ DEF $Inv, TypeOK, a$

$\langle 6 \rangle 3. \text{QED}$

BY $\langle 6 \rangle 1, \langle 6 \rangle 2$

$\langle 5 \rangle 4. (high \in 0 \dots \text{Len}(seq))'$

$\langle 6 \rangle 1. \text{CASE } seq[mid] = val$

BY $\langle 6 \rangle 1, \langle 2 \rangle 1, \langle 3 \rangle 1, Z3$ DEF $Inv, TypeOK, a$

$\langle 6 \rangle 2. \text{CASE } seq[mid] \neq val$

BY $\langle 6 \rangle 2, \langle 2 \rangle 1, \langle 3 \rangle 1, Z3$ DEF $Inv, TypeOK, a$

$\langle 6 \rangle 3. \text{QED}$

BY $\langle 6 \rangle 1, \langle 6 \rangle 2$

$\langle 5 \rangle 5. (result \in 0 \dots \text{Len}(seq))'$

$\langle 6 \rangle 1. \text{CASE } seq[mid] = val$

BY $\langle 6 \rangle 1, \langle 2 \rangle 1, \langle 3 \rangle 1, Z3$ DEF $Inv, TypeOK, a$

$\langle 6 \rangle 2. \text{CASE } seq[mid] \neq val$

BY $\langle 6 \rangle 2, \langle 2 \rangle 1, \langle 3 \rangle 1, Z3$ DEF $Inv, TypeOK, a$

$\langle 6 \rangle 3.$ QED
 BY $\langle 6 \rangle 1, \langle 6 \rangle 2$
 $\langle 5 \rangle 6.$ $(pc \in \{ \text{"a"}, \text{"Done"} \})'$
 BY $\langle 2 \rangle 1, \langle 3 \rangle 1$ DEF $Inv, TypeOK, a$
 $\langle 5 \rangle 7.$ QED
 BY $\langle 5 \rangle 1, \langle 5 \rangle 2, \langle 5 \rangle 3, \langle 5 \rangle 4, \langle 5 \rangle 5, \langle 5 \rangle 6$ DEF $TypeOK$
 $\langle 4 \rangle 2.$ $((result \neq 0) \Rightarrow (Len(seq) > 0) \wedge (seq[result] = val))'$
 $\langle 5 \rangle 1.$ CASE $seq[mid] = val$
 BY $\langle 5 \rangle 1, \langle 2 \rangle 1, \langle 3 \rangle 1$ DEF $Inv, TypeOK, a$
 $\langle 5 \rangle 2.$ CASE $seq[mid] \neq val$
 BY $\langle 5 \rangle 2, \langle 2 \rangle 1, \langle 3 \rangle 1$ DEF $Inv, TypeOK, a$
 $\langle 5 \rangle 3.$ QED
 BY $\langle 5 \rangle 1, \langle 5 \rangle 2$
 $\langle 4 \rangle 3.$ $((pc = \text{"a"}) \Rightarrow$
 IF $\exists i \in 1 \dots Len(seq) : seq[i] = val$
 THEN $\exists i \in low \dots high : seq[i] = val$
 ELSE $result = 0$)'
 $\langle 5 \rangle 1.$ CASE $seq[mid] = val$
 BY $\langle 5 \rangle 1, \langle 2 \rangle 1, \langle 3 \rangle 1$ DEF $Inv, TypeOK, a$
 $\langle 5 \rangle 2.$ CASE $seq[mid] \neq val$
 $\langle 6 \rangle 1.$ $\wedge (low \leq mid) \wedge (mid \leq high) \wedge (mid \in 1 \dots Len(seq))$
 $\wedge Len(seq) > 0 \wedge Len(seq) \in Nat$
 $\wedge low \in 1 \dots Len(seq)$
 $\wedge high \in 1 \dots Len(seq)$
 BY $ValAssump$ DEF $Inv, TypeOK$
 $\langle 6 \rangle 2.$ CASE $\exists i \in 1 \dots Len(seq) : seq[i] = val$
 $\langle 7 \rangle 1.$ PICK $i \in low \dots high : seq[i] = val$
 BY $\langle 6 \rangle 2, \langle 2 \rangle 1$ DEF a, Inv
 $\langle 7 \rangle 2.$ $\wedge (low \leq mid) \wedge (mid \leq high) \wedge (mid \in 1 \dots Len(seq))$
 $\wedge Len(seq) > 0 \wedge Len(seq) \in Nat$
 $\wedge low \in 1 \dots Len(seq)$
 $\wedge high \in 1 \dots Len(seq)$
 $\wedge seq[i] = val$
 BY $ValAssump, \langle 6 \rangle 2, \langle 7 \rangle 1$ DEF $Inv, TypeOK$
 $\langle 7 \rangle 3.$ $\forall j \in 1 \dots Len(seq) : seq[j] \in Int$
 $\langle 8 \rangle 1.$ $seq \in Seq(Values)$
 BY DEF $Inv, TypeOK, SortedSeqs$
 $\langle 8 \rangle 2.$ $seq \in Seq(Int)$
 BY $\langle 8 \rangle 1, ValAssump$
 $\langle 8 \rangle 3.$ QED
 BY $\langle 8 \rangle 2$ DEF $Inv, TypeOK, SortedSeqs$
 $\langle 7 \rangle 4.$ $\forall j, k \in 1 \dots Len(seq) : j < k \Rightarrow seq[j] \leq seq[k]$
 BY DEF $Inv, TypeOK, SortedSeqs$
 $\langle 7 \rangle 5.$ CASE $val < seq[mid]$
 $\langle 8 \rangle 1.$ $seq[i] < seq[mid]$

BY $\langle 7 \rangle 2, \langle 7 \rangle 5$, $\langle 8 \rangle 5$
 $\langle 8 \rangle 2. i < mid$
 BY $ValAssump, \langle 7 \rangle 2, \langle 8 \rangle 1, \langle 7 \rangle 4, \langle 7 \rangle 3, Z3$
 $\langle 8 \rangle 3. i \in low \dots mid - 1$
 BY ONLY $\langle 7 \rangle 2, \langle 8 \rangle 1, \langle 8 \rangle 2, Z3$
 $\langle 8 \rangle 4. \wedge (pc' = \text{"a"}) \wedge (low' = low) \wedge (high' = mid - 1)$
 $\wedge \exists j \in 1 \dots Len(seq) : seq[j] = val$
 BY $\langle 2 \rangle 1, \langle 3 \rangle 1, \langle 5 \rangle 2, \langle 6 \rangle 2, \langle 7 \rangle 5$ DEF a, mid
 $\langle 8 \rangle 5. QED$
 BY ONLY $\langle 7 \rangle 2, \langle 8 \rangle 4, \langle 8 \rangle 3$, $\langle 8 \rangle 5$
 $\langle 7 \rangle 6. CASE \neg(val < seq[mid])$
 $\langle 8 \rangle$ HIDE DEF mid
 $\langle 8 \rangle 1. seq[mid] < seq[i]$
 BY $ValAssump, \langle 7 \rangle 2, \langle 7 \rangle 6, \langle 5 \rangle 2, \langle 7 \rangle 3, Z3$
 $\langle 8 \rangle 2. mid < i$
 BY $ValAssump, \langle 7 \rangle 2, \langle 8 \rangle 1$, $\langle 8 \rangle a, \langle 9 \rangle 1, \langle 7 \rangle 3, \langle 7 \rangle 4, Z3$
 $\langle 8 \rangle 3. i \in mid + 1 \dots high$
 BY $\langle 7 \rangle 2, \langle 8 \rangle 1, \langle 8 \rangle 2, Z3$
 $\langle 8 \rangle 4. \wedge (pc' = \text{"a"}) \wedge (low' = mid + 1) \wedge (high' = high)$
 $\wedge \exists j \in 1 \dots Len(seq) : seq[j] = val$
 BY $\langle 2 \rangle 1, \langle 3 \rangle 1, \langle 5 \rangle 2, \langle 6 \rangle 2, \langle 7 \rangle 6$ DEF a, mid
 $\langle 8 \rangle 5. QED$
 BY ONLY $\langle 7 \rangle 2, \langle 8 \rangle 4, \langle 8 \rangle 3$, $\langle 8 \rangle 5$
 $\langle 7 \rangle 7. QED$
 BY $\langle 7 \rangle 5, \langle 7 \rangle 6$
 $\langle 6 \rangle 3. CASE \neg \exists i \in 1 \dots Len(seq) : seq[i] = val$
 BY $\langle 6 \rangle 3, \langle 5 \rangle 2, \langle 2 \rangle 1, \langle 3 \rangle 1$ DEF $Inv, TypeOK, a$
 $\langle 6 \rangle 4. QED$
 BY $\langle 6 \rangle 2, \langle 6 \rangle 3$
 $\langle 5 \rangle 3. QED$
 BY $\langle 5 \rangle 1, \langle 5 \rangle 2$
 $\langle 4 \rangle 4. ((pc = \text{"Done"}) \Rightarrow (result \neq 0) \vee (\forall i \in 1 \dots Len(seq) : seq[i] \neq val))'$
 BY $\langle 3 \rangle 1, \langle 2 \rangle 1$ DEF $Inv, TypeOK, a$
 $\langle 4 \rangle 5. QED$
 BY $\langle 4 \rangle 1, \langle 4 \rangle 2, \langle 4 \rangle 3, \langle 4 \rangle 4$ DEF Inv
 $\langle 3 \rangle 2. CASE \neg(low \leq high \wedge result = 0)$
 BY $\langle 3 \rangle 2, \langle 2 \rangle 1$ DEF $Inv, TypeOK, a$
 $\langle 3 \rangle 3. QED$
 BY $\langle 3 \rangle 1, \langle 3 \rangle 2$
 $\langle 2 \rangle 2. CASE UNCHANGED vars$
 BY $\langle 2 \rangle 2$ DEF $Inv, TypeOK, vars$
 $\langle 2 \rangle 3. QED$
 BY $\langle 2 \rangle 1, \langle 2 \rangle 2$ DEF $Next$
 $\langle 1 \rangle 3. Inv \Rightarrow resultCorrect$
 BY DEF $resultCorrect, Inv, TypeOK$

$\langle 1 \rangle 4$. QED
BY $\langle 1 \rangle 1$, $\langle 1 \rangle 2$, $\langle 1 \rangle 3$, *PTL* DEF *Spec*

* Modification History
* Last modified *Fri* May 03 16:28:58 *PDT* 2019 by *lamport*
* Created *Wed* Apr 17 15:15:12 *PDT* 2019 by *lamport*