

1. Events Endpoints

Method	Endpoint	Description
GET	/events	Get all race events
GET	/events/{eventId}	Get event by ID
POST	/events	Create a new event (organiser)
PUT	/events/{eventId}	Update event details (organiser)
DELETE	/events/{eventId}	Delete event (organiser)

Example: GET /events

Response (200):

```
[
  {
    "eventId": 1,
    "eventName": "City Marathon",
    "eventDate": "2025-10-25",
    "location": "Durban",
    "organiserId": 1
  }
]
```

Example: POST /events

Request Body:

```
{
  "eventName": "City Marathon",
  "eventDate": "2025-10-25",
  "location": "Durban",
  "organiserId": 1
}
```

Response (201):

```
{
  "message": "Event created successfully",
  "eventId": 1
}
```

2. Categories Endpoints

Method	Endpoint	Description
GET	/categories	Get all categories
GET	/categories/{categoryId}	Get category by ID
POST	/categories	Create a new category
PUT	/categories/{categoryId}	Update category details
DELETE	/categories/{categoryId}	Delete category

Example: GET /categories

Response (200):

```
[
  {
    "categoryId": 1,
    "categoryName": "5km",
    "distance": 5,
    "fee": 150.00
  }
]
```

3. Participants Endpoints

Method	Endpoint	Description
GET	/participants	Get all participants
GET	/participants/{participantId}	Get participant by ID
POST	/participants	Register new participant
PUT	/participants/{participantId}	Update participant details
DELETE	/participants/{participantId}	Delete participant

Example: GET /participants/{participantId}

Response (200):

```
{
  "participantId": 10,
  "fullName": "Thabo Mokoena",
  "email": "thabo@example.com",
  "phone": "0712345678",
  "roleId": 2
}
```

4. Enrolments Endpoints

Method	Endpoint	Description
GET	/enrolments	Get all enrolments
GET	/enrolments/{enrolmentId}	Get enrolment by ID
POST	/enrolments	Create new enrolment
PUT	/enrolments/{enrolmentId}	Update enrolment (e.g. payment)
DELETE	/enrolments/{enrolmentId}	Cancel enrolment

Example: POST /enrolments

Request Body:

```
{
  "participantId": 10,
  "eventId": 3,
  "categoryId": 1,
  "paymentStatus": "Pending"
}
```

Response (201):

```
{
  "message": "Enrolment created successfully",
  "enrolmentId": 25
}
```

5. Results Endpoints

Method	Endpoint	Description
GET	/results	Get all results
GET	/results/{resultId}	Get result by ID
POST	/results	Add new result (organiser)
PUT	/results/{resultId}	Update result (organiser)
DELETE	/results/{resultId}	Delete result (organiser)

Example: GET /results?eventId=3

Response (200):

```
[
  {
    "resultId": 15,
    "participantId": 10,
    "eventId": 3,
    "finishTime": "00:22:45",
    "rank": 1
  }
]
```

Authentication & General

Authentication

Headers:

Authorization: Bearer <token>

(for protected endpoints – organiser only)

Common Response Codes

Code	Description
200	Success
201	Created
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
500	Internal Server Error

Notes

- All endpoints return JSON.
- Date format: YYYY-MM-DD
- Times are in 24-hour format (HH:mm:ss).
- Role-based access control (Organiser / Participant).