```
class Solution {
    public int findContentChildren(int[] g, int[] s)
        PriorityQueue<Integer> pq1 = new PriorityQueue<>();//MIN HEAP
        PriorityQueue<Integer> pq2 = new PriorityQueue<>();//MIN HEAP
        int n=g.length;
        for(int i=0;i<n;i++)</pre>
        {
            pq1.add(g[i]);
        int m=s.length;
        for(int i=0;i<m;i++)</pre>
            pq2.add(s[i]);
        }int cnt=0;
        while(pq2.size()>0&&pq1.size()>0)
            int a=pq1.peek();
            int b=pq2.peek();
            if(a<=b)</pre>
            {
                 cnt++;
                 pq1.poll();
                 pq2.poll();
            }
            else
            {
                 while(pq2.size()>0&&pq1.peek()>pq2.peek())
                 {
                     pq2.poll();
                 }
            }
        return cnt;
    }
}
```

Fractional Knapsack Problem

```
19 October 2024 12:33
```

```
class Solution {
  // Function to get the maximum total value in the knapsack.
  class pair{
    int a;
    int b;
    pair(int a,int b)
      this.a=a;
      this.b=b;
  }
  double fractionalKnapsack(List<Integer> values, List<Integer> weight, int w)
  {
    int n=values.size();
    if(n <= 0)
      return 0;
    pair[]arr=new pair[n];
    for(int i=0;i<n;i++)
      arr[i]=(new pair(values.get(i), weight.get(i)));
    //Sort the pair of array
    Arrays.sort(arr,new Comparator<pair>(){ ----> very imp
      @Override
      public int compare(pair p1,pair p2)
         double r1=(double)p1.a/p1.b;
         double r2=(double)p2.a/p2.b;
        return Double.compare(r2,r1);
    });
    // for(int i=0;i<n;i++)
    //{
    // System.out.print(arr[i].a);
         System.out.println(arr[i].b);
    //}
    double ans=0;
    int k=n-1;
    //int w
```

```
for(int i=0;i<n;i++)
{
    if(arr[i].b<=w)
    {
        ans+=arr[i].a;
        w=w-arr[i].b;
        //System.out.println(w);
    }
    else
    {
        ans+=arr[i].a*((double)w/arr[i].b);
        //System.out.println(w);
        break;
    }
}
return ans;</pre>
```

Greedy algorithm to find minimum number of coins***

19 October 2024 12:36

#MY CODE

```
class Solution {
  public int find(int coins[],int M,int sum,int[][]dp)
    if(sum==0)
      return 0;
    if(M==0)
      return 0;
    if(dp[M][sum]!=-1)
      return dp[M][sum];
    if(coins[M-1]<=sum)
      return dp[M][sum]=Math.min(1+find(coins,M,sum-coins[M-1],dp),find(coins,M-1,sum,dp));
    }
    else
      return dp[M][sum]=find(coins,M-1,sum,dp);
    }
  }
  public int minCoins(int coins[], int M, int sum)
    int n=coins.length;
    //Base condition
    if(M==0) | sum==0)
      return 0;
    }
    //DP initialization
    int[][]dp=new int[M+1][sum+1];
    for(int i=0;i<=M;i++)
      for(int j=0;j<=sum;j++)</pre>
         dp[i][j]=-1;
    }
    int a=find(coins,M,sum,dp);
```

```
//return (a==Integer.MAX_VALUE-1)?-1:a;
    return dp[M-1][sum-1];
 }
#CORRECT CODE
class Solution {
  // Helper function to find the minimum coins recursively
  public int find(int coins[], int M, int sum, int[][] dp) {
    // Base case when sum is 0, no coins are needed
    if (sum == 0) {
      return 0;
    // If no coins are left but the sum is not zero, return a large value
    if (M == 0) {
      return Integer.MAX VALUE - 1; // To prevent overflow in further calculations
    }
    // Check if the subproblem is already solved
    if (dp[M][sum] != -1) {
      return dp[M][sum];
    }
    // If the current coin can be included
    if (coins[M - 1] \le sum) \{
      // Either include the coin or exclude it, take the minimum of both
      dp[M][sum] = Math.min(
         1 + find(coins, M, sum - coins[M - 1], dp), // Include the current coin
         find(coins, M - 1, sum, dp)
                                              // Exclude the current coin
      );
    } else {
      // Exclude the coin if it can't be included
      dp[M][sum] = find(coins, M - 1, sum, dp);
    }
    return dp[M][sum];
  }
  // Main function to find minimum coins
  public int minCoins(int coins[], int M, int sum) {
    // Initialize a DP table to store intermediate results
    int[][] dp = new int[M + 1][sum + 1];
    for (int i = 0; i \le M; i++) {
      for (int j = 0; j \le sum; j++) {
         dp[i][j] = -1;
    }
    // Call the helper function to solve the problem
    int result = find(coins, M, sum, dp);
    // If result is greater than sum, return -1 (no solution)
    return (result >= Integer.MAX_VALUE - 1) ? -1 : result;
```

}

Lemonade Change

19 October 2024 12:36

#YOU ARE DOING GREAT BROTHER

```
class Solution {
    public boolean lemonadeChange(int[] bills)
        int a=0;
        int b=0;
        int c=0;
        for(int i=0;i<bills.length;i++)</pre>
            if(bills[i]==5)
                 a++;
            else if(bills[i]==10)
                 if(a>0)
                 {
                     a--;
                     b++;
                 }
                 else
                 {
                     return false;
                 }
            else
            {
                 if(b>0&&a>0)
                 {
                     b--;
                     a--;
                 }
                 else if(b==0&&a>=3)
                 {
                     a=a-3;
                 }
                 else
                 {
                     return false;
                 }
            }
        return true;
    }
}
```

Valid Paranthesis Checker

19 October 2024 12:36

N meetings in one room

19 October 2024

Jump Game

Jump Game 2

19 October 2024

12.37

Minimum number of platforms required for a railway

```
import java.util.Arrays;
class Solution {
  // Function to find the minimum number of platforms required
  static int findPlatform(int start[], int end[]) {
    int n = start.length;
    if (n == 0) {
      return 0;
    }
    // Sort the start and end times separately
    Arrays.sort(start);
    Arrays.sort(end);
    int platformsNeeded = 1; // Tracks platforms required at any time
    int maxPlatforms = 1; // Tracks the maximum number of platforms needed
    int i = 1; // Pointer for arrival times (start[])
    int j = 0; // Pointer for departure times (end[])
    while (i < n \&\& j < n) \{
      // If the next train arrives before the previous one departs, we need an additional platform
      if (start[i] <= end[j]) {
         platformsNeeded++;
         i++;
      // If the next train departs before the next one arrives, we free a platform
         platformsNeeded--;
        j++;
      // Update the maximum number of platforms needed at any point in time
      maxPlatforms = Math.max(maxPlatforms, platformsNeeded);
    }
    return maxPlatforms;
  }
  public static void main(String[] args) {
    // Example test case
    int start[] = {900, 940, 950, 1100, 1500, 1800};
    int end[] = {910, 1200, 1120, 1130, 1900, 2000};
    System.out.println("Minimum platforms required: " + findPlatform(start, end));
}
```

Job sequencing Problem

19 October 2024

Candy

Program for Shortest Job First (or SJF) CPU Scheduling

19 October 2024

Program for Least Recently Used (LRU) Page Replacement Algorithm

Insert Interval

19 October 2024

12.38

Merge Intervals

19 October 2024

12.38

Non-overlapping Intervals

19 October 2024