

# Triangles

1.0.1

Generated by Doxygen 1.8.17



<b>1 Namespace Index</b>	<b>1</b>
1.1 Namespace List	1
<b>2 Class Index</b>	<b>3</b>
2.1 Class List	3
<b>3 File Index</b>	<b>5</b>
3.1 File List	5
<b>4 Namespace Documentation</b>	<b>7</b>
4.1 geom Namespace Reference	7
4.1.1 Detailed Description	9
4.1.2 Typedef Documentation	10
4.1.2.1 Vec2D	10
4.1.2.2 Vec2F	10
4.1.2.3 Vec3D	10
4.1.2.4 Vec3F	10
4.1.3 Enumeration Type Documentation	10
4.1.3.1 Axis	10
4.1.4 Function Documentation	11
4.1.4.1 distance()	11
4.1.4.2 isIntersect()	11
4.1.4.3 intersect() [1/2]	12
4.1.4.4 intersect() [2/2]	13
4.1.4.5 operator<<() [1/6]	14
4.1.4.6 isEqualThreshold()	14
4.1.4.7 isZeroThreshold()	15
4.1.4.8 operator<<() [2/6]	15
4.1.4.9 operator<<() [3/6]	15
4.1.4.10 operator<<() [4/6]	16
4.1.4.11 operator>>() [1/2]	16
4.1.4.12 operator+() [1/2]	17
4.1.4.13 operator-() [1/2]	17
4.1.4.14 operator*() [1/4]	18
4.1.4.15 operator*() [2/4]	18
4.1.4.16 operator/() [1/2]	19
4.1.4.17 dot() [1/2]	19
4.1.4.18 operator<<() [5/6]	20
4.1.4.19 operator+() [2/2]	21
4.1.4.20 operator-() [2/2]	21
4.1.4.21 operator*() [3/4]	22
4.1.4.22 operator*() [4/4]	22
4.1.4.23 operator/() [2/2]	23

4.1.4.24 dot() [2/2]	23
4.1.4.25 cross()	24
4.1.4.26 triple()	24
4.1.4.27 operator<<() [6/6]	25
4.1.4.28 operator>>() [2/2]	26
4.1.5 Variable Documentation	26
4.1.5.1 Number	26
4.2 geom::detail Namespace Reference	27
4.2.1 Typedef Documentation	27
4.2.1.1 Segment2D	28
4.2.1.2 Trian2	28
4.2.1.3 Segment3D	28
4.2.2 Function Documentation	28
4.2.2.1 isIntersect2D()	28
4.2.2.2 isIntersectMollerHaines()	29
4.2.2.3 helperMollerHaines()	29
4.2.2.4 isIntersectBothInvalid()	29
4.2.2.5 isIntersectValidInvalid()	30
4.2.2.6 isIntersectPointTriangle()	30
4.2.2.7 isIntersectPointSegment()	30
4.2.2.8 isIntersectSegmentSegment()	30
4.2.2.9 isPoint()	31
4.2.2.10 isOverlap()	31
4.2.2.11 isAllPosNeg() [1/2]	31
4.2.2.12 isAllPosNeg() [2/2]	31
4.2.2.13 isOnOneSide()	32
4.2.2.14 getTrian2()	32
4.2.2.15 isCounterClockwise()	32
4.2.2.16 computeInterval()	32
4.2.2.17 getSegment()	33
4.2.2.18 roguePos()	33
4.3 geom::kdtree Namespace Reference	33
4.3.1 Typedef Documentation	33
4.3.1.1 Index	33
<b>5 Class Documentation</b>	<b>35</b>
5.1 geom::BoundingBox< T > Struct Template Reference	35
5.1.1 Detailed Description	35
5.1.2 Member Function Documentation	36
5.1.2.1 belongsTo()	36
5.1.2.2 min() [1/3]	36
5.1.2.3 max() [1/3]	36

5.1.2.4 min() [2/3]	36
5.1.2.5 max() [2/3]	37
5.1.2.6 min() [3/3]	37
5.1.2.7 max() [3/3]	37
5.1.2.8 getMaxDim()	37
5.1.2.9 operator==(())	38
5.1.2.10 operator!=(())	38
5.1.3 Member Data Documentation	38
5.1.3.1 minX	38
5.1.3.2 maxX	38
5.1.3.3 minY	39
5.1.3.4 maxY	39
5.1.3.5 minZ	39
5.1.3.6 maxZ	39
5.2 geom::kdtree::Container< T > Class Template Reference	39
5.2.1 Detailed Description	40
5.2.2 Constructor & Destructor Documentation	40
5.2.2.1 Container()	40
5.2.3 Member Function Documentation	40
5.2.3.1 cbegin()	41
5.2.3.2 cend()	41
5.2.3.3 begin()	41
5.2.3.4 end()	41
5.2.3.5 indexBegin()	41
5.2.3.6 indexEnd()	42
5.2.3.7 separator()	42
5.2.3.8 sepAxis()	42
5.2.3.9 boundBox()	42
5.2.3.10 triangleByIndex()	42
5.2.3.11 left()	43
5.2.3.12 right()	43
5.2.3.13 isValid()	43
5.3 geom::kdtree::Container< T >::ConstIterator Class Reference	43
5.3.1 Detailed Description	44
5.3.2 Member Typedef Documentation	44
5.3.2.1 iterator_category	44
5.3.2.2 difference_type	44
5.3.2.3 value_type	44
5.3.2.4 reference	45
5.3.2.5 pointer	45
5.3.3 Constructor & Destructor Documentation	45
5.3.3.1 ConstIterator()	45

5.3.4 Member Function Documentation	45
5.3.4.1 getIndex()	45
5.3.4.2 operator++() [1/2]	46
5.3.4.3 operator++() [2/2]	46
5.3.4.4 operator*()	46
5.3.4.5 operator->()	46
5.3.4.6 operator==()	46
5.4 geom::kdtree::KdTree< T > Class Template Reference	47
5.4.1 Detailed Description	47
5.4.2 Constructor & Destructor Documentation	47
5.4.2.1 KdTree() [1/4]	48
5.4.2.2 KdTree() [2/4]	48
5.4.2.3 KdTree() [3/4]	48
5.4.2.4 KdTree() [4/4]	48
5.4.2.5 ~KdTree()	48
5.4.3 Member Function Documentation	48
5.4.3.1 operator=() [1/2]	49
5.4.3.2 operator=() [2/2]	49
5.4.3.3 cbegin()	49
5.4.3.4 cend()	49
5.4.3.5 begin()	49
5.4.3.6 end()	49
5.4.3.7 beginFrom()	50
5.4.3.8 insert()	50
5.4.3.9 clear()	50
5.4.3.10 setNodeCapacity()	50
5.4.3.11 empty()	50
5.4.3.12 size()	51
5.4.3.13 nodeCapacity()	51
5.4.3.14 triangleByIndex()	51
5.4.3.15 dumpRecursive()	51
5.4.3.16 isOnPosSide()	51
5.4.3.17 isOnNegSide()	52
5.4.3.18 isOnSide()	52
5.5 geom::kdtree::KdTree< T >::ConstIterator Class Reference	52
5.5.1 Detailed Description	53
5.5.2 Member Typedef Documentation	53
5.5.2.1 iterator_category	53
5.5.2.2 difference_type	53
5.5.2.3 value_type	53
5.5.2.4 reference	53
5.5.2.5 pointer	54

5.5.3 Constructor & Destructor Documentation	54
5.5.3.1 ConstIterator()	54
5.5.4 Member Function Documentation	54
5.5.4.1 operator++() [1/2]	54
5.5.4.2 operator++() [2/2]	54
5.5.4.3 operator*()	55
5.5.4.4 operator->()	55
5.5.4.5 operator==()	55
5.5.4.6 operator!=(=)	55
5.5.4.7 beginFrom()	55
5.6 geom::kdTree::KdTree< T >::ContainerPtr Struct Reference	56
5.6.1 Detailed Description	56
5.6.2 Member Function Documentation	56
5.6.2.1 operator->()	56
5.6.3 Member Data Documentation	56
5.6.3.1 cont	56
5.7 geom::kdTree::Node< T > Struct Template Reference	57
5.7.1 Detailed Description	57
5.7.2 Member Typedef Documentation	57
5.7.2.1 IndexIterator	57
5.7.2.2 IndexConstIterator	58
5.7.3 Member Function Documentation	58
5.7.3.1 dumpRecursive()	58
5.7.4 Member Data Documentation	58
5.7.4.1 separator	58
5.7.4.2 sepAxis	58
5.7.4.3 boundBox	58
5.7.4.4 indices	59
5.7.4.5 left	59
5.7.4.6 right	59
5.8 geom::Line< T > Class Template Reference	59
5.8.1 Detailed Description	60
5.8.2 Constructor & Destructor Documentation	61
5.8.2.1 Line()	61
5.8.3 Member Function Documentation	61
5.8.3.1 operator==()	61
5.8.3.2 operator!=(=)	62
5.8.3.3 org() [1/2]	62
5.8.3.4 dir() [1/2]	63
5.8.3.5 org() [2/2]	63
5.8.3.6 dir() [2/2]	63
5.8.3.7 getPoint()	63

5.8.3.8 belongs()	64
5.8.3.9 isEqual()	64
5.8.3.10 isPar()	65
5.8.3.11 isSkew()	65
5.8.3.12 getBy2Points()	66
5.9 geom::Plane< T > Class Template Reference	66
5.9.1 Detailed Description	67
5.9.2 Member Function Documentation	67
5.9.2.1 operator==( )	68
5.9.2.2 operator!=( )	68
5.9.2.3 dist()	69
5.9.2.4 norm() [1/2]	69
5.9.2.5 norm() [2/2]	69
5.9.2.6 belongs() [1/2]	69
5.9.2.7 belongs() [2/2]	70
5.9.2.8 isEqual()	70
5.9.2.9 isPar()	71
5.9.2.10 getBy3Points()	71
5.9.2.11 getParametric()	72
5.9.2.12 getNormalPoint()	72
5.9.2.13 getNormalDist()	73
5.10 geom::ThresComp< T > Class Template Reference	73
5.10.1 Detailed Description	74
5.10.2 Constructor & Destructor Documentation	74
5.10.2.1 ThresComp()	74
5.10.3 Member Function Documentation	74
5.10.3.1 setThreshold()	74
5.10.3.2 isZero()	74
5.11 geom::Triangle< T > Class Template Reference	75
5.11.1 Detailed Description	75
5.11.2 Member Typedef Documentation	76
5.11.2.1 Iterator	76
5.11.2.2 ConstIterator	76
5.11.3 Constructor & Destructor Documentation	76
5.11.3.1 Triangle() [1/2]	76
5.11.3.2 Triangle() [2/2]	76
5.11.4 Member Function Documentation	77
5.11.4.1 operator[]() [1/3]	77
5.11.4.2 operator[]() [2/3]	77
5.11.4.3 operator[]() [3/3]	78
5.11.4.4 begin() [1/2]	78
5.11.4.5 end() [1/2]	78



5.11.4.6 begin() [2/2]	79
5.11.4.7 end() [2/2]	79
5.11.4.8 getPlane()	79
5.11.4.9 isValid()	80
5.11.4.10 boundBox()	80
5.11.4.11 belongsTo()	80
5.12 geom::Vec2< T > Class Template Reference	81
5.12.1 Detailed Description	82
5.12.2 Constructor & Destructor Documentation	82
5.12.2.1 Vec2() [1/2]	82
5.12.2.2 Vec2() [2/2]	83
5.12.3 Member Function Documentation	83
5.12.3.1 operator==( )	83
5.12.3.2 operator!=( )	84
5.12.3.3 operator+=( )	84
5.12.3.4 operator-=( )	85
5.12.3.5 operator-( )	85
5.12.3.6 operator*=( ) [1/2]	85
5.12.3.7 operator/=( ) [1/2]	86
5.12.3.8 dot()	86
5.12.3.9 length2()	87
5.12.3.10 length()	87
5.12.3.11 getPerp()	88
5.12.3.12 normalized()	88
5.12.3.13 normalize()	88
5.12.3.14 operator[]() [1/3]	88
5.12.3.15 operator[]() [2/3]	89
5.12.3.16 operator[]() [3/3]	89
5.12.3.17 isPar()	90
5.12.3.18 isPerp()	90
5.12.3.19 isEqual()	91
5.12.3.20 operator*=( ) [2/2]	91
5.12.3.21 operator/=( ) [2/2]	92
5.12.4 Member Data Documentation	92
5.12.4.1 x	92
5.12.4.2 y	92
5.13 geom::Vec3< T > Class Template Reference	92
5.13.1 Detailed Description	94
5.13.2 Constructor & Destructor Documentation	94
5.13.2.1 Vec3() [1/2]	94
5.13.2.2 Vec3() [2/2]	94
5.13.3 Member Function Documentation	95

5.13.3.1 operator==( )	95
5.13.3.2 operator!=( )	95
5.13.3.3 operator+=( )	96
5.13.3.4 operator-=( )	96
5.13.3.5 operator-( )	97
5.13.3.6 operator*=( ) [1/2]	97
5.13.3.7 operator/=( ) [1/2]	98
5.13.3.8 dot( )	98
5.13.3.9 cross( )	99
5.13.3.10 length2( )	99
5.13.3.11 length( )	100
5.13.3.12 normalized( )	100
5.13.3.13 normalize( )	100
5.13.3.14 operator[]( ) [1/3]	100
5.13.3.15 operator[]( ) [2/3]	101
5.13.3.16 operator[]( ) [3/3]	101
5.13.3.17 isPar( )	102
5.13.3.18 isPerp( )	102
5.13.3.19 isEqual( )	103
5.13.3.20 operator*=( ) [2/2]	103
5.13.3.21 operator/=( ) [2/2]	104
5.13.4 Member Data Documentation	104
5.13.4.1 x	104
5.13.4.2 y	104
5.13.4.3 z	104
<b>6 File Documentation</b>	<b>105</b>
6.1 include/distance/distance.hh File Reference	105
6.2 distance.hh	106
6.3 include/intersection/detail.hh File Reference	107
6.4 detail.hh	109
6.5 include/intersection/intersection.hh File Reference	114
6.6 intersection.hh	115
6.7 include/kdtree/container.hh File Reference	117
6.8 container.hh	119
6.9 include/kdtree/kdtree.hh File Reference	121
6.10 kdtree.hh	122
6.11 include/kdtree/node.hh File Reference	128
6.12 node.hh	129
6.13 include/primitives/boundbox.hh File Reference	130
6.13.1 Macro Definition Documentation	131
6.13.1.1 BBFILL	132

---

6.14	<a href="#">bbox.h</a>	132
6.15	<a href="#">include/primitives/common.h</a> File Reference	134
6.16	<a href="#">common.h</a>	135
6.17	<a href="#">include/primitives/line.h</a> File Reference	136
6.18	<a href="#">line.h</a>	138
6.19	<a href="#">include/primitives/plane.h</a> File Reference	140
6.20	<a href="#">plane.h</a>	142
6.21	<a href="#">include/primitives/primitives.h</a> File Reference	145
6.22	<a href="#">primitives.h</a>	146
6.23	<a href="#">include/primitives/triangle.h</a> File Reference	147
6.24	<a href="#">triangle.h</a>	148
6.25	<a href="#">include/primitives/vec2.h</a> File Reference	151
6.25.1	Detailed Description	153
6.26	<a href="#">vec2.h</a>	153
6.27	<a href="#">include/primitives/vec3.h</a> File Reference	159
6.27.1	Detailed Description	161
6.28	<a href="#">vec3.h</a>	161



# Chapter 1

## Namespace Index

### 1.1 Namespace List

Here is a list of all namespaces with brief descriptions:

<a href="#">geom</a>	<a href="#">Line.hh</a> <a href="#">Line</a> class implementation . . . . .	<a href="#">7</a>
<a href="#">geom::detail</a>	. . . . .	<a href="#">27</a>
<a href="#">geom::kdtree</a>	. . . . .	<a href="#">33</a>



## Chapter 2

# Class Index

### 2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">geom::BoundingBox&lt; T &gt;</a>	35
<a href="#">geom::kdtree::Container&lt; T &gt;</a>	39
<a href="#">geom::kdtree::Container&lt; T &gt;::ConstIterator</a>	43
<a href="#">geom::kdtree::KdTree&lt; T &gt;</a>	47
<a href="#">geom::kdtree::KdTree&lt; T &gt;::ConstIterator</a>	52
<a href="#">geom::kdtree::KdTree&lt; T &gt;::ContainerPtr</a>	56
<a href="#">geom::kdtree::Node&lt; T &gt;</a>	57
<a href="#">geom::Line&lt; T &gt;</a>	
Line class implementation	59
<a href="#">geom::Plane&lt; T &gt;</a>	
Plane class realization	66
<a href="#">geom::ThresComp&lt; T &gt;</a>	73
<a href="#">geom::Triangle&lt; T &gt;</a>	
Triangle class implementation	75
<a href="#">geom::Vec2&lt; T &gt;</a>	
Vec2 class realization	81
<a href="#">geom::Vec3&lt; T &gt;</a>	
Vec3 class realization	92





## Chapter 3

# File Index

### 3.1 File List

Here is a list of all files with brief descriptions:

include/distance/ <a href="#">distance.hh</a>	105
include/intersection/ <a href="#">detail.hh</a>	107
include/intersection/ <a href="#">intersection.hh</a>	114
include/kdtree/ <a href="#">container.hh</a>	117
include/kdtree/ <a href="#">kdtree.hh</a>	121
include/kdtree/ <a href="#">node.hh</a>	128
include/primitives/ <a href="#">boundingbox.hh</a>	130
include/primitives/ <a href="#">common.hh</a>	134
include/primitives/ <a href="#">line.hh</a>	136
include/primitives/ <a href="#">plane.hh</a>	140
include/primitives/ <a href="#">primitives.hh</a>	145
include/primitives/ <a href="#">triangle.hh</a>	147
include/primitives/ <a href="#">vec2.hh</a>	151
include/primitives/ <a href="#">vec3.hh</a>	159



## Chapter 4

# Namespace Documentation

### 4.1 geom Namespace Reference

[line.hh](#) [Line](#) class implementation

#### Namespaces

- [detail](#)
- [kdtree](#)

#### Classes

- struct [BoundingBox](#)
- class [Line](#)  
*[Line](#) class implementation.*
- class [Plane](#)  
*[Plane](#) class realization.*
- class [ThresComp](#)
- class [Triangle](#)  
*[Triangle](#) class implementation.*
- class [Vec2](#)  
*[Vec2](#) class realization.*
- class [Vec3](#)  
*[Vec3](#) class realization.*

#### Typedefs

- using [Vec2D](#) = [Vec2](#)< double >
- using [Vec2F](#) = [Vec2](#)< float >
- using [Vec3D](#) = [Vec3](#)< double >
- using [Vec3F](#) = [Vec3](#)< float >

## Enumerations

- enum [Axis](#) : std::int8\_t { [Axis::X](#) = 0, [Axis::Y](#) = 1, [Axis::Z](#) = 2, [Axis::NONE](#) }

## Functions

- template<std::floating\_point T>  
T [distance](#) (const [Plane](#)< T > &pl, const [Vec3](#)< T > &pt)  
*Calculates signed distance between point and plane.*
- template<std::floating\_point T>  
bool [isIntersect](#) (const [Triangle](#)< T > &tr1, const [Triangle](#)< T > &tr2)  
*Checks intersection of 2 triangles.*
- template<std::floating\_point T>  
std::variant< std::monostate, [Line](#)< T >, [Plane](#)< T > > [intersect](#) (const [Plane](#)< T > &pl1, const [Plane](#)< T > &pl2)  
*Intersect 2 planes and return result of intersection.*
- template<std::floating\_point T>  
std::variant< std::monostate, [Vec3](#)< T >, [Line](#)< T > > [intersect](#) (const [Line](#)< T > &l1, const [Line](#)< T > &l2)  
*Intersect 2 lines and return result of intersection.*
- template<std::floating\_point T>  
std::ostream & [operator<<](#) (std::ostream &ost, const [BoundingBox](#)< T > &bb)
- template<Number T>  
bool [isEqualThreshold](#) (T num1, T num2)
- template<Number T>  
bool [isZeroThreshold](#) (T num)
- template<std::floating\_point T>  
std::ostream & [operator<<](#) (std::ostream &ost, const [Line](#)< T > &line)  
*Line print operator.*
- template<std::floating\_point T>  
std::ostream & [operator<<](#) (std::ostream &ost, const [Plane](#)< T > &pl)  
*Plane print operator.*
- template<std::floating\_point T>  
std::ostream & [operator<<](#) (std::ostream &ost, const [Triangle](#)< T > &tr)  
*Triangle print operator.*
- template<std::floating\_point T>  
std::istream & [operator>>](#) (std::istream &ist, [Triangle](#)< T > &tr)
- template<std::floating\_point T>  
[Vec2](#)< T > [operator+](#) (const [Vec2](#)< T > &lhs, const [Vec2](#)< T > &rhs)  
*Overloaded + operator.*
- template<std::floating\_point T>  
[Vec2](#)< T > [operator-](#) (const [Vec2](#)< T > &lhs, const [Vec2](#)< T > &rhs)  
*Overloaded - operator.*
- template<Number nT, std::floating\_point T>  
[Vec2](#)< T > [operator\\*](#) (const nT &val, const [Vec2](#)< T > &rhs)  
*Overloaded multiple by value operator.*
- template<Number nT, std::floating\_point T>  
[Vec2](#)< T > [operator\\*](#) (const [Vec2](#)< T > &lhs, const nT &val)  
*Overloaded multiple by value operator.*
- template<Number nT, std::floating\_point T>  
[Vec2](#)< T > [operator/](#) (const [Vec2](#)< T > &lhs, const nT &val)  
*Overloaded divide by value operator.*

- `template<std::floating_point T>`  
`T dot (const Vec2< T > &lhs, const Vec2< T > &rhs)`  
*Dot product function.*
- `template<std::floating_point T>`  
`std::ostream & operator<< (std::ostream &ost, const Vec2< T > &vec)`  
*Vec2 print operator.*
- `template<std::floating_point T>`  
`Vec3< T > operator+ (const Vec3< T > &lhs, const Vec3< T > &rhs)`  
*Overloaded + operator.*
- `template<std::floating_point T>`  
`Vec3< T > operator- (const Vec3< T > &lhs, const Vec3< T > &rhs)`  
*Overloaded - operator.*
- `template<Number nT, std::floating_point T>`  
`Vec3< T > operator* (const nT &val, const Vec3< T > &rhs)`  
*Overloaded multiple by value operator.*
- `template<Number nT, std::floating_point T>`  
`Vec3< T > operator* (const Vec3< T > &lhs, const nT &val)`  
*Overloaded multiple by value operator.*
- `template<Number nT, std::floating_point T>`  
`Vec3< T > operator/ (const Vec3< T > &lhs, const nT &val)`  
*Overloaded divide by value operator.*
- `template<std::floating_point T>`  
`T dot (const Vec3< T > &lhs, const Vec3< T > &rhs)`  
*Dot product function.*
- `template<std::floating_point T>`  
`Vec3< T > cross (const Vec3< T > &lhs, const Vec3< T > &rhs)`  
*Cross product function.*
- `template<std::floating_point T>`  
`T triple (const Vec3< T > &v1, const Vec3< T > &v2, const Vec3< T > &v3)`  
*Triple product function.*
- `template<std::floating_point T>`  
`std::ostream & operator<< (std::ostream &ost, const Vec3< T > &vec)`  
*Vec3 print operator.*
- `template<std::floating_point T>`  
`std::istream & operator>> (std::istream &ist, Vec3< T > &vec)`  
*Vec3 scan operator.*

## Variables

- `template<class T >`  
`concept Number = std::is_floating_point_v<T> || std::is_integral_v<T>`  
*Useful concept which represents floating point and integral types.*

### 4.1.1 Detailed Description

[line.hh](#) [Line](#) class implementation

[triangle.hh](#) [Triangle](#) class implementation

[Plane](#) class implementation.

## 4.1.2 Typedef Documentation

### 4.1.2.1 Vec2D

```
using geom::Vec2D = typedef Vec2<double>
```

Definition at line 328 of file [vec2.hh](#).

### 4.1.2.2 Vec2F

```
using geom::Vec2F = typedef Vec2<float>
```

Definition at line 329 of file [vec2.hh](#).

### 4.1.2.3 Vec3D

```
using geom::Vec3D = typedef Vec3<double>
```

Definition at line 374 of file [vec3.hh](#).

### 4.1.2.4 Vec3F

```
using geom::Vec3F = typedef Vec3<float>
```

Definition at line 375 of file [vec3.hh](#).

## 4.1.3 Enumeration Type Documentation

### 4.1.3.1 Axis

```
enum geom::Axis : std::int8_t [strong]
```

Enumerator

X	
Y	
Z	
NONE	

Definition at line 19 of file [common.hh](#).

## 4.1.4 Function Documentation

### 4.1.4.1 distance()

```
template<std::floating_point T>
T geom::distance (
    const Plane< T > & pl,
    const Vec3< T > & pt )
```

Calculates signed distance between point and plane.

#### Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

#### Parameters

<i>pl</i>	plane
<i>pt</i>	point

#### Returns

T signed distance between point and plane

Definition at line 26 of file [distance.hh](#).

References [geom::Plane< T >::dist\(\)](#), [dot\(\)](#), and [geom::Plane< T >::norm\(\)](#).

Referenced by [geom::detail::getSegment\(\)](#), [geom::detail::getTrian2\(\)](#), [geom::detail::isIntersectValidInvalid\(\)](#), and [geom::detail::roguePos\(\)](#).

### 4.1.4.2 isIntersect()

```
template<std::floating_point T>
bool geom::isIntersect (
    const Triangle< T > & tr1,
    const Triangle< T > & tr2 )
```

Checks intersection of 2 triangles.

#### Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

## Parameters

<i>tr1</i>	first triangle
<i>tr2</i>	second triangle

## Returns

true if triangles are intersect  
false if triangles are not intersect

Definition at line 156 of file [intersection.hh](#).

References [geom::Triangle< T >::getPlane\(\)](#), [geom::detail::isIntersect2D\(\)](#), [geom::detail::isIntersectBothInvalid\(\)](#), [geom::detail::isIntersectMollerHaines\(\)](#), [geom::detail::isIntersectValidInvalid\(\)](#), [geom::detail::isOnOneSide\(\)](#), and [geom::Triangle< T >::isValid\(\)](#).

## 4.1.4.3 intersect() [1/2]

```
template<std::floating_point T>
std::variant< std::monostate, Line< T >, Plane< T > > geom::intersect (
    const Plane< T > & pl1,
    const Plane< T > & pl2 )
```

Intersect 2 planes and return result of intersection.

Common intersection case (parallel planes case is trivial):

Let  $\vec{P}$  - point in space

$$pl_1 \text{ equation: } \vec{n}_1 \cdot \vec{P} = d_1$$

$$pl_2 \text{ equation: } \vec{n}_2 \cdot \vec{P} = d_2$$

$$\text{Intersection line direction: } \vec{dir} = \vec{n}_1 \times \vec{n}_2$$

Let origin of intersection line be a linear combination of  $\vec{n}_1$  and  $\vec{n}_2$ :

$$\vec{P} = a \cdot \vec{n}_1 + b \cdot \vec{n}_2$$

$\vec{P}$  must satisfy both  $pl_1$  and  $pl_2$  equations:

$$\vec{n}_1 \cdot \vec{P} = d_1 \Leftrightarrow \vec{n}_1 \cdot (a \cdot \vec{n}_1 + b \cdot \vec{n}_2) = d_1 \Leftrightarrow a + b \cdot \vec{n}_1 \cdot \vec{n}_2 = d_1$$

$$\vec{n}_2 \cdot \vec{P} = d_2 \Leftrightarrow \vec{n}_2 \cdot (a \cdot \vec{n}_1 + b \cdot \vec{n}_2) = d_2 \Leftrightarrow a \cdot \vec{n}_1 \cdot \vec{n}_2 + b = d_2$$

Let's find  $a$  and  $b$ :

$$a = \frac{d_2 \cdot \vec{n}_1 \cdot \vec{n}_2 - d_1}{(\vec{n}_1 \cdot \vec{n}_2)^2 - 1}$$

$$b = \frac{d_1 \cdot \vec{n}_1 \cdot \vec{n}_2 - d_2}{(\vec{n}_1 \cdot \vec{n}_2)^2 - 1}$$

Intersection line equation:

$$\vec{r}(t) = \vec{P} + t \cdot \vec{n}_1 \times \vec{n}_2 = (a \cdot \vec{n}_1 + b \cdot \vec{n}_2) + t \cdot \vec{n}_1 \times \vec{n}_2$$



## Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

## Parameters

in	<i>p/1</i>	first plane
in	<i>p/2</i>	second plane

## Returns

std::variant<std::monostate, Line<T>, Plane<T>>>

Definition at line 188 of file [intersection.hh](#).

References [cross\(\)](#), [geom::Plane< T >::dist\(\)](#), [dot\(\)](#), and [geom::Plane< T >::norm\(\)](#).

Referenced by [geom::detail::isIntersectMollerHaines\(\)](#), and [geom::detail::isIntersectSegmentSegment\(\)](#).

## 4.1.4.4 intersect() [2/2]

```
template<std::floating_point T>
std::variant< std::monostate, Vec3< T >, Line< T > > geom::intersect (
    const Line< T > & l1,
    const Line< T > & l2 )
```

Intersect 2 lines and return result of intersection.

Common intersection case (parallel & skew lines cases are trivial): Let  $\vec{P}$  - point in space, intersection point of two lines.

$$l_1 \text{ equation: } \vec{or\dot{g}}_1 + \vec{dir_1} \cdot t_1 = \vec{P}$$

$$l_2 \text{ equation: } \vec{or\dot{g}}_2 + \vec{dir_2} \cdot t_2 = \vec{P}$$

Let's equate left sides:

$$\vec{or\dot{g}}_1 + \vec{dir_1} \cdot t_1 = \vec{or\dot{g}}_2 + \vec{dir_2} \cdot t_2$$

Cross multiply both sides from right by  $\vec{dir_2}$ :

$$t_1 \cdot (\vec{dir_1} \times \vec{dir_2}) = (\vec{or\dot{g}}_2 - \vec{or\dot{g}}_1) \times \vec{dir_2}$$

Dot multiply both sides by  $\frac{\vec{dir_1} \times \vec{dir_2}}{|\vec{dir_1} \times \vec{dir_2}|^2}$ :

$$t_1 = \frac{((\vec{or\dot{g}}_2 - \vec{or\dot{g}}_1) \times \vec{dir_2}) \cdot (\vec{dir_1} \times \vec{dir_2})}{|\vec{dir_1} \times \vec{dir_2}|^2}$$

Thus we get intersection point parameter  $t_1$  on  $l_1$ , let's substitute it to  $l_1$  equation:

$$\vec{P} = \vec{or\dot{g}}_1 + \frac{((\vec{or\dot{g}}_2 - \vec{or\dot{g}}_1) \times \vec{dir_2}) \cdot (\vec{dir_1} \times \vec{dir_2})}{|\vec{dir_1} \times \vec{dir_2}|^2} \cdot \vec{dir_1}$$

## Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

## Parameters

in	<i>l1</i>	first line
in	<i>l2</i>	second line

## Returns

`std::variant<std::monostate, Vec3<T>, Line<T>>>`

Definition at line 215 of file [intersection.hh](#).

References [cross\(\)](#), [geom::Line< T >::dir\(\)](#), [dot\(\)](#), [geom::Line< T >::getPoint\(\)](#), [geom::Line< T >::isEqual\(\)](#), [geom::Line< T >::isPar\(\)](#), [geom::Line< T >::isSkew\(\)](#), and [geom::Line< T >::org\(\)](#).

## 4.1.4.5 operator&lt;&lt;() [1/6]

```
template<std::floating_point T>
std::ostream& geom::operator<< (
    std::ostream & ost,
    const BoundingBox< T > & bb )
```

Definition at line 127 of file [boundingbox.hh](#).

References [geom::BoundingBox< T >::maxX](#), [geom::BoundingBox< T >::maxY](#), [geom::BoundingBox< T >::maxZ](#), [geom::BoundingBox< T >::minX](#), [geom::BoundingBox< T >::minY](#), and [geom::BoundingBox< T >::minZ](#).

## 4.1.4.6 isEqualThreshold()

```
template<Number T>
bool geom::isEqualThreshold (
    T num1,
    T num2 )
```

Definition at line 71 of file [common.hh](#).

Referenced by [geom::Plane< T >::belongs\(\)](#), [geom::Vec2< T >::isEqual\(\)](#), [geom::Vec3< T >::isEqual\(\)](#), [geom::Vec2< T >::normalize\(\)](#), [geom::Vec3< T >::normalize\(\)](#), and [geom::BoundingBox< T >::operator==\(\)](#).

#### 4.1.4.7 isZeroThreshold()

```
template<Number T>
bool geom::isZeroThreshold (
    T num )
```

Definition at line 77 of file [common.hh](#).

References [geom::ThresComp< T >::isZero\(\)](#).

Referenced by [geom::detail::isAllPosNeg\(\)](#), [geom::detail::isIntersectValidInvalid\(\)](#), [geom::Vec2< T >::isPar\(\)](#), [geom::Vec2< T >::isPerp\(\)](#), [geom::Vec3< T >::isPerp\(\)](#), [geom::Line< T >::isSkew\(\)](#), [geom::Vec2< T >::normalize\(\)](#), and [geom::Vec3< T >::normalize\(\)](#).

#### 4.1.4.8 operator<<() [2/6]

```
template<std::floating_point T>
std::ostream& geom::operator<< (
    std::ostream & ost,
    const Line< T > & line )
```

[Line](#) print operator.

Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

Parameters

<i>in, out</i>	<i>ost</i>	output stream
<i>in</i>	<i>line</i>	<a href="#">Line</a> to print

Returns

std::ostream& modified ostream instance

Definition at line 151 of file [line.hh](#).

References [geom::Line< T >::dir\(\)](#), and [geom::Line< T >::org\(\)](#).

#### 4.1.4.9 operator<<() [3/6]

```
template<std::floating_point T>
std::ostream& geom::operator<< (
    std::ostream & ost,
    const Plane< T > & pl )
```

[Plane](#) print operator.

## Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

## Parameters

<i>in, out</i>	<i>ost</i>	output stream
<i>in</i>	<i>pl</i>	plane to print

## Returns

std::ostream& modified ostream instance

Definition at line 169 of file [plane.hh](#).

References [geom::Plane< T >::dist\(\)](#), and [geom::Plane< T >::norm\(\)](#).

## 4.1.4.10 operator&lt;&lt;() [4/6]

```
template<std::floating_point T>
std::ostream& geom::operator<< (
    std::ostream & ost,
    const Triangle< T > & tr )
```

[Triangle](#) print operator.

## Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

## Parameters

<i>in, out</i>	<i>ost</i>	output stream
<i>in</i>	<i>tr</i>	<a href="#">Triangle</a> to print

## Returns

std::ostream& modified ostream instance

Definition at line 141 of file [triangle.hh](#).

## 4.1.4.11 operator&gt;&gt;() [1/2]

```
template<std::floating_point T>
std::istream& geom::operator>> (
```

```
std::istream & ist,
Triangle< T > & tr )
```

Definition at line 153 of file [triangle.hh](#).

#### 4.1.4.12 operator+() [1/2]

```
template<std::floating_point T>
Vec2<T> geom::operator+ (
    const Vec2< T > & lhs,
    const Vec2< T > & rhs )
```

Overloaded + operator.

##### Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

##### Parameters

in	<i>lhs</i>	first vector
in	<i>rhs</i>	second vector

##### Returns

Vec2<T> sum of two vectors

Definition at line 225 of file [vec2.hh](#).

#### 4.1.4.13 operator-() [1/2]

```
template<std::floating_point T>
Vec2<T> geom::operator- (
    const Vec2< T > & lhs,
    const Vec2< T > & rhs )
```

Overloaded - operator.

##### Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

##### Parameters

in	<i>lhs</i>	first vector
in	<i>rhs</i>	second vector

**Returns**

`Vec2<T>` res of two vectors

Definition at line 241 of file [vec2.hh](#).

**4.1.4.14 `operator*()` [1/4]**

```
template<Number nT, std::floating_point T>
Vec2<T> geom::operator* (
    const nT & val,
    const Vec2< T > & rhs )
```

Overloaded multiple by value operator.

**Template Parameters**

<i>nT</i>	type of value to multiply by
<i>T</i>	vector template parameter

**Parameters**

in	<i>val</i>	value to multiply by
in	<i>rhs</i>	vector to multiply by value

**Returns**

`Vec2<T>` result vector

Definition at line 258 of file [vec2.hh](#).

**4.1.4.15 `operator*()` [2/4]**

```
template<Number nT, std::floating_point T>
Vec2<T> geom::operator* (
    const Vec2< T > & lhs,
    const nT & val )
```

Overloaded multiple by value operator.

**Template Parameters**

<i>nT</i>	type of value to multiply by
<i>T</i>	vector template parameter

## Parameters

in	<i>val</i>	value to multiply by
in	<i>lhs</i>	vector to multiply by value

## Returns

`Vec2<T>` result vector

Definition at line 275 of file [vec2.hh](#).

**4.1.4.16 operator/()** [1/2]

```
template<Number nT, std::floating_point T>
Vec2<T> geom::operator/ (
    const Vec2< T > & lhs,
    const nT & val )
```

Overloaded divide by value operator.

## Template Parameters

<i>nT</i>	type of value to divide by
<i>T</i>	vector template parameter

## Parameters

in	<i>val</i>	value to divide by
in	<i>lhs</i>	vector to divide by value

## Returns

`Vec2<T>` result vector

Definition at line 292 of file [vec2.hh](#).

**4.1.4.17 dot()** [1/2]

```
template<std::floating_point T>
T geom::dot (
    const Vec2< T > & lhs,
    const Vec2< T > & rhs )
```

Dot product function.

## Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

## Parameters

<i>in</i>	<i>lhs</i>	first vector
<i>in</i>	<i>rhs</i>	second vector

## Returns

T dot production

Definition at line 308 of file [vec2.hh](#).

References [geom::Vec2< T >::dot\(\)](#).

Referenced by [distance\(\)](#), [intersect\(\)](#), [geom::detail::isIntersectPointSegment\(\)](#), [geom::detail::isIntersectPointTriangle\(\)](#), [geom::detail::isIntersectSegmentSegment\(\)](#), [geom::Vec2< T >::isPerp\(\)](#), [geom::Vec3< T >::isPerp\(\)](#), [geom::Vec2< T >::length2\(\)](#), [geom::Vec3< T >::length2\(\)](#), and [triple\(\)](#).

4.1.4.18 **operator<<()** [5/6]

```
template<std::floating_point T>
std::ostream& geom::operator<< (
    std::ostream & ost,
    const Vec2< T > & vec )
```

[Vec2](#) print operator.

## Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

## Parameters

<i>in, out</i>	<i>ost</i>	output stream
<i>in</i>	<i>vec</i>	vector to print

## Returns

std::ostream& modified stream instance

Definition at line 322 of file [vec2.hh](#).

References [geom::Vec2< T >::x](#), and [geom::Vec2< T >::y](#).



**4.1.4.19 operator+()** [2/2]

```
template<std::floating_point T>
Vec3<T> geom::operator+ (
    const Vec3< T > & lhs,
    const Vec3< T > & rhs )
```

Overloaded + operator.

**Template Parameters**

<i>T</i>	vector template parameter
----------	---------------------------

**Parameters**

in	<i>lhs</i>	first vector
in	<i>rhs</i>	second vector

**Returns**

Vec3<T> sum of two vectors

Definition at line 227 of file [vec3.hh](#).

**4.1.4.20 operator-()** [2/2]

```
template<std::floating_point T>
Vec3<T> geom::operator- (
    const Vec3< T > & lhs,
    const Vec3< T > & rhs )
```

Overloaded - operator.

**Template Parameters**

<i>T</i>	vector template parameter
----------	---------------------------

**Parameters**

in	<i>lhs</i>	first vector
in	<i>rhs</i>	second vector

**Returns**

Vec3<T> res of two vectors

Definition at line 243 of file [vec3.hh](#).

**4.1.4.21 operator\*() [3/4]**

```
template<Number nT, std::floating_point T>
Vec3<T> geom::operator* (
    const nT & val,
    const Vec3< T > & rhs )
```

Overloaded multiple by value operator.

**Template Parameters**

<i>nT</i>	type of value to multiply by
<i>T</i>	vector template parameter

**Parameters**

in	<i>val</i>	value to multiply by
in	<i>rhs</i>	vector to multiply by value

**Returns**

Vec3<T> result vector

Definition at line 260 of file [vec3.hh](#).

**4.1.4.22 operator\*() [4/4]**

```
template<Number nT, std::floating_point T>
Vec3<T> geom::operator* (
    const Vec3< T > & lhs,
    const nT & val )
```

Overloaded multiple by value operator.

**Template Parameters**

<i>nT</i>	type of value to multiply by
<i>T</i>	vector template parameter

**Parameters**

in	<i>val</i>	value to multiply by
in	<i>lhs</i>	vector to multiply by value

**Returns**

Vec3<T> result vector

Definition at line 277 of file [vec3.hh](#).

#### 4.1.4.23 operator/() [2/2]

```
template<Number nT, std::floating_point T>
Vec3<T> geom::operator/ (
    const Vec3< T > & lhs,
    const nT & val )
```

Overloaded divide by value operator.

##### Template Parameters

<i>nT</i>	type of value to divide by
<i>T</i>	vector template parameter

##### Parameters

in	<i>val</i>	value to divide by
in	<i>lhs</i>	vector to divide by value

##### Returns

Vec3<T> result vector

Definition at line 294 of file [vec3.hh](#).

#### 4.1.4.24 dot() [2/2]

```
template<std::floating_point T>
T geom::dot (
    const Vec3< T > & lhs,
    const Vec3< T > & rhs )
```

Dot product function.

##### Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

##### Parameters

in	<i>lhs</i>	first vector
in	<i>rhs</i>	second vector

**Returns**

T dot production

Definition at line 310 of file [vec3.hh](#).

References [geom::Vec3< T >::dot\(\)](#).

**4.1.4.25 cross()**

```
template<std::floating_point T>
Vec3<T> geom::cross (
    const Vec3< T > & lhs,
    const Vec3< T > & rhs )
```

Cross product function.

**Template Parameters**

<i>T</i>	vector template parameter
----------	---------------------------

**Parameters**

in	<i>lhs</i>	first vector
in	<i>rhs</i>	second vector

**Returns**

T cross production

Definition at line 324 of file [vec3.hh](#).

References [geom::Vec3< T >::cross\(\)](#).

Referenced by [intersect\(\)](#), [geom::Vec3< T >::isPar\(\)](#), [geom::Triangle< T >::isValid\(\)](#), and [triple\(\)](#).

**4.1.4.26 triple()**

```
template<std::floating_point T>
T geom::triple (
    const Vec3< T > & v1,
    const Vec3< T > & v2,
    const Vec3< T > & v3 )
```

Triple product function.

## Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

## Parameters

<i>in</i>	<i>v1</i>	first vector
<i>in</i>	<i>v2</i>	second vector
<i>in</i>	<i>v3</i>	third vector

## Returns

T triple production

Definition at line 339 of file [vec3.hh](#).

References [cross\(\)](#), and [dot\(\)](#).

Referenced by [geom::Line< T >::isSkew\(\)](#).

## 4.1.4.27 operator&lt;&lt;() [6/6]

```
template<std::floating_point T>
std::ostream& geom::operator<< (
    std::ostream & ost,
    const Vec3< T > & vec )
```

[Vec3](#) print operator.

## Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

## Parameters

<i>in, out</i>	<i>ost</i>	output stream
<i>in</i>	<i>vec</i>	vector to print

## Returns

std::ostream& modified stream instance

Definition at line 353 of file [vec3.hh](#).

References [geom::Vec3< T >::x](#), [geom::Vec3< T >::y](#), and [geom::Vec3< T >::z](#).

#### 4.1.4.28 `operator>>()` [2/2]

```
template<std::floating_point T>
std::istream& geom::operator>> (
    std::istream & ist,
    Vec3< T > & vec )
```

Vec3 scan operator.

##### Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

##### Parameters

<i>in, out</i>	<i>ist</i>	input stram
<i>in, out</i>	<i>vec</i>	vector to scan

##### Returns

std::istream& modified stream instance

Definition at line 368 of file [vec3.hh](#).

References [geom::Vec3< T >::x](#), [geom::Vec3< T >::y](#), and [geom::Vec3< T >::z](#).

### 4.1.5 Variable Documentation

#### 4.1.5.1 Number

```
template<class T >
concept geom::Number = std::is_floating_point_v<T> || std::is_integral_v<T>
```

Useful concept which represents floating point and integral types.

@concept Number

##### Template Parameters

<i>T</i>	
----------	--

Definition at line 17 of file [common.hh](#).

## 4.2 geom::detail Namespace Reference

### Typedefs

- template<typename T >  
using [Segment2D](#) = std::pair< T, T >
- template<std::floating\_point T>  
using [Trian2](#) = std::array< [Vec2](#)< T >, 3 >
- template<std::floating\_point T>  
using [Segment3D](#) = std::pair< [Vec3](#)< T >, [Vec3](#)< T > >

### Functions

- template<std::floating\_point T>  
bool [isIntersect2D](#) (const [Triangle](#)< T > &tr1, const [Triangle](#)< T > &tr2)
- template<std::floating\_point T>  
bool [isIntersectMollerHaines](#) (const [Triangle](#)< T > &tr1, const [Triangle](#)< T > &tr2)
- template<std::floating\_point T>  
[Segment2D](#)< T > [helperMollerHaines](#) (const [Triangle](#)< T > &tr, const [Plane](#)< T > &pl, const [Line](#)< T > &l)
- template<std::floating\_point T>  
bool [isIntersectBothInvalid](#) (const [Triangle](#)< T > &tr1, const [Triangle](#)< T > &tr2)
- template<std::floating\_point T>  
bool [isIntersectValidInvalid](#) (const [Triangle](#)< T > &valid, const [Triangle](#)< T > &invalid)
- template<std::floating\_point T>  
bool [isIntersectPointTriangle](#) (const [Vec3](#)< T > &pt, const [Triangle](#)< T > &tr)
- template<std::floating\_point T>  
bool [isIntersectPointSegment](#) (const [Vec3](#)< T > &pt, const [Segment3D](#)< T > &segm)
- template<std::floating\_point T>  
bool [isIntersectSegmentSegment](#) (const [Segment3D](#)< T > &segm1, const [Segment3D](#)< T > &segm2)
- template<std::floating\_point T>  
bool [isPoint](#) (const [Triangle](#)< T > &tr)
- template<std::floating\_point T>  
bool [isOverlap](#) ([Segment2D](#)< T > &segm1, [Segment2D](#)< T > &segm2)
- template<std::forward\_iterator It>  
bool [isAllPosNeg](#) (It begin, It end)
- template<std::floating\_point T>  
bool [isAllPosNeg](#) (T num1, T num2)
- template<std::floating\_point T>  
bool [isOnOneSide](#) (const [Plane](#)< T > &pl, const [Triangle](#)< T > &tr)
- template<std::floating\_point T>  
[Trian2](#)< T > [getTrian2](#) (const [Plane](#)< T > &pl, const [Triangle](#)< T > &tr)
- template<std::floating\_point T>  
bool [isCounterClockwise](#) ([Trian2](#)< T > &tr)
- template<std::floating\_point T>  
[Segment2D](#)< T > [computeInterval](#) (const [Trian2](#)< T > &tr, const [Vec2](#)< T > &d)
- template<std::floating\_point T>  
[Segment3D](#)< T > [getSegment](#) (const [Triangle](#)< T > &tr)
- template<std::bidirectional\_iterator It>  
std::size\_t [roguePos](#) (It begin, It end)

#### 4.2.1 Typedef Documentation

#### 4.2.1.1 Segment2D

```
template<typename T >
using geom::detail::Segment2D = typedef std::pair<T, T>
```

Definition at line 15 of file [detail.hh](#).

#### 4.2.1.2 Trian2

```
template<std::floating_point T>
using geom::detail::Trian2 = typedef std::array<Vec2<T>, 3>
```

Definition at line 18 of file [detail.hh](#).

#### 4.2.1.3 Segment3D

```
template<std::floating_point T>
using geom::detail::Segment3D = typedef std::pair<Vec3<T>, Vec3<T> >
```

Definition at line 21 of file [detail.hh](#).

### 4.2.2 Function Documentation

#### 4.2.2.1 isIntersect2D()

```
template<std::floating_point T>
bool geom::detail::isIntersect2D (
    const Triangle< T > & tr1,
    const Triangle< T > & tr2 )
```

Definition at line 80 of file [detail.hh](#).

References [computeInterval\(\)](#), [geom::Triangle< T >::getPlane\(\)](#), and [getTrian2\(\)](#).

Referenced by [geom::isIntersect\(\)](#), and [isIntersectValidInvalid\(\)](#).



#### 4.2.2.2 isIntersectMollerHaines()

```
template<std::floating_point T>
bool geom::detail::isIntersectMollerHaines (
    const Triangle< T > & tr1,
    const Triangle< T > & tr2 )
```

Definition at line 103 of file [detail.hh](#).

References [geom::Triangle< T >::getPlane\(\)](#), [helperMollerHaines\(\)](#), [geom::intersect\(\)](#), and [isOverlap\(\)](#).

Referenced by [geom::isIntersect\(\)](#).

#### 4.2.2.3 helperMollerHaines()

```
template<std::floating_point T>
Segment2D< T > geom::detail::helperMollerHaines (
    const Triangle< T > & tr,
    const Plane< T > & pl,
    const Line< T > & l )
```

Definition at line 117 of file [detail.hh](#).

References [geom::Triangle< T >::begin\(\)](#), [geom::Line< T >::dir\(\)](#), [geom::Triangle< T >::end\(\)](#), [geom::Line< T >::org\(\)](#), and [roguePos\(\)](#).

Referenced by [isIntersectMollerHaines\(\)](#).

#### 4.2.2.4 isIntersectBothInvalid()

```
template<std::floating_point T>
bool geom::detail::isIntersectBothInvalid (
    const Triangle< T > & tr1,
    const Triangle< T > & tr2 )
```

Definition at line 140 of file [detail.hh](#).

References [getSegment\(\)](#), [isIntersectPointSegment\(\)](#), [isIntersectSegmentSegment\(\)](#), and [isPoint\(\)](#).

Referenced by [geom::isIntersect\(\)](#).

#### 4.2.2.5 isIntersectValidInvalid()

```
template<std::floating_point T>
bool geom::detail::isIntersectValidInvalid (
    const Triangle< T > & valid,
    const Triangle< T > & invalid )
```

Definition at line 158 of file [detail.hh](#).

References [geom::distance\(\)](#), [geom::Triangle< T >::getPlane\(\)](#), [getSegment\(\)](#), [isIntersect2D\(\)](#), [isIntersectPointTriangle\(\)](#), [isPoint\(\)](#), and [geom::isZeroThreshold\(\)](#).

Referenced by [geom::isIntersect\(\)](#).

#### 4.2.2.6 isIntersectPointTriangle()

```
template<std::floating_point T>
bool geom::detail::isIntersectPointTriangle (
    const Vec3< T > & pt,
    const Triangle< T > & tr )
```

Definition at line 183 of file [detail.hh](#).

References [geom::dot\(\)](#), and [geom::Triangle< T >::getPlane\(\)](#).

Referenced by [isIntersectValidInvalid\(\)](#).

#### 4.2.2.7 isIntersectPointSegment()

```
template<std::floating_point T>
bool geom::detail::isIntersectPointSegment (
    const Vec3< T > & pt,
    const Segment3D< T > & segm )
```

Definition at line 211 of file [detail.hh](#).

References [geom::dot\(\)](#), and [isAllPosNeg\(\)](#).

Referenced by [isIntersectBothInvalid\(\)](#), and [isIntersectSegmentSegment\(\)](#).

#### 4.2.2.8 isIntersectSegmentSegment()

```
template<std::floating_point T>
bool geom::detail::isIntersectSegmentSegment (
    const Segment3D< T > & segm1,
    const Segment3D< T > & segm2 )
```

Definition at line 224 of file [detail.hh](#).

References [geom::dot\(\)](#), [geom::intersect\(\)](#), [isIntersectPointSegment\(\)](#), and [isOverlap\(\)](#).

Referenced by [isIntersectBothInvalid\(\)](#).

#### 4.2.2.9 isPoint()

```
template<std::floating_point T>
bool geom::detail::isPoint (
    const Triangle< T > & tr )
```

Definition at line [248](#) of file [detail.hh](#).

Referenced by [isIntersectBothInvalid\(\)](#), and [isIntersectValidInvalid\(\)](#).

#### 4.2.2.10 isOverlap()

```
template<std::floating_point T>
bool geom::detail::isOverlap (
    Segment2D< T > & segm1,
    Segment2D< T > & segm2 )
```

Definition at line [254](#) of file [detail.hh](#).

Referenced by [isIntersectMollerHaines\(\)](#), and [isIntersectSegmentSegment\(\)](#).

#### 4.2.2.11 isAllPosNeg() [1/2]

```
template<std::forward_iterator It>
bool geom::detail::isAllPosNeg (
    It begin,
    It end )
```

Definition at line [260](#) of file [detail.hh](#).

References [geom::isZeroThreshold\(\)](#).

Referenced by [isIntersectPointSegment\(\)](#), [isOnOneSide\(\)](#), and [roguePos\(\)](#).

#### 4.2.2.12 isAllPosNeg() [2/2]

```
template<std::floating_point T>
bool geom::detail::isAllPosNeg (
    T num1,
    T num2 )
```

Definition at line [271](#) of file [detail.hh](#).

#### 4.2.2.13 isOnOneSide()

```
template<std::floating_point T>
bool geom::detail::isOnOneSide (
    const Plane< T > & pl,
    const Triangle< T > & tr )
```

Definition at line 278 of file [detail.hh](#).

References [geom::Triangle< T >::begin\(\)](#), [geom::Triangle< T >::end\(\)](#), and [isAllPosNeg\(\)](#).

Referenced by [geom::isIntersect\(\)](#).

#### 4.2.2.14 getTrian2()

```
template<std::floating_point T>
Trian2< T > geom::detail::getTrian2 (
    const Plane< T > & pl,
    const Triangle< T > & tr )
```

Definition at line 286 of file [detail.hh](#).

References [geom::distance\(\)](#), [isCounterClockwise\(\)](#), and [geom::Plane< T >::norm\(\)](#).

Referenced by [isIntersect2D\(\)](#).

#### 4.2.2.15 isCounterClockwise()

```
template<std::floating_point T>
bool geom::detail::isCounterClockwise (
    Trian2< T > & tr )
```

Definition at line 320 of file [detail.hh](#).

Referenced by [getTrian2\(\)](#).

#### 4.2.2.16 computeInterval()

```
template<std::floating_point T>
Segment2D< T > geom::detail::computeInterval (
    const Trian2< T > & tr,
    const Vec2< T > & d )
```

Definition at line 340 of file [detail.hh](#).

Referenced by [isIntersect2D\(\)](#).

#### 4.2.2.17 getSegment()

```
template<std::floating_point T>
Segment3D< T > geom::detail::getSegment (
    const Triangle< T > & tr )
```

Definition at line 349 of file [detail.hh](#).

References [geom::distance\(\)](#).

Referenced by [isIntersectBothInvalid\(\)](#), and [isIntersectValidInvalid\(\)](#).

#### 4.2.2.18 roguePos()

```
template<std::bidirectional_iterator It>
std::size_t geom::detail::roguePos (
    It begin,
    It end )
```

Definition at line 362 of file [detail.hh](#).

References [geom::distance\(\)](#), and [isAllPosNeg\(\)](#).

Referenced by [helperMollerHaines\(\)](#).

## 4.3 geom::kdtree Namespace Reference

### Classes

- class [Container](#)
- class [KdTree](#)
- struct [Node](#)

### Typedefs

- using [Index](#) = std::size\_t

#### 4.3.1 Typedef Documentation

##### 4.3.1.1 Index

```
using geom::kdtree::Index = typedef std::size_t
```

Definition at line 13 of file [node.hh](#).



## Chapter 5

# Class Documentation

### 5.1 geom::BoundingBox< T > Struct Template Reference

```
#include <boundingbox.hh>
```

#### Public Member Functions

- bool [belongsTo](#) (const [BoundingBox](#)< T > &bb)
- T & [min](#) ([Axis](#) axis) &
- T & [max](#) ([Axis](#) axis) &
- T [min](#) ([Axis](#) axis) &&
- T [max](#) ([Axis](#) axis) &&
- T [min](#) ([Axis](#) axis) const &
- T [max](#) ([Axis](#) axis) const &
- [Axis](#) [getMaxDim](#) () const
- bool [operator==](#) (const [BoundingBox](#) &rhs) const
- bool [operator!=](#) (const [BoundingBox](#) &rhs) const

#### Public Attributes

- T [minX](#) {}
- T [maxX](#) {}
- T [minY](#) {}
- T [maxY](#) {}
- T [minZ](#) {}
- T [maxZ](#) {}

#### 5.1.1 Detailed Description

```
template<std::floating_point T>  
struct geom::BoundingBox< T >
```

Definition at line 14 of file [boundingbox.hh](#).

## 5.1.2 Member Function Documentation

### 5.1.2.1 belongsTo()

```
template<std::floating_point T>
bool geom::BoundingBox< T >::belongsTo (
    const BoundingBox< T > & bb )
```

Definition at line 43 of file [boundingbox.hh](#).

References [geom::BoundingBox< T >::maxX](#), [geom::BoundingBox< T >::maxY](#), [geom::BoundingBox< T >::maxZ](#), [geom::BoundingBox< T >::minX](#), [geom::BoundingBox< T >::minY](#), and [geom::BoundingBox< T >::minZ](#).

### 5.1.2.2 min() [1/3]

```
template<std::floating_point T>
T & geom::BoundingBox< T >::min (
    Axis axis ) &
```

Definition at line 67 of file [boundingbox.hh](#).

References [BBFILL](#).

### 5.1.2.3 max() [1/3]

```
template<std::floating_point T>
T & geom::BoundingBox< T >::max (
    Axis axis ) &
```

Definition at line 73 of file [boundingbox.hh](#).

References [BBFILL](#).

### 5.1.2.4 min() [2/3]

```
template<std::floating_point T>
T geom::BoundingBox< T >::min (
    Axis axis ) &&
```

Definition at line 79 of file [boundingbox.hh](#).

References [BBFILL](#).



#### 5.1.2.5 max() [2/3]

```
template<std::floating_point T>
T geom::BoundingBox< T >::max (
    Axis axis ) &&
```

Definition at line 85 of file [boundingbox.hh](#).

References [BBFILL](#).

#### 5.1.2.6 min() [3/3]

```
template<std::floating_point T>
T geom::BoundingBox< T >::min (
    Axis axis ) const &
```

Definition at line 91 of file [boundingbox.hh](#).

References [BBFILL](#).

#### 5.1.2.7 max() [3/3]

```
template<std::floating_point T>
T geom::BoundingBox< T >::max (
    Axis axis ) const &
```

Definition at line 97 of file [boundingbox.hh](#).

References [BBFILL](#).

#### 5.1.2.8 getMaxDim()

```
template<std::floating_point T>
Axis geom::BoundingBox< T >::getMaxDim
```

Definition at line 105 of file [boundingbox.hh](#).

References [geom::X](#), [geom::Y](#), and [geom::Z](#).

#### 5.1.2.9 operator==( )

```
template<std::floating_point T>
bool geom::BoundingBox< T >::operator== (
    const BoundingBox< T > & rhs ) const
```

Definition at line 113 of file [boundingbox.hh](#).

References [geom::isEqualThreshold\(\)](#), [geom::BoundingBox< T >::maxX](#), [geom::BoundingBox< T >::maxY](#), [geom::BoundingBox< T >::minX](#), [geom::BoundingBox< T >::minY](#), and [geom::BoundingBox< T >::minZ](#).

#### 5.1.2.10 operator!=( )

```
template<std::floating_point T>
bool geom::BoundingBox< T >::operator!= (
    const BoundingBox< T > & rhs ) const
```

Definition at line 121 of file [boundingbox.hh](#).

### 5.1.3 Member Data Documentation

#### 5.1.3.1 minX

```
template<std::floating_point T>
T geom::BoundingBox< T >::minX {}
```

Definition at line 16 of file [boundingbox.hh](#).

Referenced by [geom::BoundingBox< T >::belongsTo\(\)](#), [geom::operator<<\(\)](#), and [geom::BoundingBox< T >::operator==\( \)](#).

#### 5.1.3.2 maxX

```
template<std::floating_point T>
T geom::BoundingBox< T >::maxX {}
```

Definition at line 17 of file [boundingbox.hh](#).

Referenced by [geom::BoundingBox< T >::belongsTo\(\)](#), [geom::operator<<\(\)](#), and [geom::BoundingBox< T >::operator==\( \)](#).

### 5.1.3.3 minY

```
template<std::floating_point T>
T geom::BoundingBox< T >::minY {}
```

Definition at line 19 of file [boundingbox.hh](#).

Referenced by [geom::BoundingBox< T >::belongsTo\(\)](#), [geom::operator<<\(\)](#), and [geom::BoundingBox< T >::operator==\(\)](#).

### 5.1.3.4 maxY

```
template<std::floating_point T>
T geom::BoundingBox< T >::maxY {}
```

Definition at line 20 of file [boundingbox.hh](#).

Referenced by [geom::BoundingBox< T >::belongsTo\(\)](#), [geom::operator<<\(\)](#), and [geom::BoundingBox< T >::operator==\(\)](#).

### 5.1.3.5 minZ

```
template<std::floating_point T>
T geom::BoundingBox< T >::minZ {}
```

Definition at line 22 of file [boundingbox.hh](#).

Referenced by [geom::BoundingBox< T >::belongsTo\(\)](#), [geom::operator<<\(\)](#), and [geom::BoundingBox< T >::operator==\(\)](#).

### 5.1.3.6 maxZ

```
template<std::floating_point T>
T geom::BoundingBox< T >::maxZ {}
```

Definition at line 23 of file [boundingbox.hh](#).

Referenced by [geom::BoundingBox< T >::belongsTo\(\)](#), and [geom::operator<<\(\)](#).

The documentation for this struct was generated from the following file:

- [include/primitives/boundingbox.hh](#)

## 5.2 geom::kdtree::Container< T > Class Template Reference

```
#include <container.hh>
```

## Classes

- class [ConstIterator](#)

## Public Member Functions

- [Container](#) (const [KdTree](#)< T > \*tree, const [Node](#)< T > \*node)
- [ConstIterator](#) [cbegin](#) () const &
- [ConstIterator](#) [cend](#) () const &
- [ConstIterator](#) [begin](#) () const &
- [ConstIterator](#) [end](#) () const &
- [Node](#)< T >::IndexConstIterator [indexBegin](#) () const &
- [Node](#)< T >::IndexConstIterator [indexEnd](#) () const &
- T [separator](#) () const
- [Axis](#) [sepAxis](#) () const
- [BoundingBox](#)< T > [boundingBox](#) () const
- const [Triangle](#)< T > & [triangleByIndex](#) ([Index](#) index) const &
- [Container](#) [left](#) () const
- [Container](#) [right](#) () const
- bool [isValid](#) () const

### 5.2.1 Detailed Description

```
template<std::floating_point T>
class geom::kdtree::Container< T >
```

Definition at line 16 of file [container.hh](#).

### 5.2.2 Constructor & Destructor Documentation

#### 5.2.2.1 Container()

```
template<std::floating_point T>
geom::kdtree::Container< T >::Container (
    const KdTree< T > * tree,
    const Node< T > * node )
```

Definition at line 78 of file [container.hh](#).

### 5.2.3 Member Function Documentation

### 5.2.3.1 cbegin()

```
template<std::floating_point T>
Container< T >::ConstIterator geom::kdtree::Container< T >::cbegin
```

Definition at line 82 of file [container.hh](#).

### 5.2.3.2 cend()

```
template<std::floating_point T>
Container< T >::ConstIterator geom::kdtree::Container< T >::cend
```

Definition at line 88 of file [container.hh](#).

### 5.2.3.3 begin()

```
template<std::floating_point T>
Container< T >::ConstIterator geom::kdtree::Container< T >::begin
```

Definition at line 94 of file [container.hh](#).

### 5.2.3.4 end()

```
template<std::floating_point T>
Container< T >::ConstIterator geom::kdtree::Container< T >::end
```

Definition at line 100 of file [container.hh](#).

### 5.2.3.5 indexBegin()

```
template<std::floating_point T>
Node< T >::IndexConstIterator geom::kdtree::Container< T >::indexBegin
```

Definition at line 106 of file [container.hh](#).

Referenced by [geom::kdtree::Container< T >::ConstIterator::ConstIterator\(\)](#).

#### 5.2.3.6 indexEnd()

```
template<std::floating_point T>
Node< T >::IndexConstIterator geom::kdtree::Container< T >::indexEnd
```

Definition at line 112 of file [container.hh](#).

Referenced by [geom::kdtree::Container< T >::ConstIterator::ConstIterator\(\)](#).

#### 5.2.3.7 separator()

```
template<std::floating_point T>
T geom::kdtree::Container< T >::separator
```

Definition at line 118 of file [container.hh](#).

#### 5.2.3.8 sepAxis()

```
template<std::floating_point T>
Axis geom::kdtree::Container< T >::sepAxis
```

Definition at line 124 of file [container.hh](#).

#### 5.2.3.9 boundBox()

```
template<std::floating_point T>
BoundingBox< T > geom::kdtree::Container< T >::boundBox
```

Definition at line 130 of file [container.hh](#).

#### 5.2.3.10 triangleByIndex()

```
template<std::floating_point T>
const Triangle< T > & geom::kdtree::Container< T >::triangleByIndex (
    Index index ) const &
```

Definition at line 136 of file [container.hh](#).

#### 5.2.3.11 left()

```
template<std::floating_point T>
Container< T > geom::kdtree::Container< T >::left
```

Definition at line 142 of file [container.hh](#).

References [geom::kdtree::Container< T >::left\(\)](#).

Referenced by [geom::kdtree::Container< T >::left\(\)](#).

#### 5.2.3.12 right()

```
template<std::floating_point T>
Container< T > geom::kdtree::Container< T >::right
```

Definition at line 148 of file [container.hh](#).

References [geom::kdtree::Container< T >::right\(\)](#).

Referenced by [geom::kdtree::Container< T >::right\(\)](#).

#### 5.2.3.13 isValid()

```
template<std::floating_point T>
bool geom::kdtree::Container< T >::isValid
```

Definition at line 154 of file [container.hh](#).

The documentation for this class was generated from the following file:

- [include/kdtree/container.hh](#)

## 5.3 geom::kdtree::Container< T >::ConstIterator Class Reference

```
#include <container.hh>
```

### Public Types

- using [iterator\\_category](#) = std::forward\_iterator\_tag
- using [difference\\_type](#) = std::size\_t
- using [value\\_type](#) = [Triangle](#)< T >
- using [reference](#) = const [Triangle](#)< T > &
- using [pointer](#) = const [Triangle](#)< T > \*

## Public Member Functions

- [ConstIterator](#) (const [Container](#) \*cont, bool isEnd=false)
- [Index](#) getIndex ()
- [ConstIterator](#) & [operator++](#) ()
- [ConstIterator](#) [operator++](#) (int)
- [reference](#) [operator\\*](#) () const
- [pointer](#) [operator->](#) () const
- bool [operator==](#) (const [ConstIterator](#) &lhs) const =default

### 5.3.1 Detailed Description

```
template<std::floating_point T>
class geom::kdtree::Container< T >::ConstIterator
```

Definition at line 45 of file [container.hh](#).

### 5.3.2 Member Typedef Documentation

#### 5.3.2.1 iterator\_category

```
template<std::floating_point T>
using geom::kdtree::Container< T >::ConstIterator::iterator_category = std::forward_iterator↵
_tag
```

Definition at line 48 of file [container.hh](#).

#### 5.3.2.2 difference\_type

```
template<std::floating_point T>
using geom::kdtree::Container< T >::ConstIterator::difference_type = std::size_t
```

Definition at line 49 of file [container.hh](#).

#### 5.3.2.3 value\_type

```
template<std::floating_point T>
using geom::kdtree::Container< T >::ConstIterator::value_type = Triangle<T>
```

Definition at line 50 of file [container.hh](#).



#### 5.3.2.4 reference

```
template<std::floating_point T>
using geom::kdtree::Container< T >::ConstIterator::reference = const Triangle<T> &
```

Definition at line 51 of file [container.hh](#).

#### 5.3.2.5 pointer

```
template<std::floating_point T>
using geom::kdtree::Container< T >::ConstIterator::pointer = const Triangle<T> *
```

Definition at line 52 of file [container.hh](#).

### 5.3.3 Constructor & Destructor Documentation

#### 5.3.3.1 ConstIterator()

```
template<std::floating_point T>
geom::kdtree::Container< T >::ConstIterator::ConstIterator (
    const Container * cont,
    bool isEnd = false )
```

Definition at line 164 of file [container.hh](#).

References [geom::kdtree::Container< T >::indexBegin\(\)](#), and [geom::kdtree::Container< T >::indexEnd\(\)](#).

### 5.3.4 Member Function Documentation

#### 5.3.4.1 getIndex()

```
template<std::floating_point T>
Index geom::kdtree::Container< T >::ConstIterator::getIndex
```

Definition at line 176 of file [container.hh](#).

**5.3.4.2 operator++()** [1/2]

```
template<std::floating_point T>
Container< T >::ConstIterator & geom::kdtree::Container< T >::ConstIterator::operator++
```

Definition at line 182 of file [container.hh](#).

**5.3.4.3 operator++()** [2/2]

```
template<std::floating_point T>
Container< T >::ConstIterator geom::kdtree::Container< T >::ConstIterator::operator++ (
    int )
```

Definition at line 189 of file [container.hh](#).

**5.3.4.4 operator\*()**

```
template<std::floating_point T>
Container< T >::ConstIterator::reference geom::kdtree::Container< T >::ConstIterator::operator*
```

Definition at line 197 of file [container.hh](#).

**5.3.4.5 operator->()**

```
template<std::floating_point T>
Container< T >::ConstIterator::pointer geom::kdtree::Container< T >::ConstIterator::operator->
```

Definition at line 203 of file [container.hh](#).

**5.3.4.6 operator==()**

```
template<std::floating_point T>
bool geom::kdtree::Container< T >::ConstIterator::operator== (
    const ConstIterator & lhs ) const [default]
```

The documentation for this class was generated from the following file:

- [include/kdtree/container.hh](#)

## 5.4 geom::kdtree::KdTree< T > Class Template Reference

```
#include <container.hh>
```

### Classes

- class [ConstIterator](#)
- struct [ContainerPtr](#)

### Public Member Functions

- [KdTree](#) (std::initializer\_list< [Triangle](#)< T >> il)
- [KdTree](#) (const [KdTree](#) &tree)
- [KdTree](#) ([KdTree](#) &&tree)=default
- [KdTree](#) ()=default
- [~KdTree](#) ()
- [KdTree](#) & [operator=](#) (const [KdTree](#) &tree)
- [KdTree](#) & [operator=](#) ([KdTree](#) &&tree)=default
- [ConstIterator](#) [cbegin](#) () const &
- [ConstIterator](#) [cend](#) () const &
- [ConstIterator](#) [begin](#) () const &
- [ConstIterator](#) [end](#) () const &
- [ConstIterator](#) [beginFrom](#) (const [ConstIterator](#) &iter) const &
- void [insert](#) (const [Triangle](#)< T > &tr)
- void [clear](#) ()
- void [setNodeCapacity](#) (std::size\_t newCap)
- bool [empty](#) () const
- std::size\_t [size](#) () const
- std::size\_t [nodeCapacity](#) () const
- const [Triangle](#)< T > & [triangleByIndex](#) ([Index](#) index) const &
- void [dumpRecursive](#) (std::ostream &ost=std::cout) const

### Static Public Member Functions

- static bool [isOnPosSide](#) ([Axis](#) axis, T separator, const [Triangle](#)< T > &tr)
- static bool [isOnNegSide](#) ([Axis](#) axis, T separator, const [Triangle](#)< T > &tr)
- static bool [isOnSide](#) ([Axis](#) axis, T separator, const [Triangle](#)< T > &tr, std::function< bool(T, T)> comparator)

#### 5.4.1 Detailed Description

```
template<std::floating_point T>
class geom::kdtree::KdTree< T >
```

Definition at line 13 of file [container.hh](#).

#### 5.4.2 Constructor & Destructor Documentation

#### 5.4.2.1 KdTree() [1/4]

```
template<std::floating_point T>
geom::kdtree::KdTree< T >::KdTree (
    std::initializer_list< Triangle< T >> il )
```

Definition at line 119 of file [kdtree.hh](#).

#### 5.4.2.2 KdTree() [2/4]

```
template<std::floating_point T>
geom::kdtree::KdTree< T >::KdTree (
    const KdTree< T > & tree )
```

Definition at line 126 of file [kdtree.hh](#).

#### 5.4.2.3 KdTree() [3/4]

```
template<std::floating_point T>
geom::kdtree::KdTree< T >::KdTree (
    KdTree< T > && tree ) [default]
```

#### 5.4.2.4 KdTree() [4/4]

```
template<std::floating_point T>
geom::kdtree::KdTree< T >::KdTree ( ) [default]
```

#### 5.4.2.5 ~KdTree()

```
template<std::floating_point T>
geom::kdtree::KdTree< T >::~~KdTree
```

Definition at line 134 of file [kdtree.hh](#).

### 5.4.3 Member Function Documentation

#### 5.4.3.1 operator=() [1/2]

```
template<std::floating_point T>
KdTree< T > & geom::kdtree::KdTree< T >::operator= (
    const KdTree< T > & tree )
```

Definition at line 140 of file [kdtree.hh](#).

#### 5.4.3.2 operator=() [2/2]

```
template<std::floating_point T>
KdTree& geom::kdtree::KdTree< T >::operator= (
    KdTree< T > && tree ) [default]
```

#### 5.4.3.3 cbegin()

```
template<std::floating_point T>
KdTree< T >::ConstIterator geom::kdtree::KdTree< T >::cbegin
```

Definition at line 149 of file [kdtree.hh](#).

#### 5.4.3.4 cend()

```
template<std::floating_point T>
KdTree< T >::ConstIterator geom::kdtree::KdTree< T >::cend
```

Definition at line 155 of file [kdtree.hh](#).

#### 5.4.3.5 begin()

```
template<std::floating_point T>
KdTree< T >::ConstIterator geom::kdtree::KdTree< T >::begin
```

Definition at line 161 of file [kdtree.hh](#).

#### 5.4.3.6 end()

```
template<std::floating_point T>
KdTree< T >::ConstIterator geom::kdtree::KdTree< T >::end
```

Definition at line 167 of file [kdtree.hh](#).

#### 5.4.3.7 beginFrom()

```
template<std::floating_point T>
KdTree< T >::ConstIterator geom::kdtree::KdTree< T >::beginFrom (
    const ConstIterator & iter ) const &
```

Definition at line 173 of file [kdtree.hh](#).

References [geom::kdtree::KdTree< T >::ConstIterator::beginFrom\(\)](#).

#### 5.4.3.8 insert()

```
template<std::floating_point T>
void geom::kdtree::KdTree< T >::insert (
    const Triangle< T > & tr )
```

Definition at line 181 of file [kdtree.hh](#).

References [geom::Triangle< T >::belongsTo\(\)](#), [geom::Triangle< T >::boundingBox\(\)](#), and [geom::NONE](#).

#### 5.4.3.9 clear()

```
template<std::floating_point T>
void geom::kdtree::KdTree< T >::clear
```

Definition at line 201 of file [kdtree.hh](#).

#### 5.4.3.10 setNodeCapacity()

```
template<std::floating_point T>
void geom::kdtree::KdTree< T >::setNodeCapacity (
    std::size_t newCap )
```

Definition at line 228 of file [kdtree.hh](#).

#### 5.4.3.11 empty()

```
template<std::floating_point T>
bool geom::kdtree::KdTree< T >::empty
```

Definition at line 235 of file [kdtree.hh](#).

#### 5.4.3.12 size()

```
template<std::floating_point T>
std::size_t geom::kdtree::KdTree< T >::size
```

Definition at line 241 of file [kdtree.hh](#).

#### 5.4.3.13 nodeCapacity()

```
template<std::floating_point T>
std::size_t geom::kdtree::KdTree< T >::nodeCapacity
```

Definition at line 247 of file [kdtree.hh](#).

#### 5.4.3.14 triangleByIndex()

```
template<std::floating_point T>
const Triangle< T > & geom::kdtree::KdTree< T >::triangleByIndex (
    Index index ) const &
```

Definition at line 253 of file [kdtree.hh](#).

#### 5.4.3.15 dumpRecursive()

```
template<std::floating_point T>
void geom::kdtree::KdTree< T >::dumpRecursive (
    std::ostream & ost = std::cout ) const
```

Definition at line 259 of file [kdtree.hh](#).

#### 5.4.3.16 isOnPosSide()

```
template<std::floating_point T>
bool geom::kdtree::KdTree< T >::isOnPosSide (
    Axis axis,
    T separator,
    const Triangle< T > & tr ) [static]
```

Definition at line 268 of file [kdtree.hh](#).

#### 5.4.3.17 isOnNegSide()

```
template<std::floating_point T>
bool geom::kdtree::KdTree< T >::isOnNegSide (
    Axis axis,
    T separator,
    const Triangle< T > & tr ) [static]
```

Definition at line 274 of file [kdtree.hh](#).

#### 5.4.3.18 isOnSide()

```
template<std::floating_point T>
bool geom::kdtree::KdTree< T >::isOnSide (
    Axis axis,
    T separator,
    const Triangle< T > & tr,
    std::function< bool(T, T)> comparator ) [static]
```

Definition at line 280 of file [kdtree.hh](#).

References [geom::Triangle< T >::begin\(\)](#), [geom::Triangle< T >::end\(\)](#), and [geom::NONE](#).

The documentation for this class was generated from the following files:

- [include/kdtree/container.hh](#)
- [include/kdtree/kdtree.hh](#)

## 5.5 geom::kdtree::KdTree< T >::ConstIterator Class Reference

```
#include <kdtree.hh>
```

### Public Types

- using [iterator\\_category](#) = std::forward\_iterator\_tag
- using [difference\\_type](#) = std::size\_t
- using [value\\_type](#) = Container< T >
- using [reference](#) = Container< T >
- using [pointer](#) = ContainerPtr

### Public Member Functions

- [ConstIterator](#) (const [KdTree](#)< T > \*tree, const [Node](#)< T > \*node)
- [ConstIterator](#) & [operator++](#) ()
- [ConstIterator](#) [operator++](#) (int)
- [reference](#) [operator\\*](#) () const
- [pointer](#) [operator->](#) () const
- bool [operator==](#) (const [ConstIterator](#) &lhs) const
- bool [operator!=](#) (const [ConstIterator](#) &lhs) const



## Static Public Member Functions

- static [ConstIterator beginFrom](#) (const [ConstIterator](#) &iter)

### 5.5.1 Detailed Description

```
template<std::floating_point T>
class geom::kdtree::KdTree< T >::ConstIterator
```

Definition at line 84 of file [kdtree.hh](#).

### 5.5.2 Member Typedef Documentation

#### 5.5.2.1 iterator\_category

```
template<std::floating_point T>
using geom::kdtree::KdTree< T >::ConstIterator::iterator_category = std::forward_iterator_tag
```

Definition at line 87 of file [kdtree.hh](#).

#### 5.5.2.2 difference\_type

```
template<std::floating_point T>
using geom::kdtree::KdTree< T >::ConstIterator::difference_type = std::size_t
```

Definition at line 88 of file [kdtree.hh](#).

#### 5.5.2.3 value\_type

```
template<std::floating_point T>
using geom::kdtree::KdTree< T >::ConstIterator::value_type = Container<T>
```

Definition at line 89 of file [kdtree.hh](#).

#### 5.5.2.4 reference

```
template<std::floating_point T>
using geom::kdtree::KdTree< T >::ConstIterator::reference = Container<T>
```

Definition at line 90 of file [kdtree.hh](#).

#### 5.5.2.5 pointer

```
template<std::floating_point T>
using geom::kdtree::KdTree< T >::ConstIterator::pointer = ContainerPtr
```

Definition at line 91 of file [kdtree.hh](#).

### 5.5.3 Constructor & Destructor Documentation

#### 5.5.3.1 ConstIterator()

```
template<std::floating_point T>
geom::kdtree::KdTree< T >::ConstIterator::ConstIterator (
    const KdTree< T > * tree,
    const Node< T > * node )
```

Definition at line 414 of file [kdtree.hh](#).

### 5.5.4 Member Function Documentation

#### 5.5.4.1 operator++() [1/2]

```
template<std::floating_point T>
KdTree< T >::ConstIterator & geom::kdtree::KdTree< T >::ConstIterator::operator++
```

Definition at line 419 of file [kdtree.hh](#).

References [geom::NONE](#).

#### 5.5.4.2 operator++() [2/2]

```
template<std::floating_point T>
KdTree< T >::ConstIterator geom::kdtree::KdTree< T >::ConstIterator::operator++ (
    int )
```

Definition at line 440 of file [kdtree.hh](#).

#### 5.5.4.3 operator\*()

```
template<std::floating_point T>
KdTree< T >::ConstIterator::reference geom::kdtree::KdTree< T >::ConstIterator::operator*
```

Definition at line 448 of file [kdtree.hh](#).

#### 5.5.4.4 operator->()

```
template<std::floating_point T>
KdTree< T >::ConstIterator::pointer geom::kdtree::KdTree< T >::ConstIterator::operator->
```

Definition at line 454 of file [kdtree.hh](#).

#### 5.5.4.5 operator==()

```
template<std::floating_point T>
bool geom::kdtree::KdTree< T >::ConstIterator::operator== (
    const ConstIterator & lhs ) const
```

Definition at line 460 of file [kdtree.hh](#).

#### 5.5.4.6 operator!=(())

```
template<std::floating_point T>
bool geom::kdtree::KdTree< T >::ConstIterator::operator!= (
    const ConstIterator & lhs ) const
```

Definition at line 466 of file [kdtree.hh](#).

#### 5.5.4.7 beginFrom()

```
template<std::floating_point T>
KdTree< T >::ConstIterator geom::kdtree::KdTree< T >::ConstIterator::beginFrom (
    const ConstIterator & iter ) [static]
```

Definition at line 472 of file [kdtree.hh](#).

Referenced by [geom::kdtree::KdTree< T >::beginFrom\(\)](#).

The documentation for this class was generated from the following file:

- include/kdtree/[kdtree.hh](#)

## 5.6 geom::kdtree::KdTree< T >::ContainerPtr Struct Reference

```
#include <kdtree.hh>
```

### Public Member Functions

- const [Container](#)< T > \* [operator->](#) () const

### Public Attributes

- [Container](#)< T > [cont](#)

#### 5.6.1 Detailed Description

```
template<std::floating_point T>
struct geom::kdtree::KdTree< T >::ContainerPtr
```

Definition at line 78 of file [kdtree.hh](#).

#### 5.6.2 Member Function Documentation

##### 5.6.2.1 operator->()

```
template<std::floating_point T>
const Container< T > * geom::kdtree::KdTree< T >::ContainerPtr::operator->
```

Definition at line 404 of file [kdtree.hh](#).

References [geom::kdtree::KdTree](#)< T >::ContainerPtr::cont.

#### 5.6.3 Member Data Documentation

##### 5.6.3.1 cont

```
template<std::floating_point T>
Container<T> geom::kdtree::KdTree< T >::ContainerPtr::cont
```

Definition at line 80 of file [kdtree.hh](#).

Referenced by [geom::kdtree::KdTree](#)< T >::ContainerPtr::operator->().

The documentation for this struct was generated from the following file:

- include/kdtree/[kdtree.hh](#)

## 5.7 geom::kdtree::Node< T > Struct Template Reference

```
#include <node.hh>
```

### Public Types

- using [IndexIterator](#) = std::vector< [Index](#) >::iterator
- using [IndexConstIterator](#) = std::vector< [Index](#) >::const\_iterator

### Public Member Functions

- void [dumpRecursive](#) (std::ostream &ost) const

### Public Attributes

- T [separator](#) {}
- Axis [sepAxis](#) {Axis::NONE}
- [BoundingBox](#)< T > [boundingBox](#) {}
- std::vector< [Index](#) > [indices](#) {}
- std::unique\_ptr< [Node](#) > [left](#) {nullptr}
- std::unique\_ptr< [Node](#) > [right](#) {nullptr}

### 5.7.1 Detailed Description

```
template<std::floating_point T>  
struct geom::kdtree::Node< T >
```

Definition at line 16 of file [node.hh](#).

### 5.7.2 Member Typedef Documentation

#### 5.7.2.1 IndexIterator

```
template<std::floating_point T>  
using geom::kdtree::Node< T >::IndexIterator = std::vector<Index>::iterator
```

Definition at line 26 of file [node.hh](#).

### 5.7.2.2 IndexConstIterator

```
template<std::floating_point T>
using geom::kdtree::Node< T >::IndexConstIterator = std::vector<Index>::const_iterator
```

Definition at line 27 of file [node.hh](#).

## 5.7.3 Member Function Documentation

### 5.7.3.1 dumpRecursive()

```
template<std::floating_point T>
void geom::kdtree::Node< T >::dumpRecursive (
    std::ostream & ost ) const
```

Definition at line 33 of file [node.hh](#).

## 5.7.4 Member Data Documentation

### 5.7.4.1 separator

```
template<std::floating_point T>
T geom::kdtree::Node< T >::separator {}
```

Definition at line 18 of file [node.hh](#).

### 5.7.4.2 sepAxis

```
template<std::floating_point T>
Axis geom::kdtree::Node< T >::sepAxis {Axis::NONE}
```

Definition at line 19 of file [node.hh](#).

### 5.7.4.3 boundBox

```
template<std::floating_point T>
BoundingBox<T> geom::kdtree::Node< T >::boundBox {}
```

Definition at line 20 of file [node.hh](#).

#### 5.7.4.4 indices

```
template<std::floating_point T>
std::vector<Index> geom::kdtree::Node< T >::indices {}
```

Definition at line 21 of file [node.hh](#).

#### 5.7.4.5 left

```
template<std::floating_point T>
std::unique_ptr<Node> geom::kdtree::Node< T >::left {nullptr}
```

Definition at line 23 of file [node.hh](#).

#### 5.7.4.6 right

```
template<std::floating_point T>
std::unique_ptr<Node> geom::kdtree::Node< T >::right {nullptr}
```

Definition at line 24 of file [node.hh](#).

The documentation for this struct was generated from the following file:

- [include/kdtree/node.hh](#)

## 5.8 geom::Line< T > Class Template Reference

[Line](#) class implementation.

```
#include <line.hh>
```

## Public Member Functions

- [Line](#) (const [Vec3](#)< T > &org, const [Vec3](#)< T > &dir)

*Construct a new [Line](#) object.*

- bool [operator==](#) (const [Line](#) &rhs) const

*[Line](#) equality operator.*

- bool [operator!=](#) (const [Line](#) &rhs) const

*[Line](#) inequality operator.*

- const [Vec3](#)< T > & [org](#) () const &

*Getter for origin vector.*

- const [Vec3](#)< T > & [dir](#) () const &

*Getter for direction vector.*

- [Vec3](#)< T > && [org](#) () &&

*Getter for origin vector.*

- [Vec3](#)< T > && [dir](#) () &&

*Getter for direction vector.*

- template<Number nType>

[Vec3](#)< T > [getPoint](#) (nType t) const

*Get point on line by parameter t.*

- bool [belongs](#) (const [Vec3](#)< T > &point) const

*Checks is point belongs to line.*

- bool [isEqual](#) (const [Line](#) &line) const

*Checks is \*this equals to another line.*

- bool [isPar](#) (const [Line](#) &line) const

*Checks is \*this parallel to another line.*

- bool [isSkew](#) (const [Line](#)< T > &line) const

*Checks is \*this is skew with another line.*

## Static Public Member Functions

- static [Line](#) [getBy2Points](#) (const [Vec3](#)< T > &p1, const [Vec3](#)< T > &p2)

*Get line by 2 points.*

### 5.8.1 Detailed Description

```
template<std::floating_point T>
class geom::Line< T >
```

[Line](#) class implementation.

Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

Definition at line 21 of file [line.hh](#).



## 5.8.2 Constructor & Destructor Documentation

### 5.8.2.1 Line()

```
template<std::floating_point T>
geom::Line< T >::Line (
    const Vec3< T > & org,
    const Vec3< T > & dir )
```

Construct a new [Line](#) object.

#### Parameters

in	<i>org</i>	origin vector
in	<i>dir</i>	direction vector

Definition at line 158 of file [line.hh](#).

References [geom::Line< T >::org\(\)](#).

## 5.8.3 Member Function Documentation

### 5.8.3.1 operator==( )

```
template<std::floating_point T>
bool geom::Line< T >::operator==(
    const Line< T > & rhs ) const
```

[Line](#) equality operator.

#### Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

#### Parameters

in	<i>rhs</i>	2nd line
----	------------	----------

#### Returns

true if lines are equal  
false if lines are not equal

Definition at line 165 of file [line.hh](#).

### 5.8.3.2 operator"!=()

```
template<std::floating_point T>
bool geom::Line< T >::operator!= (
    const Line< T > & rhs ) const
```

[Line](#) inequality operator.

#### Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

#### Parameters

<i>in</i>	<i>rhs</i>	2nd line
-----------	------------	----------

#### Returns

true if lines are not equal

false if lines are equal

Definition at line 171 of file [line.hh](#).

### 5.8.3.3 org() [1/2]

```
template<std::floating_point T>
Vec3< T > && geom::Line< T >::org
```

Getter for origin vector.

#### Returns

const Vec3<T>& const reference to origin vector

Definition at line 177 of file [line.hh](#).

Referenced by [geom::Plane< T >::belongs\(\)](#), [geom::detail::helperMollerHaines\(\)](#), [geom::intersect\(\)](#), [geom::Line< T >::Line\(\)](#), and [geom::operator<<\(\)](#).

#### 5.8.3.4 dir() [1/2]

```
template<std::floating_point T>
Vec3< T > && geom::Line< T >::dir
```

Getter for direction vector.

##### Returns

const Vec3<T>& const reference to direction vector

Definition at line 183 of file line.hh.

Referenced by [geom::Plane< T >::belongs\(\)](#), [geom::detail::helperMollerHaines\(\)](#), [geom::intersect\(\)](#), and [geom::operator<<\(\)](#).

#### 5.8.3.5 org() [2/2]

```
template<std::floating_point T>
Vec3<T>&& geom::Line< T >::org ( ) &&
```

Getter for origin vector.

##### Returns

Vec3<T>&& reference to origin vector

#### 5.8.3.6 dir() [2/2]

```
template<std::floating_point T>
Vec3<T>&& geom::Line< T >::dir ( ) &&
```

Getter for direction vector.

##### Returns

Vec3<T>&& reference to direction vector

#### 5.8.3.7 getPoint()

```
template<std::floating_point T>
template<Number nType>
Vec3< T > geom::Line< T >::getPoint (
    nType t ) const
```

Get point on line by parameter t.

**Template Parameters**

<i>nType</i>	numeric type
--------------	--------------

**Parameters**

in	<i>t</i>	point paramater from line's equation
----	----------	--------------------------------------

**Returns**

Vec3<T> Point related to parameter

Definition at line 202 of file [line.hh](#).

Referenced by [geom::intersect\(\)](#).

**5.8.3.8 belongs()**

```
template<std::floating_point T>
bool geom::Line< T >::belongs (
    const Vec3< T > & point ) const
```

Checks is point belongs to line.

**Parameters**

in	<i>point</i>	const reference to point vector
----	--------------	---------------------------------

**Returns**

true if point belongs to line  
false if point doesn't belong to line

Definition at line 208 of file [line.hh](#).

**5.8.3.9 isEqual()**

```
template<std::floating_point T>
bool geom::Line< T >::isEqual (
    const Line< T > & line ) const
```

Checks is \*this equals to another line.

## Parameters

in	<i>line</i>	const reference to another line
----	-------------	---------------------------------

## Returns

true if lines are equal  
false if lines are not equal

Definition at line 214 of file [line.hh](#).

Referenced by [geom::intersect\(\)](#).

### 5.8.3.10 isPar()

```
template<std::floating_point T>
bool geom::Line< T >::isPar (
    const Line< T > & line ) const
```

Checks is \*this parallel to another line.

## Note

Assumes equal lines as parallel

## Parameters

in	<i>line</i>	const reference to another line
----	-------------	---------------------------------

## Returns

true if lines are parallel  
false if lines are not parallel

Definition at line 220 of file [line.hh](#).

Referenced by [geom::intersect\(\)](#).

### 5.8.3.11 isSkew()

```
template<std::floating_point T>
bool geom::Line< T >::isSkew (
    const Line< T > & line ) const
```

Checks is \*this is skew with another line.

**Parameters**

in	<i>line</i>	const reference to another line
----	-------------	---------------------------------

**Returns**

true if lines are skew

false if lines are not skew

Definition at line 226 of file [line.hh](#).

References [geom::isZeroThreshold\(\)](#), and [geom::triple\(\)](#).

Referenced by [geom::intersect\(\)](#).

**5.8.3.12 getBy2Points()**

```
template<std::floating_point T>
Line< T > geom::Line< T >::getBy2Points (
    const Vec3< T > & p1,
    const Vec3< T > & p2 ) [static]
```

Get line by 2 points.

**Parameters**

in	<i>p1</i>	1st point
in	<i>p2</i>	2nd point

**Returns**

[Line](#) passing through two points

Definition at line 233 of file [line.hh](#).

The documentation for this class was generated from the following file:

- include/primitives/[line.hh](#)

**5.9 geom::Plane< T > Class Template Reference**

[Plane](#) class realization.

```
#include <plane.hh>
```

## Public Member Functions

- bool `operator==` (const [Plane](#) &rhs) const  
*Plane equality operator.*
- bool `operator!=` (const [Plane](#) &rhs) const  
*Plane inequality operator.*
- T `dist` () const  
*Getter for distance.*
- const [Vec3](#)< T > & `norm` () const &  
*Getter for normal vector.*
- [Vec3](#)< T > && `norm` () &&  
*Getter for normal vector.*
- bool `belongs` (const [Vec3](#)< T > &point) const  
*Checks if point belongs to plane.*
- bool `belongs` (const [Line](#)< T > &line) const  
*Checks if line belongs to plane.*
- bool `isEqual` (const [Plane](#) &rhs) const  
*Checks is \*this equals to another plane.*
- bool `isPar` (const [Plane](#) &rhs) const  
*Checks is \*this is parallel to another plane.*

## Static Public Member Functions

- static [Plane](#) `getBy3Points` (const [Vec3](#)< T > &pt1, const [Vec3](#)< T > &pt2, const [Vec3](#)< T > &pt3)  
*Get plane by 3 points.*
- static [Plane](#) `getParametric` (const [Vec3](#)< T > &org, const [Vec3](#)< T > &dir1, const [Vec3](#)< T > &dir2)  
*Get plane from parametric plane equation.*
- static [Plane](#) `getNormalPoint` (const [Vec3](#)< T > &norm, const [Vec3](#)< T > &point)  
*Get plane from normal point plane equation.*
- static [Plane](#) `getNormalDist` (const [Vec3](#)< T > &norm, T constant)  
*Get plane form normal const plane equation.*

### 5.9.1 Detailed Description

```
template<std::floating_point T>
class geom::Plane< T >
```

[Plane](#) class realization.

#### Template Parameters

<a href="#">T</a>	- floating point type of coordinates
-------------------	--------------------------------------

Definition at line 22 of file [plane.hh](#).

### 5.9.2 Member Function Documentation

### 5.9.2.1 operator==( )

```
template<std::floating_point T>
bool geom::Plane< T >::operator==(
    const Plane< T > & rhs ) const
```

Plane equality operator.

#### Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

#### Parameters

in	<i>rhs</i>	2nd plane
----	------------	-----------

#### Returns

true if planes are equal  
false if planes are not equal

Definition at line 183 of file [plane.hh](#).

### 5.9.2.2 operator!=( )

```
template<std::floating_point T>
bool geom::Plane< T >::operator!=(
    const Plane< T > & rhs ) const
```

Plane inequality operator.

#### Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

#### Parameters

in	<i>rhs</i>	2nd plane
----	------------	-----------

#### Returns

true if planes are not equal  
false if planes are equal

Definition at line 189 of file [plane.hh](#).



### 5.9.2.3 dist()

```
template<std::floating_point T>
T geom::Plane< T >::dist
```

Getter for distance.

#### Returns

T value of distance

Definition at line 195 of file [plane.hh](#).

Referenced by [geom::distance\(\)](#), [geom::intersect\(\)](#), and [geom::operator<<\(\)](#).

### 5.9.2.4 norm() [1/2]

```
template<std::floating_point T>
Vec3< T > && geom::Plane< T >::norm
```

Getter for normal vector.

#### Returns

const Vec3<T>& const reference to normal vector

Definition at line 201 of file [plane.hh](#).

Referenced by [geom::distance\(\)](#), [geom::detail::getTrian2\(\)](#), [geom::intersect\(\)](#), and [geom::operator<<\(\)](#).

### 5.9.2.5 norm() [2/2]

```
template<std::floating_point T>
Vec3<T>&& geom::Plane< T >::norm ( ) &&
```

Getter for normal vector.

#### Returns

Vec3<T>&& reference to normal vector

### 5.9.2.6 belongs() [1/2]

```
template<std::floating_point T>
bool geom::Plane< T >::belongs (
    const Vec3< T > & point ) const
```

Checks if point belongs to plane.

**Parameters**

in	<i>point</i>	const referene to point vector
----	--------------	--------------------------------

**Returns**

true if point belongs to plane  
false if point doesn't belong to plane

Definition at line 213 of file [plane.hh](#).

References [geom::isEqualThreshold\(\)](#).

**5.9.2.7 belongs() [2/2]**

```
template<std::floating_point T>
bool geom::Plane< T >::belongs (
    const Line< T > & line ) const
```

Checks if line belongs to plane.

**Parameters**

in	<i>line</i>	const referene to line
----	-------------	------------------------

**Returns**

true if line belongs to plane  
false if line doesn't belong to plane

Definition at line 219 of file [plane.hh](#).

References [geom::Line< T >::dir\(\)](#), and [geom::Line< T >::org\(\)](#).

**5.9.2.8 isEqual()**

```
template<std::floating_point T>
bool geom::Plane< T >::isEqual (
    const Plane< T > & rhs ) const
```

Checks is \*this equals to another plane.

**Parameters**

in	<i>rhs</i>	const reference to another plane
----	------------	----------------------------------

**Returns**

true if planes are equal  
false if planes are not equal

Definition at line 225 of file [plane.hh](#).

**5.9.2.9 isPar()**

```
template<std::floating_point T>
bool geom::Plane< T >::isPar (
    const Plane< T > & rhs ) const
```

Checks is \*this is parallel to another plane.

**Parameters**

in	<i>rhs</i>	const reference to another plane
----	------------	----------------------------------

**Returns**

true if planes are parallel  
false if planes are not parallel

Definition at line 231 of file [plane.hh](#).

References [geom::Plane< T >::isPar\(\)](#).

Referenced by [geom::Plane< T >::isPar\(\)](#).

**5.9.2.10 getBy3Points()**

```
template<std::floating_point T>
Plane< T > geom::Plane< T >::getBy3Points (
    const Vec3< T > & pt1,
    const Vec3< T > & pt2,
    const Vec3< T > & pt3 ) [static]
```

Get plane by 3 points.

**Parameters**

in	<i>pt1</i>	1st point
in	<i>pt2</i>	2nd point
in	<i>pt3</i>	3rd point

**Returns**

[Plane](#) passing through three points

Definition at line 237 of file [plane.hh](#).

Referenced by [geom::Triangle< T >::getPlane\(\)](#).

**5.9.2.11 getParametric()**

```
template<std::floating_point T>
Plane< T > geom::Plane< T >::getParametric (
    const Vec3< T > & org,
    const Vec3< T > & dir1,
    const Vec3< T > & dir2 ) [static]
```

Get plane from parametric plane equation.

**Parameters**

in	<i>org</i>	origin vector
in	<i>dir1</i>	1st direction vector
in	<i>dir2</i>	2nd direction vector

**Returns**

[Plane](#)

Definition at line 243 of file [plane.hh](#).

References [geom::Vec3< T >::cross\(\)](#).

**5.9.2.12 getNormalPoint()**

```
template<std::floating_point T>
Plane< T > geom::Plane< T >::getNormalPoint (
    const Vec3< T > & norm,
    const Vec3< T > & point ) [static]
```

Get plane from normal point plane equation.

**Parameters**

in	<i>norm</i>	normal vector
in	<i>point</i>	point lying on the plane

Returns

[Plane](#)

Definition at line 250 of file [plane.hh](#).

References [geom::Vec3< T >::normalized\(\)](#).

### 5.9.2.13 getNormalDist()

```
template<std::floating_point T>
Plane< T > geom::Plane< T >::getNormalDist (
    const Vec3< T > & norm,
    T constant ) [static]
```

Get plane form normal const plane equation.

Parameters

in	<i>norm</i>	normal vector
in	<i>constant</i>	distance

Returns

[Plane](#)

Definition at line 257 of file [plane.hh](#).

References [geom::Vec3< T >::normalized\(\)](#).

The documentation for this class was generated from the following file:

- include/primitives/[plane.hh](#)

## 5.10 geom::ThresComp< T > Class Template Reference

```
#include <common.hh>
```

### Public Member Functions

- [ThresComp](#) ()=delete

### Static Public Member Functions

- static void [setThreshold](#) (T thres) requires std
- static bool [isZero](#) (T num)

### 5.10.1 Detailed Description

```
template<Number T>
class geom::ThresComp< T >
```

Definition at line 28 of file [common.hh](#).

### 5.10.2 Constructor & Destructor Documentation

#### 5.10.2.1 ThresComp()

```
template<Number T>
geom::ThresComp< T >::ThresComp ( ) [delete]
```

### 5.10.3 Member Function Documentation

#### 5.10.3.1 setThreshold()

```
template<Number T>
static void geom::ThresComp< T >::setThreshold (
    T thres ) [inline], [static]
```

Definition at line 36 of file [common.hh](#).

#### 5.10.3.2 isZero()

```
template<Number T>
static bool geom::ThresComp< T >::isZero (
    T num ) [inline], [static]
```

Definition at line 64 of file [common.hh](#).

Referenced by [geom::isZeroThreshold\(\)](#).

The documentation for this class was generated from the following file:

- include/primitives/[common.hh](#)

## 5.11 geom::Triangle< T > Class Template Reference

[Triangle](#) class implementation.

```
#include <triangle.hh>
```

### Public Types

- using [Iterator](#) = typename std::array< [Vec3](#)< T >, 3 >::iterator
- using [ConstIterator](#) = typename std::array< [Vec3](#)< T >, 3 >::const\_iterator

### Public Member Functions

- [Triangle](#) ()  
*Construct a new [Triangle](#) object.*
- [Triangle](#) (const [Vec3](#)< T > &p1, const [Vec3](#)< T > &p2, const [Vec3](#)< T > &p3)  
*Construct a new [Triangle](#) object from 3 points.*
- const [Vec3](#)< T > & [operator\[\]](#) (std::size\_t idx) const &  
*Overloaded operator[] to get access to vertices.*
- [Vec3](#)< T > && [operator\[\]](#) (std::size\_t idx) &&  
*Overloaded operator[] to get access to vertices.*
- [Vec3](#)< T > & [operator\[\]](#) (std::size\_t idx) &  
*Overloaded operator[] to get access to vertices.*
- [Iterator](#) [begin](#) () &  
*Get begin iterator.*
- [Iterator](#) [end](#) () &  
*Get end iterator.*
- [ConstIterator](#) [begin](#) () const &  
*Get begin const iterator.*
- [ConstIterator](#) [end](#) () const &  
*Get end const iterator.*
- [Plane](#)< T > [getPlane](#) () const  
*Get triangle's plane.*
- bool [isValid](#) () const  
*Check is triangle valid.*
- [BoundingBox](#)< T > [boundingBox](#) () const  
*Returns triangle's bound box.*
- bool [belongsTo](#) (const [BoundingBox](#)< T > &bb) const  
*Checks if this [Triangle](#) belongs to [BoundingBox](#).*

#### 5.11.1 Detailed Description

```
template<std::floating_point T>
class geom::Triangle< T >
```

[Triangle](#) class implementation.

### Template Parameters

<code>T</code>	- floating point type of coordinates
----------------	--------------------------------------

Definition at line 26 of file [triangle.hh](#).

## 5.11.2 Member Typedef Documentation

### 5.11.2.1 Iterator

```
template<std::floating_point T>
using geom::Triangle< T >::Iterator = typename std::array<Vec3<T>, 3>::iterator
```

Definition at line 35 of file [triangle.hh](#).

### 5.11.2.2 ConstIterator

```
template<std::floating_point T>
using geom::Triangle< T >::ConstIterator = typename std::array<Vec3<T>, 3>::const_iterator
```

Definition at line 36 of file [triangle.hh](#).

## 5.11.3 Constructor & Destructor Documentation

### 5.11.3.1 Triangle() [1/2]

```
template<std::floating_point T>
geom::Triangle< T >::Triangle
```

Construct a new [Triangle](#) object.

Definition at line 160 of file [triangle.hh](#).

### 5.11.3.2 Triangle() [2/2]

```
template<std::floating_point T>
geom::Triangle< T >::Triangle (
    const Vec3< T > & p1,
    const Vec3< T > & p2,
    const Vec3< T > & p3 )
```

Construct a new [Triangle](#) object from 3 points.



## Parameters

in	<i>p1</i>	1st point
in	<i>p2</i>	2nd point
in	<i>p3</i>	3rd point

Definition at line 164 of file [triangle.hh](#).

## 5.11.4 Member Function Documentation

### 5.11.4.1 operator[]() [1/3]

```
template<std::floating_point T>
const Vec3< T > & geom::Triangle< T >::operator[] (
    std::size_t idx ) const &
```

Overloaded operator[] to get access to vertices.

## Parameters

in	<i>idx</i>	index of vertex
----	------------	-----------------

## Returns

const Vec3<T>& const reference to vertex

Definition at line 169 of file [triangle.hh](#).

### 5.11.4.2 operator[]() [2/3]

```
template<std::floating_point T>
Vec3< T > && geom::Triangle< T >::operator[] (
    std::size_t idx ) &&
```

Overloaded operator[] to get access to vertices.

## Parameters

in	<i>idx</i>	index of vertex
----	------------	-----------------

## Returns

Vec3<T>&& reference to vertex

Definition at line 175 of file [triangle.hh](#).

#### 5.11.4.3 operator[]() [3/3]

```
template<std::floating_point T>
Vec3< T > & geom::Triangle< T >::operator[] (
    std::size_t idx ) &
```

Overloaded operator[] to get access to vertices.

##### Parameters

in	idx	index of vertex
----	-----	-----------------

##### Returns

Vec3<T>& reference to vertex

Definition at line 181 of file [triangle.hh](#).

#### 5.11.4.4 begin() [1/2]

```
template<std::floating_point T>
Triangle< T >::ConstIterator geom::Triangle< T >::begin
```

Get begin iterator.

##### Returns

Iterator

Definition at line 187 of file [triangle.hh](#).

Referenced by [geom::detail::helperMollerHaines\(\)](#), [geom::detail::isOnOneSide\(\)](#), and [geom::kdtree::KdTree< T >::isOnSide\(\)](#).

#### 5.11.4.5 end() [1/2]

```
template<std::floating_point T>
Triangle< T >::ConstIterator geom::Triangle< T >::end
```

Get end iterator.

##### Returns

Iterator

Definition at line 193 of file [triangle.hh](#).

Referenced by [geom::detail::helperMollerHaines\(\)](#), [geom::detail::isOnOneSide\(\)](#), and [geom::kdtree::KdTree< T >::isOnSide\(\)](#).

#### 5.11.4.6 begin() [2/2]

```
template<std::floating_point T>
ConstIterator geom::Triangle< T >::begin ( ) const &
```

Get begin const iterator.

##### Returns

ConstIterator

#### 5.11.4.7 end() [2/2]

```
template<std::floating_point T>
ConstIterator geom::Triangle< T >::end ( ) const &
```

Get end const iterator.

##### Returns

ConstIterator

#### 5.11.4.8 getPlane()

```
template<std::floating_point T>
Plane< T > geom::Triangle< T >::getPlane
```

Get triangle's plane.

##### Returns

Plane<T>

Definition at line 211 of file [triangle.hh](#).

References [geom::Plane< T >::getBy3Points\(\)](#).

Referenced by [geom::isIntersect\(\)](#), [geom::detail::isIntersect2D\(\)](#), [geom::detail::isIntersectMollerHaines\(\)](#), [geom::detail::isIntersectPointTriangle\(\)](#), and [geom::detail::isIntersectValidInvalid\(\)](#).

#### 5.11.4.9 isValid()

```
template<std::floating_point T>
bool geom::Triangle< T >::isValid
```

Check is triangle valid.

##### Returns

true if triangle is valid  
false if triangle is invalid

Definition at line 217 of file [triangle.hh](#).

References [geom::cross\(\)](#).

Referenced by [geom::isIntersect\(\)](#).

#### 5.11.4.10 boundBox()

```
template<std::floating_point T>
BoundingBox< T > geom::Triangle< T >::boundBox
```

Returns triangle's bound box.

##### Returns

`BoundingBox<T>`

Definition at line 227 of file [triangle.hh](#).

Referenced by [geom::kdtree::KdTree< T >::insert\(\)](#).

#### 5.11.4.11 belongsTo()

```
template<std::floating_point T>
bool geom::Triangle< T >::belongsTo (
    const BoundingBox< T > & bb ) const
```

Checks if this [Triangle](#) belongs to [BoundingBox](#).

##### Parameters

in	<i>bb</i>	<a href="#">BoundingBox</a>
----	-----------	-----------------------------

## Returns

- true if [Triangle](#) belongs to [BoundingBox](#)
- false if [Triangle](#) doesn't belong to [BoundingBox](#)

Definition at line 240 of file [triangle.hh](#).

Referenced by [geom::kdtree::KdTree< T >::insert\(\)](#).

The documentation for this class was generated from the following file:

- [include/primitives/triangle.hh](#)

## 5.12 geom::Vec2< T > Class Template Reference

[Vec2](#) class realization.

```
#include <vec2.hh>
```

### Public Member Functions

- [Vec2](#) (T coordX, T coordY)  
*Construct a new [Vec2](#) object from 3 coordinates.*
- [Vec2](#) (T coordX={})  
*Construct a new [Vec2](#) object with equals coordinates.*
- bool [operator==](#) (const [Vec2](#) &rhs) const  
*[Vec2](#) equality operator.*
- bool [operator!=](#) (const [Vec2](#) &rhs) const  
*[Vec2](#) equality operator.*
- [Vec2](#) & [operator+=](#) (const [Vec2](#) &vec)  
*Overloaded += operator Increments vector coordinates by corresponding coordinates of vec.*
- [Vec2](#) & [operator-=](#) (const [Vec2](#) &vec)  
*Overloaded -= operator Decrements vector coordinates by corresponding coordinates of vec.*
- [Vec2](#) [operator-](#) () const  
*Unary - operator.*
- template<Number nType>  
[Vec2](#) & [operator\\*=](#) (nType val)  
*Overloaded \*= by number operator.*
- template<Number nType>  
[Vec2](#) & [operator/=](#) (nType val)  
*Overloaded /= by number operator.*
- T [dot](#) (const [Vec2](#) &rhs) const  
*Dot product function.*
- T [length2](#) () const  
*Calculate squared length of a vector function.*
- T [length](#) () const  
*Calculate length of a vector function.*
- [Vec2](#) [getPerp](#) () const  
*Get the perpendicular to this vector.*
- [Vec2](#) [normalized](#) () const

- *Get normalized vector function.*
- [Vec2](#) & [normalize](#) () &
- *Normalize vector function.*
- T & [operator\[\]](#) (std::size\_t i) &
- *Overloaded operator [] (non-const version) To get access to coordinates.*
- T [operator\[\]](#) (std::size\_t i) const &
- *Overloaded operator [] (const version) To get access to coordinates.*
- T && [operator\[\]](#) (std::size\_t i) &&
- *Overloaded operator [] (const version) To get access to coordinates.*
- bool [isPar](#) (const [Vec2](#) &rhs) const
- *Check if vector is parallel to another.*
- bool [isPerp](#) (const [Vec2](#) &rhs) const
- *Check if vector is perpendicular to another.*
- bool [isEqual](#) (const [Vec2](#) &rhs) const
- *Check if vector is equal to another.*
- template<Number nType>
- [Vec2](#)< T > & [operator\\*="](#) (nType val)
- template<Number nType>
- [Vec2](#)< T > & [operator/="](#) (nType val)

## Public Attributes

- T [x](#) {}
- *[Vec2](#) coordinates.*
- T [y](#) {}

### 5.12.1 Detailed Description

```
template<std::floating_point T>
class geom::Vec2< T >
```

[Vec2](#) class realization.

Template Parameters

<a href="#">T</a>	- floating point type of coordinates
-------------------	--------------------------------------

Definition at line 26 of file [vec2.hh](#).

### 5.12.2 Constructor & Destructor Documentation

#### 5.12.2.1 [Vec2\(\)](#) [1/2]

```
template<std::floating_point T>
geom::Vec2< T >::Vec2 (
```

```
T coordX,
T coordY ) [inline]
```

Construct a new [Vec2](#) object from 3 coordinates.

#### Parameters

in	<i>coordX</i>	x coordinate
in	<i>coordY</i>	y coordinate

Definition at line 39 of file [vec2.hh](#).

#### 5.12.2.2 Vec2() [2/2]

```
template<std::floating_point T>
geom::Vec2< T >::Vec2 (
    T coordX = {} ) [inline], [explicit]
```

Construct a new [Vec2](#) object with equals coordinates.

#### Parameters

in	<i>coordX</i>	coordinate (default to {})
----	---------------	----------------------------

Definition at line 47 of file [vec2.hh](#).

### 5.12.3 Member Function Documentation

#### 5.12.3.1 operator==( )

```
template<std::floating_point T>
bool geom::Vec2< T >::operator== (
    const Vec2< T > & rhs ) const
```

[Vec2](#) equality operator.

#### Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

#### Parameters

in	<i>rhs</i>	second vector
----	------------	---------------

**Returns**

true if vectors are equal  
false otherwise

Definition at line 332 of file [vec2.hh](#).

**5.12.3.2 operator"!="()**

```
template<std::floating_point T>
bool geom::Vec2< T >::operator!= (
    const Vec2< T > & rhs ) const
```

[Vec2](#) equality operator.

**Template Parameters**

<i>T</i>	vector template parameter
----------	---------------------------

**Parameters**

<i>in</i>	<i>rhs</i>	second vector
-----------	------------	---------------

**Returns**

true if vectors are not equal  
false otherwise

Definition at line 338 of file [vec2.hh](#).

**5.12.3.3 operator+=()**

```
template<std::floating_point T>
Vec2< T > & geom::Vec2< T >::operator+= (
    const Vec2< T > & vec )
```

Overloaded += operator Increments vector coordinates by corresponding coordinates of vec.

**Parameters**

<i>in</i>	<i>vec</i>	vector to incremented with
-----------	------------	----------------------------

**Returns**

[Vec2](#)& reference to current instance



Definition at line 344 of file [vec2.hh](#).

References [geom::Vec2< T >::x](#), and [geom::Vec2< T >::y](#).

#### 5.12.3.4 operator-=( )

```
template<std::floating_point T>
Vec2< T > & geom::Vec2< T >::operator-= (
    const Vec2< T > & vec )
```

Overloaded -= operator Decrements vector coordinates by corresponding coordinates of vec.

##### Parameters

<code>in</code>	<code>vec</code>	vector to decremented with
-----------------	------------------	----------------------------

##### Returns

[Vec2](#)& reference to current instance

Definition at line 353 of file [vec2.hh](#).

References [geom::Vec2< T >::x](#), and [geom::Vec2< T >::y](#).

#### 5.12.3.5 operator-( )

```
template<std::floating_point T>
Vec2< T > geom::Vec2< T >::operator-
```

Unary - operator.

##### Returns

[Vec2](#) negated [Vec2](#) instance

Definition at line 362 of file [vec2.hh](#).

#### 5.12.3.6 operator\*=( ) [1/2]

```
template<std::floating_point T>
template<Number nType>
Vec2& geom::Vec2< T >::operator*= (
    nType val )
```

Overloaded \*= by number operator.

**Template Parameters**

<i>nType</i>	numeric type of value to multiply by
--------------	--------------------------------------

**Parameters**

<i>in</i>	<i>val</i>	value to multiply by
-----------	------------	----------------------

**Returns**

[Vec2](#)& reference to vector instance

**5.12.3.7 operator/=() [1/2]**

```
template<std::floating_point T>
template<Number nType>
Vec2& geom::Vec2< T >::operator/= (
    nType val )
```

Overloaded /= by number operator.

**Template Parameters**

<i>nType</i>	numeric type of value to divide by
--------------	------------------------------------

**Parameters**

<i>in</i>	<i>val</i>	value to divide by
-----------	------------	--------------------

**Returns**

[Vec2](#)& reference to vector instance

**Warning**

Does not check if val equals 0

**5.12.3.8 dot()**

```
template<std::floating_point T>
T geom::Vec2< T >::dot (
    const Vec2< T > & rhs ) const
```

Dot product function.

## Parameters

<i>rhs</i>	vector to dot product with
------------	----------------------------

## Returns

T dot product of two vectors

Definition at line 388 of file [vec2.hh](#).

References [geom::Vec2< T >::x](#), and [geom::Vec2< T >::y](#).

Referenced by [geom::dot\(\)](#).

### 5.12.3.9 length2()

```
template<std::floating_point T>
T geom::Vec2< T >::length2
```

Calculate squared length of a vector function.

## Returns

T length<sup>2</sup>

Definition at line 394 of file [vec2.hh](#).

References [geom::dot\(\)](#).

### 5.12.3.10 length()

```
template<std::floating_point T>
T geom::Vec2< T >::length
```

Calculate length of a vector function.

## Returns

T length

Definition at line 400 of file [vec2.hh](#).

#### 5.12.3.11 getPerp()

```
template<std::floating_point T>
Vec2< T > geom::Vec2< T >::getPerp
```

Get the perpendicular to this vector.

##### Returns

[Vec2](#) perpendicular vector

Definition at line 406 of file [vec2.hh](#).

#### 5.12.3.12 normalized()

```
template<std::floating_point T>
Vec2< T > geom::Vec2< T >::normalized
```

Get normalized vector function.

##### Returns

[Vec2](#) normalized vector

Definition at line 412 of file [vec2.hh](#).

References [geom::Vec2< T >::normalize\(\)](#).

#### 5.12.3.13 normalize()

```
template<std::floating_point T>
Vec2< T > & geom::Vec2< T >::normalize
```

Normalize vector function.

##### Returns

[Vec2](#)& reference to instance

Definition at line 420 of file [vec2.hh](#).

References [geom::isEqualThreshold\(\)](#), and [geom::isZeroThreshold\(\)](#).

Referenced by [geom::Vec2< T >::normalized\(\)](#).

#### 5.12.3.14 operator[]() [1/3]

```
template<std::floating_point T>
T & geom::Vec2< T >::operator[] (
    std::size_t i ) &
```

Overloaded operator [] (non-const version) To get access to coordinates.

**Parameters**

<i>i</i>	index of coordinate (0 - x, 1 - y)
----------	------------------------------------

**Returns**

T& reference to coordinate value

**Note**

Coordinates calculated by mod 2

Definition at line 429 of file [vec2.hh](#).

**5.12.3.15 operator[]() [2/3]**

```
template<std::floating_point T>
T geom::Vec2< T >::operator[] (
    std::size_t i ) const &
```

Overloaded operator [] (const version) To get access to coordinates.

**Parameters**

<i>i</i>	index of coordinate (0 - x, 1 - y)
----------	------------------------------------

**Returns**

T coordinate value

**Note**

Coordinates calculated by mod 2

Definition at line 443 of file [vec2.hh](#).

**5.12.3.16 operator[]() [3/3]**

```
template<std::floating_point T>
T && geom::Vec2< T >::operator[] (
    std::size_t i ) &&
```

Overloaded operator [] (const version) To get access to coordinates.

**Parameters**

<i>i</i>	index of coordinate (0 - x, 1 - y)
----------	------------------------------------

**Returns**

T coordinate value

**Note**

Coordinates calculated by mod 2

Definition at line 457 of file [vec2.hh](#).

**5.12.3.17 isPar()**

```
template<std::floating_point T>
bool geom::Vec2< T >::isPar (
    const Vec2< T > & rhs ) const
```

Check if vector is parallel to another.

**Parameters**

<i>in</i>	<i>rhs</i>	vector to check parallelism with
-----------	------------	----------------------------------

**Returns**

true if vector is parallel  
false otherwise

Definition at line 471 of file [vec2.hh](#).

References [geom::isZeroThreshold\(\)](#), [geom::Vec2< T >::x](#), and [geom::Vec2< T >::y](#).

**5.12.3.18 isPerp()**

```
template<std::floating_point T>
bool geom::Vec2< T >::isPerp (
    const Vec2< T > & rhs ) const
```

Check if vector is perpendicular to another.

## Parameters

<code>in</code>	<code>rhs</code>	vector to check perpendicularity with
-----------------	------------------	---------------------------------------

## Returns

true if vector is perpendicular  
false otherwise

Definition at line 478 of file [vec2.hh](#).

References [geom::dot\(\)](#), and [geom::isZeroThreshold\(\)](#).

**5.12.3.19 isEqual()**

```
template<std::floating_point T>
bool geom::Vec2< T >::isEqual (
    const Vec2< T > & rhs ) const
```

Check if vector is equal to another.

## Parameters

<code>in</code>	<code>rhs</code>	vector to check equality with
-----------------	------------------	-------------------------------

## Returns

true if vector is equal  
false otherwise

Definition at line 484 of file [vec2.hh](#).

References [geom::isEqualThreshold\(\)](#), [geom::Vec2< T >::x](#), and [geom::Vec2< T >::y](#).

**5.12.3.20 operator\*=( ) [2/2]**

```
template<std::floating_point T>
template<Number nType>
Vec2<T>& geom::Vec2< T >::operator*= (
    nType val )
```

Definition at line 369 of file [vec2.hh](#).

### 5.12.3.21 operator/=( ) [2/2]

```
template<std::floating_point T>
template<Number nType>
Vec2<T>& geom::Vec2< T >::operator/= (
    nType val )
```

Definition at line 379 of file [vec2.hh](#).

## 5.12.4 Member Data Documentation

### 5.12.4.1 x

```
template<std::floating_point T>
T geom::Vec2< T >::x {}
```

[Vec2](#) coordinates.

Definition at line 31 of file [vec2.hh](#).

Referenced by [geom::Vec2< T >::dot\(\)](#), [geom::Vec2< T >::isEqual\(\)](#), [geom::Vec2< T >::isPar\(\)](#), [geom::Vec2< T >::operator+=\( \)](#), [geom::Vec2< T >::operator-=\(\)](#), and [geom::operator<<\(\)](#).

### 5.12.4.2 y

```
template<std::floating_point T>
T geom::Vec2< T >::y {}
```

Definition at line 31 of file [vec2.hh](#).

Referenced by [geom::Vec2< T >::dot\(\)](#), [geom::Vec2< T >::isEqual\(\)](#), [geom::Vec2< T >::isPar\(\)](#), [geom::Vec2< T >::operator+=\( \)](#), [geom::Vec2< T >::operator-=\(\)](#), and [geom::operator<<\(\)](#).

The documentation for this class was generated from the following file:

- [include/primitives/vec2.hh](#)

## 5.13 geom::Vec3< T > Class Template Reference

[Vec3](#) class realization.

```
#include <vec3.hh>
```



## Public Member Functions

- [Vec3](#) (T coordX, T coordY, T coordZ)  
*Construct a new [Vec3](#) object from 3 coordinates.*
- [Vec3](#) (T coordX={})  
*Construct a new [Vec3](#) object with equals coordinates.*
- bool [operator==](#) (const [Vec3](#) &rhs) const  
*[Vec3](#) equality operator.*
- bool [operator!=](#) (const [Vec3](#) &rhs) const  
*[Vec3](#) inequality operator.*
- [Vec3](#) & [operator+=](#) (const [Vec3](#) &vec)  
*Overloaded += operator Increments vector coordinates by corresponding coordinates of vec.*
- [Vec3](#) & [operator-=](#) (const [Vec3](#) &vec)  
*Overloaded -= operator Decrements vector coordinates by corresponding coordinates of vec.*
- [Vec3](#) [operator-](#) () const  
*Unary - operator.*
- template<Number nType>  
[Vec3](#) & [operator\\*==](#) (nType val)  
*Overloaded \*= by number operator.*
- template<Number nType>  
[Vec3](#) & [operator/=](#) (nType val)  
*Overloaded /= by number operator.*
- T [dot](#) (const [Vec3](#) &rhs) const  
*Dot product function.*
- [Vec3](#) [cross](#) (const [Vec3](#) &rhs) const  
*Cross product function.*
- T [length2](#) () const  
*Calculate squared length of a vector function.*
- T [length](#) () const  
*Calculate length of a vector function.*
- [Vec3](#) [normalized](#) () const  
*Get normalized vector function.*
- [Vec3](#) & [normalize](#) () &  
*Normalize vector function.*
- T & [operator\[\]](#) (std::size\_t i) &  
*Overloaded operator [] (non-const version) To get access to coordinates.*
- T [operator\[\]](#) (std::size\_t i) const &  
*Overloaded operator [] (const version) To get access to coordinates.*
- T && [operator\[\]](#) (std::size\_t i) &&  
*Overloaded operator [] (rvalue *this* version) To get access to coordinates.*
- bool [isPar](#) (const [Vec3](#) &rhs) const  
*Check if vector is parallel to another.*
- bool [isPerp](#) (const [Vec3](#) &rhs) const  
*Check if vector is perpendicular to another.*
- bool [isEqual](#) (const [Vec3](#) &rhs) const  
*Check if vector is equal to another.*
- template<Number nType>  
[Vec3](#)< T > & [operator\\*==](#) (nType val)
- template<Number nType>  
[Vec3](#)< T > & [operator/=](#) (nType val)

## Public Attributes

- `T x {}`  
*Vec3 coordinates.*
- `T y {}`
- `T z {}`

### 5.13.1 Detailed Description

```
template<std::floating_point T>
class geom::Vec3< T >
```

[Vec3](#) class realization.

#### Template Parameters

<i>T</i>	- floating point type of coordinates
----------	--------------------------------------

Definition at line 26 of file [vec3.hh](#).

### 5.13.2 Constructor & Destructor Documentation

#### 5.13.2.1 Vec3() [1/2]

```
template<std::floating_point T>
geom::Vec3< T >::Vec3 (
    T coordX,
    T coordY,
    T coordZ ) [inline]
```

Construct a new [Vec3](#) object from 3 coordinates.

#### Parameters

in	<i>coordX</i>	x coordinate
in	<i>coordY</i>	y coordinate
in	<i>coordZ</i>	z coordinate

Definition at line 40 of file [vec3.hh](#).

#### 5.13.2.2 Vec3() [2/2]

```
template<std::floating_point T>
geom::Vec3< T >::Vec3 (
    T coordX = {} ) [inline], [explicit]
```

Construct a new [Vec3](#) object with equals coordinates.

#### Parameters

in	<i>coordX</i>	coordinate (default to {})
----	---------------	----------------------------

Definition at line 48 of file [vec3.hh](#).

## 5.13.3 Member Function Documentation

### 5.13.3.1 operator==( )

```
template<std::floating_point T>
bool geom::Vec3< T >::operator==(
    const Vec3< T > & rhs ) const
```

[Vec3](#) equality operator.

#### Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

#### Parameters

in	<i>rhs</i>	second vector
----	------------	---------------

#### Returns

true if vectors are equal  
false otherwise

Definition at line 378 of file [vec3.hh](#).

### 5.13.3.2 operator!=( )

```
template<std::floating_point T>
bool geom::Vec3< T >::operator!=(
    const Vec3< T > & rhs ) const
```

[Vec3](#) inequality operator.

### Template Parameters

<i>T</i>	vector template parameter
----------	---------------------------

### Parameters

<i>in</i>	<i>rhs</i>	second vector
-----------	------------	---------------

### Returns

true if vectors are not equal  
false otherwise

Definition at line 384 of file [vec3.hh](#).

#### 5.13.3.3 operator+=()

```
template<std::floating_point T>
Vec3< T > & geom::Vec3< T >::operator+= (
    const Vec3< T > & vec )
```

Overloaded += operator Increments vector coordinates by corresponding coordinates of vec.

### Parameters

<i>in</i>	<i>vec</i>	vector to incremented with
-----------	------------	----------------------------

### Returns

[Vec3](#)& reference to current instance

Definition at line 390 of file [vec3.hh](#).

References [geom::Vec3< T >::x](#), [geom::Vec3< T >::y](#), and [geom::Vec3< T >::z](#).

#### 5.13.3.4 operator-=()

```
template<std::floating_point T>
Vec3< T > & geom::Vec3< T >::operator-= (
    const Vec3< T > & vec )
```

Overloaded -= operator Decrements vector coordinates by corresponding coordinates of vec.

## Parameters

<i>in</i>	<i>vec</i>	vector to decremented with
-----------	------------	----------------------------

## Returns

[Vec3](#)& reference to current instance

Definition at line 400 of file [vec3.hh](#).

References [geom::Vec3< T >::x](#), [geom::Vec3< T >::y](#), and [geom::Vec3< T >::z](#).

## 5.13.3.5 operator-()

```
template<std::floating_point T>
Vec3< T > geom::Vec3< T >::operator-
```

Unary - operator.

## Returns

[Vec3](#) negated [Vec3](#) instance

Definition at line 410 of file [vec3.hh](#).

## 5.13.3.6 operator\*=( ) [1/2]

```
template<std::floating_point T>
template<Number nType>
Vec3& geom::Vec3< T >::operator*= (
    nType val )
```

Overloaded \*= by number operator.

## Template Parameters

<i>nType</i>	numeric type of value to multiply by
--------------	--------------------------------------

## Parameters

<i>in</i>	<i>val</i>	value to multiply by
-----------	------------	----------------------

**Returns**

[Vec3](#)& reference to vector instance

**5.13.3.7 operator/=( ) [1/2]**

```
template<std::floating_point T>
template<Number nType>
Vec3& geom::Vec3< T >::operator/= (
    nType val )
```

Overloaded /= by number operator.

**Template Parameters**

<i>nType</i>	numeric type of value to divide by
--------------	------------------------------------

**Parameters**

<i>in</i>	<i>val</i>	value to divide by
-----------	------------	--------------------

**Returns**

[Vec3](#)& reference to vector instance

**Warning**

Does not check if val equals 0

**5.13.3.8 dot()**

```
template<std::floating_point T>
T geom::Vec3< T >::dot (
    const Vec3< T > & rhs ) const
```

Dot product function.

**Parameters**

<i>rhs</i>	vector to dot product with
------------	----------------------------

**Returns**

T dot product of two vectors

Definition at line 440 of file [vec3.hh](#).

References [geom::Vec3< T >::x](#), [geom::Vec3< T >::y](#), and [geom::Vec3< T >::z](#).

Referenced by [geom::dot\(\)](#).

#### 5.13.3.9 cross()

```
template<std::floating_point T>
Vec3< T > geom::Vec3< T >::cross (
    const Vec3< T > & rhs ) const
```

Cross product function.

##### Parameters

<i>rhs</i>	vector to cross product with
------------	------------------------------

##### Returns

[Vec3](#) cross product of two vectors

Definition at line 446 of file [vec3.hh](#).

References [geom::Vec3< T >::x](#), [geom::Vec3< T >::y](#), and [geom::Vec3< T >::z](#).

Referenced by [geom::cross\(\)](#), and [geom::Plane< T >::getParametric\(\)](#).

#### 5.13.3.10 length2()

```
template<std::floating_point T>
T geom::Vec3< T >::length2
```

Calculate squared length of a vector function.

##### Returns

$T \text{ length}^2$

Definition at line 452 of file [vec3.hh](#).

References [geom::dot\(\)](#).

#### 5.13.3.11 length()

```
template<std::floating_point T>
T geom::Vec3< T >::length
```

Calculate length of a vector function.

##### Returns

T length

Definition at line 458 of file [vec3.hh](#).

#### 5.13.3.12 normalized()

```
template<std::floating_point T>
Vec3< T > geom::Vec3< T >::normalized
```

Get normalized vector function.

##### Returns

[Vec3](#) normalized vector

Definition at line 464 of file [vec3.hh](#).

References [geom::Vec3< T >::normalize\(\)](#).

Referenced by [geom::Plane< T >::getNormalDist\(\)](#), and [geom::Plane< T >::getNormalPoint\(\)](#).

#### 5.13.3.13 normalize()

```
template<std::floating_point T>
Vec3< T > & geom::Vec3< T >::normalize
```

Normalize vector function.

##### Returns

[Vec3](#)& reference to instance

Definition at line 472 of file [vec3.hh](#).

References [geom::isEqualThreshold\(\)](#), and [geom::isZeroThreshold\(\)](#).

Referenced by [geom::Vec3< T >::normalized\(\)](#).

#### 5.13.3.14 operator[]() [1/3]

```
template<std::floating_point T>
T & geom::Vec3< T >::operator[] (
    std::size_t i ) &
```

Overloaded operator [] (non-const version) To get access to coordinates.



## Parameters

<i>i</i>	index of coordinate (0 - x, 1 - y, 2 - z)
----------	---

## Returns

T& reference to coordinate value

## Note

Coordinates calculated by mod 3

Definition at line 481 of file [vec3.hh](#).

**5.13.3.15 operator[]() [2/3]**

```
template<std::floating_point T>
T geom::Vec3< T >::operator[] (
    std::size_t i ) const &
```

Overloaded operator [] (const version) To get access to coordinates.

## Parameters

<i>i</i>	index of coordinate (0 - x, 1 - y, 2 - z)
----------	---

## Returns

T coordinate value

## Note

Coordinates calculated by mod 3

Definition at line 497 of file [vec3.hh](#).

**5.13.3.16 operator[]() [3/3]**

```
template<std::floating_point T>
T && geom::Vec3< T >::operator[] (
    std::size_t i ) &&
```

Overloaded operator [] (rvalue this version) To get access to coordinates.

**Parameters**

<i>i</i>	index of coordinate (0 - x, 1 - y, 2 - z)
----------	---

**Returns**

T coordinate value

**Note**

Coordinates calculated by mod 3

Definition at line 513 of file [vec3.hh](#).

**5.13.3.17 isPar()**

```
template<std::floating_point T>
bool geom::Vec3< T >::isPar (
    const Vec3< T > & rhs ) const
```

Check if vector is parallel to another.

**Parameters**

<i>in</i>	<i>rhs</i>	vector to check parallelism with
-----------	------------	----------------------------------

**Returns**

true if vector is parallel  
false otherwise

Definition at line 529 of file [vec3.hh](#).

References [geom::cross\(\)](#).

**5.13.3.18 isPerp()**

```
template<std::floating_point T>
bool geom::Vec3< T >::isPerp (
    const Vec3< T > & rhs ) const
```

Check if vector is perpendicular to another.

## Parameters

<i>in</i>	<i>rhs</i>	vector to check perpendicularity with
-----------	------------	---------------------------------------

## Returns

true if vector is perpendicular  
false otherwise

Definition at line 535 of file [vec3.hh](#).

References [geom::dot\(\)](#), and [geom::isZeroThreshold\(\)](#).

**5.13.3.19 isEqual()**

```
template<std::floating_point T>
bool geom::Vec3< T >::isEqual (
    const Vec3< T > & rhs ) const
```

Check if vector is equal to another.

## Parameters

<i>in</i>	<i>rhs</i>	vector to check equality with
-----------	------------	-------------------------------

## Returns

true if vector is equal  
false otherwise

Definition at line 541 of file [vec3.hh](#).

References [geom::isEqualThreshold\(\)](#), [geom::Vec3< T >::x](#), [geom::Vec3< T >::y](#), and [geom::Vec3< T >::z](#).

**5.13.3.20 operator\*=( ) [2/2]**

```
template<std::floating_point T>
template<Number nType>
Vec3<T>& geom::Vec3< T >::operator*= (
    nType val )
```

Definition at line 417 of file [vec3.hh](#).

### 5.13.3.21 operator/=( ) [2/2]

```
template<std::floating_point T>
template<Number nType>
Vec3<T>& geom::Vec3< T >::operator/= (
    nType val )
```

Definition at line 429 of file [vec3.hh](#).

## 5.13.4 Member Data Documentation

### 5.13.4.1 x

```
template<std::floating_point T>
T geom::Vec3< T >::x {}
```

[Vec3](#) coordinates.

Definition at line 31 of file [vec3.hh](#).

Referenced by [geom::Vec3< T >::cross\(\)](#), [geom::Vec3< T >::dot\(\)](#), [geom::Vec3< T >::isEqual\(\)](#), [geom::Vec3< T >::operator+=\( \)](#), [geom::Vec3< T >::operator-=\(\)](#), [geom::operator<<\(\)](#), and [geom::operator>>\(\)](#).

### 5.13.4.2 y

```
template<std::floating_point T>
T geom::Vec3< T >::y {}
```

Definition at line 31 of file [vec3.hh](#).

Referenced by [geom::Vec3< T >::cross\(\)](#), [geom::Vec3< T >::dot\(\)](#), [geom::Vec3< T >::isEqual\(\)](#), [geom::Vec3< T >::operator+=\( \)](#), [geom::Vec3< T >::operator-=\(\)](#), [geom::operator<<\(\)](#), and [geom::operator>>\(\)](#).

### 5.13.4.3 z

```
template<std::floating_point T>
T geom::Vec3< T >::z {}
```

Definition at line 31 of file [vec3.hh](#).

Referenced by [geom::Vec3< T >::cross\(\)](#), [geom::Vec3< T >::dot\(\)](#), [geom::Vec3< T >::isEqual\(\)](#), [geom::Vec3< T >::operator+=\( \)](#), [geom::Vec3< T >::operator-=\(\)](#), [geom::operator<<\(\)](#), and [geom::operator>>\(\)](#).

The documentation for this class was generated from the following file:

- [include/primitives/vec3.hh](#)


## Chapter 6

# File Documentation


### 6.1 include/distance/distance.hh File Reference

```
#include "primitives/primitives.hh"
```

Include dependency graph for distance.hh:



This graph shows which files directly or indirectly include this file:



## Namespaces

- [geom](#)  
*line.hh Line class implementation*

## Functions

- `template<std::floating_point T>`  
`T geom::distance(const Plane< T > &pl, const Vec3< T > &pt)`  
*Calculates signed distance between point and plane.*

## 6.2 distance.hh

```

00001 #ifndef __INCLUDE_DISTANCE_DISTANCE_HH__
00002 #define __INCLUDE_DISTANCE_DISTANCE_HH__
00003
00004 #include "primitives/primitives.hh"
00005
00006 namespace geom
00007 {
00008
00009 /**
00010  * @brief Calculates signed distance between point and plane
00011  *
00012  * @tparam T - floating point type of coordinates
00013  * @param pl plane
00014  * @param pt point
00015  * @return T signed distance between point and plane
00016  */
00017 template <std::floating_point T>
00018 T distance(const Plane<T> &pl, const Vec3<T> &pt);
00019
00020 } // namespace geom
00021
00022 namespace geom
00023 {
00024
00025 template <std::floating_point T>
  
```

```

00026 T distance(const Plane<T> &pl, const Vec3<T> &pt)
00027 {
00028     return dot(pt, pl.norm()) - pl.dist();
00029 }
00030
00031 } // namespace geom
00032
00033 #endif // __INCLUDE_DISTANCE_DISTANCE_HH__

```


## 6.3 include/intersection/detail.hh File Reference

```


#include <concepts>
#include <variant>
#include "distance/distance.hh"
#include "primitives/primitives.hh"
#include "primitives/vec2.hh"

```

Include dependency graph for detail.hh:



This graph shows which files directly or indirectly include this file:



## Namespaces

- [geom](#)  
     *line.hh Line class implementation*
- [geom::detail](#)

## Typedefs

- `template<typename T>`  
   using [geom::detail::Segment2D](#) = `std::pair< T, T >`
- `template<std::floating_point T>`  
   using [geom::detail::Trian2](#) = `std::array< Vec2< T >, 3 >`
- `template<std::floating_point T>`  
   using [geom::detail::Segment3D](#) = `std::pair< Vec3< T >, Vec3< T > >`

## Functions

- `template<std::floating_point T>`  
   bool [geom::detail::isIntersect2D](#) (const Triangle< T > &tr1, const Triangle< T > &tr2)
- `template<std::floating_point T>`  
   bool [geom::detail::isIntersectMollerHaines](#) (const Triangle< T > &tr1, const Triangle< T > &tr2)
- `template<std::floating_point T>`  
   Segment2D< T > [geom::detail::helperMollerHaines](#) (const Triangle< T > &tr, const Plane< T > &pl, const Line< T > &l)
- `template<std::floating_point T>`  
   bool [geom::detail::isIntersectBothInvalid](#) (const Triangle< T > &tr1, const Triangle< T > &tr2)
- `template<std::floating_point T>`  
   bool [geom::detail::isIntersectValidInvalid](#) (const Triangle< T > &valid, const Triangle< T > &invalid)
- `template<std::floating_point T>`  
   bool [geom::detail::isIntersectPointTriangle](#) (const Vec3< T > &pt, const Triangle< T > &tr)
- `template<std::floating_point T>`  
   bool [geom::detail::isIntersectPointSegment](#) (const Vec3< T > &pt, const Segment3D< T > &segm)
- `template<std::floating_point T>`  
   bool [geom::detail::isIntersectSegmentSegment](#) (const Segment3D< T > &segm1, const Segment3D< T > &segm2)



- `template<std::floating_point T>`  
`bool geom::detail::isPoint (const Triangle< T > &tr)`
- `template<std::floating_point T>`  
`bool geom::detail::isOverlap (Segment2D< T > &segm1, Segment2D< T > &segm2)`
- `template<std::forward_iterator It>`  
`bool geom::detail::isAllPosNeg (It begin, It end)`
- `template<std::floating_point T>`  
`bool geom::detail::isAllPosNeg (T num1, T num2)`
- `template<std::floating_point T>`  
`bool geom::detail::isOnOneSide (const Plane< T > &pl, const Triangle< T > &tr)`
- `template<std::floating_point T>`  
`Trian2< T > geom::detail::getTrian2 (const Plane< T > &pl, const Triangle< T > &tr)`
- `template<std::floating_point T>`  
`bool geom::detail::isCounterClockwise (Trian2< T > &tr)`
- `template<std::floating_point T>`  
`Segment2D< T > geom::detail::computeInterval (const Trian2< T > &tr, const Vec2< T > &d)`
- `template<std::floating_point T>`  
`Segment3D< T > geom::detail::getSegment (const Triangle< T > &tr)`
- `template<std::bidirectional_iterator It>`  
`std::size_t geom::detail::roguePos (It begin, It end)`

## 6.4 detail.hh

```

00001 #ifndef __INCLUDE_INTERSECTION_DETAIL_HH__
00002 #define __INCLUDE_INTERSECTION_DETAIL_HH__
00003
00004 #include <concepts>
00005 #include <variant>
00006
00007 #include "distance/distance.hh"
00008 #include "primitives/primitives.hh"
00009 #include "primitives/vec2.hh"
00010
00011 namespace geom::detail
00012 {
00013
00014 template <typename T>
00015 using Segment2D = std::pair<T, T>;
00016
00017 template <std::floating_point T>
00018 using Trian2 = std::array<Vec2<T>, 3>;
00019
00020 template <std::floating_point T>
00021 using Segment3D = std::pair<Vec3<T>, Vec3<T>>;
00022
00023 template <std::floating_point T>
00024 bool isIntersect2D(const Triangle<T> &tr1, const Triangle<T> &tr2);
00025
00026 template <std::floating_point T>
00027 bool isIntersectMollerHaines(const Triangle<T> &tr1, const Triangle<T> &tr2);
00028
00029 template <std::floating_point T>
00030 Segment2D<T> helperMollerHaines(const Triangle<T> &tr, const Plane<T> &pl, const Line<T> &l);
00031
00032 template <std::floating_point T>
00033 bool isIntersectBothInvalid(const Triangle<T> &tr1, const Triangle<T> &tr2);
00034
00035 template <std::floating_point T>
00036 bool isIntersectValidInvalid(const Triangle<T> &valid, const Triangle<T> &invalid);
00037
00038 template <std::floating_point T>
00039 bool isIntersectPointTriangle(const Vec3<T> &pt, const Triangle<T> &tr);
00040
00041 template <std::floating_point T>
00042 bool isIntersectPointSegment(const Vec3<T> &pt, const Segment3D<T> &segm);
00043
00044 template <std::floating_point T>
00045 bool isIntersectSegmentSegment(const Segment3D<T> &segm1, const Segment3D<T> &segm2);
00046
00047 template <std::floating_point T>
00048 bool isPoint(const Triangle<T> &tr);
00049
00050 template <std::floating_point T>

```

```

00051 bool isOverlap(Segment2D<T> &segm1, Segment2D<T> &segm2);
00052
00053 template <std::forward_iterator It>
00054 bool isAllPosNeg(It begin, It end);
00055
00056 template <std::floating_point T>
00057 bool isAllPosNeg(T num1, T num2);
00058
00059 template <std::floating_point T>
00060 bool isOnOneSide(const Plane<T> &pl, const Triangle<T> &tr);
00061
00062 template <std::floating_point T>
00063 Trian2<T> getTrian2(const Plane<T> &pl, const Triangle<T> &tr);
00064
00065 template <std::floating_point T>
00066 bool isCounterClockwise(Trian2<T> &tr);
00067
00068 template <std::floating_point T>
00069 Segment2D<T> computeInterval(const Trian2<T> &tr, const Vec2<T> &d);
00070
00071 template <std::floating_point T>
00072 Segment3D<T> getSegment(const Triangle<T> &tr);
00073
00074 template <std::bidirectional_iterator It>
00075 std::size_t roguePos(It begin, It end);
00076
00077 //=====
00078
00079 template <std::floating_point T>
00080 bool isIntersect2D(const Triangle<T> &tr1, const Triangle<T> &tr2)
00081 {
00082     auto pl = tr1.getPlane();
00083
00084     auto trian1 = getTrian2(pl, tr1);
00085     auto trian2 = getTrian2(pl, tr2);
00086
00087     for (auto trian : {trian1, trian2})
00088         for (std::size_t i0 = 0, i1 = 2; i0 < 3; i1 = i0, ++i0)
00089         {
00090             auto d = (trian[i0] - trian[i1]).getPerp();
00091
00092             auto s1 = computeInterval(trian1, d);
00093             auto s2 = computeInterval(trian2, d);
00094
00095             if (s2.second < s1.first || s1.second < s2.first)
00096                 return false;
00097         }
00098
00099     return true;
00100 }
00101
00102 template <std::floating_point T>
00103 bool isIntersectMollerHaines(const Triangle<T> &tr1, const Triangle<T> &tr2)
00104 {
00105     auto pl1 = tr1.getPlane();
00106     auto pl2 = tr2.getPlane();
00107
00108     auto l = std::get<Line<T>>(intersect(pl1, pl2));
00109
00110     auto params1 = helperMollerHaines(tr1, pl2, l);
00111     auto params2 = helperMollerHaines(tr2, pl1, l);
00112
00113     return isOverlap(params1, params2);
00114 }
00115
00116 template <std::floating_point T>
00117 Segment2D<T> helperMollerHaines(const Triangle<T> &tr, const Plane<T> &pl, const Line<T> &l)
00118 {
00119     /* Project the triangle vertices onto line */
00120     std::array<T, 3> vert{};
00121     std::transform(tr.begin(), tr.end(), vert.begin(),
00122         [dir = l.dir(), org = l.org()](auto &&v) { return dot(dir, v - org); });
00123
00124     std::array<T, 3> sdist{};
00125     std::transform(tr.begin(), tr.end(), sdist.begin(), std::bind_front(distance<T>, pl));
00126
00127     /* Looking for vertex which is alone on it's side */
00128     std::size_t rogue = roguePos(sdist.begin(), sdist.end());
00129
00130     std::array<T, 2> segm{};
00131     std::array<size_t, 2> arr{(rogue + 1) % 3, (rogue + 2) % 3};
00132     std::transform(arr.begin(), arr.end(), segm.begin(), [&vert, &sdist, rogue](auto i) {
00133         return vert[i] + (vert[rogue] - vert[i]) * sdist[i] / (sdist[i] - sdist[rogue]);
00134     });
00135
00136     return std::minmax(segm[0], segm[1]);
00137 }

```

```

00138
00139 template <std::floating_point T>
00140 bool isIntersectBothInvalid(const Triangle<T> &tr1, const Triangle<T> &tr2)
00141 {
00142     auto isPoint1 = isPoint(tr1);
00143     auto isPoint2 = isPoint(tr2);
00144
00145     if (isPoint1 && isPoint2)
00146         return tr1[0] == tr2[0];
00147
00148     if (isPoint1)
00149         return isIntersectPointSegment(tr1[0], getSegment(tr2));
00150
00151     if (isPoint2)
00152         return isIntersectPointSegment(tr2[0], getSegment(tr1));
00153
00154     return isIntersectSegmentSegment(getSegment(tr1), getSegment(tr2));
00155 }
00156
00157 template <std::floating_point T>
00158 bool isIntersectValidInvalid(const Triangle<T> &valid, const Triangle<T> &invalid)
00159 {
00160     if (isPoint(invalid))
00161         return isIntersectPointTriangle(invalid[0], valid);
00162
00163     auto segm = getSegment(invalid);
00164     auto pl = valid.getPlane();
00165
00166     auto dst1 = distance(pl, segm.first);
00167     auto dst2 = distance(pl, segm.second);
00168
00169     if (dst1 * dst2 > 0)
00170         return false;
00171
00172     if (isZeroThreshold(dst1) && isZeroThreshold(dst2))
00173         return isIntersect2D(valid, invalid);
00174
00175     dst1 = std::abs(dst1);
00176     dst2 = std::abs(dst2);
00177
00178     auto pt = segm.first + (segm.second - segm.first) * dst1 / (dst1 + dst2);
00179     return isIntersectPointTriangle(pt, valid);
00180 }
00181
00182 template <std::floating_point T>
00183 bool isIntersectPointTriangle(const Vec3<T> &pt, const Triangle<T> &tr)
00184 {
00185     if (!tr.getPlane().belongs(pt))
00186         return false;
00187
00188     /* TODO: comment better */
00189     /* pt = point + u * edge1 + v * edge2 */
00190     auto point = pt - tr[0];
00191     auto edge1 = tr[1] - tr[0];
00192     auto edge2 = tr[2] - tr[0];
00193
00194     auto dotE1E1 = dot(edge1, edge1);
00195     auto dotE1E2 = dot(edge1, edge2);
00196     auto dotE1PT = dot(edge1, point);
00197
00198     auto dotE2E2 = dot(edge2, edge2);
00199     auto dotE2PT = dot(edge2, point);
00200
00201     auto denom = dotE1E1 * dotE2E2 - dotE1E2 * dotE1E2;
00202     auto u = (dotE2E2 * dotE1PT - dotE1E2 * dotE2PT) / denom;
00203     auto v = (dotE1E1 * dotE2PT - dotE1E2 * dotE1PT) / denom;
00204
00205     /* Point belongs to triangle if: (u >= 0) && (v >= 0) && (u + v <= 1) */
00206     auto eps = ThresComp<T>::getThreshold();
00207     return (u > -eps) && (v > -eps) && (u + v < 1 + eps);
00208 }
00209
00210 template <std::floating_point T>
00211 bool isIntersectPointSegment(const Vec3<T> &pt, const Segment3D<T> &segm)
00212 {
00213     Line<T> l{segm.first, segm.second - segm.first};
00214     if (!l.belongs(pt))
00215         return false;
00216
00217     auto beg = dot(l.dir(), segm.first - pt);
00218     auto end = dot(l.dir(), segm.second - pt);
00219
00220     return !isAllPosNeg(beg, end);
00221 }
00222
00223 template <std::floating_point T>
00224 bool isIntersectSegmentSegment(const Segment3D<T> &segm1, const Segment3D<T> &segm2)

```

```

00225 {
00226     Line<T> l1{segm1.first, segm1.second - segm1.first};
00227     Line<T> l2{segm2.first, segm2.second - segm2.first};
00228     auto intersectionResult = intersect(l1, l2);
00229
00230     if (std::holds_alternative<Line<T>>(intersectionResult))
00231     {
00232         const auto &dir = l1.dir();
00233         Segment2D<T> s1{dot(dir, segm1.first), dot(dir, segm1.second)};
00234         Segment2D<T> s2{dot(dir, segm2.first), dot(dir, segm2.second)};
00235         return isOverlap(s1, s2);
00236     }
00237
00238     if (std::holds_alternative<Vec3<T>>(intersectionResult))
00239     {
00240         auto pt = std::get<Vec3<T>>(intersectionResult);
00241         return isIntersectPointSegment(pt, segm1) && isIntersectPointSegment(pt, segm2);
00242     }
00243
00244     return false;
00245 }
00246
00247 template <std::floating_point T>
00248 bool isPoint(const Triangle<T> &tr)
00249 {
00250     return (tr[0] == tr[1]) && (tr[0] == tr[2]);
00251 }
00252
00253 template <std::floating_point T>
00254 bool isOverlap(Segment2D<T> &segm1, Segment2D<T> &segm2)
00255 {
00256     return (segm2.first <= segm1.second) && (segm2.second >= segm1.first);
00257 }
00258
00259 template <std::forward_iterator It>
00260 bool isAllPosNeg(It begin, It end)
00261 {
00262     if (begin == end)
00263         return true;
00264
00265     bool fst = (*begin > 0);
00266     return std::none_of(std::next(begin), end,
00267         [fst](auto &&elt) { return (elt > 0) != fst || isZeroThreshold(elt); });
00268 }
00269
00270 template <std::floating_point T>
00271 bool isAllPosNeg(T num1, T num2)
00272 {
00273     auto thres = ThresComp<T>::getThreshold();
00274     return (num1 > thres && num2 > thres) || (num1 < -thres && num2 < -thres);
00275 }
00276
00277 template <std::floating_point T>
00278 bool isOnOneSide(const Plane<T> &pl, const Triangle<T> &tr)
00279 {
00280     std::array<T, 3> sdist{};
00281     std::transform(tr.begin(), tr.end(), sdist.begin(), std::bind_front(distance<T>, pl));
00282     return detail::isAllPosNeg(sdist.begin(), sdist.end());
00283 }
00284
00285 template <std::floating_point T>
00286 Trian2<T> getTrian2(const Plane<T> &pl, const Triangle<T> &tr)
00287 {
00288     auto norm = pl.norm();
00289
00290     const Vec3<T> x{1, 0, 0};
00291     const Vec3<T> y{0, 1, 0};
00292     const Vec3<T> z{0, 0, 1};
00293
00294     std::array<Vec3<T>, 3> xyz{x, y, z};
00295     std::array<T, 3> xyzDot;
00296
00297     std::transform(xyz.begin(), xyz.end(), xyzDot.begin(),
00298         [&norm](const auto &axis) { return std::abs(dot(axis, norm)); });
00299
00300     auto maxIt = std::max_element(xyzDot.begin(), xyzDot.end());
00301     auto maxIdx = static_cast<std::size_t>(std::distance(xyzDot.begin(), maxIt));
00302
00303     Trian2<T> res;
00304     for (std::size_t i = 0; i < 3; ++i)
00305         for (std::size_t j = 0, k = 0; j < 2; ++j, ++k)
00306             {
00307                 if (k == maxIdx)
00308                     ++k;
00309
00310                 res[i][j] = tr[i][k];
00311             }

```


```

00312
00313     if (!isCounterClockwise(res))
00314         std::swap(res[0], res[1]);
00315     return res;
00316 }
00317
00318 template <std::floating_point T>
00319 bool isCounterClockwise(Trian2<T> &tr)
00320 {
00321     /**
00322     * The triangle is counterclockwise ordered if \delta > 0
00323     * and clockwise ordered if \delta < 0.
00324     *
00325     *
00326     *      + 1 1 1 +
00327     * \delta = det | x0 x1 x2 | = (x1 * y2 - x2 * y1) - (x0 * y2 - x2 * y0)
00328     *              + y0 y1 y2 +              + (x0 * y1 - x1 * y0)
00329     *
00330     */
00331     auto x0 = tr[0][0], x1 = tr[1][0], x2 = tr[2][0];
00332     auto y0 = tr[0][1], y1 = tr[1][1], y2 = tr[2][1];
00333     auto delta = (x1 * y2 - x2 * y1) - (x0 * y2 - x2 * y0) + (x0 * y1 - x1 * y0);
00334     return (delta > 0);
00335 }
00336
00337 template <std::floating_point T>
00338 Segment2D<T> computeInterval(const Trian2<T> &tr, const Vec2<T> &d)
00339 {
00340     std::array<T, 3> dotArr{};
00341     std::transform(tr.begin(), tr.end(), dotArr.begin(), [&d](auto &&v) { return dot(d, v); });
00342     auto mmIt = std::minmax_element(dotArr.begin(), dotArr.end());
00343     return {mmIt.first, mmIt.second};
00344 }
00345
00346 template <std::floating_point T>
00347 Segment3D<T> getSegment(const Triangle<T> &tr)
00348 {
00349     std::array<T, 3> lenArr{};
00350     for (std::size_t i = 0; i < 3; ++i)
00351         lenArr[i] = (tr[i] - tr[i + 1]).length2();
00352     auto maxIt = std::max_element(lenArr.begin(), lenArr.end());
00353     auto maxIdx = static_cast<std::size_t>(std::distance(lenArr.begin(), maxIt));
00354     return {tr[maxIdx], tr[maxIdx + 1]};
00355 }
00356
00357 template <std::bidirectional_iterator It>
00358 std::size_t roguePos(It beg, It end)
00359 {
00360     using T = typename std::iterator_traits<It>::value_type;
00361     auto isDiffSides = [thres = ThresComp<T>::getThreshold()](auto lhs, auto rhs) {
00362         return (lhs > thres && rhs < -thres) || (lhs < -thres && rhs > thres);
00363     };
00364     for (std::size_t i = 0; i < 3; ++i)
00365         if (isDiffSides(*(beg + i), *(beg + (i + 1) % 3)))
00366             return i;
00367     std::array<bool, 3> isOneSide{};
00368     for (std::size_t i = 0; i < 3; ++i)
00369         isOneSide[i] = isAllPosNeg(*(beg + i), *(beg + (i + 1) % 3));
00370     if (std::none_of(isOneSide.begin(), isOneSide.end(), std::identity{}))
00371     {
00372         auto rbeg = std::reverse_iterator(end);
00373         auto rend = std::reverse_iterator(beg);
00374         auto rogueIt = std::find_if_not(rbeg, rend, isZeroThreshold<T>);
00375         return (rogueIt == rend) ? 0 : std::distance(rogueIt, rend) - 1;
00376     }
00377     for (std::size_t i = 0; i < 3; ++i)
00378         if (isOneSide[i])
00379             return (i + 2) % 3;
00380     return 0;
00381 }
00382
00383 } // namespace geom::detail
00384
00385 #endif // __INCLUDE_INTERSECTION_DETAIL_HH__

```

## 6.5 include/intersection/intersection.hh File Reference

```
#include <cassert>
#include <concepts>
#include <variant>
#include "distance/distance.hh"
#include "primitives/primitives.hh"
#include "primitives/vec2.hh"
#include "detail.hh"
Include dependency graph for intersection.hh:
```



### Namespaces

- [geom](#)  
*line.hh Line class implementation*

### Functions

- `template<std::floating_point T>`  
`bool geom::isIntersect (const Triangle< T > &tr1, const Triangle< T > &tr2)`  
*Checks intersection of 2 triangles.*
- `template<std::floating_point T>`  
`std::variant< std::monostate, Line< T >, Plane< T > > geom::intersect (const Plane< T > &p1, const Plane< T > &p2)`  
*Intersect 2 planes and return result of intersection.*
- `template<std::floating_point T>`  
`std::variant< std::monostate, Vec3< T >, Line< T > > geom::intersect (const Line< T > &l1, const Line< T > &l2)`  
*Intersect 2 lines and return result of intersection.*

## 6.6 intersection.hh

```

00001 #ifndef __INCLUDE_INTERSECTION_INTERSECTION_HH__
00002 #define __INCLUDE_INTERSECTION_INTERSECTION_HH__
00003
00004 #include <cassert>
00005 #include <concepts>
00006 #include <variant>
00007
00008 #include "distance/distance.hh"
00009 #include "primitives/primitives.hh"
00010 #include "primitives/vec2.hh"
00011
00012 #include "detail.hh"
00013
00014 namespace geom
00015 {
00016
00017 /**
00018  * @brief Checks intersection of 2 triangles
00019  *
00020  * @tparam T - floating point type of coordinates
00021  * @param tr1 first triangle
00022  * @param tr2 second triangle
00023  * @return true if triangles are intersect
00024  * @return false if triangles are not intersect
00025  */
00026 template <std::floating_point T>
00027 bool isIntersect(const Triangle<T> &tr1, const Triangle<T> &tr2);
00028
00029 /**
00030  * @brief Intersect 2 planes and return result of intersection
00031  * @details
00032  * Common intersection case (parallel planes case is trivial):
00033  *
00034  * Let  $\vec{P}$  - point in space
00035  *
00036  *  $\vec{p}_{l_1}$  equation:  $\vec{n}_1 \cdot \vec{P} = d_1$ 
00037  *
00038  *  $\vec{p}_{l_2}$  equation:  $\vec{n}_2 \cdot \vec{P} = d_2$ 
00039  *
00040  * Intersection line direction:  $\vec{dir} = \vec{n}_1 \times \vec{n}_2$ 
00041  *
00042  *
00043  * Let origin of intersection line be a linear combination of  $\vec{n}_1$  and  $\vec{n}_2$ :
00044  *  $\vec{P} = a \cdot \vec{n}_1 + b \cdot \vec{n}_2$ 
00045  *
00046  *
00047  *  $\vec{P}$  must satisfy both  $\vec{p}_{l_1}$  and  $\vec{p}_{l_2}$  equations:
00048  *
00049  *  $\vec{n}_1 \cdot \vec{P} = d_1$ 
00050  *  $\vec{n}_2 \cdot \vec{P} = d_2$ 
00051  *
00052  *  $a \cdot \vec{n}_1 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_1 = d_1$ 
00053  *  $a \cdot \vec{n}_1 \cdot \vec{n}_2 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00054  *
00055  *  $a \cdot \vec{n}_1 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_1 = d_1$ 
00056  *  $a \cdot \vec{n}_1 \cdot \vec{n}_2 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00057  *
00058  *  $a \cdot \vec{n}_1 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_1 = d_1$ 
00059  *  $a \cdot \vec{n}_1 \cdot \vec{n}_2 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00060  *
00061  *  $\vec{n}_2 \cdot \vec{P} = d_2$ 
00062  *  $\vec{n}_2 \cdot (a \cdot \vec{n}_1 + b \cdot \vec{n}_2) = d_2$ 
00063  *  $a \cdot \vec{n}_2 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00064  *  $a \cdot \vec{n}_2 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00065  *  $a \cdot \vec{n}_2 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00066  *  $a \cdot \vec{n}_2 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00067  *  $a \cdot \vec{n}_2 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00068  *  $a \cdot \vec{n}_2 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00069  *  $a \cdot \vec{n}_2 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00070  *  $a \cdot \vec{n}_2 \cdot \vec{n}_1 + b \cdot \vec{n}_2 \cdot \vec{n}_2 = d_2$ 
00071  *
00072  * Let's find  $a$  and  $b$ :
00073  *
00074  *  $a = \frac{d_2 \cdot \vec{n}_2 \cdot \vec{n}_1 - d_1 \cdot \vec{n}_2 \cdot \vec{n}_2}{\vec{n}_2 \cdot \vec{n}_1^2 - \vec{n}_1 \cdot \vec{n}_2^2}$ 
00075  *
00076  *  $b = \frac{d_1 \cdot \vec{n}_2 \cdot \vec{n}_1 - d_2 \cdot \vec{n}_1 \cdot \vec{n}_2}{\vec{n}_2 \cdot \vec{n}_1^2 - \vec{n}_1 \cdot \vec{n}_2^2}$ 
00077  *
00078  *
00079  *
00080  *
00081  *  $b = \frac{d_1 \cdot \vec{n}_2 \cdot \vec{n}_1 - d_2 \cdot \vec{n}_1 \cdot \vec{n}_2}{\vec{n}_2 \cdot \vec{n}_1^2 - \vec{n}_1 \cdot \vec{n}_2^2}$ 
00082  *  $b = \frac{d_1 \cdot \vec{n}_2 \cdot \vec{n}_1 - d_2 \cdot \vec{n}_1 \cdot \vec{n}_2}{\vec{n}_2 \cdot \vec{n}_1^2 - \vec{n}_1 \cdot \vec{n}_2^2}$ 
00083  *  $b = \frac{d_1 \cdot \vec{n}_2 \cdot \vec{n}_1 - d_2 \cdot \vec{n}_1 \cdot \vec{n}_2}{\vec{n}_2 \cdot \vec{n}_1^2 - \vec{n}_1 \cdot \vec{n}_2^2}$ 
00084  *  $b = \frac{d_1 \cdot \vec{n}_2 \cdot \vec{n}_1 - d_2 \cdot \vec{n}_1 \cdot \vec{n}_2}{\vec{n}_2 \cdot \vec{n}_1^2 - \vec{n}_1 \cdot \vec{n}_2^2}$ 
00085  *

```

```

00086 * \f]
00087 *
00088 * Intersection line equation:
00089 * \f[
00090 * \overrightarrow{r}(t) = \overrightarrow{P} + t \cdot \overrightarrow{n}_1 \times
00091 * \overrightarrow{n}_2 = (a \cdot \overrightarrow{n}_1 + b \cdot \overrightarrow{n}_2) +
00092 * t \cdot \overrightarrow{n}_1 \times \overrightarrow{n}_2 \f]
00093 *
00094 * @tparam T - floating point type of coordinates
00095 * @param[in] p11 first plane
00096 * @param[in] p12 second plane
00097 * @return std::variant<std::monostate, Line<T>, Plane<T>
00098 */
00099 template <std::floating_point T>
00100 std::variant<std::monostate, Line<T>, Plane<T> > intersect(const Plane<T> &p11, const Plane<T> &p12);
00101
00102 /**
00103 * @brief Intersect 2 lines and return result of intersection
00104 * @details
00105 * Common intersection case (parallel & skew lines cases are trivial):
00106 * Let \f$ \overrightarrow{P} \f$ - point in space, intersection point of two lines.
00107 *
00108 * \f$ l_1 \f$ equation: \f$ \overrightarrow{org}_1 + \overrightarrow{dir}_1 \cdot t_1 =
00109 * \overrightarrow{P} \f$
00110 *
00111 * \f$ l_2 \f$ equation: \f$ \overrightarrow{org}_2 + \overrightarrow{dir}_2
00112 * \cdot t_2 = \overrightarrow{P} \f$
00113 *
00114 * Let's equate left sides:
00115 * \f[
00116 * \overrightarrow{org}_1 + \overrightarrow{dir}_1 \cdot t_1 =
00117 * \overrightarrow{org}_2 + \overrightarrow{dir}_2 \cdot t_2
00118 * \f]
00119 * Cross multiply both sides from right by \f$ \overrightarrow{dir}_2 \f$:
00120 * \f[
00121 * t_1 \cdot \left( \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right) =
00122 * \left( \overrightarrow{org}_2 - \overrightarrow{org}_1 \right) \times \overrightarrow{dir}_2
00123 * \f]
00124 * Dot multiply both sides by \f$ \frac{\overrightarrow{dir}_1 \times \overrightarrow{dir}_2}{\left| \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right|^2} \f$:
00125 * \f[
00126 * t_1 = \frac{
00127 * \left( \left( \overrightarrow{org}_2 - \overrightarrow{org}_1 \right) \times \overrightarrow{dir}_2 \right) \cdot \left( \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right)}{
00128 * \left| \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right|^2}
00129 * \f]
00130 * \f[
00131 * t_2 = \frac{
00132 * \left( \left( \overrightarrow{org}_2 - \overrightarrow{org}_1 \right) \times \overrightarrow{dir}_2 \right) \cdot \left( \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right)}{
00133 * \left| \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right|^2}
00134 * \f]
00135 * \f[
00136 * t_1 = \frac{
00137 * \left( \left( \overrightarrow{org}_2 - \overrightarrow{org}_1 \right) \times \overrightarrow{dir}_2 \right) \cdot \left( \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right)}{
00138 * \left| \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right|^2}
00139 * \f]
00140 * \f[
00141 * t_2 = \frac{
00142 * \left( \left( \overrightarrow{org}_2 - \overrightarrow{org}_1 \right) \times \overrightarrow{dir}_2 \right) \cdot \left( \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right)}{
00143 * \left| \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right|^2}
00144 * \f]
00145 * \f[
00146 * t_2 = \frac{
00147 * \left( \left( \overrightarrow{org}_2 - \overrightarrow{org}_1 \right) \times \overrightarrow{dir}_2 \right) \cdot \left( \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right)}{
00148 * \left| \overrightarrow{dir}_1 \times \overrightarrow{dir}_2 \right|^2}
00149 * \f]
00150 * @tparam T - floating point type of coordinates
00151 * @param[in] l1 first line
00152 * @param[in] l2 second line
00153 * @return std::variant<std::monostate, Vec3<T>, Line<T>
00154 */
00155 template <std::floating_point T>
00156 std::variant<std::monostate, Vec3<T>, Line<T> > intersect(const Line<T> &l1, const Line<T> &l2);
00157
00158 template <std::floating_point T>
00159 bool isIntersect(const Triangle<T> &tr1, const Triangle<T> &tr2)
00160 {
00161     auto isInv1 = !tr1.isValid();
00162     auto isInv2 = !tr2.isValid();
00163
00164     if (isInv1 && isInv2)
00165         return detail::isIntersectBothInvalid(tr1, tr2);
00166
00167     if (isInv1)
00168         return detail::isIntersectValidInvalid(tr2, tr1);
00169
00170     if (isInv2)
00171         return detail::isIntersectValidInvalid(tr1, tr2);
00172
00173     auto p11 = tr1.getPlane();
00174     if (detail::isOnOneSide(p11, tr2))
00175         return false;
00176
00177     auto p22 = tr2.getPlane();
00178     if (detail::isOnOneSide(p22, tr1))
00179         return false;
00180
00181     auto l1 = tr1.getLine(0);
00182     auto l2 = tr2.getLine(0);
00183     auto r = intersect(l1, l2);
00184     if (r.isMonostate())
00185         return false;
00186     auto p = r.getPlane();
00187     if (detail::isOnOneSide(p, tr1) || detail::isOnOneSide(p, tr2))
00188         return false;
00189     return true;
00190 }

```



```

00173
00174     auto p12 = tr2.getPlane();
00175     if (p11 == p12)
00176         return detail::isIntersect2D(tr1, tr2);
00177
00178     if (p11.isPar(p12))
00179         return false;
00180
00181     if (detail::isOnOneSide(p12, tr1))
00182         return false;
00183
00184     return detail::isIntersectMollerHaines(tr1, tr2);
00185 }
00186
00187 template <std::floating_point T>
00188 std::variant<std::monostate, Line<T>, Plane<T>> intersect(const Plane<T> &p11, const Plane<T> &p12)
00189 {
00190     const auto &n1 = p11.norm();
00191     const auto &n2 = p12.norm();
00192
00193     auto dir = cross(n1, n2);
00194
00195     /* if planes are parallel */
00196     if (Vec3<T>{0} == dir)
00197     {
00198         if (p11 == p12)
00199             return p11;
00200
00201         return std::monostate{};
00202     }
00203
00204     auto n1n2 = dot(n1, n2);
00205     auto d1 = p11.dist();
00206     auto d2 = p12.dist();
00207
00208     auto a = (d2 * n1n2 - d1) / (n1n2 * n1n2 - 1);
00209     auto b = (d1 * n1n2 - d2) / (n1n2 * n1n2 - 1);
00210
00211     return Line<T>{(a * n1) + (b * n2), dir};
00212 }
00213
00214 template <std::floating_point T>
00215 std::variant<std::monostate, Vec3<T>, Line<T>> intersect(const Line<T> &l1, const Line<T> &l2)
00216 {
00217     if (l1.isPar(l2))
00218     {
00219         if (l1.isEqual(l2))
00220             return l1;
00221
00222         return std::monostate{};
00223     }
00224
00225     if (l1.isSkew(l2))
00226         return std::monostate{};
00227
00228     auto dir1xdir2 = cross(l1.dir(), l2.dir());
00229     auto org2l1xdir2 = cross(l2.org() - l1.org(), l2.dir());
00230
00231     auto t1_intersect = dot(org2l1xdir2, dir1xdir2) / dir1xdir2.length2();
00232
00233     auto point = l1.getPoint(t1_intersect);
00234
00235     return point;
00236 }
00237
00238 } // namespace geom
00239
00240 #endif // __INCLUDE_INTERSECTION_INTERSECTION_HH__

```


## 6.7 include/kdtree/container.hh File Reference

```


#include <concepts>
#include <exception>
#include "node.hh"

```

Include dependency graph for container.hh:



This graph shows which files directly or indirectly include this file:



## Classes

- class [geom::kdtree::KdTree< T >](#)
- class [geom::kdtree::Container< T >](#)
- class [geom::kdtree::Container< T >::ConstIterator](#)

## Namespaces

- [geom](#)
  - [line.hh](#) *Line* class implementation
- [geom::kdtree](#)

## 6.8 container.hh

```

00001 #ifndef __INCLUDE_KDTREE_CONTAINER_HH__
00002 #define __INCLUDE_KDTREE_CONTAINER_HH__
00003
00004 #include <concepts>
00005 #include <exception>
00006
00007 #include "node.hh"
00008
00009 namespace geom::kdtree
00010 {
00011
00012 template <std::floating_point T>
00013 class KdTree;
00014
00015 template <std::floating_point T>
00016 class Container final
00017 {
00018 private:
00019     const KdTree<T> *tree_;
00020     const Node<T> *node_;
00021
00022 public:
00023     Container(const KdTree<T> *tree, const Node<T> *node);
00024
00025     class ConstIterator;
00026     ConstIterator cbegin() const &;
00027     ConstIterator cend() const &;
00028
00029     ConstIterator begin() const &;
00030     ConstIterator end() const &;
00031
00032     typename Node<T>::IndexConstIterator indexBegin() const &;
00033     typename Node<T>::IndexConstIterator indexEnd() const &;
00034
00035     T separator() const;
00036     Axis sepAxis() const;
00037     BoundBox<T> boundBox() const;
00038     const Triangle<T> &triangleByIndex(Index index) const &;
00039
00040     Container left() const;
00041     Container right() const;
00042
00043     bool isValid() const;
00044
00045     class ConstIterator final
00046     {
00047     public:
00048         using iterator_category = std::forward_iterator_tag;
00049         using difference_type = std::size_t;
00050         using value_type = Triangle<T>;
00051         using reference = const Triangle<T> &;
00052         using pointer = const Triangle<T> *;
00053
00054     private:
00055         const Container *cont_;
00056         std::vector<Index>::const_iterator curIdxIt_{};
00057
00058     public:
00059         ConstIterator(const Container *cont, bool isEnd = false);
00060
00061         Index getIndex();
00062
00063         ConstIterator &operator++();
00064         ConstIterator operator++(int);
00065
00066         reference operator*() const;
00067         pointer operator->() const;
00068
00069         bool operator==(const ConstIterator &lhs) const = default;
00070     };
00071 };
00072
00073 //=====
00074 //                                     Container definitions
00075 //=====
00076
00077 template <std::floating_point T>
00078 Container<T>::Container(const KdTree<T> *tree, const Node<T> *node) : tree_(tree), node_(node)
00079 {}
00080
00081 template <std::floating_point T>
00082 typename Container<T>::ConstIterator Container<T>::cbegin() const &
00083 {
00084     return ConstIterator{this};
00085 }

```

```

00086
00087 template <std::floating_point T>
00088 typename Container<T>::ConstIterator Container<T>::cend() const &
00089 {
00090     return ConstIterator{this, /* isEnd = */ true};
00091 }
00092
00093 template <std::floating_point T>
00094 typename Container<T>::ConstIterator Container<T>::begin() const &
00095 {
00096     return cbegin();
00097 }
00098
00099 template <std::floating_point T>
00100 typename Container<T>::ConstIterator Container<T>::end() const &
00101 {
00102     return cend();
00103 }
00104
00105 template <std::floating_point T>
00106 typename Node<T>::IndexConstIterator Container<T>::indexBegin() const &
00107 {
00108     return node_>indicies.begin();
00109 }
00110
00111 template <std::floating_point T>
00112 typename Node<T>::IndexConstIterator Container<T>::indexEnd() const &
00113 {
00114     return node_>indicies.end();
00115 }
00116
00117 template <std::floating_point T>
00118 T Container<T>::separator() const
00119 {
00120     return node_>separator;
00121 }
00122
00123 template <std::floating_point T>
00124 Axis Container<T>::sepAxis() const
00125 {
00126     return node_>sepAxis;
00127 }
00128
00129 template <std::floating_point T>
00130 BoundsContainer<T> Container<T>::boundingBox() const
00131 {
00132     return node_>boundingBox;
00133 }
00134
00135 template <std::floating_point T>
00136 const Triangle<T> &Container<T>::triangleByIndex(Index index) const &
00137 {
00138     return tree_>triangleByIndex(index);
00139 }
00140
00141 template <std::floating_point T>
00142 Container<T> Container<T>::left() const
00143 {
00144     return Container<T>{tree_, node_>left.get()};
00145 }
00146
00147 template <std::floating_point T>
00148 Container<T> Container<T>::right() const
00149 {
00150     return Container<T>{tree_, node_>right.get()};
00151 }
00152
00153 template <std::floating_point T>
00154 bool Container<T>::isValid() const
00155 {
00156     return (tree_ != nullptr) && (node_ != nullptr);
00157 }
00158
00159 //=====
00160 //                               Container::ConstIterator definitions
00161 //=====
00162
00163 template <std::floating_point T>
00164 Container<T>::ConstIterator::ConstIterator(const Container<T> *cont, bool isEnd) : cont_(cont)
00165 {
00166     if (nullptr == cont_)
00167         throw std::invalid_argument("Tried to create iterator with invalid Container pointer");
00168     if (isEnd)
00169         curIdxIt_ = cont_>indexEnd();
00170     else
00171         curIdxIt_ = cont_>indexBegin();
00172

```

```

00173 }
00174
00175 template <std::floating_point T>
00176 Index Container<T>::ConstIterator::getIndex()
00177 {
00178     return *curIdxIt_;
00179 }
00180
00181 template <std::floating_point T>
00182 typename Container<T>::ConstIterator &Container<T>::ConstIterator::operator++()
00183 {
00184     ++curIdxIt_;
00185     return *this;
00186 }
00187
00188 template <std::floating_point T>
00189 typename Container<T>::ConstIterator Container<T>::ConstIterator::operator++(int)
00190 {
00191     auto tmp = *this;
00192     operator++();
00193     return tmp;
00194 }
00195
00196 template <std::floating_point T>
00197 typename Container<T>::ConstIterator::reference Container<T>::ConstIterator::operator*() const
00198 {
00199     return cont_>triangleByIndex(*curIdxIt_);
00200 }
00201
00202 template <std::floating_point T>
00203 typename Container<T>::ConstIterator::pointer Container<T>::ConstIterator::operator->() const
00204 {
00205     return &cont_>triangleByIndex(*curIdxIt_);
00206 }
00207
00208 } // namespace geom::kdtree
00209
00210 #endif // __INCLUDE_KDTREE_CONTAINER_HH__

```


## 6.9 include/kdtree/kdtree.hh File Reference

```

#include <cassert>
#include <functional>
#include <initializer_list>
#include <memory>
#include <queue>
#include <stack>
#include <vector>
#include "primitives/primitives.hh"
#include "container.hh"
#include "node.hh"

```

Include dependency graph for `kdtree.hh`:



## Classes

- class [geom::kdtree::KdTree< T >](#)
- struct [geom::kdtree::KdTree< T >::ContainerPtr](#)
- class [geom::kdtree::KdTree< T >::ConstIterator](#)

## Namespaces

- [geom](#)
  - [line.hh](#) *Line* class implementation
- [geom::kdtree](#)

## 6.10 kdtree.hh

```

00001 #ifndef __INCLUDE_KDTREE_KDTREE_HH__
00002 #define __INCLUDE_KDTREE_KDTREE_HH__
00003
00004 #include <cassert>
00005 #include <functional>
00006 #include <initializer_list>
00007 #include <memory>
00008 #include <queue>
00009 #include <stack>
00010 #include <vector>
00011
00012 #include "primitives/primitives.hh"
00013
00014 #include "container.hh"
00015 #include "node.hh"
00016
00017 namespace geom::kdtree
00018 {
00019
00020 template <std::floating_point T>
00021 class KdTree final
00022 {
00023 private:
00024     std::unique_ptr<Node<T>> root_{};
00025     std::vector<Triangle<T>> triangles_{};
00026     std::size_t nodeCapacity_{1};

```

```

00027
00028 public:
00029     KdTree(std::initializer_list<Triangle<T> il);
00030     KdTree(const KdTree &tree);
00031     KdTree(KdTree &&tree) = default;
00032     KdTree() = default;
00033     ~KdTree();
00034
00035     KdTree &operator=(const KdTree &tree);
00036     KdTree &operator=(KdTree &&tree) = default;
00037
00038     class ConstIterator;
00039
00040     // ConstIterators
00041     ConstIterator cbegin() const &;
00042     ConstIterator cend() const &;
00043
00044     ConstIterator begin() const &;
00045     ConstIterator end() const &;
00046
00047     ConstIterator beginFrom(const ConstIterator &iter) const &;
00048
00049     // Modifiers
00050     void insert(const Triangle<T> &tr);
00051     void clear();
00052     void setNodeCapacity(std::size_t newCap);
00053
00054     // Capacity
00055     bool empty() const;
00056     std::size_t size() const;
00057     std::size_t nodeCapacity() const;
00058
00059     const Triangle<T> &triangleByIndex(Index index) const &;
00060
00061     void dumpRecursive(std::ostream &ost = std::cout) const;
00062
00063     static bool isOnPosSide(Axis axis, T separator, const Triangle<T> &tr);
00064     static bool isOnNegSide(Axis axis, T separator, const Triangle<T> &tr);
00065     static bool isOnSide(Axis axis, T separator, const Triangle<T> &tr,
00066                         std::function<bool(T, T)> comparator);
00067
00068 private:
00069     void expandingInsert(const Triangle<T> &tr);
00070     void tryExpandRight(Axis axis, const BoundBox<T> &trianBB);
00071     void tryExpandLeft(Axis axis, const BoundBox<T> &trianBB);
00072
00073     void nonExpandingInsert(Node<T> *node, const Triangle<T> &tr, Index index, bool isSubdiv = false);
00074     bool isDivisible(const Node<T> *node);
00075     void subdivide(Node<T> *node);
00076
00077 public:
00078     struct ContainerPtr final
00079     {
00080         Container<T> cont;
00081         const Container<T> *operator->() const;
00082     };
00083
00084     class ConstIterator final
00085     {
00086     public:
00087         using iterator_category = std::forward_iterator_tag;
00088         using difference_type = std::size_t;
00089         using value_type = Container<T>;
00090         using reference = Container<T>;
00091         using pointer = ContainerPtr;
00092
00093     private:
00094         const KdTree<T> *tree_;
00095         const Node<T> *node_;
00096         std::queue<const Node<T> *> fifo_;
00097
00098     public:
00099         ConstIterator(const KdTree<T> *tree, const Node<T> *node);
00100
00101         ConstIterator &operator++();
00102         ConstIterator operator++(int);
00103
00104         reference operator*() const;
00105         pointer operator->() const;
00106
00107         bool operator==(const ConstIterator &lhs) const;
00108         bool operator!=(const ConstIterator &lhs) const;
00109
00110         static ConstIterator beginFrom(const ConstIterator &iter);
00111     };
00112 };
00113

```

```

00114 //=====
00115 //                                KdTree definitions
00116 //=====
00117
00118 template <std::floating_point T>
00119 KdTree<T>::KdTree(std::initializer_list<Triangle<T>> il)
00120 {
00121     for (const auto &tr : il)
00122         insert(tr);
00123 }
00124
00125 template <std::floating_point T>
00126 KdTree<T>::KdTree(const KdTree<T> &tree)
00127 {
00128     // temporary solution
00129     for (const auto &tr : tree.triangles_)
00130         insert(tr);
00131 }
00132
00133 template <std::floating_point T>
00134 KdTree<T>::~KdTree()
00135 {
00136     clear();
00137 }
00138
00139 template <std::floating_point T>
00140 KdTree<T> &KdTree<T>::operator=(const KdTree<T> &tree)
00141 {
00142     KdTree tmp{tree};
00143     operator=(std::move(tmp));
00144     return *this;
00145 }
00146
00147 // ConstIterators
00148 template <std::floating_point T>
00149 typename KdTree<T>::ConstIterator KdTree<T>::cbegin() const &
00150 {
00151     return ConstIterator{this, root_.get()};
00152 }
00153
00154 template <std::floating_point T>
00155 typename KdTree<T>::ConstIterator KdTree<T>::cend() const &
00156 {
00157     return ConstIterator{this, nullptr};
00158 }
00159
00160 template <std::floating_point T>
00161 typename KdTree<T>::ConstIterator KdTree<T>::begin() const &
00162 {
00163     return cbegin();
00164 }
00165
00166 template <std::floating_point T>
00167 typename KdTree<T>::ConstIterator KdTree<T>::end() const &
00168 {
00169     return cend();
00170 }
00171
00172 template <std::floating_point T>
00173 typename KdTree<T>::ConstIterator KdTree<T>::beginFrom(
00174     const typename KdTree<T>::ConstIterator &iter) const &
00175 {
00176     return KdTree<T>::ConstIterator::beginFrom(iter);
00177 }
00178
00179 // Modifiers
00180 template <std::floating_point T>
00181 void KdTree<T>::insert(const Triangle<T> &tr)
00182 {
00183     if (nullptr == root_)
00184     {
00185         root_ = std::unique_ptr<Node<T>>(new Node<T>{T{}, Axis::NONE, tr.boundingBox(), {0}});
00186         triangles_.push_back(tr);
00187         return;
00188     }
00189
00190     if (!tr.belongsTo(root_>boundingBox))
00191         expandingInsert(tr);
00192     else
00193     {
00194         auto index = triangles_.size();
00195         triangles_.push_back(tr);
00196         nonExpandingInsert(root_.get(), tr, index);
00197     }
00198 }
00199
00200 template <std::floating_point T>

```



```

00201 void KdTree<T>::clear()
00202 {
00203     if (nullptr == root_)
00204         return;
00205
00206     std::stack<std::unique_ptr<Node<T>*> stack{};
00207     stack.push(&root_);
00208
00209     while (!stack.empty())
00210     {
00211         auto *curNode = stack.top();
00212         auto *right = &curNode->get()->right;
00213         auto *left = &curNode->get()->left;
00214
00215         if ((nullptr == *right) && (nullptr == *left))
00216         {
00217             curNode->reset();
00218             stack.pop();
00219             continue;
00220         }
00221
00222         stack.push(right);
00223         stack.push(left);
00224     }
00225 }
00226
00227 template <std::floating_point T>
00228 void KdTree<T>::setNodeCapacity(std::size_t newCap)
00229 {
00230     nodeCapacity_ = newCap;
00231 }
00232
00233 // Capacity
00234 template <std::floating_point T>
00235 bool KdTree<T>::empty() const
00236 {
00237     return triangles_.empty();
00238 }
00239
00240 template <std::floating_point T>
00241 std::size_t KdTree<T>::size() const
00242 {
00243     return triangles_.size();
00244 }
00245
00246 template <std::floating_point T>
00247 std::size_t KdTree<T>::nodeCapacity() const
00248 {
00249     return nodeCapacity_;
00250 }
00251
00252 template <std::floating_point T>
00253 const Triangle<T> &KdTree<T>::triangleByIndex(Index index) const &
00254 {
00255     return triangles_[index];
00256 }
00257
00258 template <std::floating_point T>
00259 void KdTree<T>::dumpRecursive(std::ostream &ost) const
00260 {
00261     ost << "digraph kdtree {" << std::endl;
00262     if (root_)
00263         root_->dumpRecursive(ost);
00264     ost << "}" << std::endl;
00265 }
00266
00267 template <std::floating_point T>
00268 bool KdTree<T>::isOnPosSide(Axis axis, T separator, const Triangle<T> &tr)
00269 {
00270     return isOnSide(axis, separator, tr, std::greater<T>{});
00271 }
00272
00273 template <std::floating_point T>
00274 bool KdTree<T>::isOnNegSide(Axis axis, T separator, const Triangle<T> &tr)
00275 {
00276     return isOnSide(axis, separator, tr, std::less<T>{});
00277 }
00278
00279 template <std::floating_point T>
00280 bool KdTree<T>::isOnSide(Axis axis, T separator, const Triangle<T> &tr,
00281                          std::function<bool(T, T)> comparator)
00282 {
00283     if (Axis::NONE == axis)
00284         return false;
00285
00286     auto axisIdx = static_cast<size_t>(axis);
00287     return std::all_of(tr.begin(), tr.end(),

```

```

00288         [&](auto &&v) { return comparator(v[axisIdx], separator); });
00289     }
00290
00291     template <std::floating_point T>
00292     void KdTree<T>::expandingInsert(const Triangle<T> &tr)
00293     {
00294         auto trianBB = tr.boundingBox();
00295         auto index = triangles_.size();
00296         triangles_.push_back(tr);
00297
00298         for (auto axis : {Axis::X, Axis::Y, Axis::Z})
00299             tryExpandRight(axis, trianBB);
00300
00301         for (auto axis : {Axis::X, Axis::Y, Axis::Z})
00302             tryExpandLeft(axis, trianBB);
00303
00304         root_>indicies.push_back(index);
00305     }
00306
00307     template <std::floating_point T>
00308     void KdTree<T>::tryExpandRight(Axis axis, const BoundingBox<T> &trianBB)
00309     {
00310         const auto &rootBB = root_>boundingBox();
00311         if (trianBB.max(axis) <= rootBB.max(axis))
00312             return;
00313
00314         auto newRightBB = rootBB;
00315         newRightBB.min(axis) = rootBB.max(axis);
00316         newRightBB.max(axis) = trianBB.max(axis);
00317
00318         auto newRootBB = rootBB;
00319         newRootBB.max(axis) = newRightBB.max(axis);
00320
00321         std::unique_ptr<Node<T> newRight{new Node<T>{T{}, Axis::NONE, newRightBB}};
00322         std::unique_ptr<Node<T> newRoot{new Node<T>{rootBB.max(axis), axis, newRootBB}};
00323
00324         newRoot->right = std::move(newRight);
00325         newRoot->left = std::move(root_);
00326
00327         root_ = std::move(newRoot);
00328     }
00329
00330     template <std::floating_point T>
00331     void KdTree<T>::tryExpandLeft(Axis axis, const BoundingBox<T> &trianBB)
00332     {
00333         const auto &rootBB = root_>boundingBox();
00334         if (trianBB.min(axis) >= rootBB.min(axis))
00335             return;
00336
00337         BoundingBox<T> newLeftBB = rootBB;
00338         newLeftBB.max(axis) = rootBB.min(axis);
00339         newLeftBB.min(axis) = trianBB.min(axis);
00340
00341         BoundingBox<T> newRootBB = rootBB;
00342         newRootBB.min(axis) = newLeftBB.min(axis);
00343
00344         std::unique_ptr<Node<T> newLeft{new Node<T>{T{}, Axis::NONE, newLeftBB}};
00345         std::unique_ptr<Node<T> newRoot{new Node<T>{rootBB.min(axis), axis, newRootBB}};
00346
00347         newRoot->left = std::move(newLeft);
00348         newRoot->right = std::move(root_);
00349
00350         root_ = std::move(newRoot);
00351     }
00352
00353     template <std::floating_point T>
00354     void KdTree<T>::nonExpandingInsert(Node<T> *node, const Triangle<T> &tr, Index index, bool isSubdiv)
00355     {
00356         auto curNode = node;
00357         while (true)
00358         {
00359             if (isOnPosSide(curNode->sepAxis, curNode->separator, tr))
00360                 curNode = curNode->right.get();
00361             else if (isOnNegSide(curNode->sepAxis, curNode->separator, tr))
00362                 curNode = curNode->left.get();
00363             else
00364                 break;
00365         }
00366
00367         curNode->indicies.push_back(index);
00368         if (isDivisible(curNode) && (!isSubdiv))
00369             subdivide(curNode);
00370     }
00371
00372     template <std::floating_point T>
00373     bool KdTree<T>::isDivisible(const Node<T> *node)
00374     {

```

```

00375     return (node->indicies.size() > nodeCapacity_) && (node->sepAxis == Axis::NONE);
00376 }
00377
00378 template <std::floating_point T>
00379 void KdTree<T>::subdivide(Node<T> *node)
00380 {
00381     const auto &nodeBB = node->boundingBox;
00382     auto axis = node->sepAxis = nodeBB.getMaxDim();
00383     auto sep = node->separator = nodeBB.min(axis) + (nodeBB.max(axis) - nodeBB.min(axis)) / 2;
00384
00385     auto newRightBB = nodeBB;
00386     auto newLeftBB = nodeBB;
00387
00388     newRightBB.min(axis) = newLeftBB.max(axis) = sep;
00389     node->right.reset(new Node<T>{T{}, Axis::NONE, newRightBB});
00390     node->left.reset(new Node<T>{T{}, Axis::NONE, newLeftBB});
00391
00392     auto indicies = node->indicies;
00393     node->indicies.clear();
00394
00395     for (auto index : indicies)
00396         nonExpandingInsert(node, triangles_[index], index, /* isSubdiv = */ true);
00397 }
00398
00399 //=====
00400 //                                KdTree::ContainerPtr definitions
00401 //=====
00402
00403 template <std::floating_point T>
00404 const Container<T> *KdTree<T>::ContainerPtr::operator->() const
00405 {
00406     return &cont;
00407 }
00408
00409 //=====
00410 //                                KdTree::ConstIterator definitions
00411 //=====
00412
00413 template <std::floating_point T>
00414 KdTree<T>::ConstIterator::ConstIterator(const KdTree<T> *tree, const Node<T> *node)
00415 : tree_(tree), node_(node), fifo_({node})
00416 {}
00417
00418 template <std::floating_point T>
00419 typename KdTree<T>::ConstIterator &KdTree<T>::ConstIterator::operator++()
00420 {
00421     if (0 == fifo_.size())
00422         return *this;
00423
00424     auto fifoEntry = fifo_.front();
00425     fifo_.pop();
00426
00427     if (Axis::NONE != fifoEntry->sepAxis)
00428     {
00429         if (nullptr != fifoEntry->left)
00430             fifo_.push(fifoEntry->left.get());
00431         if (nullptr != fifoEntry->right)
00432             fifo_.push(fifoEntry->right.get());
00433     }
00434
00435     node_ = (0 == fifo_.size()) ? nullptr : fifo_.front();
00436     return *this;
00437 }
00438
00439 template <std::floating_point T>
00440 typename KdTree<T>::ConstIterator KdTree<T>::ConstIterator::operator++(int)
00441 {
00442     auto tmp = *this;
00443     operator++();
00444     return tmp;
00445 }
00446
00447 template <std::floating_point T>
00448 typename KdTree<T>::ConstIterator::reference KdTree<T>::ConstIterator::operator*() const
00449 {
00450     return Container<T>{tree_, node_};
00451 }
00452
00453 template <std::floating_point T>
00454 typename KdTree<T>::ConstIterator::pointer KdTree<T>::ConstIterator::operator->() const
00455 {
00456     return ContainerPtr{{tree_, node_}};
00457 }
00458
00459 template <std::floating_point T>
00460 bool KdTree<T>::ConstIterator::operator==(const KdTree<T>::ConstIterator &lhs) const
00461 {

```

```

00462     return (tree_ == lhs.tree_) && (node_ == lhs.node_);
00463 }
00464
00465 template <std::floating_point T>
00466 bool KdTree<T>::ConstIterator::operator!=(const KdTree<T>::ConstIterator &lhs) const
00467 {
00468     return !operator==(lhs);
00469 }
00470
00471 template <std::floating_point T>
00472 typename KdTree<T>::ConstIterator KdTree<T>::ConstIterator::beginFrom(
00473     const typename KdTree<T>::ConstIterator &iter)
00474 {
00475     return ConstIterator{iter.tree_, iter.node_};
00476 }
00477
00478 } // namespace geom::kdtree
00479
00480 #endif // __INCLUDE_KDTREE_KDTREE_HH__

```


## 6.11 include/kdtree/node.hh File Reference

```


#include <iostream>
#include <memory>
#include <vector>
#include "primitives/primitives.hh"

```

Include dependency graph for node.hh:



This graph shows which files directly or indirectly include this file:



## Classes

- struct [geom::kdtree::Node< T >](#)

## Namespaces

- [geom](#)  
     [line.hh](#) *Line* class implementation
- [geom::kdtree](#)

## Typedefs

- using [geom::kdtree::Index](#) = `std::size_t`

## 6.12 node.hh

```

00001 #ifndef __INCLUDE_KDTREE_NODE_HH__
00002 #define __INCLUDE_KDTREE_NODE_HH__
00003
00004 #include <iostream>
00005 #include <memory>
00006 #include <vector>
00007
00008 #include "primitives/primitives.hh"
00009
00010 namespace geom::kdtree
00011 {
00012
00013 using Index = std::size_t;
00014
00015 template <std::floating_point T>
00016 struct Node final
00017 {
00018     T separator{}; // separator's coordinate on separation axis
00019     Axis sepAxis{Axis::NONE}; // separation axis
00020     BoundingBox<T> boundingBox{};
00021     std::vector<Index> indices{};
00022

```

```

00023 std::unique_ptr<Node> left{nullptr};
00024 std::unique_ptr<Node> right{nullptr};
00025
00026 using IndexIterator = std::vector<Index>::iterator;
00027 using IndexConstIterator = std::vector<Index>::const_iterator;
00028
00029 void dumpRecursive(std::ostream &ost) const;
00030 };
00031
00032 template <std::floating_point T>
00033 void Node<T>::dumpRecursive(std::ostream &ost) const
00034 {
00035     ost << reinterpret_cast<std::uintptr_t>(this)
00036         << " [shape=box,label=\"axis: \" << static_cast<int>(sepAxis) << ",\\n\"
00037         << boundBox << ",\\nvec: {\";
00038
00039     for (auto elem : indicies)
00040         ost << elem << " ";
00041
00042     ost << "}\\n\";\" << std::endl;
00043
00044     if (left)
00045     {
00046         left->dumpRecursive(ost);
00047         ost << reinterpret_cast<std::uintptr_t>(this) << " -> \"
00048             << reinterpret_cast<std::uintptr_t>(left.get()) << \" [label=\"L\\n\";\" << std::endl;
00049     }
00050     if (right)
00051     {
00052         right->dumpRecursive(ost);
00053         ost << reinterpret_cast<std::uintptr_t>(this) << " -> \"
00054             << reinterpret_cast<std::uintptr_t>(right.get()) << \" [label=\"R\\n\";\" << std::endl;
00055     }
00056 }
00057
00058 } // namespace geom::kdtree
00059
00060 #endif // __INCLUDE_KDTREE_NODE_HH__

```


## 6.13 include/primitives/boundbox.hh File Reference

```


#include <exception>
#include <iostream>
#include "common.hh"
#include "vec3.hh"

```

Include dependency graph for boundbox.hh:



This graph shows which files directly or indirectly include this file:



## Classes

- struct [geom::BoundingBox< T >](#)

## Namespaces

- [geom](#)  
*line.hh Line class implementation*

## Macros

- #define [BBFILL](#)(minmax)

## Functions

- template<std::floating\_point T>  
std::ostream & [geom::operator<<](#) (std::ostream &ost, const BoundingBox< T > &bb)

### 6.13.1 Macro Definition Documentation

### 6.13.1.1 BBFILL

```
#define BBFILL(
    minmax )
```

**Value:**

```
do
{
    switch (axis)
    {
        case Axis::X:
            return minmax##X;
        case Axis::Y:
            return minmax##Y;
        case Axis::Z:
            return minmax##Z;
        case Axis::NONE:
        default:
            throw std::logic_error("BoundingBox<T>::" #minmax "(): Wrong input axis");
    }
} while (false)
```

Definition at line 49 of file [boundingbox.hh](#).

## 6.14 boundingbox.hh

```
00001 #ifndef __INCLUDE_PRIMITIVES_BOUNDBOX_HH__
00002 #define __INCLUDE_PRIMITIVES_BOUNDBOX_HH__
00003
00004 #include <exception>
00005 #include <iostream>
00006
00007 #include "common.hh"
00008 #include "vec3.hh"
00009
00010 namespace geom
00011 {
00012
00013 template <std::floating_point T>
00014 struct BoundingBox final
00015 {
00016     T minX{};
00017     T maxX{};
00018
00019     T minY{};
00020     T maxY{};
00021
00022     T minZ{};
00023     T maxZ{};
00024
00025     bool belongsTo(const BoundingBox<T> &bb);
00026
00027     T &min(Axis axis) &;
00028     T &max(Axis axis) &;
00029
00030     T min(Axis axis) &&;
00031     T max(Axis axis) &&;
00032
00033     T min(Axis axis) const &;
00034     T max(Axis axis) const &;
00035
00036     Axis getMaxDim() const;
00037
00038     bool operator==(const BoundingBox &rhs) const;
00039     bool operator!=(const BoundingBox &rhs) const;
00040 };
00041
00042 template <std::floating_point T>
00043 bool BoundingBox<T>::belongsTo(const BoundingBox<T> &bb)
00044 {
00045     return (minX >= bb.minX) && (minY >= bb.minY) && (minZ >= bb.minZ) && (maxX <= bb.maxX) &&
00046           (maxY <= bb.maxY) && (maxZ <= bb.maxZ);
00047 }
00048
00049 #define BBFILL(minmax)
00050 do
00051 {
00052     switch (axis)
00053     {
```



```


00054     case Axis::X:
00055         return minmax##X;
00056     case Axis::Y:
00057         return minmax##Y;
00058     case Axis::Z:
00059         return minmax##Z;
00060     case Axis::NONE:
00061     default:
00062         throw std::logic_error("BoundingBox<T>::" #minmax "(): Wrong input axis");
00063     }
00064 } while (false)
00065
00066 template <std::floating_point T>
00067 T &BoundingBox<T>::min(Axis axis) &
00068 {
00069     BBFILL(min);
00070 }
00071
00072 template <std::floating_point T>
00073 T &BoundingBox<T>::max(Axis axis) &
00074 {
00075     BBFILL(max);
00076 }
00077
00078 template <std::floating_point T>
00079 T BoundingBox<T>::min(Axis axis) &&
00080 {
00081     BBFILL(min);
00082 }
00083
00084 template <std::floating_point T>
00085 T BoundingBox<T>::max(Axis axis) &&
00086 {
00087     BBFILL(max);
00088 }
00089
00090 template <std::floating_point T>
00091 T BoundingBox<T>::min(Axis axis) const &
00092 {
00093     BBFILL(min);
00094 }
00095
00096 template <std::floating_point T>
00097 T BoundingBox<T>::max(Axis axis) const &
00098 {
00099     BBFILL(max);
00100 }
00101
00102 #undef BBFILL
00103
00104 template <std::floating_point T>
00105 Axis BoundingBox<T>::getMaxDim() const
00106 {
00107     return std::max({Axis::X, Axis::Y, Axis::Z}, [this](auto lhs, auto rhs) {
00108         return (this->max(lhs) - this->min(lhs)) < (this->max(rhs) - this->min(rhs));
00109     });
00110 }
00111
00112 template <std::floating_point T>
00113 bool BoundingBox<T>::operator==(const BoundingBox &rhs) const
00114 {
00115     return isEqualThreshold(minX, rhs.minX) && isEqualThreshold(maxX, rhs.maxX) &&
00116         isEqualThreshold(minY, rhs.minY) && isEqualThreshold(maxY, rhs.maxY) &&
00117         isEqualThreshold(minZ, rhs.minZ) && isEqualThreshold(maxZ, rhs.maxZ);
00118 }
00119
00120 template <std::floating_point T>
00121 bool BoundingBox<T>::operator!=(const BoundingBox &rhs) const
00122 {
00123     return !operator==(rhs);
00124 }
00125
00126 template <std::floating_point T>
00127 std::ostream &operator<<(std::ostream &ost, const BoundingBox<T> &bb)
00128 {
00129     ost << "BB: {\n";
00130     ost << "  x: [" << bb.minX << "; " << bb.maxX << "],\n";
00131     ost << "  y: [" << bb.minY << "; " << bb.maxY << "],\n";
00132     ost << "  z: [" << bb.minZ << "; " << bb.maxZ << "]\n";
00133     return ost;
00134 }
00135
00136 } // namespace geom
00137
00138 #endif // __INCLUDE_PRIMITIVES_BOUNDBOX_HH__

```


## 6.15 include/primitives/common.hh File Reference

```
#include <cmath>
#include <concepts>
#include <cstdint>
#include <limits>
```

Include dependency graph for common.hh:



This graph shows which files directly or indirectly include this file:



## Classes

- class [geom::ThresComp< T >](#)

## Namespaces

- [geom](#)  
*line.hh Line class implementation*

## Enumerations

- enum [geom::Axis](#) : std::int8\_t { [geom::Axis::X](#) = 0, [geom::Axis::Y](#) = 1, [geom::Axis::Z](#) = 2, [geom::Axis::NONE](#) }

## Functions

- template<Number T>  
bool [geom::isEqualThreshold](#) (T num1, T num2)
- template<Number T>  
bool [geom::isZeroThreshold](#) (T num)

## Variables

- template<class T >  
concept [geom::Number](#) = std::is\_floating\_point\_v<T> || std::is\_integral\_v<T>  
*Useful concept which represents floating point and integral types.*

## 6.16 common.hh

```

00001 #ifndef __INCLUDE_PRIMITIVES_COMMON_HH__
00002 #define __INCLUDE_PRIMITIVES_COMMON_HH__
00003
00004 #include <cmath>
00005 #include <concepts>
00006 #include <cstdint>
00007 #include <limits>
00008 namespace geom
00009 {
00010 /**
00011  * @concept Number
00012  * @brief Useful concept which represents floating point and integral types
00013  *
00014  * @tparam T
00015  */
00016 template <class T>
00017 concept Number = std::is_floating_point_v<T> || std::is_integral_v<T>;
00018
00019 enum class Axis : std::int8_t
00020 {
00021     X = 0,
00022     Y = 1,
00023     Z = 2,
00024     NONE
00025 };
00026
00027 template <Number T>
00028 class ThresComp final
00029 {
00030 private:
00031     static inline T threshold_ = 1e2 * std::numeric_limits<T>::epsilon();
00032
00033 public:
00034     ThresComp() = delete;
00035
00036     static void setThreshold(T thres) requires std::is_floating_point_v<T>
00037     {
00038         threshold_ = thres;
00039     }
00040
00041     static T getThreshold() requires std::is_floating_point_v<T>
00042     {

```

```


00043     return threshold_;
00044 }
00045
00046 static void scaleThreshold(T factor) requires std::is_floating_point_v<T>
00047 {
00048     threshold_ *= factor;
00049 }
00050
00051 static void resetThreshold() requires std::is_floating_point_v<T>
00052 {
00053     threshold_ = std::numeric_limits<T>::epsilon();
00054 }
00055
00056 static bool isEqual(T lhs, T rhs)
00057 {
00058     if constexpr (std::is_floating_point_v<T>)
00059         return std::abs(rhs - lhs) < threshold_;
00060     else
00061         return lhs == rhs;
00062 }
00063
00064 static bool isZero(T num)
00065 {
00066     return isEqual(num, T{});
00067 }
00068 };
00069
00070 template <Number T>
00071 bool isEqualThreshold(T num1, T num2)
00072 {
00073     return ThresComp<T>::isEqual(num1, num2);
00074 }
00075
00076 template <Number T>
00077 bool isZeroThreshold(T num)
00078 {
00079     return ThresComp<T>::isZero(num);
00080 }
00081
00082 } // namespace geom
00083
00084 #endif // __INCLUDE_PRIMITIVES_COMMON_HH__

```


## 6.17 include/primitives/line.hh File Reference

```
#include "vec3.hh"
```

Include dependency graph for line.hh:



This graph shows which files directly or indirectly include this file:



## Classes

- class [geom::Line< T >](#)  
*[Line](#) class implementation.*

## Namespaces

- [geom](#)  
*[line.hh](#) [Line](#) class implementation*

## Functions

- `template<std::floating_point T>`  
`std::ostream & geom::operator<< (std::ostream &ost, const Line< T > &line)`  
*[Line](#) print operator.*

## 6.18 line.hh

```

00001 #ifndef __INCLUDE_PRIMITIVES_LINE_HH__
00002 #define __INCLUDE_PRIMITIVES_LINE_HH__
00003
00004 #include "vec3.hh"
00005
00006 /**
00007  * @brief line.hh
00008  * Line class implementation
00009  */
00010
00011 namespace geom
00012 {
00013
00014 /**
00015  * @class Line
00016  * @brief Line class implementation
00017  *
00018  * @tparam T - floating point type of coordinates
00019  */
00020 template <std::floating_point T>
00021 class Line final
00022 {
00023 private:
00024     /**
00025      * @brief Origin and direction vectors
00026      */
00027     Vec3<T> org_{}, dir_{};
00028
00029 public:
00030     /**
00031      * @brief Construct a new Line object
00032      *
00033      * @param[in] org origin vector
00034      * @param[in] dir direction vector
00035      */
00036     Line(const Vec3<T> &org, const Vec3<T> &dir);
00037
00038     /**
00039      * @brief Line equality operator
00040      *
00041      * @tparam T - floating point type of coordinates
00042      * @param[in] rhs 2nd line
00043      * @return true if lines are equal
00044      * @return false if lines are not equal
00045      */
00046     bool operator==(const Line &rhs) const;
00047
00048     /**
00049      * @brief Line inequality operator
00050      *
00051      * @tparam T - floating point type of coordinates
00052      * @param[in] rhs 2nd line
00053      * @return true if lines are not equal
00054      * @return false if lines are equal
00055      */
00056     bool operator!=(const Line &rhs) const;
00057
00058     /**
00059      * @brief Getter for origin vector
00060      *
00061      * @return const Vec3<T>& const reference to origin vector
00062      */
00063     const Vec3<T> &org() const &;
00064
00065     /**
00066      * @brief Getter for direction vector
00067      *
00068      * @return const Vec3<T>& const reference to direction vector
00069      */
00070     const Vec3<T> &dir() const &;
00071
00072     /**
00073      * @brief Getter for origin vector
00074      *
00075      * @return Vec3<T>&& reference to origin vector
00076      */
00077     Vec3<T> &&org() &&;
00078
00079     /**
00080      * @brief Getter for direction vector
00081      *
00082      * @return Vec3<T>&& reference to direction vector
00083      */
00084     Vec3<T> &&dir() &&;
00085

```

```

00086  /**
00087   * @brief Get point on line by parameter t
00088   *
00089   * @tparam nType numeric type
00090   * @param[in] t point parameter from line's equation
00091   * @return Vec3<T> Point related to parameter
00092   */
00093  template <Number nType>
00094  Vec3<T> getPoint(nType t) const;
00095
00096  /**
00097   * @brief Checks if point belongs to line
00098   *
00099   * @param[in] point const reference to point vector
00100   * @return true if point belongs to line
00101   * @return false if point doesn't belong to line
00102   */
00103  bool belongs(const Vec3<T> &point) const;
00104
00105  /**
00106   * @brief Checks if *this equals to another line
00107   *
00108   * @param[in] line const reference to another line
00109   * @return true if lines are equal
00110   * @return false if lines are not equal
00111   */
00112  bool isEqual(const Line &line) const;
00113
00114  /**
00115   * @brief Checks if *this parallel to another line
00116   * @note Assumes equal lines as parallel
00117   * @param[in] line const reference to another line
00118   * @return true if lines are parallel
00119   * @return false if lines are not parallel
00120   */
00121  bool isPar(const Line &line) const;
00122
00123  /**
00124   * @brief Checks if *this is skew with another line
00125   *
00126   * @param[in] line const reference to another line
00127   * @return true if lines are skew
00128   * @return false if lines are not skew
00129   */
00130  bool isSkew(const Line<T> &line) const;
00131
00132  /**
00133   * @brief Get line by 2 points
00134   *
00135   * @param[in] p1 1st point
00136   * @param[in] p2 2nd point
00137   * @return Line passing through two points
00138   */
00139  static Line getBy2Points(const Vec3<T> &p1, const Vec3<T> &p2);
00140 };
00141
00142 /**
00143   * @brief Line print operator
00144   *
00145   * @tparam T - floating point type of coordinates
00146   * @param[in, out] ost output stream
00147   * @param[in] line Line to print
00148   * @return std::ostream& modified ostream instance
00149   */
00150  template <std::floating_point T>
00151  std::ostream &operator<<(std::ostream &ost, const Line<T> &line)
00152  {
00153      ost << line.org() << " + " << line.dir() << " * t";
00154      return ost;
00155  }
00156
00157  template <std::floating_point T>
00158  Line<T>::Line(const Vec3<T> &org, const Vec3<T> &dir) : org_{org}, dir_{dir}
00159  {
00160      if (dir_ == Vec3<T>{0})
00161          throw std::logic_error{"Direction vector equals zero."};
00162  }
00163
00164  template <std::floating_point T>
00165  bool Line<T>::operator==(const Line &rhs) const
00166  {
00167      return isEqual(rhs);
00168  }
00169
00170  template <std::floating_point T>
00171  bool Line<T>::operator!=(const Line &rhs) const
00172  {

```

```

00173     return !operator==(rhs);
00174 }
00175
00176 template <std::floating_point T>
00177 const Vec3<T> &Line<T>::org() const &
00178 {
00179     return org_;
00180 }
00181
00182 template <std::floating_point T>
00183 const Vec3<T> &Line<T>::dir() const &
00184 {
00185     return dir_;
00186 }
00187
00188 template <std::floating_point T>
00189 Vec3<T> &&Line<T>::org() &&
00190 {
00191     return std::move(org_);
00192 }
00193
00194 template <std::floating_point T>
00195 Vec3<T> &&Line<T>::dir() &&
00196 {
00197     return std::move(dir_);
00198 }
00199
00200 template <std::floating_point T>
00201 template <Number nType>
00202 Vec3<T> Line<T>::getPoint(nType t) const
00203 {
00204     return org_ + dir_ * t;
00205 }
00206
00207 template <std::floating_point T>
00208 bool Line<T>::belongs(const Vec3<T> &point) const
00209 {
00210     return dir_.cross(point - org_) == Vec3<T>{0};
00211 }
00212
00213 template <std::floating_point T>
00214 bool Line<T>::isEqual(const Line<T> &line) const
00215 {
00216     return belongs(line.org_) && dir_.isPar(line.dir_);
00217 }
00218
00219 template <std::floating_point T>
00220 bool Line<T>::isPar(const Line<T> &line) const
00221 {
00222     return dir_.isPar(line.dir_);
00223 }
00224
00225 template <std::floating_point T>
00226 bool Line<T>::isSkew(const Line<T> &line) const
00227 {
00228     auto res = triple(line.org_ - org_, dir_, line.dir_);
00229     return !isZeroThreshold(res);
00230 }
00231
00232 template <std::floating_point T>
00233 Line<T> Line<T>::getBy2Points(const Vec3<T> &p1, const Vec3<T> &p2)
00234 {
00235     return Line<T>{p1, p2 - p1};
00236 }
00237
00238 } // namespace geom
00239
00240 #endif // __INCLUDE_PRIMITIVES_LINE_HH__

```

## 6.19 include/primitives/plane.hh File Reference


```

#include "line.hh"
#include "vec3.hh"


```



Include dependency graph for plane.hh:



This graph shows which files directly or indirectly include this file:



## Classes

- class `geom::Plane< T >`  
*Plane* class realization.

## Namespaces

- [geom](#)  
*line.hh* *Line* class implementation

## Functions

- `template<std::floating_point T>`  
`std::ostream & geom::operator<< (std::ostream &ost, const Plane< T > &pl)`  
*Plane* print operator.

## 6.20 plane.hh

```

00001 #ifndef __INCLUDE_PRIMITIVES_PLANE_HH__
00002 #define __INCLUDE_PRIMITIVES_PLANE_HH__
00003
00004 #include "line.hh"
00005 #include "vec3.hh"
00006
00007 /**
00008  * @brief
00009  * Plane class implementation
00010  */
00011
00012 namespace geom
00013 {
00014
00015 /**
00016  * @class Plane
00017  * @brief Plane class realization
00018  *
00019  * @tparam T - floating point type of coordinates
00020  */
00021 template <std::floating_point T>
00022 class Plane final
00023 {
00024 private:
00025     /**
00026      * @brief Normal vector, length equals to 1
00027      */
00028     Vec3<T> norm_{};
00029
00030     /**
00031      * @brief Distance from zero to plane
00032      */
00033     T dist_{};
00034
00035     /**
00036      * @brief Construct a new Plane object from normal vector and distance
00037      *
00038      * @param[in] norm normal vector
00039      * @param[in] dist distance from plane to zero
00040      */
00041     Plane(const Vec3<T> &norm, T dist);
00042
00043 public:
00044     /**
00045      * @brief Plane equality operator
00046      *
00047      * @tparam T - floating point type of coordinates
00048      * @param[in] rhs 2nd plane
00049      * @return true if planes are equal
00050      * @return false if planes are not equal
00051      */
00052     bool operator==(const Plane &rhs) const;
00053
00054     /**
00055      * @brief Plane inequality operator
00056      *
00057      * @tparam T - floating point type of coordinates
00058      * @param[in] rhs 2nd plane
00059      * @return true if planes are not equal
00060      * @return false if planes are equal
00061      */
00062     bool operator!=(const Plane &rhs) const;
00063

```

```

00064  /**
00065   * @brief Getter for distance
00066   *
00067   * @return T value of distance
00068   */
00069  T dist() const;
00070
00071  /**
00072   * @brief Getter for normal vector
00073   *
00074   * @return const Vec3<T>& const reference to normal vector
00075   */
00076  const Vec3<T> &norm() const &;
00077
00078  /**
00079   * @brief Getter for normal vector
00080   *
00081   * @return Vec3<T>&& reference to normal vector
00082   */
00083  Vec3<T> &&norm() &&;
00084
00085  /**
00086   * @brief Checks if point belongs to plane
00087   *
00088   * @param[in] point const referene to point vector
00089   * @return true if point belongs to plane
00090   * @return false if point doesn't belong to plane
00091   */
00092  bool belongs(const Vec3<T> &point) const;
00093
00094  /**
00095   * @brief Checks if line belongs to plane
00096   *
00097   * @param[in] line const referene to line
00098   * @return true if line belongs to plane
00099   * @return false if line doesn't belong to plane
00100   */
00101  bool belongs(const Line<T> &line) const;
00102
00103  /**
00104   * @brief Checks is *this equals to another plane
00105   *
00106   * @param[in] rhs const reference to another plane
00107   * @return true if planes are equal
00108   * @return false if planes are not equal
00109   */
00110  bool isEqual(const Plane &rhs) const;
00111
00112  /**
00113   * @brief Checks is *this is parallel to another plane
00114   *
00115   * @param[in] rhs const reference to another plane
00116   * @return true if planes are parallel
00117   * @return false if planes are not parallel
00118   */
00119  bool isPar(const Plane &rhs) const;
00120
00121  /**
00122   * @brief Get plane by 3 points
00123   *
00124   * @param[in] pt1 1st point
00125   * @param[in] pt2 2nd point
00126   * @param[in] pt3 3rd point
00127   * @return Plane passing through three points
00128   */
00129  static Plane getBy3Points(const Vec3<T> &pt1, const Vec3<T> &pt2, const Vec3<T> &pt3);
00130
00131  /**
00132   * @brief Get plane from parametric plane equation
00133   *
00134   * @param[in] org origin vector
00135   * @param[in] dir1 1st direction vector
00136   * @param[in] dir2 2nd direction vector
00137   * @return Plane
00138   */
00139  static Plane getParametric(const Vec3<T> &org, const Vec3<T> &dir1, const Vec3<T> &dir2);
00140
00141  /**
00142   * @brief Get plane from normal point plane equation
00143   *
00144   * @param[in] norm normal vector
00145   * @param[in] point point lying on the plane
00146   * @return Plane
00147   */
00148  static Plane getNormalPoint(const Vec3<T> &norm, const Vec3<T> &point);
00149
00150  /**

```

```

00151     * @brief Get plane form normal const plane equation
00152     *
00153     * @param[in] norm normal vector
00154     * @param[in] constant distance
00155     * @return Plane
00156     */
00157     static Plane getNormalDist(const Vec3<T> &norm, T constant);
00158 };
00159
00160 /**
00161  * @brief Plane print operator
00162  *
00163  * @tparam T - floating point type of coordinates
00164  * @param[in, out] ost output stream
00165  * @param[in] pl plane to print
00166  * @return std::ostream& modified ostream instance
00167  */
00168 template <std::floating_point T>
00169 std::ostream &operator<<(std::ostream &ost, const Plane<T> &pl)
00170 {
00171     ost << pl.norm() << " * X = " << pl.dist();
00172     return ost;
00173 }
00174
00175 template <std::floating_point T>
00176 Plane<T>::Plane(const Vec3<T> &norm, T dist) : norm_(norm), dist_(dist)
00177 {
00178     if (norm == Vec3<T>{0})
00179         throw std::logic_error{"normal vector equals to zero"};
00180 }
00181
00182 template <std::floating_point T>
00183 bool Plane<T>::operator==(const Plane &rhs) const
00184 {
00185     return isEqual(rhs);
00186 }
00187
00188 template <std::floating_point T>
00189 bool Plane<T>::operator!=(const Plane &rhs) const
00190 {
00191     return !operator==(rhs);
00192 }
00193
00194 template <std::floating_point T>
00195 T Plane<T>::dist() const
00196 {
00197     return dist_;
00198 }
00199
00200 template <std::floating_point T>
00201 const Vec3<T> &Plane<T>::norm() const &
00202 {
00203     return norm_;
00204 }
00205
00206 template <std::floating_point T>
00207 Vec3<T> &&Plane<T>::norm() &&
00208 {
00209     return std::move(norm_);
00210 }
00211
00212 template <std::floating_point T>
00213 bool Plane<T>::belongs(const Vec3<T> &pt) const
00214 {
00215     return isEqualThreshold(norm_.dot(pt), dist_);
00216 }
00217
00218 template <std::floating_point T>
00219 bool Plane<T>::belongs(const Line<T> &line) const
00220 {
00221     return norm_.isPerp(line.dir()) && belongs(line.org());
00222 }
00223
00224 template <std::floating_point T>
00225 bool Plane<T>::isEqual(const Plane &rhs) const
00226 {
00227     return (norm_ * dist_ == rhs.norm_ * rhs.dist_) && (norm_.isPar(rhs.norm_));
00228 }
00229
00230 template <std::floating_point T>
00231 bool Plane<T>::isPar(const Plane &rhs) const
00232 {
00233     return norm_.isPar(rhs.norm_);
00234 }
00235
00236 template <std::floating_point T>
00237 Plane<T> Plane<T>::getBy3Points(const Vec3<T> &pt1, const Vec3<T> &pt2, const Vec3<T> &pt3)

```

```

00238 {
00239     return getParametric(pt1, pt2 - pt1, pt3 - pt1);
00240 }
00241
00242 template <std::floating_point T>
00243 Plane<T> Plane<T>::getParametric(const Vec3<T> &org, const Vec3<T> &dir1, const Vec3<T> &dir2)
00244 {
00245     auto norm = dir1.cross(dir2);
00246     return getNormalPoint(norm, org);
00247 }
00248
00249 template <std::floating_point T>
00250 Plane<T> Plane<T>::getNormalPoint(const Vec3<T> &norm, const Vec3<T> &pt)
00251 {
00252     auto normalized = norm.normalized();
00253     return Plane{normalized, normalized.dot(pt)};
00254 }
00255
00256 template <std::floating_point T>
00257 Plane<T> Plane<T>::getNormalDist(const Vec3<T> &norm, T dist)
00258 {
00259     auto normalized = norm.normalized();
00260     return Plane{normalized, dist};
00261 }
00262
00263 } // namespace geom
00264
00265 #endif // __INCLUDE_PRIMITIVES_PLANE_HH__

```


## 6.21 include/primitives/primitives.hh File Reference

```


#include "bboxbox.hh"
#include "common.hh"
#include "line.hh"
#include "plane.hh"
#include "triangle.hh"
#include "vec3.hh"

```

Include dependency graph for primitives.hh:



This graph shows which files directly or indirectly include this file:



## 6.22 primitives.hh

```

00001 #ifndef __INCLUDE_PRIMITIVES_PRIMITIVES_HH__
00002 #define __INCLUDE_PRIMITIVES_PRIMITIVES_HH__

```

```

00003
00004 #include "bboxbox.hh"
00005 #include "common.hh"
00006 #include "line.hh"
00007 #include "plane.hh"
00008 #include "triangle.hh"
00009 #include "vec3.hh"
00010
00011 #endif // __INCLUDE_PRIMITIVES_PRIMITIVES_HH__

```


## 6.23 include/primitives/triangle.hh File Reference

```


#include <algorithm>
#include <array>
#include "bboxbox.hh"
#include "plane.hh"
#include "vec3.hh"

```

Include dependency graph for triangle.hh:



This graph shows which files directly or indirectly include this file:



## Classes

- class [geom::Triangle< T >](#)  
*Triangle* class implementation.

## Namespaces

- [geom](#)  
*line.hh* *Line* class implementation

## Functions

- `template<std::floating_point T>`  
`std::ostream & geom::operator<< (std::ostream &ost, const Triangle< T > &tr)`  
*Triangle* print operator.
- `template<std::floating_point T>`  
`std::istream & geom::operator>> (std::istream &ist, Triangle< T > &tr)`

## 6.24 triangle.hh

```

00001 #ifndef __INCLUDE_PRIMITIVES_TRIANGLE_HH__
00002 #define __INCLUDE_PRIMITIVES_TRIANGLE_HH__
00003
00004 #include <algorithm>
00005 #include <array>
00006
00007 #include "boundingbox.hh"
00008 #include "plane.hh"
00009 #include "vec3.hh"
00010
00011 /**
00012  * @brief triangle.hh
00013  * Triangle class implementation

```



```

00014  */
00015
00016 namespace geom
00017 {
00018
00019 /**
00020  * @class Triangle
00021  * @brief Triangle class implementation
00022  *
00023  * @tparam T - floating point type of coordinates
00024  */
00025 template <std::floating_point T>
00026 class Triangle final
00027 {
00028 private:
00029     /**
00030      * @brief Vertices of triangle
00031      */
00032     std::array<Vec3<T>, 3> vertices_;
00033
00034 public:
00035     using Iterator = typename std::array<Vec3<T>, 3>::iterator;
00036     using ConstIterator = typename std::array<Vec3<T>, 3>::const_iterator;
00037
00038     /**
00039      * @brief Construct a new Triangle object
00040      */
00041     Triangle();
00042
00043     /**
00044      * @brief Construct a new Triangle object from 3 points
00045      *
00046      * @param[in] p1 1st point
00047      * @param[in] p2 2nd point
00048      * @param[in] p3 3rd point
00049      */
00050     Triangle(const Vec3<T> &p1, const Vec3<T> &p2, const Vec3<T> &p3);
00051
00052     /**
00053      * @brief Overloaded operator[] to get access to vertices
00054      *
00055      * @param[in] idx index of vertex
00056      * @return const Vec3<T>& const reference to vertex
00057      */
00058     const Vec3<T> &operator[](std::size_t idx) const &;
00059
00060     /**
00061      * @brief Overloaded operator[] to get access to vertices
00062      *
00063      * @param[in] idx index of vertex
00064      * @return Vec3<T>&& reference to vertex
00065      */
00066     Vec3<T> &&operator[](std::size_t idx) &&;
00067
00068     /**
00069      * @brief Overloaded operator[] to get access to vertices
00070      *
00071      * @param[in] idx index of vertex
00072      * @return Vec3<T>& reference to vertex
00073      */
00074     Vec3<T> &operator[](std::size_t idx) &;
00075
00076     /**
00077      * @brief Get begin iterator
00078      * @return Iterator
00079      */
00080     Iterator begin() &;
00081
00082     /**
00083      * @brief Get end iterator
00084      * @return Iterator
00085      */
00086     Iterator end() &;
00087
00088     /**
00089      * @brief Get begin const iterator
00090      * @return ConstIterator
00091      */
00092     ConstIterator begin() const &;
00093
00094     /**
00095      * @brief Get end const iterator
00096      * @return ConstIterator
00097      */
00098     ConstIterator end() const &;
00099
00100     /**

```

```

00101     * @brief Get triangle's plane
00102     *
00103     * @return Plane<T>
00104     */
00105     Plane<T> getPlane() const;
00106
00107     /**
00108     * @brief Check is triangle valid
00109     *
00110     * @return true if triangle is valid
00111     * @return false if triangle is invalid
00112     */
00113     bool isValid() const;
00114
00115     /**
00116     * @brief Returns triangle's bound box
00117     *
00118     * @return BoundBox<T>
00119     */
00120     BoundBox<T> boundBox() const;
00121
00122     /**
00123     * @brief Checks if this Triangle belongs to BoundBox
00124     *
00125     * @param[in] bb BoundBox
00126     * @return true if Triangle belongs to BoundBox
00127     * @return false if Triangle doesn't belong to BoundBox
00128     */
00129     bool belongsTo(const BoundBox<T> &bb) const;
00130 };
00131
00132 /**
00133 * @brief Triangle print operator
00134 *
00135 * @tparam T - floating point type of coordinates
00136 * @param[in, out] ost output stream
00137 * @param[in] tr Triangle to print
00138 * @return std::ostream& modified ostream instance
00139 */
00140 template <std::floating_point T>
00141 std::ostream &operator<<(std::ostream &ost, const Triangle<T> &tr)
00142 {
00143     ost << "Triangle: {";
00144     for (std::size_t i = 0; i < 3; ++i)
00145         ost << tr[i] << (i == 2 ? " " : ", ");
00146
00147     ost << "}";
00148
00149     return ost;
00150 }
00151
00152 template <std::floating_point T>
00153 std::istream &operator>>(std::istream &ist, Triangle<T> &tr)
00154 {
00155     ist >> tr[0] >> tr[1] >> tr[2];
00156     return ist;
00157 }
00158
00159 template <std::floating_point T>
00160 Triangle<T>::Triangle() : vertices_()
00161 {}
00162
00163 template <std::floating_point T>
00164 Triangle<T>::Triangle(const Vec3<T> &p1, const Vec3<T> &p2, const Vec3<T> &p3)
00165     : vertices_{p1, p2, p3}
00166 {}
00167
00168 template <std::floating_point T>
00169 const Vec3<T> &Triangle<T>::operator[](std::size_t idx) const &
00170 {
00171     return vertices_[idx % 3];
00172 }
00173
00174 template <std::floating_point T>
00175 Vec3<T> &&Triangle<T>::operator[](std::size_t idx) &&
00176 {
00177     return std::move(vertices_[idx % 3]);
00178 }
00179
00180 template <std::floating_point T>
00181 Vec3<T> &Triangle<T>::operator[](std::size_t idx) &
00182 {
00183     return vertices_[idx % 3];
00184 }
00185
00186 template <std::floating_point T>
00187 typename Triangle<T>::Iterator Triangle<T>::begin() &

```

```

00188 {
00189     return vertices_.begin();
00190 }
00191
00192 template <std::floating_point T>
00193 typename Triangle<T>::Iterator Triangle<T>::end() &
00194 {
00195     return vertices_.end();
00196 }
00197
00198 template <std::floating_point T>
00199 typename Triangle<T>::ConstIterator Triangle<T>::begin() const &
00200 {
00201     return vertices_.begin();
00202 }
00203
00204 template <std::floating_point T>
00205 typename Triangle<T>::ConstIterator Triangle<T>::end() const &
00206 {
00207     return vertices_.end();
00208 }
00209
00210 template <std::floating_point T>
00211 Plane<T> Triangle<T>::getPlane() const
00212 {
00213     return Plane<T>::getBy3Points(vertices_[0], vertices_[1], vertices_[2]);
00214 }
00215
00216 template <std::floating_point T>
00217 bool Triangle<T>::isValid() const
00218 {
00219     auto edge1 = vertices_[1] - vertices_[0];
00220     auto edge2 = vertices_[2] - vertices_[0];
00221
00222     auto cross12 = cross(edge1, edge2);
00223     return (cross12 != Vec3<T>{});
00224 }
00225
00226 template <std::floating_point T>
00227 BoundingBox<T> Triangle<T>::boundingBox() const
00228 {
00229     auto minMaxX = std::minmax({vertices_[0].x, vertices_[1].x, vertices_[2].x});
00230     auto minMaxY = std::minmax({vertices_[0].y, vertices_[1].y, vertices_[2].y});
00231     auto minMaxZ = std::minmax({vertices_[0].z, vertices_[1].z, vertices_[2].z});
00232
00233     return {
00234         minMaxX.first - ThresComp<T>::getThreshold(), minMaxX.second + ThresComp<T>::getThreshold(),
00235         minMaxY.first - ThresComp<T>::getThreshold(), minMaxY.second + ThresComp<T>::getThreshold(),
00236         minMaxZ.first - ThresComp<T>::getThreshold(), minMaxZ.second + ThresComp<T>::getThreshold() };
00237 }
00238
00239 template <std::floating_point T>
00240 bool Triangle<T>::belongsTo(const BoundingBox<T> &bb) const
00241 {
00242     return boundingBox().belongsTo(bb);
00243 }
00244
00245 } // namespace geom
00246
00247 #endif // __INCLUDE_PRIMITIVES_TRIANGLE_HH__

```


## 6.25 include/primitives/vec2.hh File Reference

```


#include <cmath>
#include <functional>
#include <iostream>
#include <limits>
#include "common.hh"

```

Include dependency graph for `vec2.hh`:



This graph shows which files directly or indirectly include this file:



## Classes

- class [geom::Vec2< T >](#)  
*Vec2 class realization.*

## Namespaces

- [geom](#)  
*line.hh Line class implementation*

## Typedefs

- using [geom::Vec2D](#) = Vec2< double >
- using [geom::Vec2F](#) = Vec2< float >

## Functions

- template<std::floating\_point T>  
Vec2< T > [geom::operator+](#) (const Vec2< T > &lhs, const Vec2< T > &rhs)  
*Overloaded + operator.*
- template<std::floating\_point T>  
Vec2< T > [geom::operator-](#) (const Vec2< T > &lhs, const Vec2< T > &rhs)  
*Overloaded - operator.*
- template<Number nT, std::floating\_point T>  
Vec2< T > [geom::operator\\*](#) (const nT &val, const Vec2< T > &rhs)  
*Overloaded multiple by value operator.*
- template<Number nT, std::floating\_point T>  
Vec2< T > [geom::operator\\*](#) (const Vec2< T > &lhs, const nT &val)  
*Overloaded multiple by value operator.*
- template<Number nT, std::floating\_point T>  
Vec2< T > [geom::operator/](#) (const Vec2< T > &lhs, const nT &val)  
*Overloaded divide by value operator.*
- template<std::floating\_point T>  
T [geom::dot](#) (const Vec2< T > &lhs, const Vec2< T > &rhs)  
*Dot product function.*
- template<std::floating\_point T>  
std::ostream & [geom::operator<<](#) (std::ostream &ost, const Vec2< T > &vec)  
*Vec2 print operator.*

### 6.25.1 Detailed Description

Vec2 class implementation

Definition in file [vec2.hh](#).

## 6.26 vec2.hh

```

00001 #ifndef __INCLUDE_PRIMITIVES_VEC2_HH__
00002 #define __INCLUDE_PRIMITIVES_VEC2_HH__
00003
00004 #include <cmath>
00005 #include <functional>
00006 #include <iostream>
00007 #include <limits>
00008
00009 #include "common.hh"
00010
00011 /**
00012  * @file vec2.hh
00013  * Vec2 class implementation
00014  */
00015
00016 namespace geom
00017 {
00018
00019 /**
00020  * @class Vec2
00021  * @brief Vec2 class realization
00022  *

```

```

00023  * @tparam T - floating point type of coordinates
00024  */
00025  template <std::floating_point T>
00026  struct Vec2 final
00027  {
00028      /**
00029       * @brief Vec2 coordinates
00030       */
00031      T x{}, y{};
00032
00033      /**
00034       * @brief Construct a new Vec2 object from 3 coordinates
00035       *
00036       * @param[in] coordX x coordinate
00037       * @param[in] coordY y coordinate
00038       */
00039      Vec2(T coordX, T coordY) : x(coordX), y(coordY)
00040      {}
00041
00042      /**
00043       * @brief Construct a new Vec2 object with equals coordinates
00044       *
00045       * @param[in] coordX coordinate (default to {})
00046       */
00047      explicit Vec2(T coordX = {}) : Vec2(coordX, coordX)
00048      {}
00049
00050      /**
00051       * @brief Vec2 equality operator
00052       *
00053       * @tparam T vector template parameter
00054       * @param[in] rhs second vector
00055       * @return true if vectors are equal
00056       * @return false otherwise
00057       */
00058      bool operator==(const Vec2 &rhs) const;
00059
00060      /**
00061       * @brief Vec2 equality operator
00062       *
00063       * @tparam T vector template parameter
00064       * @param[in] rhs second vector
00065       * @return true if vectors are not equal
00066       * @return false otherwise
00067       */
00068      bool operator!=(const Vec2 &rhs) const;
00069
00070      /**
00071       * @brief Overloaded += operator
00072       * Increments vector coordinates by corresponding coordinates of vec
00073       * @param[in] vec vector to incremented with
00074       * @return Vec2& reference to current instance
00075       */
00076      Vec2 &operator+=(const Vec2 &vec);
00077
00078      /**
00079       * @brief Overloaded -= operator
00080       * Decrements vector coordinates by corresponding coordinates of vec
00081       * @param[in] vec vector to decremented with
00082       * @return Vec2& reference to current instance
00083       */
00084      Vec2 &operator-=(const Vec2 &vec);
00085
00086      /**
00087       * @brief Unary - operator
00088       *
00089       * @return Vec2 negated Vec2 instance
00090       */
00091      Vec2 operator-() const;
00092
00093      /**
00094       * @brief Overloaded *= by number operator
00095       *
00096       * @tparam nType numeric type of value to multiply by
00097       * @param[in] val value to multiply by
00098       * @return Vec2& reference to vector instance
00099       */
00100      template <Number nType>
00101      Vec2 &operator*=(nType val);
00102
00103      /**
00104       * @brief Overloaded /= by number operator
00105       *
00106       * @tparam nType numeric type of value to divide by
00107       * @param[in] val value to divide by
00108       * @return Vec2& reference to vector instance
00109       */

```

```

00110     * @warning Does not check if val equals 0
00111     */
00112     template <Number nType>
00113     Vec2 &operator/=(nType val);
00114
00115     /**
00116     * @brief Dot product function
00117     *
00118     * @param rhs vector to dot product with
00119     * @return T dot product of two vectors
00120     */
00121     T dot(const Vec2 &rhs) const;
00122
00123     /**
00124     * @brief Calculate squared length of a vector function
00125     *
00126     * @return T length^2
00127     */
00128     T length2() const;
00129
00130     /**
00131     * @brief Calculate length of a vector function
00132     *
00133     * @return T length
00134     */
00135     T length() const;
00136
00137     /**
00138     * @brief Get the perpendicular to this vector
00139     *
00140     * @return Vec2 perpendicular vector
00141     */
00142     Vec2 getPerp() const;
00143
00144     /**
00145     * @brief Get normalized vector function
00146     *
00147     * @return Vec2 normalized vector
00148     */
00149     Vec2 normalized() const;
00150
00151     /**
00152     * @brief Normalize vector function
00153     *
00154     * @return Vec2& reference to instance
00155     */
00156     Vec2 &normalize() &;
00157
00158     /**
00159     * @brief Overloaded operator [] (non-const version)
00160     * To get access to coordinates
00161     * @param i index of coordinate (0 - x, 1 - y)
00162     * @return T& reference to coordinate value
00163     *
00164     * @note Coordinates calculated by mod 2
00165     */
00166     T &operator[](std::size_t i) &;
00167
00168     /**
00169     * @brief Overloaded operator [] (const version)
00170     * To get access to coordinates
00171     * @param i index of coordinate (0 - x, 1 - y)
00172     * @return T coordinate value
00173     *
00174     * @note Coordinates calculated by mod 2
00175     */
00176     T operator[](std::size_t i) const &;
00177
00178     /**
00179     * @brief Overloaded operator [] (const version)
00180     * To get access to coordinates
00181     * @param i index of coordinate (0 - x, 1 - y)
00182     * @return T coordinate value
00183     *
00184     * @note Coordinates calculated by mod 2
00185     */
00186     T &&operator[](std::size_t i) &&;
00187
00188     /**
00189     * @brief Check if vector is parallel to another
00190     *
00191     * @param[in] rhs vector to check parallelism with
00192     * @return true if vector is parallel
00193     * @return false otherwise
00194     */
00195     bool isPar(const Vec2 &rhs) const;
00196

```

```

00197  /**
00198   * @brief Check if vector is perpendicular to another
00199   *
00200   * @param[in] rhs vector to check perpendicularity with
00201   * @return true if vector is perpendicular
00202   * @return false otherwise
00203   */
00204  bool isPerp(const Vec2 &rhs) const;
00205
00206  /**
00207   * @brief Check if vector is equal to another
00208   *
00209   * @param[in] rhs vector to check equality with
00210   * @return true if vector is equal
00211   * @return false otherwise
00212   */
00213  bool isEqual(const Vec2 &rhs) const;
00214 };
00215
00216 /**
00217  * @brief Overloaded + operator
00218  *
00219  * @tparam T vector template parameter
00220  * @param[in] lhs first vector
00221  * @param[in] rhs second vector
00222  * @return Vec2<T> sum of two vectors
00223  */
00224 template <std::floating_point T>
00225 Vec2<T> operator+(const Vec2<T> &lhs, const Vec2<T> &rhs)
00226 {
00227     Vec2<T> res{lhs};
00228     res += rhs;
00229     return res;
00230 }
00231
00232 /**
00233  * @brief Overloaded - operator
00234  *
00235  * @tparam T vector template parameter
00236  * @param[in] lhs first vector
00237  * @param[in] rhs second vector
00238  * @return Vec2<T> res of two vectors
00239  */
00240 template <std::floating_point T>
00241 Vec2<T> operator-(const Vec2<T> &lhs, const Vec2<T> &rhs)
00242 {
00243     Vec2<T> res{lhs};
00244     res -= rhs;
00245     return res;
00246 }
00247
00248 /**
00249  * @brief Overloaded multiple by value operator
00250  *
00251  * @tparam nT type of value to multiply by
00252  * @tparam T vector template parameter
00253  * @param[in] val value to multiply by
00254  * @param[in] rhs vector to multiply by value
00255  * @return Vec2<T> result vector
00256  */
00257 template <Number nT, std::floating_point T>
00258 Vec2<T> operator*(const nT &val, const Vec2<T> &rhs)
00259 {
00260     Vec2<T> res{rhs};
00261     res *= val;
00262     return res;
00263 }
00264
00265 /**
00266  * @brief Overloaded multiple by value operator
00267  *
00268  * @tparam nT type of value to multiply by
00269  * @tparam T vector template parameter
00270  * @param[in] val value to multiply by
00271  * @param[in] lhs vector to multiply by value
00272  * @return Vec2<T> result vector
00273  */
00274 template <Number nT, std::floating_point T>
00275 Vec2<T> operator*(const Vec2<T> &lhs, const nT &val)
00276 {
00277     Vec2<T> res{lhs};
00278     res *= val;
00279     return res;
00280 }
00281
00282 /**
00283  * @brief Overloaded divide by value operator

```



```

00284 *
00285 * @tparam nT type of value to divide by
00286 * @tparam T vector template parameter
00287 * @param[in] val value to divide by
00288 * @param[in] lhs vector to divide by value
00289 * @return Vec2<T> result vector
00290 */
00291 template <Number nT, std::floating_point T>
00292 Vec2<T> operator/(const Vec2<T> &lhs, const nT &val)
00293 {
00294     Vec2<T> res{lhs};
00295     res /= val;
00296     return res;
00297 }
00298
00299 /**
00300 * @brief Dot product function
00301 *
00302 * @tparam T vector template parameter
00303 * @param[in] lhs first vector
00304 * @param[in] rhs second vector
00305 * @return T dot production
00306 */
00307 template <std::floating_point T>
00308 T dot(const Vec2<T> &lhs, const Vec2<T> &rhs)
00309 {
00310     return lhs.dot(rhs);
00311 }
00312
00313 /**
00314 * @brief Vec2 print operator
00315 *
00316 * @tparam T vector template parameter
00317 * @param[in, out] ost output stream
00318 * @param[in] vec vector to print
00319 * @return std::ostream& modified stream instance
00320 */
00321 template <std::floating_point T>
00322 std::ostream &operator<<(std::ostream &ost, const Vec2<T> &vec)
00323 {
00324     ost << "(" << vec.x << ", " << vec.y << ")";
00325     return ost;
00326 }
00327
00328 using Vec2D = Vec2<double>;
00329 using Vec2F = Vec2<float>;
00330
00331 template <std::floating_point T>
00332 bool Vec2<T>::operator==(const Vec2 &rhs) const
00333 {
00334     return isEqual(rhs);
00335 }
00336
00337 template <std::floating_point T>
00338 bool Vec2<T>::operator!=(const Vec2 &rhs) const
00339 {
00340     return !operator==(rhs);
00341 }
00342
00343 template <std::floating_point T>
00344 Vec2<T> &Vec2<T>::operator+=(const Vec2 &vec)
00345 {
00346     x += vec.x;
00347     y += vec.y;
00348     return *this;
00349 }
00350
00351 template <std::floating_point T>
00352 Vec2<T> &Vec2<T>::operator-=(const Vec2 &vec)
00353 {
00354     x -= vec.x;
00355     y -= vec.y;
00356     return *this;
00357 }
00358
00359 template <std::floating_point T>
00360 Vec2<T> Vec2<T>::operator-() const
00361 {
00362     return Vec2{-x, -y};
00363 }
00364
00365 template <std::floating_point T>
00366 template <Number nType>
00367 Vec2<T> &Vec2<T>::operator*=(nType val)
00368 {
00369

```

```

00371     x *= val;
00372     y *= val;
00373
00374     return *this;
00375 }
00376
00377 template <std::floating_point T>
00378 template <Number nType>
00379 Vec2<T> &Vec2<T>::operator/=(nType val)
00380 {
00381     x /= static_cast<T>(val);
00382     y /= static_cast<T>(val);
00383
00384     return *this;
00385 }
00386
00387 template <std::floating_point T>
00388 T Vec2<T>::dot(const Vec2 &rhs) const
00389 {
00390     return x * rhs.x + y * rhs.y;
00391 }
00392
00393 template <std::floating_point T>
00394 T Vec2<T>::length2() const
00395 {
00396     return dot(*this);
00397 }
00398
00399 template <std::floating_point T>
00400 T Vec2<T>::length() const
00401 {
00402     return std::sqrt(length2());
00403 }
00404
00405 template <std::floating_point T>
00406 Vec2<T> Vec2<T>::getPerp() const
00407 {
00408     return {y, -x};
00409 }
00410
00411 template <std::floating_point T>
00412 Vec2<T> Vec2<T>::normalized() const
00413 {
00414     Vec2 res{*this};
00415     res.normalize();
00416     return res;
00417 }
00418
00419 template <std::floating_point T>
00420 Vec2<T> &Vec2<T>::normalize() &
00421 {
00422     T len2 = length2();
00423     if (isZeroThreshold(len2) || isEqualThreshold(len2, T{1}))
00424         return *this;
00425     return *this /= std::sqrt(len2);
00426 }
00427
00428 template <std::floating_point T>
00429 T &Vec2<T>::operator[](std::size_t i) &
00430 {
00431     switch (i % 2)
00432     {
00433     case 0:
00434         return x;
00435     case 1:
00436         return y;
00437     default:
00438         throw std::logic_error{"Impossible case in operator[]\n"};
00439     }
00440 }
00441
00442 template <std::floating_point T>
00443 T Vec2<T>::operator[](std::size_t i) const &
00444 {
00445     switch (i % 2)
00446     {
00447     case 0:
00448         return x;
00449     case 1:
00450         return y;
00451     default:
00452         throw std::logic_error{"Impossible case in operator[]\n"};
00453     }
00454 }
00455
00456 template <std::floating_point T>
00457 T &&Vec2<T>::operator[](std::size_t i) &&

```

```

00458 {
00459     switch (i % 2)
00460     {
00461     case 0:
00462         return std::move(x);
00463     case 1:
00464         return std::move(y);
00465     default:
00466         throw std::logic_error{"Impossible case in operator[]\n"};
00467     }
00468 }
00469
00470 template <std::floating_point T>
00471 bool Vec2<T>::isPar(const Vec2 &rhs) const
00472 {
00473     auto det = x * rhs.y - rhs.x * y;
00474     return isZeroThreshold(det);
00475 }
00476
00477 template <std::floating_point T>
00478 bool Vec2<T>::isPerp(const Vec2 &rhs) const
00479 {
00480     return isZeroThreshold(dot(rhs));
00481 }
00482
00483 template <std::floating_point T>
00484 bool Vec2<T>::isEqual(const Vec2 &rhs) const
00485 {
00486     return isEqualThreshold(x, rhs.x) && isEqualThreshold(y, rhs.y);
00487 }
00488
00489 } // namespace geom
00490
00491 #endif // __INCLUDE_PRIMITIVES_VEC2_HH__

```


## 6.27 include/primitives/vec3.hh File Reference

```


#include <cmath>
#include <functional>
#include <iostream>
#include <limits>
#include "common.hh"

```

Include dependency graph for vec3.hh:



This graph shows which files directly or indirectly include this file:



## Classes

- class [geom::Vec3< T >](#)  
*Vec3 class realization.*

## Namespaces

- [geom](#)  
*line.hh Line class implementation*

## Typedefs

- using [geom::Vec3D](#) = Vec3< double >
- using [geom::Vec3F](#) = Vec3< float >

## Functions

- `template<std::floating_point T>`  
`Vec3< T > geom::operator+ (const Vec3< T > &lhs, const Vec3< T > &rhs)`  
*Overloaded + operator.*
- `template<std::floating_point T>`  
`Vec3< T > geom::operator- (const Vec3< T > &lhs, const Vec3< T > &rhs)`  
*Overloaded - operator.*
- `template<Number nT, std::floating_point T>`  
`Vec3< T > geom::operator* (const nT &val, const Vec3< T > &rhs)`  
*Overloaded multiple by value operator.*
- `template<Number nT, std::floating_point T>`  
`Vec3< T > geom::operator* (const Vec3< T > &lhs, const nT &val)`  
*Overloaded multiple by value operator.*
- `template<Number nT, std::floating_point T>`  
`Vec3< T > geom::operator/ (const Vec3< T > &lhs, const nT &val)`  
*Overloaded divide by value operator.*
- `template<std::floating_point T>`  
`T geom::dot (const Vec3< T > &lhs, const Vec3< T > &rhs)`  
*Dot product function.*
- `template<std::floating_point T>`  
`Vec3< T > geom::cross (const Vec3< T > &lhs, const Vec3< T > &rhs)`  
*Cross product function.*
- `template<std::floating_point T>`  
`T geom::triple (const Vec3< T > &v1, const Vec3< T > &v2, const Vec3< T > &v3)`  
*Triple product function.*
- `template<std::floating_point T>`  
`std::ostream & geom::operator<< (std::ostream &ost, const Vec3< T > &vec)`  
*Vec3 print operator.*
- `template<std::floating_point T>`  
`std::istream & geom::operator>> (std::istream &ist, Vec3< T > &vec)`  
*Vec3 scan operator.*

### 6.27.1 Detailed Description

Vec3 class implementation

Definition in file [vec3.hh](#).

## 6.28 vec3.hh

```

00001 #ifndef __INCLUDE_PRIMITIVES_VEC3_HH__
00002 #define __INCLUDE_PRIMITIVES_VEC3_HH__
00003
00004 #include <cmath>
00005 #include <functional>
00006 #include <iostream>
00007 #include <limits>
00008
00009 #include "common.hh"
00010
00011 /**
00012  * @file vec3.hh
00013  * Vec3 class implementation
00014  */
00015
00016 namespace geom

```

```

00017 {
00018
00019 /**
00020  * @class Vec3
00021  * @brief Vec3 class realization
00022  *
00023  * @tparam T - floating point type of coordinates
00024  */
00025 template <std::floating_point T>
00026 struct Vec3 final
00027 {
00028     /**
00029      * @brief Vec3 coordinates
00030      */
00031     T x{}, y{}, z{};
00032
00033     /**
00034      * @brief Construct a new Vec3 object from 3 coordinates
00035      *
00036      * @param[in] coordX x coordinate
00037      * @param[in] coordY y coordinate
00038      * @param[in] coordZ z coordinate
00039      */
00040     Vec3(T coordX, T coordY, T coordZ) : x(coordX), y(coordY), z(coordZ)
00041     {}
00042
00043     /**
00044      * @brief Construct a new Vec3 object with equals coordinates
00045      *
00046      * @param[in] coordX coordinate (default to {})
00047      */
00048     explicit Vec3(T coordX = {}) : Vec3(coordX, coordX, coordX)
00049     {}
00050
00051     /**
00052      * @brief Vec3 equality operator
00053      *
00054      * @tparam T vector template parameter
00055      * @param[in] rhs second vector
00056      * @return true if vectors are equal
00057      * @return false otherwise
00058      */
00059     bool operator==(const Vec3 &rhs) const;
00060
00061     /**
00062      * @brief Vec3 inequality operator
00063      *
00064      * @tparam T vector template parameter
00065      * @param[in] rhs second vector
00066      * @return true if vectors are not equal
00067      * @return false otherwise
00068      */
00069     bool operator!=(const Vec3 &rhs) const;
00070
00071     /**
00072      * @brief Overloaded += operator
00073      * Increments vector coordinates by corresponding coordinates of vec
00074      * @param[in] vec vector to incremented with
00075      * @return Vec3& reference to current instance
00076      */
00077     Vec3 &operator+=(const Vec3 &vec);
00078
00079     /**
00080      * @brief Overloaded -= operator
00081      * Decrements vector coordinates by corresponding coordinates of vec
00082      * @param[in] vec vector to decremented with
00083      * @return Vec3& reference to current instance
00084      */
00085     Vec3 &operator-=(const Vec3 &vec);
00086
00087     /**
00088      * @brief Unary - operator
00089      *
00090      * @return Vec3 negated Vec3 instance
00091      */
00092     Vec3 operator-() const;
00093
00094     /**
00095      * @brief Overloaded *= by number operator
00096      *
00097      * @tparam nType numeric type of value to multiply by
00098      * @param[in] val value to multiply by
00099      * @return Vec3& reference to vector instance
00100      */
00101     template <Number nType>
00102     Vec3 &operator*=(nType val);
00103

```

```

00104  /**
00105   * @brief Overloaded /= by number operator
00106   *
00107   * @tparam nType numeric type of value to divide by
00108   * @param[in] val value to divide by
00109   * @return Vec3& reference to vector instance
00110   *
00111   * @warning Does not check if val equals 0
00112   */
00113  template <Number nType>
00114  Vec3 &operator/=(nType val);
00115
00116  /**
00117   * @brief Dot product function
00118   *
00119   * @param rhs vector to dot product with
00120   * @return T dot product of two vectors
00121   */
00122  T dot(const Vec3 &rhs) const;
00123
00124  /**
00125   * @brief Cross product function
00126   *
00127   * @param rhs vector to cross product with
00128   * @return Vec3 cross product of two vectors
00129   */
00130  Vec3 cross(const Vec3 &rhs) const;
00131
00132  /**
00133   * @brief Calculate squared length of a vector function
00134   *
00135   * @return T length^2
00136   */
00137  T length2() const;
00138
00139  /**
00140   * @brief Calculate length of a vector function
00141   *
00142   * @return T length
00143   */
00144  T length() const;
00145
00146  /**
00147   * @brief Get normalized vector function
00148   *
00149   * @return Vec3 normalized vector
00150   */
00151  Vec3 normalized() const;
00152
00153  /**
00154   * @brief Normalize vector function
00155   *
00156   * @return Vec3& reference to instance
00157   */
00158  Vec3 &normalize() &;
00159
00160  /**
00161   * @brief Overloaded operator [] (non-const version)
00162   * To get access to coordinates
00163   * @param i index of coordinate (0 - x, 1 - y, 2 - z)
00164   * @return T& reference to coordinate value
00165   *
00166   * @note Coordinates calculated by mod 3
00167   */
00168  T &operator[](std::size_t i) &;
00169
00170  /**
00171   * @brief Overloaded operator [] (const version)
00172   * To get access to coordinates
00173   * @param i index of coordinate (0 - x, 1 - y, 2 - z)
00174   * @return T coordinate value
00175   *
00176   * @note Coordinates calculated by mod 3
00177   */
00178  T operator[](std::size_t i) const &;
00179
00180  /**
00181   * @brief Overloaded operator [] (rvalue 'this' version)
00182   * To get access to coordinates
00183   * @param i index of coordinate (0 - x, 1 - y, 2 - z)
00184   * @return T coordinate value
00185   *
00186   * @note Coordinates calculated by mod 3
00187   */
00188  T &&operator[](std::size_t i) &&;
00189
00190  /**

```

```

00191     * @brief Check if vector is parallel to another
00192     *
00193     * @param[in] rhs vector to check parallelism with
00194     * @return true if vector is parallel
00195     * @return false otherwise
00196     */
00197     bool isPar(const Vec3 &rhs) const;
00198
00199     /**
00200     * @brief Check if vector is perpendicular to another
00201     *
00202     * @param[in] rhs vector to check perpendicularity with
00203     * @return true if vector is perpendicular
00204     * @return false otherwise
00205     */
00206     bool isPerp(const Vec3 &rhs) const;
00207
00208     /**
00209     * @brief Check if vector is equal to another
00210     *
00211     * @param[in] rhs vector to check equality with
00212     * @return true if vector is equal
00213     * @return false otherwise
00214     */
00215     bool isEqual(const Vec3 &rhs) const;
00216 };
00217
00218 /**
00219  * @brief Overloaded + operator
00220  *
00221  * @tparam T vector template parameter
00222  * @param[in] lhs first vector
00223  * @param[in] rhs second vector
00224  * @return Vec3<T> sum of two vectors
00225  */
00226 template <std::floating_point T>
00227 Vec3<T> operator+(const Vec3<T> &lhs, const Vec3<T> &rhs)
00228 {
00229     Vec3<T> res{lhs};
00230     res += rhs;
00231     return res;
00232 }
00233
00234 /**
00235  * @brief Overloaded - operator
00236  *
00237  * @tparam T vector template parameter
00238  * @param[in] lhs first vector
00239  * @param[in] rhs second vector
00240  * @return Vec3<T> res of two vectors
00241  */
00242 template <std::floating_point T>
00243 Vec3<T> operator-(const Vec3<T> &lhs, const Vec3<T> &rhs)
00244 {
00245     Vec3<T> res{lhs};
00246     res -= rhs;
00247     return res;
00248 }
00249
00250 /**
00251  * @brief Overloaded multiple by value operator
00252  *
00253  * @tparam nT type of value to multiply by
00254  * @tparam T vector template parameter
00255  * @param[in] val value to multiply by
00256  * @param[in] rhs vector to multiply by value
00257  * @return Vec3<T> result vector
00258  */
00259 template <Number nT, std::floating_point T>
00260 Vec3<T> operator*(const nT &val, const Vec3<T> &rhs)
00261 {
00262     Vec3<T> res{rhs};
00263     res *= val;
00264     return res;
00265 }
00266
00267 /**
00268  * @brief Overloaded multiple by value operator
00269  *
00270  * @tparam nT type of value to multiply by
00271  * @tparam T vector template parameter
00272  * @param[in] val value to multiply by
00273  * @param[in] lhs vector to multiply by value
00274  * @return Vec3<T> result vector
00275  */
00276 template <Number nT, std::floating_point T>
00277 Vec3<T> operator*(const Vec3<T> &lhs, const nT &val)

```



```

00278 {
00279     Vec3<T> res{lhs};
00280     res *= val;
00281     return res;
00282 }
00283
00284 /**
00285  * @brief Overloaded divide by value operator
00286  *
00287  * @tparam nT type of value to divide by
00288  * @tparam T vector template parameter
00289  * @param[in] val value to divide by
00290  * @param[in] lhs vector to divide by value
00291  * @return Vec3<T> result vector
00292  */
00293 template <Number nT, std::floating_point T>
00294 Vec3<T> operator/(const Vec3<T> &lhs, const nT &val)
00295 {
00296     Vec3<T> res{lhs};
00297     res /= val;
00298     return res;
00299 }
00300
00301 /**
00302  * @brief Dot product function
00303  *
00304  * @tparam T vector template parameter
00305  * @param[in] lhs first vector
00306  * @param[in] rhs second vector
00307  * @return T dot production
00308  */
00309 template <std::floating_point T>
00310 T dot(const Vec3<T> &lhs, const Vec3<T> &rhs)
00311 {
00312     return lhs.dot(rhs);
00313 }
00314
00315 /**
00316  * @brief Cross product function
00317  *
00318  * @tparam T vector template parameter
00319  * @param[in] lhs first vector
00320  * @param[in] rhs second vector
00321  * @return T cross production
00322  */
00323 template <std::floating_point T>
00324 Vec3<T> cross(const Vec3<T> &lhs, const Vec3<T> &rhs)
00325 {
00326     return lhs.cross(rhs);
00327 }
00328
00329 /**
00330  * @brief Triple product function
00331  *
00332  * @tparam T vector template parameter
00333  * @param[in] v1 first vector
00334  * @param[in] v2 second vector
00335  * @param[in] v3 third vector
00336  * @return T triple production
00337  */
00338 template <std::floating_point T>
00339 T triple(const Vec3<T> &v1, const Vec3<T> &v2, const Vec3<T> &v3)
00340 {
00341     return dot(v1, cross(v2, v3));
00342 }
00343
00344 /**
00345  * @brief Vec3 print operator
00346  *
00347  * @tparam T vector template parameter
00348  * @param[in, out] ost output stream
00349  * @param[in] vec vector to print
00350  * @return std::ostream& modified stream instance
00351  */
00352 template <std::floating_point T>
00353 std::ostream &operator<<(std::ostream &ost, const Vec3<T> &vec)
00354 {
00355     ost << "(" << vec.x << ", " << vec.y << ", " << vec.z << ")";
00356     return ost;
00357 }
00358
00359 /**
00360  * @brief Vec3 scan operator
00361  *
00362  * @tparam T vector template parameter
00363  * @param[in, out] ist input stream
00364  * @param[in, out] vec vector to scan

```

```

00365  * @return std::istream& modified stream instance
00366  */
00367  template <std::floating_point T>
00368  std::istream &operator>(std::istream &ist, Vec3<T> &vec)
00369  {
00370      ist >> vec.x >> vec.y >> vec.z;
00371      return ist;
00372  }
00373
00374  using Vec3D = Vec3<double>;
00375  using Vec3F = Vec3<float>;
00376
00377  template <std::floating_point T>
00378  bool Vec3<T>::operator==(const Vec3 &rhs) const
00379  {
00380      return isEqual(rhs);
00381  }
00382
00383  template <std::floating_point T>
00384  bool Vec3<T>::operator!=(const Vec3 &rhs) const
00385  {
00386      return !operator==(rhs);
00387  }
00388
00389  template <std::floating_point T>
00390  Vec3<T> &Vec3<T>::operator+=(const Vec3 &vec)
00391  {
00392      x += vec.x;
00393      y += vec.y;
00394      z += vec.z;
00395
00396      return *this;
00397  }
00398
00399  template <std::floating_point T>
00400  Vec3<T> &Vec3<T>::operator-=(const Vec3 &vec)
00401  {
00402      x -= vec.x;
00403      y -= vec.y;
00404      z -= vec.z;
00405
00406      return *this;
00407  }
00408
00409  template <std::floating_point T>
00410  Vec3<T> Vec3<T>::operator-() const
00411  {
00412      return Vec3{-x, -y, -z};
00413  }
00414
00415  template <std::floating_point T>
00416  template <Number nType>
00417  Vec3<T> &Vec3<T>::operator*=(nType val)
00418  {
00419      auto fval = static_cast<T>(val);
00420      x *= fval;
00421      y *= fval;
00422      z *= fval;
00423
00424      return *this;
00425  }
00426
00427  template <std::floating_point T>
00428  template <Number nType>
00429  Vec3<T> &Vec3<T>::operator/=(nType val)
00430  {
00431      auto fval = static_cast<T>(val);
00432      x /= fval;
00433      y /= fval;
00434      z /= fval;
00435
00436      return *this;
00437  }
00438
00439  template <std::floating_point T>
00440  T Vec3<T>::dot(const Vec3 &rhs) const
00441  {
00442      return x * rhs.x + y * rhs.y + z * rhs.z;
00443  }
00444
00445  template <std::floating_point T>
00446  Vec3<T> Vec3<T>::cross(const Vec3 &rhs) const
00447  {
00448      return Vec3{y * rhs.z - z * rhs.y, z * rhs.x - x * rhs.z, x * rhs.y - y * rhs.x};
00449  }
00450
00451  template <std::floating_point T>

```

```

00452 T Vec3<T>::length2() const
00453 {
00454     return dot(*this);
00455 }
00456
00457 template <std::floating_point T>
00458 T Vec3<T>::length() const
00459 {
00460     return std::sqrt(length2());
00461 }
00462
00463 template <std::floating_point T>
00464 Vec3<T> Vec3<T>::normalized() const
00465 {
00466     Vec3 res(*this);
00467     res.normalize();
00468     return res;
00469 }
00470
00471 template <std::floating_point T>
00472 Vec3<T> &Vec3<T>::normalize() &
00473 {
00474     T len2 = length2();
00475     if (isZeroThreshold(len2) || isEqualThreshold(len2, T{1}))
00476         return *this;
00477     return *this /= std::sqrt(len2);
00478 }
00479
00480 template <std::floating_point T>
00481 T &Vec3<T>::operator[](std::size_t i) &
00482 {
00483     switch (i % 3)
00484     {
00485     case 0:
00486         return x;
00487     case 1:
00488         return y;
00489     case 2:
00490         return z;
00491     default:
00492         throw std::logic_error{"Impossible case in operator[]\n"};
00493     }
00494 }
00495
00496 template <std::floating_point T>
00497 T Vec3<T>::operator[](std::size_t i) const &
00498 {
00499     switch (i % 3)
00500     {
00501     case 0:
00502         return x;
00503     case 1:
00504         return y;
00505     case 2:
00506         return z;
00507     default:
00508         throw std::logic_error{"Impossible case in operator[]\n"};
00509     }
00510 }
00511
00512 template <std::floating_point T>
00513 T &&Vec3<T>::operator[](std::size_t i) &&
00514 {
00515     switch (i % 3)
00516     {
00517     case 0:
00518         return std::move(x);
00519     case 1:
00520         return std::move(y);
00521     case 2:
00522         return std::move(z);
00523     default:
00524         throw std::logic_error{"Impossible case in operator[]\n"};
00525     }
00526 }
00527
00528 template <std::floating_point T>
00529 bool Vec3<T>::isPar(const Vec3 &rhs) const
00530 {
00531     return cross(rhs).isEqual(Vec3<T>{0});
00532 }
00533
00534 template <std::floating_point T>
00535 bool Vec3<T>::isPerp(const Vec3 &rhs) const
00536 {
00537     return isZeroThreshold(dot(rhs));
00538 }

```

```
00539
00540 template <std::floating_point T>
00541 bool Vec3<T>::isEqual(const Vec3 &rhs) const
00542 {
00543     return isEqualThreshold(x, rhs.x) && isEqualThreshold(y, rhs.y) && isEqualThreshold(z, rhs.z);
00544 }
00545
00546 } // namespace geom
00547
00548 #endif // __INCLUDE_PRIMITIVES_VEC3_HH__
```