Creating tables

```sql
CREATE TABLE cars (
    car_id INT AUTO_INCREMENT PRIMARY KEY,
    make VARCHAR(50) NOT NULL,
    model VARCHAR(50) NOT NULL,
    price DECIMAL(10,2) NOT NULL,
    yom INT NOT NULL
);
```

Inserting Values

```sql
INSERT INTO cars (make, model, price, yom)
VALUES
('Holden', 'Astra', 14000, 2009),
('BMW', 'X3', 35000, 2010),
('Ford', 'Falcon', 39000, 2013),
('Toyota', 'Corolla', 20000, 2012),
('Holden', 'Commodore', 28000, 2009);

```

Queries

1.

```sql
SELECT * FROM cars;

```

| | car_id | make | model | price | yom |
|---|---|---|---|---|---|
| Edit Copy Delete | 1 | Holden | Astra | 14000.00 | 2009 |
| Edit Copy Delete | 2 | BMW | X3 | 35000.00 | 2010 |
| Edit Copy Delete | 3 | Ford | Falcon | 39000.00 | 2013 |
| Edit Copy Delete | 4 | Toyota | Corolla | 20000.00 | 2012 |
| Edit Copy Delete | 5 | Holden | Commodore | 28000.00 | 2009 |

2.

```sql
SELECT make, model, price FROM cars ORDER BY make, model;
```

| make ▲ 1 | model ▲ 2 | price |
|---|---|---|
| BMW | X3 | 35000.00 |
| Ford | Falcon | 39000.00 |
| Holden | Astra | 14000.00 |
| Holden | Commodore | 28000.00 |
| Toyota | Corolla | 20000.00 |

3.

```
1 SELECT make, model FROM cars WHERE price >= 20000;
```

| make | model |
|---|---|
| BMW | X3 |
| Ford | Falcon |
| Toyota | Corolla |
| Holden | Commodore |

4.

```
1 SELECT make, AVG(price) FROM cars GROUP BY make;
```

| make | AVG(price) |
|---|---|
| BMW | 35000.000000 |
| Ford | 39000.000000 |
| Holden | 21000.000000 |
| Toyota | 20000.000000 |

5.

```
1 SELECT make, model FROM cars WHERE price < 15000 AND price > 10000;
```

| make | model |
|---|---|
| Holden | Astra |