

ATP FIX 4.4 Trade API Specification

v1.20

DOCUMENT HISTORY

Version	Date	Changes
v1.20	20260417	[v1.20.0] 1. Add 'TrsType' and 'TrsExpiryDate' in New Order Single(35=D) message for normal order 2. Add 'TrsExpiryDate' and 'TrsRate' in Execution Report(35=8) message 3. Add 'OnBehalfOfSubID' in New Order Single(35=D), Order Replace(35=G) and Order Cancel(35=F) message to identify specific message originator if the message was delivered by a third party
v1.19	20251024	[v1.19.0] 1. Add 'ExecRefID' in Execution Report(35=8) message 2. Add 'CanceledPrice' and 'CanceledQty' in Execution Report(35=8) message to support notification of external trade cancel reports
v1.18	20250919	[v1.18.3] 1. Add new feature for querying currency rates ◦ Request message: Currency Rate Request(35=UZU, 20004=?) ◦ Response data: Currency Rate Report(35=UZT, 20004=?) 2. Add new feature for querying funds detail ◦ Request message: Funds Detail Request(35=UFR, 20004=?) ◦ Response data: Funds Detail Report(35=UFD, 20004=?) 3. Add new data type: Amt 4. Update description of Sequence Number Reset [v1.18.2] 1. Replace the rejection of New Order Single(35=D) message mostly from Reject(35=3) to Execution Report: Rejection(35=8) message 2. Support 'TimeInForce' = 0 (Day) for TWAP/POV order in New Order Single(35=D) message and only for single-leg symbols [v1.18.1] 1. Add 'ClOrdID' in Order Cancel(35=F) message 2. Adjust the logic of pushing Execution Report: when an order is filled, the response of Execution Report (35=8, 150=I) will not be pushed for single leg symbol 3. Update description of 'TimeInForce' to set default value for TWAP/POV orders 4. Update description of 'UnderLyingSymbol' in Security Definition(35=d) message to specify "NONE" if underlying symbol is empty 5. Update description of Sequence Number Reset [v1.18.0] 1. Refactor APIs related to TWAP/POV orders 2. Add pending ack for orders 3. Update description of Order Replace(35=G) message to add supported order types 4. Make 'NextExpectedMsgSeqNum' optional in Logon(35=A) message 5. Change 'Note' from base64 encoding to plain text in New Order Single(35=D) and Execution Report(35=8) message

		6. Add examples of spread order in New Order Single(35=D) message 7. Add ' OrigClOrdID ' in Execution Report(35=8) and Order Cancel Reject(35=9) message 8. Add ' ParentOrderID ' in Execution Report(35=8) message
v1.17	20250324	1. Remove ' ClOrdID ' in Order Replace(35=G) and Order Cancel(35=F) message 2. Add ' OrigClOrdID ' in Order Replace(35=G) and Order Cancel(35=F) message 3. Remove ' Username ' in New Order Single(35=D) , Order Replace(35=G) and Order Cancel(35=F) message 4. Use UTC time for ' TransactTime ' in Execution Report(35=8) message 5. Update the value of ' ExecID ' of Execution Report(35=8) message 6. Fix tag id of ' LastObservedQty ' and ' LastObservedTime ' in Appendix: ATP FIX Tag 7. Add missing tag ' EffectiveTime ' in Appendix: ATP FIX Tag 8. Update examples of Logon with recovery message of Logon(35=A) message 9. Update descriptions of FIX Version
v1.16	20241211	1. Add ' ActualSymbol ' in Execution Report: Confirmation/Acknowledgement(35=8) message 2. Add ' ActualSymbol ' in Execution Report: Trade(35=8, 20004=?, 150=F) message
v1.15	20240914	1. Introduce TWAP/POV orders
v1.14	20240816	1. Add new feature for querying a specific order - Request message: Order Status Request(35=H, 20004=?) - Response data: Execution Report: Order Status(35=8, 20004=?, 150=F) 2. Add new feature for querying multiple orders - Request message: Order Mass Status Request(35=AF, 20004=?) - Response ack: Request Ack(35=URA, 20004=?) - Response data: Execution Report: Order Status(35=8, 20004=?, 150=F) 3. Add new feature for querying trades - Request message: Trade Capture Report Request(35=AD, 20004=?) - Response ack: Request Ack(35=URA, 20004=?) - Response data: Execution Report: Trade(35=8, 20004=?, 150=F) 4. Add new feature for querying positions - Request message: Request For Positions(35=AN, 20004=?) - Response ack: Request Ack(35=URA, 20004=?) - Response data: Position Report(35=AP, 20004=?) 5. Add Request Ack(35=URA, 20004=?) message to acknowledge that a request has been received and processed. The message will be introduced for the following requests: Order Mass Status Request(35=AF, 20004=?) Trade Capture Report Request(35=AD, 20004=?) Request For Positions(35=AN, 20004=?)
v1.13	20240725	1. Add new values of ' RefMsgType ' and ' BusinessRejectReason ' in Business Message Reject(35=j) message 2. Add ' SecurityExchange ', ' MIC ', ' Product ' in Execution Report: Confirmation/Acknowledgement(35=8) message
v1.12	20240614	1. Add ' MIC ' in Security Definition(35=d, 20004=?) message to indicate the Market Identifier Code of the symbol 2. Add ' MaturityDate ' in Security Definition(35=d, 20004=?) message to indicate the Last Trading Date of the symbol
v1.11	20240611	1. Add a new value '3' (Done for Day) of ' OrdStatus ' in Execution Report: Confirmation/Acknowledgement(35=8) and Order Cancel Reject(35=9) message

		2. Add a new value 'E' (Pending Replace) of 'ExecType' in Execution Report: Confirmation/Acknowledgement(35=8) message
v1.10	20240607	1. Add 'OrdRejReason' in Execution Report: Rejection(35=8) message 2. Add 'CxlRejReason' in Order Cancel Reject(35=9) message 3. Add new values of 'CxlRejResponseTo' in Order Cancel Reject(35=9) message to indicate that the reject response may apply to either an Order Cancel(35=F) or an Order Replace(35=G) message 4. Add 'RequestID' in Security Definition Request(35=c, 20004=?) and Security Definition(35=d, 20004=?) message 5. Deprecate 'SecurityReqID' in Security Definition Request(35=c, 20004=?) and Security Definition(35=d, 20004=?) message 6. Rename 'MaxChunk' to 'MaxShow' and update comments 7. Add Business Message Reject(35=j) message 8. Add description of session messages 9. Update description of application messages 10. Add appendix for ATP exchange code and ATP FIX tag
v1.9	20240524	1. Add Execution Report: Rejection(35=8) message to indicate the rejection of New Order Single(35=D) message 2. Rename Reject Report(35=9) message to Order Cancel Reject(35=9) message to indicate that the message concerns rejections of Order Replace(35=G) message or Order Cancel(35=F) message 3. Add description of application messages
v1.8	20240516	1. Update description and example of Logon(35=A) message 2. Add new values of 'ExecType' in Execution Report: Confirmation/Acknowledgement(35=8) message, broadening the scope of previous Order Status('I') with additional types 3. Update description of 'OrdStatus' in Execution Report: Confirmation/Acknowledgement(35=8) message 4. Add 'PossResend' in Execution Report: Confirmation/Acknowledgement(35=8) message 5. Add 'OutdatedFlag' in Execution Report: Confirmation/Acknowledgement(35=8) message
v1.7	20240304	1. Update 'Username' in Execution Report: Confirmation/Acknowledgement(35=8) for external trades
v1.6	20231109	1. 'OrigClOrdID' has been removed 2. 'ClOrdID' has been removed for orders submitted via non-FIX API in Execution Report: Confirmation/Acknowledgement(35=8) and RejectReport(35=9) message 3. 'ClOrdID' should be uniquely generated and provided by the client for orders submitted via the FIX API 4. 'ClOrdID' will now maintain a one-to-one relationship with orders submitted via the FIX API and will not change during the whole lifetime of the order 5. For Order Replace(35=G) and Order Cancel(35=F) message, prefer to use 'OrderID' over 'ClOrdID' to identify the active order 6. Active orders originating from both FIX API and non-FIX API sources can be replaced or canceled by using 'OrderID' within Order Replace(35=G) and Order Cancel(35=F) message 7. Certain fields in Execution Report: Confirmation/Acknowledgement(35=8) message will be conditionally displayed based on the values of 'OrderType' or 'TimeInForce', rather than being displayed by default. e.g. 'StopPrice', 'ExpireDate'
v1.5	20231011	1. Add 'Note' in Execution Report: Confirmation/Acknowledgement(35=8) message
v1.2	20230113	1. Add Required 'NextExpectedMsgSeqNum' in Logon(35=A) message 2. Logout(35=5) message will be sent by server if invalid logon message received 3. 'OrigTime' is provided in Execution Report: Confirmation/Acknowledgement(35=8) and Reject Report(35=9) message 4. Update usage of 'ClOrdID'

		5. The SSL support is required to secure FIX communication for trading session
v1.1	20221208	1. Remove unused message types
v1.0	20210322	1. Initial version added

CONTENTS

DOCUMENT HISTORY	1
CONTENTS	5
1. Introduction	7
1.1. Disclaimer	7
1.2. Scope Of This Document	7
1.3. FIX Version	7
2. Connectivity	7
2.1. Connection Type	7
2.2. Hours Of Operations	7
2.3. Sequence Number Reset	7
2.4. Security And Authentication	7
3. Message Overview	8
3.1. Supported Message Types (35=?)	8
3.2. Data Types	9
3.3. General Message Header	9
3.4. General Message Trailer	10
4. Session Messages	11
4.1. Logon(35=A) (Client <-> ATP)	11
4.2. Heartbeat(35=0) (Client <-> ATP)	12
4.3. Test Request(35=1) (Client <-> ATP)	12
4.4. Resend Request(35=2) (Client <-> ATP)	13
4.5. Reject(35=3) (ATP -> Client)	13
4.6. Sequence Reset(35=4) (Client <-> ATP)	13
4.7. Logout(35=5) (Client <-> ATP)	14
5. Application Messages	15
5.1. New Order Single(35=D) (Client -> ATP)	15
5.2. Order Replace(35=G) (Client -> ATP)	19
5.3. Order Cancel(35=F) (Client -> ATP)	20
5.4. Execution Report: Confirmation/Acknowledgement(35=8) (ATP -> Client)	21
5.5. Execution Report: Rejection(35=8) (ATP -> Client)	24
5.6. Order Cancel Reject(35=9) (ATP -> Client)	26
5.7. Security Definition Request(35=c,20004=?) (Client -> ATP)	27
5.8. Security Definition(35=d,20004=?) (ATP -> Client)	28
5.9. Business Message Reject(35=j) (ATP -> Client)	30
5.10. Request Ack(35=URA,20004=?) (ATP -> Client)	30
5.11. Order Status Request(35=H,20004=?) (Client -> ATP)	31
5.12. Order Mass Status Request(35=AF,20004=?) (Client -> ATP)	32
5.13. Execution Report: Order Status(35=8,20004=?,150#F) (ATP -> Client)	33

5.14.	Trade Capture Report Request (35=AD,20004=?) (Client -> ATP)	36
5.15.	Execution Report: Trade (35=8,20004=?,150=F) (ATP -> Client)	37
5.16.	Request For Positions (35=AN,20004=?) (Client -> ATP)	39
5.17.	Position Report (35=AP,20004=?) (ATP -> Client)	40
5.18.	Currency Rate Request (35=UZU,20004=?) (Client -> ATP)	41
5.19.	Currency Rate Report (35=UZT,20004=?) (ATP -> Client)	42
5.20.	Funds Detail Request (35=UFR,20004=?) (Client -> ATP)	43
5.21.	Funds Detail Report (35=UFD,20004=?) (ATP -> Client)	44
6.	Information Needed From ATP	46
7.	Conformance Test.....	47
8.	Support and FAQs	47
9.	Appendix	48
9.1.	ATP Exchange Code.....	48
9.2.	ATP FIX Tag	49

1. Introduction

1.1. Disclaimer

This confidential document is the property of ATP and neither the document nor its contents may be disclosed to a third party, nor may it be copied, without ATP's prior written consent.

ATP endeavors to ensure that the data and other material in this publication are correct and complete but does not accept liability for any error herein or omissions here from. The development of ATP's products and services is continuous and published information may not be up to date.

1.2. Scope Of This Document

This document is intended to serve software developers as an implementation guide for the ATP FIX API.

1.3. FIX Version

ATP supports FIX version 4.4, but with custom message types and fields (and more custom message types and fields may be added in the future). For further information about this version please refer to the specifications published by the FIX Protocol Organization under <https://www.fixtrading.org/standards/fix-4-4>

2. Connectivity

2.1. Connection Type

Connection to ATP's FIX engine is available via TCP/IP. SSL/TLS is **required** to secure FIX communication for trading session.

2.2. Hours Of Operations

Connectivity to ATP's FIX engine is available on following time (America/New_York):

- SUN 18:00 - MON 17:30
- MON 18:00 - TUE 17:30
- TUE 18:00 - WED 17:30
- WED 18:00 - THU 17:30
- THU 18:00 - FRI 17:30

2.3. Sequence Number Reset

ATP FIX server will reset the sequence number to start from 1 (34=1 and 141 is N or omitted) each trading day on its startup (around 18:00, America/New_York), which is called **Normal Reset**. **Please ask your clients to do the same when first logon every trading day.**

Message sequence numbers can also be reset, when desired, by setting 34=1 and 141=Y when sending a Logon (35=A) message, which is called **Force Reset**.

Trading connections have to be configured to persist sequence numbers on logon (141=N).

2.4. Security And Authentication

Once the connection to ATP FIX server is established, client should authenticate against the server with username and password added to the Logon(35=A) message.

3. Message Overview

Each FIX message consists of a stream of <tag>=<value> fields. A fix message consists of 3 elements, a Header, a Body and a Trailer. All fields in a FIX message are terminated by ASCII SOH (#001) character.

- **Header:** Included in each message, it mainly identifies the message type, length and routing.
- **Body:** It defines the content of the actual business level data.
- **Trailer:** Included in each message with checksum value.

3.1. Supported Message Types (35=?)

Messages that are not in this list will be rejected.

Message Type	Message Name	Message Direction
A	Logon	Client <-> ATP
0	Heartbeat	Client <-> ATP
1	Test Request	Client <-> ATP
2	Resend Request	Client <-> ATP
3	Reject	ATP -> Client
4	Sequence Reset	Client <-> ATP
5	Logout	Client <-> ATP
D	New Order Single	Client -> ATP
G	Order Replace	Client -> ATP
F	Order Cancel	Client -> ATP
8	Execution Report	ATP -> Client
9	Order Cancel Reject	ATP -> Client
c	Security Definition Request	Client -> ATP
d	Security Definition	ATP -> Client
j	Business Message Reject	ATP -> Client
H	Order Status Request	Client -> ATP
AF	Order Mass Status Request	Client -> ATP
AN	Request For Positions	Client -> ATP
AD	Trade Capture Report Request	Client -> ATP
AP	Position Report	ATP -> Client
URA	Request Ack	ATP -> Client

UZU	Currency Rate Request	Client -> ATP
UZT	Currency Rate Report	ATP -> Client
UFR	Funds Detail Request	Client -> ATP
UFD	Funds Detail Report	ATP -> Client

3.2. Data Types

Each field within a FIX message has an associated data type allowing for data validation.

Type	Comments
Int	Sequence of digits without commas or decimals and optional sign character (ASCII characters "-", "0" - "9"). The sign character utilizes one byte (i.e. positive int is "99999" while negative int is "-99999")
Float	Sequence of digits with optional decimal point and sign character (ASCII characters "-", "0" - "9" and "."); the absence of the decimal point within the string will be interpreted as the float representation of an integer value. All float fields must accommodate up to 15 digits. The number of decimal places used should be a factor of business/market needs and mutual agreement between counterparties
Char	Single character value, can include any alphanumeric character or punctuation except the delimiter. All char fields are case sensitive (i.e. m - M)
String	Alpha-numeric free format strings can include any character or punctuation except the delimiter. All char fields are case sensitive (i.e. morstatt - Morstatt)
Boolean	A char field (see definition of "Char" above) containing one of two values: 'Y' = True/Yes 'N' = False/No
Currency	String field (see definition of "String" above) representing a currency type. E.g. "USD" for US dollar, "HKD" for HongKong dollar, "CNY" for Onshore Chinese Yuan, "CNH" for Offshore Chinese Yuan
Timestamp	String field (see definition of "String" above) representing the Time/date combination in UTC (Universal Time Coordinated, also known as "GMT") in YYYYMMDD-HH:MM:SS.sss (milliseconds) format, colons, dash, and period required
LocalMktDate	String field (see definition of "String" above) representing the date of local market (vs. UTC) in YYYYMMDD format
Price	Float field (see definition of "Float" above) representing a price
Amt	Float field (see definition of "float" above) typically representing a Price times a Qty
SeqNum	Int field (see definition of "Int" above) representing a message sequence number. Value must be positive
Qty	Int field (see definition of "Int" above) capable of storing quantities of derivatives, such as futures and options, denominated in whole units for trading purposes
Exchange	String field (see definition of "String" above) representing a market or exchange. Valid values: See Appendix-ATP Exchange Code
NumInGroup	Int field (see definition of "Int" above) representing the number of entries in a repeating group. Value must be positive.

3.3. General Message Header

All FIX messages use the standard message header, as specified by the FIX 4.4 specification, below describes the tags associated with the message header. Any message that does not have these tags in the correct order will be rejected.

Tag	Field Name	Req'd	Data Type	Comments
8	BeginString	Y	String	Identifies beginning of new message and protocol version (always first field in message)
9	BodyLength	Y	Int	Message length (in bytes) forward to the CheckSum field (always second field in message)
35	MsgType	Y	String	Defines message type (always 3rd tag in message)
49	SenderCompID	Y	String	Assigned value used to identify the Client sending messages (will be provided by ATP)
56	TargetCompID	Y	String	Assigned value used to identify receiving party (will be provided by ATP)
34	MsgSeqNum	Y	SeqNum	Integer message sequence number
52	SendingTime	Y	Timestamp	Message transmission time in UTC/GMT

3.4. General Message Trailer

Each message is terminated by a standard trailer. The trailer is used to segregate messages and contains the three-digits characters representation of a checksum value:

Tag	Field Name	Req'd	Data Type	Comments
10	Checksum	Y	Int	Three digits characters representing the checksum value of the message

4. Session Messages

4.1. Logon (35=A) (Client <-> ATP)

After establishing your TCP connection with the ATP FIX server, a Logon(35=A) must be the first message that the FIX client sends.

The initial user login attempt after session reset may **not** receive an immediately response from the server (due to loading of user-related internal data).

If the login response is not received within an acceptable period, the login should be considered a failure. Subsequent login attempts may be considered later.

Possible response message:

- Logon(35=A)
- Logout(35=5)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=A
98	EncryptMethod	Y	Int	Use of Encryption, set to "0"
108	HeartBtInt	Y	Int	Heart beat interval in seconds
141	ResetSeqNumFlag	N	Boolean	Indicates both sides of a FIX session should reset sequence numbers
553	Username	Y	String	Client's username
554	Password	Y	String	Client's password
789	NextExpectedMsgSeqNum	N	Int	Next expected 'MsgSeqNum' value to be received. ATP FIX server will react to the number sent from client: If equal to the next-to-be-assigned sequence in server, proceed sending new messages beginning with that number. If lower than the next-to-be-assigned sequence in server, recovery all messages from the last message delivered prior to this Logon message through the specific 'NextExpectedMsgSeqNum' sending them in order; then Sequence Reset message will be sent over the sequence number used in Logon message and proceed sending newly queue messages with a sequence number one higher than the original Logon message. If higher than the next-to-be-assigned sequence in server, send Logout to abort the session
	Standard Trailer	Y		

Full Logon Example

Logon

Client -> ATP: 8=FIX.4.4 9=101 35=A 49=CLIENT01 56=ATPFIX 34=1 52=20230112-08:46:47.852 98=0 108=10 553=user01 554=password01 789=1 10=219

ATP -> Client: 8=FIX.4.4 9=75 35=A 49=ATPFIX 56=CLIENT01 34=1 52=20230112-08:46:47.905 98=0 108=10 789=2 10=010

Logon with recovery message

Client -> ATP: 8=FIX.4.4 9=100 35=A 49=CLIENT01 56=ATPFIX 34=10 52=20250324-02:27:34.417 98=0 108=10 789=5 553=user01 554=password01 10=131

ATP -> Client: 8=FIX.4.4 9=77 35=A 49=ATPFIX 56=CLIENT01 34=12 52=20250324-02:27:34.498 98=0 108=10 789=11 10=113

ATP -> Client: 8=FIX.4.4 9=315 35=8 49=ATPFIX 56=CLIENT01 34=5 43=Y 97=N 52=20250324-02:27:34.503
 122=20250324-02:26:16.952 37=MUGKCXmq 17=0 150=I 39=2 1=CLIENT01 55=CU3M-LME 460=CU 207=LME 54=2 38=1 40=2
 44=9919 15=USD 59=0 151=0 14=1 6=9919 60=20250324-02:26:03.011 77=A 58=Filled 20001=1 20003=Y 20005=XLME
 553=user01 42=20250324-02:26:03.011 10=029

ATP -> Client: 8=FIX.4.4 9=100 35=4 49=ATPFIX 56=CLIENT01 34=6 43=Y 52=20250324-02:27:34.503 122=20250324-
 02:27:34.503 123=Y 36=13 10=034

Logon with the following outdated execution reports

Client -> ATP: 8=FIX.4.4 9=99 35=A 49=CLIENT01 56=ATPFIX 34=9 52=20250324-03:03:32.905 98=0 108=10 789=9
 553=user01 554=password01 10=059

ATP -> Client: 8=FIX.4.4 9=76 35=A 49=ATPFIX 56=CLIENT01 34=9 52=20250324-03:03:32.995 98=0 108=10 789=10
 10=064

ATP -> Client: 8=FIX.4.4 9=324 35=8 49=ATPFIX 56=CLIENT01 34=10 97=N 52=20250324-03:03:33.304 37=MUGKJySe
 17=pONa9eR_1742628603965 150=F 39=2 1=CLIENT01 55=CU3M-LME 460=CU 207=LME 54=2 38=1 40=2 15=USD 59=1 32=1
 31=9921 151=0 14=1 75=20250324 60=20250324-02:55:33.839 77=A 20001=1 20003=Y 20005=XLME 20007=CU250624-LME
 553=user01 42=20250324-02:55:33.839 10=108

ATP -> Client: 8=FIX.4.4 9=285 35=8 49=ATPFIX 56=CLIENT01 34=11 97=N 52=20250324-03:03:33.309 37=MUGKJySe 17=0
 150=I 39=2 1=CLIENT01 55=CU3M-LME 460=CU 207=LME 54=2 38=1 40=2 44=9920 15=USD 59=1 151=0 14=1 6=9921
 60=20250324-02:55:33.840 77=A 58=Filled 20001=1 20003=Y 20005=XLME 553=user01 42=20250324-02:55:33.840 10=093

Invalid Logon

Client -> ATP: 8=FIX.4.4 9=101 35=A 49=CLIENT01 56=ATPFIX 34=5 52=20230112-02:48:46.533 98=0 108=10 789=5
 553=user01 554=password01 10=218

ATP -> Client: 8=FIX.4.4 9=141 35=5 49=ATPFIX 56=CLIENT01 34=1 52=20230112-02:48:46.583 58=Tag 789
 (NextExpectedMsgSeqNum) is higher than expected. Expected 1. Received 5. 10=224

4.2. Heartbeat (35=0) (Client <-> ATP)

The Heartbeat monitor the status of the communication link. It is sent automatically based on the interval set in the logon message.

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=0
112	TestReqID	N	String	Req'd when the heartbeat is the result of a Test Request(35=1) message
	Standard Trailer	Y		

Heartbeat Example

Client -> ATP: 8=FIX.4.4 9=57 35=0 49=CLIENT01 56=ATPFIX 34=3 52=20210304-06:35:46.673 10=202

4.3. Test Request (35=1) (Client <-> ATP)

The Test Request is used to force a heartbeat in order to verify connectivity status and sequence number generation.

Possible response message:

- Heartbeat(35=0)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=1
112	TestReqID	Y	String	A unique identifier for this test message
	Standard Trailer	Y		

Test Request Example

Client -> ATP: 8=FIX.4.4 9=67 35=1 49=CLIENT01 56=ATPFIX 34=2 52=20210304-06:39:43.570 112=reqID 10=111

4.4. Resend Request (35=2) (Client <-> ATP)

In the event that a sequence number gap is detected, the Resend Request(35=2) message notifies the opposite party to resend message.

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=2
7	BeginSeqNo	Y	Int	Message sequence number of first message in range to be resent
16	EndSeqNo	Y	Int	Message sequence number of last message in range to be resent. If request is for a single message 'BeginSeqNo' = 'EndSeqNo'. If request is for all messages subsequent to a particular message, 'EndSeqNo' = 0 (representing infinity)
	Standard Trailer	Y		

Resend Request Example

Client -> ATP: 8=FIX.4.4 9=66 35=2 49=CLIENT01 56=ATPFIX 34=8 52=20210304-07:43:46.588 7=5 16=0 10=085

4.5. Reject (35=3) (ATP -> Client)

ATP FIX server uses this message to respond to a message that could not be processed. Rejections for unsupported tags, invalid message format, or field restrictions are also identified. Where applicable, the reason for the reject is included in 'Text'. This session level reject message can be sent in response to any message sent from the FIX client to the ATP FIX server.

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=3
45	RefSeqNum	Y	Int	MsgSeqNum of rejected message
371	RefTagID	N	Int	The tag number of the FIX field being referenced
372	RefMsgType	N	String	The MsgType of the FIX message being referenced
373	SessionRejectReason	N	Int	Code to identify reason for a session-level Reject(35=3) message. Valid values: 1 = Required tag missing 4 = Tag specified without a value 5 = Value is out of range for this tag 11 = Invalid MsgType 99 = Other
58	Text	N	String	Message to explain reason for rejection
	Standard Trailer	Y		

Reject Request Example

ATP -> Client: 8=FIX.4.4 9=111 35=3 34=4 49=ATPFIX 52=20250625-06:21:42.230 56=CLIENT01 45=4 58=Required tag 11 is missing 371=11 372=D 373=1 10=011

4.6. Sequence Reset (35=4) (Client <-> ATP)

In the event that either system detects an error in sequence numbers, this message is sent to rectify the situation.

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=4

123	GapFillFlag	N	Boolean	Indicates that the Sequence Reset(35=4) message is replacing administrative or application messages that will not be resent. Valid values: Y = Gap Fill message, MsgSeqNum field valid N = Sequence Reset, ignore MsgSeqNum
36	NewSeqNo	Y	Int	New sequence number
	Standard Trailer	Y		

Sequence Reset Example:

ATP -> Client: 8=FIX.4.4 9=100 35=4 49=ATPFIx 56=CLIENT01 34=5 43=Y 52=20210305-10:48:34.613 122=20210305-10:48:34.613 123=Y 36=15 10=033

4.7. Logout(35=5) (Client <-> ATP)

The Logout(35=5) message is the last message sent on the connection. Either the ATP FIX server or a FIX client can send the Logout(35=5) message.

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=5
58	Text	N	String	Reason for logout
	Standard Trailer	Y		

Logout Example

Client -> ATP: 8=FIX.4.4 9=57 35=5 49=CLIENT01 56=ATPFIx 34=9 52=20210304-06:43:13.746 10=207

ATP -> Client: 8=FIX.4.4 9=84 35=5 49=ATPFIx 56=CLIENT01 34=11 52=20210304-06:43:13.747 58=Logout acknowledgement 10=118

5. Application Messages

5.1. New Order Single (35=D) (Client -> ATP)

The FIX client sends this message to place an order with the ATP FIX server.

Possible response message:

- Reject(35=3)
- Execution Report: Confirmation/Acknowledgement(35=8)
- Execution Report: Rejection(35=8)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=D
11	ClOrdID	Y	String	Unique identifier of the order as assigned by client
1	Account	Y	String	Account as provided by Client
55	Symbol	Y	String	Symbol to trade on
54	Side	Y	Int	Side of order: 1 = Buy 2 = Sell
38	OrderQty	Y	Int	Quantity of the order
40	OrdType	Y	Char	Type of order: 1 = Market 2 = Limit 3 = Stop 4 = Stop Limit 5 = Iceberg K = Market Limit t = TWAP p = POV
44	Price	C	Price	Required if 'OrdType'=2, 4 or 5
99	StopPrice	C	Price	Required if 'OrdType'=3 or 4
110	MinQty	C	Qty	Minimum quantity of an order to be executed. Default value is 0, required if 'TimeInForce'=3
210	MaxShow	C	Qty	Maximum quantity within an order to be shown to other customers, required if 'OrdType'=5
432	ExpireDate	C	LocalMktDate	Expire date, required if 'TimeInForce'=6
77	OffsetFlag	N	String	Type of offset flag: A = Auto O = Open C = Close CY = CloseYesterday CT = CloseToday C-CT-O = Close-CloseToday-Open CT-C-O = CloseToday-Close-Open C-O = Close-Open

				CT-0 = CloseToday-Open CY-0 = CloseYesterday-Open
20001	HedgeFlag	N	Int	Type of hedge flag: 1 = Speculation 2 = Arbitrages 3 = Hedge
59	TimeInForce	N	Int	Type of time in force. Only 0 and 1 are supported for 'OrdType'=t, p Valid values: 0 = Day (default value of normal order) 1 = GTC (default value of TWAP/POV order) 3 = IOC 4 = FOK 6 = GTD
60	TransactTime	N	Timestamp	UTC Timestamp of this order request
20002	Note	N	String	Order notes in text format
20084	TrsType	N	String	TRS type. Valid values: 1 = TRS (default value) 2 = CompoTRS
20085	TrsExpiryDate	C	LocalMktDate	TRS expiry date. Required if 'TrsType'=2
20015	SubOrderQty	C	Qty	The quantities of each individual order placement. Required if 'OrdType'=t, p
20011	PriceType	C	Char	Type of price. Required if 'OrdType'=t, p. Valid values: L = Last Trade B = Market Buy S = Market Sell P = Best Bid/Offer
20012	PriceDiffInTick	C	Int	The price difference in tick which the individual order is placed. Positive values increase the probability of order execution, while negative values decrease it. Required if 'OrdType'=t, p
20018	TriggerTimeInterval	C	Int	Time interval in milliseconds between order placements for the order. Required if 'OrdType'=t, p
20019	CancelTimeInterval	C	Int	Time interval in milliseconds between order cancellations for the order. The value should not exceed the 'TriggerTimeInterval'. Required if 'OrdType'=t, p
20013	EnableLimitPrice	C	Boolean	Enable limit price for order placements. Required if 'OrdType'=t, p. Valid values: Y = Enabled N = Disabled
20014	LimitPrice	C	Price	Limit Price for order placements. Required if 'EnableLimitPrice'=Y

168	EffectiveTime	N	Timestamp	Effective time of the order. The order is activated immediately if this field is not set. The value should be set beyond the current time. Optional if 'OrdType'=t, p
126	ExpireTime	N	Timestamp	Expire time of the order. The order continues to execute until completion or cancellation if this field is not set. The value should be set beyond the current time and must be later than the 'EffectiveTime'. Optional if 'OrdType'=t, p
20020	MaxCancelOrderTimes	N	Int	The maximum limit on the number of order cancellation. If this field is not set, there is no limit on the number of order cancellations. Optional if 'OrdType'=t, p
20035	ExpectedParticipationRatio	C	Float	The expect ratio of the trader's order quantities relative to the total market quantities. The value should range from 0 (exclusive) to 1.0 (exclusive). Required if 'OrdType'=p
20026	CumulateUnmatchedQty	C	Boolean	Indicates whether to tracks the cumulative quantities of unmatched orders for the POV order, cumulating these quantities for inclusion in the next order placement. Required if 'OrdType'=p. Valid values: Y = Yes N = No
116	OnBehalfOfSubID	N	String	Assigned value used to identify specific message originator (i.e. trader) if the message was delivered by a third party
	Standard Trailer	Y		

New Order Single Example

Normal Symbol

Client -> ATP: 8=FIX.4.4 9=143 35=D 34=254 49=CLIENT01 52=20260407-07:19:51.531 56=ATPFIX 1=CLIENT01 11=2hIfK 38=5 40=2 44=111.74 54=1 55=BRN2606-ICE 20084=2 20085=20260410 10=142

ATP -> Client: 8=FIX.4.4 9=272 35=8 34=297 49=ATPFIX 52=20260407-07:19:51.600 56=CLIENT01 1=CLIENT01 6=0 11=2hIfK 14=0 17=p_DpNQ9Qdg 37=tmp_DpNQ9Qdh_2 38=5 39=A 40=2 42=20260407-07:19:51.590 44=111.74 54=1 55=BRN2606-ICE 59=0 60=20260407-07:19:51.590 77=A 99=0 110=0 150=A 151=5 20001=1 20085=20260410 10=016

ATP -> Client: 8=FIX.4.4 9=299 35=8 34=298 49=ATPFIX 52=20260407-07:19:51.912 56=CLIENT01 1=CLIENT01 6=0 11=2hIfK 14=0 15=USD 17=bJTbJ83TS 37=MVG5TiH1 38=5 39=0 40=2 42=20260407-07:19:52.121 44=111.74 54=1 55=BRN2606-ICE 59=0 60=20260407-07:19:52.121 77=A 99=0 110=0 150=0 151=5 207=ICE 460=BRN 553=user01 20001=1 20085=20260410 10=198

ATP -> Client: 8=FIX.4.4 9=388 35=8 34=309 49=ATPFIX 52=20260407-07:24:21.277 56=CLIENT01 1=CLIENT01 6=111.73 11=2hIfK 14=4 15=USD 17=kUcBbRC_7447181333611421696-517645619 31=111.73 32=4 37=MVG5TiH1 38=5 39=1 40=2 42=20260407-07:24:21.518 44=111.74 54=1 55=BRN2606-ICE 59=0 60=20260407-07:24:21.518 75=20260407 77=A 99=0 110=0 150=F 151=1 207=ICE 460=BRN 553=user01 20001=1 20007=BRN2606-ICE 20085=20260410 20086=7.54 10=136

TWAP Order

Client -> ATP: 8=FIX.4.4 9=183 35=D 34=109 49=CLIENT01 52=20250623-03:00:09.506 56=ATPFIX 1=CLIENT01 11=c1OrdIDV18 38=4 40=t 54=2 55=CU3M-LME 20010=0 20011=B 20012=0 20013=N 20015=2 20018=30000 20019=30000 20021=N 10=110

ATP -> Client: 8=FIX.4.4 9=232 35=8 34=115 49=ATPFX 52=20250623-03:00:09.518 56=CLIENT01 1=CLIENT01 6=0
11=c1OrdIDV18 14=0 17=p_wlrILEwa 37=tmp_wlrILEwb_3 38=4 39=A 40=t 42=20250623-03:00:09.518 54=2 55=CU3M-LME
60=20250623-03:00:09.518 77=A 150=A 151=4 20001=1 10=000

ATP -> Client: 8=FIX.4.4 9=275 35=8 34=116 49=ATPFX 52=20250623-03:00:09.558 56=CLIENT01 1=CLIENT01 6=0
11=c1OrdIDV18 14=0 15=USD 17=chBNacLTU 37=AOUouQxdK 38=4 39=0 40=t 42=20250623-03:00:09.509 54=2 55=CU3M-LME
59=1 60=20250623-03:00:09.509 77=A 150=0 151=4 207=LME 460=CU 553=user01 20001=1 20005=XLME 10=055

ATP -> Client: 8=FIX.4.4 9=312 35=8 34=117 49=ATPFX 52=20250623-03:00:09.558 56=CLIENT01 1=CLIENT01 6=0
11=RD_wlrIMSCO 14=0 15=USD 17=bZ7Mhhog1 37=AOUouQxdP 38=2 39=0 40=2 42=20250623-03:00:09.709 44=9622.5 54=2
55=CU3M-LME 59=0 60=20250623-03:00:09.709 77=A 99=0 110=0 150=0 151=2 207=LME 460=CU 553=user01 20001=1
20005=XLME 20037=AOUouQxdK 10=162

ATP -> Client: 8=FIX.4.4 9=338 35=8 34=118 49=ATPFX 52=20250623-03:00:09.562 56=CLIENT01 1=CLIENT01 6=9622.5
11=c1OrdIDV18 14=2 15=USD 17=it4JfmT_1750491006761 31=9622.5 32=2 37=AOUouQxdK 38=4 39=1 40=t 42=20250623-
03:00:09.710 54=2 55=CU3M-LME 59=1 60=20250623-03:00:09.710 75=20250623 77=A 150=F 151=2 207=LME 460=CU
553=user01 20001=1 20005=XLME 20007=CU250923-LME 10=203

ATP -> Client: 8=FIX.4.4 9=375 35=8 34=119 49=ATPFX 52=20250623-03:00:09.563 56=CLIENT01 1=CLIENT01 6=9622.5
11=RD_wlrIMSCO 14=2 15=USD 17=it4JfmT_1750491006761 31=9622.5 32=2 37=AOUouQxdP 38=2 39=2 40=2 42=20250623-
03:00:09.710 44=9622.5 54=2 55=CU3M-LME 59=0 60=20250623-03:00:09.710 75=20250623 77=A 99=0 110=0 150=F 151=0
207=LME 460=CU 553=user01 20001=1 20005=XLME 20007=CU250923-LME 20037=AOUouQxdK 10=026

ATP -> Client: 8=FIX.4.4 9=312 35=8 34=125 49=ATPFX 52=20250623-03:00:39.558 56=CLIENT01 1=CLIENT01 6=0
11=RD_wlrKomiQ 14=0 15=USD 17=cgFI5iyug 37=AOUouR5RL 38=2 39=0 40=2 42=20250623-03:00:39.714 44=9622.5 54=2
55=CU3M-LME 59=0 60=20250623-03:00:39.714 77=A 99=0 110=0 150=0 151=2 207=LME 460=CU 553=user01 20001=1
20005=XLME 20037=AOUouQxdK 10=197

ATP -> Client: 8=FIX.4.4 9=338 35=8 34=126 49=ATPFX 52=20250623-03:00:39.560 56=CLIENT01 1=CLIENT01 6=9622.5
11=c1OrdIDV18 14=4 15=USD 17=muxZeIc_1750491006764 31=9622.5 32=2 37=AOUouQxdK 38=4 39=2 40=t 42=20250623-
03:00:39.715 54=2 55=CU3M-LME 59=1 60=20250623-03:00:39.715 75=20250623 77=A 150=F 151=0 207=LME 460=CU
553=user01 20001=1 20005=XLME 20007=CU250923-LME 10=034

ATP -> Client: 8=FIX.4.4 9=375 35=8 34=127 49=ATPFX 52=20250623-03:00:39.560 56=CLIENT01 1=CLIENT01 6=9622.5
11=RD_wlrKomiQ 14=2 15=USD 17=muxZeIc_1750491006764 31=9622.5 32=2 37=AOUouR5RL 38=2 39=2 40=2 42=20250623-
03:00:39.715 44=9622.5 54=2 55=CU3M-LME 59=0 60=20250623-03:00:39.715 75=20250623 77=A 99=0 110=0 150=F 151=0
207=LME 460=CU 553=user01 20001=1 20005=XLME 20007=CU250923-LME 20037=AOUouQxdK 10=093

POV Order

Client -> ATP: 8=FIX.4.4 9=185 35=D 34=279 49=CLIENT01 52=20250623-03:14:23.290 56=ATPFX 1=CLIENT01
11=c1OrdIDV20 38=4 40=p 54=2 55=CU3M-LME 20011=B 20012=0 20013=N 20015=2 20018=60000 20019=60000 20026=Y
20035=0.5 10=238

ATP -> Client: 8=FIX.4.4 9=232 35=8 34=291 49=ATPFX 52=20250623-03:14:23.293 56=CLIENT01 1=CLIENT01 6=0
11=c1OrdIDV20 14=0 17=p_wlsEx00G 37=tmp_wlsEx00H_4 38=4 39=A 40=p 42=20250623-03:14:23.292 54=2 55=CU3M-LME
60=20250623-03:14:23.292 77=A 150=A 151=4 20001=1 10=224

ATP -> Client: 8=FIX.4.4 9=275 35=8 34=292 49=ATPFX 52=20250623-03:14:23.304 56=CLIENT01 1=CLIENT01 6=0
11=c1OrdIDV20 14=0 15=USD 17=cotFeQ2G3 37=AOUouUXjy 38=4 39=0 40=p 42=20250623-03:14:23.291 54=2 55=CU3M-LME
59=1 60=20250623-03:14:23.291 77=A 150=0 151=4 207=LME 460=CU 553=user01 20001=1 20005=XLME 10=055

ATP -> Client: 8=FIX.4.4 9=312 35=8 34=304 49=ATPFX 52=20250623-03:15:23.318 56=CLIENT01 1=CLIENT01 6=0
11=RD_wlsICBki 14=0 15=USD 17=cBhj3fk90 37=AOUouUnLp 38=1 39=0 40=2 42=20250623-03:15:23.492 44=9627.5 54=2
55=CU3M-LME 59=0 60=20250623-03:15:23.492 77=A 99=0 110=0 150=0 151=1 207=LME 460=CU 553=user01 20001=1
20005=XLME 20037=AOUouUXjy 10=144

ATP -> Client: 8=FIX.4.4 9=338 35=8 34=305 49=ATPFX 52=20250623-03:15:23.321 56=CLIENT01 1=CLIENT01 6=9627.5
11=c1OrdIDV20 14=1 15=USD 17=rtXTqr8_1750491006767 31=9627.5 32=1 37=AOUouUXjy 38=4 39=1 40=p 42=20250623-
03:15:23.493 54=2 55=CU3M-LME 59=1 60=20250623-03:15:23.493 75=20250623 77=A 150=F 151=3 207=LME 460=CU
553=user01 20001=1 20005=XLME 20007=CU250923-LME 10=031

ATP -> Client: 8=FIX.4.4 9=375 35=8 34=306 49=ATPFX 52=20250623-03:15:23.321 56=CLIENT01 1=CLIENT01 6=9627.5
11=RD_wlsICBki 14=1 15=USD 17=rtXTqr8_1750491006767 31=9627.5 32=1 37=AOUouUnLp 38=1 39=2 40=2 42=20250623-
03:15:23.493 44=9627.5 54=2 55=CU3M-LME 59=0 60=20250623-03:15:23.493 75=20250623 77=A 99=0 110=0 150=F 151=0
207=LME 460=CU 553=user01 20001=1 20005=XLME 20007=CU250923-LME 20037=AOUouUXjy 10=133

ATP -> Client: 8=FIX.4.4 9=312 35=8 34=318 49=ATPFX 52=20250623-03:16:23.317 56=CLIENT01 1=CLIENT01 6=0
11=RD_wlsMGnms 14=0 15=USD 17=bOSUionVN 37=AOUouV2xf 38=2 39=0 40=2 42=20250623-03:16:23.497 44=9625.5 54=2
55=CU3M-LME 59=0 60=20250623-03:16:23.497 77=A 99=0 110=0 150=0 151=2 207=LME 460=CU 553=user01 20001=1
20005=XLME 20037=AOUouUXjy 10=231

ATP -> Client: 8=FIX.4.4 9=338 35=8 34=319 49=ATPFX 52=20250623-03:16:23.319 56=CLIENT01 1=CLIENT01 6=9626.5
11=c1OrdIDV20 14=2 15=USD 17=fLiMrLV_1750491006770 31=9625.5 32=1 37=AOUouUXjy 38=4 39=1 40=p 42=20250623-
03:16:23.498 54=2 55=CU3M-LME 59=1 60=20250623-03:16:23.498 75=20250623 77=A 150=F 151=2 207=LME 460=CU
553=user01 20001=1 20005=XLME 20007=CU250923-LME 10=030

ATP -> Client: 8=FIX.4.4 9=375 35=8 34=320 49=ATPFI 52=20250623-03:16:23.320 56=CLIENT01 1=CLIENT01 6=9625.5 11=RD_wlsMGNmS 14=1 15=USD 17=fLiMr1V_1750491006770 31=9625.5 32=1 37=AUouV2xf 38=2 39=1 40=2 42=20250623-03:16:23.498 44=9625.5 54=2 55=CU3M-LME 59=0 60=20250623-03:16:23.498 75=20250623 77=A 99=0 110=0 150=F 151=1 207=LME 460=CU 553=user01 20001=1 20005=XLME 20007=CU250923-LME 20037=AOUouUXjy 10=120

ATP -> Client: 8=FIX.4.4 9=346 35=8 34=321 49=ATPFI 52=20250623-03:16:27.158 56=CLIENT01 1=CLIENT01 6=9626.166666667 11=c1OrdIDV20 14=3 15=USD 17=fGB7b96_1750491006772 31=9625.5 32=1 37=AOUouUXjy 38=4 39=1 40=p 42=20250623-03:16:27.337 54=2 55=CU3M-LME 59=1 60=20250623-03:16:27.337 75=20250623 77=A 150=F 151=1 207=LME 460=CU 553=user01 20001=1 20005=XLME 20007=CU250923-LME 10=029

ATP -> Client: 8=FIX.4.4 9=375 35=8 34=322 49=ATPFI 52=20250623-03:16:27.158 56=CLIENT01 1=CLIENT01 6=9625.5 11=RD_wlsMGNmS 14=2 15=USD 17=fGB7b96_1750491006772 31=9625.5 32=1 37=AUouV2xf 38=2 39=2 40=2 42=20250623-03:16:27.337 44=9625.5 54=2 55=CU3M-LME 59=0 60=20250623-03:16:27.337 75=20250623 77=A 99=0 110=0 150=F 151=0 207=LME 460=CU 553=user01 20001=1 20005=XLME 20007=CU250923-LME 20037=AOUouUXjy 10=221

ATP -> Client: 8=FIX.4.4 9=312 35=8 34=334 49=ATPFI 52=20250623-03:17:23.320 56=CLIENT01 1=CLIENT01 6=0 11=RD_wlsQJ9VI 14=0 15=USD 17=ck2JpwUJ 37=AUouVIZT 38=1 39=0 40=2 42=20250623-03:17:23.504 44=9627.5 54=2 55=CU3M-LME 59=0 60=20250623-03:17:23.504 77=A 99=0 110=0 150=0 151=1 207=LME 460=CU 553=user01 20001=1 20005=XLME 20037=AOUouUXjy 10=102

ATP -> Client: 8=FIX.4.4 9=338 35=8 34=335 49=ATPFI 52=20250623-03:17:23.323 56=CLIENT01 1=CLIENT01 6=9626.5 11=c1OrdIDV20 14=4 15=USD 17=nCRXVEp_1750491006775 31=9627.5 32=1 37=AOUouUXjy 38=4 39=2 40=p 42=20250623-03:17:23.506 54=2 55=CU3M-LME 59=1 60=20250623-03:17:23.506 75=20250623 77=A 150=F 151=0 207=LME 460=CU 553=user01 20001=1 20005=XLME 20007=CU250923-LME 10=216

ATP -> Client: 8=FIX.4.4 9=375 35=8 34=336 49=ATPFI 52=20250623-03:17:23.323 56=CLIENT01 1=CLIENT01 6=9627.5 11=RD_wlsQJ9VI 14=1 15=USD 17=nCRXVEp_1750491006775 31=9627.5 32=1 37=AUouVIZT 38=1 39=2 40=2 42=20250623-03:17:23.506 44=9627.5 54=2 55=CU3M-LME 59=0 60=20250623-03:17:23.506 75=20250623 77=A 99=0 110=0 150=F 151=0 207=LME 460=CU 553=user01 20001=1 20005=XLME 20007=CU250923-LME 20037=AOUouUXjy 10=221

5.2. Order Replace (35=G) (Client -> ATP)

The FIX client sends this message to request order replacement from the ATP FIX server.

Order replace is only available with the following order types:

- 1 = Market
- 2 = Limit
- 3 = Stop
- 4 = Stop Limit
- 5 = Iceberg
- K = Market Limit

Possible response message:

- Reject(35=3)
- Execution Report: Confirmation/Acknowledgement(35=8)
- Order Cancel Reject(35=9)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=G
1	Account	N	String	Account as provided by Client
55	Symbol	N	String	Symbol to trade on
37	OrderID	C	String	ATP order ID. If both 'OrderID' and 'OrigClOrdID' are provided, 'OrigClOrdID' will be ignored
41	OrigClOrdID	C	String	'ClOrdID' that assigned by client with New Order Single(35=D) message. If both 'OrderID' and 'OrigClOrdID' are provided, 'OrigClOrdID' will be ignored
38	OrderQty	Y	Qty	Quantity of the order
44	Price	C	Price	Required if 'OrdType'=2, 4 or 5

99	StopPrice	C	Price	Required if 'OrdType'=3 or 4
110	MinQty	C	Qty	Minimum accepted fill size. Defaults to 0.0, required if 'OrdType'=3. 0.0 <= x <= 'OrderQty' If 'MinQty' = 'OrderQty' then the trade will either be fully filled or rejected. If 'MinQty' is set to x, with 0.0 < x < 'OrderQty', then the trade can be partially filled in multiple deals, each deal not smaller than x
210	MaxShow	C	Qty	Maximum quantity within an order to be shown to other customers, required if 'OrdType'=5
432	ExpireDate	C	LocalMkt Date	Expire Date. Required if 'TimeInForce'=6
60	TransactTime	N	Timestamp	UTC Timestamp of this order request
116	OnBehalfOfSubID	N	String	Assigned value used to identify specific message originator (i.e. trader) if the message was delivered by a third party
	Standard Trailer	Y		

Order Replace Example

Client -> ATP: 8=FIX.4.4 9=108 35=G 34=132 49=CLIENT01 56=ATPFX 52=20250319-07:46:39.265 1=CLIENT01 38=3 41=c1OrdIDv1 44=9923 55=CU3M-LME 10=251

5.3. Order Cancel(35=F) (Client -> ATP)

The FIX client sends this message to request order cancellation from the ATP FIX server.

Possible response message:

- Reject(35=3)
- Execution Report: Confirmation/Acknowledgement(35=8)
- Order Cancel Reject(35=9)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=F
1	Account	N	String	Account as provided by client
37	OrderID	C	String	ATP order ID. Conditionally required when multiple users are associated with the same account, and one user places an order, and the other users cancel the order. If both 'OrderID' and 'OrigClOrdID' are provided, 'OrigClOrdID' will be ignored
11	ClOrdID	N	String	Unique ID of cancel request as assigned by client
41	OrigClOrdID	C	String	'ClOrdID' that assigned by client with New Order Single(35=D) message. If both 'OrderID' and 'OrigClOrdID' are provided, 'OrigClOrdID' will be ignored
60	TransactTime	N	Timestamp	UTC Timestamp of this order request
116	OnBehalfOfSubID	N	String	Assigned value used to identify specific message originator (i.e. trader) if the message was delivered by a third party
	Standard Trailer	Y		

Order Cancel Example

Client -> ATP: 8=FIX.4.4 9=77 35=F 34=9 49=CLIENT01 52=20250613-01:04:32.238 56=ATPFX 11=JNPmuu 41=wgMwtN 10=196

ATP -> Client: 8=FIX.4.4 9=317 35=8 34=11 49=ATPFIX 52=20250613-01:04:32.242 56=CLIENT01 1=CLIENT01 6=0
 11=JNPmuu 14=0 15=USD 17=p_v563pBEO 37=MUnxUY0D 38=5 39=6 40=2 41=wgMwtN 42=20250613-01:04:32.242 44=9660 54=1
 55=CU3M-LME 59=0 60=20250613-01:04:32.242 77=A 99=0 110=0 150=6 151=5 207=LME 460=CU 553=user01 20001=1
 20002=test_wgMwtN 20005=XLME 10=093

ATP -> Client: 8=FIX.4.4 9=328 35=8 34=12 49=ATPFIX 52=20250613-01:04:32.254 56=CLIENT01 1=CLIENT01 6=0
 11=JNPmuu 14=0 15=USD 17=csdXefCyU 37=MUnxUY0D 38=5 39=4 40=2 41=wgMwtN 42=20250613-01:04:32.455 44=9660 54=1
 55=CU3M-LME 58=Canceled 59=0 60=20250613-01:04:32.455 77=A 99=0 110=0 150=4 151=0 207=LME 460=CU 553=user01
 20001=1 20002=test_wgMwtN 20005=XLME 10=101

5.4. Execution Report: Confirmation/Acknowledgement (35=8) (ATP -> Client)

The message serves as a notification of trade execution and order status.

ATP FIX server sends this message in response to:

- New Order Single(35=D)
- Order Replace(35=G)
- Order Cancel(35=F)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=8
1	Account	N	String	Account as provided by Client
553	Username	N	String	Username as provided by Client, can be blank for reports of external trades
97	PossResend	C	Boolean	Indicates that the message may contain previously transmitted information. Not set for real-time execution reports. Valid values: N = Original Transmission Y = Possible Resend
20003	OutdatedFlag	C	Boolean	Indicates that the message is outdated. Not set for real-time execution reports. Valid values: Y = Outdated
37	OrderID	Y	String	ATP order ID
20037	ParentOrderID	C	String	Parent order ID. Only set when the order was triggered by TWAP/POV order
11	ClOrdID	Y	String	Unique identifier of the order as assigned by client with New Order Single(35=D) message
41	OrigClOrdID	C	String	'ClOrdID' that assigned by client with New Order Single(35=D) message. Only response to Order Cancel(35=F) message
150	ExecType	Y	Char	The reason for the Execution Report: Confirmation/Acknowledgement(35=8) message to have been sent. The execution report's type: 0 = New 3 = Done for Day 4 = Canceled 5 = Replaced 6 = Pending Cancel 7 = Stopped 8 = Rejected 9 = Suspended A = Pending New

				B = Calculated C = Expired D = Restated E = Pending Replace F = Trade G = Trade Correct H = Trade Cancel I = Order Status L = Triggered or Activated by System
17	ExecID	Y	String	Unique identifier of execution message. Set to "0" when 'ExecType'=I
19	ExecRefID	C	String	Refers to 'ExecID' of the original fill, required if 'ExecType'=G, H for external trade reports
39	OrdStatus	Y	Char	The current status of an order, i.e. after the event causing the message to be sent. Current order status: 0 = New 1 = Partially Filled 2 = Filled 3 = Done for Day 4 = Canceled 6 = Pending Cancel 7 = Stopped 8 = Rejected 9 = Suspended A = Pending New B = Calculated C = Expired E = Pending Replace In the case of replies to New Order Single(35=D) messages, an Execution Report message with 'OrdStatus'=0 will always be followed by another order state. 'OrdStatus'=1 will be followed by either 2 or 4. The final state of an order can be either 2,4 or 8
31	LastPx	C	Price	Price of this fill. Set when 'ExecType'=F, G
32	LastQty	C	Qty	Quantity of this fill. Set when 'ExecType'=F, G
20082	CanceledPrice	C	Price	Price of this fill cancel. Set when 'ExecType'=H
20083	CanceledQty	C	Qty	Quantity of this fill cancel. Set when 'ExecType'=H
14	CumQty	Y	Qty	Cumulative quantity executed
151	LeavesQty	Y	Qty	Remaining quantity open for execution
6	AvgPx	N	Price	Average price of executed quantity
75	TradeDate	C	LocalMktDate	Trade date of execution. Set when 'ExecType'=F (when an actual fill took place)
207	SecurityExchange	N	String	Exchange code. e.g. "LME"
20005	MIC	N	String	Market Identifier Code. e.g. "XLME"
460	Product	N	String	Product code. e.g. "CU"
55	Symbol	Y	String	Symbol traded on. e.g. "CU3M-LME"

20007	ActualSymbol	C	String	Actual symbol. Set when 'ExecType'=F. e.g. "CU250311-LME"
54	Side	Y	Int	Side of order: 1 = Buy 2 = Sell
38	OrderQty	Y	Qty	Quantity of the order
15	Currency	C	Currency	Currency. Absent if 'OrdStatus'=6, A or E
59	TimeInForce	C	Int	Type of time in force. Only 0 and 1 are supported for 'OrdType'=t, p Valid values: 0 = Day (default value of normal order) 1 = GTC (default value of TWAP/POV order) 3 = IOC 4 = FOK 6 = GTD
110	MinQty	C	Qty	Minimum quantity ordered. Set when 'TimeInForce'=3
432	ExpireDate	C	LocalMktDate	Requested expire date. Set when 'TimeInForce'=6
40	OrdType	Y	Char	Type of order: 1 = Market 2 = Limit 3 = Stop 4 = Stop Limit 5 = Iceberg K = Market Limit t = TWAP p = POV
44	Price	C	Price	Requested price. Set when 'OrdType'=2, 4 or 5
99	StopPrice	C	Price	Requested stop price. Set when 'OrdType'=3 or 4
210	MaxShow	C	Qty	Maximum quantity within an order to be shown to other customers. Set when 'OrdType'=5
77	OffsetFlag	Y	String	Type of offset flag: A = Auto O = Open C = Close CY = CloseYesterday CT = CloseToday C-CT-O = Close-CloseToday-Open CT-C-O = CloseToday-Close-Open C-O = Close-Open CT-O = CloseToday-Open CY-O = CloseYesterday-Open
20001	HedgeFlag	Y	Int	Type of hedge flag: 1 = Speculation 2 = Arbitrage 3 = Hedge
58	Text	N	String	Free format text string

42	OrigTime	Y	Timestamp	UTC Timestamp of message origination. Upon the first successfully client logon on each trading day, previous execution reports on the same trading day will be sent by server, use 'OrigTime' to identify message origination time
60	TransactTime	Y	Timestamp	UTC Timestamp of the transaction represented by this ExecutionReport occurred
20002	Note	N	String	Order notes in text format
20085	TrsExpiryDate	C	LocalMktDate	TRS expiry date. Required if 'TrsType'=2
20086	TrsRate	N	String	TRS rate
	Standard Trailer	Y		

Execution Report Example

ATP -> Client: 8=FIX.4.4 9=282 35=8 34=22 49=ATPFIX 52=20250324-01:22:23.535 56=CLIENT01 1=CLIENT01 6=0 11=c10rdIDv1 14=0 15=USD 17=bP8kVwMv1 37=MUGJwWD0 38=3 39=0 40=2 42=20250324-01:22:23.693 44=9872.5 54=1 55=CU3M-LME 59=0 60=20250324-01:22:23.693 77=A 150=0 151=3 207=LME 460=CU 553=user01 20001=1 20005=XLME 10=243

5.5. Execution Report: Rejection (35=8) (ATP -> Client)

The message serves as a notification of rejection for new order requests.

ATP FIX server sends this message in response to:

- New Order Single(35=D)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=8
1	Account	N	String	Account as provided by Client
553	Username	N	String	Username as provided by Client
37	OrderID	Y	String	ATP order ID
11	ClOrdID	Y	String	Unique identifier of the order as assigned by client with New Order Single(35=D) message
150	ExecType	Y	Char	The reason for the Execution Report: Rejection(35=8) message to have been sent. The value is always: 8 = Rejected
17	ExecID	Y	String	Unique identifier of execution message
39	OrdStatus	Y	Char	The current status of an order, i.e. after the event causing the message to be sent. The value is always: 8 = Rejected
55	Symbol	Y	String	Symbol traded on
54	Side	Y	Int	Side of order: 1 = Buy 2 = Sell
38	OrderQty	Y	Qty	Quantity of the order

14	CumQty	Y	Qty	Cumulative quantity executed
151	LeavesQty	Y	Qty	Remaining quantity open for execution
6	AvgPx	N	Price	Average price of executed quantity
59	TimeInForce	C	Int	Type of time in force. Only 0 and 1 are supported for 'OrdType'=t, p Valid values: 0 = Day (default value of normal order) 1 = GTC (default value of TWAP/POV order) 3 = IOC 4 = FOK 6 = GTD
110	MinQty	C	Qty	Minimum quantity ordered. Set when 'TimeInForce'=3
432	ExpireDate	C	LocalMktDate	Requested expire date. Set when 'TimeInForce'=6
40	OrdType	Y	Char	Type of order: 1 = Market 2 = Limit 3 = Stop 4 = Stop Limit 5 = Iceberg K = Market Limit t = TWAP p = POV
44	Price	C	Price	Requested price. Set when 'OrdType'=2, 4 or 5
99	StopPrice	C	Price	Requested stop price. Set when 'OrdType'=3 or 4
210	MaxShow	C	Qty	Maximum quantity within an order to be shown to other customers. Set when 'OrdType'=5
103	OrdRejReason	Y	Int	Code to identify the reason for rejection. Further explanation of this code is in the 'Text'. Valid values: 99 = Other 201 = Account is invalid 202 = Username is invalid 203 = The session is forbidden to trade 204 = Conditional required field is missing 205 = Qty is invalid (zero or negative) 206 = Price is invalid 207 = LocalMktDate is invalid 301 = ClOrdId is invalid 302 = OrdType is invalid 303 = TimeInForce is invalid 304 = Side is invalid 305 = OffsetFlag is invalid 306 = HedgeFlag is invalid 307 = TrsType is invalid 502 = TimeInterval is invalid 503 = Timestamp is invalid 504 = PriceType is invalid 505 = PriceDiffInTick is invalid 506 = Boolean data is invalid

				507 = Ratio is invalid 508 = MaxCancelOrderTimes is invalid 511 = ClOrdID is invalid
77	OffsetFlag	N	String	Type of offset flag: A = Auto O = Open C = Close CY = CloseYesterday CT = CloseToday C-CT-O = Close-CloseToday-Open CT-C-O = CloseToday-Close-Open C-O = Close-Open CT-O = CloseToday-Open CY-O = CloseYesterday-Open
20001	HedgeFlag	N	Int	Type of hedge flag: 1 = Speculation 2 = Arbitrage 3 = Hedge
58	Text	Y	String	Provides the reason why the order was rejected
42	OrigTime	Y	Timestamp	UTC Timestamp of message origination. Upon the first successfully client logon on each trading day, previous execution reports on the same trading day will be sent by server, use 'OrigTime' to identify message origination time
60	TransactTime	Y	Timestamp	UTC Timestamp of the transaction represented by this ExecutionReport occurred
20085	TrsExpiryDate	C	LocalMktDate	TRS expiry date. Required if 'TrsType'=2
	Standard Trailer	Y		

Execution Report Example

ATP -> Client: 8=FIX.4.4 9=268 35=8 34=1388 49=ATPFX 52=20250430-02:23:20.636 56=CLIENT01 1=CLIENT01 6=0 11=clOrdIDv123 14=0 17=r_ETYHtqy 37=tmp_bskQ0q8_4 38=2 39=8 40=2 42=20250430-02:23:20.636 44=9391 54=1 55=CU3M-LME 58=ClOrdID should be unique 59=0 60=20250430-02:23:20.636 103=301 150=8 151=0 10=036

5.6. Order Cancel Reject (35=9) (ATP -> Client)

The message serves as a notification of rejection for order modification or cancellation requests.

ATP FIX server sends this message in response to:

- Order Replace(35=G)
- Order Cancel(35=F)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=9
1	Account	N	String	Account as provided by Client
553	Username	N	String	Username as provided by Client
11	ClOrdID	Y	String	Unique ID of cancel request as assigned by client
41	OrigClOrdID	Y	String	'ClOrdID' that assigned by client with New Order Single(35=D) message

37	OrderID	Y	String	ATP order ID. Specify "NONE" if order not found or order id has not yet generated
434	CxlRejResponseTo	Y	Int	Identifies the type of request this Order Cancel Reject is in response to. Valid values: 1 = Order Cancel 2 = Order Replace 3 = Order Cancel / Order Replace
39	OrdStatus	Y	Char	Current order status: 0 = New 1 = Partially Filled 2 = Filled 3 = Done for Day 4 = Canceled 6 = Pending Cancel 7 = Stopped 8 = Rejected 9 = Suspended A = Pending New B = Calculated C = Expired E = Pending Replace
102	CxlRejReason	Y	Int	Code to identify reason for order cancel rejection. Further explanation of this code is in the 'Text'. Valid values: 99 = Other 201 = Account is invalid 202 = Username is invalid 203 = The session is forbidden to trade 204 = Conditional required field is missing 205 = Qty is invalid (zero or negative) 206 = Price is invalid 207 = LocalMktDate is invalid 401 = Order not found 402 = Order cannot be modified 403 = Symbol not match
58	Text	Y	String	Provides the reason why the request was rejected
42	OrigTime	Y	Timestamp	UTC Timestamp of message origination. Upon the first successfully client logon on each trading day, previous reject reports on the same trading day will be sent by server, use 'OrigTime' to identify message origination time
60	TransactTime	Y	Timestamp	UTC Timestamp of the transaction
	Standard Trailer	Y		

Reject Report Example

ATP -> Client: 8=FIX.4.4 9=209 35=9 34=156 49=ATPFX 52=20250613-01:16:31.616 56=CLIENT01 1=CLIENT01 11=CQ47A7
 37=MUnxUY0D 39=4 41=wgMwtN 42=20250613-01:16:31.616 58=order is already closed 60=20250613-01:16:31.616 102=402
 434=1 553=user01 10=169

5.7. Security Definition Request (35=c,20004=?) (Client -> ATP)

The FIX client sends this message to request security definition for the specific symbol or list of symbols.

Possible response message:

- Reject(35=3)
- Business Message Reject(35=j)
- Security Definition(35=d,20004=?)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=c
320	SecurityReqID	C	String	Identifier for this request as assigned by the FIX client. Deprecated, use 'RequestID' instead
20004	RequestID	C	String	Primary identifier for this request as assigned by the FIX client. Required if Tag 'SecurityReqID' is not present
207	SecurityExchange	N	String	Indicates the exchange of the requested symbol, e.g. "LME". If the field is not set, all the matched symbols will be returned (only the other filters will be applied)
460	Product	N	String	Indicates the product of the requested symbol, e.g. "CU". If the field is not set, all the matched symbols will be returned (only the other filters will be applied)
55	Symbol	N	String	Requested symbol, e.g. "CU3M-LME". If the field is not set, all the matched symbols will be returned (only the other filters will be applied)
	Standard Trailer	Y		

Security Definition Request Examples

Business Message Reject:

Client -> ATP: 8=FIX.4.4 9=88 35=c 34=3104 49=CLIENT01 52=20250512-06:02:19.398 56=ATPFIX 55=HSI2407-HKE 20004=req001 10=004

ATP -> Client: 8=FIX.4.4 9=121 35=j 34=45443 49=ATPFIX 52=20250512-06:02:19.400 56=CLIENT01 45=3104 58=query rate limit exceeded 372=c 379=req001 380=9 10=171

Query without matched symbols:

Client -> ATP: 8=FIX.4.4 9=88 35=c 34=3093 49=CLIENT01 52=20250512-06:02:19.392 56=ATPFIX 55=HSI2407-HKE 20004=req001 10=005

ATP -> Client: 8=FIX.4.4 9=93 35=d 34=45432 49=ATPFIX 52=20250512-06:02:19.393 56=CLIENT01 58=symbol not found 323=6 912=Y 10=248

Query with matched symbols:

Client -> ATP: 8=FIX.4.4 9=85 35=c 34=1283 49=CLIENT01 52=20250512-03:36:33.299 56=ATPFIX 55=CU3M-LME 20004=req001 10=116

ATP -> Client: 8=FIX.4.4 9=167 35=d 34=43613 49=ATPFIX 52=20250512-03:36:33.299 56=CLIENT01 15=USD 55=CU3M-LME 167=FUT 207=LME 323=1 460=CU 541=20250812 561=25 912=Y 969=0.5 20004=req001 20005=XLME 10=036

5.8. Security Definition (35=d,20004=?) (ATP -> Client)

The message serves as the security definition of requested symbols or list of symbols.

ATP FIX server sends this message in response to:

- Security Definition Request(35=c,20004=?)

Tag	Field Name	Req'd	Data Type	Comments
-----	------------	-------	-----------	----------

	Standard Header	Y		MsgType=d
320	SecurityReqID	C	String	Deprecated Identifier for this request as assigned by the FIX client and sent with the Security Definition Request(35=c, 20004=?). Set when 'SecurityReqID' is present in the request
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
912	LastRptRequested	Y	Boolean	Indicates whether this message is the last message in response to a request. Valid values: N = Not last message Y = Last message
323	SecurityResponseType	Y	Int	Valid values: 1 = Accept security proposal as is 6 = Can not match selection criteria
207	SecurityExchange	C	Exchange	Exchange, not provided if symbol is not found
20005	MIC	C	String	Market Identifier Code, not provided if the symbol is either not found or lacks the associated MIC
460	Product	C	String	Product, not provided if symbol is not found
55	Symbol	C	String	Symbol, not provided if symbol is not found
15	Currency	C	Currency	Identifies currency used for price, not provided if symbol is not found
541	MaturityDate	C	LocalMktDate	Last Trading Date of the symbol, not provided if symbol is not found
969	TickSize	C	Float	Minimal tick price, not provided if symbol is not found
561	RoundLot	C	Float	The trading lot size, not provided if symbol is not found
167	SecurityType	C	String	Indicates type of symbol, not provided if symbol is not found. Valid values: FUT = Future OPT = Option SPR = Calendar Spread
311	UnderlyingSymbol	C	String	Underlying symbol for an option. Specify "NONE" if underlying symbol is empty
201	PutOrCall	C	Int	Indicates whether an option is a put or call. Valid values: 0 = Put 1 = Call
202	StrikePrice	C	Price	Strike price for an option
58	Text	C	String	Free format text string. If the request was rejected or symbols not found, the field should be present and contain information about the reason for failure
	Standard Trailer	Y		

Security Definition Example

ATP -> Client: 8=FIX.4.4 9=161 35=d 49=ATPFI 56=CLIENT01 34=37 52=20240614-06:42:23.705 323=1 55=CU3M-LME 460=CU 167=FUT 541=20240913 207=LME 15=USD 561=25 912=Y 20004=re1 20005=XLME 969=0.5 10=176

5.9. Business Message Reject (35=j) (ATP -> Client)

The message is a low-level reject and can be sent as an answer to several request types, excluding those related to orders.

ATP FIX server sends this message in response to:

- Security Definition Request(35=c, 20004=?)
- Order Status Request(35=H, 20004=?)
- Order Mass Status Request(35=AF, 20004=?)
- Request For Positions(35=AN, 20004=?)
- Trade Capture Report Request(35=AD, 20004=?)
- Currency Rate Request(35=UZU, 20004=?)
- Funds Detail Request(35=UFR, 20004=?)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=j
45	RefSeqNum	Y	SeqNum	Sequence number of rejected message
372	RefMsgType	Y	String	MsgType of FIX message being referenced. Valid values: c = Security Definition Request H = Order Status Request AF = Order Mass Status Request AN = Request For Positions AD = Trade Capture Report Request UZU = Currency Rate Request UFR = Funds Detail Request
379	BusinessRejectRefID	N	String	Value of the business-level 'ID' field on the message being referenced
380	BusinessRejectReason	Y	String	Error code identifying reason for a Business Message Reject(35=j) message. Valid values: 0 = Other 4 = Server not available 8 = Unknown account 9 = Rate limit exceeded
58	Text	C	String	Free format text string. Provides the reason why the request was rejected
	Standard Trailer	Y		

Business Message Reject Example

ATP -> Client: 8=FIX.4.4 9=105 35=j 34=2 49=ATPFIX 52=20240904-00:32:35.447 56=CLIENT01 45=2 58=unknown account 372=AN 379=req001 380=8 10=255

5.10. Request Ack (35=URA, 20004=?) (ATP -> Client)

ATP FIX server sends this message to acknowledge that a request has been received and processed.

ATP FIX server sends this message in response to:

- Order Mass Status Request(35=AF, 20004=?)
- Request for Positions(35=AN, 20004=?)
- Trade Capture Report Request(35=AD, 20004=?)

Tag	Field Name	Req'd	Data Type	Comments
-----	------------	-------	-----------	----------

	Standard Header	Y		MsgType=URA
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
1	Account	C	String	Account as provided by Client
20006	ReqResult	Y	Int	Indicates result of the request. Valid values: 0 = Valid request 1 = Invalid or unsupported request 2 = No records found that match criteria
	Standard Trailer	Y		

Request Ack Example

ATP -> Client: 8=FIX.4.4 9=80 35=URA 34=4 49=ATPFX 52=20240914-02:36:49.586 56=CLIENT01 20004=req001 20006=0 10=255

5.11. Order Status Request (35=H, 20004=?) (Client -> ATP)

The FIX client sends this message to query order status of the specified order from the ATP FIX server, no matter if the order is active or not.

Possible response message:

- Reject(35=3)
- Business Message Reject(35=j)
- Execution Report: Order Status(35=8, 20004=?, 150=F)

Note:

- A Business Message Reject(35=j) message will be published if the 'Account', 'OrderID' or 'ClOrdID' field is invalid.
- An Execution Report: Order Status(35=8, 20004=?, 150=F) message will be published in case of a match between 'OrderID' and 'ClOrdID' field.

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=H
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
1	Account	N	String	Account as provided by Client. An optional qualifier used to filter the order by account. NOTE: A Business Message Reject(35=j) message will be published if invalid 'Account' is provided
37	OrderID	C	String	ATP order ID. Specifies order to be requested. If both 'ClOrdID' and 'OrderID' are provided, 'ClOrdID' will be ignored
11	ClOrdID	C	String	Unique identifier of the order as assigned by client with New Order Single(35=D) message. Specifies order to be requested. If both 'ClOrdID' and 'OrderID' are provided, 'ClOrdID' will be ignored
	Standard Trailer	Y		

Order Status Request Example**Business Message Reject**

Client -> ATP: 8=FIX.4.4 9=98 35=H 34=845 49=CLIENT01 52=20250512-03:00:01.462 56=ATPFX 1=CLIENT01 11=c10rdIDV123 20004=req001 10=235

ATP -> Client: 8=FIX.4.4 9=108 35=j 34=865 49=ATPFIX 52=20250512-03:00:01.462 56=CLIENT01 45=845 58=order not found 372=H 379=req001 380=4 10=051

Query with a matched order

Client -> ATP: 8=FIX.4.4 9=84 35=H 34=630 49=CLIENT01 52=20250623-03:43:29.197 56=ATPFIX 37=MUoubJZb 20004=req001 10=241

ATP -> Client: 8=FIX.4.4 9=315 35=8 34=656 49=ATPFIX 52=20250623-03:43:29.198 56=CLIENT01 1=CLIENT01 6=9651.5 11=0Cs0aK 14=2 15=USD 17=0 37=MUoubJZb 38=2 39=2 40=2 42=20250623-03:41:17.323 44=9652 54=1 55=CU3M-LME 58=Filled 59=0 60=20250623-03:41:17.323 77=A 99=0 110=0 150=I 151=0 207=LME 460=CU 553=user01 912=Y 20001=1 20004=req001 20005=XLME 10=060

5.12. Order Mass Status Request (35=AF, 20004=?) (Client -> ATP)

The FIX client sends this message to query all active orders from the ATP FIX server.

Possible response message:

- Reject(35=3)
- Business Message Reject(35=j)
- Request Ack(35=URA, 20004=?)
- Execution Report: Order Status(35=8, 20004=?, 150≠F)

Note:

- There must be a Request Ack(35=URA, 20004=?) message firstly been published to indicate that the request has been received and processed. Then Execution Report: Order Status(35=8, 20004=?, 150≠F) messages will be published if orders exist.

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=AF
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
1	Account	N	String	Account as provided by Client. An optional qualifier used to filter orders by account. NOTE: A Business Message Reject(35=j) message will be published if invalid 'Account' is provided
207	SecurityExchange	N	String	Exchange code. An optional qualifier used to filter orders by exchange. e.g. "HKE"
40	OrdType	C	Char	ATP order type. An optional qualifier used to filter orders by order type. Required if 'OrdType'=t, p. Valid values: t = TWAP p = POV
20003	OutdatedFlag	N	Boolean	An optional qualifier used to filter orders as either outdated or active. If not set, no filtering is applied. Optional if 'OrdType'=t, p Valid values: Y = Outdated N = Active
	Standard Trailer	Y		

Order Mass Status Request Example

Business Message Reject

Client -> ATP: 8=FIX.4.4 9=83 35=AF 34=38 49=CLIENT01 52=20240903-08:37:56.042 56=ATPFIX 1=CLIENT02 20004=req001 10=248

ATP -> Client: 8=FIX.4.4 9=107 35=j 34=68 49=ATPFIX 52=20240903-08:37:56.063 56=CLIENT01 45=38 58=unknown account 372=AF 379=req001 380=8 10=119

Query without matched orders

Client -> ATP: 8=FIX.4.4 9=79 35=AF 34=74 49=CLIENT01 52=20240903-08:55:17.147 56=ATPFIX 207=SH 20004=req001 10=226

ATP -> Client: 8=FIX.4.4 9=82 35=URA 34=105 49=ATPFIX 52=20240903-08:55:17.149 56=CLIENT01 20004=req001 20006=2 10=096

Query with matched orders

Client -> ATP: 8=FIX.4.4 9=81 35=AF 34=567 49=CLIENT01 52=20250623-03:38:15.590 56=ATPFIX 207=LME 20004=req002 10=082

ATP -> Client: 8=FIX.4.4 9=82 35=URA 34=589 49=ATPFIX 52=20250623-03:38:15.596 56=CLIENT01 20004=req002 20006=0 10=111

ATP -> Client: 8=FIX.4.4 9=300 35=8 34=590 49=ATPFIX 52=20250623-03:38:15.596 56=CLIENT01 1=CLIENT01 6=0 11=NzsY0J 14=0 15=USD 17=0 37=MUoua8g8 38=3 39=0 40=2 42=20250623-03:36:37.113 44=9640 54=1 55=CU3M-LME 59=0 60=20250623-03:36:37.113 77=A 99=0 110=0 150=I 151=3 207=LME 460=CU 553=user01 912=Y 20001=1 20004=req002 20005=XLME 10=050

5.13. Execution Report: Order Status (35=8, 20004=?, 150=F) (ATP -> Client)

The message indicates a report of order status.

ATP FIX server sends this message in response to:

- Order Status Request(35=H, 20004=?)
- Order Mass Status Request(35=AF, 20004=?)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=8
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
912	LastRptRequested	Y	Boolean	Indicates whether this message is the last message in response to a request. Valid values: N = Not last message Y = Last message
1	Account	N	String	Account as provided by Client
553	Username	N	String	Username as provided by Client, can be blank for reports of external trades
37	OrderID	Y	String	ATP order ID
20037	ParentOrderID	C	String	Parent order ID. Only set when the order was triggered by TWAP/POV order
11	ClOrdID	Y	String	Unique identifier of the order as assigned by client with New Order Single(35=D) message
150	ExecType	Y	Char	Execution type. Valid values: 0 = New 3 = Done for Day 4 = Canceled 5 = Replaced 6 = Pending Cancel 7 = Stopped 8 = Rejected 9 = Suspended

				A = Pending New B = Calculated C = Expired D = Restated E = Pending Replace G = Trade Correct H = Trade Cancel I = Order Status L = Triggered or Activated by System
17	ExecID	Y	String	Unique identifier of execution message. Set to "0" when 'ExecType' = "I"
54	Side	Y	Int	Side of order: 1 = Buy 2 = Sell
38	OrderQty	Y	Qty	Quantity of the order
14	CumQty	Y	Qty	Cumulative quantity executed
151	LeavesQty	Y	Qty	Remaining quantity open for execution
6	AvgPx	N	Price	Average price of executed quantity
59	TimeInForce	C	Int	Type of time in force. Only 0 and 1 are supported for 'OrdType'=t, p Valid values: 0 = Day (default value of normal order) 1 = GTC (default value of TWAP/POV order) 3 = IOC 4 = FOK 6 = GTD
110	MinQty	C	Qty	Minimum quantity ordered. Set when 'TimeInForce'=3
432	ExpireDate	C	LocalMktDate	Requested expire date. Set when 'TimeInForce'=6
40	OrdType	Y	Char	Type of order: 1 = Market 2 = Limit 3 = Stop 4 = Stop Limit 5 = Iceberg K = Market Limit t = TWAP p = POV
44	Price	C	Price	Requested price. Set when 'OrdType'=2, 4 or 5
99	StopPrice	C	Price	Requested stop price. Set when 'OrdType'=3 or 4
210	MaxShow	C	Qty	Maximum quantity within an order to be shown to other customers. Set when 'OrdType'=5
15	Currency	C	Currency	Currency. Absent if 'OrdStatus' =6, A or E
39	OrdStatus	Y	Char	The current status of an order. Current order status: 0 = New 1 = Partially Filled

				2 = Filled 3 = Done for Day 4 = Canceled 6 = Pending Cancel 7 = Stopped 8 = Rejected 9 = Suspended A = Pending New B = Calculated C = Expired E = Pending Replace In the case of replies to New Order Single(35=D) messages, an Execution Report message with 'OrdStatus'=0 will always be followed by another order state. 'OrdStatus'=1 will be followed by either 2 or 4. The final state of an order can be either 2,4 or 8
77	OffsetFlag	Y	String	Type of offset flag: A = Auto O = Open C = Close CY = CloseYesterday CT = CloseToday C-CT-O = Close-CloseToday-Open CT-C-O = CloseToday-Close-Open C-O = Close-Open CT-O = CloseToday-Open CY-O = CloseYesterday-Open
20001	HedgeFlag	Y	Int	Type of hedge flag: 1 = Speculation 2 = Arbitrage 3 = Hedge
207	SecurityExchange	N	String	Exchange code. e.g. "HKE"
20005	MIC	N	String	Market Identifier Code. e.g. "XHKG"
460	Product	N	String	Product code. e.g. "HSI"
55	Symbol	Y	String	Symbol traded on. e.g. "HSI2512-HKE"
20007	ActualSymbol	N	String	Actual Symbol. e.g. "CU250311-LME"
75	TradeDate	N	LocalMktDate	Trade date of execution
42	OrigTime	Y	Timestamp	UTC Timestamp of message origination. Upon the first successfully client logon on each trading day, previous execution reports on the same trading day will be sent by server, use 'OrigTime' to identify message origination time
60	TransactTime	Y	Timestamp	UTC Timestamp of the transaction represented by this ExecutionReport occurred
58	Text	N	String	Free format text string
20002	Note	N	String	Order notes in text format
20085	TrsExpiryDate	C	LocalMktDate	TRS expiry date. Required if 'TrsType'=2
	Standard Trailer	Y		

Execution Report Example

ATP -> Client: 8=FIX.4.4 9=315 35=8 34=656 49=ATPFI 52=20250623-03:43:29.198 56=CLIENT01 1=CLIENT01 6=9651.5 11=0Cs0aK 14=2 15=USD 17=0 37=MUoubJZb 38=2 39=2 40=2 42=20250623-03:41:17.323 44=9652 54=1 55=CU3M-LME 58=Filled 59=0 60=20250623-03:41:17.323 77=A 99=0 110=0 150=I 151=0 207=LME 460=CU 553=user01 912=Y 20001=1 20004=req001 20005=XLME 10=060

5.14. Trade Capture Report Request (35=AD, 20004=?) (Client -> ATP)

The FIX client sends this message to query trades from the ATP FIX server.

Possible response message:

- Reject(35=3)
- Business Message Reject(35=j)
- Execution Report: Trade(35=8, 20004=?, 150=F)
- Request Ack(35=URA, 20004=?)

Note:

- There must be a Request Ack(35=URA, 20004=?) message firstly been published to indicate that the request has been received and processed. Then Execution Report: Trade(35=8, 20004=?, 150=F) messages will be published if trades exist.

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=AD
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
1	Account	N	String	Account as provided by Client. An optional qualifier used to filter trades by account. NOTE: A Business Message Reject(35=j) message will be published if invalid 'Account' is provided
37	OrderID	N	String	ATP order ID. An optional qualifier used to filter trades by order ID
207	SecurityExchange	N	String	Exchange code. An optional qualifier used to filter trades by exchange. e.g. "HKE"
	Standard Trailer	Y		

Trade Capture Report Request Example**Business Message Reject**

Client -> ATP: 8=FIX.4.4 9=84 35=AD 34=105 49=CLIENT01 52=20240903-09:09:15.158 56=ATPFI 1=CLIENT02 20004=req001 10=037

ATP -> Client: 8=FIX.4.4 9=109 35=j 34=166 49=ATPFI 52=20240903-09:09:15.160 56=CLIENT01 45=105 58=unknown account 372=AD 379=req001 380=8 10=202

Query without matched trades

Client -> ATP: 8=FIX.4.4 9=85 35=AD 34=120 49=CLIENT01 52=20240903-09:15:44.163 56=ATPFI 37=MUNBQLX 20004=req001 10=178

ATP -> Client: 8=FIX.4.4 9=82 35=URA 34=184 49=ATPFI 52=20240903-09:15:44.169 56=CLIENT01 20004=req001 20006=2 10=102

Query with matched trades

Client -> ATP: 8=FIX.4.4 9=96 35=AD 34=110 49=CLIENT01 52=20250324-02:03:24.650 56=ATPFI 1=CLIENT01 37=MUGK1f9R 20004=req001 10=047

ATP -> Client: 8=FIX.4.4 9=93 35=URA 34=138 49=ATPFI 52=20250324-02:03:24.654 56=CLIENT01 1=CLIENT01 20004=req001 20006=0 10=229

ATP -> Client: 8=FIX.4.4 9=344 35=8 34=139 49=ATPFI 52=20250324-02:03:24.655 56=CLIENT01 1=CLIENT01 11=clOrdIDv3 14=2 15=USD 17=ikFjOxw_1742628603913 31=9891 32=2 37=MUGK1f9R 38=2 39=2 40=2 42=20250324-01:42:49.708 54=2 55=CU3M-LME 59=0 60=20250324-01:42:49.708 75=20250324 77=A 150=F 151=0 207=LME 460=CU 553=user01 912=Y 20001=1 20004=req001 20005=XLME 20007=CU250624-LME 10=058

5.15. Execution Report: Trade (35=8, 20004=?, 150=F) (ATP -> Client)

The message indicates a report of trade.

ATP FIX server sends this message in response to:

- Trade Capture Report Request(35=AD, 20004=?)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=8
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
912	LastRptRequested	Y	Boolean	Indicates whether this message is the last message in response to a request. Valid values: N = Not last message Y = Last message
1	Account	N	String	Account as provided by Client
553	Username	N	String	Username as provided by Client, can be blank for reports of external trades
37	OrderID	Y	String	ATP order ID
20037	ParentOrderID	C	String	Parent order ID. Only set when the order was triggered by TWAP/POV order
11	ClOrdID	Y	String	Unique identifier of the order as assigned by client with New Order Single(35=D) message
150	ExecType	Y	Char	Execution type. Valid values: F = Trade
17	ExecID	Y	String	Unique identifier of execution message
54	Side	Y	Int	Side of order: 1 = Buy 2 = Sell
40	OrdType	Y	Char	Type of order: 1 = Market 2 = Limit 3 = Stop 4 = Stop Limit 5 = Iceberg K = Market Limit t = TWAP p = POV
38	OrderQty	Y	Qty	Quantity of the order
39	OrdStatus	Y	Char	The current status of an order. Current order status: 0 = New 1 = Partially Filled 2 = Filled 3 = Done for Day 4 = Canceled 6 = Pending Cancel

				7 = Stopped 8 = Rejected 9 = Suspended A = Pending New B = Calculated C = Expired E = Pending Replace In the case of replies to New Order Single(35=D) messages, an Execution Report message with 'OrdStatus'=0 will always be followed by another order state. 'OrdStatus'=1 will be followed by either 2 or 4. The final state of an order can be either 2,4 or 8
14	CumQty	Y	Qty	Cumulative quantity executed
151	LeavesQty	Y	Qty	Remaining quantity open for execution
6	AvgPx	N	Price	Average price of executed quantity
15	Currency	C	Currency	Currency. Absent if 'OrdStatus' =6, A or E
77	OffsetFlag	Y	String	Type of offset flag: A = Auto O = Open C = Close CY = CloseYesterday CT = CloseToday C-CT-O = Close-CloseToday-Open CT-C-O = CloseToday-Close-Open C-O = Close-Open CT-O = CloseToday-Open CY-O = CloseYesterday-Open
20001	HedgeFlag	Y	Int	Type of hedge flag: 1 = Speculation 2 = Arbitrage 3 = Hedge
59	TimeInForce	C	Int	Type of time in force. Only 0 and 1 are supported for 'OrdType'=t, p Valid values: 0 = Day (default value of normal order) 1 = GTC (default value of TWAP/POV order) 3 = IOC 4 = FOK 6 = GTD
31	LastPx	Y	Price	Price of this fill
32	LastQty	Y	Qty	Quantity of this fill
75	TradeDate	Y	LocalMktDate	Trade date of execution
60	TransactTime	Y	Timestamp	UTC Timestamp of the transaction represented by this ExecutionReport occurred
207	SecurityExchange	N	String	Exchange code. e.g. "LME"
20005	MIC	N	String	Market Identifier Code. e.g. "XLME"
460	Product	N	String	Product code. e.g. "CU"

55	Symbol	Y	String	Symbol traded on. e.g. "CU3M-LME"
20007	ActualSymbol	Y	String	Actual Symbol. e.g. "CU250311-LME"
42	OrigTime	Y	Timestamp	UTC Timestamp of message origination. Upon the first successfully client logon on each trading day, previous execution reports on the same trading day will be sent by server, use 'OrigTime' to identify message origination time
20002	Note	N	String	Order notes in text format
20085	TrsExpiryDate	C	LocalMktDate	TRS expiry date. Required if 'TrsType'=2
20086	TrsRate	N	String	TRS rate
	Standard Trailer	Y		

Execution Report Example

ATP -> Client: 8=FIX.4.4 9=402 35=8 34=516 49=ATPFIX 52=20260407-09:11:36.848 56=CLIENT01 1=CLIENT01 6=0 11=2h1IfK 14=4 15=USD 17=kUcBbRC_7447181333611421696-517645619 31=111.73 32=4 37=MVG5TiHl 38=5 39=1 40=2 42=20260407-07:24:21.518 44=111.74 54=1 55=BRN2606-ICE 59=0 60=20260407-07:24:21.518 75=20260407 77=A 99=0 110=0 150=F 151=1 207=ICE 460=BRN 553=user01 912=N 20001=1 20004=req001 20007=BRN2606-ICE 20085=20260410 20086=7.54 10=189

5.16. Request For Positions (35=AN,20004=?) (Client -> ATP)

The FIX client sends this message to request positions from the ATP FIX server.

Possible response message:

- Reject(35=3)
- Business Message Reject(35=j)
- Position Report(35=AP,20004=?)
- Request Ack(35=URA,20004=?)

Note:

- There must be a Request Ack(35=URA,20004=?) message firstly been published to indicate that the request has been received and processed. Then Position Report(35=AP,20004=?) messages will be published if positions exist.

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=AN
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
1	Account	N	String	Account as provided by Client. An optional qualifier used to filter positions by account. NOTE: A Business Message Reject(35=j) message will be published if invalid 'Account' is provided
55	Symbol	N	String	Symbol to trade on. An optional qualifier used to filter positions by symbol. e.g. "HSI2512-HKE"
	Standard Trailer	Y		

Request for Positions Example**Business Message Reject**

Client -> ATP: 8=FIX.4.4 9=82 35=AN 34=2 49=CLIENT01 52=20240904-00:32:35.422 56=ATPFIX 1=CLIENT02 20004=req001 10=185

ATP -> Client: 8=FIX.4.4 9=105 35=j 34=2 49=ATPFIX 52=20240904-00:32:35.447 56=CLIENT01 45=2 58=unknown account 372=AN 379=req001 380=8 10=255

Query without matched positions

Client -> ATP: 8=FIX.4.4 9=87 35=AN 34=10 49=CLIENT01 52=20240914-02:40:28.507 56=ATPFIX 55=HSI2407-HKE 20004=req001 10=195

ATP -> Client: 8=FIX.4.4 9=81 35=URA 34=13 49=ATPFIX 52=20240914-02:40:28.508 56=CLIENT01 20004=req001 20006=2 10=036

Query with matched positions

Client -> ATP: 8=FIX.4.4 9=87 35=AN 34=88 49=CLIENT01 52=20241009-01:10:25.246 56=ATPFIX 55=HSI2512-HKE 20004=req001 10=196

ATP -> Client: 8=FIX.4.4 9=82 35=URA 34=165 49=ATPFIX 52=20241009-01:10:25.249 56=CLIENT01 20004=req001 20006=0 10=082

ATP -> Client: 8=FIX.4.4 9=236 35=AP 34=166 49=ATPFIX 52=20241009-01:10:25.250 56=CLIENT01 1=CLIENT01 55=HSI2512-HKE 912=Y 6351=2 20001=4 20004=req001 20038=0 20039=0 702=4 703=0 704=8 20008=17731.25 703=1 704=0 20008=0 703=2 705=0 20008=0 703=3 704=8 20008=17731.25 10=045

5.17. Position Report (35=AP, 20004=?) (ATP -> Client)

The message serves as a position report for a Request For Positions(35=AN, 20004=?) message. Multiple position reports can be sent for the same symbol in case of bi-directional position is enabled.

ATP FIX server sends this message in response to:

- Request For Positions(35=AN, 20004=?)

Tag	Field Name		Req'd	Data Type	Comments
	Standard Header		Y		MsgType=AP
20004	RequestID		Y	String	Primary identifier for this request as assigned by the FIX client
912	LastRptRequested		Y	Boolean	Indicates whether this message is the last message in response to a request. Valid values: N = Not last message Y = Last message
1	Account		Y	String	Account as provided by Client
55	Symbol		Y	String	Symbol traded on. e.g. "HSI2512-HKE"
6351	PositionDirection		Y	Int	Indicates direction of position. Valid values: 0 = Long 1 = Short 2 = Net NOTE: There are two types of position: uni-directional position and bi-directional position. For uni-directional position, only Net position('PositionDirection'=2) will be returned. For bi-directional position, both Long position('PositionDirection'=0) and Short position('PositionDirection'=1) will be returned
702	NoPositions		Y	NumInGroup	Number of position entries
→	703	PosType	Y	String	Used to identify the type of quantity that is being returned. There is only one position direction for the same 'PosType'.

					Valid values: 0 = Net 1 = Today Buy 2 = Today Sell 3 = Yesterday
→	704	LongQty	C	Qty	Quantity of long position. It must be a non-negative value. Only one of 'LongQty' and 'ShortQty' is available
→	705	ShortQty	C	Qty	Quantity of short position. It must be a non-negative value. Only one of 'LongQty' and 'ShortQty' is available
→	20008	PosAvgPx	Y	Price	Average price of position
20038	CloseProfitByOpenPx	Y	Amt		Indicates profit & loss of closing position by open price, can be a negative value
20039	CloseProfitBySettlePx	Y	Amt		Indicates profit & loss of closing position by settle price(mark to market), can be a negative value
20001	HedgeFlag	Y	Int		Indicates the hedge flag of the position to which the symbol belongs. 'HedgeFlag' assigns values 1, 2, or 3 to positions with specific hedging strategies. If no specific strategy is applied, it defaults to 4. Type of hedge flag: 1 = Speculation 2 = Arbitrage 3 = Hedge 4 = Unified
	Standard Trailer	Y			

Position Report Example

ATP -> Client: 8=FIX.4.4 9=236 35=AP 34=166 49=ATPFX 52=20241009-01:10:25.250 56=CLIENT01 1=CLIENT01 55=HSI2512-HKE 912=Y 6351=2 20001=4 20004=req001 20038=0 20039=0 702=4 703=0 704=8 20008=17731.25 703=1 704=0 20008=0 703=2 705=0 20008=0 703=3 704=8 20008=17731.25 10=045

5.18. Currency Rate Request (35=UZU,20004=?) (Client -> ATP)

The FIX client sends this message to request current currency rates from the ATP FIX server.

Possible response message:

- Reject(35=3)
- Business Message Reject(35=j)
- Currency Rate Report(35=UZT, 20004=?)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=UZU
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
1	Account	Y	String	Account as provided by Client. NOTE: A Business Message Reject(35=j) message will be published if invalid 'Account' is provided
	Standard Trailer	Y		

Currency Rate Request Example**Business Message Reject**

Client -> ATP: 8=FIX.4.4 9=83 35=UZU 34=2 49=CLIENT01 52=20250915-03:16:06.882 56=ATPFIX 1=CLIENT02
20004=req001 10=063

ATP -> Client: 8=FIX.4.4 9=106 35=j 34=2 49=ATPFIX 52=20250915-03:16:06.882 56=CLIENT01 45=2 58=unknown
account 372=UZU 379=req001 380=8 10=126

Query currency rate with specific account

Client -> ATP: 8=FIX.4.4 9=84 35=UZU 34=19 49=CLIENT01 52=20250915-03:18:48.547 56=ATPFIX 1=CLIENT01
20004=req001 10=125

ATP -> Client: 8=FIX.4.4 9=1084 35=UZZT 34=19 49=ATPFIX 52=20250915-03:18:48.565 56=CLIENT01 1=CLIENT01 893=Y
20004=req001 20040=20 15=RMB 20041=USD 20042=0.13747 20043=Y 15=RMB 20041=HKD 20042=1.069793 20043=N 15=RMB
20041=JPY 20042=13.747027 20043=N 15=RMB 20041=MYR 20042=0.417909 20043=N 15=RMB 20041=CNH 20042=0.912527
20043=N 15=RMB 20041=GBP 20042=0.095651 20043=N 15=RMB 20041=EUR 20042=0.126101 20043=N 15=RMB 20041=CAD
20042=0.178711 20043=N 15=RMB 20041=DEM 20042=0.235074 20043=N 15=RMB 20041=SGD 20042=0.182148 20043=N 15=RMB
20041=AUD 20042=0.180498 20043=N 15=RMB 20041=CHF 20042=0.156716 20043=N 15=RMB 20041=VND 20042=3234.12562
20043=N 15=USD 20041=RMB 20042=7.2743 20043=N 15=USD 20041=HKD 20042=7.782 20043=N 15=USD 20041=JPY 20042=100
20043=N 15=USD 20041=MYR 20042=3.04 20043=N 15=USD 20041=CNH 20042=6.638 20043=N 15=USD 20041=GBP 20042=0.6958
20043=N 15=USD 20041=EUR 20042=0.9173 20043=N 10=221

5.19. Currency Rate Report (35=UZZT, 20004=?) (ATP -> Client)

The message serves as a currency rate report for a Currency Rate Request(35=UZU, 20004=?) message

ATP FIX server sends this message in response to:

- Currency Rate Request(35=UZU, 20004=?)

Tag	Field Name		Req'd	Data Type	Comments
	Standard Header		Y		MsgType=UZZT
20004	RequestID		Y	String	Primary identifier for this request as assigned by the FIX client
893	LastFragment		Y	Boolean	Set to Y if this report contains the last fragment of results. A fragment contains up to 25 rates entries, which means 'NoRates'=25. Valid values: N = Not last fragment Y = Last fragment
1	Account		Y	String	Account as provided by Client
20040	NoRates		Y	NumInGroup	Number of currency rates to follow
→	15	Currency	Y	Currency	Source currency code. Must be the first field in the repeating group.
→	20041	MasterCurrency	Y	Currency	Target currency code
→	20042	CurrencyRate	Y	Price	Rate to convert 'Currency' (source) into 'MasterCurrency' (target)
→	20043	CurrencyConversionAllowed	Y	Boolean	Indicates whether the account is allowed to convert 'Currency' (source) into 'MasterCurrency' (target)
	Standard Trailer		Y		

Currency Rate Report Example

ATP -> Client: 8=FIX.4.4 9=1084 35=UZZT 34=19 49=ATPFIX 52=20250915-03:18:48.565 56=CLIENT01 1=CLIENT01 893=Y
20004=req001 20040=20 15=RMB 20041=USD 20042=0.13747 20043=Y 15=RMB 20041=HKD 20042=1.069793 20043=N 15=RMB
20041=JPY 20042=13.747027 20043=N 15=RMB 20041=MYR 20042=0.417909 20043=N 15=RMB 20041=CNH 20042=0.912527
20043=N 15=RMB 20041=GBP 20042=0.095651 20043=N 15=RMB 20041=EUR 20042=0.126101 20043=N 15=RMB 20041=CAD
20042=0.178711 20043=N 15=RMB 20041=DEM 20042=0.235074 20043=N 15=RMB 20041=SGD 20042=0.182148 20043=N 15=RMB
20041=AUD 20042=0.180498 20043=N 15=RMB 20041=CHF 20042=0.156716 20043=N 15=RMB 20041=VND 20042=3234.12562
20043=N 15=USD 20041=RMB 20042=7.2743 20043=N 15=USD 20041=HKD 20042=7.782 20043=N 15=USD 20041=JPY 20042=100

20043=N 15=USD 20041=MYR 20042=3.04 20043=N 15=USD 20041=CNH 20042=6.638 20043=N 15=USD 20041=GBP 20042=0.6958
 20043=N 15=USD 20041=EUR 20042=0.9173 20043=N 10=221

5.20. Funds Detail Request (35=UFR, 20004=?) (Client -> ATP)

The FIX client sends this message to request funds detail from the ATP FIX server.

Possible response message:

- Reject(35=3)
- Business Message Reject(35=j)
- Funds Detail Report(35=UFD, 20004=?)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=UFR
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
1	Account	Y	String	Account as provided by Client. NOTE: A Business Message Reject(35=j) message will be published if invalid 'Account' is provided
20063	BalanceGrpType	N	String	Balance group type. Funds Detail Report(35=UFD, 20004=?) should not contain individual balance records (BalanceGrp) if the field is not set. Valid values: 0 = Single 1 = Aggregated NOTES: Single: The balance is calculated based solely on the activity of the specified currency. It does not include any amounts converted from other currencies Aggregated: The balance is calculated by combining the native amount of the specified currency with amounts converted from other available currency sources
	Standard Trailer	Y		

Currency Rate Request Example

Business Message Reject

Client -> ATP: 8=FIX.4.4 9=93 35=UFR 34=405 49=CLIENT01 52=20250915-09:10:38.240 56=ATPFX 1=CLIENT01
 20004=req002 20063=3 10=245

ATP -> Client: 8=FIX.4.4 9=121 35=j 34=430 49=ATPFX 52=20250915-09:10:38.243 56=CLIENT01 45=405 58=invalid
 balance group type 372=UFR 379=req002 380=0 10=004

Query funds detail with specific account ('BalanceGrpType' = 0)

Client -> ATP: 8=FIX.4.4 9=91 35=UFR 34=3 49=CLIENT01 52=20250916-01:22:41.139 56=ATPFX 1=CLIENT01
 20004=req002 20063=0 10=135

ATP -> Client: 8=FIX.4.4 9=687 35=UFD 34=4 49=ATPFX 52=20250916-01:22:41.164 56=CLIENT01 1=CLIENT01 12=0
 20004=req002 20039=0 20044=USD 20045=76561.434 20046=0 20047=0 20048=-56873.2336 20049=0 20050=2500
 20051=19688.2003 20052=0 20053=0 20054=0 20055=0 20057=17188.2003 20058=76561.434 20059=0 20060=19688.2003
 20061=0 20062=2 20063=0 15=USD 20064=52441.6704 20065=0 20066=0 20067=-32779.1704 20068=0 20069=2500
 20070=19662.5 20071=0 20072=0 20073=0 20074=0 20075=0 20076=17162.5 20077=52441.6704 20078=0 20079=19662.5
 20080=0 20081=0 20063=0 15=HKD 20064=187700 20065=0 20066=0 20067=-187500 20068=0 20069=0 20070=200 20071=0
 20072=0 20073=0 20074=0 20075=0 20076=200 20077=187700 20078=0 20079=200 20080=0 20081=0 10=067

Query funds detail with specific account ('BalanceGrpType' = 1)

Client -> ATP: 8=FIX.4.4 9=92 35=UFR 34=19 49=CLIENT01 52=20250916-01:25:15.678 56=ATPFX 1=CLIENT01
 20004=req002 20063=1 10=204

ATP -> Client: 8=FIX.4.4 9=695 35=UFD 34=20 49=ATPFX 52=20250916-01:25:15.682 56=CLIENT01 1=CLIENT01 12=0
 20004=req002 20039=0 20044=USD 20045=76561.434 20046=0 20047=0 20048=-56873.2336 20049=0 20050=2500

20051=19688.2003 20052=0 20053=0 20054=0 20055=0 20057=17188.2003 20058=76561.434 20059=0 20060=19688.2003
 20061=0 20062=2 20063=1 15=USD 20064=76561.434 20065=0 20066=0 20067=-56873.2336 20068=0 20069=2500
 20070=19688.2003 20071=0 20072=0 20073=0 20074=0 20075=0 20076=17188.2003 20077=76561.434 20078=0
 20079=19688.2003 20080=0 20081=0 20082=1 15=HKD 20084=187700 20085=0 20086=0 20087=-187500 20088=0 20089=0
 20090=200 20091=0 20092=0 20093=0 20094=0 20095=0 20096=200 20097=187700 20098=0 20099=200 20100=0 20101=0
 10=236

5.21. Funds Detail Report (35=UFD, 20004=?) (ATP -> Client)

The message serves as a funds detail report for a Funds Detail Request(35=UFR, 20004=?) message

ATP FIX server sends this message in response to:

- Funds Detail Request(35=UFR, 20004=?)

Tag	Field Name	Req'd	Data Type	Comments
	Standard Header	Y		MsgType=UFD
20004	RequestID	Y	String	Primary identifier for this request as assigned by the FIX client
1	Account	Y	String	Account as provided by Client
20044	BaseCurrency	Y	Currency	Base currency code of this account
20045	PositionInitMargin	Y	Amt	Initial position margin of this account, converted and expressed in the base currency
20046	OrderInitMargin	Y	Amt	Initial order margin of this account, converted and expressed in the base currency
20047	CreditLimit	Y	Amt	Credit limit of this account, converted and expressed in the base currency
20048	AvailableFunds	Y	Amt	Available funds of this account, converted and expressed in the base currency
20049	CashMovement	Y	Amt	Deposit & withdrawal funds of this account, converted and expressed in the base currency
20050	BeginningCash	Y	Amt	Beginning cash of this account, converted and expressed in the base currency
20051	Equity	Y	Amt	Equity of this account, converted and expressed in the base currency
20052	FrozenPremium	Y	Amt	Frozen premium of this account, converted and expressed in the base currency
20053	Premium	Y	Amt	Premium of this account, converted and expressed in the base currency
20054	LongOptionValue	Y	Amt	Option value of long position, converted and expressed in the base currency
20055	ShortOptionValue	Y	Amt	Option value of short position, converted and expressed in the base currency
20039	CloseProfitBySettlePx	Y	Amt	Indicates profit & loss of closing position by settle price(mark to market) of this account, can be a negative value, converted and expressed in the base currency

20057	FloatingPnl		Y	Amt	Unrealized profit & loss of this account, converted and expressed in the base currency
20058	PositionMaintenanceMargin		Y	Amt	Maintenance position margin of this account, converted and expressed in the base currency
20059	OrderMaintenanceMargin		Y	Amt	Maintenance order margin of this account, converted and expressed in the base currency
20060	AccountMarketValue		Y	Amt	Market value of this account, converted and expressed in the base currency
20061	FrozenCommission		Y	Amt	Frozen commission of this account, converted and expressed in the base currency
12	Commission		Y	Amt	Commission of this account, converted and expressed in the base currency
20062	NoBalances		N	NumInGroup	Number of balances to follow
→	20063	BalanceGrpType	C	String	Balance group type. Must be the first field in the repeating group. Required if NoBalances > 0. Valid values: 0 = Single 1 = Aggregated NOTES: Single: The balance is calculated based solely on the activity of the specified currency. It does not include any amounts converted from other currencies Aggregated: The balance is calculated by combining the native amount of the specified currency with amounts converted from other available currency sources
→	15	Currency	N	Currency	Currency code of this balance record
→	20064	BalancePositionInitMargin	N	Amt	This balance record's initial position margin, converted and expressed in the currency of this record
→	20065	BalanceOrderInitMargin	N	Amt	This balance record's initial order margin, converted and expressed in the currency of this record
→	20066	BalanceCreditLimit	N	Amt	This balance record's credit limit, converted and expressed in the currency of this record
→	20067	BalanceAvailableFunds	N	Amt	This balance record's available funds, converted and expressed in the currency of this record
→	20068	BalanceCashMovement	N	Amt	This balance record's deposit & withdrawal funds, converted and expressed in the currency of this record
→	20069	BalanceBeginningCash	N	Amt	This balance record's beginning cash, converted and expressed in the currency of this record
→	20070	BalanceEquity	N	Amt	This balance record's equity, converted and expressed in the currency of this record
→	20071	BalanceFrozenPremium	N	Amt	This balance record's frozen premium, converted and expressed in the currency of this record
→	20072	BalancePremium	N	Amt	This balance record's premium, converted and expressed in the currency of this record

→	20073	BalanceLongOptionValue	N	Amt	This balance record's option value of long position, converted and expressed in the currency of this record
→	20074	BalanceShortOptionValue	N	Amt	This balance record's option value of short position, converted and expressed in the currency of this record
→	20075	BalanceClosedPnl	N	Amt	This balance record's realized profit & loss, converted and expressed in the currency of this record
→	20076	BalanceFloatingPnl	N	Amt	This balance record's unrealized profit & loss, converted and expressed in the currency of this record
→	20077	BalancePositionMaintenanceMargin	N	Amt	This balance record's maintenance position margin, converted and expressed in the currency of this record
→	20078	BalanceOrderMaintenanceMargin	N	Amt	This balance record's maintenance order margin, converted and expressed in the currency of this record
→	20079	BalanceAccountMarketValue	N	Amt	This balance record's market value of this account, converted and expressed in the currency of this record
→	20080	BalanceCommission	N	Amt	This balance record's commission, converted and expressed in the currency of this record
→	20081	BalanceFrozenCommission	N	Amt	This balance record's frozen commission, converted and expressed in the currency of this record
	Standard Trailer		Y		

Funds Detail Example

ATP -> Client: 8=FIX.4.4 9=501 35=UFD 34=392 49=ATPFIX 52=20250915-09:04:21.170 56=CLIENT01 1=CLIENT01 12=0 20004=req002 20039=0 20044=USD 20045=52441.6704 20046=0 20047=0 20048=-30529.1704 20049=0 20050=2500 20051=21912.5 20052=0 20053=0 20054=0 20055=0 20057=19412.5 20058=52441.6704 20059=0 20060=21912.5 20061=0 20062=1 20063=0 15=USD 20064=52441.6704 20065=0 20066=0 20067=-30529.1704 20068=0 20069=2500 20070=21912.5 20071=0 20072=0 20073=0 20074=0 20075=0 20076=19412.5 20077=52441.6704 20078=0 20079=21912.5 20080=0 20081=0 10=031

6. Information Needed From ATP

Please see below the information required in order for Client to connect and perform UAT conformance testing:

Field Name	Example	Comments
LoginUsername	user	Client's username
LoginPassword	password	Client's password
SenderCompID	CLIENT01	Client's trading session identifier (provided by ATP)
TargetCompID	ATPFIX	ATP identifier (provided by ATP)
SocketConnectHost	demo.atplatform.cn	Host of ATP's FIX Server
SocketConnectPort	20235 (with SSL/TLS) 20245 (without SSL/TLS, only available in TEST environment)	Port of ATP's FIX Server. NOTE: Only port with SSL/TLS will be provided in PROD
ResetOnLogon	NO	Predefined by ATP, not changeable

Sessions	18:00 - 17:30 (America/New_York), except weekends	Predefined by ATP, not changeable
----------	---	-----------------------------------

7. Conformance Test

ATP does not have a strict set of conformance tests required for the Client FIX API connection, and therefore we advise the Client to provide a list of test scenarios they expect to encounter while in PROD.

Below are some examples of basic conformance test scenarios to be carried out between ATP and the Client (this is by no means an exhaustive list):

- login and logout
- check the behavior (reset/persistence) of sequence numbers
- place a limit order ('OrdType'=2) to test execution, partial fill and rejections
- place orders with no partial fills allowed
- etc.

8. Support and FAQs

For support or questions about the ATP FIX Engine, please contact the support team of ATP.

9. Appendix

9.1. ATP Exchange Code

ATP Exchange Code	MIC Code(ISO10383)	Exchange
APEX	APEX	ASIA PACIFIC EXCHANGE
ASX	XASX	ASX - ALL MARKETS
BMD	XKLS	BURSA MALAYSIA
CBT	XCBT	CHICAGO BOARD OF TRADE
CF	CCFX	CHINA FINANCIAL FUTURES EXCHANGE
CFE	XCBF	CBOE FUTURES EXCHANGE
CME	XCME	CHICAGO MERCANTILE EXCHANGE
DC	XDCE	DALIAN COMMODITY EXCHANGE
DGCX	DGCX	DUBAI GOLD & COMMODITIES EXCHANGE DMCC
DME	DUMX	DUBAI MERCANTILE EXCHANGE
EEX	XEEE	EUROPEAN ENERGY EXCHANGE
EUNX	XPAR	EURONEXT - EURONEXT PARIS
EUX	XEUR	EUREX DEUTSCHLAND
HKE	XHKG	HONG KONG EXCHANGES AND CLEARING LTD
ICE	IFAD	ICE FUTURES ABU DHABI
	IFEU	ICE FUTURES EUROPE
	IFEN	ICE FUTURES EUROPE - OIL AND REFINED PRODUCTS DIVISION
	IFLL	ICE FUTURES EUROPE - FINANCIAL PRODUCTS DIVISION
	IFLO	ICE FUTURES EUROPE - EQUITY PRODUCTS DIVISION
	IFLX	ICE FUTURES EUROPE - AGRICULTURAL PRODUCTS DIVISION
	IFSG	ICE FUTURES SINGAPORE
	IFUS	ICE FUTURES U.S.
	IFED	ICE FUTURES U.S. ENERGY DIVISION
IDEM	XMIL	BORSA ITALIANA S.P.A.
INE	XINE	SHANGHAI INTERNATIONAL ENERGY EXCHANGE
KSE	XKRX	KOREA EXCHANGE (STOCK MARKET)
	XKFE	KOREA EXCHANGE (FUTURES MARKET)

LME	XLME	LONDON METAL EXCHANGE
MEFF	XMRV	MEFF FINANCIAL DERIVATIVES
MGEX	XMGE	MINNEAPOLIS GRAIN EXCHANGE
NYM	XNYM	NEW YORK MERCANTILE EXCHANGE
OSE	XOSE	OSAKA EXCHANGE
SGE	SGEX	SHANGHAI GOLD EXCHANGE
SGX	XSES	SINGAPORE EXCHANGE
SH	XSGE	SHANGHAI FUTURES EXCHANGE
TCE	XTKT	TOKYO COMMODITY EXCHANGE
TFEX	TFEX	THAILAND FUTURES EXCHANGE
ZC	XZCE	ZHENGZHOU COMMODITY EXCHANGE

9.2. ATP FIX Tag

Tag	Field Name
1	Account
6	AvgPx
7	BeginSeqNo
8	BeginString
9	BodyLength
10	Checksum
11	ClOrdID
12	Commission
14	CumQty
15	Currency
16	EndSeqNo
17	ExecID
19	ExecRefID
31	LastPx
32	LastQty
34	MsgSeqNum
35	MsgType

36	NewSeqNo
37	OrderID
38	OrderQty
39	OrdStatus
40	OrdType
41	OrigClOrdID
42	OrigTime
43	PossDupFlag
44	Price
45	RefSeqNum
49	SenderCompID
52	SendingTime
54	Side
55	Symbol
56	TargetCompID
57	TargetSubID
58	Text
59	TimeInForce
60	TransactTime
75	TradeDate
77	OffsetFlag
97	PossResend
98	EncryptMethod
99	StopPrice
102	CxlRejReason
103	OrdRejReason
108	HeartBtInt
110	MinQty
112	TestReqID
116	OnBehalfOfSubID

122	OrigSendingTime
123	GapFillFlag
126	ExpireTime
141	ResetSeqNumFlag
150	ExecType
151	LeavesQty
167	SecurityType
168	EffectiveTime
201	PutOrCall
202	StrikePrice
207	SecurityExchange
210	MaxShow
262	MDReqID
311	UnderlyingSymbol
320	SecurityReqID
323	SecurityResponseType
371	RefTagID
372	RefMsgType
373	SessionRejectReason
379	BusinessRejectRefID
380	BusinessRejectReason
432	ExpireDate
434	CxlRejResponseTo
460	Product
541	MaturityDate
553	Username
554	Password
561	RoundLot
702	NoPositions
703	PosType

704	LongQty
705	ShortQty
789	NextExpectedMsgSeqNum
893	LastFragment
912	LastRptRequested
969	TickSize
6351	PositionDirection
20001	HedgeFlag
20002	Note
20003	OutdatedFlag
20004	RequestID
20005	MIC
20006	ReqResult
20007	ActualSymbol
20008	PosAvgPx
20011	PriceType
20012	PriceDiffInTick
20013	EnableLimitPrice
20014	LimitPrice
20015	SubOrderQty
20018	TriggerTimeInterval
20019	CancelTimeInterval
20020	MaxCancelOrderTimes
20026	CumulateUnmatchedQty
20035	ExpectedParticipationRatio
20037	ParentOrderID
20038	CloseProfitByOpenPx
20039	CloseProfitBySettlePx
20040	NoRates
20041	MasterCurrency

20042	CurrencyRate
20043	CurrencyConversionAllowed
20044	BaseCurrency
20045	PositionInitMargin
20046	OrderInitMargin
20047	CreditLimit
20048	AvailableFunds
20049	CashMovement
20050	BeginningCash
20051	Equity
20052	FrozenPremium
20053	Premium
20054	LongOptionValue
20055	ShortOptionValue
20057	FloatingPnl
20058	PositionMaintenanceMargin
20059	OrderMaintenanceMargin
20060	AccountMarketValue
20061	FrozenCommission
20062	NoBalances
20063	BalanceGrpType
20064	BalancePositionInitMargin
20065	BalanceOrderInitMargin
20066	BalanceCreditLimit
20067	BalanceAvailableFunds
20068	BalanceCashMovement
20069	BalanceBeginningCash
20070	BalanceEquity
20071	BalanceFrozenPremium
20072	BalancePremium

20073	BalanceLongOptionValue
20074	BalanceShortOptionValue
20075	BalanceClosedPnl
20076	BalanceFloatingPnl
20077	BalancePositionMaintenanceMargin
20078	BalanceOrderMaintenanceMargin
20079	BalanceAccountMarketValue
20080	BalanceCommission
20081	BalanceFrozenCommission
20082	CanceledPrice
20083	CanceledQty
20084	TrsType
20085	TrsExpiryDate
20086	TrsRate