- (iii) With large deviation from the set point or smaller. Explain
- Determine the transfer function of a lead compensator that will provide a phase lead of 50° and gain of 8dB at $\omega = 5$ rad/sec. (p)
- Obtain the state space representation for the system described the equation: (a) 9

$$\frac{d^2y}{dt^3} + \frac{d^2y}{dt^2} + 6\frac{dy}{dt} = 6u(t)$$

- Check the controllability and observability of the system given in Q. 6 (a). (p)
- found in the system? Explain any five of What are the most common non-linearity these in detail. (a) 1.
- What is the difference between Regulator and Tracking Problem. (p)

Roll No.

Total Pages: 04 020602

May 2024

Robotics and Artificial Intelligence B. Tech. (RAI) (Sixth Semester) (PCC-RAI-602/21) Control Systems

Time: 3 Hours

[Maximum Marks: 75

Note: It is compulsory to answer all the questions sub-parts of a question are to be attempted (1.5 marks each) of Part A in short. Answer any four questions from Part B in detail. Different adjacent to each other.

PartA

- function and a state-space representation of What is the difference between a transfer a system? (a)
- Why positive feedback system is not advisable? 9
- What (positive or negative) should be Gain Margin for stable system? What is the reason? (3)

20


(d) Sketch the approximate polar plot for: 1.5

$$G(s)H(s) = \frac{1}{s^4(s+p)}; p > 0\mathbb{R}$$

- (e) What is corner frequency in Bode Plot? 1.5
- (f) Write the formula to evaluate 'Angle of Arrival' in root locus?
- (g) What is the relation existing between the standard test signals?
- (h) What are the units of Position error constant (K_p) , Velocity error constant (K_ν) and Acceleration error constant (K_ρ) ? 1.5
- (i) Compare lead and lag-lead compensation. 1.5
- (j) What do you mean by homogeneous and non-homogeneous state equations.

Part B

2. (a) Obtain the transfer function (C(s)/R(s)) of the system given below.



- (b) Describe the advantage of negative feedback control system on the basis of sensitivity analysis.
- 3. (a) Sketch the root locus of the system whose loop transfer function is given by

$$G(s)H(s) = \frac{K}{s(s+1)(s+2)}$$
. Also determine the range of K for which the system is

(b) The open loop transfer function of the system G(s) for a unity feedback system is given by

unstable.

$$G(s) = \frac{10(1+s)}{s^2 (6+5s)}$$
. Determine the Steady-

state error to an input $r(t) = 1 + 3t + 4t^2$ using the generalized error coefficients. 5

4. The loop transfer function of a certain control

system is given by
$$G(s)H(s) = \frac{k(s+1)^2}{s^3}$$
 Sketch the Nyquist plot and examine the stability of the system.

- 5. (a) Integral control action makes a process:
- i) Faster or Slower

More oscillatory or less

(ii)

10

C-020602