

OpenHW Group

Proven Processor IP

CORE-V Verification Overview and Status

Mike Thompson

mike@openhwgroup.org




Objectives



- Introduce of CORE-V verification to INVIA team:
 - Its mostly about CV32E40P at this time.
- Introduce the OpenHW Group workflow.
- Discuss future plans:
 - Phase 2 and 3 of CV32E40P verification
 - CV64A verification
 - Challenges
- Discuss INVIA Contribution.



Overall Status



- On-going documentation:
 - <u>Verification Strategy</u>: mature, updates pending for debug, interrupt and CV64A.
 - Verification Plans (test plans): ~60% complete not yet reviewed.
- SV/UVM verification environment for CV32E40P is in place:
 - Expect to integrate Instruction Set Simulator this week.
 - Next steps:
 - Google random instruction generator
 - Functional coverage model
 - Medium term:
 - Debug and Interrupts



Overall Status

(2 of 2)



Formal Verification:

- Formal Verification strategy captured in Verification Strategy.
- Virtual Machine created for OneSpin.
- Effort has stalled for lack of human resource.

FPGA Prototyping:

- A little early to start.
- Should be a collaborative effort with the hardware and software task groups.
- May be superseded by proposed "Soft Core" projects.
- Bluespec has expressed interest.

CV64A:

No significant progress.

Miscellaneous:

- Conducting a trial of SymbioticEDA MCY.
- Verif-ai would like to use CV32E to trial its coverage closure tool.



CV32E40P Verification




- CV32E40P is almost a direct copy of PULP RI5CY.
 - Repository has been moved (not cloned or forked) to OpenHW.
 - Future CV32E40 planned (replace PULP instructions with RV ISA).
- OpenHW verification goals:
 - deploy industrial-grade SV/UVM verification for all CORE-V cores.
 - complete verification of both CV32E and CV64A cores.
- Up to this point, work has focused almost exclusively on CV32E.
- Many members of the PULP community objected to the loss of the "Verilator" testbench:
 - As a result, we maintain it under the name "core" testbench.



CORE Testbench







Status of CORE Testbench as of 2020-05-12




- Basic functionality supported:
 - Integrated with CV32E40P
 - Default target runs hello-world test using Verilator
 - Can run all inherited RI5CY testcases
- Makefile for CORE testbench not much changed from February time-frame:
 - Common targets and variables centralized in Common.mk
 - Enforce use of specific branch/hash of the RTL.
- Purpose is to maintain simple environment for simple tests:
 - Designer-level testing
 - Demonstration platform
 - Not for regressions or coverage closure.



Phase 1 UVMT_CV32 Verification Environment








Planned UVM Environment for CV32





Status of UVMT_CV32 as of 2020-05-12





- Phase 1 development complete
 - Integrated with CV32E40P
 - Properly clone RTL from source GitHub Repos and uses Designer Manifest.
 - Can run all inherited RI5CY testcases (two known failures)
- Makefiles UVMT CV32 have been significantly updated:
 - Enforce use of specific branch/hash of the RTL.
 - Common targets and variables centralized in Common.mk
 - Moved simulator-specific Make targets into separate files
- Phase 2 development of UVM environment on-going:
 - Integration of ISS (largely complete)
 - Ready to integrate Google Instruction Generator (riscv-dv)
- Software issues are starting to become a problem:
 - Need to standardize on a supported compiler/assembler toolchain
 - Need to define and implement runtime environment (crt0.S, link.ld, etc.)



Generic CORE-V UVM Environment











Generic ENV is *Proposal*, not a *Plan*



- The idea of a Generic verification environment for CORE-V verification needs to be evaluated against several criteria:
 - Overhead of development vs. benefit of re-use
 - Buy-in by OpenHW members
- Many open questions:
 - Does the concept of a generic env imply that we standardize on a single generator and ISS?
 - How to provide support for core-specific coverage, etc.



Workflow: Task Assignment, Execution and CI



OpenHW uses **dsim** on IBM Cloud, and **xrun** on CMC Cloud







Recommend to add VTG co-chairs as pull-request reviewers.











Each AC uses their Company's compute and tools



Metrics CI regressions use *dsim* on Google Cloud



On-going Challenges



- The design specification (known as the 'user_manual') is incomplete and falling behind
 - No human resource has been allocated to work on this.
 - Design changes to the RTL are happening without prior updates and review of the design specification.
 - At this point, the effort to complete the **verification plans** is stalled until the design specification is completed.
- Use of EDA tools:
 - Some members have been voiced concerns about OpenHW use of commercial SystemVerilog simulators.
 - The verification environment is coded in UVM and cannot be compiled/simulated by open source tools.
 - To alleviate this issue, I agreed to support a "core" testbench for CV32E40P that can be run with Verilator. (In hind-sight, I view this as a mistake.)

- The Verification Strategy calls for the use of the OVPsim Instruction Set Simulator (ISS)
 - This is commercial Verification IP sold by Imperas.
 - All users of the CORE-V verification environments will need a license from Imperas.
 - These will be provided free-of-charge by Imperas to OpenHW members.

Toolchain

- The CORE-V verification environments depend on a RISC-V GCC GNU compiler/assembler known as the "toolchain".
- Verification needs support from the Software Task Group:
 - The one supported by the RISC-V foundation does not support Xpulp instructions used by CV32E40P.
 - The PULP toolchain does not support some pseudo-instructions required by the RISC-V Compliance testsuite.





Thank You!







Background Slides



Project & Tasks on GitHub








Workflow: Verification Plans





Hierarchically organized by Feature.

One Spreadsheet per Feature