
Python Data Audit



PyAudit: Python Data Audit Library API

Wenqiang Feng and Ming Chen

April 29, 2019

CONTENTS

1	Preface	3
1.1	About	3
1.1.1	About this API	3
1.1.2	About the author	3
1.2	Feedback and suggestions	4
2	How to Install	5
2.1	Clone the Repository	5
2.2	Install	5
2.3	Uninstall	5
2.4	Test	5
3	Python Data Audit Functions	9
3.1	dtypes_class	9
3.2	missing_rate	9
3.3	zero_rate	10
3.4	feature_variance	10
3.5	freq_items_df	11
3.6	feature_len	12
3.7	numeric_summary	12
4	Demos	15
5	Main Reference	17
	Bibliography	19
	Python Module Index	21
	Index	23

Python Data Audit



Welcome to our **PyAudit: Python Data Audit Library API**! The PDF version can be downloaded from [HERE](#).

PREFACE

Chinese proverb

Good tools are prerequisite to the successful execution of a job. – old Chinese proverb

1.1 About

1.1.1 About this API

This document is the API book for our PyAudit: Python Data Audit Library [PyAudit] API. The PDF version can be downloaded from [HERE](#). **You may download and distribute it. Please be aware, however, that the note contains typos as well as inaccurate or incorrect description.**

The API assumes that the reader has a preliminary knowledge of `python` programing and `Linux`. And this document is generated automatically by using `sphinx`.

1.1.2 About the author

- **Wenqiang Feng**
 - Sr. Data Scientist and PhD in Mathematics
 - University of Tennessee at Knoxville
 - Webpage: <http://web.utk.edu/~wfeng1/>
 - Email: von198@gmail.com
- **Ming Chen**
 - Data Scientist and PhD in Genome Science and Technology
 - University of Tennessee at Knoxville

– Email: ming.chen0919@gmail.com

- **Biography**

Wenqiang Feng is Data Scientist within DST’s Applied Analytics Group. Dr. Feng’s responsibilities include providing DST clients with access to cutting-edge skills and technologies, including Big Data analytic solutions, advanced analytic and data enhancement techniques and modeling.

Dr. Feng has deep analytic expertise in data mining, analytic systems, machine learning algorithms, business intelligence, and applying Big Data tools to strategically solve industry problems in a cross-functional business. Before joining DST, Dr. Feng was an IMA Data Science Fellow at The Institute for Mathematics and its Applications (IMA) at the University of Minnesota. While there, he helped startup companies make marketing decisions based on deep predictive analytics.

Dr. Feng graduated from University of Tennessee, Knoxville, with Ph.D. in Computational Mathematics and Master’s degree in Statistics. He also holds Master’s degree in Computational Mathematics from Missouri University of Science and Technology (MST) and Master’s degree in Applied Mathematics from the University of Science and Technology of China (USTC).

- **Declaration**

The work of Wenqiang Feng was supported by the IMA, while working at IMA. However, any opinion, finding, and conclusions or recommendations expressed in this material are those of the author and do not necessarily reflect the views of the IMA, UTK and DST.

1.2 Feedback and suggestions

Your comments and suggestions are highly appreciated. I am more than happy to receive corrections, suggestions or feedbacks through email (Wenqiang Feng: von198@gmail.com and Ming Chen: ming.chen0919@gmail.com) for improvements.

HOW TO INSTALL

2.1 Clone the Repository

```
git clone https://github.com/runawayhorse001/PyAudit.git
```

2.2 Install

```
cd PyAudit
pip install -r requirements.txt
python setup.py install
```

2.3 Uninstall

```
pip uninstall statspy
```

2.4 Test

```
cd PyAudit/test
python test1.py
```

test1.py

```
from PyAudit.basics import missing_rate, zero_rate, dtypes_class
from PyAudit.basics import feature_variance, freq_items_df, feature_len
from PyAudit.basics import numeric_summary
import pandas as pd
```

(continues on next page)

(continued from previous page)

```

d = {'A': [1, 0, None, 3],
     'B': [1, 0, 0, 0],
     'C': ['a', None, 'c', 'd']}

# create DataFrame
df = pd.DataFrame(d)
print(missing_rate(df))
print(zero_rate(df))
print(feature_variance(df))
print(df)
print(feature_len(df))
(num_fields, cat_fields, bool_fields, data_types, type_class) = dtypes_
    →class(df)
print(numeric_summary(df[num_fields]))

d = {
    'num': list('1223334444'),
    'cat': list('wxyyyzzzz')
}
df = pd.DataFrame(d)
df = df.astype({"num": int, "cat": object})
print(freq_items_df(df, top_n=4))

# read df
df = pd.read_csv('Heart.csv', dtype={'Sex': bool})
print(df.head(5))
(num_fields, cat_fields, bool_fields, data_types, type_class) = dtypes_
    →class(df)

print(num_fields)
print(cat_fields)
print(bool_fields)
print(data_types)
print(type_class)
print(missing_rate(df))
#print(zero_rate(df))

print(freq_items_df(df, top_n=4))
print(feature_len(df))
print(numeric_summary(df[num_fields]))

```

Results:

```

feature  missing_rate
0      A      0.25
1      B      0.00
2      C      0.25
feature  zero_rate
0      A  0.333333
1      B  0.750000
2      C  0.000000
feature  feature_variance
0      A      1.0
1      B      0.5
2      C      1.0
  Age  Sex  ChestPain  RestBP  Chol  ...  Oldpeak  Slope  Ca
→  Thal  AHD
0  63  True    typical    145   233  ...    2.3     3  0.0
→  fixed  No
1  67  True  asymptomatic    160   286  ...    1.5     2  3.0
→  normal Yes
2  67  True  asymptomatic    120   229  ...    2.6     2  2.0
→reversible Yes
3  37  True   nonanginal    130   250  ...    3.5     3  0.0
→  normal  No
4  41 False   nontypical    130   204  ...    1.4     1  0.0
→  normal  No

[5 rows x 14 columns]
['Age', 'RestBP', 'Chol', 'Fbs', 'RestECG', 'MaxHR', 'ExAng', 'Oldpeak',
→ 'Slope', 'Ca']
['ChestPain', 'Thal', 'AHD']
['Sex']
feature  dtypes
0      Age  int64
1      Sex  bool
2  ChestPain  object
3      RestBP  int64
4      Chol  int64
5      Fbs  int64
6  RestECG  int64
7      MaxHR  int64
8      ExAng  int64
9  Oldpeak  float64
10     Slope  int64
11      Ca  float64
12     Thal  object
13     AHD  object
feature  dtypes  class

```

(continues on next page)

(continued from previous page)

```
0      Age      int64      numeric
1      Sex      bool       bool
2      ChestPain object    category
3      RestBP   int64      numeric
4      Chol     int64      numeric
5      Fbs      int64      numeric
6      RestECG  int64      numeric
7      MaxHR    int64      numeric
8      ExAng    int64      numeric
9      Oldpeak  float64     numeric
10     Slope    int64      numeric
11     Ca       float64     numeric
12     Thal     object    category
13     AHD      object    category
      feature  missing_rate
0      Age      0.000000
1      Sex      0.000000
2      ChestPain 0.000000
3      RestBP   0.000000
4      Chol     0.000000
5      Fbs      0.000000
6      RestECG  0.000000
7      MaxHR    0.000000
8      ExAng    0.000000
9      Oldpeak  0.000000
10     Slope    0.000000
11     Ca       0.013201
12     Thal     0.006601
13     AHD      0.000000

Process finished with exit code 0
```

PYTHON DATA AUDIT FUNCTIONS

3.1 dtypes_class

`PyAudit.basics.dtypes_class(df_in)`
numerical, categorical and bool name list in the DataFrame

Parameters `df_in` – input pandas DataFrame

Returns numerical, categorical and bool name list

Author Wenqiang Feng and Ming Chen

Email von198@gmail.com

```
>>> from PyAudit.basics import dtypes_class
>>> df = pd.read_csv('Heart.csv', dtype={'Sex': bool})
>>> (num_fields, cat_fields, bool_fields, data_types, type_class),
↳ dtypes_class(df)
>>> num_fields
['Age', 'RestBP', 'Chol', 'Fbs', 'RestECG', 'MaxHR', 'ExAng',
↳ 'Oldpeak', 'Slope', 'Ca']
```

3.2 missing_rate

`PyAudit.basics.missing_rate(df_in)`
calculate missing rate for each feature in the DataFrame

Parameters `df_in` – input pandas DataFrame

Returns missing rate

Author Wenqiang Feng and Ming Chen

Email von198@gmail.com

```
>>> import pandas as pd
>>> d = {'A': [1, 0, None, 3],
        'B': [1, 0, 0, 0],
        'C': ['a', None, 'c', 'd']}
>>> # create DataFrame
>>> df = pd.DataFrame(d)
>>> from PyAudit.basics import missing_rate
>>> missing_rate(df)
      feature  missing_rate
0          A           0.25
1          B           0.00
2          C           0.25
```

3.3 zero_rate

`PyAudit.basics.zero_rate(df_in)`

calculate the percentage of 0 value for each feature in the DataFrame

Parameters `df_in` – input pandas DataFrame

Returns zero rate

Author Wenqiang Feng and Ming Chen

Email von198@gmail.com

```
>>> import pandas as pd
>>> d = {'A': [1, 0, None, 3],
        'B': [1, 0, 0, 0],
        'C': ['a', None, 'c', 'd']}
>>> # create DataFrame
>>> df = pd.DataFrame(d)
>>> from PyAudit.basics import zero_rate
>>> zero_rate(df)
      feature  zero_rate
0          A   0.333333
1          B   0.750000
2          C   0.000000
```

3.4 feature_variance

`PyAudit.basics.feature_variance(df_in)`

calculate the variance for each feature

Parameters `df_in` – input pandas DataFrame

Returns feature variance

Author Wenqiang Feng and Ming Chen

Email von198@gmail.com

```
>>> import pandas as pd
>>> d = {'A': [1, 0, None, 3],
        'B': [1, 0, 0, 0],
        'C': ['a', None, 'c', 'd']}
>>> # create DataFrame
>>> df = pd.DataFrame(d)
>>> from PyAudit.basics import zero_rate
>>> zero_rate(df)
      feature  feature_variance
0          A                1.0
1          B                0.5
2          C                1.0
```

3.5 freq_items_df

`PyAudit.basics.freq_items_df(df_in, top_n=3)`

find out the top n values and the corresponding frequency for each feature

Parameters

- `df_in` – input pandas DataFrame
- `top_n` – the number of the top values

Returns top n values and the corresponding frequency for each feature

```
>>> d = {
>>>     'num': list('1223334444'),
>>>     'cat': list('wxyyyzzzz')
>>> }
>>> df = pd.DataFrame(d)
>>> df = df.astype({"num": int, "cat": object})
>>> print(freq_items_df(df, top_n=4))
      feature  top_items  top_freqs
0        num  [4, 3, 2, 1]  [4, 3, 2, 1]
1        cat  [z, y, x, w]  [4, 3, 2, 1]
```

3.6 feature_len

`PyAudit.basics.feature_len(df_in)`

find out the min and max length of values for each feature

Parameters `df_in` – input pandas DataFrame

Returns min and max length DataFrame

```
>>> d = {'A': [1, 0, None, 3],
>>>       'B': [1, 0, 0, 0],
>>>       'C': ['a', None, 'c', 'd']}
>>> # create DataFrame
>>> df = pd.DataFrame(d)
>>> print(df)
   A  B  C
0  1  1  a
1  0  0 None
2 NaN 0  c
3  3  0  d
>>> print(feature_len(df))
   feature  min_length  max_length
0        A           3           3
1        B           1           1
2        C           1           4
```

3.7 numeric_summary

`PyAudit.basics.numeric_summary(df_in, deciles=False)`

generate statistical summary for numerical DataFrame

Parameters

- `df_in` –
- `deciles` – flag for percentiles style

Returns statistical summary for numerical data

```
>>> d = {'A': [1, 0, None, 3],
>>>       'B': [1, 0, 0, 0],
>>>       'C': ['a', None, 'c', 'd']}
>>> # create DataFrame
>>> df = pd.DataFrame(d)
>>> (num_fields, cat_fields, bool_fields, data_types, type_class) =
↪ dtypes_class(df)
```

(continues on next page)

(continued from previous page)

```
>>> print(numeric_summary(df[num_fields]))
  feature  min      percentiles  max  ...      std  lower_95_ci  _
↪upper_95_ci  sum
0        A  0.0    [0.5, 1.0, 2.0]  3.0  ...  1.527525    -0.395224  _
↪    3.061891  4.0
1        B  0.0    [0.0, 0.0, 0.25]  1.0  ...  0.500000    -0.240000  _
↪    0.740000  1.0
```


DEMOS

This is a usage of `PyAudit.basics.dtypes_class()`:

For example:

```
>>> from PyAudit.basics import missing_rate, zero_rate, dtypes_class
>>> df = pd.read_csv('Heart.csv', dtype={'Sex': bool})
>>> (num_fields, cat_fields, bool_fields, data_types, type_class) = _
    ↳ dtypes_class(df)
['Age', 'RestBP', 'Chol', 'Fbs', 'RestECG', 'MaxHR', 'ExAng', 'Oldpeak',
 ↳ ', 'Slope', 'Ca']
['ChestPain', 'Thal', 'AHD']
['Sex']
```

	feature	dtypes
0	Age	int64
1	Sex	bool
2	ChestPain	object
3	RestBP	int64
4	Chol	int64
5	Fbs	int64
6	RestECG	int64
7	MaxHR	int64
8	ExAng	int64
9	Oldpeak	float64
10	Slope	int64
11	Ca	float64
12	Thal	object
13	AHD	object

	feature	dtypes	class
0	Age	int64	numeric
1	Sex	bool	bool
2	ChestPain	object	category
3	RestBP	int64	numeric
4	Chol	int64	numeric
5	Fbs	int64	numeric

(continues on next page)

(continued from previous page)

6	RestECG	int64	numeric
7	MaxHR	int64	numeric
8	ExAng	int64	numeric
9	Oldpeak	float64	numeric
10	Slope	int64	numeric
11	Ca	float64	numeric
12	Thal	object	category
13	AHD	object	category

This is a usage of `PyAudit.basics.feature_variance()`:

For example:

```

    . . . .
    , , , * , , , ,
    . - ' ` ` ; - ' ) ; ; .
    / ' . - . / * ; ;
    . ' \d \; ; . , , , ,
    / o \ \; ; , _ . , , , * , , , * ,
    \ _ , _ . _ , ' \ _ . - ' ) _ ) -- . , , , , * , , , ,
    ` " " ` ; ; ; \ / - ' ) _ ) _ ) ` \ ' ' ; ; ; ;
    ; * ; ; ; - ' ) ` ) _ ) | \ | ; ; ; * ;
    ; ; ; ; | ` --- ` O | | ; ; * ; ;
    * ; * ; \ | O / ; ; ; ; *
    ; ; ; ; / | . ----- \ / ; ; ; ; ;
    ; ; ; * ; / \ | ' . ( ` . ; ; ; * ; ;
    ; ; ; ; ' . ; | ) \ | ; ; ; ;
    , ; * ; ; ; \ / | . / / ^ | ' ; ; ; * ;
    ; ; ; ; ; / | / / _ / ' ; ; ;
    ' * w f * / | / _ _ | ; * ;
    ` " " " " ` ` " " " " ` ; '

```

CHAPTER

FIVE

MAIN REFERENCE

BIBLIOGRAPHY

[PyAudit] Wenqiang Feng and Ming Chen. [Python Data Audit Library API](#), 2019.

PYTHON MODULE INDEX

p

`PyAudit.basics`, [12](#)

INDEX

D

`dtypes_class()` (in module *PyAudit.basics*), 9

F

`feature_len()` (in module *PyAudit.basics*), 12

`feature_variance()` (in module *PyAudit.basics*), 10

`freq_items_df()` (in module *PyAudit.basics*), 11

M

`missing_rate()` (in module *PyAudit.basics*), 9

N

`numeric_summary()` (in module *PyAudit.basics*), 12

P

`PyAudit.basics` (module), 9–12

Z

`zero_rate()` (in module *PyAudit.basics*), 10