RAJALAKSHMI ENGINEERING COLLEGE

V Y Aares 251801001-2025-AIDS V2

Started on	Wednesday, 23 September 2026, 10:19 PM
State	Finished
Completed on	Wednesday, 23 September 2026, 10:20 PM
Time taken	48 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int major(int nums[], int low, int high)
{
    if (low == high)
        return nums[low];

    int mid = (low + high) / 2;

    int left = major(nums, low, mid);
    int right = major(nums, mid + 1, high);

    if (left == right)
        return left;

    int lcount = 0, rcount = 0;

    for (int i = low; i <= high; i++)
    {
        if (nums[i] == left)
            lcount++;

        if (nums[i] == right)
            rcount++;
    }

    if (lcount > (high - low + 1) / 2)
        return left;

    return right;
}

int main()
```

```
{
    int n;
    scanf("%d", &n);

    int nums[n];

    for (int i = 0; i < n; i++)
    {
        scanf("%d", &nums[i]);
    }

    printf("%d\n", major(nums, 0, n - 1));

    return 0;
}
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course