Security Class:

Top-Secret ()

Secret ()

Internal ()

Public ($\sqrt{ }$)

RKNN-Toolkit2 API Reference

(Graphic Computing Platform Center)

Mark:	Version	V1.6.0
[] Editing	Author	HPC Team
[√] Released	Completed Date	15/Nov/2023
	Reviewer	Vincent
	Reviewed Date	15/Nov/2023

瑞芯微电子股份有限公司

Rockchip Electronics Co., Ltd (Copyright Reserved)



Revision History

Version	Modifier	Date	Modify description	Reviewer
V1.6.0	HPC Team	15/Nov/2023	Initial version	Vincent
			A A Y	



Content

1 OVERVIEW	4
1.1 APPLICABLE CHIP MODEL	4
1.2 REQUIREMENTS/DEPENDENCIES	4
1.3 SUPPORTED DEEP LEARNING FRAMEWORK	4
2 RKNN-TOOLKIT2 API DESCRIPTION	7
2.1 RKNN INITIALIZATION AND RELEASE	
2.1 RKNN INITIALIZATION AND RELEASE	
2.3 LOADING MODEL	11
2.3.1 Loading Caffe model	12
2.3.2 Loading TensorFlow model	
2.3.3 Loading TensorFlow Lite model	13
2.3.4 Loading ONNX model	
2.3.5 Loading DarkNet model	
2.3.6 Loading PyTorch model	
2.4 BUILDING RKNN MODEL	16
2.5 EXPORT RKNN MODEL	17
2.6 LOADING RKNN MODEL	18
2.7 INITIALIZE THE RUNTIME ENVIRONMENT	19
2.8 Inference with RKNN model	20
2.9 EVALUATE MODEL PERFORMANCE	22
2.10 EVALUATING MEMORY USAGE	22
2.11 GET SDK VERSION	23
2.12 Hybrid Quantization	24
2.12.1 hybrid quantization step1	24



2.12.2 hybrid_quantization_step2	25
2.13 QUANTITATIVE ACCURACY ANALYSIS	26
2.14 LIST DEVICES	28
2.15 EXPORT ENCRYPTED RKNN MODEL	28
2.16 REGISTER CUSTOM OPERATOR	20





1 Overview

RKNN-Toolkit2 is a development kit that provides users with model conversion, inference and performance evaluation on PC platforms.

1.1 Applicable chip model

- RK3566 series
- RK3568 series
- RK3588 series
- RV1103
- RV1106
- RK3562

Note: RK3566 / RK3568 / RK3588 are collectively referred to as RK3566 series / RK3568 series / RK3588 series in the following text.

1.2 Requirements/Dependencies

It is recommended to meet the following requirements in the operating system environment:

Operating system version			Ubuntu22.04 (x64)
Python version 3.6 / 3.7		3.8 / 3.8	3.10 / 3.11

Note:

- 1. For more detail about python library dependencies, see doc/requirements*.txt
- 2. This document mainly uses Ubuntu 20.04 / Python3.8 as an example.

1.3 Supported Deep Learning Framework

The deep learning frameworks supported by RKNN-Toolkit2 include Caffe, TensorFlow, TensorFlow Lite, ONNX, Darknet and Pytorch.



The corresponding relationship between RKNN-Toolkit2 and the version of each deep learning framework is as follows:

RKNN-Toolkit2	Caffe	TensorFlow	TF Lite	ONNX	Darknet	Pytorch
1.4.0	1.0	1.12.0~2.8.0	Schema	1.7.0~1.10.0	Commit	1.6.0~1.10.1
1.4.2			version = 3		ID:	
1.5.0					810d7f7	
1.5.2						
1.6.0	1.0	1.12.0~2.14.0	Schema	1.7.0~1.14.0	Commit	1.6.0~1.13.1
			version = 3		ID:	
					810d7f7	

Note:

- 1. According to the protobuf version, any graph or checkpoint built with a certain version of TensorFlow can be loaded and evaluated by a higher (minor or patch) version of TensorFlow in the same major version. Theoretically, the pb files generated by TensorFlow with versions before 1.14 are supported by RKNN-Toolkit2 1.4.0 and later versions. For more information about the compatibility of different TensorFlow versions, please refer to official documentation: https://www.tensorflow.org/guide/versions
- Since the schemas of different versions of TFLite are incompatible with each other, TFLite
 model exported from a different schema compared to the schema version RKNN-Toolkit2
 relies may cause loading failure.
- 3. The caffe protocols used by RKNN-Toolkit2 is the protocol based on the official modification of berkeley. The protocol based on berkeley's official modification comes from: https://github.com/BVLC/caffe/tree/master/src/caffe/proto and the commit ID is 828dd10. RKNN-Toolkit2 adds some OPs on this basis.
- 4. For the relationship between ONNX release versions and opset versions and IR versions, please refer to the onnxruntime official website:
 - https://github.com/microsoft/onnxruntime/blob/v1.10.0/docs/Versioning.md
- 5. The official Github link of Darknet: https://github.com/pjreddie/darknet. RKNN-Toolkit2's current conversion rules are based on the latest submission of the master branch (commit



number: 810d7f7).

6. When loading the Pytorch model (torchscript model), it is recommended using the same version of Pytorch to export model and convert model to RKNN model. Inconsistency may result in failure when transferring to the RKNN model.





2 RKNN-Toolkit2 API description

2.1 RKNN initialization and release

The initialization/release function group consists of API interfaces to initialize and release the RKNN object as needed. The **RKNN()** must be called before using all the API interfaces of RKNN-Toolkit2, and call the **release()** method to release the object when task finished.

When the RKNN object is initing, the users can set *verbose* and *verbose_file* parameters, used to show detailed log information of model loading, building and so on. The data type of *verbose* parameter is bool. If the value of this parameter is set to True, the RKNN-Toolkit2 will show detailed log information on screen. The data type of *verbose_file* is string. If the value of this parameter is set to a file path, the detailed log information will be written to this file (the verbose also need be set to True).

The sample code is as follows:

```
# Show the detailed log information on screen.
rknn = RKNN(verbose=True)
...
rknn.release()
```

2.2 Model configuration

Before the RKNN model is built, the model needs to be configured first through the config interface.

API	config
Description	Set model convert parameters.
	mean_values: The mean values of the input. The parameter format is a list. The list
	contains one or more mean sublists. The multi-input model corresponds to multiple
	sublists. The length of each sublist is consistent with the number of channels of the input.
	For example, if the parameter is [[128,128,128]], it means an input subtract 128 from the
	values of the three channels.
	The default value is None, means all means is zero.



std_values: The normalized value of the input. The parameter format is a list. The list contains one or more normalized value sublists. The multi-input model corresponds to multiple sublists. The length of each sublist is consistent with the number of channels of the input. For example, if the parameter is [[128,128,128]], it means the value of the three channels of an input minus the average value and then divide by 128.

The default value is None, means all stds is one.

quant_img_RGB2BGR: Indicates whether the RGB2BGR operation needs to be done first when loading the quantized image. If there are multiple inputs, the corresponding parameters for each input is split with ',', such as [True, True, False]. The default value is False.

This configuration is generally used on the Caffe model. Most of the Caffe model training will perform RGB2BGR conversion on the dataset image firstly. At this time, the configuration needs to be set to True.

In addition, this configuration is only valid for the quantized image format of jpg/jpeg/png/bmp. This configuration is ignored when the npy format is read. Therefore, when the model input is BGR, npy also needs to be in BGR format.

This configuration is only used to read the quantize image in the quantization stage (build interface) or in quantitative accuracy analysis (accuracy_analysis interface), and will not be recorded in the final RKNN model. Therefore, if the input of the model is BGR, you need to ensure that the imported image data is also in BGR format before calling the inference of the toolkit or the run function of the C-API.

quantized_dtype: Quantization type, the quantization types currently supported are asymmetric_quantized-8, asymmetric_quantized-16(asymmetric_quantized-16 is not supported yet). The default value is asymmetric_quantized-8.

quantized_algorithm: The quantization algorithm used when calcaulating the quantization parameters of each layer. Currently support: **normal**, **mmse** and



kl divergence. The default value is normal.

The characteristic of **normal** quantization algorithm is fast. The recommended quantization data is generally about 20-100 pieces. with more data, the accuracy may not be further improved.

The **mmse** quantization algorithm is slower due to the violent iteration method, but usually has higher accuracy than normal. The recommended quantization data is generally about 20-50 pieces. Users can also increase or decrease the amount of data appropriately according to the length of the quantization time.

The **kl_divergence** algorithm will take more time than normal, but will be much less than mmse. In some scenarios(when the feature distribution is uneven), better improvement effects can be obtained by "kl_divergence". the recommended quantization data is generally about 20-100 pieces.

quantized method: Currently support layer or channel. The default value is channel.

layer: each weight has only one set of quantization parameters.

channel: each channel of weight has its own set of quantization parameters. usually the channel will be more accurate than the layer.

float_dtype: Used to specify the data type of floating in the non-quantized case, the data types currently supported are float16. The default value is float16.

optimization level: Model optimization level. The default value is 3.

By modifying the model optimization level, you can turn off some or all of the optimization rules used in the model conversion process. The default value of this parameter is 3, and all optimization options are turned on. When the value is 2 or 1, turn off some optimization options that may affect the accuracy of some models. Turn off all optimization options when the value is 0.

target_platform: Specify which target chip platform the RKNN model is based on. "rk3566", "rk3568", "rk3588", "rv1103", "rv1106" and "rk3562" are currently supported.



The default value is None.

custom_string: Add custom string information to RKNN model, then can query the information at runtime. The default value is None.

remove_weight: Remove the weights to generate a RKNN slave model that can share weights with the full weighted RKNN model to reduce memory consumption. The default value is False.

compress_weight: Compress the weights of the model, which can reduce the size of RKNN model. The default value is False.

single_core_mode: Whether to generate only single-core model, which can reduce the size and memory consumption of the RKNN model. The default value is False. only valid for RK3588. The default value is False.

model_pruning: Pruning the model that can reduce the size and calculation of the transformed RKNN model for models with sparse weights. The default value is False.

op_target: Used to specify the target of each operation (NPU/CPU/GPU etc.), the format is {'op0_output_name':'cpu', 'op1_output_name':'cpu', ...}, The default value is None. 'op0_output_name' and 'op1_output_name' are the output tensor names of the corresponding OP, which can be obtained from the returned results of the accuracy_analysis feature. 'cpu' and 'npu' indicate that the execution target of the OP corresponding to this tensor is CPU or NPU. The currently available options are: 'cpu' / 'npu' / 'gpu' / 'auto', and 'auto' is for automatically selecting the execution target.

dynamic_input: Simulate the function of dynamic input according to multiple sets of input shapes specified by the user. the format is [[input0_shapeA, input1_shapeA, ...], [input0_shapeB, input1_shapeB, ...], ...].

The default value is None, experimental.

For example, the input shape of the original model is [1,3,224,224] or [1,3,height,width] or [1,3,-1,-1], but the model for deploy needs to support 3 input shapes: [1,3,224,224],



[1,3,192,192] and [1,3,160,160], you can set dynamic_input=[[[1,3,224,224]], [[1,3,192,192]], [[1,3160,160]]]. When converting to the RKNN model for inference, the input data corresponding to the shape needs to be passed in. Note: 1. This function can only be enabled when the original model itself supports dynamic input, otherwise an error will be reported. 2. If the original model input shape itself is dynamic, only the dynamic axes can set different values. quantize_weight: When 'do_quantization' of rknn.build is False, reduce the size of the rknn model by quantizing some weights. The default value is False. remove_reshape: Remove possible 'Reshape' in model inputs and outputs to improve model runtime performance. default is False. Note: Enabling this configuration may modify the shape of the input or output nodes of the model. You need to pay attention to warning printing during the conversion process, and you also need to consider the impact of input and output shape changes when deploying. Return None. Value

The sample code is as follows:

```
# model config
rknn.config(mean_values=[[103.94, 116.78, 123.68]],
std_values=[[58.82, 58.82, 58.82]],
quant_img_RGB2BGR=True,
target_platform='rk3566')
```

2.3 Loading model

RKNN-Toolkit2 currently supports load non-RKNN models of Caffe, TensorFlow, TensorFlow Lite,



ONNX, DarkNet, PyTorch. There are different calling interfaces when loading models, the loading interfaces are described in detail below.

2.3.1 Loading Caffe model

API	load_caffe		
Description	Load Caffe model.		
Parameter	model: The path of Caffe model structure file (suffixed with ".prototxt").		
	blobs: The path of Caffe model binary data file (suffixed with ".caffemodel").		
	input_name: When the caffe model has multiple inputs, you can specify the order of the		
	input layer names through this parameter, such as ['input1','input2','input3'],note that the		
	name needs to be consistent with the model input name; The default value is None, means		
	the sequence is automatically given by the caffe model file (file suffix with .prototxt).		
Return	0: Import successfully.		
Value	-1: Import failed.		

The sample code is as follows:

Load the mobilenet_v2 Caffe model in the current path ret = rknn.load_caffe(model='./mobilenet_v2.prototxt', blobs='./mobilenet_v2.caffemodel')

2.3.2 Loading TensorFlow model

API	load_tensorflow
Description	Load TensorFlow model.
Parameter	tf_pb: The path of TensorFlow model file (suffixed with ".pb").
	inputs: The input node (operand name) of model, input with multiple nodes is supported
	now. All the input node string are placed in a list.
	input_size_list: The shapes of input node, all the input shape are placed in a list. As in the



	example of ssd_mobilenet_v1 model, the input_size_list parameter should be set to
	[[1,300,300,3]].
	outputs: The output node (operand name) of model, output with multiple nodes is
	supported now. All the output nodes are placed in a list.
	input_is_nchw: Whether the input layout of the model is already NCHW. The default
	value is False , means the default input layout is NHWC.
Return	0: Import successfully.
value	-1: Import failed.

2.3.3 Loading TensorFlow Lite model

API	load_tflite
Description	Load TensorFlow Lite model.
Parameter	model: The path of TensorFlow Lite model file (suffixed with ".tflite").
	input_is_nchw: Whether the input layout of the model is already NCHW. The default
	value is False, that is, the default input layout is NHWC.
Return	0: Import successfully.
Value	-1: Import failed.

The sample code is as follows:

```
# Load the mobilenet_v1 TF-Lite model in the current path ret = rknn.load_tflite(model = './mobilenet_v1.tflite')
```



2.3.4 Loading ONNX model

API	load_onnx		
Description	Load ONNX model.		
Parameter	model: The path of ONNX model file (suffixed with ".onnx").		
	inputs: The input node (operand name) of model, input with multiple nodes is supported		
	now. All the input node string are placed in a list. The default value is None, means get		
	from model.		
	input_size_list: The shapes of input node, all the input shape are placed in a list. If inputs		
	set, the input_size_list should be set also. defualt is None.		
	input_initial_val: Set the initial value of the model input, the format is ndarray list.The		
	default value is None.		
	Mainly used to fix some input as constant, For the input that does not need to be fix as a		
	constant, it can be set to None, such as [None, np.array([1])].		
	outputs: The output node (operand name) of model, output with multiple nodes is		
	supported now. All the output nodes are placed in a list. The default value is None, means		
	get from model.		
Return	0: Import successfully.		
Value	-1: Import failed.		

The sample code is as follows:

Load the arcface onnx model in the current path
ret = rknn.load_onnx(model = './arcface.onnx')



2.3.5 Loading DarkNet model

API	load_darknet
Description	Load DarkNet model.
Parameter	model: The path of DarkNet model structure file (suffixed with ".cfg").
	weight: The path of weight file (suffixed with ".weight").
Return	0: Import successfully.
Value	-1: Import failed.

The sample code is as follows:

```
# Load the yolov3-tiny DarkNet model in the current path ret = rknn.load_darknet(model = './yolov3-tiny.cfg', weight= './yolov3.weights')
```

2.3.6 Loading PyTorch model

API	load_pytorch
Description	Load PyTorch model.
	Support the Quantization Aware Training (QAT) model, but need update torch version to
	'1.9.0' or higher.
Parameter	model: The path of PyTorch model structure file (suffixed with ".pt"), and need a model in
	the torchscript format.
	input_size_list: The shapes of input node, all the input shape are placed in a list.
Return	0: Import successfully.
Value	-1: Import failed.

The sample code is as follows:



2.4 Building RKNN model

API	build
Description	Build corresponding RKNN model according to imported model.
Parameter	do_quantization: Whether to quantize the model. The default value is True.
	dataset: A input dataset for rectifying quantization parameters. Currently supports text file
	format, the user can place the path of picture(jpg or png) or npy file which is used for
	rectification. A file path for each line. Such as:
	a.jpg
	b.jpg
	or
	a.npy
	b.npy
	If there are multiple inputs, the corresponding files are divided by space. Such as:
	a.jpg a2.jpg
	b.jpg b2.jpg
	or
	a.npy a2.npy
	b.npy b2.npy
	Note: It is generally recommended to select the quantization image which is consistent
	with the prediction scene.
	rknn_batch_size: Use to adjust batch size of input. default is None.
	If greater than 1, NPU can inference multiple frames of input image or input data in one
	inference. For example, original input of MobileNet is [1, 224, 224, 3], output shape is [1,
	1001]. When rknn_batch_size is set to 4, the input shape of MobileNet becomes [4, 224,
	224, 3], output shape becomes [4, 1001].
	Note:



	1. The adjustment of rknn_batch_size does not improve the performance of the
	1. The adjustment of Tkim_batch_size does not improve the performance of the
	general model on the NPU, but it will significantly increase memory
	consumption and increase the delay of single frame.
	2. The adjustment of rknn_batch_size can reduce the consumption of the
	ultra-small model on the CPU and improve the average frame rate of the
	ultra-small model. (Applicable to the model is too small, CPU overhead is
	greater than the NPU overhead)
	3. The value of rknn_batch_size is recommended to be less than 32, to avoid the
	memory usage is too large and the reasoning fails.
	4. After the rknn_batch_size is modified, the shape of input and output will be
	modified. So the inputs of inference should be set to correct size. It's also needed
	to process the returned outputs on post processing.
Return	0: Build successfully.
value	-1: Build failed.

Build and quantize RKNN model ret = rknn.build(do_quantization=True, dataset='./dataset.txt')

2.5 Export RKNN model

The RKNN model built by 'build' interface can be saved as a file, it can used to model deployment.

API	export_rknn
Description	Save RKNN model in the specified file (suffixed with ".rknn").
Parameter	export_path: The path of generated RKNN model file.
	cpp_gen_cfg: Whether generate C++ deployment example The default value is False.
	Generated files - At the same folder path as RKNN model, the generated files include a
	folder named "rknn_deploy_demo" and an instruction document.



	Supported functions:
	- Timing for each CAPI interface during model inference verification
	- Cosine accuracy verification for inference results
	- Support for regular API interfaces
	- Support for image/npy inputs.
	NOTE: Not support on RV1103/RV1106.
Return	0: Export successfully.
Value	-1: Export failed.

save the built RKNN model as a mobilenet_v1.rknn file in the current path ret = rknn.export_rknn(export_path = './mobilenet_v1.rknn')

2.6 Loading RKNN model

API	load_rknn
Description	Load RKNN model.
	After loading the RKNN model, there is no need to perform the steps of model
	configuration, loading model and building RKNN model. And the loaded model is limited
	to connecting to the NPU hardware for inference or performance data acquisition. It can
	not be used for simulator or accuracy analysis.
Parameter	path: The path of RKNN model file.
Return	0: Load successfully.
Value	-1: Load failed.

The sample code is as follows:

Load the mobilenet_v1 RKNN model in the current path ret = rknn.load_rknn(path='./mobilenet_v1.rknn')



2.7 Initialize the runtime environment

Before inference or performance evaluation, the runtime environment must be initialized. This interface determines the type of runtime (hardware platform or software simulator).

API	init_runtime
Description	Initialize the runtime environment.
Parameter	target: Target hardware platform, now supports "rk3566", "rk3568", "rk3588", "rv1103",
	"rv1106" and "rk3562". The default value is "None", means model runs on simulator.
	Note: When target is set to None, the build or hybrid_quantization interface needs to be
	called first.
	device_id: Device identity number, if multiple devices are connected to PC, this parameter
	needs to be specified which can be obtained by calling "list_devices" interface. The default
	value is None.
	perf_debug: Debug mode option for performance evaluation. In debug mode, the running
	time of each layer can be obtained, otherwise, only the total running time of model can be
	given. The default value is False.
	eval_mem: Whether enter memory evaluation mode. If set True, the eval_memory
	interface can be called later to fetch memory usage of model running. The default value is
	False.
	async_mode: Whether to use asynchronous mode. The default value is False.
	When calling the inference interface, it involves setting the input picture, model running,
	and fetching the inference result. If the asynchronous mode is enabled, setting the input of
	the current frame will be performed simultaneously with the inference of the previous
	frame, so in addition to the first frame, each subsequent frame can hide the setting input
	time, thereby improving performance. In asynchronous mode, the inference result returned
	each time is the previous frame. (Not Supported yet)



core mask: Sets the NPU cores at runtime. The supported platform is RK3588, and the supported configurations are as follows: RKNN.NPU CORE AUTO: Indicates the automatic scheduling model, which automatically runs on the currently idle NPU core. RKNN.NPU CORE 0: Indicates running on the NPU0 core. RKNN.NPU CORE 1: Indicates running on the NPU1 core. RKNN.NPU_CORE_2: Indicates running on the NPU2 core. RKNN.NPU CORE 0 1: Indicates running on NPU0 and NPU1 cores at the same time. RKNN.NPU CORE 0 1 2: Indicates running on NPU0, NPU1, NPU2 cores at the same time. The default value is "RKNN.NPU CORE AUTO". 0: Initialize the runtime environment successfully. Return Value -1: Initialize the runtime environment failed.

The sample code is as follows:

Initialize the runtime environment ret = rknn.init runtime(target='rk3566')

2.8 Inference with RKNN model

This interface kicks off the RKNN model inference and get the result of inference.

API	inference
Description	Use the model to perform inference with specified input and get the inference result.
	Detailed scenarios are as follows:
	1. If RKNN-Toolkit2 is running on PC and the target is set to Rockchip NPU when
	initializing the runtime environment, the inference of model is performed on the specified
	hardware platform.
	2. If RKNN-Toolkit2 is running on PC and the target is not set when initializing the



	runtime environment, the inference of model is performed on the simulator.
Parameter	inputs: Inputs list to be inferred, The object type is ndarray.
	data_format: The layout list of input data. "nchw" or "nhwc", only valid for 4-dims
	input. The default value is None, means all inputs layout is "nhwc".
	inputs_pass_through: The pass_through flag. The default value is None, means all input
	is not pass through.
	In non-pass_through mode, the tool will reduce the mean, divide the variance, etc. before
	the input is passed to the NPU driver; in pass_through mode, these operations will not be
	performed.
	The value of this parameter is an list. For example, to pass input0 and not input1, the value
	of this parameter is [1, 0].
Return	results: The result of inference, the object type is ndarray list.
Value	

For classification model, such as mobilenet_v1, the code is as follows (refer to example/tfilte/mobilenet_v1 for the complete code):

```
# Preform inference for a picture with a model and get a top-5 result outputs = rknn.inference(inputs=[img]) show_outputs(outputs)
```

The result of top-5 is as follows:

```
----TOP 5----
[ 156] score:0.928223 class:"Shih-Tzu"
[ 155] score:0.063171 class:"Pekinese, Pekingese, Peke"
[ 205] score:0.004299 class:"Lhasa, Lhasa apso"
[ 284] score:0.003096 class:"Persian cat"
[ 285] score:0.000171 class:"Siamese cat, Siamese"
```



2.9 Evaluate model performance

API	eval_perf
Description	Evaluate model performance.
	Model must run on RK3566 / RK3568 / RK3588 / RV1103 / RV1106 / RK3562 which
	connected to PC.If setting perf_debug to False when initializing runtime environment via
	the interface of "init_runtime", the performance information is obtained from hardware,
	which only contains the total running time of model. If the perf_debug is set to True, the
	running time of each layer will also be captured in detail.
	is_print: Whether to print performance information. The default value is True.
Return	perf_result: Performance information (strings).
Value	

The sample code is as follows:

```
# Evaluate model performance
perf_detail = rknn.eval_perf()
```

2.10 Evaluating memory usage

API	eval_memory
Description	Fetch memory usage when model is running on hardware platform. Model must run on RK3566 / RK3568 / RK3588 / RV1103 / RV1106 / RK3562 which connected to PC.
Parameter	is_print: Whether to print memory evaluation results in the canonical format. The default value is True.
Return	memory_detail: Detail information of memory usage. Data format is dictionary.
Value	Data shows as below: { 'weight_memory': 3698688, 'internal_memory': 1756160.



```
'other_memory': 484352,
    'total_memory': 5939200,
}

The 'weight_memory' represents the memory footprint of the weights in the model.

The 'internal_memory' represents the memory usage of the internal tensor in the model.

The 'other_memory' represents the memory usage of other tensor in the model.

The 'total_memory' represents the memory footprint of the model, that is, the sum of the weight, internal tensor and other memory.
```

```
# eval memory usage
memory_detail = rknn.eval_memory()
```

For examples/caffe/mobilenet_v2 in examples directory, the memory usage when model running on RK3588 is printed as follows:

Memory Profile Info Dump

NPU model memory detail(bytes):

Weight Memory: 3.53 MiB

Internal Tensor Memory: 1.67 MiB

Other Memory: 473.00 KiB Total Memory: 5.66 MiB

INFO: When evaluating memory usage, we need consider the size of model, current model size is: 4.09 MiB

2.11 Get SDK version

API	get_sdk_version
Description	Get API version and driver version of referenced SDK.
	Note: Before we use this interface, we must load model and initialize runtime first. And
	this API can only used on RK3566 / RK3568 / RK3588 / RV1103 / RV1106 / RK3562.



Parameter	None.
Return	sdk_version: API and driver version. Data type is string.
Value	

```
# Get SDK version

sdk_version = rknn.get_sdk_version()

print(sdk_version)
```

The SDK version looks like below:

RKNN VERSION:

API: 1.5.2 (8babfea build@2023-08-25T02:31:12)

DRV: rknn_server: 1.5.2 (8babfea build@2023-08-25T10:30:12)
DRV: rknnrt: 1.5.3b13 (42cbca6f5@2023-10-27T10:13:21)

2.12 Hybrid Quantization

2.12.1 hybrid_quantization_step1

When using the hybrid quantization function, the main interface called in the first phase is hybrid_quantization_step1, which is used to generate the temporary model file ({model_name}.model), the data file ({model_name}.data), and the quantization configuration file ({model_name}.quantization. cfg). Interface details are as follows:

API	hybrid_quantization_step1
Description	Corresponding temporary model files, data files, and quantization profiles are generated
	according to the loaded original model.
Parameter	dataset: See Building RKNN model.
	rknn_batch_size: See Building RKNN model.
	proposal: Generate hybrid quantization config suggestions. The default value is False.
	<pre>proposal_dataset_size: The size of dataset used for proposal. The default value is 1.</pre>



	Because the proposal function is time-consuming, so the default size is 1.
	custom_hybrid: Select the hybrid quantization subgraph according to multiple sets of
	input names and output names specified by the user. The format is [[input0_name,
	output0_name], [input1_name, output1_name],]. The default value is None.
	Note: Input names and output names should be chosen based on the temporary model
	file({model_name}.model).
Return	0: success.
Value	-1: failure.

Call hybrid_quantization_step1 to generate quantization config ret = rknn.hybrid_quantization_step1(dataset='./dataset.txt')

2.12.2 hybrid_quantization_step2

When using the hybrid quantization function, the primary interface for generating a hybrid quantized RKNN model phase call is hybrid_quantization_step2. The interface details are as follows:

API	hybrid_quantization_step2
Description	The temporary model file, the data file, the quantization profile, and the correction data set
	are received as inputs, and the hybrid quantized RKNN model is generated.
Parameter	model_input: The temporary model file ({model_name}.model) path generated in the
	hybrid_quantization_step1.
	data_input: The model data file ({model_name}.data) path generated in the
	hybrid_quantization_step1.
	model_quantization_cfg: Path to the modified model quantization configuration file
	({model_name}.quantization.cfg) generated by hybrid_quantization_step1.
Return	0: success.
Value	-1: failure.



2.13 Quantitative accuracy analysis

The function of this interface is inference with quantized model and generate outputs of each layers for quantitative accuracy analysis.

API	accuracy_analysis
Description	Inference with quantized model and generate snapshot, that is dump tensor data of each
	layers. It will dump a snapshot of both data types include fp32 & quant for calculate
	quantitative error.
	Note:
	1. this interface can only be called after build or hybrid_quantization_step2.
	2. If target is None and the original model is quantized model (QAT model), the
	call will fail.
	3. The quantization method used by this interface is consistent with the setting in
	config.
Parameter	inputs: the path list of image (jpg/png/bmp/npy).
	output_dir: output directory, all snapshot data will stored here. The default value is
	'./snapshot'.
	If the target is not set, the following content will be output under 'output_dir':
	• Directory simulator: Save the results of each layer on simulator when the entire
	quantitative model is fully run (The output has been converted to float32).
	Directory golden: Save the results of each layer on simulator when the entire



floating-point model is completely run down.

- error_analysis.txt: Record the cosine distance (entire_error and single_error) between each layer result on simulator and the floating-point model on simulator during the complete calculation of the quantized model. The different of entire_error/single_error is the input of each layer is come from the quantization model or floating-point model. See the error_analysis.txt file for more details.
- If the target is set, more content will output under 'output_dir':
- Directory runtime: Save the results of each layer when the entire quantitative model is fully run in NPU (The output has been converted to float32).
- error_analysis.txt: Record the cosine distance (entire_error) between each layer result on simulator and each layer on NPU during the complete calculation of the quantized model additionally. See the error analysis.txt file for more details.

target: Target hardware platform, now supports "rk3566", "rk3568", "rk3588", "rv1103", "rv1106" and "rk3562". The default value is "None".

If target is set, the output of each layer of NPU will be obtained, and analyze it's accuracy.

device_id: Device identity number, if multiple devices are connected to PC, this parameter needs to be specified which can be obtained by calling "list_devices" interface. The default value is "None".

Return

0: success.

Value

-1: failure.

The sample code is as follows:

Accuracy analysis
ret = rknn.accuracy_analysis(inputs=['./dog_224x224.jpg'])



2.14 List Devices

API	list_devices
Description	List connected RK3566 / RK3568 / RK3588 / RV1103 / RV1106 / RK3562.
	Note:
	There are currently two device connection modes: ADB and NTB. Make sure their modes are
	the same when connecting multiple devices.
Parameter	None.
Return	Return adb_devices list and ntb_devices list. If there are no devices connected to PC, it will
Value	return two empty list.

The sample code is as follows:

rknn.list_devices()

The devices list looks like below:

2.15 Export encrypted RKNN model

API	export_encrypted_rknn_model
Description	The common RKNN model is encrypted according to the encryption level specified by the
	user.
Parameter	input_model: The path of the RKNN model to be encrypted.
	output_model: Save path of encrypted model. The default value is None, means the
	{original_model_name}.crypt.rknn will be the save path of encrypted model.
	crypt_level: Crypt level, currently, support level 1, 2 or 3. The default value is 1.
	The higher the level, the higher the security and the more time-consuming decryption; on



	the contrary, the lower the security, the faster the decryption.
Return	0: Success.
Value	-1: Failure.

ret = rknn.export_encrypted_rknn_model('test.rknn')

2.16 Register custom operator

API	reg_custom_op
Description	Register custom operator, only supported for ONNX model.
Parameter	custom_op: Custom operator class, currently supports 2 types of classes:
	1. Non-ONNX standard OP: When the user needs to customize a new OP that does not
	exist in the ONNX OP specification, the Non-ONNX standard OP can be used. The
	'op_type' of this operator must start with the "cst", and the 'shape_infer' and 'compute'
	functions of the operator class also need to be implemented by the user.
	2. Replace ONNX OP: When the user only needs to replace the runtime implementation of
	ONNX, the ONNX OP can be used. The operator only needs to meet the ONNX
	specification, and there is no need to implement the 'shape_infer' and 'compute' functions
	of the operator class.
	Note: The custom_op operator class is only used for model conversion and generation of
	RKNN models with custom operators. When deploying on the device side, you also need
	to refer to Chapter 5.5 of the "RKNN User Guide".
Return	0: Success.
Value	-1: Failure.

The sample code is as follows:



```
# Non-ONNX standard OP class
import numpy as np
from rknn.api.custom_op import get_node_attr
class cstSoftmax:
    op_type = 'cstSoftmax'
    def shape_infer(self, node, in_shapes, in_dtypes):
         out_shapes = in_shapes.copy()
         out_dtypes = in_dtypes.copy()
         return out_shapes, out_dtypes
    def compute(self, node, inputs):
         x = inputs[0]
         axis = get_node_attr(node, 'axis')
         x_max = np.max(x, axis=axis, keepdims=True)
         tmp = np.exp(x - x max)
         s = np.sum(tmp, axis=axis, keepdims=True)
         outputs = [tmp / s]
         return outputs
ret = rknn.reg_custom_op(cstSoftmax)
```

Or: