[SQL Worksheet]*

```
CREATE TABLE student1 (
    id NUMBER,
    name VARCHAR2(30)
);

CREATE TABLE student2 (
    id NUMBER,
    name VARCHAR2(30)
);
INSERT INTO student1 VALUES (1, 'Sai');
INSERT INTO student1 VALUES (2, 'Rishi');
INSERT INTO student1 VALUES (3, 'Akshaya');

INSERT INTO student2 VALUES (3, 'Akshaya');
INSERT INTO student2 VALUES (4, 'Swathi');
INSERT INTO student2 VALUES (5, 'Ravi');

COMMIT;
SELECT * FROM student1
UNION
SELECT * FROM student2;
```

Query result | Script output | DBMS output | Explain Plan | SQL history

Download | Execution time: 0.031 seconds

	ID	NAME
1	1	Sai
2	2	Rishi
3	3	Akshaya
4	4	Swathi
5	5	Ravi

[SQL Worksheet]*

```sql
CREATE TABLE student1 (
    id NUMBER,
    name VARCHAR2(30)
);

CREATE TABLE student2 (
    id NUMBER,
    name VARCHAR2(30)
);

INSERT INTO student1 VALUES (1, 'Sai');
INSERT INTO student1 VALUES (2, 'Reena');
INSERT INTO student1 VALUES (3, 'Arjun');

INSERT INTO student2 VALUES (3, 'Arjun');
INSERT INTO student2 VALUES (4, 'Neha');
INSERT INTO student2 VALUES (5, 'Ravi');

COMMIT;

SELECT * FROM student1
INTERSECT
SELECT * FROM student2;
```

Query result | Script output | DBMS output | Explain Plan | SQL history

Download | Execution time: 0.011 seconds

	ID	NAME
1	3	Arjun

[SQL Worksheet]*

```sql
CREATE TABLE student1 (
    id NUMBER,
    name VARCHAR2(30)
);

CREATE TABLE student2 (
    id NUMBER,
    name VARCHAR2(30)
);

INSERT INTO student1 VALUES (1, 'Sai');
INSERT INTO student1 VALUES (2, 'Reena');
INSERT INTO student1 VALUES (3, 'Arjun');

INSERT INTO student2 VALUES (3, 'Arjun');
INSERT INTO student2 VALUES (4, 'Neha');
INSERT INTO student2 VALUES (5, 'Ravi');

COMMIT;

SELECT * FROM student1
MINUS
SELECT * FROM student2;
```

Query result | Script output | DBMS output | Explain Plan | SQL history

Download | Execution time: 0.009 seconds

	ID	NAME
1	1	Sai
2	2	Reena

[SQL Worksheet]*

```
CREATE TABLE student1 (
    id NUMBER,
    name VARCHAR2(30)
);

CREATE TABLE student2 (
    id NUMBER,
    name VARCHAR2(30)
);

INSERT INTO student1 VALUES (1, 'Sai');
INSERT INTO student1 VALUES (2, 'Reena');
INSERT INTO student1 VALUES (3, 'Arjun');

INSERT INTO student2 VALUES (3, 'Arjun');
INSERT INTO student2 VALUES (4, 'Neha');
INSERT INTO student2 VALUES (5, 'Ravi');

COMMIT;
CREATE VIEW student_view AS
SELECT id, name
FROM student1;
SELECT * FROM student_view;

```

Query result | Script output | DBMS output | Explain Plan | SQL history

Download | Execution time: 0.016 seconds

	ID	NAME
1	1	Sai
2	2	Reena
3	3	Arjun

[SQL Worksheet]*

```
1   SET SERVEROUTPUT ON;
2
3   DECLARE
4       A NUMBER(2) := 3;
5       B NUMBER(2) := 10;
6       C NUMBER;
7   BEGIN
8       C := A + B;
9       DBMS_OUTPUT.PUT_LINE('C = ' || C);
10  END;
11  /
```

Query result | Script output | DBMS output | Explain Plan | SQL history

```
SQL> DECLARE
         A NUMBER(2) := 3;
         B NUMBER(2) := 10;
         C NUMBER;...
Show more...


C = 13


PL/SQL procedure successfully completed.

Elapsed: 00:00:00.006
```

[SQL Worksheet]*

```
1   SET SERVEROUTPUT ON;
2
3   DECLARE
4       Emp_Name VARCHAR2(20);
5
6   BEGIN
7       Emp_Name := 'Kalyani';
8       DBMS_OUTPUT.PUT_LINE('Name: ' || Emp_Name);
9
10  END;
11  /
```

```
SQL> DECLARE
         Emp_Name VARCHAR2(20);

     BEGIN...
Show more...


Name: Kalyani


PL/SQL procedure successfully completed.

Elapsed: 00:00:00.005
```