

Submissions

Leaderboard

Discussions

Editorial

HackerRank

Prepare

Data Structures

Arrays

Left Rotation

Exit Full Screen View

Upload Code as File

Test against custom input

Run Code

Submit Code

A *left rotation* operation on a circular array shifts each of the array's elements 1 unit to the left. The elements that fall off the left end reappear at the right end. Given an integer d , rotate the array that many steps to the left and return the result.

Example

$d = 2$

$arr = [1, 2, 3, 4, 5]$

After 2 rotations, $arr' = [3, 4, 5, 1, 2]$.

Function Description

Complete the *rotateLeft* function with the following parameters:

- $int\ d$: the amount to rotate by
- $int\ arr[n]$: the array to rotate

Returns

- $int[n]$: the rotated array

Input Format

The first line contains two space-separated integers that denote n , the number of integers, and d , the number of left rotations to perform.

The second line contains n space-separated integers that describe $arr[]$.

Constraints

- $1 \leq n \leq 10^5$
- $1 \leq d \leq n$
- $1 \leq a[i] \leq 10^8$

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

1 5 4

2 1 2 3 4 5

Your Output (stdout)

1 5 1 2 3 4

Expected Output

1 5 1 2 3 4

Download

Download

Submissions

Leaderboard

Discussions

Editorial

HackerRank

PrepareData StructuresArraysArray Manipulation

Exit Full Screen View

Upload Code as File

Test against custom input

Run Code

Submit Code

Constraints

- $3 \leq n \leq 10^7$
- $1 \leq m \leq 2 * 10^5$
- $1 \leq a \leq b \leq n$
- $0 \leq k \leq 10^9$

Sample Input

STDIN	Function
5 3	arr[] size n = 5, queries[] size q = 3
1 2 100	queries = [[1, 2, 100], [2, 5, 100], [3, 4, 100]]
2 5 100	
3 4 100	

Sample Output

```
200
```

Explanation

After the first update the list is 100 100 0 0 0.

After the second update list is 100 200 100 100 100.

After the third update list is 100 200 200 200 100.

The maximum value is 200.

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Sample Test case 1

Sample Test case 2

Input (stdin)

1	5 3
2	1 2 100
3	2 5 100
4	3 4 100

Your Output (stdout)

1	200
---	-----

Expected Output

1	200
---	-----

Download

Download

~~~~~

## discussions

- $1 \leq A[i] \leq 10^4$ , where  $A[i]$  is the  $i^{th}$  integer in  $A$

|   |   |   |   |   |
|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 1 |
|---|---|---|---|---|

5:54 PM

There is a collection of input strings and a collection of query strings. For each query string, determine how many times it occurs in the list of input strings. Return an array of the results.

### Example

```
stringList = ['ab', 'ab', 'abc']
queries = ['ab', 'abc', 'bc']
```

There are 2 instances of 'ab', 1 of 'abc', and 0 of 'bc'. For each query, add an element to the return array: **results** = [2, 1, 0].

### Function Description

Complete the function *matchingStrings* with the following parameters:

- *string stringList[n]*: an array of strings to search
- *string queries[q]*: an array of query strings

## Returns

- $int[q]$ : the results of each query

### Input Format

The first line contains an integer  $n$ , the size of `stringList[]`.

Each of the next  $n$  lines contains a string *stringList*[*i*].

The next line contains  $q$ , the size of  $queries[]$ .

Each of the next  $q$  lines contains a string  $queries[i]$ .

### Constraints

$$1 \leq n \leq 1000$$

 Upload Code as File

|  |                           |
|--|---------------------------|
|  | Test against custom input |
|--|---------------------------|

### Random Code

www.elsevier.com/locate/jmb

**Congratulations!**

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

✔ Sample Test case 0

✔ Sample Test case 1

✔ Sample Test case 2

|   |      |
|---|------|
| 1 | 4    |
| 2 | aba  |
| 3 | baba |
| 4 | aba  |
| 5 | xzxb |
| 6 | 3    |
| 7 | aba  |
| 8 | xzxb |
| 9 | ab   |

Your Output (stdout)

|   |   |
|---|---|
| 1 | 2 |
| 2 | 1 |
| 3 | 0 |

2D Array - DS | HackerRank

hackerrank.com/challenges/2d-array/problem?isFullScreen=true

All Bookmarks

HackerRank

Prepare > Data Structures > Arrays > 2D Array - DS

Exit Full Screen View

Problem

Submissions

Leaderboard

Discussions

1 1 1 0 0 0  
0 1 0 0 0 0  
1 1 1 0 0 0  
0 0 2 4 4 0  
0 0 0 2 0 0  
0 0 1 2 4 0

Sample Output

19

Explanation

arr contains the following hourglasses:

1 1 1 1 0 1 0 0 0 0 0  
1 1 1 1 0 1 0 0 0 0 0  
1 1 1 1 0 1 0 0 0 0 0  
0 1 0 1 0 0 0 0 0 0 0  
0 0 2 0 2 4 2 4 4 4 0  
1 1 1 1 1 0 1 0 0 0 0 0  
0 0 2 0 2 4 2 4 4 4 0  
0 0 0 0 2 0 0 2 0 2 0 0  
0 0 2 0 2 4 2 4 4 4 0  
0 0 1 0 1 2 1 2 4 2 4 0

The hourglass with the maximum sum (19) is:

Congratulations

You solved this challenge. Would you like to challenge your friends?

Next Challenge

f

t

in

Test case 0

Test case 1

Test case 2

Test case 3

Test case 4

Test case 5

Test case 6

Success

Input (stdin)

1 1 1 1 0 0 0  
0 1 0 0 0 0  
1 1 1 0 0 0  
0 0 2 4 4 0  
0 0 0 2 0 0  
0 0 1 2 4 0

Expected Output

1 19

Download

Download

Sparse Arrays | HackerRank

hackerrank.com/challenges/sparse-arrays/problem?isFullScreen=true

All Bookmarks

HackerRank

Prepare > Data Structures > Arrays > Sparse Arrays

Exit Full Screen View

Submission

Leaderboard

Discussions

Editorial

the return array: `results = [2,1,0]`.

Function Description

Complete the function `matchingStrings` with the following parameters:

- `string stringList[n]`: an array of strings to search
- `string queries[q]`: an array of query strings

Returns

- `int[q]`: the results of each query

Input Format

The first line contains an integer `n`, the size of `stringList[]`.

Each of the next `n` lines contains a string `stringList[i]`.

The next line contains `q`, the size of `queries[]`.

Each of the next `q` lines contains a string `queries[i]`.

Constraints

Congratulations

You solved this challenge. Would you like to challenge your friends?

f

t

in

Next Challenge

Test case 0

Test case 1

Test case 2

Test case 3

Test case 4

Test case 5

Test case 6

Compiler Message

Success

Hidden Test Case

Unlock this testcase for 5 hacks.

Unlock