

SRI CHANDRASEKHARENDRA SARASWATHI VISWA MAHAVIDYALAYA
(UNIVERSITY ESTABLISHED under section 3 of UGC Act 1956)

ENATHUR, KANCHIPURAM – 631 561



DATA STRUCTURES AND ALGORITHMS
LABORATORY RECORD

Name : Akshay V

REG No : 112534118

Class : I YEAR BCA

Subject : UCAF252T40 – DSA Lab

SRI CHANDRASEKHARENDRA SARASWATHI
VISWA MAHAVIDYALAYA
(University Established under section 3 of UGC Act 1956)



BONAFIDE CERTIFICATE

This is to Certify that this is the bonafide record of work done

by

Mr. Akshay V with Reg. No 112534118 of I Year BCA in

the _____ Data Structures and Algorithms Lab

during the year 2026.

Staff-in-charge

Head of the Department

Submitted for the Practical Examination held on _____

Internal Examiner

External Examiner.

INDEX

S.No.	Date	Title	Page No.	Signature
1	06 Feb 2026	Program to Search an Element in the Array.	01	
2	13 Feb 2026	Program to Search an Element In the Array using Binary Search.	05	
3	20 Feb 2026	Program to Sort an Array using Bubble Sort.	10	
4	27 Feb 2026	Program to Sort an Array using Selection Sort.	13	
5	06 Feb 2026	Program to Sort an Array using Insertion Sort.	17	
6	13 Mar 2026	Program to Implement a Stack Using Arrays.	20	
7	20 Mar 2026	Program to Implement a Queue Using Arrays	26	

8	27 Mar 2026	Program to Implement a Stack using Linked List	33	
9	03 Apr 2026	Program to Implement a Queue using Linked List	38	

1	Program to Search an Element In the Array	06 Feb 2026
---	---	-------------

AIM:

Program to Search an Element in the Array using Linear Search.

ALGORITHM:

Step 1: Start.

Step 2: Declare the counter variable (i), array size (n), element to search found.

Step 3: Read = n, i = 0

Step 4: Read arr[i]

Step 5: increment i (i++)

Step 6: if (i < n) goto step 4.

Step 7: Read element to search (search).

Step 8: i = 0

Step 9: if arr[i] != Search goto step 12.

Step 10: found = 1.

Step 11: print "Element found at index = i" go to step 15.


Step 12: i++

Step 13: if i < n go to step 9.

Step 14: if found not equal to 1, print "Element not found".

Step 15: stop.

FLOW CHART:



SOURCE CODE:

<https://github.com/112534080-stack/DSALab/blob/main/ArrayStack.c>

```
#include <stdio.h>
int main()
{
    int n, i, search, found = 0;
    // Input number of elements in the array
    printf("Enter number of elements in the array: ");
    scanf("%d", &n);
    int arr[n];
    // Input array elements
    printf("Enter elements of the array: \n");
    for(i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }
    // Input the element to search
    printf("Enter element to search: ");
    scanf("%d", &search);
    // Linear search
    for(i = 0; i < n; i++)
    {
        if(arr[i] == search)
        {
            found = 1;
            printf("Element %d found at index %d.\n", search, i);
            break;
        }
    }
    // If element is not found
    if(!found)
    {
        printf("Element %d not found in the array.\n", search);
    }
    return 0;
}
```


.....

SAMPLEOUTPUT:

Enter number of elements in the array: 5

Enter elements of the array:

6

3

8

5

2

Enter element to search: 8

Element 8 found at index 2.

NEGATIVE I/O

Enter number of elements in the array: 5

Enter elements of the array:

6

3

8

5

2

Enter element to search: 10

Element 10 not found in the array

2	Program to Search an Element In the Array using Binary Search	13 Feb 2026
---	--	-------------

AIM:

Program to Search an Element in the Array using Binary Search.


ALGORITHM:

Step 1: start
 Step 2: declare no of elements (n) elements to search (key)
 Step 3: initialization array with n(arr[n])
 Step 4: i=0
 Step 5: get arr[i]
 Step 6: i++
 Step 7: if i<n goto step 5,else continue
 Step 8: read element to search(key)
 Step 9: result = binary search(arr,n,key)
 Step 10: if (result!= 1)
 Step 11: print element found at position(result)else
 Print element not found
 Step 12: stop


ALGORITHM FOR BINARY SEARCH:

Step 1: int low= 0, high= n- 1
Step 2: if low(<= high)
Step 3: mid= (low+ high)/2
Step 4: if (arr[mid]== key)
 Return mid
Step 5: else if (arr[mid]< key)
 Low= mid+ 1
 Else
 High= mid- 1
Step 6: goto step 2
Step 7: return - 1

FLOW CHART:



Binarysearch(int arr[], int n, int key)



SOURCE CODE:

<https://github.com/112534080-stack/DSALab/blob/main/Binarysearch.c>

```
#include<stdio.h>

int binarysearch(int arr[],int n, int key)
{
    int low= 0,high= n- 1,mid;
    while(low<= high)
    {
        mid=(low+high)/2;
        if (arr[mid]== key)
            return mid;
        //element found
        else if(arr[mid]< key)
            low= mid+ 1;
        //search right half
        else
            high= mid- 1;
        //search left half
    }
    return -1;
    //element not found
}

int main()
{
    int n,key,result;
```

```

printf("enter number of element:");
scanf("% d",&n);
int arr[n];
printf("enter % d sorted element:\n",n);
int i;
for(i=0;i<n;i++){
scanf("% d",&arr[i]);
}
printf("enter element to search:");
scanf("% d",&key);
result = binarysearch(arr, n, key);
if(result!= - 1)
printf("element found at index % d \n",result);
else
printf("element not found \n");
return 0;
}

```

SAMPLE OUTPUT:

```

Enter number of elements: 5
Enter 5 sorted elements:
11
12
13
14
15
Enter element to search: 14
Element found at index 3

```


3	Program to Sort an Array using Bubble Sort	20 Feb 2026
---	--	-------------


AIM:

Program to Sort an Array using Bubble Sort.

ALGORITHM:

Step 1: Start the program
 Step 2: Read the number of element n
 Step 3: Declare an array arr[n]
 Step 4: Input n elements into the array
 Step 5: for i=0 to n-2
 Step 6: for j=0 to n-i-2
 Step 7: if arr[j]>arr[j+1]
 Swap arr[j] and arr[j+1]
 Temp=arr[j]
 arr[j]=arr[j+1]
 arr[j+1]=temp
 Step 8: Print the sorted array
 Step 9: Stop

FLOW CHART:



SOURCE CODE :

<https://github.com/112534080-stack/DSALab/blob/main/BubbleSort.c>

```
#include<stdio.h>
int main()
{
int n,temp;
int i,j;
printf("enter number of element:");
scanf("%d",&n);
int arr[n];
printf("enter %d elements:\n",n);
for(i=0;i<n;i++)
scanf("%d",&arr[i]);
//bubble sort logic
for(i=0;i<n;i++)
{
for(j=0;j<n;j++)
{
if(arr[j]>arr[j+1])
{
temp=arr[j];
arr[j]=arr[j+1];
arr[j+1]=temp;
}
}
}
printf("sorted array:\n");
for(i=0;i<n;i++)
printf("%d",arr[i]);
return 0;
}
```

SAMPLE OUTPUT:

Enter number of element:5

Enter 5 element:

25

32

95

65

23

Sorted array

23 25 32 65 95

4	Program to Sort an Array using Selection Sort	27 Feb 2026
---	---	-------------

AIM:

Program to Sort an Array using Selection Sort.

ALGORITHM:

Step 1: start

Step 2: declare element count (n),

Step 3: get n

Step 4: declare arr [n]

Step 5: get arr [i]

Step 6: i++

Step 7: repeat from step 5 till i < n

Step 8: l = 0

Step 9 : minindex = i

Step 10: j = i+1

Step 11: if arr [i] < arr

Step 12: temp = arr [i]

arr[i] = arr[minindex]

arr[minindex] = temp

Step 13: j++

Step 14: repeat from step 11 till j < n

Step 15: $i++$

Step 16: repeat from step 9 till $i < n-1$

Step 17: stop $l = 0$

Step 18: print arr [i]


Step 19: $i++$

Step 20: repeat from step 18 till $i < n$

Step 21: stop

FLOW CHART:





SOURCE CODE:

<https://github.com/112534080-stack/DSALab/blob/main/SelectionSort.c>

```
#include <stdio.h>

int main()
{
    int n, temp, minindex;
    printf("enter number of elements: ");
    scanf("%d", &n);
    int arr[n];
    printf("enter %d elements:\n", n);
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    // selection sort logic
    for (int i = 0; i < n - 1; i++)
    {
        minindex = i;
        for (int j = i + 1; j < n; j++)
        {
            if (arr[j] < arr[minindex])
                minindex = j;
        }
        // swap
        temp = arr[i];
        arr[i] = arr[minindex];
        arr[minindex] = temp;
    }
    printf("sorted array:\n");
    for (int i = 0; i < n; i++)
```

```
    printf("%d ", arr[i]);  
    return 0;  
}
```

OUTPUT:

Enter number of elements: 6

Enter 6 elements:

12

14

11

22

20

19

Sorted array:

11 12 14 19 20 22

5	Program to Sort an Array using Insertion Sort.	06 Feb 2026
---	--	-------------

AIM:

Program to Sort an Array using Insertion Sort.

ALGORITHM:

Step 1: Start

Step 2: Read the number of elements (n)

Step 3: Declare an array of size n, arr[n]

Step 4: Read array elements iteratively

for i = 0 to n-1 do:

- Prompt user: "Enter element i+1"
- Read arr[i] from user input

Step 5: Sort the array using Insertion Sort

for i = 1 to n-1 do:

- key = arr[i]
- j = i - 1
- Compare and shift elements:
- while j >= 0 and arr[j] > key do:
 - move arr[j] one position right: arr[j + 1] = arr[j]
 - j = j - 1
 - insert the key at its correct position:
 - o arr[j + 1] = key
- repeat for the next element (i = i + 1)


Step 6: Display the sorted array

for i = 0 to n-1 do:

print arr[i]

Step 7: End

FLOW CHART:



SOURCE CODE:

[https://github.com/112534080-stack/DSALab/blob/main/Insertion% 20Sort.c](https://github.com/112534080-stack/DSALab/blob/main/Insertion%20Sort.c)

```
#include <stdio.h>
int main()
{
    int n, key, j;
    printf("enter number of elements: ");
    scanf("%d", &n);
    int arr[n];
    printf("enter %d elements:\n", n);
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);
    // insertion sort logic
    for (int i = 1; i < n; i++)
    {
        key = arr[i];
        j = i - 1;
        while (j >= 0 && arr[j] > key)
        {
            arr[j + 1] = arr[j];
            j--;
        }
        arr[j + 1] = key;
    }
    printf("sorted array:\n");
    for (int i = 0; i < n; i++)
        printf("%d ", arr[i]);
    return 0;
}
```

SAMPLE OUTPUT:

```
Enter number of elements: 6
Enter 6 elements:
12
14
11
22
```

20

19

Sorted array:

11 12 14 19 20 22

6	Program to Implement a Stack Using Arrays	13 March 2026
---	---	---------------

AIM:

Program to Implement a Stack Using Arrays.

ALGORITHM:

Step 1: Start – Begin program execution.
Step 2: Initialize Stack – Define a stack of size MAX (5).
Step 3: Initialize top – Set top = -1 to indicate the stack is empty.
Step 4: Display Main Menu – Show options: 1. Push 2. Pop 3. Display 4. Exit.
Step 5: Read User Choice – Read the choice from the user.
 If choice = 1, go to Push Operation Steps.
 If choice = 2, go to Pop Operation Steps.
 If choice = 3, go to Display Operation Steps.
 If choice = 4, go to Exit Operation Steps.
 Otherwise, print "Invalid choice" and return to Step 4 (Display Main Menu).

Push () Operation Steps (Choice = 1)

Step P1: Check Stack Overflow – If top == MAX – 1, print "Stack Overflow" and return to step 4 (Display MainMenu).
Step P2: Read Item – Read the element to push from the user.
Step P3: Increment top – top = top + 1.
Step P4: Assign Stack Element – stack[top] = item.
Step P5: Print Success Message – Print "Element pushed successfully" and return to Step 4 (Display Main Menu).

Pop() Operation Steps (Choice = 2)

Step O1: Check Stack Underflow – If top == -1, print "Stack Underflow" and return to Step 4 (Display Main Menu).
Step O2: Print Popped Element – Print stack[top].
Step O3: Decrement top – top = top – 1 and return to Step 4 (Display Main Menu).

Display() Operation Steps (Choice = 3)


Step D1: Check if Stack is Empty – If top == -1, print "Stack is empty" and return to Step 4 (Display Main Menu).
Step D2: Loop Through Stack – For i = top down to 0, print stack[i].
Step D3: Return to Main Menu – Go back to Step 4 (Display Main Menu).

Exit() Operation Steps (Choice = 4)


Step E1: Print Exit Message – Print "Exiting program".

Step E2: End – Program execution ends.


FLOWCHART:




1. PUSH()



2. POP()



3. DISPLAY()



SOURCE CODE:

<https://github.com/112534080-stack/DSALab/blob/main/ArrayStack.c>

```
#include <stdio.h>
#define max
int stack[max];
int top = -1;
// push operation
void push()
{
    int item;
    if (top == max - 1)
    {
        printf("stack overflow!\n");
        return;
    }
    printf("enter element to push: ");
    scanf("%d", &item);
    stack[++top] = item;
    printf("element pushed successfully.\n");
}
// pop operation
void pop()
{
    if (top == -1)
    {
        printf("stack underflow!\n");
        return;
    }
    printf("popped element: %d\n", stack[top--]);
}
// display stack elements
void display()
{
    if (top == -1)
    {
        printf("stack is empty.\n");
        return;
    }
    printf("stack elements:\n");
```

```

        for (int i = top; i >= 0; i--)
            printf("%d\n", stack[i]);
    }
    int main()
    {
        int choice;
        do
        {
            print("\n--- stack menu ---\n");
            printf("1. push\n2. pop\n3. display\n4. exit\n");
            printf("enter your choice: ");
            scanf("%d", &choice);
            switch (choice)
            {
                case 1:
                    push();
                    break;
                case 2:
                    pop();
                    break;
                case 3:
                    display();
                    break;
                case 4:
                    printf("exiting program.\n");
                    break;
                default:
                    printf("invalid choice!\n");
            }
        } while (choice != 4);

        return 0;
    }

```

SAMPLE OUTPUT:

```

--- Stack Menu ---
1. Push
2. Pop
3. Display

```

4. Exit
Enter your choice: 1
Enter element to push: 12
Element pushed successfully.

--- Stack Menu ---
1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 1
Enter element to push: 13
Element pushed successfully.

--- Stack Menu ---
1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 3
Stack elements:
13
12

--- Stack Menu ---
1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 2
Popped element: 13

--- Stack Menu ---
1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 3
Stack elements:
12

--- Stack Menu ---

1. Push
2. Pop
3. Display
4. Exit

Enter your choice:

4

Exiting program.

7	Program to Implement a Queue Using Arrays	20 March 2026
---	---	---------------

AIM:

Program to Implement a Queue Using Arrays

ALGORITHM:

Step 1: Start – Begin program execution.

Step 2: Initialize Queue – Define a queue of size MAX (5).

Step 3: Initialize front and rear – Set front = -1 and rear = -1 to indicate the queue is empty.

Step 4: Display Main Menu – Show options: 1. Enqueue 2. Dequeue 3. Display 4. Exit.

Step 5: Read User Choice – Read the choice from the user.

 If choice = 1, go to Enqueue Operation Steps.

 If choice = 2, go to Dequeue Operation Steps.

 If choice = 3, go to Display Operation Steps.

 If choice = 4, go to Exit Operation Steps.

 Otherwise, print “Invalid choice” and return to Step 4 (Display Main

Menu).

Enqueue() Operation Steps (Choice = 1)

Step E1: Check Queue Overflow – If rear == MAX – 1, print “Queue Overflow” and return to Step 4 (Display Main Menu).

Step E2: Read Item to Insert – Read the element to enqueue from the user.

Step E3: Check if Queue Empty – If front == -1, set front = 0.

Step E4: Increment rear – rear = rear + 1.

Step E5: Assign Queue Element – queue[rear] = item.

Step E6: Print Success Message – Print “Element inserted successfully” and return to Step 4 (Display Main Menu).

Dequeue() Operation Steps (Choice = 2)

Step D1: Check Queue Underflow – If front == -1 or front > rear, print “Queue Underflow” and return to Step 4 (Display Main Menu).

Step D2: Print Deleted Element – Print queue[front].

Step D3: Increment front – front = front + 1 and return to Step 4 (Display Main Menu).

Display() Operation Steps (Choice = 3)

Step DS1: Check if Queue is Empty – If front == -1 or front > rear, print “Queue is empty” and return to Step 4 (Display Main Menu).

Step DS2: Loop Through Queue – For i = front to rear, print queue[i].


Step DS3: Return to Main Menu – Go back to Step 4 (Display Main Menu).

Exit Operation Steps (Choice = 4)


Step X1: Print Exit Message – Print “Exiting program”.

Step X2: End – Program execution ends.


FLOWCHART:




1) enqueue()



2) dequeue()



3) display()



SOURCE CODE:

<https://github.com/112534080-stack/DSALab/blob/main/ArrayQueue.c>

```
#include <stdio.h>
#define max 5
int queue[max];
int front = -1, rear = -1;
// insert element (enqueue)
void enqueue()
{
    int item;
    if (rear == max - 1)
    {
        printf("queue overflow!\n");
        return;
    }
    printf("enter element to insert: ");
    scanf("%d", &item);
    if (front == -1)
        front = 0;
    queue[++rear] = item;
    printf("element inserted successfully.\n");
}
// delete element (dequeue)
void dequeue()
{
    if (front == -1 || front > rear)
    {
        printf("queue underflow!\n");
        return;
    }
    printf("deleted element: %d\n", queue[front++]);
}
// display queue elements
void display()
{
    if (front == -1 || front > rear)
    {
        printf("queue is empty.\n");
        return;
    }
}
```

```

    }
    printf("queue elements:\n");
    for (int i = front; i <= rear; i++)
        printf("%d ", queue[i]);
    printf("\n");
}
int main()
{
    int choice;
    do
    {
        printf("\n--- queue menu ---\n");
        printf("1. enqueue\n2. dequeue\n3. display\n4. exit\n");
        printf("enter your choice: ");
        scanf("%d", &choice);
        switch (choice)
        {
            case 1:
                enqueue();
                break;
            case 2:
                dequeue();
                break;
            case 3:
                display();
                break;
            case 4:
                printf("exiting program.\n");
                break;
            default:
                printf("invalid choice!\n");
        }
    } while (choice != 4);
    return 0;
}

```

SAMPLE OUTPUT:

```

--- Queue Menu ---
1. Enqueue

```

2. Dequeue

3. Display

4. Exit

Enter your choice: 1

Enter element to insert: 16

Element inserted successfully.

--- Queue Menu ---

1. Enqueue

2. Dequeue

3. Display

4. Exit

Enter your choice: 1

Enter element to insert: 23

Element inserted successfully.

--- Queue Menu ---

1. Enqueue

2. Dequeue

3. Display

4. Exit

Enter your choice: 1

Enter element to insert: 36

Element inserted successfully.

--- Queue Menu ---

1. Enqueue

2. Dequeue

3. Display

4. Exit

Enter your choice: 3

Queue elements:

16 23 36

--- Queue Menu ---

1. Enqueue

2. Dequeue

3. Display

4. Exit

Enter your choice: 3

Queue elements:

16 23 36

--- Queue Menu ---

1. Enqueue

2. Dequeue

3. Display

4. Exit

Enter your choice: 2

Deleted element: 16

--- Queue Menu ---

1. Enqueue

2. Dequeue

3. Display

4. Exit

Enter your choice: 3

Queue elements:

23 36

--- Queue Menu ---

1. Enqueue

2. Dequeue

3. Display

4. Exit

Enter your choice: 4

Exiting program.

8	Program to Implement a Stack using Linked List	27 Apr 2026
---	--	-------------

AIM:

Program to Implement a Stack using Linked List

ALGORITHM:

1. Initialization

- Define a structure node with two parts: data (integer) and next (pointer to the next node).
- Initialize a global pointer top to NULL.

2. Push Operation

1. Allocate memory for a newnode.

2. If memory allocation fails, print "Heap Overflow" and return.
3. Read the element to be pushed.
4. Set newnode->data = item.
5. Set newnode->next = top (Link the new node to the current top).
6. Update top = newnode (Move the top pointer to the new node).
3. Pop Operation
 1. Check if top == NULL. If yes, print "Stack Underflow" and return.
 2. Create a temporary pointer temp and set temp = top.
 3. Print the data of the element being popped (temp->data).
 4. Update top = top->next (Move the top pointer to the next node).
 5. free(temp) to release the memory.
4. Display Operation
 1. Check if top == NULL. If yes, print "Stack is empty" and return.
 2. Create a temporary pointer temp and set it to top.
 3. While temp is not NULL:
 - o Print temp->data.
 - o Move temp to the next node (temp = temp->next).
5. Main Menu Loop
 1. Repeat the following until the user chooses to exit (Choice 4):
 - o Display options: 1. Push, 2. Pop, 3. Display, 4. Exit.
 - o Read user choice.
 - o Execute the corresponding function based on choice.

SOURCE CODE:

<https://github.com/112534080-stack/DSALab/blob/main/StackLinkedList.c>

```
#include <stdio.h>
#include <stdlib.h>
// structure for stack node
struct node
{
    int data;
    struct node *next;
};
struct node *top = null;
// push operation
void push()
{
    int item;
    struct node *newnode;
    newnode = (struct node *)malloc(sizeof(struct node));
    if (newnode == null)
```

```

{
    printf("heap overflow!\n");
    return;
}
prints("enter element to push: ");
scanf("% d", &item);
newnode->data = item;
newnode->next = top;
top = newnode;
printf("element pushed successfully.\n");
}
// pop operation
void pop()
{
    struct node *temp;
    if (top == null)
    {
        printf("stack underflow!\n");
        return;
    }
    temp = top;
    printf("popped element: % d\n", temp->data);
    top = temp->next;
    free(temp);
}
// display stack
void display()
{
    struct node *temp;
    if (top == null)
    {
        printf("stack is empty.\n");
        return;
    }
    printf("stack elements:\n");
    temp = top;
    while (temp != null)
    {
        printf("% d\n", temp->data);
    }
}

```

```

        temp = temp->next;
    }
}
int main()
{
    int choice;
    do
    {
        printf("\n--- stack menu ---\n");
        printf("1. push\n2. pop\n3. display\n4. exit\n");
        printf("enter your choice: ");
        scanf("%d", &choice);
        switch (choice)
        {
            case 1:
                push();
                break;
            case 2:
                pop();
                break;
            case 3:
                display();
                break;
            case 4:
                printf("exiting program.\n");
                break;
            default:
                printf("invalid choice!\n");
        }
    } while (choice != 4);
    return 0;
}

```

SAMPLE OUTPUT:

```

--- Stack Menu ---
1. Push
2. Pop
3. Display

```

4. Exit
Enter your choice: 1
Enter element to push: 23
Element pushed successfully.

--- Stack Menu ---

1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 1
Enter element to push: 35
Element pushed successfully.

--- Stack Menu ---

1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 1
Enter element to push: 36
Element pushed successfully.

--- Stack Menu ---

1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 3
Stack elements:
36
35
23

--- Stack Menu ---

1. Push
2. Pop
3. Display
4. Exit

Enter your choice: 3

Stack elements:

36

35

23

--- Stack Menu ---

1. Push

2. Pop

3. Display

4. Exit

Enter your choice:

2

Popped element: 36

--- Stack Menu ---

1. Push

2. Pop

3. Display

4. Exit

Enter your choice: 3

Stack elements:

35

23

--- Stack Menu ---

1. Push

2. Pop

3. Display

4. Exit

Enter your choice: 4

Exiting program.

9	Program to Implement a Queue using Linked List	03 Apr 2026
---	--	-------------

AIM:

Program to Implement a Queue using Linked List

ALGORITHM:

1. Initialization

- Define a structure node with data and a pointer next.
- Initialize two global pointers: front = NULL and rear = NULL.

2. Enqueue Operation (Insertion)

1. Allocate memory for a newNode.
2. If memory allocation fails, print "Heap Overflow" and exit the function.
3. Read the value to be inserted into newNode->data.
4. Set newNode->next = NULL.
5. Check if Queue is Empty: If rear == NULL:
 - o Set both front and rear to newNode.
6. Else (Queue has elements):
 - o Link the current rear's next to the new node: rear->next = newNode.
 - o Update the rear pointer: rear = newNode.
7. Print "Element inserted successfully."

3. Dequeue Operation (Deletion)

1. Check if Queue is Empty: If front == NULL:
 - o Print "Queue Underflow" and return.
2. Create a temporary pointer temp and set temp = front.
3. Print the data of the node being deleted (temp->data).
4. Move the front pointer to the next node: front = front->next.
5. Check if Queue became empty: If front == NULL, set rear = NULL.
6. Free the memory occupied by temp.

4. Display Operation

1. Check if front == NULL. If yes, print "Queue is empty."
2. Initialize a pointer temp to front.
3. While temp != NULL:
 - o Print temp->data.
 - o Move temp to the next node: temp = temp->next.

5. Main Menu

1. Display choices: 1. Enqueue, 2. Dequeue, 3. Display, 4. Exit.
2. Perform the selected operation based on user input.
3. Repeat until the user chooses to exit.

SOURCE CODE:

<https://github.com/112534080-stack/DSALab/blob/main/QueueLinkedList.c>
 #include <stdio.h>

```

#include <stdlib.h>
// structure for queue node
struct node
{
    int data;
    struct node *next;
};
struct node *front = null;
struct node *rear = null;
// enqueue operation
void enqueue()
{
    int item;
    struct node *newnode;
    newnode = (struct node *)malloc(sizeof(struct node));
    if (newnode == null)
    {
        printf("heap overflow!\n");
        return;
    }
    printf("enter element to insert: ");
    scanf("%d", &item);
    newnode->data = item;
    newnode->next = null;
    if (rear == null)
    {
        front = rear = newnode;
    }
    else
    {
        rear->next = newnode;
        rear = newnode;
    }
    printf("element inserted successfully.\n");
}
// dequeue operation
void dequeue()
{
    struct node *temp;
    if (front == null)
    {
        printf("queue underflow!\n");
        return;
    }

```



```

    }
    temp = front;
    printf("deleted element: % d\n", temp->data);
    front = front->next;
    if (front == null)
        rear = null;
    free(temp);
}
// display queue elements
void display()
{
    struct node *temp;
    if (front == null)
    {
        printf("queue is empty.\n");
        return;
    }
    printf("queue elements:\n");
    temp = front;
    while (temp != null)
    {
        printf("% d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}
int main()
{
    int choice;
    do
    {
        printf("\n--- queue menu ---\n");
        printf("1. enqueue\n2. dequeue\n3. display\n4. exit\n");
        printf("enter your choice: ");
        scanf("% d", &choice);
        switch (choice)
        {
            case 1:
                enqueue();
                break;
            case 2:
                dequeue();
                break;

```

```

        case 3:
            display();
            break;
        case 4:
            printf("exiting program.\n");
            break;
        default:
            printf("invalid choice!\n");
    }
} while (choice != 4);

return 0;
}

```

SAMPLE OUTPUT:

```

--- Queue Menu ---
1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 1
Enter element to insert: 12
Element inserted successfully.

```

```

--- Queue Menu ---
1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 1
Enter element to insert: 51
Element inserted successfully.

```

```

--- Queue Menu ---
1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 3
Queue elements:
12 51

```

--- Queue Menu ---
1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 2
Deleted element: 12

--- Queue Menu ---
1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 3
Queue elements:
51

--- Queue Menu ---
1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 4
Exiting program.